

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|---|--------|--------------|---|---|-----------------------|
| Process 1: EXTERNAL COMBUSTION | | | | | |
| System 1: BOILERS | | | | | |
| BOILER, NATURAL GAS, CLEAVER-BROOKS, MODEL CEW700-750, WITH LOW NOX BURNER, 31.4 MMBTU/HR WITH A/N: 378926 BURNER, NATURAL GAS, ALZETA, MODEL CSB, WITH LOW NOX BURNER, 31.4 MMBTU/HR | D27 | | NOX: LARGE SOURCE** | CO: 100 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; CO: 2000 PPMV (5A) [RULE 407, 4-2-1982]; NOX: 9 PPMV NATURAL GAS (3) [RULE 2012, 5-6-2005]; NOX: 9 PPMV (4) [RULE 2005, 5-6-2005]; PM: 0.1 GRAINS/SCF (4) [RULE 409, 8-7-1981] | A63.1, D328.1, D328.4 |
| Process 2: STORAGE TANKS | | | | | |
| STORAGE TANK, UNDERGROUND, T-10, ISOPROPYL ALCOHOL, WITH NITROGEN BLANKET, VAPOR LOCK BALANCE RECOVERY SYSTEM, 30000 GALS; DIAMETER: 10 FT 6 IN; HEIGHT: 47 FT A/N: 278195 | D4 | | | | B27.1, E144.1 |
| STORAGE TANK, UNDERGROUND, NO. T-20, ISOPROPYL ALCOHOL, WITH TWO SETTLING TANKS (TOTES), 550 GALLONS EACH, WITH NITROGEN BLANKET, 10000 GALS; DIAMETER: 9 FT 6 IN; HEIGHT: 19 FT 11 IN A/N: 509342 | D5 | C30 | | | B27.1, C1.6, E193.2 |
| Process 3: AIR POLLUTION CONTROL | | | | | |

* (1) (1A) (1B) Denotes RECLAIM emission factor (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|---|---|
| Process 3: AIR POLLUTION CONTROL | | | | | |
| System 1: AIR POLLUTION CONTROL SYSTEM | | | | | |
| AFTERBURNER, CATALYTIC PRODUCTS INTERNATIONAL, NATURAL GAS, MODEL VECTOR-30, WITH CATALYTIC AFTERBURNER, LOW NOX BURNER, 5 MMBTU/HR A/N: 452717 | C29 | C30 | NOX: PROCESS UNIT** | CO: 2000 PPMV NATURAL GAS (5A) [RULE 407, 4-2-1982]; NOX: 30 PPMV NATURAL GAS (4) [RULE 2005, 5-6-2005]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: 0.1 GRAINS/SCF NATURAL GAS (5A) [RULE 409, 8-7-1981] | A72.1, B27.1, C8.4, D12.4, D182.1, D328.2 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|---|--------|---|---|--------------------------------|------------------------------|
| Process 3: AIR POLLUTION CONTROL | | | | | |
| FILTER, DUST COLLECTOR, REVERSE PULSE JET CLEANING, WHEELABRATOR, MODEL SERIES 8, UNIT 88, SIXTY-FOUR CARTRIDGE FILTERS, 150 HP EXHAUST BLOWER, 12160 SQ.FT. A/N: 446620 | C30 | D5 C29 D47 D54 D55 D59 D60 D64 D65 D69 D70 D101 D102 D103 C109 C110 C111 C112 C113 C114 C115 C116 C117 C118 C119 C120 C121 C122 C123 C124 C125 C126 C127 C128 C129 C130 C131 C132 C133 C134 D150 C152 C153 D156 D157 D158 D159 D163 C168 C170 C172 C174 C176 C178 C180 C182 C184 C186 C188 C190 D197 D198 | | PM: (9) [RULE 404, 2-7-1986] | D322.2, D323.2, E102.1 |
| FILTER, DUST COLLECTOR, CARTRIDGE, DONALDSON TORIT, MODEL DFO-4-16, 30-HP EXHAUST BLOWER, 3040 SQ.FT. A/N: 447717 | C196 | D146 D147 D194 D195 | | PM: (9) [RULE 404, 2-7-1986] | D322.2, D323.2, E102.1 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|---|--------|--------------------|---|--------------------------------|------------------------------|
| Process 3: AIR POLLUTION CONTROL | | | | | |
| System 2: DUST CONTROL SYSTEM | | | | | |
| FILTER, DUST COLLECTOR, TWO CARTRIDGE FILTERS, FLEXICON, MODEL NO. BV-FB1W, 1.5 HP EXHAUST BLOWER, 100 SQ.FT. A/N: 447709 | C31 | D43 | | PM: (9) [RULE 404, 2-7-1986] | D322.1, D323.2, E102.1 |
| FILTER, DUST COLLECTOR, TWO CARTRIDGE FILTERS, FLEXICON, MODEL NO. BV-FB1W, 1.5 HP EXHAUST BLOWER, 100 SQ.FT. A/N: 447710 | C32 | D44 | | PM: (9) [RULE 404, 2-7-1986] | D322.1, D323.2, E102.1 |
| FILTER, DUST COLLECTOR, TWO CARTRIDGE FILTERS, FLEXICON, MODEL NO. BV-FB1W, 1.5 HP EXHAUST BLOWER, 100 SQ.FT. A/N: 447711 | C33 | D45 | | PM: (9) [RULE 404, 2-7-1986] | D322.1, D323.2, E102.1 |
| FILTER, DUST COLLECTOR, TORIT DOWNFLOW, SIX CARTRIDGE FILTERS, DONALDSON, MODEL SDF-6, 7.5 HP EXHAUST BLOWER, 300 SQ.FT. A/N: 446620 | C34 | D50 D51 D52 D53 | | PM: (9) [RULE 404, 2-7-1986] | D322.1, D323.2, E102.1 |
| Process 4: FOOD | | | | | |
| System 2: DEHYDRATION SYSTEM 2 | | | | | |
| MIXER, FLAVORINGS, WITH A 5 HP AGITATOR, 2000 GALS; DIAMETER: 7 FT ; HEIGHT: 7 FT A/N: 508841 | D146 | C196 | | PM: (9) [RULE 405, 2-7-1986] | |
| MIXER, FLAVORINGS, WITH A 5 HP AGITATOR, 2000 GALS; DIAMETER: 7 FT ; HEIGHT: 7 FT A/N: 508841 | D147 | C196 | | PM: (9) [RULE 405, 2-7-1986] | |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|---|--------|--------------|---|---|------------------------------------|
| Process 4: FOOD | | | | | |
| DRYER, SPRAY, NATURAL GAS, 7 MMBTU/HR WITH A/N: 508841 BURNER, NATURAL GAS, MAXON, MODEL CROSSFIRE, WITH LOW NOX BURNER, 7 MMBTU/HR | D23 | D24 | NOX: PROCESS UNIT** | CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 405, 2-7-1986]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981] | B27.1, C1.1, C1.5, D323.2 |
| CYCLONE, PRIMARY HOT, 1/2 H.P. DISCHARGE VALVE MOTOR, HEIGHT: 27 FT ; DIAMETER: 6 FT A/N: 508841 | D24 | D23 D25 | | | |
| CYCLONE, SECONDARY HOT, 1/2 H.P. DISCHARGE VALVE MOTOR, HEIGHT: 27 FT ; DIAMETER: 6 FT A/N: 508841 | D25 | D24 C26 | | | |
| SCRUBBER, VENTURI, HEIGHT: 16 FT ; DIAMETER: 11 FT A/N: 451404 | C26 | D25 | | PM: (9) [RULE 404, 2-7-1986] | C8.1, C8.2, D323.2, E149.1, E193.1 |
| System 3: FLAVOR EXTRACTION SYSTEM NO. 1 (SILVER LINE) | | | | | S1.5 |
| TANK, QUENCH, ISOPROPYL ALCOHOL, 50 GALS; WIDTH: 2 FT 8 IN; HEIGHT: 5 FT 6 IN; LENGTH: 1 FT 10 IN A/N: 386708 | D54 | C30 | | | B27.1 |

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|------------|
| Process 4: FOOD | | | | | |
| TANK, QUENCH, ISOPROPYL ALCOHOL, 50 GALS; WIDTH: 2 FT 8 IN; HEIGHT: 5 FT 6 IN; LENGTH: 1 FT 10 IN A/N: 386708 | D55 | C30 | | | B27.1 |
| TANK, RECIRCULATION, ISOPROPYL ALCOHOL, 230 GALS; DIAMETER: 3 FT 6 IN; HEIGHT: 4 FT 10 IN A/N: 386708 | D56 | | | | B27.1 |
| FUGITIVE EMISSIONS, MISCELLANEOUS, HYDROCYCLONE, KREBS, ISOPROPYL ALCOHOL, MODEL P4-SS-752, LENGTH: 2 FT 1 IN; DIAMETER: 5 IN A/N: 386708 | D57 | | | | |
| CENTRIFUGE, 30 HP MOTOR, TEMA SYSTEMS, ISOPROPYL ALCOHOL, LENGTH: 1 FT 7 IN; DIAMETER: 1 FT 6 IN A/N: 386708 | D58 | | | | B27.1 |
| System 4: FLAVOR EXTRACTION SYSTEM NO. 2 (YELLOW LINE) | | | | | S1.6 |
| TANK, QUENCH, ISOPROPYL ALCOHOL, 50 GALS; WIDTH: 2 FT 8 IN; HEIGHT: 5 FT 6 IN; LENGTH: 1 FT 10 IN A/N: 386709 | D59 | C30 | | | B27.1 |
| TANK, QUENCH, ISOPROPYL ALCOHOL, 50 GALS; WIDTH: 2 FT 8 IN; HEIGHT: 5 FT 6 IN; LENGTH: 1 FT 10 IN A/N: 386709 | D60 | C30 | | | B27.1 |

- * (1) (1A) (1B) Denotes RECLAIM emission factor (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|------------|
| Process 4: FOOD | | | | | |
| TANK, RECIRCULATION, ISOPROPYL ALCOHOL, 230 GALS; DIAMETER: 3 FT 6 IN; HEIGHT: 4 FT 10 IN A/N: 386709 | D61 | | | | B27.1 |
| FUGITIVE EMISSIONS, MISCELLANEOUS, HYDROCYCLONE, KREBS, ISOPROPYL ALCOHOL, MODEL P4-SS-752, LENGTH: 2 FT 1 IN; DIAMETER: 5 IN A/N: 386709 | D62 | | | | |
| CENTRIFUGE, 30 HP MOTOR, TEMA SYSTEMS, ISOPROPYL ALCOHOL, LENGTH: 1 FT 4 IN; DIAMETER: 2 FT 1 IN A/N: 386709 | D63 | | | | B27.1 |
| System 5: FLAVOR EXTRACTION SYSTEM NO. 3 (ORANGE LINE) | | | | | S1.7 |
| TANK, QUENCH, ISOPROPYL ALCOHOL, 50 GALS; WIDTH: 2 FT 8 IN; HEIGHT: 5 FT 6 IN; LENGTH: 1 FT 10 IN A/N: 386710 | D64 | C30 | | | B27.1 |
| TANK, QUENCH, ISOPROPYL ALCOHOL, 50 GALS; WIDTH: 2 FT 8 IN; HEIGHT: 5 FT 6 IN; LENGTH: 1 FT 10 IN A/N: 386710 | D65 | C30 | | | B27.1 |
| TANK, RECIRCULATION, ISOPROPYL ALCOHOL, 230 GALS; DIAMETER: 3 FT 6 IN; HEIGHT: 4 FT 10 IN A/N: 386710 | D66 | | | | B27.1 |

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|------------|
| Process 4: FOOD | | | | | |
| FUGITIVE EMISSIONS, MISCELLANEOUS, HYDROCYCLONE, KREBS, ISOPROPYL ALCOHOL, MODEL P4-SS-752, LENGTH: 2 FT 1 IN; DIAMETER: 5 IN A/N: 386710 | D67 | | | | |
| CENTRIFUGE, 30 HP MOTOR, TEMA SYSTEMS, ISOPROPYL ALCOHOL, LENGTH: 1 FT 4 IN; DIAMETER: 2 FT 1 IN A/N: 386710 | D68 | | | | B27.1 |
| System 6: FLAVOR EXTRACTION SYSTEM NO. 4 (TAN LINE) | | | | | S1.8 |
| TANK, QUENCH, ISOPROPYL ALCOHOL, 50 GALS; WIDTH: 2 FT 8 IN; HEIGHT: 5 FT 6 IN; LENGTH: 1 FT 10 IN A/N: 386711 | D69 | C30 | | | B27.1 |
| TANK, QUENCH, ISOPROPYL ALCOHOL, 50 GALS; WIDTH: 2 FT 8 IN; HEIGHT: 5 FT 6 IN; LENGTH: 1 FT 10 IN A/N: 386711 | D70 | C30 | | | B27.1 |
| TANK, RECIRCULATION, ISOPROPYL ALCOHOL, 230 GALS; DIAMETER: 3 FT 6 IN; HEIGHT: 4 FT 10 IN A/N: 386711 | D71 | | | | B27.1 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|------------|
| Process 4: FOOD | | | | | |
| FUGITIVE EMISSIONS, MISCELLANEOUS, HYDROCYCLONE, KREBS, ISOPROPYL ALCOHOL, MODEL P4-SS-752, LENGTH: 2 FT 1 IN; DIAMETER: 5 IN A/N: 386711 | D72 | | | | |
| CENTRIFUGE, 30 HP MOTOR, TEMA SYSTEMS, ISOPROPYL ALCOHOL, LENGTH: 1 FT 7 IN; DIAMETER: 1 FT 5 IN A/N: 386711 | D73 | | | | B27.1 |
| System 7: FLAVOR EXTRACTION DRYING SYSTEM | | | | | |
| DRYER, ROTARY, NO. 1, STEAM HEATED, LENGTH: 4 FT 6 IN; DIAMETER: 4 FT 6 IN A/N: 386712 | D74 | C109 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386798 | C109 | C30 D74 | | | |
| DRYER, ROTARY, NO. 2, STEAM HEATED, LENGTH: 4 FT 6 IN; DIAMETER: 4 FT 6 IN A/N: 386713 | D75 | C110 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386799 | C110 | C30 D75 | | | |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|------------|
| Process 4: FOOD | | | | | |
| DRYER, ROTARY, NO. 3, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386714 | D76 | C111 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386800 | C111 | C30 D76 | | | |
| DRYER, ROTARY, NO. 4, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386715 | D77 | C112 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386805 | C112 | C30 D77 | | | |
| DRYER, ROTARY, NO. 5, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386716 | D78 | C113 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386806 | C113 | C30 D78 | | | |
| DRYER, ROTARY, NO. 6, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386717 | D79 | C114 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386807 | C114 | C30 D79 | | | |

* (1) (1A) (1B) Denotes RECLAIM emission factor (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|------------|
| Process 4: FOOD | | | | | |
| DRYER, ROTARY, NO. 7, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386718 | D80 | C115 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386808 | C115 | C30 D80 | | | |
| DRYER, ROTARY, NO. 8, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386725 | D81 | C116 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386809 | C116 | C30 D81 | | | |
| DRYER, ROTARY, NO. 9, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386729 | D82 | C117 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386810 | C117 | C30 D82 | | | |
| DRYER, ROTARY, NO. 10, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386733 | D83 | C118 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386811 | C118 | C30 D83 | | | |

- * (1) (1A) (1B) Denotes RECLAIM emission factor (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|------------|
| Process 4: FOOD | | | | | |
| DRYER, ROTARY, NO. 11, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386734 | D84 | C119 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386812 | C119 | C30 D84 | | | |
| DRYER, ROTARY, NO. 12, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386737 | D85 | C120 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386813 | C120 | C30 D85 | | | |
| DRYER, ROTARY, NO. 13, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386738 | D86 | C121 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386815 | C121 | C30 D86 | | | |
| DRYER, ROTARY, NO. 14, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386740 | D87 | C122 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386816 | C122 | C30 D87 | | | |

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|------------|
| Process 4: FOOD | | | | | |
| DRYER, ROTARY, NO. 15, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386741 | D88 | C123 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386817 | C123 | C30 D88 | | | |
| DRYER, ROTARY, NO. 16, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386742 | D89 | C124 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386818 | C124 | C30 D89 | | | |
| DRYER, ROTARY, NO. 17, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386744 | D90 | C125 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386819 | C125 | C30 D90 | | | |
| DRYER, ROTARY, NO. 18, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386745 | D91 | C126 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386820 | C126 | C30 D91 | | | |

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|------------|
| Process 4: FOOD | | | | | |
| DRYER, ROTARY, NO. 19, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386746 | D92 | C127 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386821 | C127 | C30 D92 | | | |
| DRYER, ROTARY, NO. 20, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386748 | D93 | C128 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386822 | C128 | C30 D93 | | | |
| DRYER, ROTARY, NO. 21, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386750 | D94 | C129 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386823 | C129 | C30 D94 | | | |
| DRYER, ROTARY, NO. 22, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386751 | D95 | C130 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386824 | C130 | C30 D95 | | | |

* (1) (1A) (1B) Denotes RECLAIM emission factor (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|------------|
| Process 4: FOOD | | | | | |
| DRYER, ROTARY, NO. 23, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386752 | D96 | C131 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386825 | C131 | C30 D96 | | | |
| DRYER, ROTARY, NO. 24, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386753 | D97 | C132 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386826 | C132 | C30 D97 | | | |
| DRYER, ROTARY, NO. 25, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386755 | D98 | C133 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386827 | C133 | C30 D98 | | | |
| DRYER, ROTARY, NO. 26, STEAM HEATED 4-1/2 FT DIA. X 4-1/2 FT L. A/N: 386756 | D99 | C134 | | | B27.1 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-D1, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 386814 | C134 | C30 D99 | | | |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|-------------|
| Process 4: FOOD | | | | | |
| DRYER, ROTARY, STEAM HEATED, PILOT NO. 1 (SMALL) A/N: 386759 | D100 | | | | B27.1 |
| DRYER, ROTARY, STEAM HEATED, PILOT NO. 2 (SMALL) A/N: 386763 | D101 | C30 | | | B27.1 |
| DRYER, ROTARY, STEAM HEATED, PILOT NO. 3 (SMALL) A/N: 386766 | D102 | C30 | | | B27.1 |
| DRYER, ROTARY, STEAM HEATED, PILOT NO. 4 (SMALL) A/N: 386768 | D103 | C30 | | | B27.1 |
| DRYER, ROTARY, RED LINE NO. 1, STEAM HEATED, ABC SHEETMETAL, 2-HP DRIVE MOTOR, LENGTH: 4 FT 6 IN; DIAMETER: 4 FT 6 IN A/N: 446650 | D167 | C168 | | | B27.1, C1.9 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-P, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 446650 | C168 | C30 D167 | | | |
| DRYER, ROTARY, RED LINE NO. 2, STEAM HEATED, ABC SHEETMETAL, 2-HP DRIVE MOTOR, LENGTH: 4 FT 6 IN; DIAMETER: 4 FT 6 IN A/N: 446651 | D169 | C170 | | | B27.1, C1.9 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-P, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 446651 | C170 | C30 D169 | | | |

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|-------------|
| Process 4: FOOD | | | | | |
| DRYER, ROTARY, RED LINE NO. 3, STEAM HEATED, ABC SHEETMETAL, 2-HP DRIVE MOTOR, LENGTH: 4 FT 6 IN; DIAMETER: 4 FT 6 IN A/N: 446652 | D171 | C172 | | | B27.1, C1.9 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-P, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 446652 | C172 | C30 D171 | | | |
| DRYER, ROTARY, RED LINE NO. 4, STEAM HEATED, ABC SHEETMETAL, 2-HP DRIVE MOTOR, LENGTH: 4 FT 6 IN; DIAMETER: 4 FT 6 IN A/N: 446653 | D173 | C174 | | | B27.1, C1.9 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-P, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 446653 | C174 | C30 D173 | | | |
| DRYER, ROTARY, RED LINE NO. 5, STEAM HEATED, ABC SHEETMETAL, 2-HP DRIVE MOTOR, LENGTH: 4 FT 6 IN; DIAMETER: 4 FT 6 IN A/N: 446654 | D175 | C176 | | | B27.1, C1.9 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-P, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 446654 | C176 | C30 D175 | | | |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|-------------|
| Process 4: FOOD | | | | | |
| DRYER, ROTARY, RED LINE NO. 6, STEAM HEATED, ABC SHEETMETAL, 2-HP DRIVE MOTOR, LENGTH: 4 FT 6 IN; DIAMETER: 4 FT 6 IN A/N: 446655 | D177 | C178 | | | B27.1, C1.9 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-P, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 446655 | C178 | C30 D177 | | | |
| DRYER, ROTARY, RED LINE NO. 7, STEAM HEATED, ABC SHEETMETAL, 2-HP DRIVE MOTOR, LENGTH: 4 FT 6 IN; DIAMETER: 4 FT 6 IN A/N: 446656 | D179 | C180 | | | B27.1, C1.9 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-P, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 446656 | C180 | C30 D179 | | | |
| DRYER, ROTARY, RED LINE NO. 8, STEAM HEATED, ABC SHEETMETAL, 2-HP DRIVE MOTOR, LENGTH: 4 FT 6 IN; DIAMETER: 4 FT 6 IN A/N: 446657 | D181 | C182 | | | B27.1, C1.9 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-P, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 446657 | C182 | C30 D181 | | | |

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|---|--------|--------------|---|--------------------------------|-------------|
| Process 4: FOOD | | | | | |
| DRYER, ROTARY, RED LINE NO. 9, STEAM HEATED, ABC SHEETMETAL, 2-HP DRIVE MOTOR, LENGTH: 4 FT 6 IN; DIAMETER: 4 FT 6 IN A/N: 446660 | D183 | C184 | | | B27.1, C1.9 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-P, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 446660 | C184 | C30 D183 | | | |
| DRYER, ROTARY, RED LINE NO. 10, STEAM HEATED, ABC SHEETMETAL, 2-HP DRIVE MOTOR, LENGTH: 4 FT 6 IN; DIAMETER: 4 FT 6 IN A/N: 446661 | D185 | C186 | | | B27.1, C1.9 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-P, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 446661 | C186 | C30 D185 | | | |
| DRYER, ROTARY, RED LINE NO. 11, STEAM HEATED, ABC SHEETMETAL, 2-HP DRIVE MOTOR, LENGTH: 4 FT 6 IN; DIAMETER: 4 FT 6 IN A/N: 446662 | D187 | C188 | | | B27.1, C1.9 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-P, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 446662 | C188 | C30 D187 | | | |

* (1) (1A) (1B) Denotes RECLAIM emission factor (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|---------------------------------|-------------|
| Process 4: FOOD | | | | | |
| DRYER, ROTARY, RED LINE NO. 12, STEAM HEATED, ABC SHEETMETAL, 2-HP DRIVE MOTOR, LENGTH: 4 FT 6 IN; DIAMETER: 4 FT 6 IN A/N: 446663 | D189 | C190 | | | B27.1, C1.9 |
| CYCLONE, AGET MANUFACTURING, MODEL 8N50-P, HEIGHT: 2 FT ; DIAMETER: 1 FT A/N: 446663 | C190 | C30 D189 | | | |
| System 8: FLAVOR EXTRACTION SCREENING SYSTEM | | | | | |
| SCREEN, CLASSIFYING, VIBRATING, FOOD FLAVOR CRYSTALS A/N: 386774 | D104 | | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |
| SCREEN, CLASSIFYING, VIBRATING, FOOD FLAVOR CRYSTALS A/N: 386777 | D105 | | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |
| SCREEN, CLASSIFYING, VIBRATING, FOOD FLAVOR CRYSTALS A/N: 386794 | D106 | | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |
| SCREEN, CLASSIFYING, VIBRATING, FOOD FLAVOR CRYSTALS A/N: 386796 | D107 | | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |
| SCREEN, CLASSIFYING, VIBRATING, FOOD FLAVOR CRYSTALS A/N: 386797 | D108 | | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |
| SCREEN, CLASSIFYING, VIBRATING, J LINE, SWECO, FOOD FLAVOR CRYSTALS, CIRCULAR STYLE, PORTABLE WITH A 2 1/2 HP MOTOR A/N: 446679 | D191 | | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|---|--------|--------------|---|--------------------------------|------------|
| Process 4: FOOD | | | | | |
| SCREEN, CLASSIFYING, VIBRATING, RED LINE #1, SWECO, FOOD FLAVOR CRYSTALS, CIRCULAR STYLE, PORTABLE WITH A 2 1/2 HP MOTOR A/N: 446680 | D192 | | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |
| SCREEN, CLASSIFYING, VIBRATING, RED LINE #2, SWECO, FOOD FLAVOR CRYSTALS, CIRCULAR STYLE, PORTABLE WITH A 2 1/2 HP MOTOR A/N: 446681 | D193 | | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |
| SCREEN, CLASSIFYING, VIBRATING, #6, SWECO, FOOD FLAVOR CRYSTALS, CIRCULAR STYLE, PORTABLE WITH A 2 1/2 HP MOTOR A/N: 463669 | D199 | | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |
| SCREEN, CLASSIFYING, VIBRATING, #31, SWECO, FOOD FLAVOR CRYSTALS, CIRCULAR STYLE, PORTABLE WITH A 2 1/2 HP MOTOR A/N: 463670 | D200 | | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |
| SCREEN, CLASSIFYING, VIBRATING, #48, SWECO, FOOD FLAVOR CRYSTALS, CIRCULAR STYLE, PORTABLE WITH A 2 1/2 HP MOTOR A/N: 463671 | D201 | | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|------------|
| Process 4: FOOD | | | | | |
| SCREEN, CLASSIFYING, VIBRATING, CDL2, SWECO, FOOD FLAVOR CRYSTALS, CIRCULAR STYLE, PORTABLE WITH A 2 1/2 HP MOTOR A/N: 463673 | D202 | | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |
| System 9: CONTINUOUS LINE | | | | | S1.3, S1.4 |
| BULK MATERIAL UNLOADING STATION, NO. 1 A/N: 510790 | D43 | C31 | | PM: (9) [RULE 405, 2-7-1986] | D323.2 |
| BULK MATERIAL UNLOADING STATION, NO. 2 A/N: 510790 | D44 | C32 | | PM: (9) [RULE 405, 2-7-1986] | D323.2 |
| BULK MATERIAL UNLOADING STATION, NO. 3 A/N: 510790 | D45 | C33 | | PM: (9) [RULE 405, 2-7-1986] | D323.2 |
| TANK, ISOPROPYL ALCOHOL, 230 GALS; DIAMETER: 3 FT ; HEIGHT: 4 FT 4 IN A/N: 510790 | D46 | | | | B27.1 |
| CONVEYOR, HAPMAN, MODEL NO. 4000 A/N: 510790 | D50 | C34 | | PM: (9) [RULE 405, 2-7-1986] | D323.2 |
| FEEDER, SCREW, FLEXWALL, MODEL NO. FW33 A/N: 510790 | D51 | C34 | | PM: (9) [RULE 405, 2-7-1986] | D323.2 |
| SCREEN, CLASSIFYING, VIBRATORY, SOUTHWESTERN VIBRECON, WITH A 1/3 HP MOTOR A/N: 510790 | D52 | C34 | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |
| HOPPER A/N: 510790 | D53 | C34 | | PM: (9) [RULE 405, 2-7-1986] | D323.2 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|---------------------|
| Process 4: FOOD | | | | | |
| TANK, QUENCH, CUSTOM, ISOPROPYL ALCOHOL WITH ONE 10 HP DISINTEGRATOR MOTOR, 50 GALS A/N: 510790 | D156 | C30 | | | B27.1, E17.1 |
| TANK, QUENCH, CUSTOM, ISOPROPYL ALCOHOL WITH ONE 10 HP DISINTEGRATOR MOTOR, 50 GALS A/N: 510790 | D47 | C30 | | | B27.1, E17.1 |
| CENTRIFUGE, TEMA SYSTEMS, MODEL NO. TS-360-FK, DECANter A/N: 510790 | D48 | | | | B27.1 |
| DRYER, STEAM HEATED, TWO 10 HP REC FANS, ONE 20 HP EX FAN AND ONE 5 HP DRIVE MOTOR A/N: 510790 | D49 | D157 | | PM: (9) [RULE 405, 2-7-1986] | B27.1, D323.2 |
| CYCLONE, WIDTH: 3 FT ; HEIGHT: 15 FT ; LENGTH: 3 FT A/N: 510790 | D157 | C30 D49 | | PM: (9) [RULE 405, 2-7-1986] | |
| System 10: FLAVORED SUGAR DRYING | | | | | |
| DRYER, FLUIDIZED BED, STEAM HEATED, A/N: 458070 | D137 | D138 D139 | | PM: (9) [RULE 405, 2-7-1986] | C1.4, D323.1, K67.2 |
| CYCLONE, VENTILEX, MODEL MEC-900, HEIGHT: 9 FT 5 IN; DIAMETER: 2 FT 11 IN A/N: 458070 | D138 | D137 C140 | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |
| CYCLONE, VENTILEX, MODEL MEC-900, HEIGHT: 9 FT 5 IN; DIAMETER: 2 FT 11 IN A/N: 458070 | D139 | D137 C140 | | PM: (9) [RULE 405, 2-7-1986] | D323.1 |

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|--------------------------------|--------------------------------------|
| Process 4: FOOD | | | | | |
| BAGHOUSE, CARTRIDGE FILTER, DONALDSON TORIT, MODEL DFO3-24, 4560 SQ.FT.; 24 CARTRIDGE A/N: 458071 | C140 | D138 D139 | | PM: (9) [RULE 404, 2-7-1986] | C10.1, D12.5, D322.1, D381.1, E102.1 |
| System 11: FLAVOR EXTRACTION SYSTEM NO. 5 (RED LINE) | | | | | S1.1 |
| TANK, QUENCH, ISOPROPYL ALCOHOL, WITH A 7 1/2 HP AGITATOR, 50 GALS; WIDTH: 2 FT 8 IN; HEIGHT: 5 FT 6 IN; LENGTH: 1 FT 10 IN A/N: 446647 | D158 | C30 | | | B27.1 |
| TANK, QUENCH, ISOPROPYL ALCOHOL, WITH A 7 1/2 HP AGITATOR, 50 GALS; WIDTH: 2 FT 8 IN; HEIGHT: 5 FT 6 IN; LENGTH: 1 FT 10 IN A/N: 446647 | D159 | C30 | | | B27.1 |
| TANK, RECIRCULATION, ISOPROPYL ALCOHOL, 230 GALS; DIAMETER: 3 FT 6 IN; HEIGHT: 4 FT 10 IN A/N: 446647 | D160 | | | | B27.1 |
| FUGITIVE EMISSIONS, MISCELLANEOUS, HYDROCYCLONE, KREBS, ISOPROPYL ALCOHOL, MODEL P4-SS-752, LENGTH: 2 FT 1 IN; DIAMETER: 5 IN A/N: 446647 | D161 | | | | |

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---------------------------------|--------------|
| Process 4: FOOD | | | | | |
| CENTRIFUGE, 30 HP MOTOR, TEMA SYSTEMS, ISOPROPYL ALCOHOL, D-LIMONENE, LENGTH: 1 FT 7 IN; DIAMETER: 1 FT 6 IN A/N: 446647 | D162 | | | | B27.1 |
| TANK, WASH, D-LIMONENE, WITH A 2 HP AGITATOR, 955 GALS; DIAMETER: 5 FT ; HEIGHT: 6 FT A/N: 446647 | D197 | C30 | | | B27.1, C1.11 |
| TANK, HOLDING, D-LIMONENE, 700 GALS; DIAMETER: 5 FT 2 IN; HEIGHT: 4 FT 5 IN A/N: 446647 | D198 | C30 | | | B27.1, C1.11 |
| System 12: FLAVOR EXTRACTION SYSTEM NO. 6 (J LINE) | | | | | S1.2 |
| TANK, QUENCH, ISOPROPYL ALCOHOL, WITH A 7 1/2 HP AGITATOR, 50 GALS; WIDTH: 2 FT 8 IN; HEIGHT: 5 FT 6 IN; LENGTH: 1 FT 10 IN A/N: 446649 | D163 | C30 | | | B27.1 |
| TANK, RECIRCULATION, ISOPROPYL ALCOHOL, 230 GALS; DIAMETER: 3 FT 6 IN; HEIGHT: 4 FT 10 IN A/N: 446649 | D164 | | | | B27.1 |
| FUGITIVE EMISSIONS, MISCELLANEOUS, HYDROCYCLONE, KREBS, ISOPROPYL ALCOHOL, MODEL P4-SS-752, LENGTH: 2 FT 1 IN; DIAMETER: 5 IN A/N: 446649 | D165 | | | | |

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|---|--------|--------------|---|--|---------------|
| Process 4: FOOD | | | | | |
| CENTRIFUGE, 30 HP MOTOR, TEMA SYSTEMS, ISOPROPYL ALCOHOL, LENGTH: 1 FT 7 IN; DIAMETER: 1 FT 6 IN A/N: 446649 | D166 | | | | B27.1 |
| System 13: BLENDING | | | | | |
| BLENDER, NO. 1, HOMOGENIZING, CUSTOM BUILT, 7,000 POUND CAPACITY A/N: 447713 | D194 | C196 | | PM: (9) [RULE 405, 2-7-1986] | C1.10, D323.1 |
| BLENDER, NO. 2, HOMOGENIZING, CUSTOM BUILT, 7,000 POUND CAPACITY A/N: 447716 | D195 | C196 | | PM: (9) [RULE 405, 2-7-1986] | C1.10, D323.1 |
| Process 5: RULE 219 EXEMPT EQUIPMENT | | | | | |
| RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS | E17 | | | VOC: (9) [RULE 1113, 11-8-1996; RULE 1113, 7-13-2007; RULE 1171, 11-7-2003; RULE 1171, 2-1-2008] | K67.1 |
| RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS | E18 | | | | H23.1 |
| RULE 219 EXEMPT EQUIPMENT, FLAVOR OIL BLENDING | E203 | | | | |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
MCP FOODS INC**

SECTION D: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

**FACILITY PERMIT TO OPERATE
 MCP FOODS INC
 SECTION D: DEVICE ID INDEX**

| Device Index For Section D | | | |
|-----------------------------------|---------------------------|----------------|---------------|
| Device ID | Section D Page No. | Process | System |
| D4 | 1 | 2 | 0 |
| D5 | 1 | 2 | 0 |
| E17 | 26 | 5 | 0 |
| E18 | 26 | 5 | 0 |
| D23 | 5 | 4 | 2 |
| D24 | 5 | 4 | 2 |
| D25 | 5 | 4 | 2 |
| C26 | 5 | 4 | 2 |
| D27 | 1 | 1 | 1 |
| C29 | 2 | 3 | 1 |
| C30 | 3 | 3 | 1 |
| C31 | 4 | 3 | 2 |
| C32 | 4 | 3 | 2 |
| C33 | 4 | 3 | 2 |
| C34 | 4 | 3 | 2 |
| D43 | 22 | 4 | 9 |
| D44 | 22 | 4 | 9 |
| D45 | 22 | 4 | 9 |
| D46 | 22 | 4 | 9 |
| D47 | 23 | 4 | 9 |
| D48 | 23 | 4 | 9 |
| D49 | 23 | 4 | 9 |
| D50 | 22 | 4 | 9 |
| D51 | 22 | 4 | 9 |
| D52 | 22 | 4 | 9 |
| D53 | 22 | 4 | 9 |
| D54 | 5 | 4 | 3 |
| D55 | 6 | 4 | 3 |
| D56 | 6 | 4 | 3 |
| D57 | 6 | 4 | 3 |
| D58 | 6 | 4 | 3 |
| D59 | 6 | 4 | 4 |
| D60 | 6 | 4 | 4 |
| D61 | 7 | 4 | 4 |
| D62 | 7 | 4 | 4 |

**FACILITY PERMIT TO OPERATE
 MCP FOODS INC
 SECTION D: DEVICE ID INDEX**

| Device Index For Section D | | | |
|-----------------------------------|---------------------------|----------------|---------------|
| Device ID | Section D Page No. | Process | System |
| D63 | 7 | 4 | 4 |
| D64 | 7 | 4 | 5 |
| D65 | 7 | 4 | 5 |
| D66 | 7 | 4 | 5 |
| D67 | 8 | 4 | 5 |
| D68 | 8 | 4 | 5 |
| D69 | 8 | 4 | 6 |
| D70 | 8 | 4 | 6 |
| D71 | 8 | 4 | 6 |
| D72 | 9 | 4 | 6 |
| D73 | 9 | 4 | 6 |
| D74 | 9 | 4 | 7 |
| D75 | 9 | 4 | 7 |
| D76 | 10 | 4 | 7 |
| D77 | 10 | 4 | 7 |
| D78 | 10 | 4 | 7 |
| D79 | 10 | 4 | 7 |
| D80 | 11 | 4 | 7 |
| D81 | 11 | 4 | 7 |
| D82 | 11 | 4 | 7 |
| D83 | 11 | 4 | 7 |
| D84 | 12 | 4 | 7 |
| D85 | 12 | 4 | 7 |
| D86 | 12 | 4 | 7 |
| D87 | 12 | 4 | 7 |
| D88 | 13 | 4 | 7 |
| D89 | 13 | 4 | 7 |
| D90 | 13 | 4 | 7 |
| D91 | 13 | 4 | 7 |
| D92 | 14 | 4 | 7 |
| D93 | 14 | 4 | 7 |
| D94 | 14 | 4 | 7 |
| D95 | 14 | 4 | 7 |
| D96 | 15 | 4 | 7 |
| D97 | 15 | 4 | 7 |

**FACILITY PERMIT TO OPERATE
 MCP FOODS INC
 SECTION D: DEVICE ID INDEX**

| Device Index For Section D | | | |
|-----------------------------------|---------------------------|----------------|---------------|
| Device ID | Section D Page No. | Process | System |
| D98 | 15 | 4 | 7 |
| D99 | 15 | 4 | 7 |
| D100 | 16 | 4 | 7 |
| D101 | 16 | 4 | 7 |
| D102 | 16 | 4 | 7 |
| D103 | 16 | 4 | 7 |
| D104 | 20 | 4 | 8 |
| D105 | 20 | 4 | 8 |
| D106 | 20 | 4 | 8 |
| D107 | 20 | 4 | 8 |
| D108 | 20 | 4 | 8 |
| C109 | 9 | 4 | 7 |
| C110 | 9 | 4 | 7 |
| C111 | 10 | 4 | 7 |
| C112 | 10 | 4 | 7 |
| C113 | 10 | 4 | 7 |
| C114 | 10 | 4 | 7 |
| C115 | 11 | 4 | 7 |
| C116 | 11 | 4 | 7 |
| C117 | 11 | 4 | 7 |
| C118 | 11 | 4 | 7 |
| C119 | 12 | 4 | 7 |
| C120 | 12 | 4 | 7 |
| C121 | 12 | 4 | 7 |
| C122 | 12 | 4 | 7 |
| C123 | 13 | 4 | 7 |
| C124 | 13 | 4 | 7 |
| C125 | 13 | 4 | 7 |
| C126 | 13 | 4 | 7 |
| C127 | 14 | 4 | 7 |
| C128 | 14 | 4 | 7 |
| C129 | 14 | 4 | 7 |
| C130 | 14 | 4 | 7 |
| C131 | 15 | 4 | 7 |
| C132 | 15 | 4 | 7 |

**FACILITY PERMIT TO OPERATE
 MCP FOODS INC
 SECTION D: DEVICE ID INDEX**

| Device Index For Section D | | | |
|-----------------------------------|---------------------------|----------------|---------------|
| Device ID | Section D Page No. | Process | System |
| C133 | 15 | 4 | 7 |
| C134 | 15 | 4 | 7 |
| D137 | 23 | 4 | 10 |
| D138 | 23 | 4 | 10 |
| D139 | 23 | 4 | 10 |
| C140 | 24 | 4 | 10 |
| D146 | 4 | 4 | 2 |
| D147 | 4 | 4 | 2 |
| D156 | 23 | 4 | 9 |
| D157 | 23 | 4 | 9 |
| D158 | 24 | 4 | 11 |
| D159 | 24 | 4 | 11 |
| D160 | 24 | 4 | 11 |
| D161 | 24 | 4 | 11 |
| D162 | 25 | 4 | 11 |
| D163 | 25 | 4 | 12 |
| D164 | 25 | 4 | 12 |
| D165 | 25 | 4 | 12 |
| D166 | 26 | 4 | 12 |
| D167 | 16 | 4 | 7 |
| C168 | 16 | 4 | 7 |
| D169 | 16 | 4 | 7 |
| C170 | 16 | 4 | 7 |
| D171 | 17 | 4 | 7 |
| C172 | 17 | 4 | 7 |
| D173 | 17 | 4 | 7 |
| C174 | 17 | 4 | 7 |
| D175 | 17 | 4 | 7 |
| C176 | 17 | 4 | 7 |
| D177 | 18 | 4 | 7 |
| C178 | 18 | 4 | 7 |
| D179 | 18 | 4 | 7 |
| C180 | 18 | 4 | 7 |
| D181 | 18 | 4 | 7 |
| C182 | 18 | 4 | 7 |

**FACILITY PERMIT TO OPERATE
 MCP FOODS INC
 SECTION D: DEVICE ID INDEX**

| Device Index For Section D | | | |
|-----------------------------------|---------------------------|----------------|---------------|
| Device ID | Section D Page No. | Process | System |
| D183 | 19 | 4 | 7 |
| C184 | 19 | 4 | 7 |
| D185 | 19 | 4 | 7 |
| C186 | 19 | 4 | 7 |
| D187 | 19 | 4 | 7 |
| C188 | 19 | 4 | 7 |
| D189 | 20 | 4 | 7 |
| C190 | 20 | 4 | 7 |
| D191 | 20 | 4 | 8 |
| D192 | 21 | 4 | 8 |
| D193 | 21 | 4 | 8 |
| D194 | 26 | 4 | 13 |
| D195 | 26 | 4 | 13 |
| C196 | 3 | 3 | 1 |
| D197 | 25 | 4 | 11 |
| D198 | 25 | 4 | 11 |
| D199 | 21 | 4 | 8 |
| D200 | 21 | 4 | 8 |
| D201 | 21 | 4 | 8 |
| D202 | 22 | 4 | 8 |
| E203 | 26 | 5 | 0 |

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F14.1 The operator shall not purchase diesel fuel containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

[**RULE 431.2, 5-4-1990**; RULE 431.2, 9-15-2000]

F14.2 The operator shall not burn diesel fuel containing sulfur compounds in excess of 500 ppm by weight.

[**RULE 431.2, 5-4-1990**; RULE 431.2, 9-15-2000]

SYSTEM CONDITIONS

S1.1 The operator shall limit the throughput to no more than 554400 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as finished Durarome product from the Red Line.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 4, System 11]

S1.2 The operator shall limit the throughput to no more than 4000 lb(s) in any one day.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, throughput shall be defined as finished product from the J Line.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 4, System 12]

- S1.3 The operator shall limit the throughput to no more than 83,348 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as isopropyl alcohol usage.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 4, System 9]

- S1.4 The operator shall limit the throughput to no more than 450000 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as product from the Continuous Line, including off spec and discarded material.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 4, System 9]

- S1.5 The operator shall limit the throughput to no more than 443520 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as finished Durarome product from the Silver Line.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 4, System 3]

- S1.6 The operator shall limit the throughput to no more than 403920 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as finished Durarome product from the Yellow Line.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 4, System 4]

- S1.7 The operator shall limit the throughput to no more than 261360 lb(s) in any one calendar month.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, throughput shall be defined as finished Durarome product from the Orange Line.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 4, System 5]

S1.8 The operator shall limit the throughput to no more than 251460 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as finished Durarome product from the Tan Line.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 4, System 6]

DEVICE CONDITIONS

A. Emission Limits

A63.1 The operator shall limit emissions from this equipment as follows:

| CONTAMINANT | EMISSIONS LIMIT |
|-------------|-------------------------------------|
| CO | Less than 1689 LBS IN ANY ONE MONTH |

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D27]

A72.1 The operator shall maintain this equipment to achieve a minimum overall control efficiency of 96.9 percent for VOC during the normal operation of the equipment it vents.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : C29]

B. Material/Fuel Type Limits

B27.1 The operator shall not use materials containing any toxic air contaminants (TACs) identified in the SCAQMD Rule 1401 (except for those compounds listed below), as amended 03/04/2005.

| COMPOUND | CAS NO. |
|-------------------|---------|
| Acetaldehyde | 75-07-0 |
| Isopropyl Alcohol | 67-63-0 |

[RULE 1401, 3-4-2005]

[Devices subject to this condition : D4, D5, D23, C29, D46, D47, D48, D49, D54, D55, D56, D58, D59, D60, D61, D63, D64, D65, D66, D68, D69, D70, D71, D73, D74, D75, D76, D77, D78, D79, D80, D81, D82, D83, D84, D85, D86, D87, D88, D89, D90, D91, D92, D93, D94, D95, D96, D97, D98, D99, D100, D101, D102, D103, D156, D158, D159, D160, D162, D163, D164, D166, D167, D169, D171, D173, D175, D177, D179, D181, D183, D185, D187, D189, D197, D198]

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C. Throughput or Operating Parameter Limits

C1.1 The operator shall limit the production rate to no more than 2200 lb(s)/hr.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D23]

C1.4 The operator shall limit the material processed to no more than 480240 lb(s) in any one month.

To comply with this condition, the operator shall maintain adequate records. Such records shall be kept on the premises for at least five years and be made available to the Executive Officer or his representative upon request..

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D137]

C1.5 The operator shall limit the production rate to no more than 528000 lb(s) in any one calendar month.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D23]

C1.6 The operator shall limit the throughput to no more than 100,000 gallon(s) in any one calendar month.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, throughput shall be defined as spent isopropyl alcohol.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D5]

- C1.9 The operator shall limit the throughput to no more than 183,040 lb(s) in any one calendar month.

For the purpose of this condition, material processed shall be defined as finished product in the Red Line.

This limit shall be based on the total combined limit for equipment D167, D169, D171, D173, D175, D177, D179, D181, D183, D185, D187 and D189.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D167, D169, D171, D173, D175, D177, D179, D181, D183, D185, D187, D189]

- C1.10 The operator shall limit the throughput to no more than 1,386 ton(s) in any one calendar month.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, throughput shall be defined as finished product blended.

This limit shall be based on the total combined limit for equipment D194 and D195.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D194, D195]

- C1.11 The operator shall limit the throughput to no more than 48 batch(es) in any one calendar month.

The purpose(s) of this condition is to limit the batches of Duralife.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D197, D198]

- C8.1 The operator shall use this equipment in such a manner that the flow rate being monitored, as indicated below, is not less than 40 gpm.

To comply with this condition, the operator shall install and maintain a(n) flow meter to accurately indicate the flow rate being supplied to the recirculation line.

The operator shall determine and record the flow rate once every day.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C26]

- C8.2 The operator shall use this equipment in such a manner that the pressure being monitored, as indicated below, is not less than 30 Psig.

To comply with this condition, the operator shall install and maintain a(n) pressure gauge to accurately indicate the pressure of the recirculation line.

The operator shall determine and record the parameter being monitored once every day.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C26]

- C8.4 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, is not less than 600 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature reading device to accurately indicate the temperature in the catalyst bed.

The operator shall also install and maintain a device to continuously record the temperature being measured.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C29]

- C10.1 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, is maintained between 0.5 and 6 inches water column.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C140]

D. Monitoring/Testing Requirements

D12.4 The operator shall install and maintain a(n) pressure sensing device to accurately indicate the pressure in the main exhaust duct and in each branch of the VOC emissions collection system.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C29]

D12.5 The operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the filter.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C140]

D182.1 The operator shall test this equipment in accordance with the following specifications:

the activity of the catalyst shall be tested once per year.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C29]

D322.1 The operator shall perform annual inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C31, C32, C33, C34, C140]

D322.2 The operator shall perform a quarterly inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C30, C196]

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D52, D104, D105, D106, D107, D108, D137, D138, D139, D191, D192, D193, D194, D195, D199, D200, D201, D202]

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.2 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a semi-annual basis, at least, unless the equipment did not operate during the entire semi-annual period. The routine semi-annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.
In addition, the operator shall have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within 72 hours of conversion to fuel oil firing and on a weekly basis thereafter, until the equipment stops firing fuel oil.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- 4). All visible emission observation records by operator or a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D23, C26, C30, C31, C32, C33, C34, D43, D44, D45, D49, D50, D51, D53, C196]

- D328.1 The operator shall determine compliance with the CO emission limit(s) either: (a) conducting a source test at least once every five years using AQMD Method 100.1 or 10.1; or (b) conducting a test at least annually using a portable analyzer and AQMD-approved test method. The test shall be conducted when the equipment is operating under normal conditions to demonstrate compliance with 1146. The operator shall comply with all general testing, reporting, and recordkeeping requirements in Sections E and K of this permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D27]

- D328.2 The operator shall determine compliance with the CO emission limit(s) either: (a) conducting a source test at least once every five years using AQMD Method 100.1 or 10.1; or (b) conducting a test at least annually using a portable analyzer and AQMD-approved test method. The test shall be conducted when the equipment is operating under normal conditions to demonstrate compliance with Rule 407. The operator shall comply with all general testing, reporting, and recordkeeping requirements in Sections E and K of this permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C29]

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D328.4 The operator shall determine compliance with the NOX emission limit(s) either: (a) conducting a source test at least once every five years using AQMD Method 100.1 or 7.1; or (b) conducting a test at least annually using a portable analyzer and AQMD-approved test method. The test shall be conducted when the equipment is operating under normal conditions to demonstrate compliance with BACT. The operator shall comply with all general testing, reporting, and recordkeeping requirements in Sections E and K of this permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D27]

D381.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a quarterly basis, at least, unless the equipment did not operate during the entire quarterly period. The routine quarterly inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions; and
- 3). Date and time visible emission was abated.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C140]

E. Equipment Operation/Construction Requirements

E17.1 The operator shall not use more than 1 of the following items simultaneously:

Device ID: D47 [QUENCH TANK]

Device ID: D156 [QUENCH TANK]

[Devices subject to this condition : D47, D156]

E102.1 The operator shall discharge dust collected in this equipment only into closed containers.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C30, C31, C32, C33, C34, C140, C196]

E144.1 The operator shall vent this equipment, during filling, only to the vessel from which it is being filled.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D4]

E149.1 The operator shall replace the scrubbing water with fresh water at least once every day.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C26]

E193.1 The operator shall operate and maintain this equipment as follows:

The operator shall bleed periodically scrubbing water and replenish with fresh water to maintain operability of the scrubber.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C26]

E193.2 The operator shall operate and maintain this equipment as follows:

The operator shall use a nitrogen blanket to maintain the pressure greater than 1.5 inches water column.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D5]

H. Applicable Rules

H23.1 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|--------------|---------------|--------------|
| Refrigerants | District Rule | 1415 |

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1415, 10-14-1994]

[Devices subject to this condition : E18]

K. Record Keeping/Reporting

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records for all coating consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coatings.

For architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coatings.

[**RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : E17]

K67.2 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

material processed by Dryer D137

[**RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D137]

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|---------------|---|--------------------------------|------------------------------|
| Process 3: AIR POLLUTION CONTROL | | | | | |
| System 2: DUST CONTROL SYSTEM | | | | | |
| FILTER, DUST COLLECTOR, DONALDSON TORIT, MODEL DFO 3-3, 570 SQ. FT. FILTER AREA, 5-HP EXHAUST BLOWER A/N: 470895 Permit to Construct Issued: 01/03/08 | C148 | D155 | | PM: (9) [RULE 404, 2-7-1986] | D322.1, D323.2, E102.1 |
| Process 4: FOOD | | | | | |
| System 11: FLAVOR EXTRACTION SYSTEM NO. 5 (RED LINE) | | | | | |
| LOADING ARM, DRUM DUMPER A/N: 481942 Permit to Construct Issued: 01/01/10 | D149 | | | | |
| HOPPER, FEED, 30 GALLON CAPACITY A/N: 481942 Permit to Construct Issued: 01/01/10 | D150 | C30 | | | |
| DRYER, NIRO, MODEL NO. D7700, FLUIDIZED BED TYPE, 500-KG CAPACITY, STEAM HEATED A/N: 481942 Permit to Construct Issued: 01/01/10 | D151 | C152 | | | B27.1, C1.7, C1.8, E71.1 |
| FILTER, NIRO, MODEL NO. DC7700, WITH 16 FILTERS, 139 SQ. FT. TOTAL FILTER AREA. A/N: 481942 Permit to Construct Issued: 01/01/10 | C152 | C30 D151 C153 | | PM: (9) [RULE 404, 2-7-1986] | |
| CONDENSER, NIRO, MODEL NO. E7701 A/N: 481942 Permit to Construct Issued: 01/01/10 | C153 | C30 C152 D154 | | | B27.1, D182.2 |

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions* And Requirements | Conditions |
|--|--------|--------------|---|-------------------------------------|------------|
| Process 4: FOOD | | | | | |
| HEAT EXCHANGER, NIRO, MODEL NO. E7702 A/N: 481942 Permit to Construct Issued: 01/01/10 | D154 | C153 | | | |
| UNLOADING STATION, WITH FOUR UNLOADING POINTS A/N: 481942 Permit to Construct Issued: 01/01/10 | D155 | C148 | | PM: (9) [RULE 405, 2-7-1986] | D323.2 |

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
MCP FOODS INC**

SECTION H: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

**FACILITY PERMIT TO OPERATE
MCP FOODS INC**

SECTION H: DEVICE ID INDEX

| Device Index For Section H | | | |
|-----------------------------------|---------------------------|----------------|---------------|
| Device ID | Section H Page No. | Process | System |
| C148 | 1 | 3 | 2 |
| D149 | 1 | 4 | 11 |
| D150 | 1 | 4 | 11 |
| D151 | 1 | 4 | 11 |
| C152 | 1 | 4 | 11 |
| C153 | 1 | 4 | 11 |
| D154 | 2 | 4 | 11 |
| D155 | 2 | 4 | 11 |

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F14.1 The operator shall not purchase diesel fuel containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

F14.2 The operator shall not burn diesel fuel containing sulfur compounds in excess of 500 ppm by weight.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

SYSTEM CONDITIONS

S1.1 The operator shall limit the throughput to no more than 554400 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as finished Durarome product from the Red Line.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 4, System 11]

S1.2 The operator shall limit the throughput to no more than 4000 lb(s) in any one day.

For the purpose of this condition, throughput shall be defined as finished product from the J Line.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 4, System 12]

- S1.3 The operator shall limit the throughput to no more than 83,348 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as isopropyl alcohol usage.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 4, System 9]

- S1.4 The operator shall limit the throughput to no more than 450000 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as product from the Continuous Line, including off spec and discarded material.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 4, System 9]

- S1.5 The operator shall limit the throughput to no more than 443520 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as finished Durarome product from the Silver Line.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 4, System 3]

- S1.6 The operator shall limit the throughput to no more than 403920 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as finished Durarome product from the Yellow Line.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 4, System 4]

- S1.7 The operator shall limit the throughput to no more than 261360 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as finished Durarome product from the Orange Line.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 4, System 5]

- S1.8 The operator shall limit the throughput to no more than 251460 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as finished Durarome product from the Tan Line.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 4, System 6]

DEVICE CONDITIONS

B. Material/Fuel Type Limits

B27.1 The operator shall not use materials containing any toxic air contaminants (TACs) identified in the SCAQMD Rule 1401 (except for those compounds listed below), as amended 03/04/2005.

| COMPOUND | CAS NO. |
|-------------------|---------|
| Acetaldehyde | 75-07-0 |
| Isopropyl Alcohol | 67-63-0 |

[RULE 1401, 3-4-2005]

[Devices subject to this condition : D151, C153]

C. Throughput or Operating Parameter Limits

C1.7 The operator shall limit the material processed to no more than 11,000 lb(s) in any one day.

To comply with this condition, the operator shall maintain adequate records. Such records shall be kept on the premises for at least five years and be made available to the Executive Officer or his representative upon request..

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D151]

C1.8 The operator shall limit the solvent usage to no more than 1,320 lb(s) in any one day.

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, solvent used shall be defined as Isopropyl alcohol.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D151]

D. Monitoring/Testing Requirements

D182.2 The operator shall test this equipment in accordance with the following specifications:

The test shall measure the total Isopropyl Alcohol collected (condensed) from the condenser per batch.

The test shall determine the weight concentration of the of Isopropyl Alcohol in the collected (condensed) solution from the condenser.

The test shall be conducted on a batch with the highest content of Isopropyl Alcohol (12 weight percent).

The test shall be conducted on a maximum batch weight (1,100 lbs/batch).

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : C153]

D322.1 The operator shall perform annual inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[**RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : C148]

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D323.2 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a semi-annual basis, at least, unless the equipment did not operate during the entire semi-annual period. The routine semi-annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.
In addition, the operator shall have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within 72 hours of conversion to fuel oil firing and on a weekly basis thereafter, until the equipment stops firing fuel oil.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and

FACILITY PERMIT TO OPERATE MCP FOODS INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

- 4). All visible emission observation records by operator or a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C148, D155]

E. Equipment Operation/Construction Requirements

- E71.1 The operator shall not process materials containing any Toxic Air Contaminant (TACs), identified in the SCAQMD Rule 1401, as amended 03/04/05, in this equipment except for Acetaldehyde and Isopropyl Alcohol.

[RULE 1401, 3-4-2005]

[Devices subject to this condition : D151]

- E102.1 The operator shall discharge dust collected in this equipment only into closed containers.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C148]