

FACILITY PERMIT TO OPERATE

**DUCOMMUN AEROSTRUCTURES INC
801 ROYAL OAK DR
MONROVIA, CA 91016**

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By _____
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	DRAFT	05/22/2008
B	RECLAIM Annual Emission Allocation	DRAFT	05/22/2008
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	DRAFT	05/22/2008
E	Administrative Conditions	DRAFT	05/22/2008
F	RECLAIM Monitoring and Source Testing Requirements	DRAFT	05/22/2008
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	DRAFT	05/22/2008
H	Permit To Construct and Temporary Permit to Operate	DRAFT	05/22/2008
I	Compliance Plans & Schedules	DRAFT	05/22/2008
J	Air Toxics	DRAFT	05/22/2008
K	Title V Administration	DRAFT	05/22/2008
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	DRAFT	05/22/2008
B	Rule Emission Limits	DRAFT	05/22/2008

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION A: FACILITY INFORMATION

LEGAL OWNER &/OR OPERATOR: DUCOMMUN AEROSTRUCTURES INC

LEGAL OPERATOR (if different than owner):

EQUIPMENT LOCATION: 801 ROYAL OAK DR
MONROVIA, CA 91016

MAILING ADDRESS: 801 ROYAL OAK DR
MONROVIA, CA 91016

RESPONSIBLE OFFICIAL: DON BACH

TITLE: VICE PRESIDENT - OPERATIONS

TELEPHONE NUMBER: (626) 305-3214

CONTACT PERSON: PHILIP TAMAYO

TITLE: MANAGER EHS

TELEPHONE NUMBER: (626) 305-3250

TITLE V PERMIT ISSUED: July 28, 2003

TITLE V PERMIT EXPIRATION DATE: July 27, 2008

TITLE V	RECLAIM
---------	---------

YES	NOx: NO SOx: NO CYCLE: 0 ZONE: INLAND
-----	--

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC**

SECTION B: RECLAIM Annual Emission Allocation

NOT APPLICABLE

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC**

SECTION C: FACILITY PLOT PLAN

(TO BE DEVELOPED)

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

Facility Equipment and Requirements (Section D)

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

Application number	Permit to Operate number	Equipment description
430371	F71725	OVEN, BAKING
430372	F71726	SCRUBBER, OTHER VENTING S.S.
430374	F71727	OVEN, BAKING
430375	F71728	OVEN, BAKING
430376	F71729	OVEN, BAKING
430379	F71730	OVEN, BAKING
430380	F71731	OVEN, DRYING
430381	F71732	TANK, SURFACE PREPARATION
430382	F71733	OVEN, DRYING
430383	F71734	TANK, SURFACE PREPARATION
430384	F71736	SCRUBBER, OTHER VENTING S.S.
430385	F71738	DEGREASER PERC
430387	F71739	SPRAY BOOTH PAINT AND SOLVENT
430388	F71740	TANK, CHROMIC ACID - ANODIZING
430389	F71741	SPRAY BOOTH PAINT AND SOLVENT
430390	F71742	SPRAY BOOTH PAINT AND SOLVENT
430392	F71744	SPRAY BOOTH PAINT AND SOLVENT
430394	F71746	SPRAY BOOTH PAINT AND SOLVENT
430396	F71747	ABRASIVE BLASTING
430398	F71748	DUST COLLECTOR CARTRIDGE TYPE
430399	F71749	TANK, CHROMIC ACID - ANODIZING
430400	F71750	TANK, CHROMIC ACID -
430401	F71751	MESH PADS, TOXIC GAS STREAM
430402	F71752	MESH PADS, TOXIC GAS STREAM
430404	F71754	MESH PADS, TOXIC GAS STREAM
430406	F71755	MESH PADS, TOXIC GAS STREAM
430410	F77116	OVEN, CURING
437283	F77117	SPRAY BOOTH PAINT AND SOLVENT
437284	F77118	SPRAY BOOTH PAINT AND SOLVENT
476446	FXXXXX	SPRAY BOOTH PAINT AND SOLVENT
478401	FXXXXX	OVEN, CURING

NOTE: EQUIPMENT LISTED ABOVE THAT HAVE NO CORRESPONDING PERMITS TO OPERATE NUMBER ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT.

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

FACILITY WIDE CONDITION(S)

Condition(s):

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:
 - A. AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGLEMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
 - B. OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (a) OF THIS CONDITION.
[RULE 401]
2. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS FACILITY SHALL NOT EXCEED 10,690 POUNDS IN ANY ONE CALENDAR MONTH.
[RULE 1303(b)(2)-OFFSET]
3. THE TOTAL QUANTITY OF HEXAVALENT CHROMIUM EMISSIONS FROM THIS FACILITY SHALL NOT EXCEED 1.41 POUNDS PER YEAR.
[RULE 1401, AB2588]
4. MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY AND SUBJECT TO DISTRICT RULES SHALL BE KEPT CURRENT AND MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]
5. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS FACILITY TO VERIFY THE VOC AND HEXAVALENT CHROMIUM EMISSIONS IN POUNDS AND THE VOC AND HEXAVALENT CHROMIUM CONTENT OF EACH MATERIAL APPLIED INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 109, 1303(b)(2)-OFFSET, 1401]
6. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC AND HEXAVALENT CHROMIUM EMISSIONS FOR THE MONTH FROM ALL EQUIPMENT AND OPERATIONS COVERED BY THE MONTHLY/ANNUAL LIMIT. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.
[RULE 109, 1303(b)(2)-OFFSET, 1401]
7. THE OPERATOR SHALL MAINTAIN A SINGLE LIST, WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC AND HEXAVALENT CHROMIUM CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.
[RULE 109, 1303(b)(2)-OFFSET, 1401]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

8. THE OPERATOR SHALL RETAIN ALL PURCHASE INVOICES FOR ALL VOC AND HEXAVALENT CHROMIUM CONTAINING MATERIAL USED OR STORED AT THE FACILITY AND ALL WASTE MANIFESTS FOR ALL WASTE VOC AND HEXAVALENT CHROMIUM CONTAINING MATERIAL REMOVED FROM THE FACILITY.
[RULE 109, 1303(b)(2)-OFFSET, 1401]

9. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED AT THE FACILITY FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET, 1401]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

Permit No. F71725
A/N 430371

Equipment Description:

OVEN, CIRCLE, 6'-0" W. X 22'-0" L. X 7'-0" H., 1,500,000 BTU PER HOUR INDIRECT GAS FIRED, WITH ONE 1/3 HP BURNER BLOWER, ONE 1/2 HP EXHAUST BLOWER, AND ONE 5 HP CIRCULATING BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE TOTAL QUANTITY OF COATINGS AND SOLVENTS USED IN THE COATING OF ARTICLES PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 10 GALLONS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT;
OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

- 5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
 - CO: 2000 PPMV, RULE 407
 - PM: 0.1 GR/SCF, RULE 409
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F71726
A/N 430372**

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. SCRUBBER, TELCAMP SYSTEM, HORIZONTAL PACKED TYPE, 8'-0" W. X 11'-6" L. X 9'-0" H., WITH TWO 3 HP PUMPS.
2. EXHAUST SYSTEM WITH ONE 3 HP BLOWER VENTING ONE PHOSPHORIC ANODIZING TANK.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE FLOW RATE OF THE SCRUBBING SOLUTION IS NOT LESS THAN 120 GPM. TO COMPLY WITH THIS CONDITION THE OPERATOR SHALL INSTALL AND MAINTAIN A FLOW METER TO ACCURATELY INDICATE THE FLOW RATE OF THE SCRUBBING SOLUTION. THE OPERATOR SHALL DETERMINE AND RECORD THE PARAMETER BEING MONITORED ONCE EVERY DAY.
[RULE 3004 (a)(4)]

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F71727
A/N 430374**

Equipment Description:

OVEN, 28'-0" W. X 13'-6" L. X 7'-10" H., 49.5 KW, ELECTRICALLY HEATED, WITH TWO 1/4 HP CIRCULATING FANS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES. THE
[RULE 204]

Emissions and Requirements:

3. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

Permit No. F71728
A/N 430375

Equipment Description:

OVEN, 30'-9" W. X 8'-0" L. X 10'-3" H., 110 KW, ELECTRICALLY HEATED, WITH ONE 3/4 HP EXHAUST BLOWER AND ONE 10 HP CIRCULATING BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F71729
A/N 430376**

Equipment Description:

OVEN, COATES ELECTRIC, 5'-11" W. X 9'-10" L. X 8'-10" H., 45 KW, ELECTRICALLY HEATED, WITH THREE 1/3 HP CIRCULATING FANS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F71730
A/N 430379**

Equipment Description:

OVEN, COATES ELECTRIC, 8'-9" W. X 12'-5" L. X 8'-4" H., 80 KW, ELECTRICALLY HEATED, WITH FOUR 1/3 HP CIRCULATING FANS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F71731
A/N 430380**

Equipment Description:

OVEN, CIRCLE INDUSTRIAL, MODEL NO. 10710150, S/N 4620; 11'-0" W. X 11'-0" L. X 8'-0" H., 76 KW ELECTRICALLY HEATED, WITH ONE 5 HP CIRCULATING FAN AND ONE 3 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 175 DEGREES F.
[RULE 401]

Periodic Monitoring:

4. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL RECORD THE OVEN TEMPERATURE ONCE EVERY DAY.
[RULE 3004(a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

Permit No. F71732
A/N 430381

Equipment Description:

AN ALODINING LINE CONSISTING OF:

1. AN ANODIZING TANK NO. 3239-3, ALODINE SOLUTION, 1'-0" W. X 27'-0" L. X 2'-0" D., UNHEATED.
2. ASSOCIATED RINSE TANKS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. ALODINE TANK NO. 3239-3 SHALL NOT BE HEATED.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F71733
A/N 430382**

Equipment Description

OVEN, CIRCLE, MODEL NO. C.I.M. 6-7-20; 6'-0" W. X 20'-0" L. X 7'-0" H., ELECTRIC HEATED 100 KW, WITH ONE 10 H.P. CIRCULATING FAN AND ONE 1/2 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 350 DEGREES F.
[RULE 401]

Periodic Monitoring:

4. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL RECORD THE OVEN TEMPERATURE ONCE EVERY DAY.
[RULE 3004(a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

Permit No. F71734
A/N 430383

Equipment Description:

A METAL FINISHING LINE CONSISTING OF

1. CHEMICAL ETCH TANK NO. 3242-23 (BLDG. U), HYDROCHLORIC ACID, 2'-6" W. X 24'-0" L. X 3'-0" D., HEATED WITH 10 KW ELECTRIC HEATER, VENTED TO AIR POLLUTION CONTROL EQUIPMENT.
2. CHEMICAL ETCH TANK NO. 3242-15 (BLDG U), SULFURIC ACID, 2'-6" W. X 4'-11" L. X 4'-0" D., HEATED WITH 9 KW ELECTRIC HEATER, VENTED TO AIR POLLUTION CONTROL EQUIPMENT.
3. PICKLE TANK NO. 3242-6 (BLDG U) NITRIC ACID, 4'-6" W. X 10'-0" L. X 1'-6" D., HEATED WITH 1.5 KW ELECTRIC HEATER, VENTED TO AIR POLLUTION CONTROL EQUIPMENT.
4. STRIP TANK NO. 3242-16 (BLDG U), NITRIC ACID, 2'-0" W. X 4'-11" L. X 4'-0" D., HEATED WITH 9 KW ELECTRIC HEATER, VENTED TO AIR POLLUTION CONTROL EQUIPMENT.
5. PASSIVATION TANK NO. 3242-12 (BLDG U), NITRIC ACID, 0'- 11" W. X 4'-11" L. X 4'-0" D., HEATED WITH 4.5 KW ELECTRIC HEATER, VENTED TO AIR POLLUTION CONTROL EQUIPMENT.
6. STAINLESS STEEL ETCH TANK NO. 3242-7 (BLDG U), SULFURIC ACID, 3'-0" W. X 20'-0" L. X 3'-0" D., HEATED WITH 49.5 KW ELECTRIC HEATER, VENTED TO AIR POLLUTION CONTROL EQUIPMENT.
7. STAINLESS STEEL, DESMUTTING TANK NO. 3242-18 (BLDG U), SULFURIC ACID, 0'-11" W. X 4'-11" L. X 4'-0" D., HEATED WITH 12 KW ELECTRIC HEATER, VENTED TO AIR POLLUTION CONTROL EQUIPMENT.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO CONSTRUCT OR PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

Emissions And Requirements:

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F71736
A/N 430384**

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. HORIZONTAL FUME SCRUBBER, HARRINGTON, MODEL ECH 9 9-5 LB, WITH TWO 7-1/2 H.P. RECIRCULATION PUMPS, FORTY-FIVE SPRAY NOZZLES, 5 FEET PACKING DEPTH CONTAINING 3-1/2 INCH DIAMETER LANTEC POLY-PROPYLENE PACKING, A BLADE TYPE MIST ELIMINATOR, AND A 98.6 CUBIC FOOT SUMP.
2. EXHAUST SYSTEM WITH A 35.3 BHP EXHAUST FAN VENTING NINE PROCESS TANK NOS. 3242-1, 3242-4, 3242-15, 3242-17, 3242-24, 3242-26, 3242-27, 3242-31, 3242-33, LOCATED IN BUILDING "U".

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. A FLOWMETER SHALL BE INSTALLED AND MAINTAINED IN THE RECIRCULATING WATER LINE. IN PRACTICE, THE RECIRCULATION FLOW RATE SHALL NOT BE LESS THAN 324 GALLONS PER MINUTE.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL DETERMINE AND RECORD THE FLOW RATE OF THE SCRUBBING SOLUTION ONCE EVERY DAY.
[RULE 3004(a)(4)]
5. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE pH OF THE SCRUBBING SOLUTION IS NOT LESS THAN 7.1 OF THE pH SCALE. TO COMPLY WITH THIS CONDITION THE OPERATOR SHALL INSTALL AND MAINTAIN A pH METER TO ACCURATELY INDICATE THE pH OF THE SCRUBBING SOLUTION. THE OPERATOR SHALL DETERMINE AND RECORD THE PARAMETER BEING MONITORED ONCE EVERY DAY.
[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

Permit No. F71738
A/N 430385

Equipment Description:

DEGREASING SYSTEM, SEREC, AIRLESS LOW EMISSION CLOSED LOOP VACUUM VAPOR TYPE, CONSISTING OF:

1. CLEANING COMPARTMENT #1, 2'-0" DIA. X 22'-0" L., 518 GALLONS CAPACITY
2. CLEANING COMPARTMENT #2, 5'-0" W. X 13'-0" L. X 1'-6" H., 730 GALLONS CAPACITY
3. STEAM HEATED, WITH A 10 HP VACUUM PUMP AND A 20 HP VACUUM PUMP
4. SOLVENT HOLDING TANK, 3'-6" DIA. X 10'-0" L., 660 GALLONS CAPACITY
5. VAPOR SUPPLY TANK, 2'-0" DIA. X 13'-0" L., 350 GALLONS CAPACITY
6. DISTILLATION TANK, 3'-0" DIA. X 3'-0" L., 160 GALLONS CAPACITY
7. CHILLED WATER PRIMARY COOLER
8. ONE CARBON BED FILTER, 85 GALLON DRUM

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE EQUIPMENT SHALL BE OPERATED IN COMPLIANCE WITH RULE 1122 AND 40CFR 63, SUBPART T.
[RULE 1122, 40CFR63 SUBPART T]
4. THE OPERATOR SHALL ONLY USE PERCHLOROETHYLENE AS THE CLEANING SOLVENT IN THIS DEGREASER.
[RULE 1303(b)(2)-OFFSET]
5. A MONITOR SHALL BE INSTALLED AND MAINTAINED IN THE EXHAUST OF THE CARBON BED FILTER TO MEASURE THE CONCENTRATION OF PERCHLOROETHYLENE IN PPM.
[RULE 1401, 40CFR63 SUBPART T]
6. THE CONCENTRATION OF PERCHLOROETHYLENE IN THE EXHAUST OF THE CARBON BED FILTER SHALL NOT EXCEED 25 PPM.
[RULE 1401, 40CFR63 SUBPART T]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

7. THE OPERATOR SHALL RECORD THE CONCENTRATION OF PERCHLOROETHYLENE IN THE EXHAUST OF THE CARBON BED FILTER AT LEAST ONCE EACH DAY OF OPERATION.
[RULE 1401, 40CFR63 SUBPART T]
8. NO MORE THAN 250 CLEANING LOADS SHALL BE PROCESSED IN THIS DEGREASER IN ANY CALENDAR MONTH.
[RULE 1401, 40CFR63 SUBPART T]
9. THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE NUMBER OF LOADS CLEANED IN THIS DEGREASER EACH CALENDAR MONTH.
[RULE 1401, 40CFR63 SUBPART T]
10. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED AT THE FACILITY FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.
[RULE 109, 1401, 40CFR63 SUBPART T]
11. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN RULE 1401, TABLE 1, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

Emissions And Requirements:

12. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1122
HAP: 40 CFR 63, SUBPART T, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

Permit No. F71739
A/N 430387

Equipment Description:

SPRAY BOOTH NO. 3030, CIRCLE, FLOOR TYPE, 41'-6" W. X 37'-3" L. X 10'-3" H., WITH NINETY-TWO 20" X 20" EXHAUST FILTER, AND THREE 15-H.P. EXHAUST FANS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS ALL EXHUAST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]
5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY HEXAVALENT CHROMIUM.
[RULE 1401]
6. IN ADDITION TO RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOC EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

7. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

- FILTER MEDIA;
- B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
- C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
[RULE 3004 (a)(4)]
8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTERS ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

Emissions And Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
HAP(s): 40CFR63, SUBPART GG, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

Permit No. F71740
A/N 430388

Equipment Description:

AN ANODIZING LINE CONSISTING OF:

1. AN ANODIZING TANK NO. 3240-9, PHOSPHORIC ACID, 4'-0" W. X 33'-0" L. X 7'-0" D., HEATED WITH 22.5 KW ELECTRIC HEATER, VENTED TO AIR POLLUTION CONTROL EQUIPMENT.
2. A DEOXIDIZING TANK NO. 3240-3, SULFURIC ACID, 4'-0" W. X 33'-0" L. X 7'-0" D., HOT WATER HEATED VENTED TO AIR POLLUTION CONTROL EQUIPMENT.
3. A DEOXIDIZING TANK NO. 3240-4, SULFURIC ACID, 4'-0" W. X 33'-0" L. X 7'-0" D., HOT WATER HEATED VENTED TO AIR POLLUTION CONTROL EQUIPMENT.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. TANK NOS. 3240-9, 3240-3 AND 3240-4 SHALL NOT BE OPERATED UNLESS THEY ARE VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED AN OPERATING PERMIT BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F71741
A/N 430389**

Equipment Description:

SPRAY BOOTH NO. 3010A, BINKS, FLOOR TYPE, SHEILA MODEL 300-8T, 12'-0" W. X 32'-0" L. X 8'-0" H., WITH THREE 60" X 60" EXHAUST FILTERS, AND ONE 7 ½ H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS ALL EXHUAST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]
5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY HEXAVALENT CHROMIUM.
[RULE 1401]
6. IN ADDITION TO RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOC EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

7. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

- FILTER MEDIA;
- B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
- C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
[RULE 3004 (a)(4)]
8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTERS ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

Emissions And Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
HAP(s): 40CFR63, SUBPART GG, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F71742
A/N 430390**

Equipment Description:

SPRAY BOOTH NO. 3010E, BINKS, FLOOR TYPE, 19'-0" W. X 32'-0" L. X 8'-0" H., WITH THREE 60" X 60" EXHAUST FILTERS, AND ONE 7 ½ H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]
5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY HEXAVALENT CHROMIUM.
[RULE 1401]
6. IN ADDITION TO RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOC EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

7. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

- FILTER MEDIA;
- B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
- C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
[RULE 3004 (a)(4)]
8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTERS ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

Emissions And Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
HAP(s): 40CFR63, SUBPART GG, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

Permit No. F71744
A/N 430392

Equipment Description:

SPRAY BOOTH NO. 3036, BLEEKER, FLOOR TYPE, MODEL F-20-8, 20'-0" W. X 12'-0" L. X 8'-0" H., WITH FORTY-FOUR 20" X 20" PRIMARY EXHAUST FILTERS, FORTY-FOUR 20" X 20" SECONDARY EXHAUST FILTERS, FOURTEEN 24" X 24" X 12" HEPA EXHAUST FILTERS AND ONE 10 H.P. EXHAUST BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE PRIMARY, SECONDARY EXHAUST FILTERS AND HEPA EXHAUST FILTERS.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS EACH SET OF EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER FOR THE PREFILTER AND 1.6 INCHES OF WATER FOR THE HEPA EXHAUST FILTERS.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 61 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER WITH THE EXCEPTION OF HEXAVALENT CHROMIUM.
[RULE 1401]
7. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE VOC AND HEXAVALENT CHROMIUM EMISSIONS IN POUNDS AND THE VOC AND HEXAVALENT CHROMIUM CONTENT OF EACH MATERIAL APPLIED INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 109, 1303(b)(2)-OFFSET, 1401]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTERS ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
HAP(s): 40CFR63, SUBPART GG, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

Permit No. F71746
A/N 430394

Equipment Description:

SPRAY BOOTH NO. 3038, CIRCLE INDUSTRIAL, DRY FILTER TYPE, 25'-0" W. X 12'-0" L. X 7'-0" H., WITH FORTY-FOUR 20" X 20" PRIMARY EXHAUST FILTERS, FORTY-FOUR 20" X 20" SECONDARY EXHAUST FILTERS, FOURTEEN 24" X 24" X 12" HEPA EXHAUST FILTERS AND TWO 7.5 H.P. EXHAUST BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE PRIMARY, SECONDARY EXHAUST FILTERS AND HEPA EXHAUST FILTERS.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS EACH SET OF EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER FOR THE PRIMARY EXHAUST FILTERS AND 1.6 INCHES OF WATER FOR THE HEPA EXHAUST FILTERS.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 26 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER WITH THE EXCEPTION OF HEXAVALENT CHROMIUM.
[RULE 1401]
7. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE VOC AND HEXAVALENT CHROMIUM EMISSIONS IN POUNDS AND THE VOC AND HEXAVALENT CHROMIUM CONTENT OF EACH MATERIAL APPLIED INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 109, 1303(b)(2)-OFFSET, 1401]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTERS ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
HAP(s): 40CFR63, SUBPART GG, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

Permit No. F71747
A/N 430396

Equipment Description:

ABRASIVE BLASTING SYSTEM CONSISTING OF:

1. ABRASIVE BLASTING CABINET, ZERO PRODUCTS, MODEL A200, 6'-0" L. X 5'-0" W. X 5'-6" H.
2. SIX NOZZLES WITH A MAXIMUM INSIDE DIAMETER OF 3/8", MAXIMUM AIR PRESSURE OF 80 PSIG.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED AN OPERATING PERMIT BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT;
OR

- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

- 5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
 - PM: RULE 1140, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F71748
A/N 430398**

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF

1. DUST COLLECTOR, ZERO PRODUCTS, MODEL RPH-4L, WITH 4 CARTRIDGE-TYPE FILTERS, 13" X 36" EACH, TOTAL FILTER AREA OF 944 SQ. FT., WITH A REVERSE AIR CLEANING SYSTEM.
2. EXHAUST SYSTEM WITH A 7.5 H.P. BLOWER VENTING ONE ABRASIVE BLASTING CABINET.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. DUST COLLECTED IN THE DUST COLLECTOR SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]
4. A MECHANICAL GAUGE SHALL BE MAINTAINED SO AS TO INDICATE, IN INCHES OF WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE CARTRIDGE FILTERS.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

5. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
 - A. THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

FOLLOWING RECORDS:

- B. STACK OR EMISSION POINT IDENTIFICATION;
 - C. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
AND
 - D. DATE AND TIME VISIBLE EMISSION WAS ABATED.
[RULE 3004(a)(4)]
6. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
[RULE 3004(a)(4)]
7. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE CARTRIDGE FILTER ONCE EVERY WEEK.
[RULE 3004(a)(4)]

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

Permit No. F71749
A/N 430399

Equipment Description:

ANODIZING TANK NO. 3240-10, ANODIZING CHROMIC ACID SOLUTION, 4'-0" W. X 33'-0" L. X 7'-0" D.,
6,500-GALLON CAPACITY, ELECTRICALLY HEATED.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT BY THE DISTRICT.
[RULE 1401, 1469]

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
CR+6 RULE 1469, SEE APPENDIX B FOR REQUIREMENTS, #16

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F71750
A/N 430400**

Equipment Description:

ANODIZING TANK NO. 3240-12, CHROMIC ACID SOLUTION, 3'-0" W. X 3'-0" L. X 2'-0" D., 123 GALLON CAPACITY, ELECTRICALLY HEATED, NO RECTIFIER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

Permit No. F71751
A/N 430401

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. TWO STAGE MESH PAD MIST ELIMINATOR, MIDWEST AIR PRODUCT CO., 5'-6" H. X 4'-0" DIA.
2. EXHAUST SYSTEM WITH A 10 H.P. BLOWER VENTING AN ALODINE WASH TABLE.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL BE IN FULL USE WHENEVER THE ALODINING LINE VENTED TO IT IS IN OPERATION.
[RULE 1303(a)(1)-BACT]
4. A MECHANICAL GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS BOTH MESH PAD MIST ELIMINATORS. THE SCALE ON THE GAUGE SHALL NOT EXCEED FOUR TIMES THE LIMIT SPECIFIED IN CONDITION NO. 5.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL STATIC PRESSURE DIFFERENTIAL ACROSS BOTH STAGES OF MESH PAD SHALL NOT EXCEED 5.25 INCHES OF WATER COLUMN DURING OPERATION.
[RULE 1303(a)(1)-BACT]
6. THE MECHANICAL GAUGES SHALL BE LOCATED SO THAT THEY CAN BE EASILY VIEWED AND ARE IN CLEAR SIGHT OF THE OPERATION OR MAINTENANCE PERSONNEL.
[RULE 1303(a)(1)-BACT]
7. THE OWNER/OPERATOR SHALL MAINTAIN A WEEKLY RECORD OF THE STATIC PRESSURE DIFFERENTIAL, IN INCHES WATER COLUMN, ACROSS THE MESH PAD MIST ELIMINATOR. THIS RECORD SHALL BE KEPT AND MAINTAINED ON SITE.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F71752
A/N 430402**

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. TWO STAGE MIST ELIMINATOR, VERTICAL COMPOSITE MESH PAD TYPE, MAPCO, WITH TWO MESH PADS, EACH 72" W. X 72" L. X 4" THICK.
2. HEPA FILTER HOUSING, CONSERVE ENGINEERING, WITH NINE PREFILTERS, EACH 24" W. X 24" L. X 1" THICK, AND SEVEN HEPA FILTERS, EACH 24" W. X 24" L. X 12" THICK.
3. EXHAUST SYSTEM WITH A 30 H.P. EXHAUST FAN VENTING A CHROMIC ACID ANODIZING TANK NO. 3240-10.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL BE IN FULL USE WHENEVER THE CHROME ANODIZING TANK VENTED TO IT IS IN OPERATION.
[RULE 1401, RULE 1469]
4. THE HEPA FILTERS USED IN THIS EQUIPMENT SHALL BE CERTIFIED BY THE MANUFACTURER TO HAVE A MINIMUM CONTROL EFFICIENCY ON 0.3 MICRON PARTICLES OF AT LEAST 99.97 PERCENT.
[RULE 1401, RULE 1469]
5. DURING TANK OPERATION, HEXAVALENT CHROMIUM EMISSIONS DISCHARGED TO THE ATMOSPHERE SHALL BE LESS THAN 0.006 MG PER AMP-HR.
[RULE 1401, RULE 1469]
6. A MECHANICAL GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS BOTH MESH PAD MIST ELIMINATORS. THE SCALE ON THE GAUGE SHALL NOT EXCEED FOUR TIMES THE LIMIT SPECIFIED IN CONDITION NO. 7.
[RULE 1401, RULE 1469]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

7. THE TOTAL STATIC PRESSURE DIFFERENTIAL ACROSS BOTH STAGES OF MESH PAD SHALL NOT EXCEED 5.25 INCHES OF WATER COLUMN DURING OPERATION.
[RULE 1401, RULE 1469]
8. A MECHANICAL GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE HEPA FILTER SYSTEM. THE SCALE ON THE GAUGE SHALL NOT EXCEED FOUR TIMES THE LIMITS SPECIFIED IN CONDITION NO. 9.
[RULE 1401, RULE 1469]
9. THE TOTAL STATIC PRESSURE DIFFERENTIAL ACROSS THE HEPA FILTER SYSTEM (PREFILTER AND HEPA FILTER) SHALL NOT EXCEED 4.25 INCHES OF WATER COLUMN DURING OPERATION.
[RULE 1401, RULE 1469]
10. A MECHANICAL GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE PREFILTERS AND HEPA FILTERS. THE SCALE ON THE GAUGE SHALL NOT EXCEED FOUR TIMES THE LIMITS SPECIFIED IN CONDITION NO. 11.
[RULE 1401, RULE 1469]
11. THE TOTAL STATIC PRESSURE DIFFERENTIAL ACROSS THE PREFILTER SHALL NOT EXCEED 0.75 INCHES OF WATER COLUMN AND THE DIFFERENTIAL ACROSS THE HEPA FILTER STAGE SHALL NOT EXCEED 3.5 INCHES OF WATER COLUMN DURING OPERATION.
[RULE 1401, RULE 1469]
12. THE MECHANICAL GAUGES SHALL BE LOCATED SO THAT THEY CAN BE EASILY VIEWED AND ARE IN CLEAR SIGHT OF THE OPERATION OR MAINTENANCE PERSONNEL.
[RULE 1401, RULE 1469]
13. THE OWNER/OPERATOR SHALL MAINTAIN A WEEKLY RECORD OF THE STATIC PRESSURE DIFFERENTIAL, IN INCHES WATER COLUMN, ACROSS THE MESH PAD MIST ELIMINATOR AND HEPA FILTER SYSTEM. THIS RECORD SHALL BE KEPT AND MAINTAINED ON SITE.
[RULE 1469]
14. THE OWNER/OPERATOR SHALL ANNUALLY COMPLETE, BY FEBRUARY 1 OF EACH YEAR, AN ONGOING COMPLIANCE STATUS REPORT FOR THE PRECEDING CALENDAR YEAR. THE REPORT SHALL CONTAIN THE INFORMATION IDENTIFIED IN APPENDIX 3 OF RULE 1469. THE REPORT SHALL BE MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 1469]
15. THE OWNER/OPERATOR SHALL REPORT BREAKDOWNS AS REQUIRED BY DISTRICT RULE 430.
[RULE 1469]
16. THE OWNER/OPERATOR SHALL MAINTAIN RECORDS OF EXCESS EMISSIONS INCLUDING, BUT NOT LIMITED TO, RECORDS OF ANY EXCEEDANCES OF THE EMISSION LIMITATION AND/OR PARAMETER MONITORING REQUIREMENTS CONTAINED IN THIS PERMIT. THE RECORDS SHALL INCLUDE THE DATE OF THE OCCURRENCE, THE DURATION, CAUSE (IF KNOWN), AND, WHERE POSSIBLE, THE MAGNITUDE OF ANY EXCESS EMISSIONS.
[RULE 1469]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

17. AFTER THE EFFECTIVE DATE OF RULE 1469, NO PERSON MAY CONSTRUCT OR MODIFY A SOURCE SUCH THAT IT BECOMES A SOURCE SUBJECT TO THIS SECTION WITHOUT SUBMITTING A NOTIFICATION OF CONSTRUCTION OR MODIFICATION TO THE AQMD AND RECEIVING APPROVAL IN ADVANCE TO CONSTRUCT OR MODIFY THE SOURCE. THE NOTIFICATION OF CONSTRUCTION OR MODIFICATION SHALL CONTAIN THE INFORMATION IDENTIFIED IN APPENDIX 4 OF RULE 1469.
[RULE 1469]

18. THE OWNER/OPERATOR SHALL COMPLY WITH THE INSPECTION AND MAINTENANCE REQUIREMENTS LISTED BELOW:
 - A. QUARTERLY VISUAL INSPECTION OF THE DEVICE TO ENSURE THERE IS PROPER DRAINAGE, NO UNUSUAL CHROMIC ACID BUILDUP ON THE MESH PADS, AND NO EVIDENCE OF CHEMICAL ATTACK THAT AFFECTS THE STRUCTURAL INTEGRITY OF THE DEVICE.
 - B. QUARTERLY VISUAL INSPECTION OF THE BACK PORTION OF THE MESH PAD CLOSEST TO THE FAN TO ENSURE THERE IS NO BREAKTHROUGH OF CHROMIC ACID MIST.
 - C. QUARTERLY VISUAL INSPECTION OF THE DUCTWORK FROM TANK TO THE CONTROL DEVICE TO ENSURE THERE ARE NO LEAKS.
 - D. REPAIR ANY LEAKS DETECTED.
 - E. PERFORM WASHDOWN OF THE COMPOSITE MESH PADS IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.
[RULE 1469]

19. THE OWNER/OPERATOR SHALL MAINTAIN INSPECTION AND MAINTENANCE RECORDS FOR THE MESH PAD MIST ELIMINATOR, HEPA FILTERS, AND MONITORING EQUIPMENT TO DOCUMENT COMPLIANCE WITH THE INSPECTION AND MAINTENANCE REQUIREMENTS OF THIS PERMIT. THE RECORD SHOULD IDENTIFY:
 - A. THE DEVICE INSPECTED,
 - B. THE DATE AND TIME OF INSPECTION,
 - C. THE WORKING CONDITION OF THE DEVICE DURING THE INSPECTION,
 - D. ANY MAINTENANCE ACTIVITIES PERFORMED ON THE MESH PAD MIST ELIMINATOR OR PARAMETER MONITORING SYSTEM, AND
 - E. ANY ACTIONS TAKEN TO CORRECT DEFICIENCIES FOUND DURING THE INSPECTION.
[RULE 1469]

20. THE OWNER/OPERATOR SHALL MAINTAIN MONITORING DATA RECORDS THAT ARE USED TO DEMONSTRATE COMPLIANCE WITH THE PARAMETER MONITORING REQUIREMENTS IDENTIFIED IN THIS PERMIT. THE RECORDS SHALL INCLUDE THE DATE AND TIME THE DATA ARE COLLECTED.
[RULE 1469]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

21. THE OWNER/OPERATOR SHALL COMPLY WITH THE INSPECTION AND MAINTENANCE REQUIREMENTS LISTED BELOW:
 - A. WEEKLY INSPECTION FOR CHANGES IN PRESSURE DROP.
 - B. REPLACE THE MESH PADS AND HEPA FILTERS WHEN THEY HAVE EXCEEDED THE ABOVE MENTIONED LIMITS.
[RULE 1469]
22. A LOG CONCERNING THE OPERATION OF THIS EQUIPMENT SHALL BE KEPT ON FILE FOR A MINIMUM OF FIVE YEARS. THE PAST TWO YEARS' RECORDS SHALL BE KEPT ON SITE AND SHALL BE MADE AVAILABLE UPON REQUEST OF DISTRICT PERSONNEL. THIS LOG SHALL CONTAIN THE FOLLOWING INFORMATION:
 - A. A COPY OF THE MANUFACTURER'S CERTIFICATION OF EFFICIENCY FOR THE HEPA FILTERS.
 - B. COPIES OF ALL RECORDS AND REPORTS REQUIRED BY CONDITION NOS. 15 TO 23, INCLUSIVE.
[RULE 1469]
23. THE STACK SHALL DISCHARGE IN AN UPWARD DIRECTION AND THE STACK HEIGHT SHALL NOT BE LESS THAN 25 FEET ABOVE THE GROUND.
[RULE 1401, RULE 1469]

Emissions And Requirements:

24. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
CR+6 RULE 1469, SEE APPENDIX B FOR REQUIREMENTS, #16

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F71754
A/N 430404**

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. HORIZONTAL FLOW TWO STAGE MESH PAD MIST ELIMINATOR, MIDWEST AIR PRODUCT CO., 5'-11" W. X 9'-0" L. X 6'-11" H.
2. EXHAUST SYSTEM WITH A 30 H.P. BLOWER VENTING TANK NO. 3240-3.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. A MECHANICAL GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS BOTH MESH PAD MIST ELIMINATORS. THE SCALE ON THE GAUGE SHALL NOT EXCEED FOUR TIMES THE LIMIT SPECIFIED IN CONDITION NO. 4.
[RULE 1303(a)(1)-BACT]
4. THE TOTAL STATIC PRESSURE DIFFERENTIAL ACROSS BOTH STAGES OF MESH PAD SHALL NOT EXCEED 5.25 INCHES OF WATER COLUMN DURING OPERATION.
RULE 1303(a)(1)-BACT]
5. THIS EQUIPMENT SHALL BE IN OPERATION WHENEVER THE DEOXIDATION TANK IS IN OPERATION.
RULE 1303(a)(1)-BACT]

Periodic Monitoring:

6. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE MIST ELIMINATOR ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

Emissions And Requirements:

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F71755
A/N 430406**

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. HORIZONTAL FLOW TWO STAGE MESH PAD MIST ELIMINATOR, MIDWEST AIR PRODUCT CO.,
5'-11" W. X 9'-0" L. X 6'-11" H.
2. EXHAUST SYSTEM WITH A 30 H.P. BLOWER VENTING TANK NO. 3240-4.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. A MECHANICAL GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS BOTH MESH PAD MIST ELIMINATORS. THE SCALE ON THE GAUGE SHALL NOT EXCEED FOUR TIMES THE LIMIT SPECIFIED IN CONDITION NO. 4.
[RULE 1303(a)(1)-BACT]
4. THE TOTAL STATIC PRESSURE DIFFERENTIAL ACROSS BOTH STAGES OF MESH PAD SHALL NOT EXCEED 5.25 INCHES OF WATER COLUMN DURING OPERATION.
RULE 1303(a)(1)-BACT]
5. THIS EQUIPMENT SHALL BE IN OPERATION WHENEVER THE DEOXIDATION TANK IS IN OPERATION.
RULE 1303(a)(1)-BACT]

Periodic Monitoring:

6. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE MIST ELIMINATOR ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

Emissions And Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

**Permit No. F77116
A/N 430410**

Equipment Description:

OVEN, SPRAY TECH, MODEL ST81035PO, 35'-0" W. X 10'-0" L. X 8'-0" H., WITH ONE 2,700,000 BTU/HOUR MAXON CYCLOMAX LOW NOX NATURAL GAS FIRED BURNER, ONE 2 H.P. COMBUSTION BLOWER, TWO 10 H.P. CIRCULATING BLOWERS AND ONE 20 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OXIDE OF NITROGEN (NOX) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NO₂ BY VOLUME ON A DRY BASIS @ 3% OXYGEN, AVERAGED OVER 30 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)-BACT]
4. THE OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 500 DEGREES F.
[RULE 401, 1303(a)(1)-BACT]
5. THIS OVEN SHALL ONLY BE USED FOR CURING PARTS IN A CLOSED MOLD OR CURING COATINGS WITH NO VOC.
[RULE 1303(b)(2)-OFFSET]
6. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE 1 WITH AN EFFECTIVE DATE OF MAY 2, 2003 OR EARLIER.
[RULE 1401]

Periodic Monitoring:

7. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT;
OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

- 8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 407
NO_x: 30 PPMV, RULE 1303(a)(1)-BACT
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

Permit No. F77117
A/N 437283

Equipment Description:

SPRAY BOOTH NO. 3026, CIRCLE INDUSTRIAL MFG., FLOOR TYPE, 33'-0" W. X 45'-0" L. X 10'-0" H., WITH NINETY-SIX 20" X 20" EXHAUST PREFILTERS, TWENTY 24" X 24" PRIMARY FILTERS, TWENTY 24" X 24" X 12" SECONDARY EXHAUST FILTERS, TWENTY 24" X 24" X 12" HEPA EXHAUST FILTERS AND ONE 50 H.P. EXHAUST BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE PREFILTERS, PRIMARY, SECONDARY EXHAUST FILTERS AND HEPA EXHAUST FILTERS.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS EACH SET OF EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER FOR THE PREFILTERS AND 1.6 INCHES OF WATER FOR THE HEPA EXHAUST FILTERS.
[RULE 1303(a)(1)-BACT]
5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER WITH THE EXCEPTION OF HEXAVALENT CHROMIUM.
[RULE 1401]
6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE VOC AND HEXAVALENT CHROMIUM EMISSIONS IN POUNDS AND THE VOC AND HEXAVALENT CHROMIUM CONTENT OF EACH MATERIAL APPLIED INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 109, 1303(b)(2)-OFFSET, 1401]

Periodic Monitoring:

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

7. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
[RULE 3004 (a)(4)]

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTERS ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

Emissions and Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
HAP(S): 40CFR63, SUBPART GG, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO OPERATE

Permit No. F77118
A/N 437284

Equipment Description:

SPRAY BOOTH NO. 3037, BLEEKER, FLOOR TYPE, 16'-0" W. X 12'-0" L. X 8'-0" H., WITH FORTY-FOUR 20" X 20" PRIMARY EXHAUST FILTERS, THIRTY-SIX 20" X 20" X SECONDARY EXHAUST FILTERS, FOURTEEN 24" X 24" X 12" HEPA EXHAUST FILTERS AND ONE 10 H.P. EXHAUST BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE PRIMARY, SECONDARY EXHAUST FILTERS AND HEPA EXHAUST FILTERS.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS EACH SET OF EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER FOR THE PRIMARY EXHAUST FILTERS AND 1.6 INCHES OF WATER FOR THE HEPA EXHAUST FILTERS.
[RULE 1303(a)(1)-BACT]
5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER WITH THE EXCEPTION OF HEXAVALENT CHROMIUM.
[RULE 1401]
6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE VOC AND HEXAVALENT CHROMIUM EMISSIONS IN POUNDS AND THE VOC AND HEXAVALENT CHROMIUM CONTENT OF EACH MATERIAL APPLIED INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 109, 1303(b)(2)-OFFSET, 1401]

Periodic Monitoring:

7. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
[RULE 3004 (a)(4)]
8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTERS ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

Emissions and Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
 - VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 481
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - HAP(S): 40CFR63, SUBPART GG, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO CONSTRUCT

A/N 476446
Granted as of

Equipment Description:

SPRAY BOOTH, AUTOMOTIVE DOWN-DRAFT TYPE, SPRAYTECH, MODEL NO. ST91424 HPFD, 14'-0" W. X 45'-0" L. X 9'-11" H. (INSIDE DIMENSIONS), WITH ONE 13'-1.5" X 42'-8" PRIMARY EXHAUST FILTER, TWENTY 20" x 20" x 15" SECONDARY EXHAUST BAG FILTERS, TWENTY 20" x 20" x 11" HEPA EXHAUST FILTERS, ONE 15 H. P. EXHAUST FAN AND ONE 2,200,000 BTU/HR NATURAL GAS-FIRED HEATER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE PRIMARY, SECONDARY AND HEPA EXHAUST FILTERS.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE PRIMARY FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]
5. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE HEPA FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 2.5 INCH OF WATER AND SHALL NOT BE LOWER THAN 0.5 INCH OF WATER.
[RULE 1303(a)(1)-BACT]
6. THE HEPA FILTERS USED IN THIS EQUIPMENT SHALL BE INDIVIDUALLY DOP TESTED WITH 0.3 MICRON PARTICLES AND CERTIFIED TO HAVE AN EFFICIENCY OF NOT LESS THAN 99.997%.
[RULE 1303(a)(1)-BACT, 1469.1]
7. THIS EQUIPMENT SHALL NOT USE MORE THAN 10,000 CUBIC FEET OF NATURAL GAS IN ANY ONE DAY.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

8. A NON-RESETTABLE TOTALIZING FUEL METER SHALL BE INSTALLED AND MAINTAINED TO VERIFY COMPLIANCE WITH CONDITION NO. 7.
[RULE 1303(a)(1)-BACT]
9. THE OPERATOR SHALL MAINTAIN A FUEL USAGE LOG TO DEMONSTRATE COMPLIANCE WITH CONDITION NO. 7. THE LOG SHALL INCLUDE, AT A MINIMUM, THE DATE THE SPRAY BOOTH IS OPERATED, THE METER READINGS AT THE BEGINNING AND AT THE END OF THE OPERATION, AND THE DAILY FUEL USAGE.
[RULE 1303(a)(1)-BACT]
10. THE TOTAL QUANTITY OF VOC EMISSIONS FROM THIS EQUIPMENT SHALL BE LESS THAN 667 POUNDS IN ANY ONE CALENDAR MONTH.
[RULE 1303(a)(1)-BACT]
11. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER WITH THE EXCEPTION OF HEXAVALENT CHROMIUM (CAS # 18540-29-9), FORMALDEHYDE (CAS # 50-00-0), LEAD & LEAD COMPOUNDS (CAS # 7439-92-1), METHYL ALCOHOL (CAS # 67-56-1), METHYL ETHYL KETONE (CAS # 78-93-3), TOLUENE (CAS # 108-88-3) AND XYLENE (CAS # 1330-20-7).
[RULE 1401]
12. THE TOTAL QUANTITY OF MATERIALS CONTAINING FORMALDEHYDE, LEAD AND LEAD COMPOUNDS AND CHROMIUM & CHROMIUM COMPOUNDS USED IN THIS EQUIPMENT SHALL NOT EXCEED 250 GALLONS IN ANY ONE CALENDAR YEAR.
[RULE 1401]
13. THE MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN MORE THAN THE FOLLOWING:

A.	CHROMIUM & CHROMIUM COMPOUNDS (CAS # 18540-29-9)	30% BY WEIGHT
B.	LEAD & LEAD COMPOUNDS (CAS # 7439-92-1)	10% BY WEIGHT
C.	FORMALDEHYDE (CAS # 50-00-0)	0.004% BY WEIGHT

[RULE 1401]
14. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE VOC AND HEXAVALENT CHROMIUM EMISSIONS IN POUNDS AND THE VOC AND HEXAVALENT CHROMIUM CONTENT OF EACH MATERIAL APPLIED INCLUDING WATER AND EXEMPT COMPOUNDS. RECORDS SHALL ALSO BE KEPT OF PERCENT BY WEIGHT OF CHROMIUM & CHROMIUM COMPOUNDS, LEAD & LEAD COMPOUNDS, AND FORMALDEHYDE CONTAINED IN THE MATERIALS USED IN THIS EQUIPMENT.
[RULE 109, 1303(b)(2)-OFFSET, 1401]
15. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC AND HEXAVALENT CHROMIUM EMISSIONS FOR THE MONTH FROM THIS EQUIPMENT. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

COMPLIANCE WITH DISTRICT RULES.
[RULE 109, 1303(b)(2)-OFFSET, 1401]

16. THE OPERATOR SHALL MAINTAIN A SINGLE LIST, WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC AND HEXAVALENT CHROMIUM CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED IN THIS EQUIPMENT DURING THE PRECEDING 12 MONTHS.
[RULE 109, 1303(b)(2)-OFFSET, 1401]
17. THE OPERATOR SHALL RETAIN ALL PURCHASE INVOICES FOR ALL VOC AND HEXAVALENT CHROMIUM CONTAINING MATERIAL USED IN THIS EQUIPMENT OR STORED AT THE FACILITY AND ALL WASTE MANIFESTS FOR ALL WASTE VOC AND HEXAVALENT CHROMIUM CONTAINING MATERIAL REMOVED FROM THE FACILITY.
[RULE 109, 1303(b)(2)-OFFSET, 1401]

Periodic Monitoring:

18. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
[RULE 3004 (a)(4)]
19. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTERS ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

Emissions and Requirements:

20. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
HAP(S): 40CFR63, SUBPART GG, SEE SECTION J FOR REQUIREMENTS
CR+6: RULE 1469.1

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

PERMIT TO CONSTRUCT

A/N 478401
Granted as of

Equipment Description:

OVEN, SPRAY-TECH, MODEL NO. OVEN36108.5, 10'-0" W. X 35'-0" L. X 8'-0" H., WITH A 2,700,000 BTU/HR INDIRECT NATURAL GAS-FIRED MAXON CYCLOMAX BURNER, A 5 H.P. EXHAUST FAN, A 10 H.P. RECIRCULATION FAN AND A 2 H.P. COMBUSTION AIR BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OXIDE OF NITROGEN (NO_x) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NO₂ BY VOLUME ON A DRY BASIS @ 3% OXYGEN, AVERAGED OVER 30 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)-BACT]
4. THE OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 400 DEGREES F.
[RULE 401, 1303(a)(1)-BACT]
5. THIS OVEN SHALL ONLY BE USED TO PROCESS PARTS COATED IN THE SPRAY BOOTH UNDER APPLICATION NO. 476446.

Periodic Monitoring:

6. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- C. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT;
OR
- D. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 407
NOx: 30 PPMV, RULE 1303(a)(1)-BACT
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

Periodic Monitoring:

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (G/L) OF MATERIALS FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS SUPPLIED IN G/L OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATINGS.

FOR ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS APPLIED IN GRAMS PER LITER (G/L) OF MATERIALS USED FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS APPLIED IN G/L OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATINGS.

[RULE 3004 (a)(4)]

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, LOW USE OR EMISSIONS

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND LAY, BRUSH AND ROLL UP RESIN OPERATIONS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
VOC: RULE 109
VOC: RULE 1162, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, ADHESIVE OPERATIONS, LOW USE OR EMISSIONS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
 - VOC: RULE 109
 - VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, BOILER, > 400,000 BTU/HR BUT < 2 MMBTU/HR.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: 0.1 gr/scf, RULE 409
NOx: 30 PPMV, RULE 1146.2
CO: 400 PPMV, RULE 1146.2
CO: 2000 PPMV, RULE 407

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1415

VOC: 40CFR 82 SUBPART F

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, ABRASIVE BLASTING EQUIPMENT, SHOT PEENING, AND ANY CONTROL EQUIPMENT.

Periodic Monitoring:

1. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
[RULE 3004 (a)(4)]

2. THE OPERATOR SHALL DISCHARGE DUST COLLECTED IN THIS EQUIPMENT ONLY INTO CLOSED CONTAINERS.
[RULE 3004 (a)(4)]

3. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
 - A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
[RULE 3004 (a)(4)]

Emissions And Requirements:

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES, INC

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1140, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION E: ADMINISTRATIVE CONDITIONS

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]
 - a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]
 - b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]
 - c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]
2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]
3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the AQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations, or statutes of other governmental agencies. [204]
4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]
5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation. [204]
6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to AQMD personnel upon request and be maintained for at least five years. [204]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION E: ADMINISTRATIVE CONDITIONS

7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by AQMD rules or permit conditions: [204]
 - a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134]
 - b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]
 - c. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes; [204]
 - d. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compounds which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO₂) and be averaged over 15 consecutive minutes; [407]
 - e. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent of carbon dioxide (CO₂) at standard conditions and averaged over a minimum of 15 consecutive minutes. [409]
 - f. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O₂) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]

8. The operator shall, when a source test is required by AQMD, provide a source test protocol to AQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by AQMD. The test protocol shall contain the following information: [204, 304]
 - a. Brief description of the equipment tested.
 - b. Brief process description, including maximum and normal operating temperatures, pressures, throughput, etc.
 - c. Operating conditions under which the test will be performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream)

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION E: ADMINISTRATIVE CONDITIONS

- e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.
 - f. Description of calibration and quality assurance procedures.
 - g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (conflict of interest).
9. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by AQMD rules or equipment-specific conditions. The report shall contain the following information: [204]
- a. The results of the source test.
 - b. Brief description of the equipment tested.
 - c. Operating conditions under which the test was performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream)
 - e. Field and laboratory data forms, strip charts and analyses.
 - f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.
10. The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of AQMD Source Test Method 1.1 and 1.2. [217]
11. Whenever required to submit a written report, notification or other submittal to the Executive Officer, AQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, AQMD, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182. [204]

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC**

SECTION F: RECLAIM Monitoring and Source Testing Requirements

NOT APPLICABLE

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC**

SECTION G: Recordkeeping and Reporting Requirements for RECLAIM Sources

NOT APPLICABLE

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES, INC**

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

See Section D of this permit for any Permit to Construct issued to this facility.

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION I: PLANS AND SCHEDULES

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules.

NONE

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.

FACILITY PERMIT TO OPERATE

DUCOMMUN AEROSTRUCTURES INC

SECTION J: AIR TOXICS [40CFR 63 Subpart GG 12-8-2000]

NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS FOR AEROSPACE MANUFACTURING AND REWORK FACILITIES

1. The operator shall comply with all applicable requirements of 40 CFR 63, Subpart GG and of 40 CFR 63, Subpart A - General Provisions by the compliance date(s) specified in these subparts.
2. The operator shall conduct all cleaning operations pursuant to all applicable requirements specified in Section 63.744.
3. The operator shall comply with all applicable requirements of Sections 63.745 and 63.747 for all primer, topcoat, and chemical milling maskant application operations. Primers, topcoats, and chemical milling maskants that are applied to aerospace parts without being vented to a control system shall comply with the following limits.

Coating Type	Organic HAP Limits (g/l) (less water)	VOC Limit (g/l) (less water/exempt solvents)
Primer	350	350
Topcoats	420	420
Self-priming Topcoats	420	420
Chemical Milling Maskant Type I	622	622
Chemical Milling Maskant Type II	160	160

For primer, topcoat, and chemical milling maskant application operations that are vented to a control system, each control system shall reduce the operation's organic HAP and VOC emissions to the atmosphere by 81% or greater, taking into account capture and destruction or removal efficiencies, as determined using the procedures in Section 63.750(g) when a carbon adsorber is used and in Section 63.750(h) when a control device other than a carbon adsorber is used.

4. The operator shall comply with all applicable requirements of Section 63.746 for all depainting operations.
5. The operator shall conduct the handling and transfer of the waste to and from containers, tanks, vats, vessels, and piping systems in such a manner that minimizes spills pursuant to Section 63.748.

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION J: AIR TOXICS [40CFR 63 Subpart GG 12-8-2000]

6. The operator shall comply with all applicable requirements of this subpart by the compliance dates specified in Section 63.749.
7. The operator of a facility using any HAP-containing chemicals or control equipment venting such chemicals, that are required by this subpart to conduct chemical analyses and/or performance testing, shall submit a protocol to the AQMD for approval of no less than 60 days prior to testing. The tests shall be conducted in accordance with the test methods and procedures specified in Section 63.750.
8. The operator shall comply with all applicable monitoring requirements specified in Section 63.751.
9. The operator shall keep all records pursuant to Section 63.752 of this subpart and Subpart A to demonstrate compliance with all applicable requirements. All records including data, calculations and any supporting documentation shall be prepared in a format which is acceptable to the AQMD.
10. The operator shall submit all reports, notifications, plans, submittals and other communications required by Section 63.753 of this subpart or Subpart A to the AQMD and, unless notified to the contrary by AQMD or US EPA, to US EPA Region IX (See Sections E and K of this permit for addresses).
11. Alternative plans, compliance plans, and the construction and operation of new or modified air pollution control equipment that are required by this subpart shall be approved through the AQMD permit system.

FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC

SECTION J: AIR TOXICS
[40CFR 63 Subpart T, #31 6-5-1995]

BATCH COLD CLEANING MACHINES

1. The operator shall comply with all applicable requirements and standards of Subpart T and Subpart A - General Provisions by the date(s) specified in these subparts.
2. The operator shall comply with the cleaning machine standards and work practices of 40 CFR 63.462.
3. The operator shall comply with all applicable recordkeeping and reporting required by 40 CFR 63.10 and 63.468. All records and reports, including data, calculations and any supporting documentation shall be prepared in a format which is acceptable to the AQMD.
4. The operator shall file application(s) and be granted approval by the AQMD prior to the installation/modification of equipment to comply with this NESHAP or implementing equivalent methods of control as allowed by 40 CFR 63.469.
5. The operator shall submit all reports, notifications, plans, submittals and other communications required by Subpart T or Subpart A to the AQMD and, unless notified to the contrary by AQMD or US EPA, to US EPA Region IX. (See Sections E and K of this permit for addresses.)

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under Section 129(e) of the Clean Air Act, this permit shall expire five years from the date that the initial Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
 - (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION K: TITLE V Administration

- (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
- (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

- 8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
 - (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

- 9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]
- 10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION K: TITLE V Administration

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]
12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]
13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]
14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]
15. Nothing in this permit or in any permit shield can alter or affect:
 - (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]
16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION K: TITLE V Administration

commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION K: TITLE V Administration

EMERGENCY PROVISIONS

17. An emergency¹ constitutes an affirmative defense to an action brought for non-compliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
 - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
 - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
 - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
 - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
 - (B) The operator complies with the breakdown provisions of Rule 430 - Breakdown Provisions, or subdivision (i) of Rule 2004 - Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

¹ "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION K: TITLE V Administration

RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
 - (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
 - (B) The date(s) analyses were performed;
 - (C) The company or entity that performed the analyses;
 - (D) The analytical techniques or methods used;
 - (E) The results of such analyses; and
 - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:
 - (A) Breakdowns shall be reported as required by Rule 430 - Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.
 - (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION K: TITLE V Administration

- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
 - (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;
 - (B) The compliance status during the reporting period;
 - (C) Whether compliance was continuous or intermittent;
 - (D) The method(s) used to determine compliance over the reporting period and currently, and
 - (E) Any other facts specifically required by the Executive Officer to determine compliance.
- The EPA copy of the certification shall be sent to: Director of the Air Division Attn: Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]
25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION K: TITLE V Administration

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the Title V application file. [3004(a)(4)]

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations:

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 109	5-2-2003	Federally enforceable
RULE 1107	1-6-2006	Non federally enforceable
RULE 1107	11-9-2001	Federally enforceable
RULE 1113	11-8-1996	Federally enforceable
RULE 1113	7-13-2007	Non federally enforceable
RULE 1122	10-1-2004	Federally enforceable
RULE 1124	9-21-2001	Federally enforceable
RULE 1140	2-1-1980	Federally enforceable
RULE 1140	8-2-1985	Non federally enforceable
RULE 1146.2	1-7-2005	Non federally enforceable
RULE 1146.2	1-9-1998	Federally enforceable
RULE 1162	11-17-2000	Federally enforceable
RULE 1162	7-8-2005	Non federally enforceable
RULE 1168	1-7-2005	Non federally enforceable
RULE 1168	10-3-2003	Federally enforceable
RULE 1171	11-7-2003	Federally enforceable
RULE 1171	2-1-2008	Non federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303(a)(1)-BACT	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	12-6-2002	Non federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1401	12-7-1990	Non federally enforceable
RULE 1401	3-4-2005	Non federally enforceable
RULE 1415	10-14-1994	Non federally enforceable
RULE 1469, #16	10-9-1998	Non federally enforceable
RULE 1469.1	3-4-2005	Non federally enforceable
RULE 204	10-8-1993	Federally enforceable
RULE 217	1-5-1990	Federally enforceable

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 219	6-1-2007	Non federally enforceable
RULE 219	9-4-1981	Federally enforceable
RULE 3002	11-14-1997	Federally enforceable
RULE 3003	11-14-1997	Federally enforceable
RULE 3003	3-16-2001	Non federally enforceable
RULE 3004	12-12-1997	Federally enforceable
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3005	3-16-2001	Non federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	6-9-2006	Non federally enforceable
RULE 401	11-9-2001	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 405	2-7-1986	Federally enforceable
RULE 407	4-2-1982	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 409	8-7-1981	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 442	12-15-2000	Federally enforceable
RULE 481	1-11-2002	Federally enforceable
40CFR 63 Subpart GG	12-8-2000	Federally enforceable
40CFR 63 Subpart T, #31	6-5-1995	Federally enforceable
RULE 701	6-13-1997	Federally enforceable
40CFR 82 Subpart F	5-14-1993	Federally enforceable

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN
PERMIT PURSUANT TO RULE 219**

NONE

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1107 1-6-2006]**

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS								
Less Water and Less Exempt Compounds								
Effective Dates								
Coating	Air-Dried				Baked			
	gm/l		lb/gal		gm/l		lb/gal	
	Current	7/1/07	Current	7/1/07	Current	7/1/07	Current	7/1/07
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1107 1-6-2006]**

VOC LIMITS								
Less Water and Less Exempt Compounds								
Effective Dates, cont.								
Coating	Air-Dried				Baked			
	gm/l		lb/gal		gm/l		lb/gal	
	Current	7/1/07	Current	7/1/07	Current	7/1/07	Current	7/1/07
Extreme Performance	420	420	3.5	3.5	360	360	3.0	3.0
Prefabricated Architectural One-Component	420	275	3.5	2.3	275	275	2.3	2.3
Prefabricated Architectural Multi-Component	420	340	3.5	2.8	275	275	2.3	2.3
Touch Up	420	420	3.5	3.5	360	360	3.0	3.0
Repair	420	420	3.5	3.5	360	360	3.0	3.0
Silicone Release	420	420	3.5	3.5	420	420	3.5	3.5
High-Performance Architectural	420	420	3.5	3.5	420	420	3.5	3.5
Camouflage	420	420	3.5	3.5	420	420	3.5	3.5
Vacuum-Metalizing	420	420	3.5	3.5	420	420	3.5	3.5
Mold-Seal	420	420	3.5	3.5	420	420	3.5	3.5
High-Temperature	420	420	3.5	3.5	420	420	3.5	3.5
Electric-Insulating Varnish	420	420	3.5	3.5	420	420	3.5	3.5
Pan Backing	420	420	3.5	3.5	420	420	3.5	3.5
Pretreatment Coatings	420	420	3.5	3.5	420	420	3.5	3.5

- (2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1107 11-9-2001]**

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

<u>Coating</u>	LIMITS			
	Grams of VOC Per Liter of Coating, Less Water and Less Exempt Compounds			
	<u>Air Dried</u>	<u>(lb/gal)</u>	<u>Baked</u>	<u>(lb/gal)</u>
General				
One-Component	275	(2.3)	275	(2.3)
Multi-Component	340	(2.8)	275	(2.3)
Military Specification	340	(2.8)	275	(2.3)
Etching Filler	420	(3.5)	420	(3.5)
Solar-Absorbent	420	(3.5)	360	(3.0)
Heat-Resistant	420	(3.5)	360	(3.0)
Extreme High-Gloss	420	(3.5)	360	(3.0)
Metallic	420	(3.5)	420	(3.5)
Extreme Performance	420	(3.5)	360	(3.0)
Prefabricated Architectural Component	420	(3.5)	275	(2.3)
Touch Up	420	(3.5)	360	(3.0)
Repair	420	(3.5)	360	(3.0)
Silicone Release	420	(3.5)	420	(3.5)
High Performance Architectural	420	(3.5)	420	(3.5)
Camouflage	420	(3.5)	420	(3.5)
Vacuum-Metalizing	420	(3.5)	420	(3.5)
Mold-Seal	420	(3.5)	420	(3.5)
High-Temperature	420	(3.5)	420	(3.5)
Electric-Insulating Varnish	420	(3.5)	420	(3.5)
Pan Backing	420	(3.5)	420	(3.5)
Pretreatment Coatings	420	(3.5)	420	(3.5)

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 11-9-2001]**

- (2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1113 11-8-1996]**

- (1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.
- (2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

TABLE OF STANDARDS

VOC LIMITS

**Grams of VOC Per Liter of Coating,
 Less Water And Less Exempt Compounds**

COATING	Limit*	Effective Date of Adoption	Effective 1/1/1998	Effective 1/1/1999	Effective 7/1/2001	Effective 1/1/2005	Effective 7/1/2008
Bond Breakers	350						
Clear Wood Finishes							
Varnish	350						
Sanding Sealers	350						
Lacquer	680		550			275	
Concrete-Curing Compounds	350						
Dry-Fog Coatings	400						
Fire-proofing Exterior Coatings	350	450		350			
Fire-Retardant Coatings							
Clear	650						
Pigmented	350						
Flats	250					100	
Graphic Arts (Sign) Coatings	500						50
Industrial Maintenance							

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-8-1996]

Primers and Topcoats						
Alkyds	420					
Catalyzed Epoxy	420					
Bituminous Coatings	420					
Materials						
Inorganic Polymers	420					
Vinyl Chloride Polymers	420					
Chlorinated Rubber	420					
Acrylic Polymers	420					
Urethane Polymers	420					
Silicones	420					
Unique Vehicles	420					
Japans/Faux Finishing	350	700		350		
Coatings						
Magnesite Cement Coatings	600			450		
Mastic Coatings	300					
Metallic Pigmented Coatings	500					
Multi-Color Coatings	420		250			
Pigmented Lacquer	680		550		275	
Pre-Treatment Wash Primers	780					
Primers, Sealers, and	350					
Undercoaters						
Quick-Dry Enamels	400					
Roof Coatings	300					
Shellac						
Clear	730					
Pigmented	550					
Stains	350					
Swimming Pool Coatings						
Repair	650					
Other	340					
Traffic Coatings	250		150			
Waterproofing Sealers	400					
Wood Preservatives						
Below-Ground	350					
Other	350					

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 11-8-1996]**

TABLE OF STANDARDS (cont.)

VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 7-13-2007]**

- (1) Except as provided in paragraphs (c)(2), (c)(3), (c)(4), and specified coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage any architectural coating for use in the District which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, and no person shall apply or solicit the application of any architectural coating within the District that exceeds 250 grams of VOC per liter of coating as calculated in this paragraph.
- (2) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified, and no person shall apply or solicit the application of any architectural coating within the District that exceeds the VOC limit as specified in this paragraph. No person shall apply or solicit the application within the District of any industrial maintenance coatings, except anti-graffiti coatings, for residential use or for use in areas such as office space and meeting rooms of industrial, commercial or institutional facilities not exposed to such extreme environmental conditions described in the definition of industrial maintenance coatings; or of any rust-preventative coating for industrial use, unless such a rust preventative coating complies with the Industrial Maintenance Coating VOC limit specified in the Table of Standards.

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1113 7-13-2007]**

**TABLE OF STANDARDS
 VOC LIMITS**

**Grams of VOC Per Liter of Coating,
 Less Water and Less Exempt Compounds**

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Bond Breakers	350							
Clear Wood Finishes	350					275		
Varnish	350					275		
Sanding Sealers	350					275		
Lacquer	680	550			275			
Clear Brushing Lacquer	680				275			
Concrete-Curing Compounds	350						100	
Concrete-Curing Compounds For Roadways and Bridges**	350							
Dry-Fog Coatings	400						150	
Fire-Proofing Exterior Coatings	450	350						
Fire-Retardant Coatings***								
Clear	650							
Pigmented	350							
Flats	250	100						50
Floor Coatings	420		100			50		
Graphic Arts (Sign) Coatings	500							
Industrial Maintenance (IM) Coatings	420			250		100		
High Temperature IM Coatings			420					
Zinc-Rich IM Primers	420		340			100		
Japans/Faux Finishing Coatings	700	350						
Magnesite Cement Coatings	600	450						
Mastic Coatings	300							
Metallic Pigmented Coatings	500							
Multi-Color Coatings	420	250						
Nonflat Coatings	250		150			50		
Nonflat High Gloss	250		150				50	

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 7-13-2007]

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Pigmented Lacquer	680	550			275			
Pre-Treatment Wash Primers	780		420					
Primers, Sealers, and Undercoaters	350		200			100		
Quick-Dry Enamels	400		250			150	50	
Quick-Dry Primers, Sealers, and Undercoaters	350		200			100		
Recycled Coatings			250					
Roof Coatings	300		250		50			
Roof Coatings, Aluminum	500				100			
Roof Primers, Bituminous	350		350					
Rust Preventative Coatings	420		400			100		
Shellac								
Clear	730							
Pigmented	550							
Specialty Primers	350					250	100	
Stains	350		250				100	
Stains, Interior	250							
Swimming Pool Coatings								
Repair	650		340					
Other	340							
Traffic Coatings	250	150					100	
Waterproofing Sealers	400		250			100		
Waterproofing	400					100		
Concrete/Masonry Sealers								
Wood Preservatives								
Below-Ground	350							
Other	350							

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.

** Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

*** The Fire-Retardant Coating category will be eliminated on January 1, 2007 and subsumed by the coating category for which they are formulated.

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 7-13-2007]**

**TABLE OF STANDARDS (cont.)
VOC LIMITS**

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1124 9-21-2001]**

Except as otherwise provided in Rule 1124

- (1) VOC Content of Aerospace Materials
 - (A) A person shall not apply to aerospace components any materials, including any VOC-containing materials added to the original material supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC Limit			
Grams of VOC per Liter, Less Water and Less Exempt Compounds			
Primers	Current VOC Limit	VOC Limit Effective 1-1-03	VOC Limit Effective 1-1-05
General Primer	350	350	350
Low-Solids Corrosion Resistant Primer	350	350	350
Pretreatment Primer	780	780	780
Rain Erosion-Resistant Coating Compatible Primer	850	850	850
Adhesion Promoter	850	850	250
Adhesive Bonding Primer			
New Commercial Aircraft	805	250	250
All Military Aircraft	805	805	805
Remanufactured Commercial Aircraft Parts	805	805	805
Sonic and Acoustic Applications	805	805	805
Adhesive Bonding Primer			
Long Term	250	250	250
Short Term	250	250	250

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1124 9-21-2001]**

Coatings	Current VOC Limit	VOC Limit Effective 3-01-02
Topcoat	420	420
Clear Topcoat	520	520
Unicoat	420	420
Wing Coating	750	750
Impact Resistant Coating	420	420
High-Temperature Coating	850	850
Antichafe Coating	600	420
Rain Erosion-Resistant Coating	800	800
Conformal Coating	750	750
Optical Anti-Reflective Coating	700	700
Scale Inhibitor	880	880
Metallized Epoxy Coating	700	700
Electric or Radiation Effect Coating	800	800
Temporary Protective Coating	250	250
Fuel Tank Coatings	420	420
Mold Release Coatings	780	780
Flight Test Coatings		
Used on Missiles or Single Use Target Craft	420	420
All Other	840	840
Fire Resistant Coatings		
Commercial	650	650
Military	970	800
Wire Coatings		
Phosphate Ester Resistant Ink	925	925
Other	420	420
Space Vehicle Coatings		
Electrostatic Discharge Protection Coating	800	800
Other	1000	1000

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1124 9-21-2001]**

Adhesives	Current VOC Limit
Non-Structural Adhesive	250
Structural Adhesive	
Autoclavable	50
Non-Autoclavable	850
Space Vehicle Adhesive	800
Fuel Tank Adhesive	620

Sealants	Current VOC Limit	VOC Limit Effective 3-01-02
Fastener Sealant	675	675
Extrudable, Rollable or Brushable Sealant	600	280
Other	600	600

Maskants	Current VOC Limit
For Chemical Processing	250
For Chemical Milling	
Type I	250
Type II	160
Photolithographic	850
Touch-up, Line Sealer Maskants	750

Lubricants	Current VOC Limit
Fastener Installation	
Solid-Film Lubricant	880
Dry Lubricative Materials	675
Fastener-Lubricative Coatings, Fastener Manufacturing	
Solid Film Lubricant	250
Dry Lubricative Materials	120
Barrier Coating	420
Non-Fastener Lubricative Coatings, Fastener Manufacturing	
Solid Film Lubricant	880
Dry Lubricative Materials	675

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1124 9-21-2001]**

VOC LIMIT	
Grams of VOC per Liter of Material	
Cleaning Solvents and Strippers	Current VOC Limit
Cleaning Solvents	200 g/L or 45 mm Hg VOC Composite Partial Pressure
Strippers	300 g/L or 9.5 mm Hg VOC Composite Partial Pressure

- (B) Documents shall be provided to the Executive Officer or his designee demonstrating that unicoat is being used in lieu of the application of a primer and topcoat, and the applicant must receive written approval for the use of unicoat specifying the conditions of application from the Executive Officer or his designee.
 - (C) For low-solids adhesives, coatings, primers or sealants, the appropriate limits in subparagraph (c)(1)(A) shall be expressed in grams of VOC per liter of material.
- (2) Solvent Cleaning Operations; Storage and Disposal of VOC-Containing Materials
- (A) Cleaning of material application equipment and storage of solvent laden cloth and paper shall comply with provisions of Rule 1171.
 - (B) A person shall not atomize any solvent into open air.

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1140 2-1-1980]

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines,
or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).

- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines,
or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1140 8-2-1985]

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines,
or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).

- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines,
or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1162 11-17-2000]

The operator shall not use a polyester resin material in a polyester resin operation which has a monomer content in excess of the limits specified in the Table below.

Polyester Resin Materials	Monomer Content in Polyester Resin Materials as Applied (By Weight Percent)
General Purpose Polyester Resin	35
Corrosion-Resistant	48
Fire Retardant	42
High Strength	48
Clear Gel Coat	50
Pigmented Gel Coat	45

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1162 7-8-2005]**

The operator shall not use polyester resin material in an open molding system, which has a monomer content in excess of the limits specified in the following Table.

Polyester Resin Materials	Monomer Percentage by Weight as Applied	
	Prior to 11-09-2001	Current Limits
Clear Gel Coat	50	-
For Marble Resins	-	40
For Other Resins	-	44
Pigmented Gel Coat	45	-
White and Off White	-	30
Non-White	-	37
Primer	-	28
Specialty Gel Coats	-	48
General Purpose Resin	35	-
Marble Resins	-	10 or (32 % as supplied, no fillers) 17
Solid Surface Resins	-	24 or
Tub/Shower Resins	-	(35 % as supplied, no fillers)
Lamination Resins	-	31 or (35 % as supplied, no fillers)
Others	-	35
Fire Retardant Resin	42	38
Corrosion Resistant Resin	48	48
High Strength Resin	48	40

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 1-7-2005]**

- (1) Unless otherwise specified in paragraph (c)(2), a person shall not apply any adhesives, adhesive bonding primers, adhesive primers, or any other primer which have a VOC content in excess of 250 g/L less water and less exempt compounds.
- (2) A person shall not apply adhesives, adhesive bonding primers, adhesive primers, sealants, sealant primers, or any other primer which have a VOC content in excess of the limits specified below:

VOC Limit*, Less Water and Less Exempt Compounds in Grams per Liter

Architectural Applications	Current VOC Limit*
Indoor Carpet Adhesives	50
Carpet Pad Adhesives	50
Outdoor Carpet Adhesives	150
Wood Flooring Adhesive	100
Rubber Floor Adhesives	60
Subfloor Adhesives	50
Ceramic Tile Adhesives	65
VCT and Asphalt Tile Adhesives	50
Dry Wall and Panel Adhesives	50
Cove Base Adhesives	50
Multipurpose Construction Adhesives	70
Structural Glazing Adhesives	100
Single Ply Roof Membrane Adhesives	250

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1168 1-7-2005]**

Specialty Applications	VOC Limits and Effective Dates**			
	Current VOC Limit*	1-1-05	7-1-05	1-1-07
PVC Welding	510			
CPVC Welding	490			
ABS Welding	400		325	
Plastic Cement Welding	350	250		
Adhesive Primer for Plastic	650		550	
Computer Diskette Manufacturing	350			
Contact Adhesive	80			
Special Purpose Contact Adhesive	250			
Tire Retread	100			
Adhesive Primer for Traffic Marking Tape	150			
Structural Wood Member Adhesive	140			
Sheet Applied Rubber Lining Operations	850			
Top and Trim Adhesive	540			250

** The specified limits remain in effect unless revised limits are listed in subsequent columns.

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 1-7-2005]**

For adhesives, adhesive bonding primers, or any other primer not regulated by the above two tables and applied to the following substrates, the following limits shall apply:

Substrate Specific Applications	Current VOC Limit*
Metal to Metal	30
Plastic Foams	50
Porous Material (except wood)	50
Wood	30
Fiberglass	80

If an adhesive is used to bond dissimilar substrates together the adhesive with the highest VOC content shall be allowed.

Sealants	Current VOC Limit*
Architectural	250
Marine Deck	760
Nonmembrane Roof	300
Roadway	250
Single-Ply Roof Membrane	450
Other	420

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 1-7-2005]**

Sealant Primers	Current VOC Limit*
Architectural	
Non Porous	250
Porous	775
Modified Bituminous	500
Marine Deck	760
Other	750

* For low-solid adhesives or sealants the VOC limit is expressed in grams per liter of material as determined in paragraph (b)(32); for all other adhesives and sealants, VOC limits are expressed as grams of VOC per liter of adhesive or sealant less water and less exempt compounds as determined in paragraph (b)(31).

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1168 10-3-2003]**

- (1) Unless otherwise specified in paragraph (c)(2), a person shall not apply any adhesives, adhesive bonding primers, adhesive primers, or any other primer which have a VOC content in excess of 250 g/L less water and less exempt compounds.
- (2) A person shall not apply adhesives, adhesive bonding primers, adhesive primers, sealants, sealant primers, or any other primer which have a VOC content in excess of the limits specified below:

VOC Limit*, Less Water and Less Exempt Compounds in Grams per Liter

Architectural Applications	Current VOC Limit
Indoor Carpet Adhesives	50
Carpet Pad Adhesives	50
Outdoor Carpet Adhesives	150
Wood Flooring Adhesive	100
Rubber Floor Adhesives	60
Subfloor Adhesives	50
Ceramic Tile Adhesives	65
VCT and Asphalt Tile Adhesives	50
Dry Wall and Panel Adhesives	50
Cove Base Adhesives	50
Multipurpose Construction Adhesives	70
Structural Glazing Adhesives	100
Single Ply Roof Membrane Adhesives	250

* For low-solid adhesives or sealants the VOC limit is expressed in grams per liter of material as determined in paragraph (b)(32); for all other adhesives and sealants, VOC limits are expressed as grams of VOC per liter of adhesive or sealant less water and less exempt compounds as determined in paragraph (b)(31).

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1168 10-3-2003]**

.Specialty Applications	VOC Limits and Effective Dates**			
	Current VOC Limit	6-7-02	1-1-03	1-1-05
PVC Welding	510			285
CPVC Welding	490			270
ABS Welding	400			
Plastic Cement Welding	350			250
Adhesive Primer for Plastic	650			250
Computer Diskette Manufacturing	350			
Contact Adhesive	250		80	
Special Purpose Contact Adhesive	250			
Tire Retread	100			
Adhesive Primer for Traffic Marking Tape	150			
Structural Wood Member Adhesive	140			
Sheet Applied Rubber Lining Operations	850			
Top and Trim Adhesive	250	540		250

** The specified limits remain in effect unless revised limits are listed in subsequent columns.

Substrate Specific Applications	Current VOC Limit
Metal to Metal	30
Plastic Foams	50
Porous Material (except wood)	50

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1168 10-3-2003]**

Substrate Specific Applications	Current VOC Limit
Wood	30
Fiberglass	80

If an adhesive is used to bond dissimilar substrates together the adhesive with the highest VOC content shall be allowed.

Sealants	Current VOC Limit
Architectural	250
Marine Deck	760
Nonmembrane Roof	300
Roadway	250
Single-Ply Roof Membrane	450
Other	420

Sealant Primers	Current VOC Limit
Architectural	
Non Porous	250
Porous	775
Modified Bituminous	500
Marine Deck	760
Other	750

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 11-7-2003]**

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	500 (4.2)
(iii) Medical Devices & Pharmaceuticals	800 (6.7)
(B) Repair and Maintenance Cleaning	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)
(iii) Medical Devices & Pharmaceuticals	
(A) Tools, Equipment, & Machinery	800 (6.7)
(B) General Work Surfaces	600 (5.0)

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 11-7-2003]**

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(C) Cleaning of Coatings or Adhesives Application Equipment	550 (4.6)
(D) Cleaning of Ink Application Equipment	
(i) General	25 (0.21)
(ii) Flexographic Printing	25 (0.21)
(iii) Gravure Printing	
(A) Publication	750 (6.3)
(B) Packaging	25 (0.21)
(iv) Lithographic or Letter Press Printing	
(A) Roller Wash – Step 1	600 (5.0)
(B) Roller Wash-Step 2, Blanket Wash, & On-Press Components	800 (6.7)
(C) Removable Press Components	25 (0.21)
(v) Screen Printing	750 (6.3)
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	800 (6.7)

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-7-2003]**

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(vii) Specialty Flexographic Printing	600 (5.0)
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 2-1-2008]**

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		
(iii) Medical Devices & Pharmaceuticals	800 (6.7)		
(B) Repair and Maintenance Cleaning			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 2-1-2008]**

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals			
(A) Tools, Equipment, & Machinery	800 (6.7)		
(B) General Work Surfaces	600 (5.0)		
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)		
(D) Cleaning of Ink Application Equipment			
(i) General	25 (0.21)		
(ii) Flexographic Printing	25 (0.21)		
(iii) Gravure Printing			
(A) Publication	100 (0.83)		
(B) Packaging	25 (0.21)		
(iv) Lithographic (Offset) or Letter Press Printing			
(A) Roller Wash, Blanket Wash, & On-Press Components			
(I) Newsprint	100 (0.83)		

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 2-1-2008]**

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(II) Other Substrates	500 (4.2)	100 (0.83)	
(B) Removable Press Components	25 (0.21)		
(v) Screen Printing	500 (4.2)	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)		
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)		

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1469, #16 10-9-1998]

Chromic Acid Anodizing Tank Vented To A Composite Mesh Pad

Rule 1469 incorporates and implements California Air Resources Board Airborne Toxics Control Measure (Chrome Plating ATCM) requirements for control of hexavalent chromium emissions from chrome plating operations. Furthermore, the Chrome Plating ATCM, which subsumes the Federal NESHAP requirements of 40CFR63 Subpart N-National Emission Standards for Chromium Emissions from Hard and Decorative Chromium Electroplating and Chromium Anodizing Tanks, has been accepted by EPA to be equivalent to the NESHAP. Therefore, the following permit conditions are federally enforceable.

1. The emissions of hexavalent chromium from the chromic acid anodizing tank (s) shall not exceed 0.01 milligrams per dry standard cubic meter, measured at the air pollution control system outlet.
2. The chromic acid anodizing tank (s) shall be equipped with a continuous recording, non-resettable ampere-hour meter (s) that operates on the electrical power line (s) connected to each tank. A separate meter shall be hard-wired for each rectifier.
3. Mechanical gauges shall be installed and maintained so as to indicate, in inches water column, the static pressure differential across each stage of the mesh pad mist eliminator (s). The static pressure differential across the mesh pad mist eliminator (s) shall be maintained within plus or minus 1 inch of water column of the value established during the performance test which demonstrated compliance with the emission limitation. Please refer to Sections D and/or H of this permit for specific static pressure differential requirements or limits.
4. The mechanical gauges shall be located so that they can be easily viewed and are in clear sight of the operation or maintenance personnel.
5. The owner/operator shall maintain a weekly record of the static pressure differential, in inches water column, across the mesh pad mist eliminator. This record shall be kept and maintained on site.
6. The owner/operator shall inspect and maintain the ampere-hour meter (s) according to the manufacturer's recommendations.
7. The owner/operator shall comply with the inspection and maintenance requirements for the composite mesh pad system(s) listed below:

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1469, #16 10-9-1998]

- A. Quarterly visual inspection of the device to ensure there is proper drainage, no unusual chromic acid buildup on the mesh pads, and no evidence of chemical attack that affects the structural integrity of the device.
 - B. Quarterly visual inspection of the back portion of the mesh pad closest to the fan to ensure there is no breakthrough of chromic acid mist.
 - C. Quarterly visual inspection of the ductwork from tank (s) to the control device to ensure there are no leaks.
 - D. Perform washdown of the composite mesh pads in accordance with the manufacturer's recommendations.
8. The owner/operator shall maintain inspection and maintenance records for the ampere-hour meter (s), the composite mesh pad mist eliminator (s), and monitoring equipment to document compliance with the inspection and maintenance requirements of this permit. The record should identify:
- A. The device inspected,
 - B. The date and time of inspection,
 - C. The working condition of the device during the inspection,
 - D. Any maintenance activities performed on the ampere-hour meter (s), the mesh pad mist eliminator (s), and
 - E. Any actions taken to correct deficiencies found during the inspection.
9. The owner/operator shall record the actual cumulative rectifier ampere-hour usage of each chromic acid anodizing tank used during each month, and the total capacity used to date for each calendar year.
10. The owner/operator shall maintain records of excess emissions including, but not limited to, records of any exceedances of the emission limitation and/or parameter monitoring requirements contained in this permit. The records shall include the date

FACILITY PERMIT TO OPERATE DUCOMMUN AEROSTRUCTURES INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1469, #16 10-9-1998]

of the occurrence, the duration, cause (if known), and, where possible, the magnitude of any excess emissions.

11. The owner/operator shall maintain all documentation supporting the notifications and reports required by Rule 1469.
12. The owner/operator shall report breakdowns as required by district Rule 430.
13. The owner/operator shall maintain records of the occurrence, duration, and causes (if known) and action taken on each breakdown.
14. After the effective date of Rule 1469, no person may construct or modify a source such that it becomes a source subject to this section without submitting a notification of construction or modification to the AQMD and receiving approval in advance to construct or modify the source. The notification of construction or modification shall contain the information identified in Appendix 4 of Rule 1469.
15. The owner/operator shall prepare an operation and maintenance plan.
16. The operation and maintenance plan shall incorporate the inspection and maintenance requirements identified in this permit and shall include the following elements:
 - A. A standardized checklist to document the operation and maintenance of the source, the add-on air pollution control device, and the process and control system monitoring equipment, and
 - B. The procedures to be followed to ensure that equipment is properly maintained.
17. The owner/operator shall keep the written operation and maintenance plan on record, after it is developed, to be made available for inspection upon request by AQMD personnel.
18. Any changes made to the operation and maintenance plan shall be documented in an addendum to the plan and signed by the owner/operator or appropriate designee.
19. The owner/operator shall annually complete, by February 1 of each year, an ongoing compliance status report for the preceding calendar year. The report shall contain the

**FACILITY PERMIT TO OPERATE
DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1469, #16 10-9-1998]**

information identified in Appendix 3 of Rule 1469. The report shall be made available to AQMD personnel upon request.

20. A log concerning the operation of this equipment shall be kept on file for a minimum of five years. The past two years' records shall be kept on site and shall be made available upon request of district personnel. This log shall contain all records and reports required by condition nos. 5 to 19, inclusive.

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 404 2-7-1986]**

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a).

Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 404 2-7-1986]**

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 405 2-7-1986]**

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process)		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process)	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
100 or less	220 or less	0.450	0.99	9000	19840	5.308	11.7
150	331	0.585	1.29	10000	22050	5.440	12.0
200	441	0.703	1.55	12500	27560	5.732	12.6
250	551	0.804	1.77	15000	33070	5.982	13.2
300	661	0.897	1.98	17500	38580	6.202	13.7
350	772	0.983	2.17	20000	44090	6.399	14.1
400	882	1.063	2.34	25000	55120	6.743	14.9
450	992	1.138	2.51	30000	66140	7.037	15.5
500	1102	1.209	2.67	35000	77160	7.296	16.1
600	1323	1.340	2.95	40000	88180	7.527	16.6
700	1543	1.461	3.22	45000	99210	7.738	17.1
800	1764	1.573	3.47	50000	110200	7.931	17.5
900	1984	1.678	3.70	60000	132300	8.277	18.2
1000	2205	1.777	3.92	70000	154300	8.582	18.9

**FACILITY PERMIT TO OPERATE
 DUCOMMUN AEROSTRUCTURES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 405 2-7-1986]**

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process)		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process)	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
1250	2756	2.003	4.42	80000	176400	8.854	19.5
1500	3307	2.206	4.86	90000	198400	9.102	20.1
1750	3858	2.392	5.27	100000	220500	9.329	20.6
2000	4409	2.563	5.65	125000	275600	9.830	21.7
2250	4960	2.723	6.00	150000	330700	10.26	22.6
2500	5512	2.874	6.34	175000	385800	10.64	23.5
2750	6063	3.016	6.65	200000	440900	10.97	24.2
3000	6614	3.151	6.95	225000	496000	11.28	24.9
3250	7165	3.280	7.23	250000	551200	11.56	25.5
3600	7716	3.404	7.50	275000	606300	11.82	26.1
4000	8818	3.637	8.02	300000	661400	12.07	26.6
4500	9921	3.855	8.50	325000	716500	12.30	27.1
5000	11020	4.059	8.95	350000	771600	12.51	27.6
6000	13230	4.434	9.78	400000	881800	12.91	28.5
7000	15430	4.775	10.5	450000	992100	13.27	29.3
8000	17640	5.089	11.2	500000 or more	1102000 or more	13.60	30.0