

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

Facility Equipment and Requirements (Section D)

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

Application number	Permit to Operate number	Equipment description
290557	D82794	PAINTS DRYING
294317	D85454	TANK, OTHER AQUEOUS SOLUTION
294318	D85458	TANK, OTHER AQUEOUS SOLUTION
294323	D84916	OVEN, DRYING
297028	R-D89314	ABRASIVE BLASTING (CABINET/MACHINE/ROOM)
479021		SPRAY BOOTH PAINT AND SOLVENT NO.2
461233	F86451	SPRAY BOOTH PAINT AND SOLVENT NO.4
313858	R-D99109	TANK, SURFACE PREPARATION - OTHER ACIDS
313859	R-D99110	TANK, SURFACE PREPARATION - OTHER ACIDS
317172	F01116	ABRASIVE BLASTING (CABINET/MACHINE/ROOM)
448521	N18903	AVGAS STORAGE & DISPENSE SYS.
461234	F86452	SPRAY BOOTH PAINT AND SOLVENT NO.3
431947	F72810	ABRASIVE BLASTING
431948	F72811	ABRASIVE BLASTING
431949	F72812	ABRASIVE BLASTING
432115	F72813	BAGHOUSE
437179	F73621	SPRAY BOOTH- POWDER
437180	F73640	OVEN-CURING
454420	F82293	ABRASIVE BLASTING
454421	F82291	BAGHOUSE
437239	F84117	REGENERATIVE THERMAL OXIDIZER
437240	F84118	SPRAY BOOTH PAINT AND SOLVENT
437241	F84119	OVEN-DRYING
437243	F84120	SPRAY BOOTH PAINT AND SOLVENT NO.1
437244	F84121	OVEN-DRYING
479022		ABRASIVE BLASTING
479023		DUST COLLECTOR

NOTE: EQUIPMENT LISTED ABOVE THAT HAVE NO CORRESPONDING PERMITS TO OPERATE NUMBER ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT.

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

FACILITY WIDE CONDITION(S)

Condition(s):

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:
 - A. AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGELMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
 - B. OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (A) OF THIS CONDITION.
[RULE 401]
2. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS FACILITY SHALL NOT EXCEED 98 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
3. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS FACILITY EXCLUDING THE EMISSIONS FROM THE AVGAS STORAGE AND DISPENSING SYSTEM SHALL NOT EXCEED 95 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
4. IN ADDITION TO THE RECORDKEEPING REQUIREMENT OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR FACILITY TO VERIFY DAILY VOLATILE ORGANIC COMPOUND (VOC), EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS). ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303 (b)(2)-OFFSET]
5. MATERIAL SAFETY DATA SHEETS FOR ALL COATING AND SOLVENTS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303 (b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. D82794
A/N 290557

Equipment Description:

DRYING ROOM #2, BINKS, INFRA RED, 14'-0" W. X 40'-0" L. X 12'-0" H., WITH TWENTY SIX LAMPS 76 KW TOTAL, ONE ½ HP EXHAUST FAN AND 3 HP CIRCULATING FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED ABOVE 200 DEGREES FAHRENHEIT.
[RULE 401]

Periodic Monitoring:

4. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE TEMPERATURE ONCE EVERY DAY.
[RULE 3004 (a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. D85454
A/N 294317

Equipment Description:

SYSTEM FOR SURFACE CLEANING AND PREPARATION FOR PAINTING CONSISTING OF:

1. ALKALINE CLEANING TANK, BORAX SOLUTION 2'-0" W. X 4'-0" D. X 4'-0" L., 10- KW ELECTRICALLY HEATED, THERMOSTATICALLY CONTROLLED (110-130⁰ F), WITH MECHANICAL AGITATION.
2. RINSE WATER TANK, 2'-0" W. X 4'-0" D. X 4'-0" L.
3. DEOXIDIZER TANK, 10-15% NITRIC ACID, 2'-0" W. X 4'-0" D. X 4'-0" L., 10 KW ELECTRICALLY HEATED, THERMOSTATICALLY CONTROLLED (60-100⁰ F), WITH MECHANICAL AGITATION.
4. RINSE WATER TANK, 2'-0" W. X 4'-0" D. X 4'-0" L.
5. CHEMICAL FILM TANK, CHROMIUM SILICOFLUORIDE, 2'-0" W. X 4'-0" D. X 4'-0" L., 7.5 KW, ELECTRICALLY HEATED, THERMOSTATICALLY CONTROLLED (70-90⁰ F), WITH MECHANICAL AGITATION.
6. RINSE WATER TANK, 2'-0" W. X 4'-0" D. X 4'-0" L.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. D85458
A/N 294318

Equipment Description:

SYSTEM FOR SURFACE CLEANING, PARTS CLEANING, AND PREPARATION FOR PAINTING CONSISTING OF:

1. TWO ALKALINE CLEANING TANK, BORAX SOLUTION EACH 3'-0" W. X 4'-0" D. X 5'-0" L., 27- KW ELECTRICALLY HEATED, THERMOSTATICALLY CONTROLLED (110-130⁰ F), WITH MECHANICAL AGITATION.
2. RINSE WATER TANK, 3'-0" W. X 4'-4" D. X 5'-0" L.
3. DEOXIDIZER TANK, 10-15% NITRIC ACID, 3'-0" W. X 4'-4" D. X 5'-0" L., 10 KW ELECTRICALLY HEATED, THERMOSTATICALLY CONTROLLED (60-100 F), WITH MECHANICAL AGITATION.
4. RINSE WATER TANK, 3'-0" W. X 4'-4" D. X 5'-0" L.
5. CHEMICAL FILM TANK, CHROMIUM SILICOFLUORIDE, 3'-0" W. X 4'-4" D. X 5'-0" L., 10 KW, ELECTRICALLY HEATED, THERMOSTATICALLY CONTROLLED (70-90⁰ F), WITH MECHANICAL AGITATION.
6. RINSE WATER TANK, 3'-0" W. X 4'-4" D. X 5'-0" L.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. D84916
A/N 294323

Equipment Description:

DRYING OVEN, BINKS, BATCH TYPE, 10'-0" W. X 12'-4" L. X 8'-0" H., NATURAL GAS HEATED, 250,000 BTU/HR, WITH A 2,600-SCFM CIRCULATING FAN, AND A 600-SCFM EXHAUST FAN, FOR DRYING PAINTED HELICOPTER PARTS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions And Requirements:

- 4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
 - CO: 2000 PPM, RULE 407
 - PM: 0.1 gr/scf, RULE 409
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. R-D89314
A/N 297028

Equipment Description:

ABRASIVE-BLASTING SYSTEM WITH INTEGRAL CONTROL CONSISTING OF:

1. CABINET, PAULI & GRIFFIN, MODEL NO. PRAM 31, SERIAL NO. 040-431, 6'-0" W. X 6'-0" L. X 3'-0" H.
2. NOZZLE WITH A MAXIMUM INSIDE DIAMETER OF 5/16" AND A MAXIMUM AIR PRESSURE OF 100 PSIG.
3. INTEGRAL BAGHOUSE WITH THREE CARTRIDGE TYPE FILTERS, 678 SQ.FT. TOTAL FILTER AREA, AND A 5 HP BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE BAGHOUSE SHALL BE OPERATED WHILE THE ABRASIVE-BLASTING EQUIPMENT IS IN OPERATION.
[RULE 1303(a)(1)-BACT]
4. DUST COLLECTED IN THE BAGHOUSE SHALL BE DISCHARGED ONLY INTO A CLOSED CONTAINER.
[RULE 1303(a)(1)-BACT]
5. A MECHANICAL GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE BAGS.
[RULE 1303(a)(1)-BACT]
6. THE STATIC PRESSURE DIFFERENTIAL ACROSS THE BAGS SHALL NOT EXCEED 4 INCHES OF WATER COLUMN.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

7. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
- B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
- C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

[RULE 3004(a)(4)]

8. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

[RULE 3004(a)(4)]

Emissions and Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

- PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
- PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
- PM: RULE 1140, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No.
A/N 479021

Equipment Description:

SPRAY BOOTH #2, BINKS MODEL NUMBER CA-642-TLO, AUTOMOTIVE TYPE, 15'-1" W. X 49'-10" L. X 13'-6" H., WITH FIRST STAGE 20" X 20" OSM FILTERS, SECOND STAGE OSM-100 FILTERS, AND THIRTY TWO THIRD-STAGE 20" X 20" P.E. CELL FILTERS BY AIR TECHNOLOGIES INC., AND ONE 7.5 H.P. EXHAUST FAN 15,700 SCFM CAPACITY.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THREE STAGE FILTER SYSTEM.
[RULE 1303 (a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER THE STATIC PRESSURE DIFFERENTIAL ACROSS THE THREE STAGE FILTER SYSTEM. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 1.85 INCHES OF WATER.
[RULE 1303 (a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 80 POUNDS IN ANY ONE DAY.
[RULE 1303 (b)(2) -OFFSET]
6. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, AS AMENDED MARCH 7, 2008, WITH THE EXCEPTION OF ETHYL BENZENE (CAS NO. 100-41-4), METHYL ETHYL KETONE (CAS NO. 78-93-3), TOLUENE (CAS NO. 108-88-3), XYLENE (CAS NO. 1330-20-7), AND NICKEL OXIDE (CAS NO 1313-99-1).
[RULE 1401]
7. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY DAILY VOLATILE ORGANIC COMPOUND (VOC), EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS). ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF ANY DISTRICT REPRESENTATIVE.
[RULE 109, 1303 (b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

8. THE TOTAL QUANTITY OF COATINGS CONTAINING NICKEL OXIDE SPRAYED IN THIS EQUIPMENT SHALL NOT EXCEED 30 GALLONS IN ANY ONE CALENDAR MONTH.
[RULE 1401]
9. THE OPERATOR SHALL MAINTAIN RECORDS TO VERIFY COMPLIANCE WITH CONDITION NO. 8. THE RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF ANY DISTRICT REPRESENTATIVE.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
11. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

Emissions And Requirements:

12. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
HAP: 40 CFR 63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. F86451
A/N 461233

Equipment Description:

SPRAY BOOTH #4, BINKS AUTOMOTIVE TYPE, MODEL NUMBER CA-533-TLO, 14'-0" W. X 42'-10" L. X 12'-0" H., WITH FIRST STAGE 20" X 20" OSM FILTERS, SECOND STAGE OSM-100 FILTERS, AND THIRTY TWO THIRD-STAGE 20" X 20" P.E. CELL FILTERS BY AIR TECHNOLOGIES INC., AND ONE 1,750,000 BTU PER HOUR NATURAL GAS FIRED HEATER, AND ONE 7.5 H.P. EXHAUST FAN 16,400 SCFM CAPACITY.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THREE STAGE FILTER SYSTEM.
[RULE 1303 (a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER THE STATIC PRESSURE DIFFERENTIAL ACROSS THE THREE STAGE FILTER SYSTEM. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 1.85 INCHES OF WATER.
[RULE 1303 (a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 80 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. THE TOTAL QUANTITY OF METHYLENE CHLORIDE USED IN THIS EQUIPMENT SHALL NOT EXCEED TWO HUNDRED POUNDS IN ANY CALENDAR MONTH.
[RULE 1401]
7. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN RULE 1401 AS AMENDED DECEMBER 7, 1990, WITH EXCEPTION OF METHYLENE CHLORIDE.
[RULE 1401]
8. IN ADDITION TO THE RECORDKEEPING REQUIREMENT OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY DAILY VOLATILE ORGANIC COMPOUND (VOC), EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS). ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

Emissions And Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
 - VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - HAP: 40 CFR 63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: 0.1 gr/scf, RULE 409
 - CO: 2000 PPM, RULE 407
 - PM: RULE 481

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. R-D99109
A/N 313858

Equipment Description:

OPEN PROCESS TANKS CONSISTING OF:

1. ALKALINE TANK, TANK NO. 1., BRULIN 815GD AND WATER, 2'-0" W. X 4'-0" L. X 4'-0" H., 10 KW ELECTRICALLY HEATED, WITH A MECHANICAL AGITATOR.
2. RINSE TANK, TANK NO. 2, 2'-0" W. X 4'-0" L. X 4'-0" H.
3. NITAL ETCH TANK, TANK NO. 3, NITRIC ACID WATER, 55-GALLON CAPACITY.
4. RINSE TANK, NO. 4, 2'-0" W. X 4'-0" L. X 4'-0" H.
5. NITAL ETCH TANK, TANK NO. 5, HYDROCHLORIC ACID AND WATER, 55-GALLON CAPACITY.
6. RINSE TANK, NO. 6, 2'-0" W. X 4'-0" L. X 4'-0" H.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE ETCH TANKS SHALL NOT BE HEATED OR RECTIFIED.
[RULE 1303 (b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. R-D99110
A/N 313859

Equipment Description:

OPEN PROCESS TANKS CONSISTING OF:

1. ALKALINE TANK, TANK NO. 1., BRULIN 815GD AND WATER 2'-0" W. X 4'-0" L. X 4'-0" H., 10 KW ELECTRICALLY HEATED, WITH A MECHANICAL AGITATOR.
2. RINSE TANK, TANK NO. 2, 2'-0" W. X 4'-0" L. X 4'-0" H.
3. PASSIVATION TANK, TANK NO. 3A, NITRIC ACID, SODIUM DICHROMATE AND WATER, 2'-0" W. X 4'-0" L. X 2'-0" H.
4. PASSIVATION TANK, TANK NO. 3B, NITRIC ACID AND WATER, 55-GALLON CAPACITY.
5. RINSE TANK, TANK NO. 4., 2'-0" W. X 4'-0" L. X 4'-0" H.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE204]
3. THE ETCH TANKS SHALL NOT BE HEATED OR RECTIFIED.
[RULE 1303 (b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

**Permit No. F01116
A/N 317172**

Equipment Description:

ABRASIVE-BLASTING SYSTEM WITH INTEGRAL CONTROL CONSISTING OF:

1. CABINET, PAULI & GRIFFIN, MODEL NO. PRAM 31, SERIAL NO. 208, 5'-0" W. X 3'-0" L. X 4'-0" H.
2. NOZZLE WITH A MAXIMUM INSIDE DIAMETER OF 3/8" INCH AND A MAXIMUM AIR PRESSURE OF 100 PSIG.
3. INTEGRAL BAGHOUSE WITH THREE CARTRIDGE TYPE FILTERS, 450 SQ.FT. TOTAL FILTER AREA, AND A 2 HP BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE ABRASIVE-BLASTING EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO THE INTEGRAL BAGHOUSE.
[RULE 1303 (a)(1)-BACT]
4. DUST COLLECTED IN THE BAGHOUSE SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303 (a)(1)-BACT]
5. A MECHANICAL GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE BAGS.
[RULE 1303 (a)(1)-BACT]
6. THE STATIC PRESSURE DIFFERENTIAL ACROSS THE BAGS SHALL NOT EXCEED 4 INCHES OF WATER COLUMN.
[RULE 1303 (a)(1)-BACT]

Periodic Monitoring:

7. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
- B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
- C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

[RULE 3004(a)(4)]

8. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

[RULE 3004(a)(4)]

Emissions and Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1140, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. N18903
A/N 448521

Equipment Description:

FUEL STORAGE AND DISPENSING FACILITY CONSISTING OF:

1. 1-AVGAS UNDERGROUND STORAGE TANK, 10,000-GALLON CAPACITY, EQUIPPED WITH PHASE I VAPOR RECOVERY (G-70-97-A).
2. 1-AVGAS DISPENSING NOZZLE, NOT EQUIPPED WITH PHASE II VAPOR RECOVERY SYSTEM.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. PHASE I VAPOR RECOVERY SYSTEMS SHALL BE IN FULL OPERATION WHENEVER FUEL IS BEING TRANSFERRED INTO STORAGE TANKS.
[RULE 461]
4. ALL PHASE I VAPOR RECOVERY EQUIPMENT AT THIS FACILITY SHALL BE INSTALLED, OPERATED AND MAINTAINED TO MEET ALL CALIFORNIA AIR RESOURCES BOARD CERTIFICATION REQUIREMENTS.
[RULE 461]
5. ALL RECORDS THAT ARE REQUIRED TO BE MAINTAINED BY RULE 461 SHALL BE KEPT ON SITE FOR FIVE YEARS AND MADE AVAILABLE TO DISTRICT REPRESENTATIVES UPON REQUEST.
[RULE 461]
6. THE MAXIMUM QUANTITY OF AVGAS DISPENSED FROM THE STORAGE TANKS AT THIS FACILITY SHALL NOT EXCEED 9,000 GALLONS IN ANY ONE CALENDAR MONTH.
[RULE 1303 (b)(2)-OFFSET]
7. RECORDS OF MONTHLY AND ANNUAL FUEL RECEIVED SHALL BE PREPARED, SHALL BE RETAINED FOR FIVE YEARS, AND SHALL BE MADE AVAILABLE TO DISTRICT REPRESENTATIVES UPON REQUEST.
[RULE 1303 (b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

Periodic Monitoring:

8. THE OPERATOR SHALL HAVE A PERSON THAT HAS BEEN TRAINED IN ACCORDANCE WITH RULE 461(d) CONDUCT AN ANNUAL INSPECTION OF THE PHASE I VAPOR RECOVERY SYSTEM IN ACCORDANCE WITH RULE 461, ATTACHMENT C. THE OPERATOR SHALL KEEP RECORDS OF THE INSPECTION AND THE REPAIRS IN ACCORDANCE TO RULE 461 AND SECTION K OF THIS PERMIT.
[RULE 3004(a)(4)]

Emissions And Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 461

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. F86452
A/N 461234

Equipment Description:

SPRAY BOOTH #3, BINKS MODEL NUMBER CWE-16-THL, FLOOR TYPE, 16'-0" W. X 12'-7" L. X 7'-10" H., WITH A CONVEYOR, 48-KW DRYING OVEN, 3-STAGE DRY FILTERS BY AIR TECHNOLOGIES INC., AND ONE 7.5 HP EXHAUST BLOWER, 17000 SCFM.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH 3-STAGE DRY FILTER SYSTEM.
[RULE 1303 (a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE THREE STAGE FILTER SYSTEM WHICH SHALL NOT EXCEED 1.85 INCHES OF WATER WHEN THE SPRAY BOOTH IS IN OPERATION.
[RULE 1303 (a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 80 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN RULE 1401, AS AMENDED DECEMBER 7, 1990.
[RULE 1401]
7. IN ADDITION TO THE RECORDKEEPING REQUIREMENT OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY DAILY VOLATILE ORGANIC COMPOUND (VOC), EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS). ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303 (b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

[RULE 3004 (a)(4)]
9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.

[RULE 3004 (a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
 - VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - HAP: 40 CFR 63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 481

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. F72810
A/N 431947

Equipment Description:

ABRASIVE-BLASTING SYSTEM CONSISTING OF:

1. CABINET, EMPIRE, MODEL NO. 6060, 5'-1" W. X 5'-0" L. X 3'-8" H.
2. NOZZLE WITH A MAXIMUM INSIDE DIAMETER OF 1/4" INCH AND A MAXIMUM AIR PRESSURE OF 100 PSIG.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO A BAGHOUSE WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT/OPERATE BY THE DISTRICT.
[RULE 1303 (a)(1)-BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

- ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATIONS RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1140, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

**Permit No. F72811
A/N 431948**

Equipment Description:

ABRASIVE-BLASTING SYSTEM CONSISTING OF:

1. CABINET, EMPIRE, MODEL NO. 4652, 4'-4" W. X 3'-10" L. X 4'-0" H.
2. NOZZLE WITH A MAXIMUM INSIDE DIAMETER OF 5/16 INCH AND A MAXIMUM AIR PRESSURE OF 100 PSIG.
3. INTEGRAL BAGHOUSE WITH TWO CARTRIDGE TYPE FILTERS, 206 SQ. FT. TOTAL FILTER AREA, AND A 1 1/2 HP BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE ABRASIVE-BLASTING EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO THE INTEGRAL BAGHOUSE.
[RULE 1303 (a)(1)-BACT]
4. DUST COLLECTED IN THE BAGHOUSE SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303 (a)(1)-BACT]
5. A MECHANICAL GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE BAGS.
[RULE 1303 (a)(1)-BACT]
6. THE STATIC PRESSURE DIFFERENTIAL ACROSS THE BAGS SHALL NOT EXCEED 4 INCHES OF WATER COLUMN.
[RULE 1303 (a)(1)-BACT]

Periodic Monitoring:

7. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
- B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
- C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

[RULE 3004(a)(4)]

8. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

[RULE 3004(a)(4)]

Emissions and Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1140, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

**Permit No. F72812
A/N 431949**

Equipment Description:

ABRASIVE-BLASTING SYSTEM CONSISTING OF:

1. CABINET, EMPIRE, MODEL NO. 4652, 4'-4" W. X 3'-10" L. X 4'-0" H.
2. NOZZLE WITH A MAXIMUM INSIDE DIAMETER OF 5/16 INCH AND A MAXIMUM AIR PRESSURE OF 100 PSIG.
3. INTEGRAL BAGHOUSE WITH TWO CARTRIDGE TYPE FILTERS, 206 SQ.FT. TOTAL FILTER AREA, AND A 1 1/2 HP BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE ABRASIVE-BLASTING EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO THE INTEGRAL BAGHOUSE.
[RULE 1303 (a)(1)-BACT]
4. DUST COLLECTED IN THE BAGHOUSE SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303 (a)(1)-BACT]
5. A MECHANICAL GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE BAGS.
[RULE 1303 (a)(1)-BACT]
6. THE STATIC PRESSURE DIFFERENTIAL ACROSS THE BAGS SHALL NOT EXCEED 4 INCHES OF WATER COLUMN.
[RULE 1303 (a)(1)-BACT]

Periodic Monitoring:

7. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
- B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
- C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

[RULE 3004(a)(4)]

8. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

[RULE 3004(a)(4)]

Emissions and Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1140, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. F72813
A/N 432115

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. BAGHOUSE, EMPIRE, MODEL CDC9, WITH TWO CARTRIDGE FILTERS, 452 SQ. FT. FILTER AREA TOTAL, AND PULSE JET CLEANING.
2. EXHAUST SYSTEM WITH 2 HP BLOWER VENTING AN ABRASIVE BLASTING SYSTEM.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. DUST COLLECTED IN THE BAGHOUSE SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303 (a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED AND MAINTAINED TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE FILTERS.
[RULE 1303 (a)(1)-BACT]
5. THE STATIC PRESSURE DIFFERENTIAL ACROSS THE FILTERS SHALL NOT EXCEED 4 INCHES OF WATER COLUMN.
[RULE 1303 (a)(1)-BACT]

Periodic Monitoring:

6. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

7. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

[RULE 3004(a)(4)]

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO CONSTRUCT/OPERATE

Permit No. F73621
A/N 437179

Equipment Description:

POWDER SPRAY BOOTH, NORDSON, MODEL NUMBER RCM8000, 5'-0" W. X 9'-0" L. X 7'-0" H., WITH TEN 13" DIA. X 36" L. CARTRIDGE FIRST STAGE EXHAUST FILTER, EIGHT 18" X 22" X 12" SECOND STAGE EXHAUST FILTERS AND ONE 10-HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH CARTRIDGE FILTER MEDIA AND DRY FILTER MEDIA.
[RULE 1303 (a)(1)- BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 3 INCHES OF WATER ACROSS THE SECOND STAGE.
[RULE 1303 (a)(1)- BACT]
5. THE TOTAL QUANTITY OF POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT EXCEED 100 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. DUST COLLECTED IN THIS EQUIPMENT SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]
7. CLEAN-UP MATERIALS ASSOCIATED WITH THIS EQUIPMENT SHALL CONTAIN NO VOC.
[RULE 1303(b)(2)-OFFSET]
8. IN ADDITION TO RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE FOLLOWING:
 - A. POWDER COATING USAGE IN POUNDS.

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

- B. THE VOC EMISSIONS FROM THE USE OF POWDER COATING SHALL BE CALCULATED USING ONE OF THE FOLLOWING:
1. THE VOC CONTENT DETERMINED PURSUANT TO AQMD METHOD 316C OR
 2. THE VOC CONTENT ON THE MATERIAL SAFETY DATA SHEET (MSDS) BUT NOT LESS THAN 0.01 POUND OF VOC PER POUND OF POWDER COATING APPLIED, OR
 3. THE DEFAULT EMISSION FACTOR OF 0.01 POUND OF VOC PER POUND OF POWDER COATING APPLIED WHEN MSDS DOES NOT SPECIFY THE VOC CONTENT OR INDICATES THAT THE VOC CONTENT IS ZERO.
- C. DAILY VOC EMISSIONS IN POUNDS.

ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT AND MAINTAINED FOR FIVE YEARS.
[RULE 109, 1303(b)(2)-OFFSET]

9. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN RULE 1401, TABLE 1, AS AMENDED MAY 2, 2003 OR EARLIER.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
- [RULE 3004 (a)(4)]
11. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

Emissions And Requirements:

12. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
HAP: 40 CFR 63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO CONSTRUCT/OPERATE

**Permit No. F73640
A/N 437180**

Equipment Description:

CURING OVEN, WISCONSIN, MODEL NO. EWN-4-10231, 14'-11" W. X 16'-5" L. X 11'-8" H., NATURAL GAS FIRED, WITH ONE 1,200,000 BTU/HR ECLIPSE WINNOX 100 LOW NO_x BURNER AND ONE 1-HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED ABOVE 500 DEGREES FAHRENHEIT.
(RULE 401)
4. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE TEMPERATURE ONCE EVERY DAY.
[RULE 3004 (a)(4)]

Periodic Monitoring:

5. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

- HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- CO: 2000 PPM, RULE 407
PM: 0.1 gr/scf, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO CONSTRUCT/OPERATE

Permit No. F82293
A/N 454420

Equipment Description:

ABRASIVE-BLASTING SYSTEM CONSISTING OF:

1. CABINET, EMPIRE, MODEL NO. 7272, 6'-2" W. X 6'-3" L. X 7'-5" H.
2. NOZZLE WITH A MAXIMUM INSIDE DIAMETER OF 5/16" INCH AND A MAXIMUM AIR PRESSURE OF 100 PSIG.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO A BAGHOUSE WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT/OPERATE BY THE DISTRICT.
[RULE 1303 (a)(1)-BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

- ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1140, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO CONSTRUCT/OPERATE

Permit No. F82291
A/N 454421

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. BAGHOUSE, EMPIRE, MODEL CDC12, WITH TWO CARTRIDGE FILTERS, 452 SQ. FT. FILTER AREA TOTAL, AND PULSE JET CLEANING.
2. EXHAUST SYSTEM WITH 2 HP BLOWER VENTING AN ABRASIVE BLASTING SYSTEM.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. DUST COLLECTED IN THE BAGHOUSE SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303 (a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED AND MAINTAINED TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE FILTERS.
[RULE 1303 (a)(1)-BACT]
5. THE STATIC PRESSURE DIFFERENTIAL ACROSS THE FILTERS SHALL NOT EXCEED 4 INCHES OF WATER COLUMN.
[RULE 1303 (a)(1)-BACT]

Periodic Monitoring:

6. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

7. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
- THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
- [RULE 3004 (a)(4)]

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. F84117
A/N 437239

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF

1. THERMAL OXIDIZER, REGENERATIVE TYPE, ADWEST TECHNOLOGIES, MODEL RETOX 12, 24'-6" L. X 15'-11" W. X 10'-5" H., 12,000 SCFM CAPACITY WITH A 3.43 MMBTU PER HOUR BURNER, A 1.8 MMBTU PER HOUR GAS INJECTION SYSTEM, 2 CERAMIC BEDS, A 7 ½ HP COMBUSTION BLOWER, AND A COIL MEDIA HEAT EXCHANGER.
2. EXHAUST SYSTEM WITH ONE 27 HP FAN VENTING TWO SPRAY BOOTHS AND TWO DRYING OVENS, ALL OPERATING AS PERMANENT TOTAL ENCLOSURES

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL BE IN OPERATION WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.
[RULE 1303(a)(1)-BACT]
4. THE OPERATOR SHALL OPERATE AND MAINTAIN THIS EQUIPMENT ACCORDING TO THE FOLLOWING REQUIREMENTS:

THE COMBUSTION CHAMBER TEMPERATURE SHALL BE MAINTAINED AT A MINIMUM OF 1,500 DEGREES FAHRENHEIT WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.

THE OPERATOR SHALL OPERATE AND MAINTAIN A TEMPERATURE MEASURING AND RECORDING SYSTEM TO CONTINUOUSLY MEASURE AND RECORD THE COMBUSTION CHAMBER TEMPERATURE PURSUANT TO THE OPERATION AND MAINTENANCE REQUIREMENTS SPECIFIED IN 40 CFR PART 64.7. SUCH A SYSTEM SHALL HAVE AN ACCURACY OF WITHIN 1% OF THE TEMPERATURE BEING MONITORED AND SHALL BE INSPECTED, MAINTAINED, AND CALIBRATED ON AN ANNUAL BASIS IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS.

FOR THE PURPOSE OF THIS CONDITION, A DEVIATION SHALL BE DEFINED AS WHEN A COMBUSTION CHAMBER TEMPERATURE OF LESS THAN 1,500 DEGREES FAHRENHEIT OCCURS DURING NORMAL OPERATION OF THE EQUIPMENT IT SERVES. THE OPERATOR SHALL REVIEW

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

THE RECORDS OF THE COMBUSTION CHAMBER TEMPERATURE ON A DAILY BASIS TO DETERMINE IF A DEVIATION OCCURS OR SHALL INSTALL AN ALARM SYSTEM TO ALERT THE OPERATOR WHEN A DEVIATION OCCURS.

WHENEVER A DEVIATION OCCURS, THE OPERATOR SHALL INSPECT THIS EQUIPMENT TO IDENTIFY THE CAUSE OF SUCH A DEVIATION, TAKE IMMEDIATE CORRECTIVE ACTION TO MAINTAIN THE COMBUSTION CHAMBER TEMPERATURE AT OR ABOVE 1,500 DEGREES FAHRENHEIT, AND KEEP RECORDS OF THE DURATION AND CAUSE (INCLUDING UNKNOWN CAUSE, IF APPLICABLE) OF THE DEVIATION AND THE CORRECTIVE ACTION TAKEN.

ALL DEVIATIONS SHALL BE REPORTED TO THE AQMD PURSUANT TO THE REQUIREMENTS SPECIFIED IN 40 CFR PART 64.9 AND CONDITION NOS. 22 AND 23 IN SECTION K OF THIS PERMIT. THE REPORT SHALL INCLUDE THE TOTAL OPERATING TIME OF THIS EQUIPMENT AND THE TOTAL ACCUMULATED DURATION OF ALL DEVIATIONS FOR EACH SEMI-ANNUAL REPORTING PERIOD SPECIFIED IN CONDITION NO. 23 IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL SUBMIT AN APPLICATION WITH A QUALITY IMPROVEMENT PLAN (QIP) IN ACCORDANCE WITH 40 CFR PART 64.8 TO THE AQMD IF AN ACCUMULATION OF DEVIATIONS EXCEEDS 5 PERCENT DURATION OF THIS EQUIPMENT'S TOTAL OPERATING TIME FOR ANY SEMI-ANNUAL REPORTING PERIOD SPECIFIED IN CONDITION NO. 23 IN SECTION K OF THIS PERMIT. THE REQUIRED QIP SHALL BE SUBMITTED TO THE AQMD WITHIN 90 CALENDAR DAYS AFTER THE DUE DATE FOR THE SEMI-ANNUAL MONITORING REPORT.

THE OPERATOR SHALL INSPECT AND MAINTAIN ALL COMPONENTS OF THIS EQUIPMENT ON AN ANNUAL BASIS IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS.

THE OPERATOR SHALL KEEP ADEQUATE RECORDS IN A FORMAT THAT IS ACCEPTABLE TO THE AQMD TO DEMONSTRATE COMPLIANCE WITH ALL APPLICABLE REQUIREMENTS SPECIFIED IN THIS CONDITION AND 40 CFR PART 64.9 FOR A MINIMUM OF FIVE YEARS. [RULE 1303(a)(1)-BACT, RULE 3004(a)(4)-PERIODIC MONITORING, 40CFR Part 64]

5. THE TEMPERATURE INDICATOR AND A DATA RECORDER SHALL BE IN OPERATION WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.
[RULE 1303(a)(1)-BACT]
6. THE TEMPERATURE INDICATOR SHALL BE PROPERLY CALIBRATED AND MAINTAINED IN GOOD OPERATING CONDITION.
[RULE 1303(a)(1)-BACT]
7. ALL ACCESS DOORS TO THE PERMANENT TOTAL ENCLOSURES SHALL BE KEPT CLOSED DURING NORMAL OPERATIONS.
[RULE 1303(a)(1)-BACT]
8. THE OPERATOR SHALL OPERATE AND MAINTAIN THIS EQUIPMENT TO ACHIEVE DESTRUCTION EFFICIENCY OF AT LEAST 95 % BY WEIGHT WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

9. THE OPERATOR SHALL OPERATE AND MAINTAIN THIS EQUIPMENT TO ACHIEVE AN OVERALL CONTROL EFFICIENCY OF AT LEAST 95 %.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]

Periodic Monitoring:

10. THE OPERATOR SHALL CONDUCT SOURCE TEST(S) IN ACCORDANCE WITH THE FOLLOWING SPECIFICATIONS:
- A. THE TEST SHALL BE CONDUCTED AT LEAST ONCE DURING THE LIFE OF THE PERMIT.
 - B. THE TEST SHALL BE CONDUCTED NO LATER THAN FEBRUARY 4, 2011 UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT.
 - C. THE TEST SHALL BE CONDUCTED TO DETERMINE THE VOC EMISSIONS USING AN APPROVED DISTRICT METHOD TO DEMONSTRATE COMPLIANCE WITH ALL APPLICABLE PERMIT CONDITION(S), RULES AND REGULATIONS.
 - D. THE SOURCE TEST SHALL BE CONDUCTED WHILE THE OXIDIZER IS OPERATING AT A TEMPERATURE OF NOT LESS THAN THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THIS PERMIT. IF THE OPERATING TEMPERATURE DURING THE SOURCE TEST IS GREATER THAN THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THIS PERMIT, THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THIS PERMIT MAY BE INCREASED TO REFLECT THE OPERATING TEMPERATURE DURING THE SOURCE TEST.
 - E. THE OPERATOR SHALL COMPLY WITH ADMINISTRATIVE CONDITIONS NOs. 8, 9, AND 10 OF SECTION E OF THIS FACILITY PERMIT.
 - F. THE OPERATOR SHALL SUBMIT TWO COMPLETE COPIES OF THE SOURCE TEST REPORT SPECIFIED IN CONDITION NO. 9 OF SECTION E OF THIS FACILITY PERMIT TO THE DISTRICT ENGINEERING AND COMPLIANCE DIVISION. THE ENGINEERING COPY OF THE REPORT SHALL BE SENT TO: SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, COATING, PRINTING AND AEROSPACE OPERATIONS, ATTN: AIR QUALITY AND COMPLIANCE SUPERVISOR, 21865 COPLEY DRIVE, DIAMOND BAR, CA 91765. THE COMPLIANCE COPY OF THE REPORT SHALL BE SENT TO: SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, P.O. BOX 4941, DIAMOND BAR, CA 91765
- [RULE 3004(a)(4)]

Emissions And Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- CO: 2000 PPMV, RULE 407
 - PM: 0.1 GR/SCF, RULE 409
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. F84118
A/N 437240

Equipment Description:

SPRAY BOOTH # 5, SPRAY SYSTEM, MODEL NUMBER TB451612-PDT, AUTOMOTIVE TYPE, 22'-0" W. X 49'-10" L. X 13'-8" H., WITH THIRTY-EIGHT 20" X 20" INTAKE FILTERS, FORTY-SIX 20" X 20" ATI FIRST STAGE EXHAUST FILTERS, FORTY SIX 20" X 20" ATI OSM 100 SECOND STAGE EXHAUST FILTERS, FORTY-SIX 20" X 20" ATI A3000 THIRD STAGE EXHAUST FILTERS, ONE 15 H.P. RECIRCULATION BLOWER AND 200,000 BTU PER HOUR NATURAL GAS FIRED HEATER WITH INDIRECT HEAT EXCHANGER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THREE STAGES FILTER MEDIA.
[RULE 1303 (a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 1.85 INCHES OF WATER.
[RULE 1303 (a)(1)-BACT]
5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC/ CARCINOGENIC AIR CONTAMINANTS LISTED IN TABLE 1 IN RULE 1401, AS AMENDED MAY 2, 2003 OR EARLIER WITH THE EXCEPTION OF ETHYL BENZENE, MEK, XYLENE, ISOPROPYL ALCOHOL, TOLUENE, AND NICKEL OXIDE.
[RULE 1401]
6. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AN AIR POLLUTION CONTROL SYSTEM WHICH HAS BEEN ISSUED A VALID PERMIT BY THE EXECUTIVE OFFICER.
[RULE 1303 (a)(1)-BACT]
7. THE OPERATOR SHALL MAINTAIN THIS EQUIPMENT AS A PERMANENT TOTAL ENCLOSURE (PTE) AND COMPLY WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303 (a)(1)-BACT]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

8. IN ADDITION TO THE RECORDKEEPING REQUIREMENT OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY DAILY VOLATILE ORGANIC COMPOUND (VOC), EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS). ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 1303 (b)(2)-OFFSET]

Periodic Monitoring:

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
- [RULE 3004 (a)(4)]
10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

Emissions And Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - HAP: 40 CFR 63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS
 - CO: 2000 PPM, RULE 407
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: 0.1 GR/SCF, RULE 409
 - PM: RULE 481

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. F84119
A/N 437241

Equipment Description:

DRYING OVEN # 5, SPRAY SYSTEMS INC, INFRA RED, MODEL NUMBER DR451412-FDT, 15'-4" W. X 42'-2" L. X 13'-8" H., WITH TWENTY-EIGHT INFRARED LAMPS 600 KW TOTAL, 400,000 BTU PER HOUR NATURAL GAS FIRED CIRCULATION HEATER WITH INDIRECT HEAT EXCHANGER, AND ONE 2 HP CIRCULATION BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. MATERIALS USED ON THE ARTICLES THAT ARE PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC/ CARCINOGENIC AIR CONTAMINANTS LISTED IN TABLE 1 IN RULE 1401, AS AMENDED MAY 2, 2003 OR EARLIER WITH THE EXCEPTION OF ETHYL BENZENE, MEK, XYLENE, ISOPROPYL ALCOHOL, TOLUENE, AND NICKEL OXIDE.
[RULE 1401]
4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AN AIR POLLUTION CONTROL SYSTEM WHICH HAS BEEN ISSUED A VALID PERMIT BY THE EXECUTIVE OFFICER.
[RULE 1303 (a)(1)-BACT]
5. THE OPERATOR SHALL MAINTAIN THIS EQUIPMENT AS A PERMANENT TOTAL ENCLOSURE (PTE) AND COMPLY WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303 (a)(1)-BACT]

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: 0.1 GR/SCF, RULE 409
CO: 2000 PPM, RULE 407

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. F84120
A/N 437243

Equipment Description:

SPRAY BOOTH #1, BINKS MODEL NUMBER CA-642-TLO, AUTOMOTIVE TYPE, 15'-1" W. X 49'-10" L. X 13'-6" H., WITH THIRTY-EIGHT 20" X 20" INTAKE FILTERS, FORTY-SIX 20" X 20" ATI FIRST STAGE EXHAUST FILTERS, FORTY SIX 20" X 20" ATI OSM 100 SECOND STAGE EXHAUST FILTERS, FORTY-SIX 20" X 20" ATI A3000 THIRD STAGE EXHAUST FILTERS, ONE 15 H.P. RECIRCULATION BLOWER, AND 200,000 BTU PER HOUR NATURAL GAS FIRED HEATER WITH INDIRECT HEAT EXCHANGER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THREE STAGES FILTER MEDIA.
[RULE 1303 (a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 1.85 INCHES OF WATER.
[RULE 1303 (a)(1)-BACT]
5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC/ CARCINOGENIC AIR CONTAMINANTS LISTED IN TABLE 1 IN RULE 1401, AS AMENDED MAY 2, 2003 OR EARLIER WITH THE EXCEPTION OF ETHYL BENZENE, MEK, XYLENE, ISOPROPYL ALCOHOL, TOLUENE, AND NICKEL OXIDE.
[RULE 1401]
6. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AN AIR POLLUTION CONTROL SYSTEM WHICH HAS BEEN ISSUED A VALID PERMIT BY THE EXECUTIVE OFFICER.
[RULE 1303 (a)(1)-BACT]
7. THE OPERATOR SHALL MAINTAIN THIS EQUIPMENT AS A PERMANENT TOTAL ENCLOSURE (PTE) AND COMPLY WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303 (a)(1)-BACT]
8. IN ADDITION TO THE RECORDKEEPING REQUIREMENT OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY DAILY VOLATILE ORGANIC COMPOUND (VOC), EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS). ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 1303 (b)(2)-OFFSET]

Periodic Monitoring:

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

[RULE 3004 (a)(4)]

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.

[RULE 3004 (a)(4)]

Emissions And Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 109

HAP: 40 CFR 63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS

CO: 2000 PPM, RULE 407

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

PM: 0.1 GR/SCF, RULE 409

PM: RULE 481

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO OPERATE

Permit No. F84121
A/N 437244

Equipment Description:

DRYING OVEN # 1, BINKS, INFRA RED, 14'-0" W. X 40'-0" L. X 12'-0" H., WITH TWENTY-SIX INFRARED LAMPS 76 KW TOTAL, 304,000 BTU PER HOUR NATURAL GAS FIRED CIRCULATION HEATER WITH INDIRECT HEAT EXCHANGER, ONE 3 HP CIRCULATION BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. MATERIALS USED ON THE ARTICLES THAT ARE PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC/ CARCINOGENIC AIR CONTAMINANTS LISTED IN TABLE 1 IN RULE 1401, AS AMENDED MAY 2, 2003 OR EARLIER WITH THE EXCEPTION OF ETHYL BENZENE, MEK, XYLENE, ISOPROPYL ALCOHOL, TOLUENE, AND NICKEL OXIDE.
[RULE 1401]
4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AN AIR POLLUTION CONTROL SYSTEM WHICH HAS BEEN ISSUED A VALID PERMIT BY THE EXECUTIVE OFFICER.
[RULE 1303 (a)(1)-BACT]
5. THE OPERATOR SHALL MAINTAIN THIS EQUIPMENT AS A PERMANENT TOTAL ENCLOSURE (PTE) AND COMPLY WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303 (a)(1)-BACT]

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: 0.1 GR/SCF, RULE 409
CO: 2000 PPM, RULE 407

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO CONSTRUCT

A/N 479022
Granted as of
X/X/2008

Equipment Description:

ABRASIVE BLASTING SYSTEM, CONSISTING OF:

1. ONE COMMON BLASTING CABINET, EMPIRE, MODEL NO. P60120, 10'-0" L. X 5'-0" W. X 3'-7" H.,
2. TWO NOZZLES, 3/8" DIA. EACH,
3. PLANT AIR, SUPPLIED AT 100 PSI MAXIMUM,
VENTED TO AIR POLLUTION CONTROL EQUIPMENT.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AN AIR POLLUTION CONTROL SYSTEM WHICH HAS BEEN ISSUED A VALID PERMIT BY THE DISTRICT.
[RULE 1303 (a)(1)-BACT]
4. ONLY PLASTIC ABRASIVE MEDIA SHALL BE USED IN THIS EQUIPMENT.
[RULE 1303 (b)(2)-OFFSET]

Periodic Monitoring:

5. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.
IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

- 6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1140, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

PERMIT TO CONSTRUCT

A/N 479023
Granted as of
X/X/2008

Equipment Description:

AIR POLLUTION CONTROL SYSTEM, CONSISTING OF:

1. TWO DUST COLLECTORS, EACH WITH TWO 14" DIA X 28" L. CARTRIDGE-TYPE FILTERS, 452 SQ. FT. TOTAL FILTER AREA,
2. EXHAUST SYSTEM WITH TWO 2 H.P. BLOWERS VENTING AN ABRASIVE BLASTING SYSTEM.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. DUST COLLECTED IN THE EQUIPMENT SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303 (a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED AND MAINTAINED TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE FILTERS.
[RULE 1303 (a)(1)-BACT]
5. THE STATIC PRESSURE DIFFERENTIAL ACROSS THE FILTERS SHALL NOT EXCEED 4 INCHES OF WATER COLUMN.
[RULE 1303 (a)(1)-BACT]

Periodic Monitoring:

6. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

- B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
[RULE 3004(a)(4)]
7. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
- THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
[RULE 3004 (a)(4)]

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

Periodic Monitoring:

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (g/l) OF MATERIALS FOR LOW-SOLIDS COATINGS AND, AND (c) VOC CONTENT AS SUPPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATINGS.

FOR OTHER ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS APPLIED IN GRAMS PER LITER (g/l) OF MATERIALS USED FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS APPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

[RULE 3004 (a) (4)]

Emissions And Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

HAP: 40 CFR 63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, CLEANING EQUIPMENT, SMALL UNHEATED, NON- CONVEYORIZED.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1122

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, ABRASIVE BLASTING EQUIPMENT, GLOVE-BOX, < 53 FT3, WITH DUST FILTER.

Periodic Monitoring:

1. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

2. THE OPERATOR SHALL DISCHARGE DUST COLLECTED IN THIS EQUIPMENT ONLY INTO CLOSED CONTAINERS.
[RULE 3004 (a)(4)]

3. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
 - A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1140, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under Section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:

(A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

SECTION K: TITLE V Administration

- (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
- (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

- 8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
 - (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

- 9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]
- 10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

SECTION K: TITLE V Administration

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]
12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]
13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]
14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]
15. Nothing in this permit or in any permit shield can alter or affect:
 - (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]
16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

SECTION K: TITLE V Administration

commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

SECTION K: TITLE V Administration

EMERGENCY PROVISIONS

17. An emergency¹ constitutes an affirmative defense to an action brought for non-compliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
 - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
 - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
 - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
 - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
 - (B) The operator complies with the breakdown provisions of Rule 430 - Breakdown Provisions, or subdivision (i) of Rule 2004 - Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

¹ "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

SECTION K: TITLE V Administration

RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
 - (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
 - (B) The date(s) analyses were performed;
 - (C) The company or entity that performed the analyses;
 - (D) The analytical techniques or methods used;
 - (E) The results of such analyses; and
 - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:
 - (A) Breakdowns shall be reported as required by Rule 430 - Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.
 - (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

SECTION K: TITLE V Administration

- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
 - (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;
 - (B) The compliance status during the reporting period;
 - (C) Whether compliance was continuous or intermittent;
 - (D) The method(s) used to determine compliance over the reporting period and currently, and
 - (E) Any other facts specifically required by the Executive Officer to determine compliance.
- The EPA copy of the certification shall be sent to: Director of the Air Division Attn: Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]
25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

SECTION K: TITLE V Administration

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the Title V application file. [3004(a)(4)]

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations:

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 109	5-2-2003	Federally enforceable
RULE 1113	11-8-1996	Federally enforceable
RULE 1113	7-13-2007	Non federally enforceable
RULE 1122	10-1-2004	Federally enforceable
RULE 1124	9-21-2001	Federally enforceable
RULE 1140	2-1-1980	Federally enforceable
RULE 1140	8-2-1985	Non federally enforceable
RULE 1171	11-7-2003	Federally enforceable
RULE 1171	2-1-2008	Non federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1401	12-7-1990	Non federally enforceable
RULE 1401	3-7-2008	Non federally enforceable
RULE 204	10-8-1993	Federally enforceable
RULE 217	1-5-1990	Federally enforceable
RULE 219	6-1-2007	Non federally enforceable
RULE 219	9-4-1981	Federally enforceable
RULE 3002	11-14-1997	Federally enforceable
RULE 3003	11-14-1997	Federally enforceable
RULE 3003	3-16-2001	Non federally enforceable
RULE 3004	12-12-1997	Federally enforceable
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3005	3-16-2001	Non federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	6-9-2006	Non federally enforceable
RULE 401	11-9-2001	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 405	2-7-1986	Federally enforceable
RULE 407	4-2-1982	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 409	8-7-1981	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 442	12-15-2000	Federally enforceable
RULE 461	3-7-2008	Federally enforceable
RULE 480	10-7-1977	Federally enforceable
RULE 481	1-11-2002	Federally enforceable
40CFR 63 Subpart GG	12-8-2000	Federally enforceable
RULE 701	6-13-1997	Federally enforceable
40CFR Part 64	10-22-1997	Federally enforceable

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1113 11-8-1996]**

- (1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.
- (2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

TABLE OF STANDARDS

VOC LIMITS

**Grams of VOC Per Liter of Coating,
 Less Water And Less Exempt Compounds**

COATING	Limit*	Effective Date of Adoption	Effective 1/1/1998	Effective 1/1/1999	Effective 7/1/2001	Effective 1/1/2005	Effective 7/1/2008
Bond Breakers	350						
Clear Wood Finishes							
Varnish	350						
Sanding Sealers	350						
Lacquer	680		550			275	
Concrete-Curing Compounds	350						
Dry-Fog Coatings	400						
Fire-proofing Exterior Coatings	350	450		350			
Fire-Retardant Coatings							
Clear	650						
Pigmented	350						
Flats	250					100	
Graphic Arts (Sign) Coatings	500						50
Industrial Maintenance							

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-8-1996]

Primers and Topcoats						
Alkyds	420					
Catalyzed Epoxy	420					
Bituminous Coatings	420					
Materials						
Inorganic Polymers	420					
Vinyl Chloride Polymers	420					
Chlorinated Rubber	420					
Acrylic Polymers	420					
Urethane Polymers	420					
Silicones	420					
Unique Vehicles	420					
Japans/Faux Finishing	350	700		350		
Coatings						
Magnesite Cement Coatings	600			450		
Mastic Coatings	300					
Metallic Pigmented Coatings	500					
Multi-Color Coatings	420		250			
Pigmented Lacquer	680		550		275	
Pre-Treatment Wash Primers	780					
Primers, Sealers, and	350					
Undercoaters						
Quick-Dry Enamels	400					
Roof Coatings	300					
Shellac						
Clear	730					
Pigmented	550					
Stains	350					
Swimming Pool Coatings						
Repair	650					
Other	340					
Traffic Coatings	250		150			
Waterproofing Sealers	400					
Wood Preservatives						
Below-Ground	350					
Other	350					

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

**FACILITY PERMIT TO OPERATE
ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 11-8-1996]**

TABLE OF STANDARDS (cont.)

VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 7-13-2007]

- (1) Except as provided in paragraphs (c)(2), (c)(3), (c)(4), and specified coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage any architectural coating for use in the District which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, and no person shall apply or solicit the application of any architectural coating within the District that exceeds 250 grams of VOC per liter of coating as calculated in this paragraph.
- (2) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified, and no person shall apply or solicit the application of any architectural coating within the District that exceeds the VOC limit as specified in this paragraph. No person shall apply or solicit the application within the District of any industrial maintenance coatings, except anti-graffiti coatings, for residential use or for use in areas such as office space and meeting rooms of industrial, commercial or institutional facilities not exposed to such extreme environmental conditions described in the definition of industrial maintenance coatings; or of any rust-preventative coating for industrial use, unless such a rust preventative coating complies with the Industrial Maintenance Coating VOC limit specified in the Table of Standards.

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1113 7-13-2007]**

**TABLE OF STANDARDS
 VOC LIMITS**

**Grams of VOC Per Liter of Coating,
 Less Water and Less Exempt Compounds**

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Bond Breakers	350							
Clear Wood Finishes	350					275		
Varnish	350					275		
Sanding Sealers	350					275		
Lacquer	680	550			275			
Clear Brushing Lacquer	680				275			
Concrete-Curing Compounds	350						100	
Concrete-Curing Compounds For Roadways and Bridges**	350							
Dry-Fog Coatings	400						150	
Fire-Proofing Exterior Coatings	450	350						
Fire-Retardant Coatings***								
Clear	650							
Pigmented	350							
Flats	250	100						50
Floor Coatings	420		100			50		
Graphic Arts (Sign) Coatings	500							
Industrial Maintenance (IM) Coatings	420			250		100		
High Temperature IM Coatings			420					
Zinc-Rich IM Primers	420		340			100		
Japans/Faux Finishing Coatings	700	350						
Magnesite Cement Coatings	600	450						
Mastic Coatings	300							
Metallic Pigmented Coatings	500							
Multi-Color Coatings	420	250						
Nonflat Coatings	250		150			50		
Nonflat High Gloss	250		150				50	

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 7-13-2007]

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Pigmented Lacquer	680	550			275			
Pre-Treatment Wash Primers	780		420					
Primers, Sealers, and Undercoaters	350		200			100		
Quick-Dry Enamels	400		250			150	50	
Quick-Dry Primers, Sealers, and Undercoaters	350		200			100		
Recycled Coatings			250					
Roof Coatings	300		250		50			
Roof Coatings, Aluminum	500				100			
Roof Primers, Bituminous	350		350					
Rust Preventative Coatings	420		400			100		
Shellac								
Clear	730							
Pigmented	550							
Specialty Primers	350					250	100	
Stains	350		250				100	
Stains, Interior	250							
Swimming Pool Coatings								
Repair	650		340					
Other	340							
Traffic Coatings	250	150					100	
Waterproofing Sealers	400		250			100		
Waterproofing	400					100		
Concrete/Masonry Sealers								
Wood Preservatives								
Below-Ground	350							
Other	350							

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.

** Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

*** The Fire-Retardant Coating category will be eliminated on January 1, 2007 and subsumed by the coating category for which they are formulated.

**FACILITY PERMIT TO OPERATE
ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 7-13-2007]**

**TABLE OF STANDARDS (cont.)
VOC LIMITS**

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1124 9-21-2001]**

Except as otherwise provided in Rule 1124

- (1) VOC Content of Aerospace Materials
 - (A) A person shall not apply to aerospace components any materials, including any VOC-containing materials added to the original material supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC Limit			
Grams of VOC per Liter, Less Water and Less Exempt Compounds			
Primers	Current VOC Limit	VOC Limit Effective 1-1-03	VOC Limit Effective 1-1-05
General Primer	350	350	350
Low-Solids Corrosion Resistant Primer	350	350	350
Pretreatment Primer	780	780	780
Rain Erosion-Resistant Coating Compatible Primer	850	850	850
Adhesion Promoter	850	850	250
Adhesive Bonding Primer			
New Commercial Aircraft	805	250	250
All Military Aircraft	805	805	805
Remanufactured Commercial Aircraft Parts	805	805	805
Sonic and Acoustic Applications	805	805	805
Adhesive Bonding Primer			
Long Term	250	250	250
Short Term	250	250	250

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1124 9-21-2001]**

Coatings	Current VOC Limit	VOC Limit Effective 3-01-02
Topcoat	420	420
Clear Topcoat	520	520
Unicoat	420	420
Wing Coating	750	750
Impact Resistant Coating	420	420
High-Temperature Coating	850	850
Antichafe Coating	600	420
Rain Erosion-Resistant Coating	800	800
Conformal Coating	750	750
Optical Anti-Reflective Coating	700	700
Scale Inhibitor	880	880
Metallized Epoxy Coating	700	700
Electric or Radiation Effect Coating	800	800
Temporary Protective Coating	250	250
Fuel Tank Coatings	420	420
Mold Release Coatings	780	780
Flight Test Coatings		
Used on Missiles or Single Use Target Craft	420	420
All Other	840	840
Fire Resistant Coatings		
Commercial	650	650
Military	970	800
Wire Coatings		
Phosphate Ester Resistant Ink	925	925
Other	420	420
Space Vehicle Coatings		
Electrostatic Discharge Protection Coating	800	800
Other	1000	1000

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1124 9-21-2001]**

Adhesives	Current VOC Limit
Non-Structural Adhesive	250
Structural Adhesive	
Autoclavable	50
Non-Autoclavable	850
Space Vehicle Adhesive	800
Fuel Tank Adhesive	620

Sealants	Current VOC Limit	VOC Limit Effective 3-01-02
Fastener Sealant	675	675
Extrudable, Rollable or Brushable Sealant	600	280
Other	600	600

Maskants	Current VOC Limit
For Chemical Processing	250
For Chemical Milling	
Type I	250
Type II	160
Photolithographic	850
Touch-up, Line Sealer Maskants	750

Lubricants	Current VOC Limit
Fastener Installation	
Solid-Film Lubricant	880
Dry Lubricative Materials	675
Fastener-Lubricative Coatings, Fastener Manufacturing	
Solid Film Lubricant	250
Dry Lubricative Materials	120
Barrier Coating	420
Non-Fastener Lubricative Coatings, Fastener Manufacturing	
Solid Film Lubricant	880
Dry Lubricative Materials	675

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1124 9-21-2001]**

VOC LIMIT	
Grams of VOC per Liter of Material	
Cleaning Solvents and Strippers	Current VOC Limit
Cleaning Solvents	200 g/L or 45 mm Hg VOC Composite Partial Pressure
Strippers	300 g/L or 9.5 mm Hg VOC Composite Partial Pressure

- (B) Documents shall be provided to the Executive Officer or his designee demonstrating that unicoat is being used in lieu of the application of a primer and topcoat, and the applicant must receive written approval for the use of unicoat specifying the conditions of application from the Executive Officer or his designee.
- (C) For low-solids adhesives, coatings, primers or sealants, the appropriate limits in subparagraph (c)(1)(A) shall be expressed in grams of VOC per liter of material.
- (2) Solvent Cleaning Operations; Storage and Disposal of VOC-Containing Materials
 - (A) Cleaning of material application equipment and storage of solvent laden cloth and paper shall comply with provisions of Rule 1171.
 - (B) A person shall not atomize any solvent into open air.

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1140 2-1-1980]

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).
- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

FACILITY PERMIT TO OPERATE ROBINSON HELICOPTER CO INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1140 8-2-1985]

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines,
or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).
- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines,
or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 11-7-2003]**

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	500 (4.2)
(iii) Medical Devices & Pharmaceuticals	800 (6.7)
(B) Repair and Maintenance Cleaning	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)
(iii) Medical Devices & Pharmaceuticals	
(A) Tools, Equipment, & Machinery	800 (6.7)
(B) General Work Surfaces	600 (5.0)

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 11-7-2003]**

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(C) Cleaning of Coatings or Adhesives Application Equipment	550 (4.6)
(D) Cleaning of Ink Application Equipment	
(i) General	25 (0.21)
(ii) Flexographic Printing	25 (0.21)
(iii) Gravure Printing	
(A) Publication	750 (6.3)
(B) Packaging	25 (0.21)
(iv) Lithographic or Letter Press Printing	
(A) Roller Wash – Step 1	600 (5.0)
(B) Roller Wash-Step 2, Blanket Wash, & On-Press Components	800 (6.7)
(C) Removable Press Components	25 (0.21)
(v) Screen Printing	750 (6.3)
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	800 (6.7)

FACILITY PERMIT TO OPERATE
ROBINSON HELICOPTER CO INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-7-2003]

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(vii) Specialty Flexographic Printing	600 (5.0)
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 2-1-2008]**

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		
(iii) Medical Devices & Pharmaceuticals	800 (6.7)		
(B) Repair and Maintenance Cleaning			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 2-1-2008]**

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals			
(A) Tools, Equipment, & Machinery	800 (6.7)		
(B) General Work Surfaces	600 (5.0)		
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)		
(D) Cleaning of Ink Application Equipment			
(i) General	25 (0.21)		
(ii) Flexographic Printing	25 (0.21)		
(iii) Gravure Printing			
(A) Publication	100 (0.83)		
(B) Packaging	25 (0.21)		
(iv) Lithographic (Offset) or Letter Press Printing			
(A) Roller Wash, Blanket Wash, & On-Press Components			
(I) Newsprint	100 (0.83)		

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 2-1-2008]**

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(II) Other Substrates	500 (4.2)	100 (0.83)	
(B) Removable Press Components	25 (0.21)		
(v) Screen Printing	500 (4.2)	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)		
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)		

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 404 2-7-1986]**

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 404 2-7-1986]**

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 405 2-7-1986]**

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process)		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process)	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
100 or less	220 or less	0.450	0.99	9000	19840	5.308	11.7
150	331	0.585	1.29	10000	22050	5.440	12.0
200	441	0.703	1.55	12500	27560	5.732	12.6
250	551	0.804	1.77	15000	33070	5.982	13.2
300	661	0.897	1.98	17500	38580	6.202	13.7
350	772	0.983	2.17	20000	44090	6.399	14.1
400	882	1.063	2.34	25000	55120	6.743	14.9
450	992	1.138	2.51	30000	66140	7.037	15.5
500	1102	1.209	2.67	35000	77160	7.296	16.1
600	1323	1.340	2.95	40000	88180	7.527	16.6
700	1543	1.461	3.22	45000	99210	7.738	17.1
800	1764	1.573	3.47	50000	110200	7.931	17.5
900	1984	1.678	3.70	60000	132300	8.277	18.2
1000	2205	1.777	3.92	70000	154300	8.582	18.9

**FACILITY PERMIT TO OPERATE
 ROBINSON HELICOPTER CO INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 405 2-7-1986]**

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process)		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process)	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
1250	2756	2.003	4.42	80000	176400	8.854	19.5
1500	3307	2.206	4.86	90000	198400	9.102	20.1
1750	3858	2.392	5.27	100000	220500	9.329	20.6
2000	4409	2.563	5.65	125000	275600	9.830	21.7
2250	4960	2.723	6.00	150000	330700	10.26	22.6
2500	5512	2.874	6.34	175000	385800	10.64	23.5
2750	6063	3.016	6.65	200000	440900	10.97	24.2
3000	6614	3.151	6.95	225000	496000	11.28	24.9
3250	7165	3.280	7.23	250000	551200	11.56	25.5
3600	7716	3.404	7.50	275000	606300	11.82	26.1
4000	8818	3.637	8.02	300000	661400	12.07	26.6
4500	9921	3.855	8.50	325000	716500	12.30	27.1
5000	11020	4.059	8.95	350000	771600	12.51	27.6
6000	13230	4.434	9.78	400000	881800	12.91	28.5
7000	15430	4.775	10.5	450000	992100	13.27	29.3
8000	17640	5.089	11.2	500000 or more	1102000 or more	13.60	30.0