



FACILITY PERMIT TO OPERATE

**U.S. GOVT, DEPT OF NAVY
SAN CLEMENTE ISLAND
SAN CLEMENTE, CA 92672**

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

For *Amir Deylami*
By Amir Deylami
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance



**FACILITY PERMIT TO OPERATE
U.S. GOVT, DEPT OF NAVY**

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	1	08/29/2012
B	RECLAIM Annual Emission Allocation	1	08/29/2012
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	7	09/05/2013
E	Administrative Conditions	1	08/29/2012
F	RECLAIM Monitoring and Source Testing Requirements	1	08/29/2012
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	1	08/29/2012
H	Permit To Construct and Temporary Permit to Operate	4	05/28/2013
I	Compliance Plans & Schedules	1	08/29/2012
J	Air Toxics	1	08/29/2012
K	Title V Administration	3	09/05/2013
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	1	08/29/2012
B	Rule Emission Limits	3	09/05/2013

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: NALF SAN CLEMENTE ISLAND (ID NO. 47651)					
System 2: Emergency I.C. Engines					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, CATERPILLAR, MODEL NO. 3508, EIGHT CYLINDERS, 515 HP A/N: 161208	D21			HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; PM: (9) [RULE 404, 2-7-1986]	C1.1, D12.1, K67.8
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, PERKINS, MODEL NO. 4-236, 4 CYLINDERS, WITH TURBOCHARGER, 102 HP A/N: 271398	D26			HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; PM: (9) [RULE 404, 2-7-1986]	C1.1, D12.1, K67.8
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, VOLVO, MODEL TID121LG, 6 CYLINDERS, 440 HP A/N: 240412	D30			HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; PM: (9) [RULE 404, 2-7-1986]	C1.5, C177.1, D12.1, K67.8

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: NALF SAN CLEMENTE ISLAND (ID NO. 47651)					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, CATERPILLAR, MODEL 3406, 6 CYLINDERS, 449 HP A/N: 356268	D186			CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; PM: (9) [RULE 404, 2-7-1986]; ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]	C1.1, C1.7, C177.3, D12.1, K67.8
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, JOHN DEERE, MODEL 4039DF001, 4 CYLINDERS, 66 HP A/N: 305903	D154			HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; PM: (9) [RULE 404, 2-7-1986]	C1.1, D12.1, K67.8
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, JOHN DEERE, MODEL 6076T, 6 CYLINDERS, 211 HP A/N: 305387	D169			HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; PM: (9) [RULE 404, 2-7-1986]	C1.1, C177.1, D12.1, K67.8

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: NALF SAN CLEMENTE ISLAND (ID NO. 47651)					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, JOHN DEERE, MODEL 4045TF, 4 CYLINDERS, WITH TURBOCHARGER, 100 HP A/N: 359675	D190			CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; PM: (9) [RULE 404, 2-7-1986]; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]	C1.1, C177.1, D12.1, K67.8
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, JOHN DEERE, MODEL 4045TF, 4 CYLINDERS, WITH TURBOCHARGER, 100 HP A/N: 359679	D191			CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; PM: (9) [RULE 404, 2-7-1986]; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]	C1.1, C177.1, D12.1, K67.8

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: NALF SAN CLEMENTE ISLAND (ID NO. 47651)					
INTERNAL COMBUSTION ENGINE, DRIVING AN EMERGENCY AIRCRAFT LANDING RUNWAY ARRESTING GEAR SYSTEM, GASOLINE, WISCONSIN MOTORS, LLC, MODEL V465D1, FOUR CYLINDERS, SERIAL NO. 10100043, 65 HP A/N: 539197	D226			HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; PM: (9) [RULE 404, 2-7-1986]	C1.1, C1.16, D12.1, K67.8
INTERNAL COMBUSTION ENGINE, DRIVING AN EMERGENCY AIRCRAFT LANDING RUNWAY ARRESTING GEAR SYSTEM, GASOLINE, WISCONSIN MOTORS, LLC, MODEL V465D1, FOUR CYLINDERS, SERIAL NO. 10100048, 65 HP A/N: 539198	D227			HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; PM: (9) [RULE 404, 2-7-1986]	C1.1, C1.16, D12.1, K67.8
INTERNAL COMBUSTION ENGINE, DRIVING AN EMERGENCY AIRCRAFT LANDING RUNWAY ARRESTING GEAR SYSTEM, GASOLINE, WISCONSIN MOTORS, LLC, MODEL V465D1, FOUR CYLINDERS, SERIAL NO. 11030008, 65 HP A/N: 539199	D228			HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; PM: (9) [RULE 404, 2-7-1986]	C1.1, C1.16, D12.1, K67.8

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: NALF SAN CLEMENTE ISLAND (ID NO. 47651)					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY AIRCRAFT LANDING RUNWAY ARRESTING GEAR SYSTEM, GASOLINE, WISCONSIN MOTORS, LLC., MODEL V465D1, FOUR CYLINDERS, SERIAL NO. 11030011, 65 HP A/N: 539200	D229			HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; PM: (9) [RULE 404, 2-7-1986]	C1.1, C1.16, D12.1, K67.8
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, JOHN DEERE, MODEL 4045DF, 4 CYLINDERS, 71 HP A/N: 375099	D198			CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; PM: (9) [RULE 404, 2-7-1986]; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]	C1.1, D12.1, K67.8

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: NALF SAN CLEMENTE ISLAND (ID NO. 47651)					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, CATERPILLAR, MODEL 3406 DITA, SERIAL NO. 1LS01312, 6 CYLINDERS, 449 HP A/N: 374527	D199			CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; PM: (9) [RULE 404, 2-7-1986]; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]	C1.1, D12.1, K67.8
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, JOHN DEERE, MODEL 6068TF150, SERIAL NO. T06068T890437, 6 CYLINDERS, WITH TURBOCHARGER, 150 HP A/N: 392660	D200			CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; HAP: (10) [40CFR 63SubpartZZZZ, 3-9-2011]; NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; PM: (9) [RULE 404, 2-7-1986]; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]	C1.1, C1.8, D12.1, K67.8

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: NALF SAN CLEMENTE ISLAND (ID NO. 47651)					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, PERKINS, MODEL 1004-4-TW, 4 CYLINDERS, WITH AFTERCOOLER, TURBOCHARGER, 117 HP A/N: 401766	D203			CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; HAP: (10) [40CFR 63SubpartZZZ, 3-9-2011]; NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; PM: (9) [RULE 404, 2-7-1986]; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]	C1.1, C1.8, D12.1, K67.8
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, DETROIT DIESEL, MODEL 6063 MK35, 6 CYLINDERS, WITH AFTERCOOLER, TURBOCHARGER, 490 HP A/N: 404871	D204			CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; HAP: (10) [40CFR 63SubpartZZZ, 3-9-2011]; NOX + ROG: 4.8 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; PM: (9) [RULE 404, 2-7-1986]; PM10: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]	C1.1, C1.8, D12.1, K67.8

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: NALF SAN CLEMENTE ISLAND (ID NO. 47651)					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, JOHN DEERE, MODEL 6068HF275L, 6 CYLINDERS, WITH TURBOCHARGER, 220 HP A/N: 432648	D205			CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; HAP: (10) [40CFR 63SubpartZZZ, 3-9-2011]; NOX + ROG: 4.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]	B61.2, C1.1, C1.8, D12.1, K67.8
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, DEUTZ, MODEL BF6M1013C/FC, 6 CYLINDERS, WITH AFTERCOOLER, TURBOCHARGER, 218 HP A/N: 442457	D206			CO: 2.6 GRAM/BHP-HR DIESEL (8) [40CFR 60 Subpart III, 6-28-2011]; CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; NOX + ROG: 4.9 GRAM/BHP-HR DIESEL (8) [40CFR 60 Subpart III, 6-28-2011]; NOX + ROG: 4.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; PM: 0.15 GRAM/BHP-HR DIESEL (8) [40CFR 60 Subpart III, 6-28-2011]	B61.1, C1.1, C1.8, D12.1, H23.9, K67.8

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: NALF SAN CLEMENTE ISLAND (ID NO. 47651)					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, DEUTZ, MODEL BF6M1013C/FC, 6 CYLINDERS, WITH AFTERCOOLER, TURBOCHARGER, 218 HP A/N: 442459	D207			CO: 2.6 GRAM/BHP-HR DIESEL (8) [40CFR 60 Subpart III, 6-28-2011]; CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; NOX + ROG: 4.9 GRAM/BHP-HR DIESEL (8) [40CFR 60 Subpart III, 6-28-2011]; NOX + ROG: 4.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; PM: 0.15 GRAM/BHP-HR DIESEL (8) [40CFR 60 Subpart III, 6-28-2011]	B61.1, C1.1, C1.8, D12.1, H23.9, K67.8

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: NALF SAN CLEMENTE ISLAND (ID NO. 47651)					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, DEUTZ, MODEL BF6M1013C/FC, 6 CYLINDERS, WITH AFTERCOOLER, TURBOCHARGER, 218 HP A/N: 451789	D208			CO: 2.6 GRAM/BHP-HR DIESEL (8) [40CFR 60 Subpart III, 6-28-2011]; CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; NOX + ROG: 4.9 GRAM/BHP-HR DIESEL (8) [40CFR 60 Subpart III, 6-28-2011]; NOX + ROG: 4.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; PM: 0.15 GRAM/BHP-HR DIESEL (8) [40CFR 60 Subpart III, 6-28-2011]	B61.1, C1.1, C1.8, D12.1, H23.9, K67.8

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: NALF SAN CLEMENTE ISLAND (ID NO. 47651)					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, PERKINS (CATERPILLAR), MODEL D150-8 (C6.6), 6 CYLINDERS, WITH AFTERCOOLER, TURBOCHARGER, 230 HP A/N: 517041	D224			CO: 2.6 GRAM/BHP-HR DIESEL (8) [40CFR 60 Subpart III, 6-28-2011]; CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; NOX + ROG: 3 GRAM/BHP-HR DIESEL (8) [40CFR 60 Subpart III, 6-28-2011]; NOX + ROG: 3 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; PM: 0.15 GRAM/BHP-HR DIESEL (8) [40CFR 60 Subpart III, 6-28-2011]	B61.1, C1.1, C1.8, D12.1, H23.9, K67.8
System 4: Boilers					
BOILER, FUEL OIL NO. 2, HASTINGS, MODEL P5002, 0.625 MMBTU/HR A/N: 132690	D39			CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; HAP: (10) [40CFR 63SubpartJJJJ, 3-21-2011]; NOX: 40 PPMV FUEL OIL 2 (5) [RULE 1147, 9-9-2011]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]; SOX: 500 PPMV (5) [RULE 407, 4-2-1982]	H23.7

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: NALF SAN CLEMENTE ISLAND (ID NO. 47651)					
BOILER, FUEL OIL NO. 2, WEIL MCLAIN, MODEL P-578-W, SERIAL NO. CP3488608, 0.521 MMBTU/HR A/N: 356138	D187			CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; HAP: (10) [40CFR 63SubpartJJJJJ, 3-21-2011]; NOX: 40 PPMV FUEL OIL 2 (5) [RULE 1147, 9-9-2011]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]; SOX: 500 PPMV (5) [RULE 407, 4-2-1982]	H23.7
BOILER, FUEL OIL NO. 2, WEIL MCLAIN, MODEL P-578-W, SERIAL NO. CP3488609, 0.521 MMBTU/HR A/N: 356139	D188			CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; HAP: (10) [40CFR 63SubpartJJJJJ, 3-21-2011]; NOX: 40 PPMV FUEL OIL 2 (5) [RULE 1147, 9-9-2011]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]; SOX: 500 PPMV (5) [RULE 407, 4-2-1982]	H23.7
System 5: Fueling Stations					
STORAGE TANK, UNDERGROUND, JP-5, 26000 GALS A/N: 214115	D58				B22.1, K67.2
STORAGE TANK, UNDERGROUND, JP-5, 26000 GALS A/N: 214115	D59				B22.1, K67.2
STORAGE TANK, JP-5, 50000 GALS A/N: 214115	D60				B22.1, K67.2
STORAGE TANK, UNDERGROUND, JP-5, 250000 GALS A/N: 214115	D61				B22.1, K67.2
LOADING ARM, BOTTOM, JP5, DIAMETER: 2.5 IN A/N: 214115	D62				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: NALF SAN CLEMENTE ISLAND (ID NO. 47651)					
LOADING ARM, BOTTOM, JP5, DIAMETER: 2.5 IN A/N: 214115	D63				
STORAGE TANK, FIXED ROOF, GASOLINE, ABOVE GROUND, WITH SUBMERGED FILLING, 10000 GALS; DIAMETER: 8 FT ; LENGTH: 28 FT A/N: 504366	D211			HAP: (10) [40CFR 63SubpartCCCCC, 1-24-2011]	D330.1, E193.1, H23.8, J109.1, J373.3, K67.9
STORAGE TANK, FIXED ROOF, GASOLINE, ABOVE GROUND, WITH SUBMERGED FILLING, 10000 GALS; DIAMETER: 8 FT ; LENGTH: 28 FT A/N: 504366	D212			HAP: (10) [40CFR 63SubpartCCCCC, 1-24-2011]	D330.1, E193.1, H23.8, J109.1, J373.3, K67.9
STORAGE TANK, FIXED ROOF, GASOLINE, ABOVE GROUND, WITH SUBMERGED FILLING, 10000 GALS; DIAMETER: 8 FT ; LENGTH: 28 FT A/N: 504366	D213			HAP: (10) [40CFR 63SubpartCCCCC, 1-24-2011]	D330.1, E193.1, H23.8, J109.1, J373.3, K67.9
STORAGE TANK, FIXED ROOF, GASOLINE, ABOVE GROUND, WITH SUBMERGED FILLING, 10000 GALS; DIAMETER: 8 FT ; LENGTH: 28 FT A/N: 504366	D214			HAP: (10) [40CFR 63SubpartCCCCC, 1-24-2011]	D330.1, E193.1, H23.8, J109.1, J373.3, K67.9
STORAGE TANK, FIXED ROOF, GASOLINE, ABOVE GROUND, WITH SUBMERGED FILLING, 10000 GALS; DIAMETER: 8 FT ; LENGTH: 28 FT A/N: 504366	D215				D330.1, E193.1, H23.8, J109.1, J373.3, K67.9
STORAGE TANK, FIXED ROOF, GASOLINE, ABOVE GROUND, WITH SUBMERGED FILLING, 10000 GALS; DIAMETER: 8 FT ; LENGTH: 28 FT A/N: 504366	D216				D330.1, E193.1, H23.8, J109.1, J373.3, K67.9

- | | |
|--|--|
| <ul style="list-style-type: none"> * (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits | <ul style="list-style-type: none"> (2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements |
|--|--|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: NALF SAN CLEMENTE ISLAND (ID NO. 47651)					
FUEL DISPENSING NOZZLE, TOP MOUNTED, PHASE II CONTROL, HEALY, MODEL 400 ORVR (G-70-187) A/N: 504366	D217				C1.10, C1.11, D330.1, E193.1, H23.8, J110.1, J373.3, K67.9
FUEL DISPENSING NOZZLE, TOP MOUNTED, PHASE II CONTROL, HEALY, MODEL 400 ORVR (G-70-187) A/N: 504366	D218				C1.10, C1.11, D330.1, E193.1, H23.8, J110.1, J373.3, K67.9
LOADING ARM, GASOLINE, ONE HOSE WITH DRY BREAK CONNECT COUPLER FOR BOTTOM LOADER A/N: 504366	D222			HAP: (10) [40CFR 63SubpartBBBBBB, 1-24-2011]	C1.14, C1.15, J373.4, K67.9
LOADING ARM, GASOLINE, ONE VAPOR RECOVERY HOSE WITH CAMLOCK QUICK CONNECT COUPLER A/N: 504366	D223			HAP: (10) [40CFR 63SubpartBBBBBB, 1-24-2011]	C1.14, C1.15, J373.4, K67.9
Process 2: PUBLIC WORK CENTER, SAN CLEMENTE ISLAND (ID NO. 66802)					
System 1: Non-Emergency I.C. Engines					
INTERNAL COMBUSTION ENGINE, NON-EMERGENCY, DIESEL FUEL, GENERAL MOTORS POWER, MODEL NO. 12-645-E1, 1200 HP WITH GENERATOR	D17			CO: 23 PPMV (8) [40CFR 63SubpartZZZZ, 3-9-2011]; PM: (9) [RULE 404, 2-7-1986]	D323.1, H23.10, K67.1

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2: PUBLIC WORK CENTER, SAN CLEMENTE ISLAND (ID NO. 66802)					
INTERNAL COMBUSTION ENGINE, NON-EMERGENCY, DIESEL FUEL, GENERAL MOTORS POWER, MODEL 8-567-CR, 720 HP WITH A/N: GENERATOR	D18			CO: 23 PPMV (8) [40CFR 63SubpartZZZZ, 3-9-2011]; PM: (9) [RULE 404, 2-7-1986]	D323.1, H23.10, K67.1
INTERNAL COMBUSTION ENGINE, NON-EMERGENCY, DIESEL FUEL, GENERAL MOTORS POWER, MODEL 8-567-CR, 720 HP WITH A/N: GENERATOR	D19			CO: 23 PPMV (8) [40CFR 63SubpartZZZZ, 3-9-2011]; PM: (9) [RULE 404, 2-7-1986]	D323.1, H23.10, K67.1
INTERNAL COMBUSTION ENGINE, NON-EMERGENCY, SERIAL NO. 67-L1-1129, DRIVING A GENERATOR, DIESEL FUEL, GENERAL MOTORS POWER, MODEL 12-645-E4, 1440 HP WITH A/N: GENERATOR	D20			CO: 23 PPMV (8) [40CFR 63SubpartZZZZ, 3-9-2011]; PM: (9) [RULE 404, 2-7-1986]	D323.1, H23.10, K67.1
System 2: Emergency I.C. Engines					

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2: PUBLIC WORK CENTER, SAN CLEMENTE ISLAND (ID NO. 66802)					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DRIVING AN EMERGENCY ELECTRICAL GENERATOR, DIESEL FUEL, JOHN DEERE, MODEL 4045TF, 4 CYLINDERS, WITH TURBOCHARGER, 100 HP A/N: 363403	D196			CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; HAP: (10) [40CFR 63SubpartZZZ, 3-9-2011]; NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; PM: (9) [RULE 404, 2-7-1986]; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]	C1.1, C177.1, D12.1, K67.8
System 4: Maintenance Support Systems					
ABRASIVE BLASTING, OPEN, MODEL K-125V, SAND, 800 LBS CAPACITY WITH A/N: 331640	D103			PM: (9) [RULE 1140, 2-1-1980; RULE 1140, 8-2-1985; RULE 405, 2-7-1986]	D323.1, K67.5
ABRASIVE BLASTING NOZZLE, DIAMETER: .5 IN	D104				
System 6: Sewage Treatment Plant, Aer-O-Flo Aerobic Digestion, Model No. S-300					S1.1
HEADWORK, COMMON TO TITAN MBR SYSTEM, WITH ONE COMMUNTOR, SCREEN, GRIT CHAMBER, PRIMARY LET AND SECONDARY LET A/N: 554637	D189				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2: PUBLIC WORK CENTER, SAN CLEMENTE ISLAND (ID NO. 66802)					
DIGESTER, SECONDARY TREATMENT, WITH AERATION BASIN AND CLARIFIERS A/N: 554637	D194				
EVAPORATOR, SLUDGE DRYING BEDS, FOUR A/N: 554637	D195				
System 7: Waste Water Treatment Plant, Smith and Loveless, Titan MBR					S1.2
HEADWORK, COMMON TO TITAN MBR SYSTEM, WITH ONE COMMUNTOR, SCREEN, GRIT CHAMBER, PRIMARY LET AND SECONDARY LET A/N: 554637	D189				
SCREEN, FINE A/N: 554637	D234				
TANK, FLOW EQUILIZATION, WITH A 3 HP BLOWER A/N: 554637	D235				
TANK, SLUDGE HOLDING, 1200 CU.FT. A/N: 554637	D236				
TANK, WITH TWO ANOXIC ZONES, EACH WITH 800 CU. FT. CAPACITY, WITH MIXERS A/N: 554637	D237				
TANK, AERATION ZONE, WITH TWO 20-HP BLOWERS, CONTAINING AN IMMERSION TYPE MEMBRANE, 3544 CU.FT. A/N: 554637	D238				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2: PUBLIC WORK CENTER, SAN CLEMENTE ISLAND (ID NO. 66802)					
TANK, CHLORINE CONTACT, WITH A TABLET CHLORINATOR, 1000 GALS A/N: 554637	D239				
TANK, BLENDING, CITRIC ACID OR SODIUM HYPOCHLORITE, MEMBRANE CLEANING SOLUTION, 325 GALS A/N: 554637	D240				
STORAGE TANK, SPENT MEMBRANE CLEANING SOLUTION, 1100 GALS A/N: 554637	D241				
Process 3: R-219 Exempt Equipment Subject to Source-Specific Rules					
RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS	E157				H23.2
RULE 219 EXEMPT EQUIPMENT, REFRIGERATION UNITS	E158				H23.2
RULE 219 EXEMPT EQUIPMENT, REFRIGERANT RECOVERY AND/OR RECYCLING UNITS,	E159				H23.3
RULE 219 EXEMPT EQUIPMENT, ABRASIVE BLASTING EQUIPMENT, PORTABLE, < 66 % VOLUME WATER	E160			PM: (9) [RULE 1140, 2-1-1980; RULE 1140, 8-2-1985; RULE 405, 2-7-1986]	D323.1, K67.5
RULE 219 EXEMPT EQUIPMENT, CLEANING EQUIPMENT, SMALL, UNHEATED, NON-CONVEYORIZED	E161			VOC: (9) [RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	H23.4
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, LOW USE OR EMISSIONS	E162			VOC: (9) [RULE 1107, 1-6-2006; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	H23.6

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 3: R-219 Exempt Equipment Subject to Source-Specific Rules					
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS	E163			VOC: (9) [RULE 1113, 7-13-2007; RULE 1113, 6-3-2011; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	K67.4
RULE 219 EXEMPT EQUIPMENT, HALON UNITS	E164				H23.1
RULE 219 EXEMPT EQUIPMENT, EXEMPT HAND WIPING OPERATIONS	E165			VOC: (9) [RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	H23.6
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, LOW USE OR EMISSIONS	E166			VOC: (9) [RULE 1106, 1-13-1995; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	H23.6
RULE 219 EXEMPT EQUIPMENT, ASBESTOS REMOVAL	E185				H23.5
RULE 219 EXEMPT EQUIPMENT, HAND LAY, BRUSH AND ROLL UP RESIN OPERATIONS	E192			VOC: (9) [RULE 1162, 11-17-2000; RULE 1162, 7-8-2005; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	H23.6

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
U.S. GOVT, DEPT OF NAVY**

SECTION D: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

**FACILITY PERMIT TO OPERATE
 U.S. GOVT, DEPT OF NAVY
 SECTION D: DEVICE ID INDEX**

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D17	14	2	1
D18	15	2	1
D19	15	2	1
D20	15	2	1
D21	1	1	2
D26	1	1	2
D30	1	1	2
D39	11	1	4
D58	12	1	5
D59	12	1	5
D60	12	1	5
D61	12	1	5
D62	12	1	5
D63	13	1	5
D103	16	2	4
D104	16	2	4
D154	2	1	2
E157	18	3	0
E158	18	3	0
E159	18	3	0
E160	18	3	0
E161	18	3	0
E162	18	3	0
E163	19	3	0
E164	19	3	0
E165	19	3	0
E166	19	3	0
D169	2	1	2
E185	19	3	0
D186	2	1	2
D187	12	1	4
D188	12	1	4
D189	16	2	6
D189	17	2	7
D190	3	1	2

**FACILITY PERMIT TO OPERATE
 U.S. GOVT, DEPT OF NAVY
 SECTION D: DEVICE ID INDEX**

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D191	3	1	2
E192	19	3	0
D194	17	2	6
D195	17	2	6
D196	16	2	2
D198	5	1	2
D199	6	1	2
D200	6	1	2
D203	7	1	2
D204	7	1	2
D205	8	1	2
D206	8	1	2
D207	9	1	2
D208	10	1	2
D211	13	1	5
D212	13	1	5
D213	13	1	5
D214	13	1	5
D215	13	1	5
D216	13	1	5
D217	14	1	5
D218	14	1	5
D222	14	1	5
D223	14	1	5
D224	11	1	2
D226	4	1	2
D227	4	1	2
D228	4	1	2
D229	5	1	2
D234	17	2	7
D235	17	2	7
D236	17	2	7
D237	17	2	7
D238	17	2	7
D239	18	2	7

**FACILITY PERMIT TO OPERATE
U.S. GOVT, DEPT OF NAVY
SECTION D: DEVICE ID INDEX**

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D240	18	2	7
D241	18	2	7

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or

(b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[**RULE 401, 3-2-1984**; RULE 401, 11-9-2001]

F14.1 The operator shall not purchase diesel fuel containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

[RULE 431.2, 9-15-2000]

F14.2 The operator shall not use diesel fuel containing sulfur compounds in excess of 0.05 percent by weight.

[**RULE 431.2, 5-4-1990**; RULE 431.2, 9-15-2000]

SYSTEM CONDITIONS

S1.1 The operator shall limit the throughput to no more than 60000 gallon(s) per day.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall use this system for the treatment of domestic wastewater

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

This system shall only be used as a backup to Process 2, System 7

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 2, System 6]

S1.2 The operator shall limit the throughput to no more than 30000 gallon(s) per day.

The operator shall use this system for the treatment of domestic wastewater

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 2, System 7]

DEVICE CONDITIONS

B. Material/Fuel Type Limits

B22.1 The operator shall not use this equipment with materials having a(n) Reid vapor pressure of 0.1 psia or greater under actual operating conditions.

[**RULE 1303(b)(2)-Offset, 5-10-1996**]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D58, D59, D60, D61]

B61.1 The operator shall not use diesel fuel containing the following specified compounds:

Compound	ppm by weight
Sulfur greater than	15

[RULE 1303(a)(1)-BACT, 5-10-1996; 40CFR 60 Subpart III, 6-28-2011]

[Devices subject to this condition : D206, D207, D208, D224]

B61.2 The operator shall not use diesel fuel containing the following specified compounds:

Compound	ppm by weight
Sulfur greater than	15

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D205]

C. Throughput or Operating Parameter Limits

C1.1 The operator shall limit the operating time to no more than 200 hours in any one year.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D21, D26, D154, D169, D186, D190, D191, D196, D198, D199, D200, D203, D204, D205, D206, D207, D208, D224, D226, D227, D228, D229]

C1.5 The operator shall limit the operating time to no more than 125 hour(s) in any one year.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996]

[Devices subject to this condition : D30]

C1.7 The operator shall limit the operating time to no more than 1 hour(s) in any one day.

For the purpose of this condition, operating time shall be defined as testing time for this engine.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D186]

C1.8 The operator shall limit the maintenance testing to no more than 50 hour(s) in any one year.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D200, D203, D204, D205, D206, D207, D208, D224]

C1.10 The operator shall limit the gasoline dispensed to no more than 23000 gallon(s) in any one calendar month.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D217, D218]

C1.11 The operator shall limit the gasoline dispensed to no more than 276000 gallon(s) per year.

[RULE 1401, 3-4-2005]

[Devices subject to this condition : D217, D218]

C1.14 The operator shall limit the gasoline dispensed to no more than 10000 gallon(s) in any one calendar month.

This condition applies to bulk unloading operations.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D222, D223]

C1.15 The operator shall limit the gasoline dispensed to no more than 120000 gallon(s) per year.

This condition applies to bulk unloading operations..

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 3-4-2005]

[Devices subject to this condition : D222, D223]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C1.16 The operator shall limit the maintenance testing to no more than 50 hour(s) in any one year.

Except for testing and maintenance, this engine shall only operate during emergency aircraft landing operations.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D226, D227, D228, D229]

C177.1 The operator shall set and maintain the fuel injection timing of the engine at 4 degrees retarded relative to standard timing.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D30, D169, D190, D191, D196]

C177.3 The operator shall set and maintain the fuel injection timing of the engine at 6 degrees retarded relative to standard timing.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D186]

D. Monitoring/Testing Requirements

D12.1 The operator shall install and maintain a(n) non-resettable elapsed time meter to accurately indicate the elapsed operating time of the engine.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D21, D26, D30, D154, D169, D186, D190, D191, D196, D198, D199, D200, D203, D204, D205, D206, D207, D208, D224, D226, D227, D228, D229]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a quarterly basis, at least, unless the equipment did not operate during the entire quarterly period. The routine quarterly inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D17, D18, D19, D20, D103, E160]

D330.1 The operator shall have a person that has been trained in accordance with Rule 461 conduct a semi-annual inspection of the gasoline transfer and dispensing equipment. The first inspection shall be in accordance with Rule 461, Attachment B, the second inspection shall be in accordance with Rule 461, Attachment C, and the subsequent inspections shall alternate protocols. The operator shall keep records of the inspection and the repairs in accordance to Rule 461 and Section K of this Permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D211, D212, D213, D214, D215, D216, D217, D218]

E. Equipment Operation/Construction Requirements

E193.1 The operator shall operate and maintain this equipment as follows:

All phase I and phase II vapor recovery equipment at this facility shall be installed, operated and maintained to meet all California Air Resources Board certification requirements

[RULE 461, 6-3-2005; RULE 461, 4-6-2012]

[Devices subject to this condition : D211, D212, D213, D214, D215, D216, D217, D218]

H. Applicable Rules

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H23.1 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
Halon	District Rule	1418

[RULE 1418, 9-10-1999]

[Devices subject to this condition : E164]

H23.2 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
Refrigerants	District Rule	1415
Refrigerants	40CFR82, SUBPART	F

[RULE 1415, 12-3-2010; **40CFR 82 Subpart F, 5-14-1993**]

[Devices subject to this condition : E157, E158]

H23.3 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
Refrigerants	District Rule	1411
Refrigerants	40CFR82, SUBPART	B

[RULE 1411, 3-1-1991; **40CFR 82 Subpart B, 7-14-1992**]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : E159]

H23.4 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	1122

[RULE 1122, 10-1-2004; RULE 1122, 5-1-2009]

[Devices subject to this condition : E161]

H23.5 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
Asbestos	District Rule	1403

[RULE 1403, 10-5-2007]

[Devices subject to this condition : E185]

H23.6 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	109

[RULE 109, 5-2-2003]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : E162, E165, E166, E192]

H23.7 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
NOX	District Rule	1147

Prior to modification of the equipment to come into compliance with the emission limit of the Rule, the operator shall submit an application and receive approval for construction or modification of the equipment

[RULE 1147, 9-9-2011]

[Devices subject to this condition : D39, D187, D188]

H23.8 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	461

[**RULE 461, 6-3-2005**; RULE 461, 4-6-2012]

[Devices subject to this condition : D211, D212, D213, D214, D215, D216, D217, D218]

H23.9 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
-------------	------	--------------

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

HAPs	40CFR63, SUBPART	ZZZZ
------	------------------	------

[40CFR 63SubpartZZZZ, 3-9-2011]

[Devices subject to this condition : D206, D207, D208, D224]

H23.10 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
HAPs	40CFR63, SUBPART	ZZZZ

[40CFR 63SubpartZZZZ, 3-9-2011]

[Devices subject to this condition : D17, D18, D19, D20]

J. Rule 461

J109.1 The operator shall use, except for diesel transfer, the phase I vapor recovery system in full operation whenever this equipment is in use. This system shall be installed, operated and maintained to meet all CARB certification requirements.

[RULE 461, 6-3-2005; RULE 461, 4-6-2012]

[Devices subject to this condition : D211, D212, D213, D214, D215, D216]

J110.1 The operator shall use, except for diesel transfer, the phase II vapor recovery system in full operation whenever gasoline from this equipment is dispensed to motor vehicles as defined in Rule 461. This system shall be installed, operated and maintained to meet all CARB certification requirements.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[**RULE 461, 6-3-2005**; RULE 461, 4-6-2012]

[Devices subject to this condition : D217, D218]

J373.3 The operator shall comply with the following gasoline transfer and dispensing requirements:

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

a) A static pressure integrity test shall be conducted to demonstrate that the storage tanks, the remote and/or nozzle vapor recovery check valves, associated vapor return piping and fittings are free from vapor leaks. The test shall be conducted as outlined in exhibit 3 of CARB executive order G-70-187 as a performance test and as a reverification test. Results shall be submitted to the AQMD, office of Engineering and Compliance, within (72) hours of test.

b) A vapor return line vacuum integrity test shall be conducted to verify the vapor tightness of the Healy system. the test shall be conducted as outlined in exhibit 4 of CARB executive order G-70-187 as a performance test reverification test. results shall be submitted to the AQMD office of Engineering and Compliance, within seventy-two (72) hours of test.

c) A fillneck vapor pressure regulation fueling test shall be conducted to verify proper operation of the nozzle boot pressure regulation which is unique to the Healy model 400 ORVR nozzle. The test shall be conducted as outlined in exhibit 5 of CARB executive order G-70-187 as a performance test and as a reverification test. Results shall be submitted to the AQMD, office of Engineering and Compliance, within seventy-two (72) hours of the test.

The AQMD shall be notified by e-mail at r461testing@aqmd.gov or by facsimile at telephone number (909) 396-3606 at least seventy-two (72) hours prior to any of the above mentioned testing requirements. such notification shall include the name of the owner or operator; the name of the contractor; the location of the facility; and the scheduled start and completion dates of the tests to be performed.

The testing frequency for the above mentioned tests shall be conducted in accordance with the most recent AQMD Rule 461 amendment or CARB Executive Order requirements, whichever is more stringent.

[**RULE 461, 6-3-2005**; RULE 461, 4-6-2012]

[Devices subject to this condition : D211, D212, D213, D214, D215, D216, D217, D218]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

J373.4 The operator shall comply with the following gasoline transfer and dispensing requirements:

This equipment shall be operated for bottom loading only during the transfer of gasoline fuel from the underground storage tank into any tank truck. All vapor return lines shall be connected between the underground gasoline storage tank and tank truck

The bulk loading transfer equipment shall be operated and maintained so that there are no overfills, facility vapor leaks, liquid leaks, or liquid leaks from disconnect operations

The bulk loading equipment shall be operated so that the backpressure in the vapor recovery system does not exceed 18 inches of water column pressure

This Class "B" loading facility shall be installed, operated and maintained in accordance with district Rule 462

The bulk plant vapor recovery system shall be certified by the California Air Resources Board (CARB) as required in District Rule 462. The copy of the CARB bulk plant vapor recovery certification test results shall be retained on site and made available to District representatives upon request

[RULE 462, 5-14-1999]

[Devices subject to this condition : D222, D223]

K. Record Keeping/Reporting

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Days and hours of operation

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D17, D18, D19, D20]

K67.2 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

throughput

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D58, D59, D60, D61]

K67.4 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records for all coating consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coatings.

For architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coatings.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : E163, E167]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.5 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

purchase records of abrasive used or daily records of abrasives used and evidence of ARB certification

If abrasives are re-used, records to demonstrate that such abrasives are tested with CARB Method 371-A

Daily records of the description of items blasted to demonstrate compliance

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D103, E160]

K67.8 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

A. Emergency use hours of operation

B. Maintenance and testing hours

C. Other operating hours (describe the reason for operation)

The log shall include the date of operation and the timer reading in hours at the beginning and end of operation. The log shall be kept for a minimum of five calendar years prior to the current year and made available to District personnel upon request. The total hours of operation for the previous calendar year shall be recorded sometime during the first 15 days of January of each year.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D21, D26, D30, D154, D169, D186, D190, D191, D196, D198, D199, D200, D203, D204, D205, D206, D207, D208, D224, D226, D227, D228, D229]

K67.9 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

All records and test results that are required to be maintained by Rule 461 and Rule 462 shall be kept on site for five years and made available to District representatives upon request

Records of monthly and annual fuel dispensed shall be prepared, shall be retained on site for five years, and shall be made available to District representatives upon request

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 3-4-2005; RULE 461, 6-3-2005; RULE 461, 4-6-2012; RULE 462, 5-14-1999]

[Devices subject to this condition : D211, D212, D213, D214, D215, D216, D217, D218, D222, D223]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION K: TITLE V Administration

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
- (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.
 - (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
 - (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
- (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]

10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]

12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]

13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION K: TITLE V Administration

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]
15. Nothing in this permit or in any permit shield can alter or affect:
- (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]
16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION K: TITLE V Administration EMERGENCY PROVISIONS

17. An emergency¹ constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
 - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
 - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
 - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
 - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
 - (B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

¹ "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION K: TITLE V Administration RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:

- (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
- (B) The date(s) analyses were performed;
- (C) The company or entity that performed the analyses;
- (D) The analytical techniques or methods used;
- (E) The results of such analyses; and
- (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]

20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]

21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:

- (A) Breakdowns shall be reported as required by Rule 430 – Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION K: TITLE V Administration

- (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.
 - (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
 - (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION K: TITLE V Administration

- (B) The compliance status during the reporting period;
- (C) Whether compliance was continuous or intermittent;
- (D) The method(s) used to determine compliance over the reporting period and currently, and
- (E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn:
Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 109	5-2-2003	Federally enforceable
RULE 1106	1-13-1995	Federally enforceable
RULE 1107	1-6-2006	Federally enforceable
RULE 1113	6-3-2011	Non federally enforceable
RULE 1113	7-13-2007	Federally enforceable
RULE 1122	10-1-2004	Federally enforceable
RULE 1122	5-1-2009	Non federally enforceable
RULE 1140	2-1-1980	Federally enforceable
RULE 1140	8-2-1985	Non federally enforceable
RULE 1147	9-9-2011	Non federally enforceable
RULE 1162	11-17-2000	Federally enforceable
RULE 1162	7-8-2005	Non federally enforceable
RULE 1171	2-1-2008	Federally enforceable
RULE 1171	5-1-2009	Non federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303(a)(1)-BACT	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	12-6-2002	Non federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1304(a)-Modeling and Offset Exemption	6-14-1996	Federally enforceable
RULE 1401	3-4-2005	Non federally enforceable

FACILITY PERMIT TO OPERATE U.S. GOVT, DEPT OF NAVY

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 1403	10-5-2007	Non federally enforceable
RULE 1411	3-1-1991	Non federally enforceable
RULE 1415	12-3-2010	Non federally enforceable
RULE 1418	9-10-1999	Non federally enforceable
RULE 204	10-8-1993	Federally enforceable
RULE 217	1-5-1990	Federally enforceable
RULE 219	5-3-2013	Non federally enforceable
RULE 219	9-4-1981	Federally enforceable
RULE 222	3-5-2004	Non federally enforceable
RULE 3002	11-14-1997	Federally enforceable
RULE 3002	11-5-2010	Non federally enforceable
RULE 3003	11-14-1997	Federally enforceable
RULE 3003	11-5-2010	Non federally enforceable
RULE 3004	12-12-1997	Federally enforceable
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3005	11-5-2010	Non federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	6-1-2012	Non federally enforceable
RULE 401	11-9-2001	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 405	2-7-1986	Federally enforceable
RULE 407	4-2-1982	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 409	8-7-1981	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 431.2	5-4-1990	Federally enforceable
RULE 431.2	9-15-2000	Non federally enforceable
RULE 442	12-15-2000	Federally enforceable
RULE 461	4-6-2012	Non federally enforceable

**FACILITY PERMIT TO OPERATE
 U.S. GOVT, DEPT OF NAVY**

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 461	6-3-2005	Federally enforceable
RULE 462	5-14-1999	Federally enforceable
RULE 701	6-13-1997	Federally enforceable
40CFR 60 Subpart IIII	6-28-2011	Federally enforceable
40CFR 63SubpartBBBBBB	1-24-2011	Federally enforceable
40CFR 63SubpartCCCCC	1-24-2011	Federally enforceable
40CFR 63SubpartJJJJJ	3-21-2011	Federally enforceable
40CFR 63SubpartZZZZ	3-9-2011	Federally enforceable
40CFR 82 Subpart B	7-14-1992	Federally enforceable
40CFR 82 Subpart F	5-14-1993	Federally enforceable

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1106 01-13-1995]

Except as otherwise provided in Rule 1106, the operator shall not apply a marine coating with a VOC content in excess of the following limits, expressed as grams of VOC per liter of coating as applied, less water and less exempt solvents:

<u>COATING</u>	<u>VOC LIMIT</u>	
	<u>Baked</u>	<u>Air Dried</u>
General Coating	275 g/L	340 g/L
Specialty Coating		
Heat Resistant	360	420
Metallic Heat Resistant		530
High Temperature		500
Pre-Treatment Wash Primer	780	780
Underwater Weapons Systems	275	340
Elastomeric Adhesives with 15%, by Weight, Natural or Synthetic Rubber		730
Solvent-Based Inorganic Zinc		650
Navigational Aids		340
Sealant for Wire-Sprayed Aluminum		610
Special Marking		490
Tack Coat		610
Low Activation Interior Coating		420
Repair and Maintenance Thermoplastic		550
Extreme High-Gloss Coating	420	490
Antenna Coating		530
Antifoulant		400
High Gloss	275	340

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS								
Less Water and Less Exempt Compounds								
Effective Dates								
Coating	Air-Dried				Baked			
	gm/l		lb/gal		gm/l		lb/gal	
	Current	7/1/07	Current	7/1/07	Current	7/1/07	Current	7/1/07
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

VOC LIMITS								
Less Water and Less Exempt Compounds								
Effective Dates, cont.								
Coating	Air-Dried				Baked			
	gm/l		lb/gal		gm/l		lb/gal	
	Current	7/1/07	Current	7/1/07	Current	7/1/07	Current	7/1/07
Extreme Performance	420	420	3.5	3.5	360	360	3.0	3.0
Prefabricated Architectural One-Component	420	275	3.5	2.3	275	275	2.3	2.3
Prefabricated Architectural Multi-Component	420	340	3.5	2.8	275	275	2.3	2.3
Touch Up	420	420	3.5	3.5	360	360	3.0	3.0
Repair	420	420	3.5	3.5	360	360	3.0	3.0
Silicone Release	420	420	3.5	3.5	420	420	3.5	3.5
High-Performance Architectural	420	420	3.5	3.5	420	420	3.5	3.5
Camouflage	420	420	3.5	3.5	420	420	3.5	3.5
Vacuum-Metalizing	420	420	3.5	3.5	420	420	3.5	3.5
Mold-Seal	420	420	3.5	3.5	420	420	3.5	3.5
High-Temperature	420	420	3.5	3.5	420	420	3.5	3.5
Electric-Insulating Varnish	420	420	3.5	3.5	420	420	3.5	3.5
Pan Backing	420	420	3.5	3.5	420	420	3.5	3.5
Pretreatment Coatings	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

- (2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

- (1) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6) of Rule 1113, no person shall supply, sell, offer for sale, market, manufacture, blend, repackage, apply, store at a worksite, or solicit the application of any architectural coating within the District:
 - (A) That is listed in the Table of Standards 1 and contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified; or
 - (B) That is not listed in the Table of Standards 1, and contains VOC (excluding any colorant added to tint bases) in excess of 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, until January 1, 2014, at which time the limit drops to 50 grams of VOC per liter of coating, less water, less exempt compounds (0.42 pounds per gallon).
- (2) No person within the District shall add colorant at the point of sale that is listed in the Table of Standards 2 and contains VOC in excess of the corresponding VOC limit specified in the Table of Standards 2, after the effective date specified.

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

TABLE OF STANDARDS 1 VOC LIMITS

**Grams of VOC Per Liter of Coating,
Less Water and Less Exempt Compounds**

COATING CATEGORY	Ceiling Limit ¹	Current Limit ²	Effective Date		
			7/1/08	1/1/12	1/1/14
Bond Breakers		350			
Clear Wood Finishes		275			
Varnish	350	275			
Sanding Sealers	350	275			
Lacquer		275			
Concrete-Curing Compounds		100			
Concrete-Curing Compounds For Roadways and Bridges ³		350			
Concrete Surface Retarder		250			50
Driveway Sealer		100		50	
Dry-Fog Coatings		150			50
Faux Finishing Coatings					
Clear Topcoat		350		200	
Decorative Coatings		350			100
Glazes		350			
Japan		350			
Trowel Applied Coatings		350		150	50
Fire-Proofing Coatings		350			150
Flats	250	50	50		
Floor Coatings	100	50			
Form Release Compound		250			100
Graphic Arts (Sign) Coatings		500			150
Industrial Maintenance (IM) Coatings	420	100			
High Temperature IM Coatings		420			
Non-Sacrificial Anti-Graffiti Coatings		100			
Zinc-Rich IM Primers	340	100			
Magnesite Cement Coatings		450			
Mastic Coatings		300			100
Metallic Pigmented Coatings	500	500			150
Multi-Color Coatings		250			
Nonflat Coatings	150	50			
Pre-Treatment Wash Primers		420			
Primers, Sealers, and Undercoaters	200	100			
Reactive Penetrating Sealers		350			
Recycled Coatings		250			
Roof Coatings	250	50			
Roof Coatings, Aluminum		100			

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

Roof Primers, Bituminous	350	350		
Rust Preventative Coatings	400	100		
Stone Consolidant		450		
Sacrificial Anti-Graffiti Coatings		100		50
Shellac				
Clear		730		
Pigmented		550		
Specialty Primers	350	100		
Stains		100		

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

COATING CATEGORY	Ceiling Limit ¹	Current Limit ²	Effective Date		
			7/1/08	1/1/12	1/1/14
Stains, Interior	250	250			
Swimming Pool Coatings					
Repair		340			
Other		340			
Traffic Coatings		100			
Waterproofing Sealers	250	100			
Waterproofing Concrete/Masonry Sealers	400	100			
Wood Preservatives		350			

1. The specified ceiling limits are applicable to products sold under the Averaging Compliance Option.
2. The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.
3. Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

TABLE OF STANDARDS 1 (cont.) VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

TABLE OF STANDARDS 2 VOC LIMITS FOR COLORANTS

Grams of VOC Per Liter of Colorant Less Water and Less Exempt Compounds

COLORANT	Limit ⁴
Architectural Coatings, excluding IM Coatings	50
Solvent-Based IM	600
Waterborne IM	50

4. Effective January 1, 2014.

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007]

- (1) Except as provided in paragraphs (c)(2), (c)(3), (c)(4), and specified coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage any architectural coating for use in the District which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, and no person shall apply or solicit the application of any architectural coating within the District that exceeds 250 grams of VOC per liter of coating as calculated in this paragraph.
- (2) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified, and no person shall apply or solicit the application of any architectural coating within the District that exceeds the VOC limit as specified in this paragraph. No person shall apply or solicit the application within the District of any industrial maintenance coatings, except anti-graffiti coatings, for residential use or for use in areas such as office space and meeting rooms of industrial, commercial or institutional facilities not exposed to such extreme environmental conditions described in the definition of industrial maintenance coatings; or of any rust-preventative coating for industrial use, unless such a rust preventative coating complies with the Industrial Maintenance Coating VOC limit specified in the Table of Standards.

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007] TABLE OF STANDARDS VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water and Less Exempt Compounds

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Bond Breakers	350							
Clear Wood Finishes	350					275		
Varnish	350					275		
Sanding Sealers	350					275		
Lacquer	680	550			275			
Clear Brushing Lacquer	680				275			
Concrete-Curing Compounds	350						100	
Concrete-Curing Compounds For Roadways and Bridges**	350							
Dry-Fog Coatings	400						150	
Fire-Proofing Exterior Coatings	450	350						
Fire-Retardant Coatings***								
Clear	650							
Pigmented	350							
Flats	250	100						50
Floor Coatings	420		100			50		
Graphic Arts (Sign) Coatings	500							
Industrial Maintenance (IM) Coatings	420			250		100		
High Temperature IM Coatings			420					
Zinc-Rich IM Primers	420		340			100		
Japans/Faux Finishing Coatings	700	350						
Magnesite Cement Coatings	600	450						
Mastic Coatings	300							
Metallic Pigmented Coatings	500							
Multi-Color Coatings	420	250						
Nonflat Coatings	250		150			50		

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007]

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Nonflat High Gloss	250		150				50	
Pigmented Lacquer	680	550			275			
Pre-Treatment Wash Primers	780		420					
Primers, Sealers, and Undercoaters	350		200			100		
Quick-Dry Enamels	400		250			150	50	
Quick-Dry Primers, Sealers, and Undercoaters	350		200			100		
Recycled Coatings			250					
Roof Coatings	300		250		50			
Roof Coatings, Aluminum	500				100			
Roof Primers, Bituminous	350		350					
Rust Preventative Coatings	420		400			100		
Shellac								
Clear	730							
Pigmented	550							
Specialty Primers	350					250	100	
Stains	350		250				100	
Stains, Interior	250							
Swimming Pool Coatings								
Repair	650		340					
Other	340							
Traffic Coatings	250	150					100	
Waterproofing Sealers	400		250			100		
Waterproofing	400					100		
Concrete/Masonry Sealers								
Wood Preservatives								
Below-Ground	350							
Other	350							

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.

** Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

*** The Fire-Retardant Coating category will be eliminated on January 1, 2007 and subsumed by the coating category for which they are formulated.

**FACILITY PERMIT TO OPERATE
U.S. GOVT. DEPT OF NAVY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 07-13-2007]**

**TABLE OF STANDARDS (cont.)
VOC LIMITS**

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1140 02-01-1980]

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).
- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1140 08-02-1985]

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).
- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1162 11-17-2000]

The operator shall not use a polyester resin material in a polyester resin operation which has a monomer content in excess of the limits specified in the Table below.

Polyester Resin Materials	Monomer Content in Polyester Resin Materials as Applied (By Weight Percent)
General Purpose Polyester Resin	35
Corrosion-Resistant	48
Fire Retardant	42
High Strength	48
Clear Gel Coat	50
Pigmented Gel Coat	45

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1162 07-08-2005]

The operator shall not use polyester resin material in an open molding system, which has a monomer content in excess of the limits specified in the following Table.

Polyester Resin Materials	Monomer Percentage by Weight as Applied	
	Prior to 11-09-2001	Current Limits
Clear Gel Coat	50	-
For Marble Resins	-	40
For Other Resins	-	44
Pigmented Gel Coat	45	-
White and Off White	-	30
Non-White	-	37
Primer	-	28
Specialty Gel Coats	-	48
General Purpose Resin	35	-
Marble Resins	-	10 or (32 % as supplied, no fillers) 17
Solid Surface Resins	-	24 or
Tub/Shower Resins	-	(35 % as supplied, no fillers)
Lamination Resins	-	31 or (35 % as supplied, no fillers) 35
Others	-	
Fire Retardant Resin	42	38
Corrosion Resistant Resin	48	48
High Strength Resin	48	40

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		
(iii) Medical Devices & Pharmaceuticals	800 (6.7)		
(B) Repair and Maintenance Cleaning			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals			
(A) Tools, Equipment, & Machinery	800 (6.7)		
(B) General Work Surfaces	600 (5.0)		
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)		
(D) Cleaning of Ink Application Equipment			
(i) General	25 (0.21)		
(ii) Flexographic Printing	25 (0.21)		
(iii) Gravure Printing			
(A) Publication	100 (0.83)		
(B) Packaging	25 (0.21)		
(iv) Lithographic (Offset) or Letter Press Printing			
(A) Roller Wash, Blanket Wash, & On-Press Components			
(I) Newsprint	100 (0.83)		

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(II) Other Substrates	500 (4.2)	100 (0.83)	
(B) Removable Press Components	25 (0.21)		
(v) Screen Printing	500 (4.2)	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)		
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)		

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals	800 (6.7)	
(B) Repair and Maintenance Cleaning		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals		
(A) Tools, Equipment, & Machinery	800 (6.7)	
(B) General Work Surfaces	600 (5.0)	
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)	
(D) Cleaning of Ink Application Equipment		
(i) General	25 (0.21)	
(ii) Flexographic Printing	25 (0.21)	
(iii) Gravure Printing		
(A) Publication	100 (0.83)	
(B) Packaging	25 (0.21)	
(iv) Lithographic (Offset) or Letter Press Printing		
(A) Roller Wash, Blanket Wash, & On-Press Components	100 (0.83)	

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(B) Removable Press Components	25 (0.21)	
(v) Screen Printing	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)	
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)	

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter” Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter” Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 405 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process	
		Kilograms Per Hour	Pounds Per Hour			Kilograms Per Hour	Pounds Per Hour
100 or less	220 or less	0.450	0.99	9000	19840	5.308	11.7
150	331	0.585	1.29	10000	22050	5.440	12.0
200	441	0.703	1.55	12500	27560	5.732	12.6
250	551	0.804	1.77	15000	33070	5.982	13.2
300	661	0.897	1.98	17500	38580	6.202	13.7
350	772	0.983	2.17	20000	44090	6.399	14.1
400	882	1.063	2.34	25000	55120	6.743	14.9
450	992	1.138	2.51	30000	66140	7.037	15.5
500	1102	1.209	2.67	35000	77160	7.296	16.1
600	1323	1.340	2.95	40000	88180	7.527	16.6

FACILITY PERMIT TO OPERATE U.S. GOVT. DEPT OF NAVY

APPENDIX B: RULE EMISSION LIMITS [RULE 405 02-07-1986]

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
700	1543	1.461	3.22	45000	99210	7.738	17.1
800	1764	1.573	3.47	50000	110200	7.931	17.5
900	1984	1.678	3.70	60000	132300	8.277	18.2
1000	2205	1.777	3.92	70000	154300	8.582	18.9
1250	2756	2.003	4.42	80000	176400	8.854	19.5
1500	3307	2.206	4.86	90000	198400	9.102	20.1
1750	3858	2.392	5.27	100000	220500	9.329	20.6
2000	4409	2.563	5.65	125000	275600	9.830	21.7
2250	4960	2.723	6.00	150000	330700	10.26	22.6
2500	5512	2.874	6.34	175000	385800	10.64	23.5
2750	6063	3.016	6.65	200000	440900	10.97	24.2
3000	6614	3.151	6.95	225000	496000	11.28	24.9
3250	7165	3.280	7.23	250000	551200	11.56	25.5
3600	7716	3.404	7.50	275000	606300	11.82	26.1
4000	8818	3.637	8.02	300000	661400	12.07	26.6
4500	9921	3.855	8.50	325000	716500	12.30	27.1
5000	11020	4.059	8.95	350000	771600	12.51	27.6
6000	13230	4.434	9.78	400000	881800	12.91	28.5
7000	15430	4.775	10.5	450000	992100	13.27	29.3
8000	17640	5.089	11.2	500000 or more	1102000 or more	13.60	30.0