

FACILITY PERMIT TO OPERATE

**FRITO-LAY, INC.
9535 ARCHIBALD AVE
RANCHO CUCAMONGA, CA 91730**

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By _____
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	DRAFT	03/08/2013
B	RECLAIM Annual Emission Allocation	DRAFT	03/08/2013
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	DRAFT	03/08/2013
E	Administrative Conditions	DRAFT	03/08/2013
F	RECLAIM Monitoring and Source Testing Requirements	DRAFT	03/08/2013
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	DRAFT	03/08/2013
H	Permit To Construct and Temporary Permit to Operate	DRAFT	03/08/2013
I	Compliance Plans & Schedules	DRAFT	03/08/2013
J	Air Toxics	DRAFT	03/08/2013
K	Title V Administration	DRAFT	03/08/2013
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	DRAFT	03/08/2013
B	Rule Emission Limits	DRAFT	03/08/2013

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

SECTION A: FACILITY INFORMATION

LEGAL OWNER &/OR OPERATOR: FRITO-LAY, INC.

LEGAL OPERATOR (if different than owner):

EQUIPMENT LOCATION: 9535 ARCHIBALD AVE
 RANCHO CUCAMONGA, CA 91730-5737

MAILING ADDRESS: 9535 ARCHIBALD AVE
 RANCHO CUCAMONGA, CA 91730-5737

RESPONSIBLE OFFICIAL: ROBERT BIACSI

TITLE: DIRECTOR, MAINTENANCE AND
 ENGINEERING

TELEPHONE NUMBER: (661) 328-6010

CONTACT PERSON: ROBERT (BOB) BIACSI

TITLE: DIRECTOR, MAINTENANCE AND
 ENGINEERING

TELEPHONE NUMBER: (909) 941-6203

TITLE V PERMIT ISSUED: March 25, 2008

TITLE V PERMIT EXPIRATION DATE: March 24, 2013

TITLE V	RECLAIM
YES	NOx: YES SOx: NO CYCLE: 1 ZONE: INLAND

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

The annual allocation of NOx RECLAIM Trading Credits (RTCs) for this facility is calculated pursuant to Rule 2002. Total NOx emission shall not exceed such annual allocations unless the operator obtains RTCs corresponding to the facility's increased emissions in compliance with Rules 2005 and 2007.

The level of Starting Allocation plus Non-Tradable Credits used to determine compliance with Rule 2005(c)(4) and applicability of Rule 2005(e) - Trading Zone Restrictions is listed on the last page of this Section.

The following table lists the annual allocations that were issued to this facility and the amounts of RTCs held by this facility on the day of printing this Section.

RECLAIM POLLUTANT ANNUAL ALLOCATION (POUNDS)

Year Begin End (month/year)	Zone	NOx RTC Initially Allocated	NOx RTC ¹ Holding as of 01/01/2013 (pounds)	Non-Tradable ² Non-Usable RTCs (pounds)
1/2011 12/2011	Coastal	0	9981	2856
1/2011 12/2011	Inland	12877	0	1391
1/2012 12/2012	Coastal	0	20493	2856
1/2012 12/2012	Inland	12877	9980	1391
1/2013 12/2013	Coastal	0	20493	2856
1/2013 12/2013	Inland	12877	9980	1391
1/2014 12/2014	Coastal	0	20493	2856
1/2014 12/2014	Inland	12877	9980	1391
1/2015 12/2015	Coastal	0	20493	2856
1/2015 12/2015	Inland	12877	9980	1391
1/2016 12/2016	Coastal	0	20493	2856
1/2016 12/2016	Inland	12877	9980	1391
1/2017 12/2017	Coastal	0	20493	2856
1/2017 12/2017	Inland	12877	9980	1391
1/2018 12/2018	Coastal	0	20493	2856
1/2018 12/2018	Inland	12877	9980	1391
1/2019 12/2019	Coastal	0	20493	2856

Footnotes:

1. This number may change due to pending trades, emissions reported under Quarterly Certification of Emissions Report (QCER) and Annual Permit Emission Program (APEP) Report required pursuant to Rule 2004, or deductions made pursuant to Rule 2010(b). The most recent total RTC information can be obtained from the District's RTC Listing.
2. The use of such credits is subject to restrictions set forth in paragraph (f)(1) of Rule 2002.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

The annual allocation of NOx RECLAIM Trading Credits (RTCs) for this facility is calculated pursuant to Rule 2002. Total NOx emission shall not exceed such annual allocations unless the operator obtains RTCs corresponding to the facility's increased emissions in compliance with Rules 2005 and 2007.

The level of Starting Allocation plus Non-Tradable Credits used to determine compliance with Rule 2005(c)(4) and applicability of Rule 2005(e) - Trading Zone Restrictions is listed on the last page of this Section.

The following table lists the annual allocations that were issued to this facility and the amounts of RTCs held by this facility on the day of printing this Section.

RECLAIM POLLUTANT ANNUAL ALLOCATION (POUNDS)

Year Begin End (month/year)	Zone	NOx RTC Initially Allocated	NOx RTC ¹ Holding as of 01/01/2013 (pounds)	Non-Tradable ² Non-Usable RTCs (pounds)
1/2019 12/2019	Inland	12877	9980	1391
1/2020 12/2020	Coastal	0	20493	2856
1/2020 12/2020	Inland	12877	9980	1391
1/2021 12/2021	Coastal	0	20493	2856
1/2021 12/2021	Inland	12877	9980	1391
1/2022 12/2022	Coastal	0	20493	2856
1/2022 12/2022	Inland	12877	9980	1391
1/2023 12/2023	Coastal	0	20493	2856
1/2023 12/2023	Inland	12877	9980	1391
1/2024 12/2024	Coastal	0	20493	2856
1/2024 12/2024	Inland	12877	9980	1391
1/2025 12/2025	Coastal	0	20493	2856
1/2025 12/2025	Inland	12877	9980	1391
1/2026 12/2026	Coastal	0	20493	2856
1/2026 12/2026	Inland	12877	9980	1391
1/2027 12/2027	Coastal	0	20493	2856
1/2027 12/2027	Inland	12877	9980	1391

Footnotes:

1. This number may change due to pending trades, emissions reported under Quarterly Certification of Emissions Report (QCER) and Annual Permit Emission Program (APEP) Report required pursuant to Rule 2004, or deductions made pursuant to Rule 2010(b). The most recent total RTC information can be obtained from the District's RTC Listing.
2. The use of such credits is subject to restrictions set forth in paragraph (f)(1) of Rule 2002.

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

The annual allocation of NOx RECLAIM Trading Credits (RTCs) for this facility is calculated pursuant to Rule 2002. Total NOx emission shall not exceed such annual allocations unless the operator obtains RTCs corresponding to the facility's increased emissions in compliance with Rules 2005 and 2007.

The level of Starting Allocation plus Non-Tradable Credits used to determine compliance with Rule 2005(c)(4) and applicability of Rule 2005(e) - Trading Zone Restrictions is listed on the last page of this Section.

The following table lists the annual allocations that were issued to this facility and the amounts of RTCs held by this facility on the day of printing this Section.

RECLAIM POLLUTANT ANNUAL ALLOCATION (POUNDS)

Year Begin End (month/year)	Zone	NOx RTC Initially Allocated	NOx RTC ¹ Holding as of 01/01/2013 (pounds)	Non-Tradable ² Non-Usable RTCs (pounds)
1/2028 12/2028	Coastal	0	20493	2856
1/2028 12/2028	Inland	12877	9980	1391

Footnotes:

1. This number may change due to pending trades, emissions reported under Quarterly Certification of Emissions Report (QCER) and Annual Permit Emission Program (APEP) Report required pursuant to Rule 2004, or deductions made pursuant to Rule 2010(b). The most recent total RTC information can be obtained from the District's RTC Listing.
2. The use of such credits is subject to restrictions set forth in paragraph (f)(1) of Rule 2002.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

The annual allocation of RECLAIM Trading Credits (RTCs) for this facility is calculated pursuant to Rule 2002. If the facility submits a permit application to increase in an annual allocation to a level greater than the facility's starting Allocation plus Non-Tradable credits as listed below, the application will be evaluated for compliance with Rule 2005(c)(4). Rule 2005(e) - Trading Zone Restrictions applies if an annual allocation is increased to a level greater than the facility's Starting Allocation plus Non-Tradable Credits:

Year		Zone	NOx RTC	Non-Tradable
Begin	End		Starting Allocation	Credits(NTC)
(month/year)			(pounds)	(pounds)
1/1994	12/1994	Inland	26573	0

**FACILITY PERMIT TO OPERATE
FRITO-LAY, INC.**

SECTION C: FACILITY PLOT PLAN

(TO BE DEVELOPED)

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: SNACK FOOD PRODUCTION					
System 1: CORN RECEIVING AND STORAGE					S1.2
STORAGE SILO, SHELLED DRIED CORN, 93136 GALLON CAPACITY A/N: 332104	D1			PM: (9) [RULE 405, 2-7-1986]	A63.2, D323.2
STORAGE SILO, SHELLED DRIED CORN, 93136 GALLON CAPACITY A/N: 332104	D2	C8		PM: (9) [RULE 405, 2-7-1986]	D323.2
CONVEYOR, BELT, SHELLED DRIED CORN TRANSFER A/N: 332104	D3			PM: (9) [RULE 405, 2-7-1986]	D323.2
BUCKET ELEVATOR, SHELLED DRIED CORN TRANSFER A/N: 332104	D4			PM: (9) [RULE 405, 2-7-1986]	D323.2
STORAGE SILO, SHELLED DRIED CORN, 93136 GALLON CAPACITY A/N: 332118	D5	C9		PM: (9) [RULE 405, 2-7-1986]	D323.2
CONVEYOR, BELT, SHELL DRIED CORN TRANSFER A/N: 332118	D6			PM: (9) [RULE 405, 2-7-1986]	D323.2
BUCKET ELEVATOR, SHELLED DRIED CORN A/N: 332118	D7			PM: (9) [RULE 405, 2-7-1986], VOC: 2 GRAINS/SCF (3)	D323.2
CYCLONE A/N: 332113	C8	D2		PM: (9) [RULE 404, 2-7-1986]	D323.1
CYCLONE A/N: 332109	C9	D5		PM: (9) [RULE 404, 2-7-1986]	D323.1
System 2: CORN MEAL RECEIVING AND STORAGE					S1.3
CONVEYOR, PNEUMATIC, RAILCAR UNLOADING A/N: 332117	D10			PM: (9) [RULE 405, 2-7-1986]	D323.2

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (3) Denotes RECLAIM concentration limit
- (4) Denotes BACT emission limit
- (5) (5A) (5B) Denotes command and control emission limit
- (6) Denotes air toxic control rule limit
- (7) Denotes NSR applicability limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (9) See App B for Emission Limits
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: SNACK FOOD PRODUCTION					
STORAGE SILO, CORN MEAL, 37400 GALLON CAPACITY, HEIGHT: 60 FT ; DIAMETER: 12 FT A/N: 332117	D11	C13		PM: (9) [RULE 405, 2-7-1986]	D323.2
STORAGE SILO, CORN MEAL, 37400 GALLON CAPACITY, HEIGHT: 60 FT ; DIAMETER: 12 FT A/N: 332117	D12	C14		PM: (9) [RULE 405, 2-7-1986]	D323.2
BAGHOUSE, MODEL 58AJ-16, 117 SQ.FT. A/N: 332117	C13	D11		PM: (9) [RULE 404, 2-7-1986]	D12.1, D322.1, D381.1, E102.1, K67.1
BAGHOUSE, MODEL 58AJ-16, 117 SQ.FT A/N: 332117	C14	D12		PM: (9) [RULE 404, 2-7-1986]	D12.1, D322.1, D381.1, E102.1, K67.1
System 3: CORN TRANSFER AND CLEANING					S1.4
CONVEYOR, DRAG, CORN TRANSFER A/N: 387955	D15			PM: (9) [RULE 405, 2-7-1986]	D323.2
CONVEYOR, DRAG, CORN TRANSFER A/N: 387955	D16			PM: (9) [RULE 405, 2-7-1986]	D323.2
CONVEYOR, DRAG, CORN TRANSFER A/N: 387955	D17			PM: (9) [RULE 405, 2-7-1986]	D323.2
CONVEYOR, DRAG, CORN TRANSFER A/N: 387955	D18			PM: (9) [RULE 405, 2-7-1986]	D323.2
HOPPER, SURGE, CORN, 1 TONS A/N: 387955	D19			PM: (9) [RULE 405, 2-7-1986]	D323.2
CONVEYOR, PNEUMATIC, CORN A/N: 387955	D112				

* (1) (1A) (1B) Denotes RECLAIM emission factor (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: SNACK FOOD PRODUCTION					
BIN, SURGE, MAC WORK BIN MODEL SX3 A/N: 387955	D103	C111		PM: (9) [RULE 405, 2-7-1986]	D323.2
CLEANER, CARTER-DAY MODULAR PRECISION SIZER AND ASPIRATOR A/N: 387955	D110	C111		PM: (9) [RULE 405, 2-7-1986]	D323.2
CONVEYOR, PNEUMATIC, CORN A/N: 387955	D113				
STORAGE SILO, CORN RECEIVER MODEL CT17 A/N: 387955	D106	C111		PM: (9) [RULE 405, 2-7-1986]	D323.2
STORAGE SILO, TWO COMPARTMENT CLEAN CORN TANK A/N: 387955	D104	C111		PM: (9) [RULE 405, 2-7-1986]	D323.2
VESSEL, DENSE PHASE CONVEYING VESSEL MODEL 55CF72SV12 A/N: 387955	D105	C111		PM: (9) [RULE 405, 2-7-1986]	D323.2
CONVEYOR, PNEUMATIC, CORN A/N: 387955	D114				
STORAGE SILO, CORN RECEIVER MODEL CT17 A/N: 387955	D107	C111		PM: (9) [RULE 405, 2-7-1986]	D323.2
STORAGE SILO, CORN RECEIVER MODEL CT17 A/N: 387955	D108	C111		PM: (9) [RULE 405, 2-7-1986]	D323.2
STORAGE SILO, CORN RECEIVER MODEL CT17 A/N: 387955	D109	C111		PM: (9) [RULE 405, 2-7-1986]	D323.2

- (1) (1A) (1B) Denotes RECLAIM emission factor
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (3) Denotes RECLAIM concentration limit
- (4) Denotes BACT emission limit
- (5) (5A) (5B) Denotes command and control emission limit
- (6) Denotes air toxic control rule limit
- (7) Denotes NSR applicability limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (9) See App B for Emission Limits
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: SNACK FOOD PRODUCTION					
BAGHOUSE, MACTIFLO CARTRIDGE FILTER, MODEL 2MTF8, 2360 SQ. FT. A/N: 384771	C111	D103 D104 D105 D106 D107 D108 D109 D110		PM: (9) [RULE 404, 2-7-1986]	C6.3, D12.7, D322.1, D381.1, E102.1, K67.1
System 4: CORN CHIP LINE					
FRYER, AC HORN, NATURAL GAS, TORTILLA CHIP, 3.9 MMBTU/HR A/N: 500033	D65	C167	NOX: PROCESS UNIT**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	C1.3, C6.1, D323.1
MIST ELIMINATOR, HEAT AND CONTROL, 20" DIA A/N: 522959	C167	D65 C154		PM: (9) [RULE 404, 2-7-1986]	
COOLER, PANEL FILTER, TORTILLA CHIP A/N: 500033	D67			PM: (9) [RULE 404, 2-7-1986]	
OXIDIZER, REGENERATIVE THERMAL, ADWEST TECHNOLOGIES, MODEL NO. RETOX 1.5 RTO95, 22 FT. 3/4 IN. L. X 7 FT. 11 IN. W. X 10 FT H. WITH A/N: 522959	C153	C154	NOX: PROCESS UNIT**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 30 PPMV NATURAL GAS (4) [RULE 2005, 6-3-2011]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	A433.1, C8.3, D182.1, D323.1
BURNER, LOW NOX, NATURAL GAS, MAXON, MODEL KINEDIZER, 1 TOTAL; 0.433 MMBTU/HR	D155				
INJECTOR, .225 MMBTU/HR, NATURAL GAS	D156				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: SNACK FOOD PRODUCTION					
FILTER, PRE-FILTER, 3.9 SQ. FEET SURFACE AREA, 304 STAINLESS STEEL A/N: 522959	C154	C153 C167		PM: (9) [RULE 404, 2-7-1986]	
System 5: TORTILLA CHIP LINE NO. A1					
FRYER, # 1, NATURAL GAS, TORTILLA CHIP, 3 MMBTU/HR A/N: 11668B	D31		NOX: PROCESS UNIT**	CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	D323.1
FRYER, # 2, NATURAL GAS, TORTILLA CHIP, 3 MMBTU/HR A/N: 11669B	D29		NOX: PROCESS UNIT**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	D323.1
OVEN, DRYING, NATURAL GAS, 4.77 MMBTU/HR A/N: 484103	D85		NOX: PROCESS UNIT**	CO 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982]; NOX: 64 PPMV NATURAL GAS (4) [RULE 2005, 6-3-2011]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	D28.7, D323.2

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: SNACK FOOD PRODUCTION					
OVEN, DRYING, NATURAL GAS, 4.77 MMBTU/HR A/N: 484104	D86		NOX: PROCESS UNIT**	CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982], NOX: 64 PPMV NATURAL GAS (4) [RULE 2005, 6-3-2011]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	D28.7, D323.2
System 6: TORTILLA CHIP LINE NO. B1					S16
FRYER, #1 DTC/DIP, NATURAL GAS, TORTILLA CHIP, 4 MMBTU/HR A/N: 484101	D36		NOX: PROCESS UNIT**	CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	D323.1
OVEN, BAKING, CASA HERRERA, MACH4XW, NATURAL GAS, 4.77 MMBTU/HR A/N: 484101	D79		NOX: PROCESS UNIT**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	D323.2, E73.1
COOLER, WITH MAT OR PANEL FILTER A/N: 484101	D70			PM: (9) [RULE 404, 2-7-1986]	
System 7: TORTILLA CHIP LINE NO. B2					

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: SNACK FOOD PRODUCTION					
FRYER, #2 DTC/DIP, NATURAL GAS, 4 MMBTU/HR A/N: 484102	D32		NOX: PROCESS UNIT**	CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982]. NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	D323.1
OVEN, BAKING, CASA HERRERA, MACH4XW, NATURAL GAS, 4.77 MMBTU/HR A/N: 484102	D80		NOX: PROCESS UNIT**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	D323.2, E73.1
System 8: FRIED CHEESE PUFF LINE					
FRYER, NATURAL GAS, CHEETOS FRIED, 0.6 MMBTU/HR A/N: 282575	D40		NOX: PROCESS UNIT**	CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982]. NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	D323.1
SEASONING TUMBLER, FRIED CHEETOS LINE A/N: 02501E	D41			PM: (9) [RULE 405, 2-7-1986]	D323.2
System 9: BAKED CHEESE PUFF LINE					

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 - (3) Denotes RECLAIM concentration limit
 - (5) (5A) (5B) Denotes command and control emission limit
 - (7) Denotes NSR applicability limit
 - (9) See App B for Emission Limits
 - (2) (2A) (2B) Denotes RECLAIM emission rate
 - (4) Denotes BACT emission limit
 - (6) Denotes air toxic control rule limit
 - (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 - (10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: SNACK FOOD PRODUCTION					
OVEN, BAKING, NATURAL GAS, PROPANE, CHESSE PUFF LINE, 1.2 MMBTU/HR A/N: 229787	D42		NOX: PROCESS UNIT**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 12.8 LBS/1000 GAL PROPANE (1) [RULE 2012, 5-6-2005]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	D323.2
SEASONING TUMBLER A/N: 229787	D44			PM: (9) [RULE 405, 2-7-1986]	D323.2
System 11: FRIED CHEESE PUFF LINE #2					
FRYER, NATURAL GAS, WIDTH: 3 FT; LENGTH: 9 FT 6 IN; HEIGHT: 3 FT; 0.8 MMBTU/HR A/N: 282575	D59		NOX: PROCESS UNIT**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	A63.2, C6.2, D12.3, D323.1
System 12: EXTRUDED SNACK FOOD LINE					
FRYER, HEAT & CONTROL, CC 1.5, NATURAL GAS, 2 MMBTU/HR WITH A/N: 455361 BURNER, HEAT EXCHANGER/ POLLUTION CONTROL, NATURAL GAS, HEAT AND CONTROL, MODEL KHX-0.85, 2 MMBTU/HR	D68		NOX: PROCESS UNIT**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981] NOX: 12.8 LBS/1000 GAL PROPANE (1) [RULE 2012, 5-6-2005]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]	C6.1, C8.1, D12.3, D323.1
SCREEN, AZO, CORNMEAL, MODEL NO. E 650 A/N: 494156	D151	D121		PM: (9) [RULE 405, 2-7-1986]	D323.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: SNACK FOOD PRODUCTION					
HOPPER, WEIGH, CORN MEAL A/N: 494156	D121	D122 D151		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, RECEIVING, CORN MEAL A/N: 494156	D122	D121 D128		PM: (9) [RULE 405, 2-7-1986]	D323.1
BLENDER, CORN MEAL, 700 LBS CAPACITY A/N: 494156	D128	D122 D134		PM: (9) [RULE 405, 2-7-1986]	D323.1
BUCKET ELEVATOR, CORN MEAL A/N: 494156	D134	D128 D157 D158		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, TORPEDO, CORNMEAL A/N: 494156	D157	D134 D140		PM: (9) [RULE 405, 2-7-1986]	D323.1
EXTRUDER, CORN MEAL A/N: 494156	D140	D150 D157		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, TORPEDO, CORNMEAL A/N: 494156	D158	D134 D141		PM: (9) [RULE 405, 2-7-1986]	D323.1
EXTRUDER, CORN MEAL A/N: 494156	D141	D150 D158		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, RECEIVING, CORN MEAL A/N: 494158	D123	D129		PM: (9) [RULE 405, 2-7-1986]	D323.1
BLENDER, CORN MEAL, 700 LBS CAPACITY A/N: 494158	D129	D123 D135		PM: (9) [RULE 405, 2-7-1986]	D323.1
BUCKET ELEVATOR, CORN MEAL A/N: 494158	D135	D129 D159 D160		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, TORPEDO, CORNMEAL A/N: 494158	D159	D135 D142		PM: (9) [RULE 405, 2-7-1986]	D323.1
EXTRUDER, CORN MEAL A/N: 494158	D142	D150 D159		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, TORPEDO, CORNMEAL A/N: 494158	D160	D135 D143		PM: (9) [RULE 405, 2-7-1986]	D323.1
EXTRUDER, CORN MEAL A/N: 494158	D143	D150 D160		PM: (9) [RULE 405, 2-7-1986]	D323.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: SNACK FOOD PRODUCTION					
HOPPER, RECEIVING, CORN MEAL A/N: 494159	D124	D130		PM: (9) [RULE 405, 2-7-1986]	D323.1
BLENDER, CORN MEAL, 700 LBS CAPACITY A/N: 494159	D130	D124 D136		PM: (9) [RULE 405, 2-7-1986]	D323.1
BUCKET ELEVATOR, CORN MEAL A/N: 494159	D136	D130 D161 D162		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, TORPEDO, CORNMEAL A/N: 494159	D161	D136 D144		PM: (9) [RULE 405, 2-7-1986]	D323.1
EXTRUDER, CORN MEAL A/N: 494159	D144	D150 D161		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, TORPEDO, CORNMEAL A/N: 494159	D162	D136 D145		PM: (9) [RULE 405, 2-7-1986]	D323.1
EXTRUDER, CORN MEAL A/N: 494159	D145	D150 D162		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, RECEIVING, CORN MEAL A/N: 494160	D125	D131		PM: (9) [RULE 405, 2-7-1986]	D323.1
BLENDER, CORN MEAL, 700 LBS CAPACITY A/N: 494160	D131	D125 D137		PM: (9) [RULE 405, 2-7-1986]	D323.1
BUCKET ELEVATOR, CORN MEAL A/N: 494160	D137	D131 D163 D164		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, TORPEDO, CORNMEAL A/N: 494160	D163	D137 D146		PM: (9) [RULE 405, 2-7-1986]	D323.1
EXTRUDER, CORN MEAL A/N: 494160	D146	D150 D163		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, TORPEDO, CORNMEAL A/N: 494160	D164	D137 D147		PM: (9) [RULE 405, 2-7-1986]	D323.1
EXTRUDER, CORN MEAL A/N: 494160	D147	D150 D164		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, RECEIVING, CORN MEAL A/N: 494161	D126	D132		PM: (9) [RULE 405, 2-7-1986]	D323.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: SNACK FOOD PRODUCTION					
BLENDER, CORN MEAL, 700 LBS CAPACITY A/N: 494161	D132	D126 D138		PM: (9) [RULE 405, 2-7-1986]	D323.1
BUCKET ELEVATOR, CORN MEAL A/N: 494161	D138	D132 D165		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, TORPEDO, CORNMEAL A/N: 494161	D165	D138 D148		PM: (9) [RULE 405, 2-7-1986]	D323.1
EXTRUDER, CORN MEAL A/N: 494161	D148	D150 D165		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, RECEIVING, CORN MEAL A/N: 494163	D127	D133		PM: (9) [RULE 405, 2-7-1986]	D323.1
BLENDER, CORN MEAL, 700 LBS CAPACITY A/N: 494163	D133	D127 D139		PM: (9) [RULE 405, 2-7-1986]	D323.1
BUCKET ELEVATOR, CORN MEAL A/N: 494163	D139	D133 D166		PM: (9) [RULE 405, 2-7-1986]	D323.1
HOPPER, TORPEDO, CORNMEAL A/N: 494163	D166	D139 D149		PM: (9) [RULE 405, 2-7-1986]	D323.1
EXTRUDER, CORN MEAL A/N: 494163	D149	D150 D166		PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, PNEUMATIC, CORN MEAL A/N: 494163	D150	D140 D141 D142 D143 D144 D145 D146 D147 D148 D149 D150		PM: (9) [RULE 405, 2-7-1986]	D323.1
System 13: CORNMEAL RECEIVING AND STORAGE					S1.7
CONVEYOR, PNEUMATIC, RAILCAR & TRUCK UNLOADING A/N: 454861	D72			PM: (9) [RULE 405, 2-7-1986]	D323.2

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: SNACK FOOD PRODUCTION					
STORAGE SILO, CORNMEAL, WITH A 108 SQ. FT. FILTER VENT, HEIGHT: 59 FT 2 IN; DIAMETER: 10 FT 11 IN A/N: 454861	D73			PM: (9) [RULE 404, 2-7-1986; RULE 405, 2-7-1986]	D381.1
STORAGE SILO, CORNMEAL, WITH A 108 SQ. FT. FILTER VENT, HEIGHT: 59 FT 2 IN; DIAMETER: 10 FT 11 IN A/N: 454861	D74			PM: (9) [RULE 404, 2-7-1986; RULE 405, 2-7-1986]	D381.1
System 14: CHEESE PUFF LINE #3					
MIXER, CORN MEAL, 120 GALS A/N: 371970	D87			PM: (9) [RULE 405, 2-7-1986]	D323.1
MIXER, CORN MEAL, 120 GALS A/N: 371970	D88			PM: (9) [RULE 405, 2-7-1986]	D323.1
EXTRUDER, NO. 1 A/N: 371970	D89	C98		PM: (9) [RULE 404, 2-7-1986]	D323.1
EXTRUDER, NO. 2 A/N: 371970	D90	C98		PM: (9) [RULE 404, 2-7-1986]	D323.1
EXTRUDER, NO. 3 A/N: 371970	D91	C98		PM: (9) [RULE 404, 2-7-1986]	D323.1
EXTRUDER, NO. 4 A/N: 371970	D92	C98		PM: (9) [RULE 404, 2-7-1986]	D323.1
EXTRUDER, NO. 5 A/N: 371970	D93	C98		PM: (9) [RULE 404, 2-7-1986]	D323.1
EXTRUDER, NO. 6 A/N: 371970	D94	C98		PM: (9) [RULE 404, 2-7-1986]	D323.1
SCREEN, ROTARY, CHAFF TUMBLER A/N: 499293	D116			PM: (9) [RULE 405, 2-7-1986]	D323.1
SCREEN, SHAKER TABLE A/N: 499293	D117			PM: (9) [RULE 405, 2-7-1986]	D323.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (3) Denotes RECLAIM concentration limit
- (4) Denotes BACT emission limit
- (5) (5A) (5B) Denotes command and control emission limit
- (6) Denotes air toxic control rule limit
- (7) Denotes NSR applicability limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (9) See App B for Emission Limits
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: SNACK FOOD PRODUCTION					
FRYER, HEAT & CONTROL, MODEL NO. PP-3610 WITH A/N: 499293 MIST ELIMINATOR BURNER, HEAT EXCHANGER/ POLLUTION CONTROL, INTEGRAL AFTERBURNER, NATURAL GAS. KLEENHEAT, 1 MMBTU/HR	D95		NOX PROCESS UNIT**	CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982], PM: (9) [RULE 404, 2-7-1986; RULE 405, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 404, 2-7-1986; RULE 409, 8-7-1981] NOX: 70 PPMV NATURAL GAS (3) [RULE 2012, 5-6-2005]	C6.1, C8.1, D12.3, D323.1, E17.1
OVEN, DRYING, MAXON, MODEL NO. CI 120-28 RGX (E), NATURAL GAS, BAKED CHEESE PUFF LINE WITH A/N: 499293 BURNER, LOW NOX, MAXON CYCLOMAX, NATURAL GAS. 1.6 MMBTU/HR	D118			CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982], PM 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981] CO: 75 PPMV NATURAL GAS (7) [RULE 1303, 5-10-1996; RULE 1303, 12-6-2002], NOX: 25 PPMV NATURAL GAS (3) [RULE 2012, 5-6-2005], NOX: 30 PPMV NATURAL GAS (4) [RULE 1303(a)-BACT, 5-10-1996; RULE 1303(a), 12-6-2002]	B59.1, D28.9, E17.1
COOLER, CHEETOS A/N: 499293	D96			PM: (9) [RULE 405, 2-7-1986]	D323.1
SEASONING TUMBLER A/N: 499293	D97			PM: (9) [RULE 405, 2-7-1986]	D323.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (3) Denotes RECLAIM concentration limit
- (4) Denotes BACT emission limit
- (5) (5A) (5B) Denotes command and control emission limit
- (6) Denotes air toxic control rule limit
- (7) Denotes NSR applicability limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (9) See App B for Emission Limits
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: SNACK FOOD PRODUCTION					
SCRUBBER, ROTOCLONE, AAF INTERNATIONAL, TYPE W A/N: 371971	C98	D89 D90 D91 D92 D93 D94		PM: (9) [RULE 404, 2-7-1986; RULE 405, 2-7-1986]	C8.2, D12.6, D323.1
Process 4: INTERNAL COMBUSTION EQUIPMENT					
INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, DIESEL FUEL, DETROIT DIESEL, MODEL DDFP-04AT, WITH TURBOCHARGER, 235 BHP A/N: 309749	D71		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]	C1.2, D12.2
Process 5: Rule 219 Equipment Subject to Source Specific Rules					
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS	E81			VOC: (9) [RULE 1113, 11-8-1996; RULE 1113, 6-3-2011; RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	K67.2
RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS	E82				H23.1
RULE 219 EXEMPT EQUIPMENT, ABRASIVE BLASTING EQUIPMENT, GLOVE-BOX, <= 53 FT3, WITH DUST FILTER	E83			PM: (9) [RULE 1140, 2-1-1980; RULE 1140, 8-2-1985; RULE 404, 2-7-1986; RULE 405, 2-7-1986]	D322.1, D381.1, E102.1, K67.1, M333.1
RULE 219 EXEMPT EQUIPMENT, FIRE EXTINGUISHING EQUIPMENT USING HALONS	E84				H23.2

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
FRITO-LAY, INC.**

SECTION D: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D1	1	1	1
D2	1	1	1
D3	1	1	1
D4	1	1	1
D5	1	1	1
D6	1	1	1
D7	1	1	1
C8	1	1	1
C9	1	1	1
D10	1	1	2
D11	2	1	2
D12	2	1	2
C13	2	1	2
C14	2	1	2
D15	2	1	3
D16	2	1	3
D17	2	1	3
D18	2	1	3
D19	2	1	3
D29	5	1	5
D31	5	1	5
D32	7	1	7
D36	6	1	6
D40	7	1	8
D41	7	1	8
D42	8	1	9
D44	8	1	9
D59	8	1	11
D65	4	1	4
D67	4	1	4
D68	8	1	12
D70	6	1	6
D71	14	4	0
D72	11	1	13
D73	12	1	13

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D74	12	1	13
D79	6	1	6
D80	7	1	7
E81	14	5	0
E82	14	5	0
E83	14	5	0
E84	14	5	0
D85	5	1	5
D86	6	1	5
D87	12	1	14
D88	12	1	14
D89	12	1	14
D90	12	1	14
D91	12	1	14
D92	12	1	14
D93	12	1	14
D94	12	1	14
D95	13	1	14
D96	13	1	14
D97	13	1	14
C98	14	1	14
D103	3	1	3
D104	3	1	3
D105	3	1	3
D106	3	1	3
D107	3	1	3
D108	3	1	3
D109	3	1	3
D110	3	1	3
C111	4	1	3
D112	2	1	3
D113	3	1	3
D114	3	1	3
D116	12	1	14
D117	12	1	14

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D118	13	1	14
D121	9	1	12
D122	9	1	12
D123	9	1	12
D124	10	1	12
D125	10	1	12
D126	10	1	12
D127	11	1	12
D128	9	1	12
D129	9	1	12
D130	10	1	12
D131	10	1	12
D132	11	1	12
D133	11	1	12
D134	9	1	12
D135	9	1	12
D136	10	1	12
D137	10	1	12
D138	11	1	12
D139	11	1	12
D140	9	1	12
D141	9	1	12
D142	9	1	12
D143	9	1	12
D144	10	1	12
D145	10	1	12
D146	10	1	12
D147	10	1	12
D148	11	1	12
D149	11	1	12
D150	11	1	12
D151	8	1	12
C153	4	1	4
C154	5	1	4
D155	4	1	4

**FACILITY PERMIT TO OPERATE
FRITO-LAY, INC.**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D156	4	1	4
D157	9	1	12
D158	9	1	12
D159	9	1	12
D160	9	1	12
D161	10	1	12
D162	10	1	12
D163	10	1	12
D164	10	1	12
D165	11	1	12
D166	11	1	12
C167	4	1	4

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or

(b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

F14.1 The operator shall not use fuel oil containing sulfur compounds in excess of 0.05 percent by weight.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

F14.2 The operator shall not purchase diesel fuel containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

F30.1 For the purpose of exemption from Title V requirements, the total emissions from this facility shall not equal or exceed the following specified amounts:

Pollutant	Emission Limit (Tons in any 12 consecutive calendar-month period)
NOx	10

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(1), 12-12-1997]

SYSTEM CONDITIONS

S1.2 The operator shall limit the material processed to no more than 5250 ton(s) in any 30-day period.

For the purpose of this condition, material processed shall be defined as pre-cleaned corn.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 1, System 1]

S1.3 The operator shall limit the material processed to no more than 6000 ton(s) in any 30-day period.

For the purpose of this condition, material processed shall be defined as corn meal.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 1, System 2]

S1.4 The operator shall limit the material processed to no more than 2880 ton(s) in any 30-day period.

For the purpose of this condition, material processed shall be defined as pre-cleaned corn.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 1, System 3]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

S1.5 The operator shall limit the material processed to no more than 936 ton(s) in any 30-day period.

For the purpose of this condition, material processed shall be defined as corn meal.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 1, System 12]

S1.6 The operator shall limit the material processed to no more than 673 ton(s) in any one month.

For the purpose of this condition, material processed shall be defined as Tortilla chips.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 1, System 6]

S1.7 The operator shall limit the material processed to no more than 1520 ton(s) in any one month.

For the purpose of this condition, material processed shall be defined as cornmeal.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 1, System 13]

DEVICE CONDITIONS

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

A. Emission Limits

A63.2 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
ROG	Less than or equal to 6 LBS IN ANY ONE DAY
CO	Less than or equal to 0.7 LBS IN ANY ONE DAY
PM10	Less than or equal to 0.5 LBS IN ANY ONE DAY

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D1, D59]

A433.1 The operator shall limit emissions from this equipment as follows::

Contaminant	Requirement	Emission Limit (Units)
PM10	less than or equal to	0.10 lbs/ton
VOC	less than or equal to	0.28 lbs/ton

For the purpose of this condition, tons shall be defined as tons of raw "masa" entering the fryer (input).

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : C153]

B. Material/Fuel Type Limits

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

B59.1 The operator shall only use the following material(s) in this device :

Cornmeal puffs, which do not contain VOC's.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D118]

C. Throughput or Operating Parameter Limits

C1.2 The operator shall limit the operating time to no more than 200 hour(s) in any one year.

**[RULE 1110.2, 6-3-2005; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996;
RULE 2012, 5-6-2005]**

[Devices subject to this condition : D71]

C1.3 The operator shall limit the material processed to no more than 615.6 ton(s) in any 30-day period.

To comply with this condition, the operator shall keep records, in a manner approved by the district for the following parameter(s) or item(s): A. The amount of material processed for every 30-day period, expressed in tons; and B. The start date and end date for every 30-day period.

For the purpose of this condition, material processed should be defined as "masa" entering the fryer (input).

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D65]

- C6.1 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 425 Deg F.

The operator shall install and maintain a(n) temperature guage to accurately measure and record the temperature of the oil.

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002**]

[Devices subject to this condition : D65, D68, D95]

- C6.2 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 400 Deg F.

To comply with this condition, the operator shall monitor the temperature as specified in condition number 12-3.

[**RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : D59]

- C6.3 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 4 inches water column.

To comply with this condition, the operator shall monitor the differential pressure as specified in condition number 12-7.

[**RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : C111]

- C8.1 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, is not less than 1400 Deg F.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

To comply with this condition, the operator shall install and maintain a(n) temperature reading device to accurately indicate the temperature of the afterburner.

[RULE 1303, 5-10-1996; RULE 1303, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D68, D95]

- C8.2 The operator shall use this equipment in such a manner that the pressure being monitored, as indicated below, is not less than 40 Psig.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C98]

- C8.3 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, is not less than 1500 Deg F.

The operator shall install a continuous temperature recorder to measure and record the temperature in the combustion chamber of the oxidizer. Such a system shall have an accuracy of within 1% of the temperature being monitored and shall be inspected, maintained, and calibrated on an annual basis in accordance with the manufacturer's specifications. The temperature indicating and recording system shall be in operation whenever the equipment it serves is in operation.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : C153]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D. Monitoring/Testing Requirements

D12.1 The operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the bags.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C13, C14]

D12.2 The operator shall install and maintain a(n) timer to accurately indicate the elapsed operating time of the engine.

**[RULE 1110.2, 6-3-2005; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996;
RULE 2012, 5-6-2005]**

[Devices subject to this condition : D71]

D12.3 The operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature of the oil.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D59, D68, D95]

D12.6 The operator shall install and maintain a(n) pressure gauge to accurately indicate the pressure of the water supply line.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C98]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D12.7 The operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the filter.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C111]

D28.7 The operator shall conduct source test(s) in accordance with the following specifications:

The test shall be conducted to determine the NOX emissions at the outlet.

The test shall be conducted within 60 days after achieving maximum production rate, but no later than 180 days after initial start-up.

The test shall be conducted only after a source test protocol has been approved by the District.

Source test shall be conducted when this equipment is operating at maximum load.

The District shall be notified of the date and time of the test at least 10 days prior to the test.

The test shall be conducted at least once every five years.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D85, D86]

D28.9 The operator shall conduct source test(s) in accordance with the following specifications:

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The test shall be conducted every five-year period with the first five-year period ending on December 31, 2009.

The test shall be conducted to determine the NOX emissions at the outlet.

[RULE 2012, 5-6-2005]

[Devices subject to this condition : D118]

D182.1 The operator shall test this equipment in accordance with the following specifications:

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The test shall be conducted to demonstrate compliance with the VOC and PM10 mass emission rates specified on this permit.

A source test protocol shall be submitted to the district no later than 60 days after the initial start-up of this equipment unless otherwise approved in writing by the district. The test protocol shall be approved in writing by the district before the test commences. The test protocol shall include completed district forms ST-1 and ST-2 specifying the proposed operating conditions of the equipment during the test, and the identity of the testing laboratory.

The source test protocol shall include a statement from the testing laboratory certifying it meets the criteria in district rule 304(k) and a description of the sampling and analytical procedures to be used.

The source test shall consist of, but may not be limited to, testing at the exhaust of the oxidizer for: 1) Volatile Organic Compounds (VOC), in LBS/TON. 2) PM10, in LBS/TON. 3) Process Rate 4) Temperature.

A written notice of the source tests shall be submitted to the district at least 14 days prior to the source testing date so that an observer from the district may be present.

The test shall be conducted once every 5 year period with the first period ending December 31, 2017.

Two complete copies of the source test report shall be submitted to the district within 45 days after the source test date unless otherwise approved in writing by the district. The source test report shall include, but may not be limited to, all testing data required by this condition.

A testing laboratory certified by the California Air Resources Board in the required test methods for criteria pollutants to be measured, and in compliance with the district rule 304 (no conflict of interest) shall conduct the test.

Sampling facilities shall comply with the district guideline for construction of sampling and testing facilities, pursuant to rule 217.

**FACILITY PERMIT TO OPERATE
FRITO-LAY, INC.**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

**[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring,
12-12-1997]**

[Devices subject to this condition : C153]

D322.1 The operator shall perform annual inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C13, C14, E83, C111]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a semi-annual basis, at least, unless the equipment did not operate during the entire semi-annual period. The routine semi-annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C8, C9, D29, D31, D32, D36, D40, D59, D65, D68, D87, D88, D89, D90, D91, D92, D93, D94, D95, D96, D97, C98, D116, D117, D121, D122, D123, D124, D125, D126, D127, D128, D129, D130, D131, D132, D133, D134, D135, D136, D137, D138, D139, D140, D141, D142, D143, D144, D145, D146, D147, D148, D149, D150, D151, C153, D157, D158, D159, D160, D161, D162, D163, D164, D165, D166]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.2 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D1, D2, D3, D4, D5, D6, D7, D10, D11, D12, D15, D16, D17, D18, D19, D41, D42, D44, D72, D79, D80, D85, D86, D103, D104, D105, D106, D107, D108, D109, D110]

D381.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions; and
- 3). Date and time visible emission was abated.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C13, C14, D73, D74, E83, C111]

E. Equipment Operation/Construction Requirements

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E17.1 The operator shall not use more than 1 of the following items simultaneously:

Device ID: D95 [FRYER]

Device ID: D118 [Drying Oven]

This condition shall not apply during equipment sanitation period.

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002**]

[Devices subject to this condition : D95, D118]

E73.1 Notwithstanding the requirements of Section E conditions, the operator shall not use this equipment for baking leavened bakery products.:

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002**]

[Devices subject to this condition : D79, D80]

E102.1 The operator shall discharge dust collected in this equipment only into closed containers.

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : C13, C14, E83, C111]

H. Applicable Rules

H23.1 This equipment is subject to the applicable requirements of the following rules or regulations:

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Contaminant	Rule	Rule/Subpart
Refrigerants	District Rule	1415
Refrigerants	40CFR82, SUBPART	F

[RULE 1415, 10-14-1994; 40CFR 82 Subpart F, 5-14-1993]

[Devices subject to this condition : E82]

H23.2 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
Halon	District Rule	1418

[RULE 1418, 9-10-1999]

[Devices subject to this condition : E84]

K. Record Keeping/Reporting

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

the date, time and description of any maintenance or repairs resulting from the inspection

the name of the person performing the inspection and/or maintenance of the filter media

the date, time and results of the inspection

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C13, C14, E83, C111]

K67.2 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records for all coating consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coatings.

For architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coatings.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : E81]

M. Title V Permit Shield

M333.1 Permit Shield. Notwithstanding the other requirements and conditions in this permit, this device is not subject to the following rule requirement(s):

Rule	Number/Subpart	Adopted/Amended Date	Non-Applicable Requirement(s)
District Rule	1140	02-Aug-1985	(d)

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Compliance with the conditions of this Title V permit shall be deemed in compliance with any regulatory requirements applicable as of the date of permit issuance to this device, provided that such regulatory requirements are included and specifically identified in this permit. Nothing in this permit or in any permit shield can alter or affect: (a) under Section 303 of the Federal Clean Air Act, the provisions for emergency orders; (b) the liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance; (c) the applicable requirements of the Acid Rain Program; (d) the ability of EPA to obtain information from the operator pursuant to Section 114 of the Federal Clean Air Act; (e) the applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do not apply to the facility, such as toxics requirements unique to the State; or, (f) the applicability of regulatory requirements with compliance dates after the permit issuance date. This permit shield shall not apply to any operational change made pursuant to the operational flexibility provisions of District Rule 3005.

[RULE 3004(c)-Permit Shield, 12-12-1997]

[Devices subject to this condition : E83]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION E: ADMINISTRATIVE CONDITIONS

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]
 - a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]
 - b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]
 - c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]
2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]
3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the AQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations, or statutes of other governmental agencies. [204]
4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION E: ADMINISTRATIVE CONDITIONS

5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation. [204]
6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to AQMD personnel upon request and be maintained for at least: [204]
 - a. Three years for a facility not subject to Title V; or
 - b. Five years for a facility subject to Title V.
7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by AQMD rules or permit conditions: [204]
 - a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134, 204]
 - b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]
 - c. For a large NO_x source, compliance with a RECLAIM concentration limit shall be measured over a continuous 60 minutes for that source; [2012]
 - d. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes; [204]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION E: ADMINISTRATIVE CONDITIONS

- e. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compounds which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO₂) and be averaged over 15 consecutive minutes; [407]
 - f. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent of carbon dioxide (CO₂) at standard conditions and averaged over 15 consecutive minutes. [409]
 - g. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O₂) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]
8. All equipment operating under the RECLAIM program shall comply concurrently with all provisions of AQMD Rules and Regulations, except those listed in Table 1 of Rule 2001 for NO_x RECLAIM sources and Table 2 of Rule 2001 for SO_x RECLAIM sources. Those provisions listed in Tables 1 or 2 shall not apply to NO_x or SO_x emissions after the date the facility has demonstrated compliance with all monitoring and reporting requirements of Rules 2011 or 2012, as applicable. Provisions of the listed AQMD rules in Tables 1 or 2 which have initial implementation dates in 1994 shall not apply to a RECLAIM NO_x or SO_x source, respectively. [2001]
9. The operator shall, when a source test is required by AQMD, provide a source test protocol to AQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by AQMD. The test protocol shall contain the following information: [204, 304]
- a. Brief description of the equipment tested.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION E: ADMINISTRATIVE CONDITIONS

- b. Brief process description, including maximum and normal operating temperatures, pressures, through-put, etc.
 - c. Operating conditions under which the test will be performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts/stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.
 - f. Description of calibration and quality assurance procedures.
 - g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (no conflict of interest).
10. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by AQMD Rules or equipment-specific conditions. The report shall contain the following information: [204]
- a. The results of the source test.
 - b. Brief description of the equipment tested.
 - c. Operating conditions under which test will be performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts/stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Field and laboratory data forms, strip charts and analyses.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION E: ADMINISTRATIVE CONDITIONS

- f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.
- 11. The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of AQMD Source Test Method 1.1 and 1.2. [217]
- 12. Whenever required to submit a written report, notification or other submittal to the Executive Officer, AQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, AQMD, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182. [204]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

The Facility shall comply with all applicable monitoring and source testing requirements in Regulation XX. These requirements may include but are not limited to the following:

I. NO_x Monitoring Conditions

A. The Operator of a NO_x Major Source, as defined in Rule 2012, shall, as applicable:

Not Applicable

B. The Operator of a NO_x large Source, as defined in Rule 2012, shall, as applicable:

Not Applicable

C. The Operator of a NO_x Process Unit, as defined in Rule 2012, shall, as applicable:

1. Install, maintain, and operate a totalizing fuel meter or any device approved by the Executive Officer to measure quarterly fuel usage or other applicable variables specified in Rule 2012, Table 2012-1, and Rule 2012, Appendix A, Table 4-A. The sharing of totalizing fuel meters may be allowed by the Executive Officer if the fuel meter serves process units which have the same emission factor or emission rate. The sharing of totalizing meter shall not be allowed for process units which are required to comply with an annual heat input limit. [2012]

II. NO_x Source Testing and Tune-up conditions

1. The operator shall conduct all required NO_x source testing in compliance with an AQMD-approved source test protocol. [2012]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

2. The operator shall, as applicable, conduct source tests for every large NO_x source no later than December 31, 1996 and every 3 years thereafter. The source test shall include the determination of NO_x concentration and a relative accuracy audit of the exhaust stack flow determination (e.g. in-stack flow monitor or fuel flow monitor based F-factor calculation). Such source test results shall be submitted per the schedule described by APEP. In lieu of submitting the first source test report, the facility permit holder may submit the results of a source test not more than 3 years old which meets the requirements when conducted. [2012]
3. All NO_x large sources and NO_x process units shall be tuned-up in accordance with the schedule specified in Rule 2012, Appendix A, Chapter 5, Table 5-B. [2012]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR RECLAIM SOURCES

The Facility shall comply with all applicable reporting and recordkeeping requirements in Regulation XX. These requirements may include but are not limited to the following:

I. Recordkeeping Requirements for all RECLAIM Sources

1. The operator shall maintain all monitoring data required to be measured or reported pursuant to Rule 2011 and Rule 2012, whichever is applicable. All records shall be made available to AQMD staff upon request and be maintained for at least:
 - a. Three years after each APEP report is submitted to AQMD for a facility not subject to Title V, unless a different time period is required in Rule 2011 or Rule 2012 [2011 & 2012]; or
 - b. Five years after each APEP report is submitted to AQMD for a facility subject to Title V. [3004(a)(4)(E)]
 - c. Notwithstanding the above, all data gathered or computed for intervals of less than 15 minutes shall only be maintained a minimum of 48 hours. [2011 & 2012]
2. The operator shall store on site and make available to the Executive Officer upon request: records used to determine emissions, maintenance records, sources test reports, relative accuracy test audit reports, relative accuracy audit reports and fuel meter calibration records. [2011 & 2012]

II. Reporting Requirements for all RECLAIM Sources

1. The operator shall submit a quarterly certification of emissions including the total facility NO_x or SO_x emissions, whichever is applicable, for the quarter within 30 days after the end of the first three quarters and 60 days after the end of the fourth quarter of a compliance year. [2004]

NO_x Reporting Requirements

- A. The Operator of a NO_x Major Source, as defined in Rule 2012, shall, as applicable:

Not Applicable

**FACILITY PERMIT TO OPERATE
FRITO-LAY, INC.**

**SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR
RECLAIM SOURCES**

B. The Operator of a NO_x Large Source, as defined in Rule 2012, shall:

Not Applicable

C. The Operator of a NO_x Process Unit, as defined in Rule 2012, shall:

1. Electronically report the calculated quarterly NO_x emissions for each NO_x process unit. The Operator shall comply with this requirement within 12 months of the date of entry to the RECLAIM Program. [2012]

**FACILITY PERMIT TO OPERATE
FRITO-LAY, INC.**

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

NONE

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION I: PLANS AND SCHEDULES

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules.

NONE

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.

**FACILITY PERMIT TO OPERATE
FRITO-LAY, INC.**

SECTION J: AIR TOXICS

NOT APPLICABLE

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION K: TITLE V Administration

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
- (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.
 - (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
 - (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
- (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]

10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]

12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]

13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION K: TITLE V Administration

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]
15. Nothing in this permit or in any permit shield can alter or affect:
- (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]
16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION K: TITLE V Administration EMERGENCY PROVISIONS

17. An emergency¹ constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
 - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
 - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
 - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
 - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
 - (B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

¹ "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION K: TITLE V Administration RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
- (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
 - (B) The date(s) analyses were performed;
 - (C) The company or entity that performed the analyses;
 - (D) The analytical techniques or methods used;
 - (E) The results of such analyses; and
 - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:
- (A) Breakdowns shall be reported as required by Rule 430 - Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION K: TITLE V Administration

- (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.
 - (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
 - (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION K: TITLE V Administration

- (B) The compliance status during the reporting period;
- (C) Whether compliance was continuous or intermittent;
- (D) The method(s) used to determine compliance over the reporting period and currently, and
- (E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn:
Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 1110.2	6-3-2005	Non federally enforceable
RULE 1113	11-8-1996	Federally enforceable
RULE 1113	6-3-2011	Non federally enforceable
RULE 1140	2-1-1980	Federally enforceable
RULE 1140	8-2-1985	Non federally enforceable
RULE 1171	11-7-2003	Federally enforceable
RULE 1171	5-1-2009	Non federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303	5-10-1996	Federally enforceable
RULE 1303(a)	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(a)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	12-6-2002	Non federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1304(a)-Modeling and Offset Exemption	6-14-1996	Federally enforceable
RULE 1415	10-14-1994	Non federally enforceable
RULE 1418	9-10-1999	Non federally enforceable
RULE 2005	6-3-2011	Federally enforceable
RULE 2012	5-6-2005	Federally enforceable
RULE 204	10-8-1993	Federally enforceable

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 217	1-5-1990	Federally enforceable
RULE 219	6-1-2007	Non federally enforceable
RULE 2202	2-6-2004	Non federally enforceable
RULE 3002	11-14-1997	Federally enforceable
RULE 3002	11-5-2010	Non federally enforceable
RULE 3003	11-14-1997	Federally enforceable
RULE 3003	11-5-2010	Non federally enforceable
RULE 3004(a)(1)	12-12-1997	Federally enforceable
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3004(c)-Permit Shield	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3005	11-5-2010	Non federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	6-1-2012	Non federally enforceable
RULE 401	11-9-2001	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 405	2-7-1986	Federally enforceable
RULE 407	4-2-1982	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 409	8-7-1981	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 431.2	5-4-1990	Federally enforceable
RULE 431.2	9-15-2000	Non federally enforceable
RULE 701	6-13-1997	Federally enforceable
40CFR 82 Subpart F	5-14-1993	Federally enforceable

**FACILITY PERMIT TO OPERATE
FRITO-LAY, INC.**

**APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN
PERMIT PURSUANT TO RULE 219**

1. SIX MIURA BOILERS, NATURAL GAS
2. PRESSURE WASHER, NATURAL GAS
3. WATER HEATERS, NATURAL GAS
4. SPACE HEATERS, NATURAL GAS

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1113 11-08-1996]**

- (1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.
- (2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

TABLE OF STANDARDS

VOC LIMITS

**Grams of VOC Per Liter of Coating,
 Less Water And Less Exempt Compounds**

COATING	Limit*	Effective Date of Adoption	Effective 1/1/1998	Effective 1/1/1999	Effective 7/1/2001	Effective 1/1/2005	Effective 7/1/2008
Bond Breakers	350						
Clear Wood Finishes							
Varnish	350						
Sanding Sealers	350						
Lacquer	680		550			275	
Concrete-Curing Compounds	350						
Dry-Fog Coatings	400						
Fire-proofing Exterior Coatings	350	450		350			
Fire-Retardant Coatings							
Clear	650						
Pigmented	350						
Flats	250				100		
Graphic Arts (Sign) Coatings	500						50

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1113 11-08-1996]**

Industrial Maintenance						
Primers and Topcoats						
Alkyds	420					
Catalyzed Epoxy	420					
Bituminous Coatings	420					
Materials						
Inorganic Polymers	420					
Vinyl Chloride Polymers	420					
Chlorinated Rubber	420					
Acrylic Polymers	420					
Urethane Polymers	420					
Silicones	420					
Unique Vehicles	420					
Japans/Faux Finishing	350	700		350		
Coatings						
Magnesite Cement Coatings	600			450		
Mastic Coatings	300					
Metallic Pigmented Coatings	500					
Multi-Color Coatings	420		250			
Pigmented Lacquer	680		550			275
Pre-Treatment Wash Primers	780					
Primers, Sealers, and	350					
Undercoaters						
Quick-Dry Enamels	400					
Roof Coatings	300					
Shellac						
Clear	730					
Pigmented	550					
Stains	350					
Swimming Pool Coatings						
Repair	650					
Other	340					
Traffic Coatings	250		150			
Waterproofing Sealers	400					
Wood Preservatives						
Below-Ground	350					
Other	350					

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

TABLE OF STANDARDS (cont.)

VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

- (1) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6) of Rule 1113, no person shall supply, sell, offer for sale, market, manufacture, blend, repackage, apply, store at a worksite, or solicit the application of any architectural coating within the District:
 - (A) That is listed in the Table of Standards 1 and contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified; or
 - (B) That is not listed in the Table of Standards 1, and contains VOC (excluding any colorant added to tint bases) in excess of 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, until January 1, 2014, at which time the limit drops to 50 grams of VOC per liter of coating, less water, less exempt compounds (0.42 pounds per gallon).
- (2) No person within the District shall add colorant at the point of sale that is listed in the Table of Standards 2 and contains VOC in excess of the corresponding VOC limit specified in the Table of Standards 2, after the effective date specified.

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1113 06-03-2011]**

**TABLE OF STANDARDS 1
 VOC LIMITS**

**Grams of VOC Per Liter of Coating,
 Less Water and Less Exempt Compounds**

COATING CATEGORY	Ceiling Limit ¹	Current Limit ²	Effective Date		
			7/1/08	1/1/12	1/1/14
Bond Breakers		350			
Clear Wood Finishes		275			
Varnish	350	275			
Sanding Sealers	350	275			
Lacquer		275			
Concrete-Curing Compounds		100			
Concrete-Curing Compounds For Roadways and Bridges ³		350			
Concrete Surface Retarder		250			50
Driveway Sealer		100		50	
Dry-Fog Coatings		150			50
Faux Finishing Coatings					
Clear Topcoat		350		200	
Decorative Coatings		350			100
Glazes		350			
Japan		350			
Trowel Applied Coatings		350		150	50
Fire-Proofing Coatings		350			150
Flats	250	50	50		
Floor Coatings	100	50			
Form Release Compound		250			100
Graphic Arts (Sign) Coatings		500			150
Industrial Maintenance (IM) Coatings	420	100			
High Temperature IM Coatings		420			
Non-Sacrificial Anti-Graffiti Coatings		100			
Zinc-Rich IM Primers	340	100			
Magnesite Cement Coatings		450			
Mastic Coatings		300			100
Metallic Pigmented Coatings	500	500			150
Multi-Color Coatings		250			
Nonflat Coatings	150	50			
Pre-Treatment Wash Primers		420			
Primers, Sealers, and Undercoaters	200	100			
Reactive Penetrating Sealers		350			
Recycled Coatings		250			
Roof Coatings	250	50			
Roof Coatings, Aluminum		100			

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1113 06-03-2011]**

Roof Primers, Bituminous	350	350		
Rust Preventative Coatings	400	100		
Stone Consolidant		450		
Sacrificial Anti-Graffiti Coatings		100	50	
Shellac				
Clear		730		
Pigmented		550		
Specialty Primers	350	100		
Stains		100		

**FACILITY PERMIT TO OPERATE
FRITO-LAY, INC.**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 06-03-2011]**

COATING CATEGORY	Ceiling Limit ¹	Current Limit ²	Effective Date		
			7/1/08	1/1/12	1/1/14
Stains, Interior	250	250			
Swimming Pool Coatings					
Repair		340			
Other		340			
Traffic Coatings		100			
Waterproofing Sealers	250	100			
Waterproofing Concrete/Masonry Sealers	400	100			
Wood Preservatives		350			

1. The specified ceiling limits are applicable to products sold under the Averaging Compliance Option.
2. The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.
3. Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

**TABLE OF STANDARDS 1 (cont.)
VOC LIMITS**

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

**TABLE OF STANDARDS 2
VOC LIMITS FOR COLORANTS**

**Grams of VOC Per Liter of Colorant
Less Water and Less Exempt Compounds**

COLORANT	Limit ⁴
Architectural Coatings, excluding IM Coatings	50
Solvent-Based IM	600
Waterborne IM	50

4. Effective January 1, 2014.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1140 02-01-1980]

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).

- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1140 08-02-1985]

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).
- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

**FACILITY PERMIT TO OPERATE
FRITO-LAY, INC.**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]**

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	500 (4.2)
(iii) Medical Devices & Pharmaceuticals	800 (6.7)
(B) Repair and Maintenance Cleaning	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 11-07-2003]**

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals	
(A) Tools, Equipment, & Machinery	800 (6.7)
(B) General Work Surfaces	600 (5.0)
(C) Cleaning of Coatings or Adhesives Application Equipment	550 (4.6)
(D) Cleaning of Ink Application Equipment	
(i) General	25 (0.21)
(ii) Flexographic Printing	25 (0.21)
(iii) Gravure Printing	
(A) Publication	750 (6.3)
(B) Packaging	25 (0.21)
(iv) Lithographic or Letter Press Printing	

**FACILITY PERMIT TO OPERATE
 FRITO-LAY. INC.**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 11-07-2003]**

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(A) Roller Wash – Step 1	600 (5.0)
(B) Roller Wash-Step 2, Blanket Wash, & On-Press Components	800 (6.7)
(C) Removable Press Components	25 (0.21)
(v) Screen Printing	750 (6.3)
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	800 (6.7)
(vii) Specialty Flexographic Printing	600 (5.0)
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals	800 (6.7)	
(B) Repair and Maintenance Cleaning		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	

**FACILITY PERMIT TO OPERATE
FRITO-LAY, INC.**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 05-01-2009]**

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals		
(A) Tools, Equipment, & Machinery	800 (6.7)	
(B) General Work Surfaces	600 (5.0)	
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)	
(D) Cleaning of Ink Application Equipment		
(i) General	25 (0.21)	
(ii) Flexographic Printing	25 (0.21)	
(iii) Gravure Printing		
(A) Publication	100 (0.83)	
(B) Packaging	25 (0.21)	
(iv) Lithographic (Offset) or Letter Press Printing		
(A) Roller Wash, Blanket Wash, & On-Press Components	100 (0.83)	

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 05-01-2009]**

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(B) Removable Press Components	25 (0.21)	
(v) Screen Printing	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)	
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)	

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 404 02-07-1986]**

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100

FACILITY PERMIT TO OPERATE FRITO-LAY, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 405 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process	
		Kilograms Per Hour	Pounds Per Hour			Kilograms Per Hour	Pounds Per Hour
100 or less	220 or less	0.450	0.99	9000	19840	5.308	11.7
150	331	0.585	1.29	10000	22050	5.440	12.0
200	441	0.703	1.55	12500	27560	5.732	12.6
250	551	0.804	1.77	15000	33070	5.982	13.2
300	661	0.897	1.98	17500	38580	6.202	13.7
350	772	0.983	2.17	20000	44090	6.399	14.1
400	882	1.063	2.34	25000	55120	6.743	14.9
450	992	1.138	2.51	30000	66140	7.037	15.5
500	1102	1.209	2.67	35000	77160	7.296	16.1
600	1323	1.340	2.95	40000	88180	7.527	16.6

**FACILITY PERMIT TO OPERATE
 FRITO-LAY, INC.**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 405 02-07-1986]**

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
700	1543	1.461	3.22	45000	99210	7.738	17.1
800	1764	1.573	3.47	50000	110200	7.931	17.5
900	1984	1.678	3.70	60000	132300	8.277	18.2
1000	2205	1.777	3.92	70000	154300	8.582	18.9
1250	2756	2.003	4.42	80000	176400	8.854	19.5
1500	3307	2.206	4.86	90000	198400	9.102	20.1
1750	3858	2.392	5.27	100000	220500	9.329	20.6
2000	4409	2.563	5.65	125000	275600	9.830	21.7
2250	4960	2.723	6.00	150000	330700	10.26	22.6
2500	5512	2.874	6.34	175000	385800	10.64	23.5
2750	6063	3.016	6.65	200000	440900	10.97	24.2
3000	6614	3.151	6.95	225000	496000	11.28	24.9
3250	7165	3.280	7.23	250000	551200	11.56	25.5
3600	7716	3.404	7.50	275000	606300	11.82	26.1
4000	8818	3.637	8.02	300000	661400	12.07	26.6
4500	9921	3.855	8.50	325000	716500	12.30	27.1
5000	11020	4.059	8.95	350000	771600	12.51	27.6
6000	13230	4.434	9.78	400000	881800	12.91	28.5
7000	15430	4.775	10.5	450000	992100	13.27	29.3
8000	17640	5.089	11.2	500000 or more	1102000 or more	13.60	30.0