

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

PERMIT TO OPERATE

Permit No.
A/N 518450

Equipment Description:

STORAGE TANK NO. 2001, CAPACITY 2,000 BARRELS, 30'-0" DIA. X 15'-10 1/2 " H., INTERNAL FLOATING ROOF, WELDED SHELL AND SHOE TYPE SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 50 PERCENT OF THE LOWER EXPLOSIVE LIMIT. THE OPERATOR SHALL USE AN EXPLOSIMETER TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE A YEAR AT A 4 TO 8 MONTH INTERVAL TO ENSURE COMPLIANCE WITH THIS CONDITION.
[RULE 463, RULE 1178]
4. THIS TANK SHALL NOT BE USED FOR STORING ORGANIC LIQUIDS HAVING A VAPOR PRESSURE OF 176 MMHG (3.4 PSIA) OR GREATER UNDER ACTUAL STORAGE CONDITIONS.
[RULE 1303(b)(2) - OFFSET]
5. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
TYPE OF LIQUID STORED, THROUGHPUT, AND ITS TRUE VAPOR PRESSURE UNDER ACTUAL STORAGE CONDITION.
[RULE 463, 40 CFR 60 SUBPART Ka]

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

Periodic Monitoring: NONE

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC/TOC: 40 CFR 60 SUBPART Ka
VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

PERMIT TO OPERATE

Permit No.
A/N 518456

Equipment Description:

STORAGE TANK NO. 30001, CAPACITY 30,000 BARRELS, 68'-3" DIA. X 48'-0" H., WITH A FIXED ROOF AND AN INTERNAL FLOATING PAN WITH A SHOE TYPE SEAL.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
 2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
 3. THIS TANK SHALL NOT BE USED FOR STORING PURE ORGANIC COMPOUNDS.
[RULE 1303(b)(2) - OFFSET]
 4. THE OPERATOR SHALL PROVIDE PROCEDURES FOR REMOVAL OF ANY FLOATING ROOF TANK FROM SERVICE THAT HAS STORED ANY CRUDE OIL CONTAINING MORE THAN 200 PPM BY WEIGHT HYDROGEN SULFIDE. SUCH PROCEDURES SHALL BE APPROVED BY THE EXECUTIVE OFFICER.
[RULE 402]
 5. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 50 PERCENT OF THE LOWER EXPLOSIVE LIMIT. THE OPERATOR SHALL USE AN EXPLOSIMETER TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE A YEAR AT A 4 TO 8 MONTH INTERVAL TO ENSURE COMPLIANCE WITH THIS CONDITION.
[RULE 463, RULE 1178]
 6. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
TYPE OF LIQUID STORED, THROUGHPUT, AND ITS TRUE VAPOR PRESSURE UNDER ACTUAL STORAGE CONDITION.
[RULE 463]
-

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

Periodic Monitoring: NONE

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC:	RULE 463
VOC:	RULE 1149
VOC:	RULE 1178

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

PERMIT TO OPERATE

Permit No.
A/N 518459

Equipment Description:

STORAGE TANK NO. 30002, CAPACITY 30,000 BARRELS, 68'-3" DIA. X 48'-0" H., WITH A FIXED ROOF AND AN INTERNAL FLOATING PAN WITH A **SHOE** TYPE SEAL.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 50 PERCENT OF THE LOWER EXPLOSIVE LIMIT. THE OPERATOR SHALL USE AN EXPLOSIMETER TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE A YEAR AT A 4 TO 8 MONTH INTERVAL TO ENSURE COMPLIANCE WITH THIS CONDITION.
[RULE 463, RULE 1178]
4. THIS TANK SHALL NOT BE USED FOR STORING PURE ORGANIC COMPOUNDS.
[RULE 204]
5. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
TYPE OF LIQUID STORED, THROUGHPUT, AND ITS TRUE VAPOR PRESSURE UNDER ACTUAL STORAGE CONDITION.
[RULE 463]

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

Periodic Monitoring: NONE

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC/TOC:	RULE 463
VOC:	RULE 1149
VOC:	RULE 1178

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

PERMIT TO OPERATE

Permit No.
A/N 518460

Equipment Description:

STORAGE TANK NO. 30003, CAPACITY 30,000 BARRELS, 68'-3" DIA. X 48'-0" H., WITH A FIXED ROOF AND AN INTERNAL FLOATING PAN WITH A **SHOE TYPE SEAL**.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS TANK SHALL NOT BE USED FOR STORING PURE ORGANIC COMPOUNDS.
[RULE 204]
4. THE OPERATOR SHALL PROVIDE PROCEDURES FOR REMOVAL OF ANY FLOATING ROOF TANK FROM SERVICE THAT HAS STORED ANY CRUDE OIL CONTAINING MORE THAN 200 PPM BY WEIGHT HYDROGEN SULFIDE. SUCH PROCEDURES SHALL BE APPROVED BY THE EXECUTIVE OFFICER.
[RULE 402]
5. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 50 PERCENT OF THE LOWER EXPLOSIVE LIMIT. THE OPERATOR SHALL USE AN EXPLOSIMETER TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE A YEAR AT A 4 TO 8 MONTH INTERVAL TO ENSURE COMPLIANCE WITH THIS CONDITION.
[RULE 463, RULE 1178]
6. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
TYPE OF LIQUID STORED, THROUGHPUT, AND ITS TRUE VAPOR PRESSURE UNDER ACTUAL STORAGE CONDITION.
[RULE 463]

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

Periodic Monitoring: NONE

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

PERMIT TO OPERATE

Permit No.
A/N 518461

Equipment Description:

STORAGE TANK NO. 30004, CAPACITY 30,000 BARRELS, 68'-0" DIA. X 48'-0" H., WELDED SHELL, PONTON INTERNAL FLOATING ROOF, WITH A SHOE TYPE PRIMARY SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS TANK SHALL NOT BE USED FOR STORING PURE ORGANIC COMPOUNDS.
[RULE 204]
4. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 50 PERCENT OF THE LOWER EXPLOSIVE LIMIT. THE OPERATOR SHALL USE AN EXPLOSIMETER TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE A YEAR AT A 4 TO 8 MONTH INTERVAL TO ENSURE COMPLIANCE WITH THIS CONDITION.
[RULE 463, RULE 1178]
5. THE OPERATOR SHALL PROVIDE PROCEDURES FOR REMOVAL OF ANY FLOATING ROOF TANK FROM SERVICE THAT HAS STORED ANY CRUDE OIL CONTAINING MORE THAN 200 PPM BY WEIGHT HYDROGEN SULFIDE. SUCH PROCEDURES SHALL BE APPROVED BY THE EXECUTIVE OFFICER.
[RULE 402]
6. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
TYPE OF LIQUID STORED, THROUGHPUT, AND ITS TRUE VAPOR PRESSURE UNDER ACTUAL STORAGE CONDITION.
[RULE 463, 40 CFR 60 SUBPART Ka]

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

Periodic Monitoring: NONE

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC/TOC: 40 CFR 60 SUBPART Ka
VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

PERMIT TO OPERATE

Permit No.
A/N 518462

Equipment Description:

STORAGE TANK NO. 50001, CAPACITY 50,000 BARRELS, 88'-6" DIA. X 48'-0" H., WELDED SHELL, INTERNAL FLOATING ROOF PAN, WITH A SHOE TYPE SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 30 PERCENT OF THE LOWER EXPLOSIVE LIMIT. THE OPERATOR SHALL USE AN EXPLOSIMETER TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE A YEAR AT A 4 TO 8 MONTH INTERVAL TO ENSURE COMPLIANCE WITH THIS CONDITION.
[RULE 463, RULE 1178]
4. THE OPERATOR SHALL LIMIT THE THROUGHPUT TO NO MORE THAN 1,496,500 BARRELS IN ANY ONE CALENDAR YEAR.
[RULE 1303(b)(2) - OFFSET]
5. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
TYPE OF LIQUID STORED, THROUGHPUT, AND ITS TRUE VAPOR PRESSURE UNDER ACTUAL STORAGE CONDITION.
[RULE 463, 40 CFR 60 SUBPART Kb]

Periodic Monitoring: NONE

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC/TOC:	40 CFR 60 SUBPART Kb
VOC:	RULE 463
VOC:	RULE 1149
VOC:	RULE 1178

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

PERMIT TO OPERATE

Permit No.
A/N 518463

Equipment Description:

STORAGE TANK NO. 50002, CAPACITY 50,000 BARRELS, 88'-6" DIA. X 48'-0" H., WELDED SHELL, INTERNAL FLOATING ROOF PAN, WITH A SHOE TYPE SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 30 PERCENT OF THE LOWER EXPLOSIVE LIMIT. THE OPERATOR SHALL USE AN EXPLOSIMETER TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE A YEAR AT A 4 TO 8 MONTH INTERVAL TO ENSURE COMPLIANCE WITH THIS CONDITION.
[RULE 463, RULE 1178]
4. THE OPERATOR SHALL LIMIT THE THROUGHPUT TO NO MORE THAN 1,496,500 BARRELS IN ANY ONE CALENDAR YEAR.
[RULE 1303(b)(2) - OFFSET]
5. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
TYPE OF LIQUID STORED, THROUGHPUT, AND ITS TRUE VAPOR PRESSURE UNDER ACTUAL STORAGE CONDITION.
[RULE 463, 40 CFR 60 SUBPART Kb]

Periodic Monitoring: NONE

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC/TOC: 40 CFR 60 SUBPART Kb
VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

PERMIT TO OPERATE

Permit No.
A/N 518464

Equipment Description:

STORAGE TANK NO. 50003, CAPACITY 50,000 BARRELS, 88'-6" DIA. X 48'-0" H., WITH FIXED ROOF, EQUIPPED WITH INTERNAL FLOATING ROOF PAN WITH A SHOE TYPE PRIMARY SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS TANK SHALL NOT BE USED FOR STORING ORGANIC LIQUIDS HAVING A VAPOR PRESSURE OF 6.2 PSIA OR GREATER UNDER ACTUAL STORAGE CONDITIONS.
[RULE 1303(b)(2) - OFFSET]
4. THE OPERATOR SHALL ONLY USE GASOLINE AND CRUDE OIL IN THIS EQUIPMENT.
[RULE 1303(b)(2) - OFFSET]
5. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 30 PERCENT OF THE LOWER EXPLOSIVE LIMIT. THE OPERATOR SHALL USE AN EXPLOSIMETER TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE A YEAR AT A 4 TO 8 MONTH INTERVAL TO ENSURE COMPLIANCE WITH THIS CONDITION.
[RULE 463, RULE 1178]
6. THE OPERATOR SHALL LIMIT THE THROUGHPUT TO NO MORE THAN 1,496,500 BARRELS IN ANY ONE CALENDAR YEAR.
[RULE 1303(b)(2) - OFFSET]
7. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
TYPE OF LIQUID STORED, THROUGHPUT, AND ITS TRUE VAPOR PRESSURE UNDER ACTUAL STORAGE CONDITION.
[RULE 463, 40 CFR 60 SUBPART Kb]

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

Periodic Monitoring: NONE

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOCTOC: 40 CFR 60 SUBPART Kb
VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

PERMIT TO OPERATE

Permit No.
A/N 518470

Equipment Description:

STORAGE TANK NO: 217,001, CAPACITY 217,000 BARRELS, 180'-0" DIA. X 48'-0" H., WELDED SHELL, DOUBLE DECK EXTERNAL FLOATING ROOF, WITH A SHOE TYPE PRIMARY SEAL AND A RFI "WEATHER GUARD" SECONDARY SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS TANK SHALL NOT BE USED FOR STORING PURE ORGANIC COMPOUNDS.
[RULE 204]
4. THE OPERATOR SHALL PROVIDE PROCEDURES FOR REMOVAL OF ANY FLOATING ROOF TANK FROM SERVICE THAT HAS STORED ANY CRUDE OIL CONTAINING MORE THAN 200 PPM BY WEIGHT HYDROGEN SULFIDE. SUCH PROCEDURES SHALL BE APPROVED BY THE EXECUTIVE OFFICER.
[RULE 402]
5. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
TYPE OF LIQUID STORED, THROUGHPUT, AND ITS TRUE VAPOR PRESSURE UNDER ACTUAL STORAGE CONDITION.
[RULE 463, 40 CFR 60 SUBPART K]

Periodic Monitoring: NONE

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC/TOC:	40 CFR 60, SUBPART K
VOC:	RULE 463
VOC:	RULE 1149
VOC:	RULE 1178

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

PERMIT TO CONSTRUCT

A/N 555129
Granted x/xx/2014

Equipment Description:

MODIFICATION OF TANK TRUCK LOADING RACK NO. 1, FOR PETROLEUM PRODUCTS, CONSISTING OF:

1. FOUR 4" EMCO-WHEATON TYPE BOTTOM LOADING CONNECTOR.
2. TWO 3" VAPOR CONNECTIONS.
3. THREE METERS
4. LOADING PUMPS, COMMON TO RACKS NO. 2, NO. 3 AND NO. 4
TWO 25 H.P. CENTRIFUGAL, WITH MECHANICAL SEALS
TWO 25 H.P. CENTRIFUGAL, WITH MECHANICAL SEALS
TWO 25 H.P. CENTRIFUGAL, WITH MECHANICAL SEALS

BY THE ADDITION OF:

1. TWO BIO-DIESEL METERS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL VENT ALL VENT GASES FROM THIS LOADING RACK TO THE VAPOR CONTROL SYSTEM WHICH SHALL HAVE A VALID PERMIT TO RECEIVE THE VENT GASES FROM THIS EQUIPMENT AND SHALL ALSO BE CARB CERTIFIED. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS THE VAPOR COLLECTION BLADDER TANK HAS A SUFFICIENT CAPACITY TO RECEIVE VENT GASE FROM THIS EQUIPMENT.

[RULE 462, RULE 1303 (a) (1) - BACT, 40 CFR 60 SUBPART XX]

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

4. THE OPERATOR SHALL NOT USE THIS EQUIPMENT TO LOAD PURE ORGANIC COMPOUNDS OR LIQUIDS, EXCEPT ETHANOL.

[RULE 204]

5. THE OPERATOR SHALL LIMIT THE COMBINED THROUGHPUT OF TANK TRUCK LOADING RACKS NOS. 1, 2, 3, AND 4 TO NO MORE THAN 650,000 GALLONS OF ORGANIC LIQUID IN ANY ONE DAY.

[RULE 462]

6. THE OPERATOR SHALL LIMIT THE COMBINED THROUGHPUT OF ALL MATERIALS IN TANK TRUCK LOADING RACKS NOS. 1, 2, 3, AND 4 TO NO MORE THAN 1,600,000 GALLONS IN ANY ONE DAY.

[RULE 1303(b)(2) - OFFSET]

7. THE OPERATOR SHALL USE TOTALIZER FLOW METERS TO MEASURE THE LOADING THROUGHPUT TO COMPLY WITH CONDITION NO. 5.

[RULE 1303(b)(2) - OFFSET]

8. IN ADDITION TO THE RECORDS REQUIRED IN RULE 462, THE LOADING THROUGHPUT RECORDS SHALL BE MAINTAINED FOR AT LEAST TWO YEARS IN A FORMAT APPROVE BY THE DISTRICT, AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.

[RULE 462]

ALL COMPONENTS IN VOC SERVICE, EXCEPT THOSE SPECIFICALLY EXEMPTED IN RULE 1173, SHALL BE INSPECTED MONTHLY USING EPA REFERENCE METHOD 21. THE OPERATOR MAY REVERT TO A QUARTERLY INSPECTION UPON DISTRICT APPROVAL, AFTER TWO CONSECUTIVE MONTHS OF INSPECTIONS IN WHICH ONLY TWO PERCENT OR LESS OF THE FUGITIVE COMPONENTS ARE DETECTED TO LEAK OVER 500 PPM_v ABOVE BACKGROUND.

ALL COMPONENTS IN VOC SERVICE, WITH A LEAK GREATER THAN 500 PPM_v BUT LESS THAN 1,000 PPM_v MEASURED AS METHANE ABOVE BACKGROUND USING EPA REFERENCE METHOD 21, SHALL BE REPAIRED WITHIN 14 DAYS OF DETECTION. A LEAK OF 1,000 PPM_v OR GREATER SHALL BE REPAIRED ACCORDING TO RULE 1173.

THE RECORDS OF THE MONTHLY INSPECTION, SUBSEQUENT REPAIRS AND RE-INSPECTIONS, IF ANY, SHALL BE MAINTAINED FOR TWO YEARS (FIVE YEARS FOR A TITLE V FACILITY) IN A FORMAT APPROVED BY THE DISTRICT, AND SHALL BE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST

[RULE 1303(a)(1)-BACT]

9. THIS PERMIT TO CONSTRUCT SHALL EXPIRE ONE YEAR FROM THE DATE OF ISSUANCE UNLESS AN EXTENSION IS GRANTED BY THE EXECUTIVE OFFICER.

[RULE 205]

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

Periodic Monitoring: NONE

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC/TOC: 35 MG/L GASOLINE LOADED 40 CFR 60 SUBPART XX
VOC: 0.08 LBS/1000 GAL. ORGANIC LIQUID LOADED RULE 462

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

PERMIT TO CONSTRUCT

A/N 555131
Granted x/xx/2014

Equipment Description:

MODIFICATION OF TANK TRUCK LOADING RACK NO. 2, FOR PETROLEUM PRODUCTS, CONSISTING OF:

1. FOUR 4" EMCO-WHEATON TYPE BOTTOM LOADING CONNECTOR.
2. TWO 3" VAPOR CONNECTIONS.
3. THREE METERS
4. LOADING PUMPS, COMMON TO RACKS NO. 1, NO. 3 AND NO. 4

TWO 25 H.P. CENTRIFUGAL, WITH MECHANICAL SEALS

TWO 25 H.P. CENTRIFUGAL, WITH MECHANICAL SEALS

TWO 25 H.P. CENTRIFUGAL, WITH MECHANICAL SEALS

BY THE ADDITION OF:

1. TWO BIO-DIESEL METERS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL VENT ALL VENT GASES FROM THIS LOADING RACK TO THE VAPOR CONTROL SYSTEM WHICH SHALL HAVE A VALID PERMIT TO RECEIVE THE VENT GASES FROM THIS EQUIPMENT AND SHALL ALSO BE CARB CERTIFIED. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS THE VAPOR COLLECTION BLADDER TANK HAS A SUFFICIENT CAPACITY TO RECEIVE VENT GASES FROM THIS EQUIPMENT.

[RULE 462, RULE 1303 (a) (1) - BACT, 40 CFR 60 SUBPART XX]

FACILITY PERMIT TO OPERATE CHEMOIL TERMINALS CORPORATION

4. THE OPERATOR SHALL NOT USE THIS EQUIPMENT TO LOAD PURE ORGANIC COMPOUNDS OR LIQUIDS, EXCEPT ETHANOL.

[RULE 204]

5. THE OPERATOR SHALL LIMIT THE COMBINED THROUGHPUT OF TANK TRUCK LOADING RACKS NOS. 1, 2, 3, AND 4 TO NO MORE THAN 650,000 GALLONS OF ORGANIC LIQUID IN ANY ONE DAY.

[RULE 462]

6. THE OPERATOR SHALL LIMIT THE COMBINED THROUGHPUT OF ALL MATERIALS IN TANK TRUCK LOADING RACKS NOS. 1, 2, 3, AND 4 TO NO MORE THAN 1,600,000 GALLONS IN ANY ONE DAY.

[RULE 1303(b)(2) - OFFSET]

7. THE OPERATOR SHALL USE TOTALIZER FLOW METERS TO MEASURE THE LOADING THROUGHPUT TO COMPLY WITH CONDITION NO. 5.

[RULE 1303(b)(2) - OFFSET]

8. IN ADDITION TO THE RECORDS REQUIRED IN RULE 462, THE LOADING THROUGHPUT RECORDS SHALL BE MAINTAINED FOR AT LEAST TWO YEARS IN A FORMAT APPROVED BY THE DISTRICT, AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.

[RULE 462]

9. THIS PERMIT TO CONSTRUCT SHALL EXPIRE ONE YEAR FROM THE DATE OF ISSUANCE UNLESS AN EXTENSION IS GRANTED BY THE EXECUTIVE OFFICER.

[RULE 205]

Periodic Monitoring: NONE

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC/TOC: 35 MG/L GASOLINE LOADED 40 CFR 60 SUBPART XX
VOC: 0.08 LBS/1000 GAL. ORGANIC LIQUID LOADED RULE 462

