

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

Facility Equipment and Requirements (Section D)

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

Application Number	Permit to Operate Number	Equipment description
409320	F66301	Lithographic Printing Press, Heidelberg, with I. R. Dryer
424941	F66302	Lithographic Printing Press, Heidelberg, with I. R. Dryer
427793	F69028	Lithographic Printing Press, Heidelberg, I.R. Dry & U.V. curing units
556339		Lithographic Printing Press, Heidelberg, with U.V. curing unit

NOTE: EQUIPMENT LISTED ABOVE THAT HAVE NO CORRESPONDING PERMITS TO OPERATE NUMBER ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT.

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

FACILITY WIDE CONDITION(S)

Condition(s):

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:
 - A. AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGELMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
 - B. OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (A) OF THIS CONDITION.
[RULE 401]
2. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMISSIONS FROM THIS FACILITY SHALL NOT EXCEED 2040 POUNDS IN ANY ONE CALENDAR MONTH.
[RULE 1303(b)(2)-OFFSET]
3. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS FACILITY TO VERIFY THE CALENDAR MONTHLY VOC EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS).
[RULE 109, 1303(b)(2)-OFFSET]
4. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC EMISSIONS FOR THE MONTH FROM ALL EQUIPMENT AND OPERATIONS COVERED BY THE MONTHLY LIMIT. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.
[RULE 109, 1303(b)(2)-OFFSET]
5. THE OPERATOR SHALL MAINTAIN A SINGLE LIST THAT INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC-CONTAINING MATERIALS REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.
[RULE 109, 1303(b)(2)-OFFSET]
6. THE OPERATOR SHALL RETAIN ALL PURCHASE INVOICES FOR ALL VOC-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE VOC-CONTAINING MATERIAL REMOVED FROM THE FACILITY, FOR AT LEAST FIVE YEARS.
[RULE 109, 1303(b)(2)-OFFSET]
7. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT THAT IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED AT THE FACILITY FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

8. MATERIAL SAFETY DATA SHEETS FOR ALL VOC-CONTAINING MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

PERMIT TO OPERATE

**Permit No. F66301
A/N 409320**

Equipment Description:

LITHOGRAPHIC PRINTING AND DRYING SYSTEM CONSISTING OF:

1. PRESS, HEIDELBERG, MODEL CD102+6+LXCD, SERIAL NO. 542442, 6-COLOR PLUS COATER, 40-INCH SHEET FED, 126.7 HP.
2. DRYER, INFRA-RED, WITH 6 INFRA-RED LAMPS, 36 KW TOTAL.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. FOUNTAIN SOLUTION USED IN THIS EQUIPMENT SHALL NOT CONTAIN MORE THAN 8 PERCENT OF VOC BY VOLUME, AS APPLIED, INCLUDING WATER AND EXEMPT SOLVENTS.
[RULE 1303(a)(1)-BACT]
4. THE COMPOSITE VAPOR PRESSURE OF THE VOC IN THE BLANKET WASHES AND ROLLER WASHES USED ON THIS EQUIPMENT SHALL NOT EXCEED 10 MM HG @ 20 DEGREES CELSIUS.
[RULE 1303(a)(1)-BACT]
5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE 1 WITH AN EFFECTIVE DATE OF MARCH 17, 2000 OR EARLIER, WITH THE EXCEPTION OF AMMONIA, ETHYLENE GLYCOL MONOBUTYL ETHER, ETHYLENE GLYCOL, ISOPROPNOL, NAPHTHALENE, PHOSPHORIC ACID, AND XYLENES.
[RULE 1401]
6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE FOLLOWING ON A DAILY BASIS:
 - A. USAGE OF INKS, FOUNTAIN SOLUTIONS INCLUDING WATER, ROLLER WASHES, BLANKET WASHES, AND ALL OTHER MATERIALS CONTAINING VOC, IN GALLONS.
 - B. DENSITY OF INKS, IN POUNDS PER GALLON, AND PERCENTAGE BY WEIGHT OF LITHOGRAPHIC OILS IN THE INKS.

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

- C. INK ABSORPTION FACTOR AS SPECIFIED BY CURRENT SCAQMD GUIDELINES.
- D. EMISSIONS IN POUNDS OF VOC.
[RULE 109, 1303(b)(2)-OFFSET]
7. PERMIT SHIELD: NOT WITHSTANDING THE OTHER REQUIREMENTS AND CONDITIONS IN THIS PERMIT, THIS EQUIPMENT IS NOT SUBJECT TO THE FOLLOWING RULE REQUIREMENTS:

RULE 1128, 3/8/1996

COMPLIANCE WITH THE CONDITIONS OF THIS TITLE V PERMIT SHALL BE DEEMED IN COMPLIANCE WITH ANY REGULATORY REQUIREMENTS APPLICABLE AS OF THE DATE OF PERMIT ISSUANCE TO THIS EQUIPMENT, PROVIDED THAT SUCH REGULATORY REQUIREMENTS ARE INCLUDED AND SPECIFICALLY IDENTIFIED IN THIS PERMIT. NOTHING IN THIS PERMIT OR IN ANY PERMIT SHIELD CAN ALTER OR AFFECT: (a) UNDER SECTION 303 OF THE FEDERAL CLEAN AIR ACT, THE PROVISIONS FOR EMERGENCY ORDERS; (b) THE LIABILITY OF THE OPERATOR FOR ANY VIOLATION OF APPLICABLE REQUIREMENTS PRIOR TO OR AT THE TIME OF PERMIT ISSUANCE; (c) THE APPLICABLE REQUIREMENTS OF THE ACID RAIN PROGRAM; (d) THE ABILITY OF EPA TO OBTAIN INFORMATION FROM THE OPERATOR PURSUANT TO SECTION 114 OF THE FEDERAL CLEAN AIR ACT; (e) THE APPLICABILITY OF STATE OR LOCAL REQUIREMENTS THAT ARE NOT "APPLICABLE REQUIREMENTS", AS DEFINED IN RULE 3000, AT THE TIME OF PERMIT ISSUANCE BUT WHICH DO NOT APPLY TO THE FACILITY, SUCH AS TOXICS REQUIREMENTS UNIQUE TO THE STATE; OR (f) THE APPLICABILITY OF REGULATORY REQUIREMENTS WITH COMPLIANCE DATES AFTER THE PERMIT ISSUANCE DATE. THIS PERMIT SHIELD SHALL NOT APPLY TO ANY OPERATIONAL CHANGE MADE PURSUANT TO THE OPERATIONAL FLEXIBILITY PROVISIONS OF DISTRICT RULE 3005.
[RULE 3004 (c) - PERMIT SHIELD]

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
VOC: RULE 1130, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

PERMIT TO OPERATE

Permit No. F66302
A/N 424941

Equipment Description:

LITHOGRAPHIC PRESS SYSTEM CONSISTING OF:

1. PRESS, HEIDELBERG, MODEL CD-74-6+LX, 6-COLOR PLUS COATER, 29-INCH SHEET FED, 74.76 HP TOTAL.
2. DRYER, TECHNOTRANS, INFRA-RED, 10 LAMPS AT 2 KW EACH, 20 KW TOTAL.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE FOUNTAIN SOLUTION USED IN THIS EQUIPMENT SHALL NOT EXCEED 8 PERCENT OF VOC BY VOLUME, AS APPLIED, INCLUDING WATER AND EXEMPT SOLVENTS.
[RULE 1303(a)(1)-BACT]
4. THE COMPOSITE VAPOR PRESSURE OF THE VOCS IN THE BLANKET WASHES AND ROLLER WASHES USED ON THIS EQUIPMENT SHALL NOT EXCEED 10 MM HG @ 20 DEGREES CELSIUS.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS TO THE ATMOSPHERE FROM THIS EQUIPMENT SHALL NOT EXCEED 900 POUNDS PER CALENDAR MONTH.
[RULE 1303(b)(2)-OFFSET]
6. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF FEBRUARY 7, 2003, OR EARLIER, WITH THE EXCEPTION OF AMMONIA, ETHYLENE GLYCOL MONOBUTYL ETHER, ETHYLENE GLYCOL, ISOPROPNOL, NAPHTHALENE, PHOSPHORIC ACID, AND XYLENE.
[RULE 1401]
7. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE FOLLOWING ON A DAILY BASIS:

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

- A. USAGE OF INKS, FOUNTAIN SOLUTIONS INCLUDING WATER, ROLLER WASHES, BLANKET WASHES, AND ALL OTHER MATERIALS CONTAINING VOC, IN GALLONS.
 - B. DENSITY OF INKS, IN POUNDS PER GALLON, AND PERCENTAGE BY WEIGHT OF LITHOGRAPHIC OILS IN THE INKS.
 - C. INK ABSORPTION FACTOR AS SPECIFIED BY CURRENT SCAQMD GUIDELINES.
 - D. EMISSIONS IN POUNDS OF VOC.
[RULE 109, 1303(b)(2)-OFFSET]
8. PERMIT SHIELD: NOT WITHSTANDING THE OTHER REQUIREMENTS AND CONDITIONS IN THIS PERMIT, THIS EQUIPMENT IS NOT SUBJECT TO THE FOLLOWING RULE REQUIREMENTS:

RULE 1128, 3/8/1996

COMPLIANCE WITH THE CONDITIONS OF THIS TITLE V PERMIT SHALL BE DEEMED IN COMPLIANCE WITH ANY REGULATORY REQUIREMENTS APPLICABLE AS OF THE DATE OF PERMIT ISSUANCE TO THIS EQUIPMENT, PROVIDED THAT SUCH REGULATORY REQUIREMENTS ARE INCLUDED AND SPECIFICALLY IDENTIFIED IN THIS PERMIT. NOTHING IN THIS PERMIT OR IN ANY PERMIT SHIELD CAN ALTER OR AFFECT: (a) UNDER SECTION 303 OF THE FEDERAL CLEAN AIR ACT, THE PROVISIONS FOR EMERGENCY ORDERS; (b) THE LIABILITY OF THE OPERATOR FOR ANY VIOLATION OF APPLICABLE REQUIREMENTS PRIOR TO OR AT THE TIME OF PERMIT ISSUANCE; (c) THE APPLICABLE REQUIREMENTS OF THE ACID RAIN PROGRAM; (d) THE ABILITY OF EPA TO OBTAIN INFORMATION FROM THE OPERATOR PURSUANT TO SECTION 114 OF THE FEDERAL CLEAN AIR ACT; (e) THE APPLICABILITY OF STATE OR LOCAL REQUIREMENTS THAT ARE NOT "APPLICABLE REQUIREMENTS", AS DEFINED IN RULE 3000, AT THE TIME OF PERMIT ISSUANCE BUT WHICH DO NOT APPLY TO THE FACILITY, SUCH AS TOXICS REQUIREMENTS UNIQUE TO THE STATE; OR (f) THE APPLICABILITY OF REGULATORY REQUIREMENTS WITH COMPLIANCE DATES AFTER THE PERMIT ISSUANCE DATE. THIS PERMIT SHIELD SHALL NOT APPLY TO ANY OPERATIONAL CHANGE MADE PURSUANT TO THE OPERATIONAL FLEXIBILITY PROVISIONS OF DISTRICT RULE 3005.
[RULE 3004 (c) - PERMIT SHIELD]

Emissions And Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
 - VOC: RULE 1130, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

PERMIT TO OPERATE

Permit No. F69028
A/N 427793

Equipment Description:

LITHOGRAPHIC PRINTING AND DRYING SYSTEM CONSISTING OF:

1. PRESS, HEIDELBERG, MODEL CD102+6+LX, 6-COLOR PLUS COATER, 40-INCH SHEET WIDTH.
2. DRYER, INFRA-RED, 20 KW TOTAL.
3. U.V. CURING UNIT, 135.6 KW TOTAL.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. FOUNTAIN SOLUTION USED IN THIS EQUIPMENT SHALL NOT EXCEED 8 PERCENT OF VOC BY VOLUME, AS APPLIED, INCLUDING WATER AND EXEMPT SOLVENTS.
[RULE 1303(a)(1)-BACT]
4. THE COMPOSITE VAPOR PRESSURE OF THE VOC IN THE BLANKET WASHES AND ROLLER WASHES USED ON THIS EQUIPMENT SHALL NOT EXCEED 10 MM HG @ 20 DEGREES CELSIUS.
[RULE 1303(a)(1)-BACT]
5. THE MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE 1 WITH AN EFFECTIVE DATE OF MAY 2, 2003 OR EARLIER, EXCEPT AMMONIA, ETHYLENE GLYCOL MONOBUTYL ETHER, ETHYLENE GLYCOL, ISOPROPANOL, NAPHTHALENE, PHOSPHORIC ACID, AND XYLENE.
[RULE 1401]
6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE FOLLOWING ON A DAILY BASIS:
 - A. USAGE OF INKS, FOUNTAIN SOLUTIONS INCLUDING WATER, ROLLER WASHES, BLANKET WASHES, AND ALL OTHER MATERIALS CONTAINING VOC, IN GALLONS.
 - B. DENSITY OF INKS, IN POUNDS PER GALLON, AND PERCENTAGE BY WEIGHT OF LITHOGRAPHIC OILS IN THE INKS.

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

C. INK ABSORPTION FACTOR AS SPECIFIED BY CURRENT SCAQMD GUIDELINES.

D. EMISSIONS IN POUNDS OF VOC.
[RULE 109, 1303(b)(2)-OFFSET]

7. PERMIT SHIELD: NOT WITHSTANDING THE OTHER REQUIREMENTS AND CONDITIONS IN THIS PERMIT, THIS EQUIPMENT IS NOT SUBJECT TO THE FOLLOWING RULE REQUIREMENTS:

RULE 1128, 3/8/1996

COMPLIANCE WITH THE CONDITIONS OF THIS TITLE V PERMIT SHALL BE DEEMED IN COMPLIANCE WITH ANY REGULATORY REQUIREMENTS APPLICABLE AS OF THE DATE OF PERMIT ISSUANCE TO THIS EQUIPMENT, PROVIDED THAT SUCH REGULATORY REQUIREMENTS ARE INCLUDED AND SPECIFICALLY IDENTIFIED IN THIS PERMIT. NOTHING IN THIS PERMIT OR IN ANY PERMIT SHIELD CAN ALTER OR AFFECT: (a) UNDER SECTION 303 OF THE FEDERAL CLEAN AIR ACT, THE PROVISIONS FOR EMERGENCY ORDERS; (b) THE LIABILITY OF THE OPERATOR FOR ANY VIOLATION OF APPLICABLE REQUIREMENTS PRIOR TO OR AT THE TIME OF PERMIT ISSUANCE; (c) THE APPLICABLE REQUIREMENTS OF THE ACID RAIN PROGRAM; (d) THE ABILITY OF EPA TO OBTAIN INFORMATION FROM THE OPERATOR PURSUANT TO SECTION 114 OF THE FEDERAL CLEAN AIR ACT; (e) THE APPLICABILITY OF STATE OR LOCAL REQUIREMENTS THAT ARE NOT "APPLICABLE REQUIREMENTS", AS DEFINED IN RULE 3000, AT THE TIME OF PERMIT ISSUANCE BUT WHICH DO NOT APPLY TO THE FACILITY, SUCH AS TOXICS REQUIREMENTS UNIQUE TO THE STATE; OR (f) THE APPLICABILITY OF REGULATORY REQUIREMENTS WITH COMPLIANCE DATES AFTER THE PERMIT ISSUANCE DATE. THIS PERMIT SHIELD SHALL NOT APPLY TO ANY OPERATIONAL CHANGE MADE PURSUANT TO THE OPERATIONAL FLEXIBILITY PROVISIONS OF DISTRICT RULE 3005.

[RULE 3004 (c) - PERMIT SHIELD]

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109

VOC: RULE 1130, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

PERMIT TO CONSTRUCT

A/N 556339
Granted as of xx/xx/xx

Equipment Description:

LITHOGRAPHIC PRINTING AND CURING SYSTEM CONSISTING OF:

1. PRESS, HEIDELBERG, MODEL XL 106-7+LYY-LX3_UV, SEVEN COLOR, 41.73-INCH SHEET WIDTH.
2. U.V. CURING UNIT, 124.8 KW TOTAL.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TMES.
[RULE 204]
3. FOUNTAIN SOLUTION USED IN THIS EQUIPMENT SHALL NOT EXCEED 8 PERCENT OF VOC BY VOLUME, AS APPLIED, INCLUDING WATER AND EXEMPT SOLVENTS.
[RULE 1303(a)(1)-BACT]
4. THE COMPOSITE VAPOR PRESSURE OF THE VOC IN THE BLANKET WASHES AND ROLLER WASHES USED ON THIS EQUIPMENT SHALL NOT EXCEED 10 MM HG @ 20 DEGREES CELSIUS.
[RULE 1303(a)(1)-BACT]
5. THE MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE 1 WITH AN EFFECTIVE DATE OF SEPTEMBER 10, 2010 OR EARLIER, EXCEPT AMMONIA, ETHYLENE GLYCOL MONOBUTYL ETHER, ISOPROPYL ALCOHOL, PHOSPHORIC ACID, ETHYL BENZENE, STYRENE, ACRYLIC ACID, AND XYLENE.
[RULE 1401]
6. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS TO THE ATMOSPHERE FROM THIS EQUIPMENT SHALL NOT EXCEED 900 POUNDS PER CALENDAR MONTH.
[RULE 1303(b)(2)-OFFSET]
7. THE TOTAL QUANTITY OF ETHYL BENZENE EMISSIONS TO THE ATMOSPHERE FROM THIS EQUIPMENT SHALL NOT EXCEED 120 POUNDS PER CALENDAR YEAR.
[RULE 1401]

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE FOLLOWING ON A DAILY BASIS:
 - A. USAGE OF INKS, FOUNTAIN SOLUTIONS INCLUDING WATER, ROLLER WASHES, BLANKET WASHES, AND ALL OTHER MATERIALS CONTAINING VOC, IN GALLONS.
 - B. DENSITY OF INKS, IN POUNDS PER GALLON, AND PERCENTAGE BY WEIGHT OF LITHOGRAPHIC OILS IN THE INKS.
 - C. INK ABSORPTION FACTOR AS SPECIFIED BY CURRENT SCAQMD GUIDELINES.
 - D. EMISSIONS IN POUNDS OF VOC.
 - E. EMISSIONS IN POUNDS OF ETHYL BENZENE
[RULE 109, 1303(b)(2)-OFFSET]
9. WITHIN 7 DAYS OF OPERATION OF THIS EQUIPMENT, LITHOGRAPHIC PRINTING SYSTEM OPERATING UNDER PERMIT NO. F66302 SHALL BE REMOVED FROM SERVICE.
[RULE 1303(b)(2)-OFFSET]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1130, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

Periodic Monitoring:

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (g/l) OF MATERIALS FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS SUPPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

FOR OTHER ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS APPLIED IN GRAMS PER LITER (g/l) OF MATERIALS USED FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS APPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

[RULE 3004 (a) (4)]

Emissions And Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, PRE-PRESS PREP AREA.

Conditions:

1. PERMIT SHIELD. NOT WITHSTANDING THE OTHER REQUIREMENTS AND CONDITIONS IN THIS PERMIT, THIS EQUIPMENT IS NOT SUBJECT TO THE FOLLOWING RULE REQUIREMENTS:

RULE 1128, 3/8/1996

COMPLIANCE WITH THE CONDITIONS OF THIS TITLE V PERMIT SHALL BE DEEMED IN COMPLIANCE WITH ANY REGULATORY REQUIREMENTS APPLICABLE AS OF THE DATE OF PERMIT ISSUANCE TO THIS EQUIPMENT, PROVIDED THAT SUCH REGULATORY REQUIREMENTS ARE INCLUDED AND SPECIFICALLY IDENTIFIED IN THIS PERMIT. NOTHING IN THIS PERMIT OR IN ANY PERMIT SHIELD CAN ALTER OR AFFECT: (a) UNDER SECTION 303 OF THE FEDERAL CLEAN AIR ACT, THE PROVISIONS FOR EMERGENCY ORDERS; (b) THE LIABILITY OF THE OPERATOR FOR ANY VIOLATION OF APPLICABLE REQUIREMENTS PRIOR TO OR AT THE TIME OF PERMIT ISSUANCE; (c) THE APPLICABLE REQUIREMENTS OF THE ACID RAIN PROGRAM; (d) THE ABILITY OF EPA TO OBTAIN INFORMATION FROM THE OPERATOR PURSUANT TO SECTION 114 OF THE FEDERAL CLEAN AIR ACT; (e) THE APPLICABILITY OF STATE OR LOCAL REQUIREMENTS THAT ARE NOT "APPLICABLE REQUIREMENTS", AS DEFINED IN RULE 3000, AT THE TIME OF PERMIT ISSUANCE BUT WHICH DO NOT APPLY TO THE FACILITY, SUCH AS TOXICS REQUIREMENTS UNIQUE TO THE STATE; OR (f) THE APPLICABILITY OF REGULATORY REQUIREMENTS WITH COMPLIANCE DATES AFTER THE PERMIT ISSUANCE DATE. THIS PERMIT SHIELD SHALL NOT APPLY TO ANY OPERATIONAL CHANGE MADE PURSUANT TO THE OPERATIONAL FLEXIBILITY PROVISIONS OF DISTRICT RULE 3005.
[RULE 3004 (c) - PERMIT SHIELD]

Emissions And Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1130, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, PRINTING EQUIPMENT, LOW-USE OR EMISSIONS, WITH RELATED COATING, LAMINATING, GLUING, AND DRYING EQUIPMENT.

Emissions And Requirements:

Conditions:

1. PERMIT SHIELD. NOT WITHSTANDING THE OTHER REQUIREMENTS AND CONDITIONS IN THIS PERMIT, THIS EQUIPMENT IS NOT SUBJECT TO THE FOLLOWING RULE REQUIREMENTS:

RULE 1128, 3/8/1996

COMPLIANCE WITH THE CONDITIONS OF THIS TITLE V PERMIT SHALL BE DEEMED IN COMPLIANCE WITH ANY REGULATORY REQUIREMENTS APPLICABLE AS OF THE DATE OF PERMIT ISSUANCE TO THIS EQUIPMENT, PROVIDED THAT SUCH REGULATORY REQUIREMENTS ARE INCLUDED AND SPECIFICALLY IDENTIFIED IN THIS PERMIT. NOTHING IN THIS PERMIT OR IN ANY PERMIT SHIELD CAN ALTER OR AFFECT: (a) UNDER SECTION 303 OF THE FEDERAL CLEAN AIR ACT, THE PROVISIONS FOR EMERGENCY ORDERS; (b) THE LIABILITY OF THE OPERATOR FOR ANY VIOLATION OF APPLICABLE REQUIREMENTS PRIOR TO OR AT THE TIME OF PERMIT ISSUANCE; (c) THE APPLICABLE REQUIREMENTS OF THE ACID RAIN PROGRAM; (d) THE ABILITY OF EPA TO OBTAIN INFORMATION FROM THE OPERATOR PURSUANT TO SECTION 114 OF THE FEDERAL CLEAN AIR ACT; (e) THE APPLICABILITY OF STATE OR LOCAL REQUIREMENTS THAT ARE NOT "APPLICABLE REQUIREMENTS", AS DEFINED IN RULE 3000, AT THE TIME OF PERMIT ISSUANCE BUT WHICH DO NOT APPLY TO THE FACILITY, SUCH AS TOXICS REQUIREMENTS UNIQUE TO THE STATE; OR (f) THE APPLICABILITY OF REGULATORY REQUIREMENTS WITH COMPLIANCE DATES AFTER THE PERMIT ISSUANCE DATE. THIS PERMIT SHIELD SHALL NOT APPLY TO ANY OPERATIONAL CHANGE MADE PURSUANT TO THE OPERATIONAL FLEXIBILITY PROVISIONS OF DISTRICT RULE 3005.
[RULE 3004 (c) - PERMIT SHIELD]

Emissions And Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1130, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, INKJET PRINTING EQUIPMENT.

Conditions:

1. PERMIT SHIELD. NOT WITHSTANDING THE OTHER REQUIREMENTS AND CONDITIONS IN THIS PERMIT, THIS EQUIPMENT IS NOT SUBJECT TO THE FOLLOWING RULE REQUIREMENTS:

RULE 1128, 3/8/1996
RULE 1130, 10/8/99

COMPLIANCE WITH THE CONDITIONS OF THIS TITLE V PERMIT SHALL BE DEEMED IN COMPLIANCE WITH ANY REGULATORY REQUIREMENTS APPLICABLE AS OF THE DATE OF PERMIT ISSUANCE TO THIS EQUIPMENT, PROVIDED THAT SUCH REGULATORY REQUIREMENTS ARE INCLUDED AND SPECIFICALLY IDENTIFIED IN THIS PERMIT. NOTHING IN THIS PERMIT OR IN ANY PERMIT SHIELD CAN ALTER OR AFFECT: (a) UNDER SECTION 303 OF THE FEDERAL CLEAN AIR ACT, THE PROVISIONS FOR EMERGENCY ORDERS; (b) THE LIABILITY OF THE OPERATOR FOR ANY VIOLATION OF APPLICABLE REQUIREMENTS PRIOR TO OR AT THE TIME OF PERMIT ISSUANCE; (c) THE APPLICABLE REQUIREMENTS OF THE ACID RAIN PROGRAM; (d) THE ABILITY OF EPA TO OBTAIN INFORMATION FROM THE OPERATOR PURSUANT TO SECTION 114 OF THE FEDERAL CLEAN AIR ACT; (e) THE APPLICABILITY OF STATE OR LOCAL REQUIREMENTS THAT ARE NOT "APPLICABLE REQUIREMENTS", AS DEFINED IN RULE 3000, AT THE TIME OF PERMIT ISSUANCE BUT WHICH DO NOT APPLY TO THE FACILITY, SUCH AS TOXICS REQUIREMENTS UNIQUE TO THE STATE; OR (f) THE APPLICABILITY OF REGULATORY REQUIREMENTS WITH COMPLIANCE DATES AFTER THE PERMIT ISSUANCE DATE. THIS PERMIT SHIELD SHALL NOT APPLY TO ANY OPERATIONAL CHANGE MADE PURSUANT TO THE OPERATIONAL FLEXIBILITY PROVISIONS OF DISTRICT RULE 3005.
[RULE 3004 (c) - PERMIT SHIELD]

Emissions And Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 442
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

SECTION K: TITLE V Administration

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
- (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.
 - (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
 - (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
- (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]

10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]

12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]

13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

SECTION K: TITLE V Administration

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]

15. Nothing in this permit or in any permit shield can alter or affect:
 - (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]

16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

SECTION K: TITLE V Administration EMERGENCY PROVISIONS

17. An emergency¹ constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
 - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
 - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
 - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
 - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
 - (B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

¹ "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

SECTION K: TITLE V Administration RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
- (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
 - (B) The date(s) analyses were performed;
 - (C) The company or entity that performed the analyses;
 - (D) The analytical techniques or methods used;
 - (E) The results of such analyses; and
 - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:
- (A) Breakdowns shall be reported as required by Rule 430 – Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

SECTION K: TITLE V Administration

- (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.
- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
- (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

SECTION K: TITLE V Administration

- (B) The compliance status during the reporting period;
- (C) Whether compliance was continuous or intermittent;
- (D) The method(s) used to determine compliance over the reporting period and currently, and
- (E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn:
Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 109	5-2-2003	Federally enforceable
RULE 1113	7-13-2007	Federally enforceable
RULE 1113	9-6-2013	Non federally enforceable
RULE 1130	10-8-1999	Federally enforceable
RULE 1171	11-7-2003	Federally enforceable
RULE 1171	2-1-2008	Federally enforceable
RULE 1171	5-1-2009	Non federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303(a)(1)-BACT	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	12-6-2002	Non federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1401	2-7-2003	Non federally enforceable
RULE 1401	3-17-2000	Non federally enforceable
RULE 1401	5-2-2003	Non federally enforceable
RULE 1401	9-10-2010	Non federally enforceable
RULE 204	10-8-1993	Federally enforceable
RULE 217	1-5-1990	Federally enforceable
RULE 219	5-3-2013	Non federally enforceable
RULE 219	9-4-1981	Federally enforceable
RULE 3002	11-14-1997	Federally enforceable
RULE 3002	11-5-2010	Non federally enforceable

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 3003	11-14-1997	Federally enforceable
RULE 3003	11-5-2010	Non federally enforceable
RULE 3004	12-12-1997	Federally enforceable
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3004(c)-Permit Shield	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3005	11-5-2010	Non federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	6-1-2012	Non federally enforceable
RULE 401	11-9-2001	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 442	12-15-2000	Federally enforceable
RULE 701	6-13-1997	Federally enforceable

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007]

- (1) Except as provided in paragraphs (c)(2), (c)(3), (c)(4), and specified coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage any architectural coating for use in the District which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, and no person shall apply or solicit the application of any architectural coating within the District that exceeds 250 grams of VOC per liter of coating as calculated in this paragraph.
- (2) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified, and no person shall apply or solicit the application of any architectural coating within the District that exceeds the VOC limit as specified in this paragraph. No person shall apply or solicit the application within the District of any industrial maintenance coatings, except anti-graffiti coatings, for residential use or for use in areas such as office space and meeting rooms of industrial, commercial or institutional facilities not exposed to such extreme environmental conditions described in the definition of industrial maintenance coatings; or of any rust-preventative coating for industrial use, unless such a rust preventative coating complies with the Industrial Maintenance Coating VOC limit specified in the Table of Standards.

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007] TABLE OF STANDARDS VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water and Less Exempt Compounds

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Bond Breakers	350							
Clear Wood Finishes	350					275		
Varnish	350					275		
Sanding Sealers	350					275		
Lacquer	680	550			275			
Clear Brushing Lacquer	680				275			
Concrete-Curing Compounds	350						100	
Concrete-Curing Compounds For Roadways and Bridges**	350							
Dry-Fog Coatings	400						150	
Fire-Proofing Exterior Coatings	450	350						
Fire-Retardant Coatings***								
Clear	650							
Pigmented	350							
Flats	250	100						50
Floor Coatings	420		100			50		
Graphic Arts (Sign) Coatings	500							
Industrial Maintenance (IM) Coatings	420			250		100		
High Temperature IM Coatings			420					
Zinc-Rich IM Primers	420		340			100		
Japans/Faux Finishing Coatings	700	350						
Magnesite Cement Coatings	600	450						
Mastic Coatings	300							
Metallic Pigmented Coatings	500							
Multi-Color Coatings	420	250						
Nonflat Coatings	250		150			50		

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007]

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Nonflat High Gloss	250		150				50	
Pigmented Lacquer	680	550			275			
Pre-Treatment Wash Primers	780		420					
Primers, Sealers, and Undercoaters	350		200			100		
Quick-Dry Enamels	400		250			150	50	
Quick-Dry Primers, Sealers, and Undercoaters	350		200			100		
Recycled Coatings			250					
Roof Coatings	300		250		50			
Roof Coatings, Aluminum	500				100			
Roof Primers, Bituminous	350		350					
Rust Preventative Coatings	420		400			100		
Shellac								
Clear	730							
Pigmented	550							
Specialty Primers	350					250	100	
Stains	350		250				100	
Stains, Interior	250							
Swimming Pool Coatings								
Repair	650		340					
Other	340							
Traffic Coatings	250	150					100	
Waterproofing Sealers	400		250			100		
Waterproofing	400					100		
Concrete/Masonry Sealers								
Wood Preservatives								
Below-Ground	350							
Other	350							

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.

** Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

*** The Fire-Retardant Coating category will be eliminated on January 1, 2007 and subsumed by the coating category for which they are formulated.

**FACILITY PERMIT TO OPERATE
THORO PACKAGING INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 07-13-2007]**

**TABLE OF STANDARDS (cont.)
VOC LIMITS**

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 09-06-2013]

- (1) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6), no person shall supply, sell, offer for sale, market, manufacture, blend, repackage, apply, store at a worksite, or solid the application of any architectural coating within in the District:
 - (A) That is listed in the Table of Standards 1 and contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified; or
 - (B) That is not listed in the Table of Standards 1, and contains VOC (excluding any colorant added to tint bases) in excess of 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, until January 1, 2014, at which time the limit drops to 50 grams of VOC per liter of coating, less water, less exempt compounds (0.42 pounds per gallon).
- (2) No person within the District shall add colorant at the point of sale that is listed in the Table of Standards 2 and contains VOC in excess of the corresponding VOC limit specified in the Table of Standards 2, after the effective date specified.

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 09-06-2013]

TABLE OF STANDARDS 1 VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water and Less Exempt Compounds

COATING CATEGORY	Ceiling Limit ¹	Current Limit ²	Effective Date		
			7/1/08	1/1/12	1/1/14
Bond Breakers		350			
Clear Wood Finishes		275			
Varnish	350	275			
Sanding Sealers	350	275			
Lacquer		275			
Concrete-Curing Compounds		100			
Concrete-Curing Compounds For Roadways and Bridges ³		350			
Concrete Surface Retarder		250			50
Driveway Sealer		100		50	
Dry-Fog Coatings		150			50
Faux Finishing Coatings					
Clear Topcoat		350		200	100
Decorative Coatings		350			
Glazes		350			
Japan		350			
Trowel Applied Coatings		350		150	50
Fire-Proofing Coatings		350			150
Flats	250	50	50		
Floor Coatings	100	50			
Form Release Compound		250			100
Graphic Arts (Sign) Coatings		500			150
Industrial Maintenance (IM) Coatings	420	100			
High Temperature IM Coatings		420			
Non-Sacrificial/Anti-Graffiti Coatings		100			
Zinc-Rich IM Primers		100			
Magnesite Cement Coatings		450			
Mastic Coatings		300			100
Metallic Pigmented Coatings	500	500			150
Multi-Color Coatings		250			
Nonflat Coatings	150	50			
Pre-Treatment Wash Primers		420			
Primers, Sealers, and Undercoaters		100			
Reactive Penetrating Sealers		350			

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 09-06-2013]

Recycled Coatings		250			
Roof Coatings		50			
Roof Coatings, Aluminum		100			
Roof Primers, Bituminous		350			
Rust Preventative Coatings	400	100			
Sacrificial Anti-Graffiti Coatings		100		50	
Shellac					
Clear		730			

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 09-06-2013]

COATING CATEGORY	Ceiling Limit ¹	Current Limit ²	Effective Date		
			7/1/08	1/1/12	1/1/14
Pigmented		550			
Specialty Primers		100			
Stains	350	100			
Stains, Interior	250	250			
Stone Consolidant		450			
Swimming Pool Coatings					
Repair		340			
Other		340			
Traffic Coatings		100			
Waterproofing Sealers		100			
Waterproofing Concrete/Masonry Sealers		100			
Wood Preservatives		350			

- 1 The specified ceiling limits are applicable to products sold under the Averaging Compliance Option.
- 2 The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.
- 3 Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

TABLE OF STANDARDS 1 (cont.) VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

TABLE OF STANDARDS 2 VOC LIMITS FOR COLORANTS

Grams of VOC Per Liter of Colorant Less Water and Less Exempt Compounds

COLORANT ADDED TO	Limit ⁴
Architectural Coatings, excluding IM Coatings	50
Solvent-Based IM	600
Waterborne IM	50

4. Effective January 1, 2014.

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1130 10-08-1999]

(Amended October 8, 1999)

RULE 1130. GRAPHIC ARTS

Except as otherwise provided in Rule 1130

(1) VOC Content of Graphic Arts Materials

The operator shall not apply any graphic arts material, including any VOC-containing materials added to the original graphic arts materials, which contains a total VOC in excess of the limits specified below:

<u>GRAPHIC ARTS MATERIAL</u>	VOC LIMIT Grams per Liter of Coating (or Ink or Adhesive), Less Water and Less Exempt Compounds	
	<u>(October 8, 1999)</u>	<u>Effective</u> <u>January 1, 2000</u>
Lithographic Ink	300	300
Letterpress Ink	300	300
Gravure Ink	300	300
Flexographic Ink Non-Porous Substrate	300	300
Flexographic Ink Porous Substrate	300	225
Flexographic Fluorescent Ink	300	300
Coating	300	300
Adhesive	300	150

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1130 10-08-1999]

(2) VOC Content of Fountain Solution

Through December 31, 1999, the operator shall not apply in any graphic arts operation any fountain solution, including any VOC-containing materials added to the original fountain solution, which contains a total VOC in excess of 100 grams per liter of material. Effective January 1, 2000, the VOC content of fountain solution, including any VOC containing material added to the original fountain solution as applied, shall be:

- (A) no greater than 80 grams per liter of material, or
- (B) no greater than 100 grams per liter of material, if a refrigerated chiller is used.

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		
(iii) Medical Devices & Pharmaceuticals	800 (6.7)		
(B) Repair and Maintenance Cleaning			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals			
(A) Tools, Equipment, & Machinery	800 (6.7)		
(B) General Work Surfaces	600 (5.0)		
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)		
(D) Cleaning of Ink Application Equipment			
(i) General	25 (0.21)		
(ii) Flexographic Printing	25 (0.21)		
(iii) Gravure Printing			
(A) Publication	100 (0.83)		
(B) Packaging	25 (0.21)		
(iv) Lithographic (Offset) or Letter Press Printing			
(A) Roller Wash, Blanket Wash, & On-Press Components			
(I) Newsprint	100 (0.83)		

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(II) Other Substrates	500 (4.2)	100 (0.83)	
(B) Removable Press Components	25 (0.21)		
(v) Screen Printing	500 (4.2)	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)		
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)		

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals	800 (6.7)	
(B) Repair and Maintenance Cleaning		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals		
(A) Tools, Equipment, & Machinery	800 (6.7)	
(B) General Work Surfaces	600 (5.0)	
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)	
(D) Cleaning of Ink Application Equipment		
(i) General	25 (0.21)	
(ii) Flexographic Printing	25 (0.21)	
(iii) Gravure Printing		
(A) Publication	100 (0.83)	
(B) Packaging	25 (0.21)	
(iv) Lithographic (Offset) or Letter Press Printing		
(A) Roller Wash, Blanket Wash, & On-Press Components	100 (0.83)	

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(B) Removable Press Components	25 (0.21)	
(v) Screen Printing	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)	
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)	

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter” Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148

FACILITY PERMIT TO OPERATE THORO PACKAGING INC

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter” Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100