

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
<b>Process 1: COATING OPERATIONS</b>					
<b>System 2: ROLL COATING LINE 2</b>					
COATER, ROLL, LINE NO. 2 A/N: 450258	D4	C6		VOC: (9) [RULE 1125, 1-13-1995; RULE 1125, 3-7-2008; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	H23.4
OVEN, NO. 2, HEAT SUPPLIED FROM AFTERBURNER NO. 2 A/N: 450259	D5	C6			
AFTERBURNER, NO. 2, NATURAL GAS, 8.35 MMBTU/HR A/N: 450260	C6	D4 D5	NOX: PROCESS UNIT**	CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	D182.1, E193.1
<b>System 3: ROLL COATING LINE 3</b>					
COATER, ROLL, LINE NO. 3, WAGNER A/N:	D27	C29		VOC: (9) [RULE 1125, 1-13-1995; RULE 1125, 3-7-2008; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.1, A63.5, B59.4, H23.4, K67.1
OVEN, NO. 3, LTG METAL DECORATING, HEAT SUPPLIED FROM AFTERBURNER NO. 3 A/N: 492622	D28	C29			A63.1, H23.4
AFTERBURNER, NO. 3, NATURAL GAS, LTG METAL DECORATING, 6 MMBTU/HR A/N: 508746	C29	D27 D28	NOX: PROCESS UNIT**	CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	A63.1, A72.1, A72.2, C1.2, D12.1, D182.1, E193.1, K67.1

\* (1) (1A) (1B) Denotes RECLAIM emission factor  
 (2) (2A) (2B) Denotes RECLAIM emission rate  
 (3) Denotes RECLAIM concentration limit  
 (4) Denotes BACT emission limit  
 (5) (5A) (5B) Denotes command and control emission limit  
 (6) Denotes air toxic control rule limit  
 (7) Denotes NSR applicability limit  
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)  
 (9) See App B for Emission Limits  
 (10) See section J for NESHAP/MACT requirements

\*\* Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
<b>Process 1: COATING OPERATIONS</b>					
<b>System 4: END LINERS</b>					
COATER, FLOW, END LINER NO. 5 A/N: 450265	D26			VOC: (9) [RULE 1125, 1-13-1995; RULE 1125, 3-7-2008; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	B59.3, H23.4
COATER, FLOW, END LINER NO. 6 A/N: 450266	D30			VOC: (9) [RULE 1125, 1-13-1995; RULE 1125, 3-7-2008; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	B59.3, H23.4
COATER, ROLLER, COVE MACHINERY INC, 3" DIA X 37" L A/N: 450267	D161			VOC: (9) [RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.3, B27.2, C1.3, H23.4, H23.5, K67.4
FEEDER, SHEET, DEXTER, 69"L. X 58"W X 50"H A/N: 450267	D164				
<b>System 5: STORAGE TANKS</b>					
STORAGE TANK, UNHEATED, NO. 3, SOLVENT, WITH VAPOR RECOVERY SYSTEM, 5000 GALS A/N: 450268	D18				B59.1, C1.1
STORAGE TANK, UNHEATED, NO. 4, SOLVENT, 5000 GALS A/N: 450269	D19				B59.1, C1.1
STORAGE TANK, UNHEATED, NO. B, 6300 GALS A/N: 450270	D20				B22.1
STORAGE TANK, UNHEATED, NO. A, 6300 GALS A/N: 450271	D21				B22.1
<b>Process 2: R219 EXEMPT EQUIPMENT SUBJECT TO SOURCE-SPECIFIC RULE</b>					

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>* (1) (1A) (1B) Denotes RECLAIM emission factor</li> <li>(3) Denotes RECLAIM concentration limit</li> <li>(5) (5A) (5B) Denotes command and control emission limit</li> <li>(7) Denotes NSR applicability limit</li> <li>(9) See App B for Emission Limits</li> </ul> | <ul style="list-style-type: none"> <li>(2) (2A) (2B) Denotes RECLAIM emission rate</li> <li>(4) Denotes BACT emission limit</li> <li>(6) Denotes air toxic control rule limit</li> <li>(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)</li> <li>(10) See section J for NESHAP/MACT requirements</li> </ul> |
|--|--|

\*\* Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
<b>Process 2: R219 EXEMPT EQUIPMENT SUBJECT TO SOURCE-SPECIFIC RULE</b>					
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS	E31			VOC: (9) [RULE 1113, 7-13-2007; RULE 1113, 6-3-2011; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	K67.2
RULE 219 EXEMPT EQUIPMENT, EXEMPT HAND WIPING OPERATIONS	E148			VOC: (9) [RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	H23.4
RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS	E158				H23.2
RULE 219 EXEMPT EQUIPMENT, CLEANING EQUIPMENT, SMALL, UNHEATED, NON-CONVEYORIZED	E160			VOC: (9) [RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	H23.3
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, LOW USE OR EMISSIONS	E166			VOC: (9) [RULE 1107, 1-6-2006; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	H23.4

\* (1) (1A) (1B) Denotes RECLAIM emission factor  
 (2) (2A) (2B) Denotes RECLAIM emission rate  
 (3) Denotes RECLAIM concentration limit  
 (4) Denotes BACT emission limit  
 (5) (5A) (5B) Denotes command and control emission limit  
 (6) Denotes air toxic control rule limit  
 (7) Denotes NSR applicability limit  
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)  
 (9) See App B for Emission Limits  
 (10) See section J for NESHAP/MACT requirements

\*\* Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE  
ARDAGH METAL PACKAGING USA INC.**

**SECTION D: DEVICE ID INDEX**

**The following sub-section provides an index  
to the devices that make up the facility  
description sorted by device ID.**

**FACILITY PERMIT TO OPERATE  
 ARDAGH METAL PACKAGING USA INC.**

**SECTION D: DEVICE ID INDEX**

<b>Device Index For Section D</b>			
<b>Device ID</b>	<b>Section D Page No.</b>	<b>Process</b>	<b>System</b>
D4	1	1	2
D5	1	1	2
C6	1	1	2
D18	2	1	5
D19	2	1	5
D20	2	1	5
D21	2	1	5
D26	2	1	4
D27	1	1	3
D28	1	1	3
C29	1	1	3
D30	2	1	4
E31	3	2	0
E148	3	2	0
E158	3	2	0
E160	3	2	0
D161	2	1	4
D164	2	1	4
E166	3	2	0

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

#### FACILITY CONDITIONS

F2.1 The operator shall limit emissions from this facility as follows:

CONTAMINANT	EMISSIONS LIMIT
VOC	Less than 833 LBS IN ANY ONE MONTH

For the purpose of this condition, the VOC emission limit shall be based on the total combined emissions from all equipment and operations that are subject to Rule 442 at this facility.

To ensure compliance with the monthly Volatile Organic Compound(VOC) emission limit(s) of this condition, the operator shall comply with the following recordkeeping requirements:

- (1) The operator shall comply with Rule 109 (Recordkeeping for Volatile Organic Compound Emissions).
- (2) Within 14 calendar days after the end of each month, the operator shall total and record VOC emissions for the month from all equipment and operations covered by the monthly emission limit(s). The record shall include any procedures used to account for control device efficiencies and/or waste disposal. It shall be signed and certified for accuracy by the highest ranking individual responsible for compliance with District rules.
- (3) The operator shall maintain a single list which includes only the name and address of each person from whom the facility acquired VOC-containing material regulated by the District that was used or stored at the facility during the preceding 12 months.
- (4) The operator shall retain all purchase invoices for all VOC-containing material used or stored at the facility, and all waste manifests for all waste VOC-containing material removed from the facility, for five years.

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

**[RULE 109, 5-2-2003; RULE 442, 12-15-2000]**

F2.2 The operator shall limit emissions from this facility as follows:

CONTAMINANT	EMISSIONS LIMIT
Single Volatile Hazardous Air Pollutant (VHAP)	Less than or equal to 10 TONS IN ANY 12-MONTH PERIOD
Combination of Volatile Hazardous Air Pollutants (VHAPs)	Less than or equal to 25 TONS IN ANY 12-MONTH PERIOD

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

To maintain exemption from the national emission standards for hazardous air pollutants (NESHAP) requirements, the operator shall comply with the Volatile Hazardous Air Pollutant (VHAP) emission limits of this condition

To ensure compliance with the monthly emission caps of this condition, the facility operator shall:

- (a) In addition to the recordkeeping requirements of rule 109, keep adequate records for this equipment and this facility to verify the monthly hap emissions in pounds and the hap content of each material as applied (including water and exempt compounds). the records shall be prepared in a format which is acceptable to the district.
- (b) Within 14 calendar days after the end of each month, total and record hap emissions for the month from all equipment and operations that are required to have written permits or are exempt from written permits pursuant to rule 219. the record shall include any procedures used to account for control device efficiencies and/or waste disposal. it shall be signed and certified for accuracy by the highest ranking individual responsible for compliance with district rules.
- (c) Maintain a single list which includes only the name and address of each person from whom the facility acquired hap-containing material regulated by the district that was used or stored at the facility during the preceding 12 months.
- (d) Retain all purchase invoices for all hap-containing material used or stored at the facility, and all waste manifests for all waste hap-containing material removed from the facility, for five years.
- (e) All records required by this permit shall be prepared in a format which is acceptable to the district, retained at the facility for five years, and made available to any district representative upon request.

[40CFR 63 Subpart KKKK, 11-13-2003]

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

- (a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or
- (b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

### DEVICE CONDITIONS

#### A. Emission Limits

A63.1 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
VOC	Less than or equal to 9240 LBS IN ANY ONE MONTH

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

For the purposes of this condition, the limit(s) shall be based on the total combined emissions from D27, D28, and C29.

To ensure compliance with the monthly Volatile Organic Compound (VOC) emission limit(s) of this condition, the operator shall comply with the following recordkeeping requirements:

- (1) The operator shall comply with Rule 109 (Recordkeeping for Volatile Organic Compound Emissions).
- (2) Within 14 calendar days after the end of each month, the operator shall total and record VOC emissions for the month from all equipment and operations covered by the monthly emission limit(s). The record shall include any procedures used to account for control device efficiencies and/or waste disposal. It shall be signed and certified for accuracy by the highest ranking individual responsible for compliance with District rules.
- (3) The operator shall maintain a single list which includes only the name and address of each person from whom the facility acquired VOC-containing material regulated by the District that was used or stored at the facility during the preceding 12 months.
- (4) The operator shall retain all purchase invoices for all VOC-containing material used or stored at the facility, and all waste manifests for all waste VOC-containing material removed from the facility, for five years.

**[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]**

[Devices subject to this condition : D27, D28, C29]

A63.3 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
<hr/>	

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

VOC	Less than or equal to 30 LBS IN ANY ONE DAY
-----	---

For the purposes of this condition, the limit(s) shall be based on the total combined emissions from D161.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D161]

A63.5 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
Naphthalene	Less than or equal to 53 LBS IN ANY ONE MONTH

The operator shall maintain records to demonstrate compliance with this condition.

[RULE 1401, 9-10-2010]

[Devices subject to this condition : D27]

A72.1 The operator shall maintain this equipment to achieve a minimum destruction efficiency of 95 percent for ROG during the normal operation of the equipment it vents.

[**RULE 1125, 1-13-1995**; RULE 1125, 3-7-2008; **RULE 1303(a)(1)-BACT, 5-10-1996**;  
 RULE 1303(a)(1)-BACT, 12-6-2002; **RULE 1303(b)(2)-Offset, 5-10-1996**; RULE  
 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : C29]

A72.2 The operator shall maintain this equipment to achieve a minimum overall control efficiency of 90 percent for ROG during the normal operation of the equipment it vents.

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

[**RULE 1125, 1-13-1995**; RULE 1125, 3-7-2008; **RULE 1303(a)(1)-BACT, 5-10-1996**;  
RULE 1303(a)(1)-BACT, 12-6-2002; **RULE 1303(b)(2)-Offset, 5-10-1996**; RULE  
1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : C29]

#### **B. Material/Fuel Type Limits**

B22.1 The operator shall not use this equipment with materials having a(n) Reid vapor pressure of 4 psia or greater under actual operating conditions.

[**RULE 1303(a)(1)-BACT, 5-10-1996**; RULE 1303(a)(1)-BACT, 12-6-2002; **RULE  
1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D20, D21]

B27.2 The operator shall not use materials containing any carcinogenic compounds identified in the SCAQMD Rule 1401, as amended 05-02-2003.

For the purposes of this condition, carcinogenic compounds are those in Table I of the above mentioned rule, with an effective date of 05-02-2003 or earlier.

[RULE 1401, 5-2-2003]

[Devices subject to this condition : D161]

B59.1 The operator shall only use the following material(s) in this device :

solvents having a vapor pressure of 0.35 psia or less at 70 Deg. F.

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

**[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]**

[Devices subject to this condition : D18, D19]

B59.3 The operator shall only use the following material(s) in this device :

Coating materials having no VOC

**[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]**

[Devices subject to this condition : D26, D30]

B59.4 The operator shall not use the following material(s) in this device :

Materials containing any toxic air contaminants listed in Table 1 of Rule 1401, with effective date of May 2, 2003 or earlier, except ethyl benzene (CAS 100-41-4), ethylene glycol butyl ether (CAS 11-76-2), formaldehyde (CAS 50-00-0), isophorone (CAS 78-59-1), methyl ethyl ketone (CAS 78-93-3), toluene (CAS 108-88-3), naphthalene (CAS 91-20-3), propylene glycol mono methyl ether (CAS 107-98-2), and xylenes (CAS 1330-20-7).

For the purpose of this condition, the total quantity of naphthalene controlled emissions from this equipment shall be less than 53 pounds in any one month.

[RULE 1401, 5-2-2003]

[Devices subject to this condition : D27]

### **C. Throughput or Operating Parameter Limits**

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

- C1.1 The operator shall limit the material processed to no more than 5000 gallons per day.

For the purpose of this condition, material processed shall be defined as throughput.

**[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]**

[Devices subject to this condition : D18, D19]

- C1.2 The operator shall limit the exhaust flow to no more than 7060 cubic feet per minute.

For the purpose of this condition, exhaust flow shall be defined as maximum process flow to this equipment.

**[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]**

[Devices subject to this condition : C29]

- C1.3 The operator shall limit the material processed to no more than 194 gallon(s) per day.

For the purpose of this condition, material processed shall be defined as usage of lubricant compound.

The VOC content of lubricant compound used in D161 shall not exceed 1.73 pounds per gallon, including water and exempt solvent.

**[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]**

[Devices subject to this condition : D161]

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

#### **D. Monitoring/Testing Requirements**

D12.1 The operator shall install and maintain a(n) flow meter to accurately indicate the flow rate being supplied to the afterburner in standard cubic feet.

[**RULE 1303(a)(1)-BACT, 5-10-1996**; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C29]

D182.1 The operator shall test this equipment in accordance with the following specifications:

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

The test shall be conducted at least once during the life of the permit

The test shall be conducted no later than 1/30/2015

The test shall be conducted to determine the VOC emissions using an approved district method to demonstrate compliance with all applicable permit condition(s), rules and regulations

The source test shall be conducted while the oxidizer is operating at a temperature of not less than the minimum operating temperature specified in this permit. If the operating temperature during the source test is greater than the minimum operating temperature specified in this permit, the minimum operating temperature specified in this permit may be increased to reflect the operating temperature during the source test

The operator shall comply with administrative conditions nos. 8, 9, and 10 of section E of this facility permit

The operator shall submit two complete copies of the source test report specified in condition no. 9 of section E of this facility permit to the District Engineering and Compliance Division. The engineering copy of the report shall be sent to: South Coast Air Quality Management District, Coating, Printing and Aerospace Operations, attn: Air Quality and Compliance Supervisor, 21865 Copley Drive, Diamond Bar, CA 91765

The compliance copy of the report shall be sent to: South Coast Air Quality Management District, P.O. Box 4941, Diamond Bar, CA 91765

The source test report shall also include VOC emissions in ppmv and pounds per hour, usage of all VOC-containing material during the test, the number and type of equipment operated during the test, amount and type of solvent used, oxygen content, moisture content, temperature, and exhaust flow rate expressed in terms of dry standard cubic feet per minute (DSCFM) and dry actual cubic feet per minute (DACFM), and natural gas usage

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### **SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS**

**The operator shall comply with the terms and conditions set forth below:**

**[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]**

[Devices subject to this condition : C6, C29]

#### **E. Equipment Operation/Construction Requirements**

E193.1 The operator shall operate and maintain this equipment according to the following requirements:

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### **SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS**

**The operator shall comply with the terms and conditions set forth below:**

The combustion chamber temperature shall be maintained at a minimum of 1,360 degrees Fahrenheit whenever the equipment it serves is in operation.

The operator shall operate and maintain a temperature measuring and recording system to continuously measure and record the combustion chamber temperature pursuant to the operation and maintenance requirements specified in 40 CFR Part 64.7. Such system shall have an accuracy of within 1% of the temperature being monitored and shall be inspected, maintained, and calibrated on an annual basis in accordance with the manufacturer's specifications.

For the purpose of this condition, a deviation shall be defined as when a combustion chamber temperature of less than 1,360 degrees Fahrenheit occurs during normal operation of the equipment it serves. The operator shall review the records of the combustion chamber temperature on a daily basis to determine if a deviation occurs or shall install an alarm system to alert the operator when a deviation occurs.

Whenever a deviation occurs, the operator shall inspect this equipment to identify the cause of such a deviation, take immediate corrective action to maintain the combustion chamber temperature at or above 1,360 degrees Fahrenheit, and keep records of the duration and cause (including unknown cause, if applicable) of the deviation and the corrective action taken.

All deviations shall be reported to the AQMD pursuant to the requirements specified in 40 CFR Part 64.9 and Condition Nos. 22 and 23 in Section K of this permit. The report shall include the total operating time of this equipment and the total accumulated duration of all deviations for each semi-annual reporting period specified in Condition No. 23 in Section K of this permit.

The operator shall submit an application with a Quality Improvement Plan (QIP) in accordance with 40 CFR Part 64.8 to the AQMD if an accumulation of deviations exceeds 5 percent duration of this equipment's total operating time for any semi-annual reporting period specified in Condition No. 23 in Section K of this permit. The required QIP shall be submitted to the AQMD within 90 calendar days after the due date for the semi-annual monitoring report.

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

The operator shall inspect and maintain all components of this equipment on an annual basis in accordance with the manufacturer's specifications.

The operator shall keep adequate records in a format that is acceptable to the AQMD to demonstrate compliance with all applicable requirements specified in this condition and 40 CFR Part 64.9 for a minimum of five years.

**[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; 40CFR Part 64, 10-22-1997]**

[Devices subject to this condition : C6, C29]

#### H. Applicable Rules

H23.2 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
Refrigerants	District Rule	1415
Refrigerants	40CFR82, SUBPART	F

**[RULE 1415, 12-3-2010; 40CFR 82 Subpart F, 5-14-1993]**

[Devices subject to this condition : E158]

H23.3 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	1122

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

**[RULE 1122, 10-1-2004; RULE 1122, 5-1-2009]**

[Devices subject to this condition : E160]

H23.4 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	109

**[RULE 109, 5-2-2003]**

[Devices subject to this condition : D4, D26, D27, D28, D30, E148, D161, E166]

H23.5 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule
VOC	District Rule 442

**[RULE 442, 12-15-2000]**

[Devices subject to this condition : D161]

#### **K. Record Keeping/Reporting**

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

To show compliance with conditions C1.2, D12.1, and A63.1 and shall be maintained and kept on file for at least five years and shall be made available to the Executive Officer or his representative upon request

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

**[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]**

[Devices subject to this condition : D27, C29]

K67.2 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records for all coating consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coatings.

For architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coatings.

**[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]**

[Devices subject to this condition : E31]

K67.4 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Material safety data sheets for all solvents used at this facility shall be kept current and made available to district personnel

**[RULE 109, 5-2-2003; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]**

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### **SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS**

**The operator shall comply with the terms and conditions set forth below:**

[Devices subject to this condition : D161]

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### **SECTION K: TITLE V Administration**

#### **GENERAL PROVISIONS**

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

#### **Permit Renewal and Expiration**

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]  
  
(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

#### **Duty to Provide Information**

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

#### **Payment of Fees**

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### **SECTION K: TITLE V Administration**

#### **Reopening for Cause**

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
- (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.
  - (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
  - (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

#### **COMPLIANCE PROVISIONS**

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
- (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
  - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
  - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
  - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
  - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
  - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]
  
10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]
  
11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]
  
12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]
  
13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### **SECTION K: TITLE V Administration**

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]
  
15. Nothing in this permit or in any permit shield can alter or affect:
  - (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
  - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
  - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
  - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
  - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
  - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]
  
16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION K: TITLE V Administration EMERGENCY PROVISIONS

17. An emergency<sup>1</sup> constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
    - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
    - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
    - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
    - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
  - (B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

---

<sup>1</sup> "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### **SECTION K: TITLE V Administration RECORDKEEPING PROVISIONS**

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
- (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
  - (B) The date(s) analyses were performed;
  - (C) The company or entity that performed the analyses;
  - (D) The analytical techniques or methods used;
  - (E) The results of such analyses; and
  - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

### **REPORTING PROVISIONS**

22. The operator shall comply with the following requirements for prompt reporting of deviations:
- (A) Breakdowns shall be reported as required by Rule 430 – Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### SECTION K: TITLE V Administration

- (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.
  - (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
  - (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### **SECTION K: TITLE V Administration**

- (B) The compliance status during the reporting period;
- (C) Whether compliance was continuous or intermittent;
- (D) The method(s) used to determine compliance over the reporting period and currently, and
- (E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn:  
Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

### **PERIODIC MONITORING**

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION K: TITLE V Administration

#### *FACILITY RULES*

*This facility is subject to the following rules and regulations*

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

<b>RULE SOURCE</b>	<b>Adopted/Amended Date</b>	<b>FEDERAL Enforceability</b>
RULE 109	5-2-2003	Federally enforceable
RULE 1107	1-6-2006	Federally enforceable
RULE 1113	6-3-2011	Non federally enforceable
RULE 1113	7-13-2007	Federally enforceable
RULE 1122	10-1-2004	Federally enforceable
RULE 1122	5-1-2009	Non federally enforceable
RULE 1125	1-13-1995	Federally enforceable
RULE 1125	3-7-2008	Non federally enforceable
RULE 1171	2-1-2008	Federally enforceable
RULE 1171	5-1-2009	Non federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303(a)(1)-BACT	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	12-6-2002	Non federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1401	5-2-2003	Non federally enforceable
RULE 1401	9-10-2010	Non federally enforceable
RULE 1415	12-3-2010	Non federally enforceable
RULE 2012	5-6-2005	Federally enforceable
RULE 204	10-8-1993	Federally enforceable
RULE 217	1-5-1990	Federally enforceable
RULE 219	6-1-2007	Non federally enforceable

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### SECTION K: TITLE V Administration

<b>RULE SOURCE</b>	<b>Adopted/Amended Date</b>	<b>FEDERAL Enforceability</b>
RULE 219	9-4-1981	Federally enforceable
RULE 3002	11-14-1997	Federally enforceable
RULE 3002	11-5-2010	Non federally enforceable
RULE 3003	11-14-1997	Federally enforceable
RULE 3003	11-5-2010	Non federally enforceable
RULE 3004	12-12-1997	Federally enforceable
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3005	11-5-2010	Non federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	6-1-2012	Non federally enforceable
RULE 401	11-9-2001	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 407	4-2-1982	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 409	8-7-1981	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 442	12-15-2000	Federally enforceable
RULE 480	10-7-1977	Federally enforceable
RULE 701	6-13-1997	Federally enforceable
40CFR 63 Subpart KKKK	11-13-2003	Federally enforceable
40CFR 82 Subpart F	5-14-1993	Federally enforceable
40CFR Part 64	10-22-1997	Federally enforceable

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

<b>VOC LIMITS</b>								
<b>Less Water and Less Exempt Compounds</b>								
<b>Effective Dates</b>								
<b>Coating</b>	<b>Air-Dried</b>				<b>Baked</b>			
	<b>gm/l</b>		<b>lb/gal</b>		<b>gm/l</b>		<b>lb/gal</b>	
	<b>Current</b>	<b>7/1/07</b>	<b>Current</b>	<b>7/1/07</b>	<b>Current</b>	<b>7/1/07</b>	<b>Current</b>	<b>7/1/07</b>
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

<b>VOC LIMITS</b>								
<b>Less Water and Less Exempt Compounds</b>								
<b>Effective Dates, cont.</b>								
<b>Coating</b>	<b>Air-Dried</b>				<b>Baked</b>			
	<b>gm/l</b>		<b>lb/gal</b>		<b>gm/l</b>		<b>lb/gal</b>	
	<b>Current</b>	<b>7/1/07</b>	<b>Current</b>	<b>7/1/07</b>	<b>Current</b>	<b>7/1/07</b>	<b>Current</b>	<b>7/1/07</b>
Extreme Performance	420	420	3.5	3.5	360	360	3.0	3.0
Prefabricated Architectural One-Component	420	275	3.5	2.3	275	275	2.3	2.3
Prefabricated Architectural Multi-Component	420	340	3.5	2.8	275	275	2.3	2.3
Touch Up	420	420	3.5	3.5	360	360	3.0	3.0
Repair	420	420	3.5	3.5	360	360	3.0	3.0
Silicone Release	420	420	3.5	3.5	420	420	3.5	3.5
High-Performance Architectural	420	420	3.5	3.5	420	420	3.5	3.5
Camouflage	420	420	3.5	3.5	420	420	3.5	3.5
Vacuum-Metalizing	420	420	3.5	3.5	420	420	3.5	3.5
Mold-Seal	420	420	3.5	3.5	420	420	3.5	3.5
High-Temperature	420	420	3.5	3.5	420	420	3.5	3.5
Electric-Insulating Varnish	420	420	3.5	3.5	420	420	3.5	3.5
Pan Backing	420	420	3.5	3.5	420	420	3.5	3.5
Pretreatment Coatings	420	420	3.5	3.5	420	420	3.5	3.5

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### **APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]**

- (2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### **APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]**

- (1) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6) of Rule 1113, no person shall supply, sell, offer for sale, market, manufacture, blend, repackage, apply, store at a worksite, or solicit the application of any architectural coating within the District:
  - (A) That is listed in the Table of Standards 1 and contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified; or
  - (B) That is not listed in the Table of Standards 1, and contains VOC (excluding any colorant added to tint bases) in excess of 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, until January 1, 2014, at which time the limit drops to 50 grams of VOC per liter of coating, less water, less exempt compounds (0.42 pounds per gallon).
- (2) No person within the District shall add colorant at the point of sale that is listed in the Table of Standards 2 and contains VOC in excess of the corresponding VOC limit specified in the Table of Standards 2, after the effective date specified.

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

#### TABLE OF STANDARDS 1 VOC LIMITS

**Grams of VOC Per Liter of Coating,  
Less Water and Less Exempt Compounds**

COATING CATEGORY	Ceiling Limit <sup>1</sup>	Current Limit <sup>2</sup>	Effective Date		
			7/1/08	1/1/12	1/1/14
Bond Breakers		350			
Clear Wood Finishes		275			
Varnish	350	275			
Sanding Sealers	350	275			
Lacquer		275			
Concrete-Curing Compounds		100			
Concrete-Curing Compounds For Roadways and Bridges <sup>3</sup>		350			
Concrete Surface Retarder		250			50
Driveway Sealer		100		50	
Dry-Fog Coatings		150			50
Faux Finishing Coatings					
Clear Topcoat		350		200	
Decorative Coatings		350			100
Glazes		350			
Japan		350			
Trowel Applied Coatings		350		150	50
Fire-Proofing Coatings		350			150
Flats	250	50	50		
Floor Coatings	100	50			
Form Release Compound		250			100
Graphic Arts (Sign) Coatings		500			150
Industrial Maintenance (IM) Coatings	420	100			
High Temperature IM Coatings		420			
Non-Sacrificial Anti-Graffiti Coatings		100			
Zinc-Rich IM Primers	340	100			
Magnesite Cement Coatings		450			
Mastic Coatings		300			100
Metallic Pigmented Coatings	500	500			150
Multi-Color Coatings		250			
Nonflat Coatings	150	50			
Pre-Treatment Wash Primers		420			
Primers, Sealers, and Undercoaters	200	100			
Reactive Penetrating Sealers		350			
Recycled Coatings		250			
Roof Coatings	250	50			
Roof Coatings, Aluminum		100			

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

Roof Primers, Bituminous	350	350		
Rust Preventative Coatings	400	100		
Stone Consolidant		450		
Sacrificial Anti-Graffiti Coatings		100		50
Shellac				
Clear		730		
Pigmented		550		
Specialty Primers	350	100		
Stains		100		

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

COATING CATEGORY	Ceiling Limit <sup>1</sup>	Current Limit <sup>2</sup>	Effective Date		
			7/1/08	1/1/12	1/1/14
Stains, Interior	250	250			
Swimming Pool Coatings					
Repair		340			
Other		340			
Traffic Coatings		100			
Waterproofing Sealers	250	100			
Waterproofing Concrete/Masonry Sealers	400	100			
Wood Preservatives		350			

1. The specified ceiling limits are applicable to products sold under the Averaging Compliance Option.
2. The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.
3. Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

#### TABLE OF STANDARDS 1 (cont.) VOC LIMITS

##### Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

#### TABLE OF STANDARDS 2 VOC LIMITS FOR COLORANTS

##### Grams of VOC Per Liter of Colorant Less Water and Less Exempt Compounds

COLORANT	Limit <sup>4</sup>
Architectural Coatings, excluding IM Coatings	50
Solvent-Based IM	600
Waterborne IM	50

4. Effective January 1, 2014.

## **FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.**

### **APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007]**

- (1) Except as provided in paragraphs (c)(2), (c)(3), (c)(4), and specified coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage any architectural coating for use in the District which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, and no person shall apply or solicit the application of any architectural coating within the District that exceeds 250 grams of VOC per liter of coating as calculated in this paragraph.
- (2) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified, and no person shall apply or solicit the application of any architectural coating within the District that exceeds the VOC limit as specified in this paragraph. No person shall apply or solicit the application within the District of any industrial maintenance coatings, except anti-graffiti coatings, for residential use or for use in areas such as office space and meeting rooms of industrial, commercial or institutional facilities not exposed to such extreme environmental conditions described in the definition of industrial maintenance coatings; or of any rust-preventative coating for industrial use, unless such a rust preventative coating complies with the Industrial Maintenance Coating VOC limit specified in the Table of Standards.

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007] TABLE OF STANDARDS VOC LIMITS

#### Grams of VOC Per Liter of Coating, Less Water and Less Exempt Compounds

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Bond Breakers	350							
Clear Wood Finishes	350					275		
Varnish	350					275		
Sanding Sealers	350					275		
Lacquer	680	550			275			
Clear Brushing Lacquer	680				275			
Concrete-Curing Compounds	350						100	
Concrete-Curing Compounds For Roadways and Bridges**	350							
Dry-Fog Coatings	400						150	
Fire-Proofing Exterior Coatings	450	350						
Fire-Retardant Coatings***								
Clear	650							
Pigmented	350							
Flats	250	100						50
Floor Coatings	420		100			50		
Graphic Arts (Sign) Coatings	500							
Industrial Maintenance (IM) Coatings	420			250		100		
High Temperature IM Coatings			420					
Zinc-Rich IM Primers	420		340			100		
Japans/Faux Finishing Coatings	700	350						
Magnesite Cement Coatings	600	450						
Mastic Coatings	300							
Metallic Pigmented Coatings	500							
Multi-Color Coatings	420	250						
Nonflat Coatings	250		150			50		

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007]

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Nonflat High Gloss	250		150				50	
Pigmented Lacquer	680	550			275			
Pre-Treatment Wash Primers	780		420					
Primers, Sealers, and Undercoaters	350		200			100		
Quick-Dry Enamels	400		250			150	50	
Quick-Dry Primers, Sealers, and Undercoaters	350		200			100		
Recycled Coatings			250					
Roof Coatings	300		250		50			
Roof Coatings, Aluminum	500				100			
Roof Primers, Bituminous	350		350					
Rust Preventative Coatings	420		400			100		
Shellac								
Clear	730							
Pigmented	550							
Specialty Primers	350					250	100	
Stains	350		250				100	
Stains, Interior	250							
Swimming Pool Coatings								
Repair	650		340					
Other	340							
Traffic Coatings	250	150					100	
Waterproofing Sealers	400		250			100		
Waterproofing	400					100		
Concrete/Masonry Sealers								
Wood Preservatives								
Below-Ground	350							
Other	350							

\* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.

\*\* Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

\*\*\* The Fire-Retardant Coating category will be eliminated on January 1, 2007 and subsumed by the coating category for which they are formulated.

**FACILITY PERMIT TO OPERATE  
ARDAGH METAL PACKAGING USA INC.**

**APPENDIX B: RULE EMISSION LIMITS  
[RULE 1113 07-13-2007]**

**TABLE OF STANDARDS (cont.)  
VOC LIMITS**

**Grams of VOC Per Liter of Material**

COATING	Limit
Low-Solids Coating	120

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1125 01-13-1995]

Except as otherwise provided in Rule 1125, the operator shall not use or apply any coating on any coating line of the type designated below which contains any volatile organic compound in excess of the following limits:

<u>COATING</u>	<b>VOC LIMITS</b>	
	Grams per Liter of Coating, Less Water and Less Exempt Compounds	
	<u>g/L</u>	<u>lb/gal</u>
Can Coating		
(A) Three-Piece Can Sheet Basecoat (exterior and interior and overvarnish)	225	1.9
(B) Two-Piece Can Exterior Basecoat and Overvarnish	250	2.1
(C) Inks	300	2.5
(D) Can Interior Body Spray		
(i) Two-Piece Can	440	3.7
(ii) Three-Piece Can	510	4.2
(E) Three-Piece Can Side Seam Spray	660	5.5
(F) End Sealing Compound		
(i) Food/Beverage Cans	440	3.7
(ii) Non-Food Cans (After March 1, 1991)	440 0	3.7 0
(G) Drums, Pails, and Lids Coating		
(i) New		
Exterior	340	2.8
Interior	420	3.5
(ii) Reconditioned		
Exterior	420	3.5
Interior	510	4.2
(H) Necker Lubricants	100	0.8
Coil Coating	200	1.7

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1125 03-07-2008]

Except as otherwise provided in Rule 1125, the operator shall not use or apply any coating on any coating line of the type designated below which contains any volatile organic compound in excess of the following limits, expressed as grams of VOC per liter of coating or pounds per gallon of coating, less water and less exempt compounds, except for inkjet inks and inkjet make-up solvents, where the referenced VOC limit is expressed as grams of VOC per liter of material or pounds per gallon of material:

COATING CATEGORY	VOC LIMITS	
	g/L	Lb/gal
<b>Can Coatings</b>		
Three-Piece Can Sheet Basecoat (Exterior and Interior Overvarnish)	225	1.9
Two-Piece Can Exterior Basecoat and Overvarnish	250	2.1
Can Interior Body Spray		
Two-Piece Can	440	3.7
Three-Piece Can	510	4.2
Three-Piece Can Side Seam Spray	660	5.5
<b>Drums, Pails, and Lids Coatings</b>		
New		
Exterior	340	2.8
Interior	420	3.5
Reconditioned		
Exterior	420	3.5
Interior	510	4.2
<b>Coil Coatings</b>		
Coatings	200	1.7

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1125 03-07-2008]

<b>All Operations</b>		
Necker Lubricants	100	0.8
End Sealing Compounds		
Food/Beverage Cans	440	3.7
Effective 7-1-08	20	0.17
Non-Food Containers	0	0
Inks		
Other than Inkjet	300	2.5
Inkjet	250*	2.1*
Thermochromic Inkjet	700*	5.8*
Inkjet Make-Up Solvents		
General Inkjet	250*	2.1*
Thermochromic Inkjet	800*	5.8*

\* Different VOC determination method

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	<b>CURRENT LIMITS*</b>	<b>EFFECTIVE 1/1/2008*</b>	<b>EFFECTIVE 1/1/2009</b>
<b>SOLVENT CLEANING ACTIVITY</b>	<b>VOC g/l (lb/gal)</b>	<b>VOC g/l (lb/gal)</b>	<b>VOC g/l (lb/gal)</b>
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		
(iii) Medical Devices & Pharmaceuticals	800 (6.7)		
(B) Repair and Maintenance Cleaning			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

	<b>CURRENT LIMITS*</b>	<b>EFFECTIVE 1/1/2008*</b>	<b>EFFECTIVE 1/1/2009</b>
<b>SOLVENT CLEANING ACTIVITY (cont.)</b>	<b>VOC g/l (lb/gal)</b>	<b>VOC g/l (lb/gal)</b>	<b>VOC g/l (lb/gal)</b>
(iii) Medical Devices & Pharmaceuticals			
(A) Tools, Equipment, & Machinery	800 (6.7)		
(B) General Work Surfaces	600 (5.0)		
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)		
(D) Cleaning of Ink Application Equipment			
(i) General	25 (0.21)		
(ii) Flexographic Printing	25 (0.21)		
(iii) Gravure Printing			
(A) Publication	100 (0.83)		
(B) Packaging	25 (0.21)		
(iv) Lithographic (Offset) or Letter Press Printing			
(A) Roller Wash, Blanket Wash, & On-Press Components			
(I) Newsprint	100 (0.83)		

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

	<b>CURRENT LIMITS*</b>	<b>EFFECTIVE 1/1/2008*</b>	<b>EFFECTIVE 1/1/2009</b>
<b>SOLVENT CLEANING ACTIVITY (cont.)</b>	<b>VOC g/l (lb/gal)</b>	<b>VOC g/l (lb/gal)</b>	<b>VOC g/l (lb/gal)</b>
(II) Other Substrates	500 (4.2)	100 (0.83)	
(B) Removable Press Components	25 (0.21)		
(v) Screen Printing	500 (4.2)	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)		
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)		

\* The specified limits remain in effect unless revised limits are listed in subsequent columns.

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	<b>CURRENT LIMITS*</b>	<b>EFFECTIVE 1/1/2010</b>
<b>SOLVENT CLEANING ACTIVITY</b>	<b>VOC g/l (lb/gal)</b>	<b>VOC g/l (lb/gal)</b>
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals	800 (6.7)	
(B) Repair and Maintenance Cleaning		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

	<b>CURRENT LIMITS*</b>	<b>EFFECTIVE 1/1/2010</b>
<b>SOLVENT CLEANING ACTIVITY (cont.)</b>	<b>VOC g/l (lb/gal)</b>	<b>VOC g/l (lb/gal)</b>
(iii) Medical Devices & Pharmaceuticals		
(A) Tools, Equipment, & Machinery	800 (6.7)	
(B) General Work Surfaces	600 (5.0)	
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)	
(D) Cleaning of Ink Application Equipment		
(i) General	25 (0.21)	
(ii) Flexographic Printing	25 (0.21)	
(iii) Gravure Printing		
(A) Publication	100 (0.83)	
(B) Packaging	25 (0.21)	
(iv) Lithographic (Offset) or Letter Press Printing		
(A) Roller Wash, Blanket Wash, & On-Press Components	100 (0.83)	

**FACILITY PERMIT TO OPERATE  
 ARDAGH METAL PACKAGING USA INC.**

**APPENDIX B: RULE EMISSION LIMITS  
 [RULE 1171 05-01-2009]**

	<b>CURRENT LIMITS*</b>	<b>EFFECTIVE 1/1/2010</b>
<b>SOLVENT CLEANING ACTIVITY (cont.)</b>	<b>VOC g/l (lb/gal)</b>	<b>VOC g/l (lb/gal)</b>
(B) Removable Press Components	25 (0.21)	
(v) Screen Printing	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)	
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)	

\* The specified limits remain in effect unless revised limits are listed in subsequent columns.

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

**TABLE 404(a)**

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445

## FACILITY PERMIT TO OPERATE ARDAGH METAL PACKAGING USA INC.

### APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter” Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148

**FACILITY PERMIT TO OPERATE  
 ARDAGH METAL PACKAGING USA INC.**

**APPENDIX B: RULE EMISSION LIMITS  
 [RULE 404 02-07-1986]**

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter” Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100