

FACILITY PERMIT TO OPERATE

**OLD COUNTRY MILLWORK INC
1212 E 58TH PL
LOS ANGELES, CA 90001**

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By _____
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	7	07/06/2010
B	RECLAIM Annual Emission Allocation	19	07/06/2010
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	7	08/31/2010
E	Administrative Conditions	9	07/06/2010
F	RECLAIM Monitoring and Source Testing Requirements	6	07/06/2010
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	6	07/06/2010
H	Permit To Construct and Temporary Permit to Operate	6	08/31/2010
I	Compliance Plans & Schedules	4	07/06/2010
J	Air Toxics	2	07/06/2010
K	Title V Administration	3	07/06/2010
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	4	07/06/2010
B	Rule Emission Limits	2	07/06/2010

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: COIL COATING EQUIPMENT					P42.1
System 4: STRIP COATING AND BAKING SYSTEM NO. 4					
PROCESS TANK, LINE NO 4, CLEANING A/N: 259218	D27			VOC: (9) [RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	
PROCESS TANK, LINE NO. 4, CLEANING A/N: 259218	D28			VOC: (9) [RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	
PROCESS TANK, LINE NO. 4, CLEANING A/N: 259218	D29			VOC: (9) [RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	
COATER, NO. 1, LINE NO. 4 A/N: 259218	D31	C46 C50		VOC: (9) [RULE 1125, 1-13-1995; RULE 1125, 3-7-2008; RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	H23.2
OVEN, NO. 1, LINE NO. 4, 60 KW A/N: 259218	D32	C46 C50		PM: (9) [RULE 404, 2-7-1986]	
COATER, NO. 2, LINE NO. 4 A/N: 259218	D33	C46 C50		VOC: (9) [RULE 1125, 1-13-1995; RULE 1125, 3-7-2008; RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	H23.2
OVEN, NO. 2, LINE NO. 4, 60 KW A/N: 259218	D34	C46 C50		PM: (9) [RULE 404, 2-7-1986]	
System 5: STRIP COATING AND BAKING SYSTEM NO. 5					
PROCESS TANK, LINE NO. 5, CLEANING A/N: 261762	D35			VOC: (9) [RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	
PROCESS TANK, LINE NO. 5, CLEANING A/N: 261762	D36			VOC: (9) [RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	
PROCESS TANK, LINE NO. 5, CLEANING A/N: 261762	D37			VOC: (9) [RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	

- | | |
|--|--|
| <ul style="list-style-type: none"> * (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits | <ul style="list-style-type: none"> (2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements |
|--|--|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: COIL COATING EQUIPMENT					P42.1
COATER, NO. 1, LINE NO. 5 A/N: 261762	D39	C46 C50		VOC: (9) [RULE 1125, 1-13-1995; RULE 1125, 3-7-2008; RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	H23.2
OVEN, NO. 1, LINE NO. 5, 100 KW A/N: 261762	D40	C46 C50		PM: (9) [RULE 404, 2-7-1986]	
COATER, NO. 2, LINE NO. 5 A/N: 261762	D41	C46 C50		VOC: (9) [RULE 1125, 1-13-1995; RULE 1125, 3-7-2008; RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	H23.2
OVEN, NO. 2, LINE NO. 5, 100 KW A/N: 261762	D42	C46 C50		PM: (9) [RULE 404, 2-7-1986]	
PRINTING PRESS, LINE NO. 5 A/N: 261762	D43	C46 C50		VOC: (9) [RULE 1125, 1-13-1995; RULE 1125, 3-7-2008; RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	H23.2
OVEN, NO. 3, LINE NO. 5, 100 KW A/N: 261762	D44	C46 C50		PM: (9) [RULE 404, 2-7-1986]	
Process 2: AIR POLLUTION CONTROL EQUIPMENT					
AFTERBURNER, HIRT, MODEL NO. HIL10M7MX, NATURAL GAS, 11 MMBTU/HR A/N: 261761	C46	D31 D32 D33 D34 D39 D40 D41 D42 D43 D44	NOX: PROCESS UNIT**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	C1.1, D12.1, D28.1, E71.1, E193.1
Process 3: R219 EXEMPT EQUIPMENT SUBJECT TO SOURCE-SPECIFIC RULES					
RULE 219 EXEMPT EQUIPMENT, CLEANING EQUIPMENT, SMALL, UNHEATED, NON-CONVEYORIZED	E47			VOC: (9) [RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	H23.1

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 3: R219 EXEMPT EQUIPMENT SUBJECT TO SOURCE-SPECIFIC RULES					
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS	E48			VOC: (9) [RULE 1113, 11-8-1996; RULE 1113, 7-13-2007; RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	K67.1
RULE 219 EXEMPT EQUIPMENT, EXEMPT HAND WIPING OPERATIONS	E49			VOC: (9) [RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION D: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

**FACILITY PERMIT TO OPERATE
 OLD COUNTRY MILLWORK INC
 SECTION D: DEVICE ID INDEX**

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D27	1	1	4
D28	1	1	4
D29	1	1	4
D31	1	1	4
D32	1	1	4
D33	1	1	4
D34	1	1	4
D35	1	1	5
D36	1	1	5
D37	1	1	5
D39	2	1	5
D40	2	1	5
D41	2	1	5
D42	2	1	5
D43	2	1	5
D44	2	1	5
C46	2	2	0
E47	2	3	0
E48	3	3	0
E49	3	3	0

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F2.1 The operator shall limit emissions from this facility as follows:

CONTAMINANT	EMISSION LIMIT
Single Volatile Hazardous Air Pollutant (VHAP)	Less than 10 TONS IN ANY 12-MONTH PERIOD
Combination of Volatile Hazardous Air Pollutants (VHAPs)	Less than 25 TONS IN ANY 12-MONTH PERIOD

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

To maintain exemption from the requirements of 40 CFR 63, Subpart SSSS, the operator shall comply with the Volatile Hazardous Air Pollutant (VHAP) emission limits of this condition. To ensure compliance with the VHAP emission limits of this condition, the operator shall:

(a) Comply with Rule 109 (Recordkeeping for Volatile Organic Compound Emissions).

b) Within 14 calendar days after the end of each month, total and record VHAP emissions for the month and for the previous 12 month period from all equipment and operations that are required to have written permits or are exempt from written permits pursuant to Rule 219. The record shall include any procedures used to account for control device efficiencies and/or waste disposal. It shall be signed and certified for accuracy by the highest ranking individual responsible for compliance with District rules

(c) Maintain a single list which includes only the name and address of each person from whom the facility acquired VHAP-containing material regulated by the District that was used or stored at the facility during the preceding 12 months.

(d) Retain all purchase invoices for all VHAP-containing material used or stored at the facility, and all waste manifests for all waste VHAP-containing material removed from the facility.

(e) Retain all records required by this permit at the facility for five years, and make all records available to any District representative upon request.

[40CFR 63 Subpart SSSS, 6-10-2002]

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

- (a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or
- (b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[**RULE 401, 3-2-1984**; RULE 401, 11-9-2001]

PROCESS CONDITIONS

P42.1 The operator shall comply with the following requirement:

Contaminant	Rule	Subpart
VOC	40 CFR 60	TT

[**40CFR 60 Subpart TT, 10-4-1991**]

[Processes subject to this condition : 1]

DEVICE CONDITIONS

C. Throughput or Operating Parameter Limits

C1.1 The operator shall limit the heat input to no more than 23000 MM Btu in any one year.

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The purpose(s) of this condition is to ensure that this equipment qualifies as a process unit.

[RULE 2012, 5-6-2005]

[Devices subject to this condition : C46]

D. Monitoring/Testing Requirements

D12.1 The operator shall install and maintain a(n) non-resettable totalizing fuel flow meter to accurately indicate the fuel usage of the equipment.

[RULE 2012, 5-6-2005]

[Devices subject to this condition : C46]

D28.1 The operator shall conduct source test(s) in accordance with the following specifications:

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The test shall be conducted to demonstrate compliance with Rule 1125.

The test shall be conducted to determine the ROG emissions using District method 25.1 measured over a 60 minute averaging time period.

The test shall be conducted at least once during the life of the permit.

The test shall be conducted to determine the ROG emissions at the inlet and outlet simultaneously.

The test shall be conducted no later than July 6, 2014 unless otherwise approved in writing by the District.

The test shall be conducted while the oxidizer is operating at a temperature of not less than the minimum operating temperature specified in this permit. If the operating temperature during the source test is greater than the minimum operating temperature specified in this permit, the minimum operating temperature specified in this permit may be increased to reflect the operating temperature during the source test.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C46]

E. Equipment Operation/Construction Requirements

E71.1 The operator shall only operate this equipment if it can achieve a minimum overall efficiency of 83 percent.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : C46]

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E193.1 The operator shall operate and maintain this equipment according to the following requirements:

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The combustion chamber temperature shall be maintained at a minimum of 1,450 degrees Fahrenheit whenever the equipment it serves is in operation.

The operator shall operate and maintain a temperature measuring and recording system to continuously measure and record the combustion chamber temperature pursuant to the operation and maintenance requirements specified in 40 CFR Part 64.7. Such a system shall have an accuracy of within of the temperature being monitored and shall be inspected, maintained, and calibrated on an annual basis in accordance with the manufacturer's specifications using an applicable AQMD or EPA approved method.

For the purpose of this condition, a deviation shall be defined as when the combustion chamber temperature of less than 1,450 degrees Fahrenheit occurs during the normal operation of the equipment it serves. The operator shall review the records of the combustion chamber temperature on a daily basis to determine if a deviation occurs or shall install an alarm system to alert the operator when a deviation occurs.

Whenever a deviation occurs, the operator shall inspect this equipment to identify the cause of such a deviation, take immediate corrective actions to maintain the combustion chamber temperature at or above 1,450 degrees Fahrenheit, and keep records of the duration and cause (including unknown cause, if applicable) of the deviation and the corrective actions taken.

All deviations shall be reported to the AQMD on a semi-annual basis pursuant to the requirements specified in 40 CFR Part 64.9 and Condition Nos. 22 and 23 in Section K of this permit. The semi-annual monitoring report shall include the total operating time of this equipment and the total accumulated duration of all deviations for each semi-annual reporting period specified in Condition No. 23 in Section K of this permit.

The operator shall submit an application with an Quality Improvement Plan (QIP) in accordance with 40 CFR Part 64.8 to the AQMD if an accumulation of deviations exceeds 5 percent duration of this equipment's total operating time for any semi-annual reporting period specified in Condition No. 23 in Section K of this

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

permit. The required QIP shall be submitted to the AQMD within 90 calendar days after the due date for the semi-annual monitoring report.

The operator shall inspect and maintain all components of this equipment on an annual basis in accordance with the manufacturer's specifications.

The operator shall keep adequate records in a format that is acceptable to the AQMD to demonstrate compliance with all applicable requirements specified in this condition and 40 CFR Part 64.9 for a minimum of five years.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; 40CFR Part 64, 10-22-1997]

[Devices subject to this condition : C46]

H. Applicable Rules

H23.1 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	1122

[RULE 1122, 10-1-2004; RULE 1122, 5-1-2009]

[Devices subject to this condition : E47]

H23.2 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	109

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 109, 5-2-2003]

[Devices subject to this condition : D31, D33, D39, D41, D43]

K. Record Keeping/Reporting

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records for all coating consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coatings.

For architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coatings.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : E48]

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 2: AIR POLLUTION CONTROL EQUIPMENT					
OXIDIZER, THERMAL REGENERATIVE, ADWEST TECHNOLOGIES, MODEL 10.0RTO95, 10,000 CFM, NATURAL GAS FIRED, WITH 1,500 CFH NATURAL GAS INJECTION, 2.89 MMBTU/HR WITH A/N: 511563 Permit to Construct Issued: 08/31/10 BURNER, MAXON KINEDIZER LE-4, LOW-NOX BURNER, 2.89 MMBTU/HR	C50	D31 D32 D33 D34 D39 D40 D41 D42 D43 D44	NOX: PROCESS UNIT**	CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	D12.1, D28.1, D29.1, D323.1, E71.2, E193.2

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION H: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION H: DEVICE ID INDEX

Device Index For Section H			
Device ID	Section H Page No.	Process	System
C50	1	2	0

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F2.1 The operator shall limit emissions from this facility as follows:

CONTAMINANT	EMISSION LIMIT
Single Volatile Hazardous Air Pollutant (VHAP)	Less than 10 TONS IN ANY 12-MONTH PERIOD
Combination of Volatile Hazardous Air Pollutants (VHAPs)	Less than 25 TONS IN ANY 12-MONTH PERIOD

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

To maintain exemption from the requirements of 40 CFR 63, Subpart SSSS, the operator shall comply with the Volatile Hazardous Air Pollutant (VHAP) emission limits of this condition. To ensure compliance with the VHAP emission limits of this condition, the operator shall:

- (a) Comply with Rule 109 (Recordkeeping for Volatile Organic Compound Emissions).
- b) Within 14 calendar days after the end of each month, total and record VHAP emissions for the month and for the previous 12 month period from all equipment and operations that are required to have written permits or are exempt from written permits pursuant to Rule 219. The record shall include any procedures used to account for control device efficiencies and/or waste disposal. It shall be signed and certified for accuracy by the highest ranking individual responsible for compliance with District rules
- (c) Maintain a single list which includes only the name and address of each person from whom the facility acquired VHAP-containing material regulated by the District that was used or stored at the facility during the preceding 12 months.
- (d) Retain all purchase invoices for all VHAP-containing material used or stored at the facility, and all waste manifests for all waste VHAP-containing material removed from the facility.
- (e) Retain all records required by this permit at the facility for five years, and make all records available to any District representative upon request.

[40CFR 63 Subpart SSSS, 6-10-2002]

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

- (a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or
- (b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

PROCESS CONDITIONS

P42.1 The operator shall comply with the following requirement:

Contaminant	Rule	Subpart
VOC	40 CFR 60	TT

[40CFR 60 Subpart TT, 10-4-1991]

[Processes subject to this condition : 1]

DEVICE CONDITIONS

D. Monitoring/Testing Requirements

D12.1 The operator shall install and maintain a(n) non-resettable totalizing fuel flow meter to accurately indicate the fuel usage of the equipment.

[RULE 2012, 5-6-2005]

[Devices subject to this condition : C50]

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D28.1 The operator shall conduct source test(s) in accordance with the following specifications:

The test shall be conducted to demonstrate compliance with Rule 1125.

The test shall be conducted to determine the ROG emissions using District method 25.1 measured over a 60 minute averaging time period.

The test shall be conducted at least once during the life of the permit.

The test shall be conducted to determine the ROG emissions at the inlet and outlet simultaneously.

The test shall be conducted no later than July 6, 2014 unless otherwise approved in writing by the District.

The test shall be conducted while the oxidizer is operating at a temperature of not less than the minimum operating temperature specified in this permit. If the operating temperature during the source test is greater than the minimum operating temperature specified in this permit, the minimum operating temperature specified in this permit may be increased to reflect the operating temperature during the source test.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C50]

D29.1 The operator shall conduct source test(s) for the pollutant(s) identified below.

Pollutant(s) to be tested	Required Test Method(s)	Averaging Time	Test Location
VOC	Approved District method	District-approved averaging time	Simultaneous inlet and outlet
NOX emissions	Approved District method	District-approved averaging time	Outlet

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

CO emissions		Approved District method		District-approved averaging time		Outlet
--------------	--	--------------------------	--	-------------------------------------	--	--------

In addition to the source test requirements of Section E of this facility permit, notify the District of the date and time of the test at least 10 days prior to the test.

In addition to the source test requirements of Section E of this facility permit, the facility permit holder shall submit a source test protocol to the District engineer no later than 45 days prior to the proposed test date.

The test(s) shall be conducted within 90 days after achieving maximum production rate, but no later than 120 days after initial start-up.

The test shall be conducted to determine the collection and destruction efficiencies.

The test shall be conducted to demonstrate compliance with a destruction efficiency of 95% and an overall collection/destruction efficiency of 83%.

Notwithstanding the requirements of Section E conditions, the source test results shall be submitted to the District no later than 60 days after the source test was conducted.

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002**]

[Devices subject to this condition : C50]

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a semi-annual basis, at least, unless the equipment did not operate during the entire semi-annual period. The routine semi-annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C50]

E. Equipment Operation/Construction Requirements

E71.2 The operator shall only operate this equipment if it can achieve a 95% destruction efficiency and a minimum overall efficiency of 83 percent.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : C50]

E193.2 The operator shall operate and maintain this equipment according to the following requirements:

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

The combustion chamber temperature shall be maintained at a minimum of 1,500 degrees Fahrenheit whenever the equipment it serves is in operation.

The operator shall operate and maintain a temperature measuring and recording system to continuously measure and record the combustion chamber temperature pursuant to the operation and maintenance requirements specified in 40 CFR Part 64.7. Such a system shall have an accuracy of within of the temperature being monitored and shall be inspected, maintained, and calibrated on an annual basis in accordance with the manufacturer's specifications using an applicable AQMD or EPA approved method.

For the purpose of this condition, a deviation shall be defined as when the combustion chamber temperature of less than 1,500 degrees Fahrenheit occurs during the normal operation of the equipment it serves. The operator shall review the records of the combustion chamber temperature on a daily basis to determine if a deviation occurs or shall install an alarm system to alert the operator when a deviation occurs.

Whenever a deviation occurs, the operator shall inspect this equipment to identify the cause of such a deviation, take immediate corrective actions to maintain the combustion chamber temperature at or above 1,500 degrees Fahrenheit, and keep records of the duration and cause (including unknown cause, if applicable) of the deviation and the corrective actions taken.

All deviations shall be reported to the AQMD on a semi-annual basis pursuant to the requirements specified in 40 CFR Part 64.9 and Condition Nos. 22 and 23 in Section K of this permit. The semi-annual monitoring report shall include the total operating time of this equipment and the total accumulated duration of all deviations for each semi-annual reporting period specified in Condition No. 23 in Section K of this permit.

The operator shall submit an application with an Quality Improvement Plan (QIP) in accordance with 40 CFR Part 64.8 to the AQMD if an accumulation of deviations exceeds 5 percent duration of this equipment's total operating time for any semi-annual reporting period specified in Condition No. 23 in Section K of this permit. The required QIP shall be submitted to the AQMD within 90 calendar

FACILITY PERMIT TO OPERATE OLD COUNTRY MILLWORK INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

days after the due date for the semi-annual monitoring report.

The operator shall inspect and maintain all components of this equipment on an annual basis in accordance with the manufacturer's specifications.

The operator shall keep adequate records in a format that is acceptable to the AQMD to demonstrate compliance with all applicable requirements specified in this condition and 40 CFR Part 64.9 for a minimum of five years.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; 40CFR Part 64, 10-22-1997]

[Devices subject to this condition : C50]