

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: DISTILLATION					
System 1: USED OIL DEHYDRATION					S15.1
PUMP, P-002A, 1000-SERIES NORTH TRANSFER, 15 HP A/N:	D426				
PUMP, P-002B, 1000-SERIES SOUTH TRANSFER, 15 HP A/N:	D427				
PUMP, P-215, TANK 2003 CIRCULATION, 25 HP A/N:	D428				
PUMP, P-XX2, SWTF TRANSFER, 15 HP A/N:	D429				
PUMP, P-XX3, SWTF TRANSFER, 15 HP A/N:	D430				
PUMP, AP-412, DRAIN, AIR-POWERED A/N:	D431				
PUMP, P-204A/B/C, EAST/MIDDLE/WEST DEHYDRATION CHARGE, 50 HP EACH, 3 TOTAL A/N:	D326				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-406A/B IN SERIES, NORTH PREHEATER, 2 TOTAL; DIAMETER: 3 FT 4 IN; LENGTH: 14 FT 6 IN A/N:	D132				

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: DISTILLATION					
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-405A/B, IN SERIES, SOUTH PREHEATER, 2 TOTAL; DIAMETER: 3 FT 4 IN; LENGTH: 14 FT 6 IN A/N:	D133				
TOWER, FLASH, DEHYDRATION VESSEL, C-201, HEIGHT: 22 FT ; DIAMETER: 5 FT A/N:	D125	D266 D267			
PUMP, P-201A/B IN SERIES, EAST/WEST C-201 BOTTOMS, 50 HP EACH, 2 TOTAL A/N:	D237				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-203, LENGTH: 15 FT 11 IN; DIAMETER: 2 FT 8 IN A/N:	D247				
TOWER, FLASH, DEHYDRATION VESSEL, C-202, HEIGHT: 22 FT ; DIAMETER: 5 FT A/N:	D126	D266 D267			
PUMP, P-202A/B IN SERIES, NORTH/SOUTH C-202 BOTTOMS, 50 HP EACH, 2 TOTAL A/N:	D263				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-203A,, LENGTH: 15 FT 11 IN; DIAMETER: 2 FT 8 IN A/N:	D265				

- | | |
|--|--|
| <ul style="list-style-type: none"> * (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits | <ul style="list-style-type: none"> (2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements |
|--|--|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: DISTILLATION					
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-202,C-202 OVERHEAD COOLER, LENGTH: 14 FT 6 IN; DIAMETER: 3 FT A/N:	D266	D125 D126 D128			
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-201,C-201 OVERHEAD COOLER, LENGTH: 14 FT 6 IN; DIAMETER: 3 FT A/N:	D267	D125 D126 D128			
TOWER, FLASH, VACUUM DEHYDRATION VESSEL, C-203, HEIGHT: 22 FT ; DIAMETER: 5 FT A/N:	D127	D258			
PUMP, P-203A/B, NORTH/SOUTH C-203 BOTTOMS, 15 HP EACH, 2 TOTAL A/N:	D305				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-206, FUELOIL COOLER, LENGTH: 14 FT 6 IN; DIAMETER: 2 FT 2 IN A/N:	D525				
TOWER, FLASH, VACUUM DEHYDRATION VESSEL, C-206, HEIGHT: 10 FT 6 IN; DIAMETER: 5 FT A/N:	D178	D258			
PUMP, P-206A, EAST C-206 BOTTOMS, 10 HP A/N:	D351				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: DISTILLATION					
PUMP, P-206B, WEST C-206 BOTTOMS, 20 HP A/N:	D423				
CONDENSER, BAROMETRIC, LENGTH: 10 FT 11 IN; DIAMETER: 10 IN A/N:	D258	D127 D178 D260 D344			
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-205, BAROMETRIC COOLER, LENGTH: 12 FT 4 IN; DIAMETER: 2 FT 6 IN A/N:	D260	D128 D258			
ACCUMULATOR, PHASE SEPARATOR, D-204, LENGTH: 20 FT ; DIAMETER: 5 FT A/N:	D128	D9 D31 D121 D176 D177 D260 D266 D267 D294 D295 D361 D373 D380 D383 D385 D394 D395 D417			
PUMP, EAST/WEST BAROMETRIC, P-701A/B, 15 HP EACH, 2 TOTAL A/N:	D255				
PUMP, EAST NAPHTHA, P-702A, 5 HP A/N:	D256				
PUMP, WEST NAPHTHA, P-702B, 7.5 HP A/N:	D259				
PUMP, EAST/WEST WATER, P-703A/B, 7.5 HP EACH, 2 TOTAL A/N:	D257				

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: DISTILLATION					
PUMP, AP-205A/B, EAST/WEST SLOP INJECTION, AIR-POWERED A/N:	D508				
PUMP, AP-213, DEHYDRATION CHARGE PUMP DRAIN PUMPS POT, AIR-POWERED A/N:	D509				
System 2: VACUUM DISTILLATION UNIT NO. 1					S15.1
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-404, NORTH VAPORIZER, VACUUM UNIT NO. 1, HEIGHT: 26 FT 6 IN; DIAMETER: 2 FT 6 IN A/N: 528469	D364				
COLUMN, C-205, DISTILLATION, VACUUM UNIT NO. 1, HEIGHT: 28 FT ; DIAMETER: 5 FT A/N: 528469	D236	D240			
PUMP, P-402, C-205 BOTTOMS CIRCULATION, 20 HP A/N: 528469	D354				
PUMP, P-402A, C-205 SEAL FLUSH, 0.25 HP A/N: 528469	D355				
DRUM, PS-1, PUMP SEAL OIL, HEIGHT: 4 FT ; DIAMETER: 3 FT 6 IN A/N: 528469	D363				
PUMP, P-401A/B, NORTH/SOUTH C-205 BOTTOMS, 15 HP EACH, 2 TOTAL A/N: 528469	D356				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: DISTILLATION					
CONDENSER, SHELL AND TUBE, E-400, C-205 OVERHEAD, VACUUM UNIT NO. 1, LENGTH: 14 FT 6 IN; DIAMETER: 2 FT 10 IN A/N: 528469	D240	D1 D236			
ACCUMULATOR, MDO, D-400, LENGTH: 6 FT 9 IN; DIAMETER: 3 FT A/N: 528469	D353				
PUMP, P-403A/B, NORTH/SOUTH MDO, 15 HP EACH, 2 TOTAL A/N: 528469	D357				
EJECTOR, EJ-1A, 1ST STAGE, VACUUM UNIT NO. 1 A/N: 528469	D1	D240 D358			
CONDENSER, SHELL AND TUBE, E-401A, 1ST STAGE, VACUUM UNIT NO. 1, LENGTH: 17 FT ; DIAMETER: 1 FT A/N: 528469	D358	D1 D2			
DRUM, D-401A, CONDENSATE, VACUUM UNIT NO. 1, LENGTH: 3 FT 2 IN; DIAMETER: 3 FT A/N: 528469	D238				
EJECTOR, EJ-1B, 2ND STAGE, VACUUM UNIT NO. 1 A/N: 528469	D2	D358 D359			
CONDENSER, SHELL AND TUBE, E-401B, 2ND STAGE, VACUUM UNIT NO. 1, LENGTH: 13 FT 6 IN; DIAMETER: 8 IN A/N: 528469	D359	D2 D3			

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: DISTILLATION					
DRUM, D-401B, CONDENSATE, VACUUM UNIT NO. 1, LENGTH: 2 FT 6 IN; DIAMETER: 3 FT A/N: 528469	D239				
PUMP, P-404A, NORTH CONDENSATE, 1 HP A/N: 528469	D360				
PUMP, P-404B/C, MIDDLE/SOUTH CONDENSATE, 2 HP EACH, 2 TOTAL A/N: 528469	D520				
EJECTOR, EJ-1C, 3RD STAGE, VACUUM UNIT NO. 1 A/N: 528469	D3	D359 D361			
CONDENSER, SHELL AND TUBE, E-401C, 3RD STAGE, VACUUM UNIT NO. 1, LENGTH: 10 FT 2 IN; DIAMETER: 8 IN A/N: 528469	D361	D3 D128 D176			
HEAT EXCHANGER, SHELL AND TUBE, E-425, CIRCULATION COOLER, LENGTH: 12 FT ; DIAMETER: 2 FT 10 IN A/N: 528469	D362				
PUMP, AP-411, DRAIN POT, AIR-POWERED A/N: 528469	D510				
System 3: VACUUM DISTILLATION UNIT NO.2					S15.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: DISTILLATION					
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-403, SOUTH VAPORIZER, VACUUM UNIT NO. 2, HEIGHT: 26 FT 6 IN; DIAMETER: 2 FT 6 IN A/N: 512558	D299				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-423, VAPORIZER, VACUUM UNIT NO. 2, HEIGHT: 11 FT 8 IN; DIAMETER: 2 FT A/N: 512558	D186				
COLUMN, C-207, DISTILLATION, VACUUM UNIT NO. 2, HEIGHT: 48 FT ; DIAMETER: 7 FT A/N: 512558	D188	D185			
PUMP, P-422A/B, C-207 BOTTOMS CIRCULATION, 50 HP EACH, 2 TOTAL A/N: 512558	D365				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-XX, VAPORIZER, VACUUM UNITS NO. 1 AND NO. 2, LENGTH: 19 FT 2 IN; DIAMETER: 3 FT 8 IN A/N: 512558	D424				
PUMP, P-405A/B, NORTH/SOUTH C-207 BOTTOMS, 15 HP EACH, 2 TOTAL A/N: 512558	D366				
CONDENSER, SHELL AND TUBE, E-420, C-207 OVERHEAD, VACUUM UNIT NO. 2, LENGTH: 14 FT 6 IN; DIAMETER: 2 FT 10 IN A/N: 512558	D185	D180 D188			

- | | |
|--|--|
| <ul style="list-style-type: none"> * (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits | <ul style="list-style-type: none"> (2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements |
|--|--|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: DISTILLATION					
ACCUMULATOR, D-420, VACUUM UNIT NO. 2, LENGTH: 6 FT 2 IN; DIAMETER: 3 FT 4 IN A/N: 512558	D179				
PUMP, P-406A, NORTH MDO, 7.5 HP A/N: 512558	D521				
PUMP, P-406B, SOUTH MDO, 15 HP A/N: 512558	D367				
EJECTOR, EJ-2A, FIRST STAGE, VACUUM UNIT NO. 2 A/N: 512558	D180	D181 D185			
CONDENSER, E-421A, FIRST STAGE, VACUUM UNIT NO. 2, LENGTH: 14 FT ; DIAMETER: 2 FT 8 IN A/N: 512558	D181	D180 D183			
DRUM, D-421A, CONDENSATE, VACUUM UNIT NO. 2, LENGTH: 3 FT ; DIAMETER: 2 FT 6 IN A/N: 512558	D182				
EJECTOR, EJ-2B, SECOND STAGE, VACUUM UNIT NO. 2 A/N: 512558	D183	D181 D184			
CONDENSER, E-421B, SECOND STAGE, VACUUM UNIT NO. 2, LENGTH: 16 FT ; DIAMETER: 1 FT 1 IN A/N: 512558	D184	D183 D370			
DRUM, D-421B, CONDENSATE, VACUUM UNIT NO. 2, LENGTH: 3 FT ; DIAMETER: 2 FT 6 IN A/N: 512558	D368				

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: DISTILLATION					
PUMP, P-407A/B/C, NORTH/MIDDLE/SOUTH CONDENSATE, 2 HP EACH, 3 TOTAL A/N: 512558	D369				
EJECTOR, EJ-2C, THIRD STAGE, VACUUM UNIT NO. 2 A/N: 512558	D370	D184 D373			
CONDENSER, E-421C, THIRD STAGE, VACUUM UNIT NO. 2, LENGTH: 15 FT 2 IN; DIAMETER: 9 IN A/N: 512558	D373	D128 D176 D370			
PUMP, VACUUM, VP-408A, 15 HP A/N: 512558	D176	D128 D361 D373			
HEAT EXCHANGER, E-429, FLUX RUNDOWN COOLER, TUBE/WATER BOX, WIDTH: 8 FT ; HEIGHT: 5 FT 6 IN; LENGTH: 26 FT A/N: 512558	D173				
PUMP, P-011, FLUX CIRCULATION, 15 HP A/N: 512558	D371				
PUMP, P-009, WEST FLUX, 20 HP A/N: 512558	D372				
HEAT EXCHANGER, N-10, FLUX RUNDOWN COOLER A/N: 512558	D102				
DRUM, BLEEDER, 3 TOTAL; DIAMETER: 1 FT ; HEIGHT: 2 FT A/N: 512558	D425				
System 4: VACUUM DISTILLATION UNIT HEATERS					

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2: LUBRICATION OIL PRODUCTION					
CONDENSER, SHELL AND TUBE, WATER COOLED, E-124, PRM OVERHEAD, LENGTH: 8 FT ; DIAMETER: 10 IN A/N: 528469	D344	D5 D258			
POT, CONDENSATE, HEIGHT: 6 FT ; DIAMETER: 3 FT A/N: 528469	D348				
PUMP, P-220/221, CONDENSATE, 2 HP EACH, 2 TOTAL A/N: 528469	D350				
PUMP, P-208A/B, NORTH/SOUTH MDO STRIPPER BOTTOMS, 5 HP EACH, 2 TOTAL A/N: 528469	D349				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-123, PRM CIRCULATION HEATER, LENGTH: 8 FT ; DIAMETER: 8 IN A/N: 528469	D345				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-122A/B, MDO COOLER, 2 TOTAL; DIAMETER: 1 FT 4 IN; LENGTH: 12 FT 2 IN A/N: 528469	D346				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-125, MDO COOLER A/N: 528469	D347				
Process 3: TREATING/STRIPPING					
System 1: NAPHTHA SPLITTER UNIT					S15.1
PUMP, P-601A/B, CHARGE, 3 HP EACH, 2 TOTAL A/N: 547512	D374				

- | | |
|--|--|
| <ul style="list-style-type: none"> * (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits | <ul style="list-style-type: none"> (2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements |
|--|--|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 3: TREATING/STRIPPING					
VESSEL, D-507, NORTH SALT DRYER, HEIGHT: 10 FT 11 IN; DIAMETER: 4 FT 6 IN A/N: 547512	D375				
VESSEL, D-508, SOUTH SALT DRYER, HEIGHT: 10 FT 11 IN; DIAMETER: 4 FT 6 IN A/N: 547512	D376				
PUMP, AP-021, SALT DRYER DRAIN, AIR-POWERED A/N: 547512	D531				
HEAT EXCHANGER, DOUBLE PIPE, E-501A/B, FEED PRE-HEATER, 2 TOTAL; DIAMETER: 1 IN; LENGTH: 9 FT 6 IN A/N: 547512	D377				
HEAT EXCHANGER, DOUBLE PIPE, E-501C/D, FEED PRE-HEATER, 2 TOTAL; DIAMETER: 1 IN; LENGTH: 18 FT A/N: 547512	D422				
COLUMN, C-501, SPLITTER TOWER, HEIGHT: 7 FT 9 IN; DIAMETER: 1 FT 5 IN WITH A/N: 547512	D7	D379			
EVAPORATOR, THIN-FILM, WITH 2 HP ROTOR, P-607, LENGTH: 12 FT 2 IN; DIAMETER: 2 FT 6 IN	D378				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 3: TREATING/STRIPPING					
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-502, OVERHEAD CONDENSER, LENGTH: 5 FT ; DIAMETER: 4 IN A/N: 547512	D379	D7 D8			
PUMP, VACUUM, VP-603, 2 HP A/N: 547512	D8	D9 D379			
ACCUMULATOR, D-501, OVERHEAD SEPARATOR, HEIGHT: 1 FT ; DIAMETER: 8 IN A/N: 547512	D9	D8 D128			
DRUM, D-502, REFLUX SEPARATOR, HEIGHT: 3 FT ; DIAMETER: 8 IN A/N: 547512	D380	D128			
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-503, SEAL WATER COOLER, LENGTH: 2 FT 6 IN; DIAMETER: 4 IN A/N: 547512	D381				
PUMP, P-604, SPLITTER OVERHEAD, 0.75 HP A/N: 547512	D13				
PUMP, P-605, WATER, 0.75 HP A/N: 547512	D11				
ACCUMULATOR, D-503, BOTTOMS, HEIGHT: 4 FT 8 IN; DIAMETER: 10 IN A/N: 547512	D6				
PUMP, SEALLESS, P-602, BOTTOMS, 2 HP A/N: 547512	D12				

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 3: TREATING/STRIPPING					
HEAT EXCHANGER, DOUBLE PIPE, E-504A, BOTTOMS COOLER, LENGTH: 15 FT ; DIAMETER: 4 IN A/N: 547512	D382				
Process 4: ETHYLENE GLYCOL RECYCLING UNIT					
System 1: ETHYLENE GLYCOL DISTILLATION					S15.1
TANK, S-13, USED GLYCOL FEED, 18543 GALS; DIAMETER: 12 FT ; HEIGHT: 20 FT 3 IN A/N: 512565	D383	D128			
PUMP, P-929, TANK S-13 TRANSFER, 5 HP A/N: 512565	D384				
TANK, S-11, USED GLYCOL FEED, 17181 GALS; DIAMETER: 11 FT ; HEIGHT: 22 FT A/N: 512565	D385	D128			
PUMP, P-901, E.G. UNIT CHARGE, 15 HP A/N: 512565	D386				

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 4: ETHYLENE GLYCOL RECYCLING UNIT					
DRUM, D-901, ATMOSPHERIC FLASH, HEIGHT: 9 FT 6 IN; DIAMETER: 2 FT WITH A/N: 512565	D387				
PUMP, P-902, CIRCULATION, 15 HP	D388				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-901A/B, ATMOSPHERIC FEED PREHEATER, 2 TOTAL; DIAMETER: 1 FT 6 IN; LENGTH: 17 FT 6 IN	D389				
DRUM, D-902, VACUUM FLASH, HEIGHT: 9 FT 6 IN; DIAMETER: 2 FT WITH A/N: 512565	D390				
PUMP, P-903, CIRCULATION, 15 HP	D391				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-902A/B, VACUUM PREHEATER, 2 TOTAL; DIAMETER: 1 FT 6 IN; LENGTH: 17 FT 6 IN	D392				
DRUM, D-908, WATER, HEIGHT: 3 FT 5 IN; DIAMETER: 3 FT A/N: 512565	D421				
PUMP, P-904A/B, RESIDUE, 1 HP EACH, 2 TOTAL A/N: 512565	D393				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 4: ETHYLENE GLYCOL RECYCLING UNIT					
TANK, S-12, GLYCOL RESIDUE, 17181 GALS; DIAMETER: 11 FT ; HEIGHT: 22 FT A/N: 512565	D394	D128			
TANK, S-14, GLYCOL RESIDUE, 14219 GALS; DIAMETER: 11 FT ; HEIGHT: 20 FT 9 IN A/N: 512565	D395	D128			
COLUMN, C-901, ATMOSPHERIC, HEIGHT: 27 FT ; DIAMETER: 2 FT WITH A/N: 512565	D396				
PUMP, P-905, C-901 BOTTOMS, 0.75 HP	D397				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-906, C-901 OVERHEAD COOLER, LENGTH: 11 FT 6 IN; DIAMETER: 1 FT 6 IN	D398				
CONDENSER, FF-904, FIN-FAN COOLER, WIDTH: 4 FT 4 IN; HEIGHT: 3 FT 10 IN; LENGTH: 4 FT 7 IN	D399				

- | | |
|--|--|
| <ul style="list-style-type: none"> * (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits | <ul style="list-style-type: none"> (2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements |
|--|--|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 4: ETHYLENE GLYCOL RECYCLING UNIT					
COLUMN, C-902, VACUUM, HEIGHT: 26 FT ; DIAMETER: 2 FT WITH A/N: 512565	D400				
PUMP, P-906, C-902 BOTTOMS, 0.75 HP	D401				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-907, C-902 OVERHEAD COOLER, LENGTH: 11 FT 4 IN; DIAMETER: 1 FT 8 IN	D402				
CONDENSER, FF-903, FIN-FAN COOLER, WIDTH: 4 FT 10 IN; HEIGHT: 2 FT ; LENGTH: 5 FT 8 IN	D122				
PUMP, P-910, VACUUM, 5 HP A/N: 512565	D123				
ACCUMULATOR, D-903, HEIGHT: 2 FT 6 IN; DIAMETER: 1 FT 10 IN A/N: 512565	D121	D128			
PUMP, P-909, V-903 WATER, 0.75 HP A/N: 512565	D124				
DRUM, D-907, REFLUX WATER, HEIGHT: 4 FT ; DIAMETER: 5 FT 10 IN A/N: 512565	D404				
PUMP, P-911A, WATER TANK REFLUX, 0.75 HP A/N: 512565	D405				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 4: ETHYLENE GLYCOL RECYCLING UNIT					
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-908, SEAL WATER COOLER, LENGTH: 1 FT 6 IN; DIAMETER: 6 IN A/N: 512565	D403				
PUMP, P-911B, WATER TANK DISCHARGE, 0.75 HP A/N: 512565	D406				
COLUMN, C-903, VACUUM, HEIGHT: 26 FT ; DIAMETER: 2 FT WITH A/N: 512565	D407				
PUMP, P-907, C-903 BOTTOMS CIRCULATION, 1.5 HP	D408				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-903, REBOILER, LENGTH: 6 FT 9 IN; DIAMETER: 1 FT 8 IN	D409				
HEATER, H-901, ELECTRICALLY-POWERED REBOILER, LENGTH: 5 FT 6 IN; DIAMETER: 5 IN	D410				
CONDENSER, FF-905, FIN-FAN COOLER, WIDTH: 4 FT 4 IN; HEIGHT: 3 FT 10 IN; LENGTH: 4 FT 7 IN A/N: 512565	D411				
PUMP, P-908, E.G. PRODUCT, 1.5 HP A/N: 512565	D412				
VESSEL, D-904, CARBON, HEIGHT: 14 FT 8 IN; DIAMETER: 4 FT A/N: 512565	D413				

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 4: ETHYLENE GLYCOL RECYCLING UNIT					
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-909, COOLER, LENGTH: 5 FT ; DIAMETER: 8 IN A/N: 512565	D420				
VESSEL, D-905, ACTIVATED CARBON, HEIGHT: 14 FT 8 IN; DIAMETER: 4 FT A/N: 512565	D414				
VESSEL, D-906, ACTIVATED CARBON, HEIGHT: 14 FT 8 IN; DIAMETER: 4 FT A/N: 512565	D415				
VESSEL, RESIN BED, UP TO 40 CU. FT. VOLUME A/N: 512565	D416				
TANK, K-7, EG RESIDUE, 3743 GALS; DIAMETER: 7 FT ; HEIGHT: 13 FT A/N: 512565	D417	D128			
PUMP, AP-XXX, EG TO TANK K7, AIR-POWERED, 2 TOTAL A/N: 512565	D545				
PUMP, AP-920, GLYCOL TRANSFER, AIR-POWERED A/N: 512565	D512				
PUMP, AP-922, AIR-POWERED A/N: 512565	D513				
PUMP, P-924, 10 HP A/N: 512565	D514				
PUMP, AP-928, AIR-POWERED A/N: 512565	D515				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 4: ETHYLENE GLYCOL RECYCLING UNIT					
PUMP, AP-930, TRANSFER, AIR-POWERED A/N: 512565	D516				
PUMP, AP-931, AIR-POWERED A/N: 512565	D517				
Process 5: OIL/WATER SEPARATION					
System 1: WASTE WATER TREATMENT					S1.12, S15.6
PUMP, P-012, WATER DRAW - 1100-SERIES TANKS, 3 HP A/N: 447670	D435				
PUMP, P-013, KO-301 DRAIN, 0.75 HP A/N: 447670	D436				
PUMP, P-019B, WATER DRAW : 500-SERIES TANKS, 25 HP A/N: 447670	D437				
PUMP, P-XX1, SWTF TRANSFER, 15 HP A/N: 447670	D438				
PUMP, P-104, N-10 FLUX COOLER DRAIN, 2 HP A/N: 447670	D439				
PUMP, P-307, LAB COLLECTION BOX, 7.5 HP A/N: 447670	D440				
PUMP, P-308, LAB COLLECTION BOX, 5 HP A/N: 447670	D441				
PUMP, P-XX, LAB COLLECTION BOX, 5 HP A/N: 447670	D442				

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
PUMP, P-810, CONTROL ROOM DRAIN, 3 HP A/N: 447670	D443				
BIN, HOP300, SOLID, WITH CHAIN DRIVEN SCRAPER, WIDTH: 6 FT ; HEIGHT: 7 FT ; LENGTH: 12 FT A/N: 447670	D29	D323			H23.2
WASTE WATER SEPARATOR, TR300, WITH SEALED COVER, WIDTH: 8 FT ; HEIGHT: 4 FT ; LENGTH: 80 FT A/N: 447670	D30	D205			H23.2
PUMP, P-300A/B, EAST/WEST TROUGH OUTLET, 30 HP EACH, 2 TOTAL A/N: 447670	D444				
PUMP, P-003, TANK 9001 TRANSFER, 15 HP A/N: 447670	D432				
PUMP, P-004A, EAST TANK 1107 TRANSFER, 30 HP A/N: 447670	D433				
PUMP, P-004B, WEST TANK 1107 TRANSFER, 15 HP A/N: 447670	D434				
TANK, FIXED ROOF, NO. 1108, WASTEWATER, 46200 GALS; DIAMETER: 20 FT ; HEIGHT: 19 FT 11 IN A/N: 447670	D86	D205			

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
TANK, FIXED ROOF, NO.661, WASTEWATER, 28579 GALS; DIAMETER: 16 FT ; HEIGHT: 20 FT A/N: 447670	D96	D205			
TANK, V2, CONE-BOTTOM WASTEWATER SURGE, STEAM-HEATED, 29826 GALS; DIAMETER: 15 FT 6 IN; HEIGHT: 18 FT A/N: 447670	D25	D205			
TANK, HOLDING, NO.624, WASTEWATER, 42000 GALS; DIAMETER: 18 FT ; HEIGHT: 24 FT A/N: 447670	D27	D205			
PUMP, P-522, V2 CIRCULATION, 10 HP A/N: 447670	D446				
PUMP, P-505, TRANSFER, 15 HP A/N: 447670	D447				
PUMP, P-500, DRAIN, 5 HP A/N: 447670	D448				
DRUM, D303, WASTEWATER, BULLET NO. 1, 13,000 GAL, LENGTH: 55 FT ; DIAMETER: 6 FT A/N: 447670	D28	D205			
PUMP, P-501A/B, OUTLET, 15 HP EACH, 2 TOTAL A/N: 447670	D449				
TANK, V1, CONE-BOTTOM WASTEWATER SURGE, 53663 GALS; DIAMETER: 20 FT ; HEIGHT: 20 FT 6 IN A/N: 447670	D26	D205			H23.2

- | | |
|--|--|
| <ul style="list-style-type: none"> * (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits | <ul style="list-style-type: none"> (2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements |
|--|--|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
PUMP, P-504A/B, EAST/WEST CHARGE, 15 HP EACH, 2 TOTAL A/N: 447670	D450				
AIR FLOATATION UNIT, NO.1, HEIGHT: 9 FT 6 IN; DIAMETER: 20 FT A/N: 447670	D33	D205			H23.2
AIR FLOATATION UNIT, NO.2, HEIGHT: 8 FT ; DIAMETER: 13 FT 10 IN A/N: 447670	D32	D205			H23.2
TANK, FLOC ACCUMULATION, HEIGHT: 8 FT 6 IN; DIAMETER: 6 FT 8 IN A/N: 447670	D451	D205			
COLUMN, SURGE, D305, HEIGHT: 8 FT 10 IN; DIAMETER: 3 FT 10 IN A/N: 447670	D190	D205			
PUMP, P-509A/B, CHARGE, 25 HP EACH, 2 TOTAL A/N: 447670	D452				
DRUM, AIR DISSOLVER, HEIGHT: 3 FT 6 IN; DIAMETER: 1 FT A/N: 447670	D453				
PUMP, P-510A/B, 25 HP EACH, 2 TOTAL A/N: 447670	D454				
DRUM, D350, WASTEWATER, BULLET NO. 2, LENGTH: 55 FT ; DIAMETER: 6 FT A/N: 447670	D23	D194			

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
PUMP, P-511A/B, 25 HP EACH, 2 TOTAL A/N: 447670	D455				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-352, STRIPPER PRE-HEATER, LENGTH: 14 FT 6 IN; DIAMETER: 1 FT 10 IN A/N: 447670	D456				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-353, STRIPPER PRE-HEATER, LENGTH: 15 FT 4 IN; DIAMETER: 2 FT A/N: 447670	D457				

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
COLUMN, STRIPPER TOWER, T350, WASTEWATER, HEIGHT: 36 FT ; DIAMETER: 3 FT WITH A/N: 447670	D31	D128			
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-351, STRIPPER REBOILER, LENGTH: 8 FT ; DIAMETER: 2 FT 6 IN	D458				
CONDENSER, SHELL AND TUBE TYPE, E-350, STRIPPER OVERHEAD COOLER, LENGTH: 11 FT ; DIAMETER: 1 FT	D459				
ACCUMULATOR, D-351, STRIPPER OVERHEAD RECEIVER, LENGTH: 7 FT ; DIAMETER: 4 FT	D51				
PUMP, VP-515, VACUUM, 15 HP	D45				
PUMP, P-514A, OVERHEAD RECEIVER, 3 HP	D522				
PUMP, P-514B, OVERHEAD RECEIVER, 5 HP	D460				
PUMP, VP-516A/B, VACUUM, 0.5 HP EACH, 2 TOTAL	D461				
ACCUMULATOR, D-352, HEIGHT: 4 FT ; DIAMETER: 3 FT	D44				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
PUMP, P-512A/B, BOTTOMS, 25 HP EACH, 2 TOTAL A/N: 447670	D462				
PUMP, P-513, BOOSTER, 10 HP A/N: 447670	D463				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-355A/B & E-357A/B, EFFLUENT COOLERS, 4 TOTAL; DIAMETER: 2 FT ; LENGTH: 14 FT 6 IN A/N: 447670	D464				
VESSEL, D-353, ACTIVATED CARBON, HEIGHT: 12 FT 10 IN; DIAMETER: 8 FT A/N: 447670	D46				
VESSEL, D-354, ACTIVATED CARBON, HEIGHT: 12 FT 10 IN; DIAMETER: 8 FT A/N: 447670	D47				
VESSEL, D-355, ACTIVATED CARBON, HEIGHT: 17 FT ; DIAMETER: 8 FT A/N: 447670	D48				
VESSEL, D-356, ACTIVATED CARBON, HEIGHT: 17 FT ; DIAMETER: 8 FT A/N: 447670	D49				
PUMP, P-521, CIRCULATION, 10 HP A/N: 447670	D465				
VESSEL, D-710, ACTIVATED CARBON, HEIGHT: 12 FT 10 IN; DIAMETER: 8 FT A/N: 447670	D200				

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
VESSEL, D-711, ACTIVATED CARBON, HEIGHT: 12 FT 10 IN; DIAMETER: 8 FT A/N: 447670	D201				
TANK, FIXED ROOF, NO.701, TREATED WATER, HEIGHT: 26 FT ; DIAMETER: 17 FT 6 IN A/N: 447670	D36	D136			
TANK, FIXED ROOF, NO. 702, 703, 704 & 705, TREATED WATER, 4 TOTAL, HEIGHT: 24 FT ; DIAMETER: 17 FT A/N: 447670	D38	D136			
TANK, FIXED ROOF, NO.706, TREATED WATER, HEIGHT: 36 FT ; DIAMETER: 12 FT A/N: 447670	D37	D136			
PUMP, P-518, CIRCULATION, 7.5 HP A/N: 447670	D466				
PUMP, P-519/520, DISCHARGE, 10 HP EACH, 2 TOTAL A/N: 447670	D467				
ENCLOSURE, LACSD EFFLUENT DISCHARGE, WIDTH: 3 FT ; HEIGHT: 4 FT 8 IN; LENGTH: 3 FT A/N: 447670	D468	D136			K67.20
PUMP, P-517, BACKWASH, 60 HP A/N: 447670	D511				

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
PUMP, LIST OF SUMP PUMPS WITH A/N: 447670	B469				
PUMP, AP-014, VACUUM UNITS SUMP, AIR-POWERED	D494				
PUMP, AP-214, HOT OIL EXCHANGERS SUMP, AIR-POWERED	D470				
PUMP, AP-306, SUMP, AIR-POWERED	D471				
PUMP, P-309, SUMP, 3 HP	D472				
PUMP, P-310, SUMP, 10 HP	D473				
PUMP, P-311, SUMP, 15 HP	D474				
PUMP, P-312, SUMP, 7.5 HP	D475				
PUMP, AP-313, SUMP, AIR-POWERED	D476				
PUMP, P-314, SUMP, 5 HP	D477				
PUMP, AP-315, SUMP, AIR-POWERED	D478				
PUMP, AP-316, SUMP, AIR-POWERED	D479				

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
PUMP, LIST OF SUMP PUMPS, CONTINUED WITH A/N: 447670	B518				
PUMP, P-318, SUMP, 15 HP	D480				
PUMP, AP-319, SUMP, AIR-POWERED	D481				
PUMP, P-320, SUMP, 5 HP	D482				
PUMP, AP-321, SUMP, AIR-POWERED	D483				
PUMP, AP-324, SUMP, AIR-POWERED	D484				
PUMP, AP-327, SUMP, AIR-POWERED	D485				
PUMP, AP-328, SUMP, AIR-POWERED	D486				
PUMP, AP-329, SUMP, AIR-POWERED	D487				
PUMP, AP-330, SUMP, AIR-POWERED	D488				
PUMP, AP-331, SUMP, AIR-POWERED	D489				
PUMP, AP-413, SUMP, AIR-POWERED	D490				

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
PUMP, LIST OF SUMP PUMPS, CONTINUED WITH A/N: 447670	B519				
PUMP, P-912, SUMP, 7.5 HP	D491				
PUMP, P-923, SUMP, 7.5 HP	D492				
PUMP, AP-925, SUMP, AIR-POWERED	D493				
PUMP, P-538, SUMP, 3 HP	D504				
PUMP, P-XX, SUMP, 5 HP, WALKWAY WEST OF VACUUM UNIT #1	D523				
PUMP, AP-XXX, SUMP, LOADING RACK #8, AIR-POWERED	D535				
PUMP, P-XX, SUMP, 5 HP, A-SERIES TANKS	D536				
PUMP, AP-322, SUMP, TANK 55001, AIR-POWERED	D537				
PUMP, AP-XXX, SUMP, VAC UNITS, AIR-POWERED, 2 TOTAL	D538				
PUMP, AP-XXX, SUMP, EG UNIT AREA BY SINK, AIR-POWERED	D541				
PUMP, AP-XXX, SUMP, EG UNIT AREA BY D-908, AIR-POWERED	D542				

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
PUMP, P-XX, SUMP, 7.5 HP, BOILER	D543				
PUMP, LIST OF AIR-POWERED PUMPS WITH A/N: 447670	B495				
PUMP, AP-302, CIRCULATION/STORAGE, AIR-POWERED	D497				
PUMP, AP-502, TRANSFER, AIR-POWERED	D498				
PUMP, AP-503, SKIM, AIR-POWERED	D499				
PUMP, AP-506, TRANSFER, AIR-POWERED	D500				
PUMP, AP-507A/B, EAST/WEST FLOC TANK, 2 TOTAL, AIR-POWERED	D501				
PUMP, AP-523, CIRCULATION, AIR-POWERED	D502				
PUMP, AP-524, 1107 WELL WATER DRAIN, AIR-POWERED	D503				
PUMP, AP-709, SEAL POT DRAIN, AIR-POWERED	D505				
PUMP, AP-710, TANK 180 DRAIN, AIR-POWERED	D506				

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
PUMP, LIST OF AIR-POWERED PUMPS, CONTINUED WITH A/N: 447670	B549				
PUMP, AP-005, TANK 1107 DRAIN, AIR-POWERED	D526				
PUMP, AP-018, TANK 55001 SKIM, AIR-POWERED	D527				
PUMP, AP-022, KO-501 DRAIN, AIR-POWERED	D528				
PUMP, AP-XXX, TANK 151/181 TRANSFER, AIR-POWERED	D532				
PUMP, AP-XXX, TANK 661/1108 TRANSFER, AIR-POWERED	D533				
PUMP, AP-XXX, KO-400/401 DRAIN, AIR-POWERED	D534				
PUMP, AP-XXX, D-355/D-356 DRAIN, AIR-POWERED	D539				
PUMP, AP-XXX, COLLECTION CONTAINER DRAIN, AIR-POWERED	D540				
PUMP, AP-XXX, MISCELLANEOUS, AIR-POWERED, 5 TOTAL	D544				
System 2: SLUDGE DEWATERING					S1.2

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
UNLOADING STATION, TRUCK WASHOUT, LOCATED INSIDE THE TRUCK WASHOUT ENCLOSURE, WITH A 10 HP CONVEYOR, WIDTH: 8 FT ; HEIGHT: 7 FT ; LENGTH: 28 FT A/N:	D52	D322			H23.2
PUMP, AP-301, WASHOUT BOX, AIR-POWERED A/N:	D496				
TANK, HOLDING, V-701, WASTE WATER, 500 BBL A/N:	D60	D322			
CENTRIFUGE, SHARPLES, MODEL P-4600 SUPER-D-CANTER, 75 HP ELECTRIC MOTOR WITH ENCLOSURE, CENTRIFUGE UNIT, WIDTH: 11 FT ; HEIGHT: 17 FT ; LENGTH: 21 FT	D64	D322			H23.2
HOPPER, PORTABLE, UP TO 4 CUBIC YARD CAPACITY EACH, COVERED, 10 TOTAL A/N:	D418				H23.2
BIN, ROLLOFF, UP TO 40 CUBIC YARD CAPACITY EACH, COVERED, 10 TOTAL A/N:	D524				
System 3: STORAGE SILO					

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
STORAGE SILO, 1400 CU FT CAPACITY, FLY ASH, CEMENT KILN DUST, WITH A SEALED 10" DISCHARGE AUGER AND A 10 HP ELECTRIC MOTOR, HEIGHT: 37 FT ; DIAMETER: 8 FT 6 IN WITH A/N: 514875	D329			PM: (9) [RULE 404, 2-7-1986; RULE 405, 2-7-1986]	C1.6, D323.1, E184.1, H23.12, K67.18
FILTER, VENT, 150 SQ FT TOTAL FILTER AREA, WITH 18 FILTER BAGS, EACH, LENGTH: 4 FT ; DIAMETER: 8 IN	C330				
Process 6: STORAGE TANKS					
System 1: FIXED ROOF STORAGE TANKS : SOUTHWEST TANK FARM					S15.4
STORAGE TANK, FIXED ROOF, NO.1001, USED OIL, 1000 BBL; DIAMETER: 14 FT ; HEIGHT: 37 FT A/N: 493144	D71				B22.6, C1.1, E336.4, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO.1002, USED OIL, 1000 BBL; DIAMETER: 14 FT ; HEIGHT: 37 FT A/N: 493145	D73				B22.6, C1.1, E336.4, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO.1003, USED OIL, 1000 BBL; DIAMETER: 14 FT ; HEIGHT: 37 FT A/N: 493146	D74				B22.6, C1.1, E336.4, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO.1004, USED OIL, 1000 BBL; DIAMETER: 14 FT ; HEIGHT: 37 FT A/N: 493147	D80				B22.6, C1.1, E336.4, H23.6, H23.7, K67.4

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 6: STORAGE TANKS					
STORAGE TANK, FIXED ROOF, NO.1005, USED OIL, 1000 BBL; DIAMETER: 14 FT ; HEIGHT: 37 FT A/N: 493148	D81				B22.6, C1.1, E336.4, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO. 1006, USED OIL, 1000 BBL; DIAMETER: 14 FT ; HEIGHT: 37 FT A/N: 493149	D82				B22.6, C1.1, E336.4, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO. 1007, USED OIL, 1000 BBL; DIAMETER: 14 FT ; HEIGHT: 37 FT A/N: 493150	D83				B22.6, C1.1, E336.4, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO. 1008, USED OIL, 1000 BBL; DIAMETER: 14 FT ; HEIGHT: 37 FT A/N: 493151	D84				B22.6, C1.1, E336.4, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO. 2003, USED OIL, 2500 BBL; DIAMETER: 30 FT 6 IN; HEIGHT: 20 FT A/N: 493152	D88				B22.6, C1.8, E336.4, H23.6, H23.7, H23.13, K67.4
STORAGE TANK, FIXED ROOF, NO. 520, MARINE DIESEL OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512755	D225				B22.10, C1.2, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO. 521, MARINE DIESEL OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512756	D224				B22.10, C1.2, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO. 522, MARINE DIESEL OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512757	D223				B22.10, C1.2, E336.4, K67.4

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 6: STORAGE TANKS					
STORAGE TANK, FIXED ROOF, NO. 523, MARINE DIESEL OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512758	D222				B22.10, C1.2, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO. 524, MARINE DIESEL OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512759	D221				B22.10, C1.2, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO. 525, MARINE DIESEL OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512760	D220				B22.10, C1.2, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO. 526, WASTEWATER, USED OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512761	D219				B22.6, B22.7, C1.1, C1.3, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO. 527, WASTEWATER, USED OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512762	D218				B22.6, B22.7, C1.1, C1.3, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO. 528, WASTEWATER, USED OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512763	D217				B22.6, B22.7, C1.1, C1.3, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO. 529, WASTEWATER, USED OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512764	D216				B22.6, B22.7, C1.1, C1.3, E336.4, K67.4

- | | |
|--|--|
| <ul style="list-style-type: none"> * (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits | <ul style="list-style-type: none"> (2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements |
|--|--|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 6: STORAGE TANKS					
STORAGE TANK, FIXED ROOF, NO. 530, WASTEWATER, USED OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512765	D215				B22.6, B22.7, C1.1, C1.3, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO. 531, WASTEWATER, USED OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512766	D214				B22.6, B22.7, C1.1, C1.3, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO. 532, WASTEWATER, USED OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512767	D213				B22.6, B22.7, C1.1, C1.3, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO. 533, WASTEWATER, USED OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512768	D212				B22.6, B22.7, C1.1, C1.3, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO. 534, WASTEWATER, USED OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512769	D211				B22.6, B22.7, C1.1, C1.3, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO. 535, WASTEWATER, USED OIL, 514 BBL; DIAMETER: 12 FT ; HEIGHT: 27 FT A/N: 512770	D210				B22.6, B22.7, C1.1, C1.3, E336.4, K67.4
System 2: FIXED ROOF STORAGE TANKS : WASTEWATER TANKS					S15.4

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 6: STORAGE TANKS					
STORAGE TANK, FIXED ROOF, NO. 151, WASTEWATER, 6670 GALS; DIAMETER: 8 FT ; HEIGHT: 19 FT A/N: 512567	D209				B22.7, C1.3, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO.181, WASTEWATER, 8398 GALS; DIAMETER: 8 FT 3 IN; HEIGHT: 22 FT A/N: 493889	D92				B22.7, C1.3, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO.1009, WASTEWATER, USED OIL, 42657 GALS; DIAMETER: 22 FT ; HEIGHT: 16 FT 4 IN A/N: C35633	D67				B22.6, B22.7, C1.1, C1.3, E336.4, K67.4
STORAGE TANK, FIXED ROOF, NO. 1107, WASTEWATER, USED OIL, 43479 GALS; DIAMETER: 20 FT ; HEIGHT: 19 FT 9 IN A/N: 493883	D85				B22.6, B22.7, C1.1, C1.3, E336.4, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO. 1109, WASTEWATER, USED OIL, 43879 GALS; DIAMETER: 20 FT ; HEIGHT: 19 FT 8 IN A/N: 493887	D87				B22.6, B22.7, C1.1, C1.3, E336.4, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO.2001, WASTEWATER, 2500 BBL; DIAMETER: 30 FT 6 IN; HEIGHT: 20 FT A/N: 493143	D68				B22.7, C1.3, E336.4, H23.6, H23.7, H23.13, K67.4
STORAGE TANK, FIXED ROOF, NO.2002, WASTEWATER, 2500 BBL; DIAMETER: 30 FT 6 IN; HEIGHT: 20 FT A/N: 493142	D66				B22.7, C1.3, E336.4, H23.6, H23.7, H23.13, K67.4

- | | |
|--|--|
| <ul style="list-style-type: none"> * (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits | <ul style="list-style-type: none"> (2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements |
|--|--|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 6: STORAGE TANKS					
STORAGE TANK, FIXED ROOF, NO.8001, WASTEWATER, 336000 GALS; DIAMETER: 52 FT ; HEIGHT: 23 FT A/N: 512566	D93				B22.7, C1.3, E336.4, H23.6, H23.7, H23.13, K67.4
STORAGE TANK, FIXED ROOF, NO.9001, WASTEWATER, USED OIL, 378000 GALS; DIAMETER: 48 FT ; HEIGHT: 28 FT A/N: 493890	D94				B22.6, B22.7, C1.1, C1.3, E336.4, H23.6, H23.7, H23.13, K67.4
STORAGE TANK, FIXED ROOF, NO.9002, WASTEWATER, USED OIL, 378000 GALS; DIAMETER: 48 FT ; HEIGHT: 28 FT A/N: 493891	D95				B22.6, B22.7, C1.1, C1.3, E336.4, H23.6, H23.7, H23.13, K67.4
STORAGE TANK, FIXED ROOF, NO.55001, WASTEWATER, 58000 BBL; DIAMETER: 93 FT ; HEIGHT: 48 FT A/N: 493880	D79				B22.7, C1.3, E336.4, H23.6, H23.7, H23.13, K67.4
System 4: FIXED ROOF STORAGE TANKS : RCRA FUEL & NAPHTHA TANKS					S15.5
STORAGE TANK, FIXED ROOF, NO.501, NAPHTHA, 22144 GALS; DIAMETER: 15 FT ; HEIGHT: 17 FT 10 IN A/N: C33640	D72				B22.8, C1.10, E336.5, H23.6, H23.7, H23.13, K67.4
STORAGE TANK, FIXED ROOF, NO.502, NAPHTHA, 22144 GALS; DIAMETER: 15 FT ; HEIGHT: 17 FT 10 IN A/N: C33639	D70				B22.8, C1.10, E336.5, H23.6, H23.7, H23.13, K67.4

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 6: STORAGE TANKS					
STORAGE TANK, FIXED ROOF, NO. 503, NAPHTHA, 22144 GALS; DIAMETER: 15 FT ; HEIGHT: 17 FT 10 IN A/N: 493867	D89				B22.8, C1.10, E336.5, H23.6, H23.7, H23.13, K67.4
STORAGE TANK, FIXED ROOF, NO. 504, NAPHTHA, 22144 GALS; DIAMETER: 15 FT ; HEIGHT: 17 FT 10 IN A/N: 493874	D65				B22.8, C1.10, E336.5, H23.6, H23.7, H23.13, K67.4
STORAGE TANK, FIXED ROOF, NO.505, NAPHTHA, 22144 GALS; DIAMETER: 15 FT ; HEIGHT: 17 FT 10 IN A/N: 493877	D90				B22.8, C1.10, E336.5, H23.6, H23.7, H23.13, K67.4
STORAGE TANK, FIXED ROOF, NO.515, RCRA FUEL, 21000 GALS; DIAMETER: 16 FT ; HEIGHT: 14 FT 6 IN WITH A/N: C34790	D69				B22.11, C1.9, E336.5, H23.6, H23.7, H23.13, K67.4
PUMP, AP-XXX, TANK 515/516 TRANSFER, AIR-POWERED	D546				
PUMP, AP-XXX, TANK 515 CIRCULATION, AIR-POWERED	D547				
STORAGE TANK, FIXED ROOF, NO.516, RCRA FUEL, 21000 GALS; DIAMETER: 16 FT ; HEIGHT: 14 FT 6 IN WITH A/N: 213214	D91				B22.11, C1.9, E336.5, H23.6, H23.7, H23.13, K67.4
PUMP, AP-XXX, TANK 516 CIRCULATION, AIR-POWERED	D548				

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 6: STORAGE TANKS					
System 5: FIXED ROOF STORAGE TANKS : PRODUCT TANKS					S15.3
STORAGE TANK, FIXED ROOF, NO.506, MARINE DIESEL OIL, 21000 GALS; DIAMETER: 12 FT ; HEIGHT: 25 FT 8 IN A/N: 512137	D77				B22.10, C1.2, E336.1, K67.4
STORAGE TANK, FIXED ROOF, NO.507, MARINE DIESEL OIL, 21000 GALS; DIAMETER: 12 FT ; HEIGHT: 25 FT 8 IN A/N: 512138	D78				B22.10, C1.2, E336.1, K67.4
STORAGE TANK, FIXED ROOF, NO.1101, ASPHALT FLUX, 48152 GALS; DIAMETER: 21 FT ; HEIGHT: 19 FT 7 IN A/N: 213226	D104				B22.3, C1.7, C6.2, E336.1, K67.4
STORAGE TANK, FIXED ROOF, NO.1102, ASPHALT FLUX, 48152 GALS; DIAMETER: 21 FT ; HEIGHT: 19 FT 7 IN A/N: 213227	D105				B22.3, C1.7, C6.2, E336.1, K67.4
STORAGE TANK, FIXED ROOF, NO.1103, MARINE DIESEL OIL, 48152 GALS; DIAMETER: 21 FT ; HEIGHT: 19 FT 7 IN A/N: 493894	D106				B22.10, C1.2, E336.1, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO.1104, MARINE DIESEL OIL, 48152 GALS; DIAMETER: 21 FT ; HEIGHT: 19 FT 7 IN A/N: 493900	D103				B22.10, C1.2, E336.1, H23.6, H23.7, K67.4

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 6: STORAGE TANKS					
STORAGE TANK, FIXED ROOF, NO.1105, MARINE DIESEL OIL, 48152 GALS; DIAMETER: 21 FT ; HEIGHT: 19 FT 7 IN A/N: 512139	D75				B22.10, C1.2, E336.1, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO.1106, MARINE DIESEL OIL, 48152 GALS; DIAMETER: 21 FT ; HEIGHT: 19 FT 7 IN A/N: 512140	D76				B22.10, C1.2, E336.1, H23.6, H23.7, K67.4
System 6: FIXED ROOF STORAGE TANKS : A-SERIES TANKS					S15.3
STORAGE TANK, FIXED ROOF, NO. A-1, ASPHALT FLUX, 44654 GALS; DIAMETER: 20 FT ; HEIGHT: 19 FT 11 IN A/N: 511871	D309				B22.3, C1.5, C6.1, E336.1, K67.4
STORAGE TANK, FIXED ROOF, NO. A-2, WITH A STEAM HEATING COIL, USED GLYCOL, 44654 GALS; DIAMETER: 20 FT ; HEIGHT: 19 FT 11 IN A/N: 493901	D107				B22.5, C1.11, C6.3, E336.1, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO.A-3, USED GLYCOL, 44654 GALS; DIAMETER: 20 FT ; HEIGHT: 19 FT 11 IN A/N: 493902	D109				B22.5, C1.11, E336.1, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO.A-4, USED GLYCOL, 44654 GALS; DIAMETER: 20 FT ; HEIGHT: 19 FT 11 IN A/N: 493903	D112				B22.5, C1.11, E336.1, H23.6, H23.7, K67.4

- | | |
|--|--|
| <ul style="list-style-type: none"> * (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits | <ul style="list-style-type: none"> (2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements |
|--|--|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 6: STORAGE TANKS					
STORAGE TANK, FIXED ROOF, NO.A-5, USED GLYCOL, 44654 GALS; DIAMETER: 20 FT ; HEIGHT: 19 FT 11 IN A/N: 493905	D111				B22.5, C1.11, E336.1, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO.A-6, USED GLYCOL, 44654 GALS; DIAMETER: 20 FT ; HEIGHT: 19 FT 11 IN A/N: 493906	D108				B22.5, C1.11, E336.1, H23.6, H23.7, K67.4
STORAGE TANK, FIXED ROOF, NO. A-7, HEATED, USED GLYCOL, 44654 GALS; DIAMETER: 20 FT ; HEIGHT: 19 FT 11 IN WITH A/N: 493907	D113				B22.5, C1.11, C6.4, E336.1, H23.6, H23.7, K67.4
PUMP, CIRCULATION, P-933, 25 HP	D341				
HEAT EXCHANGER, EXTERNAL STEAM HEAT, SHELL AND TUBE	D340				
PUMP, TANK A-7 TRANSFER, P-921, 15 HP	D342				

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 6: STORAGE TANKS					
STORAGE TANK, FIXED ROOF, NO.A-8, USED OIL, USED GLYCOL, 44654 GALS; DIAMETER: 20 FT ; HEIGHT: 19 FT 11 IN WITH A/N: 493908	D110				B22.5, C1.11, C6.4, E336.1, H23.6, H23.7, K67.4
PUMP, AP-020, TANK A-8 TRANSFER, AIR-POWERED	D529				
PUMP, AP-XXX, TANK A-8 DRAIN, AIR-POWERED	D530				
System 7: FIXED ROOF STORAGE TANKS : N-SERIES TANKS					S15.3
STORAGE TANK, FIXED ROOF, NO. N-3, ASPHALT FLUX, 44654 GALS; DIAMETER: 20 FT ; HEIGHT: 19 FT 11 IN A/N: 512983	D99				B22.3, C1.5, C6.1, E336.1, K67.4
STORAGE TANK, FIXED ROOF, NO. N-4, ASPHALT FLUX, 44654 GALS; DIAMETER: 20 FT ; HEIGHT: 19 FT 11 IN A/N: 513071	D100				B22.3, C1.5, C6.1, E336.1, K67.4
STORAGE TANK, FIXED ROOF, NO. 1110, ASPHALT FLUX, 44654 GALS; DIAMETER: 20 FT ; HEIGHT: 19 FT 11 IN A/N: 513070	D101				B22.3, C1.5, C6.1, E336.1, K67.4
Process 7: LOADING AND UNLOADING RACKS					
System 1: USED OIL UNLOADING					S1.4
UNLOADING ARM, BOTTOM, TANK TRUCK, USED OIL, 6 TOTAL A/N: 512564	D231				B22.6, K67.4

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 7: LOADING AND UNLOADING RACKS					
PUMP, TRANSFER, P-100A, P-100B, P-101A, P-101B, P-102A, P-102B, 25 HP EACH, 6 TOTAL A/N: 512564	D232				
System 2: WASTEWATER UNLOADING					S1.5
UNLOADING ARM, BOTTOM, TANK TRUCK, WASTEWATER, 12 TOTAL A/N: 494201	D242				B22.7, K67.4
VAPOR RETURN LINE, 4 TOTAL CONNECTIONS A/N: 494201	D243	D24			
TANK, BLOWDOWN BLADDER, WASTEWATER, HEIGHT: 20 FT ; DIAMETER: 16 FT A/N: 494201	D24	C34 C35 D243			
CARBON ADSORBER, TWO IN SERIES, 150 LBS EACH A/N: 494201	C34	D24		VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.3, E128.1, E153.1, K67.22
CARBON ADSORBER, TWO IN SERIES, 150 LBS EACH A/N: 494201	C35	D24		VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.3, E128.1, E153.1, K67.22
System 3: USED GLYCOL UNLOADING					S1.3
UNLOADING ARM, BOTTOM, TANK TRUCK, USED GLYCOL, 3 TOTAL A/N: 512562	D336				B22.5, K67.4
PUMP, TRANSFER, P-927, 25 HP A/N: 512562	D337				
System 4: FUEL OIL CUTTER LOADING					S1.7, S15.9

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 7: LOADING AND UNLOADING RACKS					
LOADING ARM, BOTTOM, TANK TRUCK, FUEL OIL CUTTER, 2 TOTAL A/N: 494199	D229				B22.9, E336.3, K67.4
PUMP, NORTH FUEL OIL SHIPPING, P-001A, 25 HP A/N: 494199	D230				
PUMP, SOUTH FUEL OIL SHIPPING, P-001B, 30 HP A/N: 494199	D310				
System 5: NAPHTHA LOADING					S1.6, S13.3, S15.9
LOADING ARM, BOTTOM, TANK TRUCK, NAPHTHA A/N: 512559	D227			VOC: 0.08 LBS/1000 GAL ORGANIC LIQUID (5) [RULE 462, 5-14-1999]	B22.8, E336.3, K67.4
PUMP, SEAL-LESS, NAPHTHA SHIPPING, P-606, 15 HP A/N: 512559	D228				
System 6: MARINE DIESEL OIL LOADING					S1.8, S15.9
LOADING ARM, BOTTOM, TANK TRUCK, MARINE DIESEL OIL, 4 TOTAL A/N: 512561	D338				B22.10, E336.3, K67.4
PUMP, MDO SHIPPING, 15 HP A/N: 512561	D339				
PUMP, P-XX3, SWTF : MDO SHIPPING, 25 HP A/N: 512561	D507				
System 7: ASPHALT FLUX LOADING - RACK NO. 4					S1.1, S15.9
LOADING ARM, BOTTOM, TANK TRUCK, ASPHALT FLUX, 2 TOTAL A/N: 511874	D20				B22.3, E336.3, K67.4

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 7: LOADING AND UNLOADING RACKS					
PUMP, FLUX SHIPPING, P-103, 25 HP A/N: 511874	D21				
System 8: ASPHALT FLUX LOADING - RACK NO. 7					S1.1, S15.8
LOADING ARM, TANK TRUCK, TOP AND BOTTOM, ASPHALT FLUX A/N: 511876	D16				B22.3, E336.2, K67.4
PUMP, EAST FLUX TOP LOADING, P-006, 10 HP A/N: 511876	D10				
PUMP, FLUX LOADING, P-007, 25 HP A/N: 511876	D19				
System 9: RCRA FUEL LOADING AND UNLOADING					S1.9, S1.10, S13.3, S15.9
LOADING ARM, BOTTOM, TANK TRUCK, RCRA FUEL A/N: 512560	D233			VOC: 0.08 LBS/1000 GAL ORGANIC LIQUID (5) [RULE 462, 5-14-1999]	B22.11, E336.3, K67.4
PUMP, RCRA FUEL SHIPPING, AP-XXX, AIR-POWERED A/N: 512560	D352			VOC: 0.08 LBS/1000 GAL ORGANIC LIQUID (5) [RULE 462, 5-14-1999]	
UNLOADING ARM, BOTTOM, TANK TRUCK, RCRA FUEL A/N: 512560	D235				B22.11, K67.4
PUMP, RCRA FUEL RECEIVING, P-008, 25 HP A/N: 512560	D234				
System 10: USED GLYCOL LOADING					S1.13, S15.8
LOADING ARM, BOTTOM, TANK TRUCK, USED GLYCOL A/N: 519868	D552				B22.5, E336.2, K67.4
PUMP, AP-XXX, USED GLYCOL SHIPPING, AIR-POWERED A/N: 519868	D553				

- | | |
|--|--|
| <ul style="list-style-type: none"> * (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits | <ul style="list-style-type: none"> (2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements |
|--|--|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 7: LOADING AND UNLOADING RACKS					
System 11: MARINE DIESEL OIL UNLOADING					S1.14
UNLOADING ARM, BOTTOM, TANK TRUCK, MARINE DIESEL OIL A/N: 551689	D562				B22.10, K67.4
PUMP, MARINE DIESEL OIL UNLOADING, SINGLE MECHANICAL SEALS, P-XXX, 7.5 HP A/N: 551689	D563				
Process 8: STEAM GENERATION					
BOILER, NATURAL GAS, CLEAVER BROOKS, MODEL CB700-800-200 FIRETUBE TYPE, WITH LOW NOX BURNER, FLUE GAS RECIRCULATION, 33.472 MMBTU/HR WITH A/N: 395526 BURNER, NATURAL GAS, TODD, MODEL DRMB, ONE BURNER, WITH LOW NOX BURNER, 33.472 MMBTU/HR	D116		NOX: LARGE SOURCE**	CO: 400 PPMV (5) [RULE 1146, 11-17-2000; RULE 1146, 9-5-2008]; CO: 2000 PPMV (5A) [RULE 407, 4-2-1982]; NOX: 9 PPMV NATURAL GAS (4) [RULE 2005, 10-15-1993]; NOX: 9 PPMV NATURAL GAS (3) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	D12.9, D328.1, H23.9, K67.12

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 8: STEAM GENERATION					
BOILER, NATURAL GAS, KEWANEE, MODEL H33-1000, WITH LOW NOX BURNER, FLUE GAS RECIRCULATION, 39.5 MMBTU/HR WITH A/N: 307640 BURNER, NATURAL GAS, TODD, MODEL DRMB, ONE BURNER, WITH LOW NOX BURNER, 39.5 MMBTU/HR	D191		NOX: LARGE SOURCE**	CO: 400 PPMV (5) [RULE 1146, 11-17-2000; RULE 1146, 9-5-2008]; CO: 2000 PPMV (5A) [RULE 407, 4-2-1982]; NOX: 9 PPMV NATURAL GAS (3) [RULE 2012, 5-6-2005]; NOX: 9 PPMV NATURAL GAS (4) [RULE 2005, 10-15-1993]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	D12.9, D328.1, H23.9, K67.12
Process 9: AIR POLLUTION CONTROL					
System 1: VAPOR RECOVERY SYSTEM - NORTH TANK FARMS					S15.2, S18.6
CARBON ADSORBER, 150 LBS A/N:	C311			VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.5, D90.7, E128.1, E153.1, K67.10
KNOCK OUT POT, KO-200, HEIGHT: 6 FT 7 IN; DIAMETER: 2 FT 6 IN A/N:	D131				
CARBON ADSORBER, 150 LBS A/N:	C312			VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.5, D90.7, E128.1, E153.1, K67.10
KNOCK OUT POT, KO-201, HEIGHT: 7 FT ; DIAMETER: 3 FT 5 IN A/N:	D129				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
KNOCK OUT POT, KO-202, HEIGHT: 6 FT 8 IN; DIAMETER: 2 FT A/N:	D130				
POT, SEAL, SP-200, HEIGHT: 5 FT 10 IN; DIAMETER: 2 FT A/N:	D193				
BLOWER, VACUUM, BL-702, 5 HP A/N:	D195	C142 C281			D90.6, K67.11
System 2: VAPOR RECOVERY SYSTEM - SOUTH TANK FARMS					S15.2, S18.4
CARBON ADSORBER, 150 LBS A/N:	C303			VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.5, D90.7, E128.1, E153.1, K67.10
KNOCK OUT POT, KO-500, HEIGHT: 5 FT ; DIAMETER: 2 FT A/N:	D134				
KNOCK OUT POT, KO-505, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N:	D283				
CARBON ADSORBER, TWO IN SERIES, EACH 150 LBS A/N:	C313			VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.5, D90.7, E128.1, E153.1, K67.10
KNOCK OUT POT, KO-506, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N:	D286				
CARBON ADSORBER, 150 LBS A/N:	C304			VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.5, D90.7, E128.1, E153.1, K67.10
KNOCK OUT POT, KO-501, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N:	D135				

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
KNOCK OUT POT, KO-502, HEIGHT: 13 FT 4 IN; DIAMETER: 9 FT 4 IN A/N:	D136	D36 D37 D38 D468			
KNOCK OUT POT, KO-503, HEIGHT: 6 FT 6 IN; DIAMETER: 2 FT A/N:	D291				
KNOCK OUT POT, KO-504, HEIGHT: 3 FT 6 IN; DIAMETER: 3 FT 5 IN A/N:	D292				
BLOWER, VACUUM, BL-701B, 15 HP A/N:	D196	C142 C281			D90.6, K67.11
BLOWER, VACUUM, BL-701A, 15 HP A/N:	D284	C142 C281			D90.6, K67.11
System 3: VAPOR RECOVERY SYSTEM - PROCESS WASTE GAS					S15.2, S18.2
KNOCK OUT POT, KO-703, HEIGHT: 7 FT 4 IN; DIAMETER: 1 FT 10 IN A/N:	D295	D128			
KNOCK OUT POT, KO-700, HEIGHT: 7 FT 4 IN; DIAMETER: 2 FT A/N:	D294	D128			
PUMP, KO POT DRAIN, P-708, 5 HP A/N:	D250				
SCRUBBER, D-601, HEIGHT: 29 FT ; DIAMETER: 2 FT A/N: 514876	C137				C8.1, C8.8, K67.19
SCRUBBER, D-602, SPARE, HEIGHT: 29 FT ; DIAMETER: 2 FT A/N: 514876	C138				C8.1, C8.8, K67.19
DRUM, CAUSTIC, D-606, LENGTH: 16 FT ; DIAMETER: 8 FT A/N: 514876	D248				

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
PUMP, NORTH CAUSTIC CIRCULATION, P-704A, 5 HP A/N: 514876	D251				
PUMP, MIDDLE CAUSTIC CIRCULATION, P-704B, 3 HP A/N: 514876	D282				
PUMP, SOUTH CAUSTIC CIRCULATION, P-704C, 5 HP A/N: 514876	D325				
DRUM, WASH WATER, D-607, LENGTH: 11 FT ; DIAMETER: 3 FT 6 IN A/N: 514876	D249				
PUMP, SOUTH HOT WATER WASH FOR SCRUBBER, P-705, 5 HP A/N: 514876	D252				
KNOCK OUT POT, KO-701, HEIGHT: 13 FT ; DIAMETER: 3 FT A/N: 514876	D290				
PUMP, KO TANK DRAIN, P-706, 5 HP A/N: 514876	D253				
KNOCK OUT POT, KO-702, HEIGHT: 13 FT ; DIAMETER: 4 FT 2 IN A/N:	D141	C281			
PUMP, KO-702 DRAIN, P-711, 5 HP A/N:	D254				
KNOCK OUT POT, KO-704, HEIGHT: 5 FT 6 IN; DIAMETER: 2 FT 2 IN A/N:	D241	C142			
KNOCK OUT POT, KO-705, HEIGHT: 6 FT 6 IN; DIAMETER: 3 FT A/N:	D226	C142			

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
System 4: CAUSTIC SCRUBBER SERVING ASPHALT BLOWING STILLS					S15.2, S18.1
SCRUBBER, HEIGHT: 38 FT ; DIAMETER: 3 FT 6 IN A/N: 534591	C139	D118 D119 D120 C142 C281			C8.2, C8.8, K67.19
BLOWER, CENTRIFUGAL, 10HP A/N: 534591	D143				
System 5: VAPOR RECOVERY SYSTEM - RCRA FUEL & NAPHTHA TANKS					S15.2, S18.5
CARBON ADSORBER, TWO IN SERIES, EACH 150 LBS A/N:	C308			VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.5, D90.7, E128.1, E153.1, K67.10
KNOCK OUT POT, KO-300, HEIGHT: 7 FT ; DIAMETER: 3 FT 5 IN A/N:	D306				
KNOCK OUT POT, KO-301, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N:	D293				
POT, SEAL, SP-300, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N:	D307				
BLOWER, VACUUM, BL-705, 5 HP A/N:	D140	C142 C281			D90.6, K67.11
System 7: AFTERBURNER					
AFTERBURNER, NATURAL GAS, PROCESS GAS, 8.2 MMBTU/HR A/N:	C142	C139 D140 D195 D196 D197 D198 D226 D241 D284 D287 D288 D289 D324	NOX: PROCESS UNIT**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]; SO2: 500 PPMV AT 15 MINS. (5) [RULE 407, 4-2-1982]	C4.1, C8.5, D12.5, D28.1, D323.1

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
System 8: VAPOR RECOVERY SYSTEM - WASTEWATER TREATMENT					S15.2, S18.7
KNOCK OUT POT, KO-600, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N:	D205	D25 D26 D27 D28 D30 D32 D33 D86 D96 D190 D451			
KNOCK OUT POT, KO-601, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N:	D285				
KNOCK OUT POT, KO-602, HEIGHT: 5 FT 4 IN; DIAMETER: 2 FT A/N:	D194	D23			
KNOCK OUT POT, KO-603, HEIGHT: 3 FT 6 IN; DIAMETER: 3 FT 5 IN A/N:	D206				
BLOWER, VACUUM, BL-703A, 15 HP A/N:	D197	C142 C281			D90.6, K67.11
BLOWER, VACUUM, BL-703B, 15 HP A/N:	D287	C142 C281			D90.6, K67.11
System 9: VAPOR RECOVERY SYSTEM - FRONT LOADING RACKS					S13.3, S15.2, S18.8
VAPOR RETURN LINE, 6 TOTAL A/N:	C17	D315			
VAPOR RETURN LINE, 5 TOTAL A/N:	C22	D314			
KNOCK OUT POT, KO-100, HEIGHT: 3 FT 4 IN; DIAMETER: 1 FT 6 IN A/N:	D315	C17			
KNOCK OUT POT, KO-101, HEIGHT: 3 FT 4 IN; DIAMETER: 1 FT 6 IN A/N:	D314	C22			

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
KNOCK OUT POT, KO-102, HEIGHT: 6 FT 8 IN; DIAMETER: 2 FT A/N:	D207				
POT, SEAL, SP-100, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N:	D208				
BLOWER, VACUUM, BL-704, 7.5 HP A/N:	D198	C142 C281			D90.6, K67.11
System 10: VAPOR RECOVERY SYSTEM - VACUUM TRUCK WASHOUT					
ENCLOSURE, TRUCK WASHOUT STATION, WIDTH: 30 FT ; HEIGHT: 15 FT ; LENGTH: 50 FT WITH A/N: 422151	D274	C276			D12.4, E193.2, K67.7
BLOWER, BL-709, 30 HP, 3100 CU.FT./MIN	D277				
CARBON ADSORBER, TWO CANISTERS, CONNECTED IN SERIES, 1000 LBS EACH A/N: 422151	C276	D274		VOC: 20 PPMV (4) [RULE 1303(a)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D12.4, D90.4, E153.2, K67.22
System 11: VAPOR RECOVERY SYSTEM - ASPHALT FLUX LOADING RACK NO. 7					
VAPOR RETURN LINE A/N: 519869	C18	D318			
KNOCK OUT POT, KO-400, HEIGHT: 12 FT ; DIAMETER: 3 FT A/N: 519869	D318	C18			
KNOCK OUT POT, KO-401, HEIGHT: 10 FT ; DIAMETER: 3 FT A/N: 519869	D317				
POT, SEAL, SP-400, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N: 519869	D316				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
BLOWER, VACUUM, BL-707, 10 HP A/N: 519869	D288	C142 C281			D90.6, K67.11
System 12: VAPOR RECOVERY SYSTEM - SLUDGE DEWATERING					S15.2, S18.9
KNOCK OUT POT, KO-800, HEIGHT: 4 FT ; DIAMETER: 2 FT A/N:	D323	D29			
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N:	C578	D322			E17.1
KNOCK OUT POT, KO-801, HEIGHT: 13 FT ; DIAMETER: 2 FT A/N:	D322	D52 D60 D64 C578			
KNOCK OUT POT, KO-802, HEIGHT: 4 FT ; DIAMETER: 3 FT A/N:	D321				
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N:	C579	D320			E17.1
KNOCK OUT POT, KO-803, HEIGHT: 4 FT ; DIAMETER: 3 FT A/N:	D320	C579			
POT, SEAL, SP-800, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N:	D319				
BLOWER, VACUUM, BL-706, 7.5 HP A/N:	D289	C142 C281			D90.6, K67.11
BLOWER, AUXILIARY AIR, BL-708, 20 HP A/N:	D324	C142 C281			
System 13: AFTERBURNER/SCRUBBER					

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
AFTERBURNER, ZEECO, WITH URS CORP. BURNER, MODEL RMBF-9-NG, 24 MMBTU/HR (PROCESS GAS AND NAT., , GAS), 9 MMBTU/HR (NAT. GAS), WITH A HEAT RECOVERY UNIT. A/N: 527511	C281	C139 D140 D141 D195 D196 D197 D198 D284 D287 D288 D289 C301 D324 D555	NOX: LARGE SOURCE**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 50 PPMV NATURAL GAS (4) [RULE 2005, 5-6-2005]; NOX: 135 PPMV (3) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]; SO2: 500 PPMV AT 15 MINS. (5) [RULE 407, 4-2-1982]	C4.3, C8.5, D12.5, D12.7, D28.1, D28.3, D323.1, E71.2, E448.1, E448.6, H116.4, H116.5, H116.6, I298.1
SCRUBBER, PACKED BED, CAUSTIC, ENVITECH, MODEL VT7-10-2, TWO STAGE, WITH MIST ELIMINATOR, MUNTERS, T-271, AND A QUENCH TOWER, WITH A COMMON STACK WITH DEVICE C300., HEIGHT: 50 FT ; DIAMETER: 7 FT A/N: 527511	C301	C281			C8.7, C8.11, D82.1, E448.1, E448.2
Process 10: INTERNAL COMBUSTION ENGINE					
System 1: FIRE PUMP					

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 10: INTERNAL COMBUSTION ENGINE					
INTERNAL COMBUSTION ENGINE, FIRE PUMP, DIESEL FUEL, JOHN DEERE, MODEL NO. JU6H-UFAD98, TURBOCHARGED & AFTERCOOLED, 315 BHP. A/N: 494498	D298		NOX: PROCESS UNIT**	CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012, 5-6-2005]; NOX + ROG: 3 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; PM: (9) [RULE 404, 2-7-1986]; PM10: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	B61.1, C1.4, D12.8, H23.10, I298.2, K67.8
Process 11: MISCELLANEOUS					
System 1: ASPHALT BLOWING					S1.11, S13.1, S15.7
STILL, ASPHALT, HEIGHT: 50 FT ; DIAMETER: 12 FT A/N: 534590	D118	C139		PM: (9) [RULE 405, 2-7-1986]; PM: 1.2 LBS/TON CHARGED MATERIAL (8) [40CFR 60 Subpart UU, 8-5-1983]	D323.1, H116.1
DRUM, QUENCH, HEIGHT: 22 FT ; DIAMETER: 7 FT 6 IN A/N: 534590	D119	C139			D323.1
POT, QUENCH SEAL, HEIGHT: 6 FT ; DIAMETER: 6 FT A/N: 534590	D120	C139			D323.1
System 2: CONTAINER CRUSHING					

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements
 ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 11: MISCELLANEOUS					
ENCLOSURE, CAN & DRUM CRUSHING STATION, WIDTH: 17 FT ; HEIGHT: 10 FT 6 IN; LENGTH: 10 FT 8 IN WITH A/N: 512563 CRUSHER, CANS & PAILS UP TO 6 GALLON CRUSHER, DRUMS UP TO 55 GALLON	D331	D334			
BLOWER, EXHAUST, BL-XX, 0.5 HP A/N: 512563	D334	D331 C335			
CARBON ADSORBER, 150 LBS A/N: 512563	C335	D334		VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.10, E128.1, E153.3, K67.22
System 3: PORTABLE ODOR CONTROL					S42.1
BLOWER, VACUUM, 1000 CU.FT./MIN A/N: 467018	D550	C551			
CARBON ADSORBER, TWO CANISTERS, CONNECTED IN SERIES, 2000 LBS EACH A/N: 467018	C551	D550		VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.11, E128.1, E153.4, K67.21
System 4: SOIL VAPOR EXTRACTION					S15.2
VAPOR EXTRACTION WELL, UP TO 54 TOTAL A/N: 527509	D554	D556			E71.5, E193.3
KNOCK OUT POT, KO-XXX, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N: 527509	D556	D554 D555			E71.5, E193.3

- | | |
|--|--|
| <ul style="list-style-type: none"> * (1) (1A) (1B) Denotes RECLAIM emission factor (3) Denotes RECLAIM concentration limit (5) (5A) (5B) Denotes command and control emission limit (7) Denotes NSR applicability limit (9) See App B for Emission Limits | <ul style="list-style-type: none"> (2) (2A) (2B) Denotes RECLAIM emission rate (4) Denotes BACT emission limit (6) Denotes air toxic control rule limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.) (10) See section J for NESHAP/MACT requirements |
|--|--|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 11: MISCELLANEOUS					
BLOWER, VACUUM, BL-XXX, 200 CU.FT./MIN A/N: 527509	D555	C142 C281 D556			C1.12, D12.10, D90.12, D90.13, E71.5, E193.3, K67.23
PUMP, AP-XXX, KNOCK OUT POT DRAIN, AIR-POWERED A/N: 527509	D564				
Process 12: R-219 Exempt Equipment Subject to Source Specific Rules					
System 1: Miscellaneous					
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS	E261			ROG: (9) [RULE 1113, 11-8-1996; RULE 1113, 7-13-2007; RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	K67.1
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, LOW USE OR EMISSIONS	E262			VOC: (9) [RULE 1107, 11-9-2001; RULE 1107, 1-6-2006; RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	
RULE 219 EXEMPT EQUIPMENT, CLEANING EQUIPMENT, SMALL, UNHEATED, NON-CONVEYORIZED	E264			VOC: (9) [RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	H23.4
RULE 219 EXEMPT EQUIPMENT, EQUIPMENT USED FOR THE STORAGE OF UNHEATED ORGANIC MATERIALS	E328				H23.6
RULE 219 EXEMPT EQUIPMENT, EQUIPMENT USED FOR THE TRANSFER OF UNHEATED ORGANIC MATERIALS	E343				H23.14

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
DEMENNO/KERDOON**

SECTION D: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

**FACILITY PERMIT TO OPERATE
 DEMENNO/KERDOON**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D1	6	1	2
D2	6	1	2
D3	7	1	2
D5	12	2	1
D6	15	3	1
D7	14	3	1
D8	15	3	1
D9	15	3	1
D10	49	7	8
D11	15	3	1
D12	15	3	1
D13	15	3	1
D16	49	7	8
C17	56	9	9
C18	57	9	11
D19	49	7	8
D20	48	7	7
D21	49	7	7
C22	56	9	9
D23	25	5	1
D24	47	7	2
D25	24	5	1
D26	24	5	1
D27	24	5	1
D28	24	5	1
D29	23	5	1
D30	23	5	1
D31	27	5	1
D32	25	5	1
D33	25	5	1
C34	47	7	2
C35	47	7	2
D36	29	5	1
D37	29	5	1
D38	29	5	1

**FACILITY PERMIT TO OPERATE
 DEMENNO/KERDOON**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D44	27	5	1
D45	27	5	1
D46	28	5	1
D47	28	5	1
D48	28	5	1
D49	28	5	1
D51	27	5	1
D52	35	5	2
D60	35	5	2
D64	35	5	2
D65	42	6	4
D66	40	6	2
D67	40	6	2
D68	40	6	2
D69	42	6	4
D70	41	6	4
D71	36	6	1
D72	41	6	4
D73	36	6	1
D74	36	6	1
D75	44	6	5
D76	44	6	5
D77	43	6	5
D78	43	6	5
D79	41	6	2
D80	36	6	1
D81	37	6	1
D82	37	6	1
D83	37	6	1
D84	37	6	1
D85	40	6	2
D86	23	5	1
D87	40	6	2
D88	37	6	1
D89	42	6	4

**FACILITY PERMIT TO OPERATE
 DEMENNO/KERDOON**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D90	42	6	4
D91	42	6	4
D92	40	6	2
D93	41	6	2
D94	41	6	2
D95	41	6	2
D96	24	5	1
D99	46	6	7
D100	46	6	7
D101	46	6	7
D102	10	1	3
D103	43	6	5
D104	43	6	5
D105	43	6	5
D106	43	6	5
D107	44	6	6
D108	45	6	6
D109	44	6	6
D110	46	6	6
D111	45	6	6
D112	44	6	6
D113	45	6	6
D116	50	8	0
D118	60	11	1
D119	60	11	1
D120	60	11	1
D121	19	4	1
D122	19	4	1
D123	19	4	1
D124	19	4	1
D125	2	1	1
D126	2	1	1
D127	3	1	1
D128	4	1	1
D129	51	9	1

**FACILITY PERMIT TO OPERATE
 DEMENNO/KERDOON**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D130	52	9	1
D131	51	9	1
D132	1	1	1
D133	2	1	1
D134	52	9	2
D135	52	9	2
D136	53	9	2
C137	53	9	3
C138	53	9	3
C139	55	9	4
D140	55	9	5
D141	54	9	3
C142	55	9	7
D143	55	9	4
D173	10	1	3
D176	10	1	3
D178	3	1	1
D179	9	1	3
D180	9	1	3
D181	9	1	3
D182	9	1	3
D183	9	1	3
D184	9	1	3
D185	8	1	3
D186	8	1	3
D188	8	1	3
D190	25	5	1
D191	51	8	0
D193	52	9	1
D194	56	9	8
D195	52	9	1
D196	53	9	2
D197	56	9	8
D198	57	9	9
D200	28	5	1

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D201	29	5	1
D205	56	9	8
D206	56	9	8
D207	57	9	9
D208	57	9	9
D209	40	6	2
D210	39	6	1
D211	39	6	1
D212	39	6	1
D213	39	6	1
D214	39	6	1
D215	39	6	1
D216	38	6	1
D217	38	6	1
D218	38	6	1
D219	38	6	1
D220	38	6	1
D221	38	6	1
D222	38	6	1
D223	37	6	1
D224	37	6	1
D225	37	6	1
D226	54	9	3
D227	48	7	5
D228	48	7	5
D229	48	7	4
D230	48	7	4
D231	46	7	1
D232	47	7	1
D233	49	7	9
D234	49	7	9
D235	49	7	9
D236	5	1	2
D237	2	1	1
D238	6	1	2

**FACILITY PERMIT TO OPERATE
 DEMENNO/KERDOON**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D239	7	1	2
D240	6	1	2
D241	54	9	3
D242	47	7	2
D243	47	7	2
D247	2	1	1
D248	53	9	3
D249	54	9	3
D250	53	9	3
D251	54	9	3
D252	54	9	3
D253	54	9	3
D254	54	9	3
D255	4	1	1
D256	4	1	1
D257	4	1	1
D258	4	1	1
D259	4	1	1
D260	4	1	1
E261	62	12	1
E262	62	12	1
D263	2	1	1
E264	62	12	1
D265	2	1	1
D266	3	1	1
D267	3	1	1
D270	11	1	4
D272	12	1	4
D274	57	9	10
C276	57	9	10
D277	57	9	10
C281	59	9	13
D282	54	9	3
D283	52	9	2
D284	53	9	2

**FACILITY PERMIT TO OPERATE
 DEMENNO/KERDOON**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D285	56	9	8
D286	52	9	2
D287	56	9	8
D288	58	9	11
D289	58	9	12
D290	54	9	3
D291	53	9	2
D292	53	9	2
D293	55	9	5
D294	53	9	3
D295	53	9	3
D298	60	10	1
D299	8	1	3
C301	59	9	13
C303	52	9	2
C304	52	9	2
D305	3	1	1
D306	55	9	5
D307	55	9	5
C308	55	9	5
D309	44	6	6
D310	48	7	4
C311	51	9	1
C312	51	9	1
C313	52	9	2
D314	56	9	9
D315	56	9	9
D316	57	9	11
D317	57	9	11
D318	57	9	11
D319	58	9	12
D320	58	9	12
D321	58	9	12
D322	58	9	12
D323	58	9	12

**FACILITY PERMIT TO OPERATE
 DEMENNO/KERDOON**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D324	58	9	12
D325	54	9	3
D326	1	1	1
D327	12	2	1
E328	62	12	1
D329	36	5	3
C330	36	5	3
D331	61	11	2
D334	61	11	2
C335	61	11	2
D336	47	7	3
D337	47	7	3
D338	48	7	6
D339	48	7	6
D340	45	6	6
D341	45	6	6
D342	45	6	6
E343	62	12	1
D344	13	2	1
D345	13	2	1
D346	13	2	1
D347	13	2	1
D348	13	2	1
D349	13	2	1
D350	13	2	1
D351	3	1	1
D352	49	7	9
D353	6	1	2
D354	5	1	2
D355	5	1	2
D356	5	1	2
D357	6	1	2
D358	6	1	2
D359	6	1	2
D360	7	1	2

**FACILITY PERMIT TO OPERATE
 DEMENNO/KERDOON**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D361	7	1	2
D362	7	1	2
D363	5	1	2
D364	5	1	2
D365	8	1	3
D366	8	1	3
D367	9	1	3
D368	9	1	3
D369	10	1	3
D370	10	1	3
D371	10	1	3
D372	10	1	3
D373	10	1	3
D374	13	3	1
D375	14	3	1
D376	14	3	1
D377	14	3	1
D378	14	3	1
D379	15	3	1
D380	15	3	1
D381	15	3	1
D382	16	3	1
D383	16	4	1
D384	16	4	1
D385	16	4	1
D386	16	4	1
D387	17	4	1
D388	17	4	1
D389	17	4	1
D390	17	4	1
D391	17	4	1
D392	17	4	1
D393	17	4	1
D394	18	4	1
D395	18	4	1

**FACILITY PERMIT TO OPERATE
 DEMENNO/KERDOON
 SECTION D: DEVICE ID INDEX**

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D396	18	4	1
D397	18	4	1
D398	18	4	1
D399	18	4	1
D400	19	4	1
D401	19	4	1
D402	19	4	1
D403	20	4	1
D404	19	4	1
D405	19	4	1
D406	20	4	1
D407	20	4	1
D408	20	4	1
D409	20	4	1
D410	20	4	1
D411	20	4	1
D412	20	4	1
D413	20	4	1
D414	21	4	1
D415	21	4	1
D416	21	4	1
D417	21	4	1
D418	35	5	2
D420	21	4	1
D421	17	4	1
D422	14	3	1
D423	4	1	1
D424	8	1	3
D425	10	1	3
D426	1	1	1
D427	1	1	1
D428	1	1	1
D429	1	1	1
D430	1	1	1
D431	1	1	1

**FACILITY PERMIT TO OPERATE
 DEMENNO/KERDOON**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D432	23	5	1
D433	23	5	1
D434	23	5	1
D435	22	5	1
D436	22	5	1
D437	22	5	1
D438	22	5	1
D439	22	5	1
D440	22	5	1
D441	22	5	1
D442	22	5	1
D443	23	5	1
D444	23	5	1
D446	24	5	1
D447	24	5	1
D448	24	5	1
D449	24	5	1
D450	25	5	1
D451	25	5	1
D452	25	5	1
D453	25	5	1
D454	25	5	1
D455	26	5	1
D456	26	5	1
D457	26	5	1
D458	27	5	1
D459	27	5	1
D460	27	5	1
D461	27	5	1
D462	28	5	1
D463	28	5	1
D464	28	5	1
D465	28	5	1
D466	29	5	1
D467	29	5	1

**FACILITY PERMIT TO OPERATE
 DEMENNO/KERDOON**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D468	29	5	1
B469	30	5	1
D470	30	5	1
D471	30	5	1
D472	30	5	1
D473	30	5	1
D474	30	5	1
D475	30	5	1
D476	30	5	1
D477	30	5	1
D478	30	5	1
D479	30	5	1
D480	31	5	1
D481	31	5	1
D482	31	5	1
D483	31	5	1
D484	31	5	1
D485	31	5	1
D486	31	5	1
D487	31	5	1
D488	31	5	1
D489	31	5	1
D490	31	5	1
D491	33	5	1
D492	33	5	1
D493	33	5	1
D494	30	5	1
B495	33	5	1
D496	35	5	2
D497	33	5	1
D498	33	5	1
D499	33	5	1
D500	33	5	1
D501	33	5	1
D502	33	5	1

**FACILITY PERMIT TO OPERATE
 DEMENNO/KERDOON**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D503	33	5	1
D504	33	5	1
D505	33	5	1
D506	33	5	1
D507	48	7	6
D508	5	1	1
D509	5	1	1
D510	7	1	2
D511	29	5	1
D512	21	4	1
D513	21	4	1
D514	21	4	1
D515	21	4	1
D516	22	4	1
D517	22	4	1
B518	31	5	1
B519	33	5	1
D520	7	1	2
D521	9	1	3
D522	27	5	1
D523	33	5	1
D524	35	5	2
D525	3	1	1
D526	34	5	1
D527	34	5	1
D528	34	5	1
D529	46	6	6
D530	46	6	6
D531	14	3	1
D532	34	5	1
D533	34	5	1
D534	34	5	1
D535	33	5	1
D536	33	5	1
D537	33	5	1

**FACILITY PERMIT TO OPERATE
 DEMENNO/KERDOON
 SECTION D: DEVICE ID INDEX**

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D538	33	5	1
D539	34	5	1
D540	34	5	1
D541	33	5	1
D542	33	5	1
D543	33	5	1
D544	34	5	1
D545	21	4	1
D546	42	6	4
D547	42	6	4
D548	42	6	4
B549	34	5	1
D550	61	11	3
C551	61	11	3
D552	49	7	10
D553	49	7	10
D554	61	11	4
D555	62	11	4
D556	61	11	4
D562	50	7	11
D563	50	7	11
D564	62	11	4
C578	58	9	12
C579	58	9	12

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F2.1 The operator shall limit emissions from this facility as follows:

CONTAMINANT	EMISSIONS LIMIT
VOC	Less than 2550 LBS IN ANY ONE MONTH

The facility afterburners stacks and facility fugitive components shall comply with the above Volatile Organic Compounds (VOC) emission limit.

To ensure compliance with the monthly Volatile Organic Compounds (VOC) emission limit of this condition, the operator shall comply with the following recordkeeping requirements:

- (1) Within 14 calendar days after the end of each month, the operator shall total and record VOC emissions for the month from afterburners and fugitive components.
- (2) The operator shall retain the VOC emissions records for at least 5 years.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

F2.2 The operator shall limit emissions from this facility as follows:

CONTAMINANT	EMISSIONS LIMIT
SOX	Less than 4 TONS IN ANY ONE YEAR

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The facility afterburners systems shall comply with the above Sulfur Oxides (SOX) emission limit.

To ensure compliance with the Sulfur Oxides (SOX) emission limit of this condition, the operator shall comply with the following monitoring and recordkeeping requirements:

1. Monitor SOX concentrations at the exhaust stack of the afterburner C281/scrubber C301 or the afterburner C142/scrubber C300 using AQMD certified Continuous Emissions Monitoring System (CEMS), OR
2. If afterburner C281/scrubber C301 is out of operation and scrubber C300 is under construction, monitor the sulfur content of the vapor recovery stream and calculate the SOX emissions from the afterburner C142 on a daily basis.
3. Within 14 calendar days after the end of each month, the operator shall total and record SOX emissions for the month and for the calendar year from the two afterburners C281 and C142.
4. The operator shall retain sulfur content and the SOX emissions records for at least 5 years.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

- F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
- (a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or
 - (b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

F14.1 The operator shall not use liquid fuel containing sulfur compounds in excess of 500 ppm by weight.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

F14.2 The operator shall not purchase any diesel fuel , for stationary source application as defined in Rule 431.2, containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

F16.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Records of the monthly (and quarterly where applicable) inspection, and subsequent repair and reinspection, of VOC fugitive components subject to District Rule 1173

[RULE 1173, 2-6-2009]

F48.2 The operator shall not operate at this facility any combustion devices burning gaseous fuels (except natural gas) unless total sulfur compounds emissions from the facility are less than 5 pounds per day (calculated as H₂S).

This condition shall no longer apply once this facility has demonstrated to the satisfaction of the District that the operation of all combustion devices at this facility will comply with all applicable requirements of Rule 431.1.

[RULE 431.1, 6-12-1998]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

F48.3 The operator shall not operate at this facility any device used to produce gasoline, kerosene, distillate fuel oils, residual fuel oils, lubricants, or other products through distillation of petroleum or through redistillation, cracking or reforming of unfinished petroleum derivatives.

For the purpose of this condition, petroleum shall be defined as the crude oil removed from the earth and the oils derived from tar sands, shale, and coal.

The operator shall submit to the Executive Officer, as a part of an annual compliance certification, a statement that certifies compliance with this condition.

[RULE 204, 10-8-1993]

F48.4 The operator shall not operate at this facility any device used to treat, store, or dispose of benzene-containing hazardous waste from any chemical manufacturing plant, coke by-product recovery plant, or petroleum refinery.

The operator shall submit to the Executive Officer, as a part of an annual compliance certification, a statement that certifies compliance with this condition.

A copy of each manifest, or the manifest data stored in a manifest database, for benzene-containing hazardous waste received at this facility shall be kept and maintained for at least five years, and shall be made available to the Executive Officer or his authorized representative upon request

[RULE 204, 10-8-1993]

F52.1 This facility is subject to the applicable requirements of the following rules or regulation(s):

40 CFR 60 Subpart A

40 CFR 61 Subpart A

40 CFR 63 Subpart A

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[40CFR 60 Subpart A, 4-4-2014; 40CFR 61 Subpart A, 2-27-2014; 40CFR 63 Subpart A, 3-27-2014]

SYSTEM CONDITIONS

S1.1 The operator shall limit the loading rate to no more than 6,132,000 gallon(s) in any one calendar month.

This limit shall be based on the total combined throughput of Asphalt Flux Loading Rack No. 4 (Process 7, System 7) and Asphalt Flux Loading Rack No. 7 (Process 7, System 8).

The operator shall monitor the throughput of materials loaded, in gallons, by using certified truck scale records to determine the pounds of material loaded, and a measurement of the specific gravity or API gravity of the material loaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 7 , 8]

S1.2 The operator shall limit the material processed to no more than 4,320,000 gallon(s) in any one calendar month.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, material processed shall be defined as the total amount of sludge or any other hydrocarbon containing material processed in this system before dewatering.

To comply with this condition, the operator shall install and maintain a non-resettable totalizing flow meter to accurately indicate the total volume of volume of sludge processed in this system before dewatering.

The operator shall determine and record the volume of sludge processed once every calendar month.

The operator shall calibrate the flow meter per the manufacturer's specifications.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 5, System 2]

S1.3 The operator shall limit the unloading rate to no more than 1,520,833 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials unloaded, in gallons, by using certified truck scale records to determine the pounds of material unloaded, and a measurement of the specific gravity or API gravity of the material unloaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 3]

S1.4 The operator shall limit the unloading rate to no more than 6,387,500 gallon(s) in any one calendar month.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall monitor the throughput of materials unloaded, in gallons, by using certified truck scale records to determine the pounds of material unloaded, and a measurement of the specific gravity or API gravity of the material unloaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 1]

- S1.5 The operator shall limit the unloading rate to no more than 3,832,500 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials unloaded, in gallons, by using certified truck scale records to determine the pounds of material unloaded, and a measurement of the specific gravity or API gravity of the material unloaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 2]

- S1.6 The operator shall limit the loading rate to no more than 243,334 gallon(s) in any one calendar month.

For the purpose of this condition, the loading rate shall be defined as the loading rate of Naphtha.

The operator shall monitor the throughput of materials loaded, in gallons, by using certified truck scale records to determine the pounds of material loaded, and a measurement of the specific gravity or API gravity of the material loaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 7, System 5]

- S1.7 The operator shall limit the loading rate to no more than 3,193,750 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials loaded, in gallons, by using certified truck scale records to determine the pounds of material loaded, and a measurement of the specific gravity or API gravity of the material loaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 4]

- S1.8 The operator shall limit the loading rate to no more than 6,083,333 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials loaded, in gallons, by using certified truck scale records to determine the pounds of material loaded, and a measurement of the specific gravity or API gravity of the material loaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 6]

- S1.9 The operator shall limit the loading rate to no more than 100,000 gallon(s) in any one calendar month.

For the purpose of this condition, the loading rate shall be defined as the loading rate of RCRA Fuel.

The operator shall monitor the throughput of materials loaded, in gallons, by using certified truck scale records to determine the pounds of material loaded, and a measurement of the specific gravity or API gravity of the material loaded.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 9]

- S1.10 The operator shall limit the unloading rate to no more than 100,000 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials unloaded, in gallons, by using certified truck scale records to determine the pounds of material unloaded, and a measurement of the specific gravity or API gravity of the material unloaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 9]

- S1.11 The operator shall limit the material processed to no more than 9,060 ton(s) in any one calendar month.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 11, System 1]

- S1.12 The operator shall limit the throughput to no more than 8,500,000 gallon(s) in any one calendar month.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, throughput shall be defined as the volume of wastewater, in gallons, discharged to the LACSD sewer connection (D468).

To comply with this condition, the operator shall install and maintain a non-resettable totalizing flow meter to accurately indicate the total volume of wastewater discharged to the LACSD sewer connection (D468).

The operator shall determine and record the volume of wastewater discharged to the LACSD sewer connection once every calendar month.

The operator shall calibrate the flow meter per the manufacturer's specifications.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 5, System 1]

- S1.13 The operator shall limit the loading rate to no more than 25,000 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials loaded, in gallons, by using certified truck scale records to determine the pounds of material loaded, and a measurement of the specific gravity or API gravity of the material loaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 10]

- S1.14 The operator shall limit the unloading rate to no more than 100,000 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials unloaded, in gallons, by using certified truck scale records to determine the pounds of material unloaded, and a measurement of the specific gravity or API gravity of the material unloaded.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 11]

S13.1 All devices under this system are subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
PM	40CFR60, SUBPART	UU
PM	40CFR63, SUBPART	AAAAAAA

[40CFR 60 Subpart UU, 8-5-1983; 40CFR 63 Subpart AAAAAAA, 12-2-2009]

[Systems subject to this condition : Process 11, System 1]

S13.3 All devices under this system are subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	462

[RULE 462, 5-14-1999]

[Systems subject to this condition : Process 7, System 5 , 9; Process 9, System 9]

S15.1 The vent gases from all affected devices of this process/system shall be vented as follows:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

All vent gases from any process vent of this system shall be vented to the Vapor Recovery System - Process Waste Gas (Process 9, System 3).

This process/system shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 1, System 1, 2, 3; Process 2, System 1; Process 3, System 1; Process 4, System 1]

S15.2 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases from this system shall be vented to the Afterburners (Process 9, Systems 7 & 13).

This process/system shall not be operated unless at least one of the afterburners is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 1, 2, 3, 4, 5, 8, 9, 11, 12; Process 11, System 4]

S15.3 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be vented to the Vapor Recovery System - North Tank Farms (Process 9, System 1).

This process/system shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 6, System 5 , 6 , 7]

S15.4 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be vented to the Vapor Recovery System - South Tank Farms (Process 9, System 2).

This process/system shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 6, System 1 , 2]

S15.5 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be vented to the Vapor Recovery System - RCRA Fuel & Naphtha Tanks (Process 9, System 5).

This process/system shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 6, System 4]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

S15.6 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be vented to the Vapor Recovery System - Wastewater Treatment (Process 9, System 8).

This process/system shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 5, System 1]

S15.7 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be vented to the Caustic Scrubber Serving Asphalt Blowing Stills (Process 9, System 4).

This process/system shall not be operated unless the above caustic scrubber is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 11, System 1]

S15.8 The vent gases from all affected devices of this process/system shall be vented as follows:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

All vent gases under normal operating conditions shall be vented to the Vapor Recovery System - Asphalt Flux Loading Rack No. 7 (Process 9, System 11).

This process/system shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 7, System 8 , 10]

S15.9 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be vented to the Vapor Recovery System - Front Loading Racks (Process 9, System 9).

This process/system shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 7, System 4 , 5 , 6 , 7 , 9]

S18.1 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Asphalt Blowing (Process: 11, System: 1)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 9, System 4]

S18.2 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Used Oil Dehydration (Process: 1, System: 1)

Vacuum Distillation Unit No. 1 (Process: 1, System: 2)

Vacuum Distillation Unit No. 2 (Process: 1, System: 3)

PRM Stripper (Process: 2, System: 1)

Naphtha Splitter Unit (Process: 3, System: 1)

Ethylene Glycol Distillation (Process: 4, System: 1)

Waste Water Treatment (Process: 5, System: 1)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 3]

S18.3 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Asphalt Flux Loading - Rack No. 7 (Process: 7, System: 8)

Used Glycol Loading (Process: 7, System: 10)

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 11]

S18.4 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Fixed Roof Storage Tanks : Southwest Tank Farm (Process: 6, System: 1)

Fixed Roof Storage Tanks - Wastewater Tanks (Process: 6, System: 2)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 2]

S18.5 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Fixed Roof Storage Tanks : RCRA Fuel & Naphtha Tanks (Process: 6, System: 4)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 5]

S18.6 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Fixed Roof Storage Tanks : Product Tanks (Process: 6, System: 5)

Fixed Roof Storage Tanks : A-Series Tanks (Process: 6, System: 6)

Fixed Roof Storage Tanks : N-Series Tanks (Process: 6, System: 7)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 1]

S18.7 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Wastewater Treatment (Process: 5, System: 1)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 8]

S18.8 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Fuel Oil Cutter Loading (Process: 7, System: 4)

Naphtha Loading (Process: 7, System: 5)

Marine Diesel Oil Loading (Process: 7, System: 6)

Asphalt Flux Loading - Rack No. 4 (Process: 7, System: 7)

RCRA Fuel Loading and Unloading (Process: 7, System: 9)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 9]

S18.9 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Sludge Dewatering (Process: 5, System: 2)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 12]

S42.1 The operator shall not use this system for Rule 1149 compliance:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	1149

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1149, 5-2-2008]

[Systems subject to this condition : Process 11, System 3]

DEVICE CONDITIONS

B. Material/Fuel Type Limits

B22.3 The operator shall only use this equipment with materials having a(n) true vapor pressure of 0.05 psia or less under actual operating conditions.

The operator shall sample the asphalt flux, from any of the devices subject to this condition, at least once each calendar year, and test each sample for true vapor pressure (TVP) using SCAQMD-approved methods.

The operator shall maintain on file a copy of the Material Safety Data Sheet (MSDS) for the asphalt flux.

For compliance with this condition, the average of the TVP measurements for each calendar year shall be not greater than 0.05 psia.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D16, D20, D99, D100, D101, D104, D105, D309]

B22.5 The operator shall only use this equipment with materials having a(n) Reid vapor pressure of 1.00 psia or less under actual operating conditions.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall sample the used glycol, from any of the devices subject to this condition, at least twice each calendar month, and test each sample for Reid vapor pressure (RVP) using SCAQMD-approved methods.

For compliance with this condition, the average of the RVP measurements for each calendar month shall be not greater than 1.00 psia.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D107, D108, D109, D110, D111, D112, D113, D336, D552]

- B22.6 The operator shall only use this equipment with materials having a(n) Reid vapor pressure of 1.00 psia or less under actual operating conditions.

The operator shall sample the used oil, from any of the devices subject to this condition, at least twice each calendar month, and test each sample for Reid vapor pressure (RVP) using SCAQMD-approved methods.

For compliance with this condition, the average of the RVP measurements for each calendar month shall be not greater than 1.00 psia.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D67, D71, D73, D74, D80, D81, D82, D83, D84, D85, D87, D88, D94, D95, D210, D211, D212, D213, D214, D215, D216, D217, D218, D219, D231]

- B22.7 The operator shall only use this equipment with materials having a(n) Reid vapor pressure of 1.00 psia or less under actual operating conditions.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall sample the wastewater, from any of the devices subject to this condition, at least twice each calendar month, and test each sample for Reid vapor pressure (RVP) using SCAQMD-approved methods.

For compliance with this condition, the average of the RVP measurements for each calendar month shall be not greater than 1.00 psia.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D66, D67, D68, D79, D85, D87, D92, D93, D94, D95, D209, D210, D211, D212, D213, D214, D215, D216, D217, D218, D219, D242]

- B22.8 The operator shall only use this equipment with materials having a(n) Reid vapor pressure of 6.00 psia or less under actual operating conditions.

The operator shall sample the naphtha, from any of the devices subject to this condition, at least twice each calendar month, and test each sample for Reid vapor pressure (RVP) using SCAQMD-approved methods.

For compliance with this condition, the average of the RVP measurements for each calendar month shall be not greater than 6.00 psia.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D65, D70, D72, D89, D90, D227]

- B22.9 The operator shall only use this equipment with materials having a(n) Reid vapor pressure of 1.00 psia or less under actual operating conditions.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall sample the fuel oil cutter, from any of the devices subject to this condition, at least twice each calendar month, and test each sample for Reid vapor pressure (RVP) using SCAQMD-approved methods.

For compliance with this condition, the average of the RVP measurements for each calendar month shall be not greater than 1.00 psia.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D229]

B22.10 The operator shall only use this equipment with materials having a(n) Reid vapor pressure of 1.20 psia or less under actual operating conditions.

The operator shall sample the marine diesel oil, from any of the devices subject to this condition, at least twice each calendar month, and test each sample for Reid vapor pressure (RVP) using SCAQMD-approved methods.

For compliance with this condition, the average of the RVP measurements for each calendar month shall be not greater than 1.20 psia.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D75, D76, D77, D78, D103, D106, D220, D221, D222, D223, D224, D225, D338, D562]

B22.11 The operator shall only use this equipment with materials having a(n) Reid vapor pressure of 6.00 psia or less under actual operating conditions.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall sample the RCRA fuel, from any of the devices subject to this condition, at least twice each calendar month, and test each sample for Reid vapor pressure (RVP) using SCAQMD-approved methods.

For compliance with this condition, the average of the RVP measurements for each calendar month shall be not greater than 6.00 psia.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D69, D91, D233, D235]

B61.1 The operator shall only use diesel fuel containing the following specified compounds:

Compound	ppm by weight
Sulfur less than or equal to	15

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1470, 6-1-2007]

[Devices subject to this condition : D298]

C. Throughput or Operating Parameter Limits

C1.1 The operator shall limit the throughput to no more than 6,387,500 gallon(s) in any one calendar month.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

This limit shall be based on the total combined throughput of used oil for equipment D71 (Tank 1001), D73 (Tank 1002), D74 (Tank 1003), D80 (Tank 1004), D81 (Tank 1005), D82 (Tank 1006), D83 (Tank 1007), D84 (Tank 1008), D67 (Tank 1009), D85 (Tank 1107), D87 (Tank 1109), D94 (Tank 9001), D95 (Tank 9002), D219 (Tank 526), D218 (Tank 527), D217 (Tank 528), D216 (Tank 529), D215 (Tank 530), D214 (Tank 531), D213 (Tank 532), D212 (Tank 533), D211 (Tank 534), and D210 (Tank 535).

For compliance with this condition, the operator shall monitor the throughput of materials unloaded at the Used Oil Unloading (Process 7, System 1).

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D67, D71, D73, D74, D80, D81, D82, D83, D84, D85, D87, D94, D95, D210, D211, D212, D213, D214, D215, D216, D217, D218, D219]

- C1.2 The operator shall limit the throughput to no more than 6,083,333 gallon(s) in any one calendar month.

This limit shall be based on the total combined throughput of marine diesel oil for equipment D75 (Tank 1105), D76 (Tank 1106), D77 (Tank 506), D78 (Tank 507), D103 (Tank 1104), D106 (Tank 1103), D220 (Tank 525), D221 (Tank 524), D222 (Tank 523), D223 (Tank 522), D224 (Tank 521) and D225 (Tank 520)..

For compliance with this condition, the operator shall monitor the throughput of materials loaded at the Marine Diesel Loading (Process 7, System 6).

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D75, D76, D77, D78, D103, D106, D220, D221, D222, D223, D224, D225]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- C1.3 The operator shall limit the throughput to no more than 3,832,500 gallon(s) in any one calendar month.

This limit shall be based on the total combined throughput of wastewater for equipment D66 (Tank 2002), D67 (Tank 1009), D68 (Tank 2001), D79 (Tank 55001), D85 (Tank 1107), D87 (Tank 1109), D92 (Tank 181), D93 (Tank 8001), D94 (Tank 9001), D95 (Tank 9002), D209 (Tank 151), D210 (Tank (535), D211 (Tank 534), D212 (Tank 533), D213 (Tank 532), D214 (Tank 531), D215 (Tank 530), D216 (Tank 529), D217 (Tank 528), D218 (Tank 527) and D219 (Tank 526)..

For compliance with this condition, the operator shall monitor the throughput of the materials unloaded at the Wastewater Unloading (Process 7, System 2)..

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D66, D67, D68, D79, D85, D87, D92, D93, D94, D95, D209, D210, D211, D212, D213, D214, D215, D216, D217, D218, D219]

- C1.4 The operator shall limit the operating time to no more than 200 hour(s) in any one year.

Operations for maintenance and testing as defined in Rule 1470 shall not exceed 50 hours in any one calendar year.

Operations for maintenance and testing as defined in Rule 1470 shall not exceed 4.2 hours in any one calendar month..

The total annual operating time includes all operations including maintenance and testing operations.

**[RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996; RULE 1470, 6-1-2007;
RULE 2012, 5-6-2005]**

[Devices subject to this condition : D298]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- C1.5 The operator shall limit the throughput to no more than 6,132,000 gallon(s) in any one calendar month.

This limit shall be based on the total combined throughput of asphalt flux for equipment D99 (Tank N3), D100 (Tank N4), D101 (Tank 1110), and D309 (Tank A1)..

For compliance with this condition, the operator shall monitor the throughput of materials loaded at the Asphalt Flux Loading Rack No. 4 (Process 7, System 7) and Asphalt Flux Loading Rack No. 7 (Process 7, System 8)..

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D99, D100, D101, D309]

- C1.6 The operator shall limit the throughput to no more than 166,667 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as the total weight of materials transferred to the silo.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D329]

- C1.7 The operator shall limit the throughput to no more than 6,132,000 gallon(s) in any one calendar month.

This limit shall be based on the total combined throughput of asphalt flux for equipment D104 (Tank 1101), and D105 (Tank 1102)..

For compliance with this condition, the operator shall monitor the throughput of materials loaded at the Asphalt Flux Loading Rack No. 4 (Process 7, System 7) and Asphalt Flux Loading Rack No. 7 (Process 7, System 8)..

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]**]

[Devices subject to this condition : D104, D105]

- C1.8 The operator shall limit the throughput to no more than 6,387,500 gallon(s) in any one calendar month.

For compliance with this condition, the operator shall monitor the throughput of materials unloaded at the Used Oil Unloading (Process 7, System 1).

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]**]

[Devices subject to this condition : D88]

- C1.9 The operator shall limit the throughput to no more than 100,000 gallon(s) in any one calendar month.

This limit shall be based on the total combined throughput of RCRA Fuel for equipment D69 (Tank 515), and D91 (Tank 516).

For compliance with this condition, the operator shall monitor the throughput of materials unloaded at the RCRA Fuel Loading & Unloading (Process 7, System 9).

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]**]

[Devices subject to this condition : D69, D91]

- C1.10 The operator shall limit the throughput to no more than 243,334 gallon(s) in any one calendar month.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

This limit shall be based on the total combined throughput of naphtha for equipment D65 (Tank 504), D70 (Tank 502), D72 (Tank 501), D89 (Tank 503) and D90 (Tank 505)..

For compliance with this condition, the operator shall monitor the throughput of materials loaded at the Naphtha Loading (Process 7, System 5)..

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D65, D70, D72, D89, D90]

- C1.11 The operator shall limit the throughput to no more than 1,520,833 gallon(s) in any one calendar month.

For compliance with this condition, the operator shall monitor the throughput of materials unloaded at the Used Glycol Unloading (Process 7, System 3).

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D107, D108, D109, D110, D111, D112, D113]

- C1.12 The operator shall limit the throughput to no more than 200 cubic feet per minute.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D555]

- C4.1 The operator shall limit the residence time to no less than 0.5 seconds.

[**RULE 1303(a)(1)-BACT, 5-10-1996**; RULE 1303(a)(1)-BACT, 12-6-2002]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C142]

C4.3 The operator shall limit the residence time to no less than 1.0 seconds.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C281]

C6.1 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 450 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature reading device to accurately indicate the temperature of the stored material.

The operator shall determine and record the parameter being monitored once every 7 days.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D99, D100, D101, D309]

C6.2 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 500 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature reading device to accurately indicate the temperature of the stored material.

The operator shall determine and record the parameter being monitored once every 7 days.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D104, D105]

C6.3 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 160 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature reading device to accurately indicate the temperature of the stored material.

The operator shall determine and record the parameter being monitored once every 7 days.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D107]

C6.4 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 200 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature reading device to accurately indicate the temperature of the stored material.

The operator shall determine and record the parameter being monitored once every 7 days.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D110, D113]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- C8.1 The operator shall use this equipment in such a manner that the pH being monitored, as indicated below, is not less than 10 of the pH scale.

The operator shall monitor and record the pH of the scrubbing solution at least twice per day..

The operator shall calibrate the instrument used to measure the pH per the manufacturer's specifications.

[RULE 204, 10-8-1993; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C137, C138]

- C8.2 The operator shall use this equipment in such a manner that the pH being monitored, as indicated below, is not less than 11.5 of the pH scale.

The operator shall monitor and record the pH of the scrubbing solution at least twice per day.

The operator shall calibrate the instrument used to measure the pH per the manufacturer's specifications.

[RULE 204, 10-8-1993; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C139]

- C8.5 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, is not less than 1400 Deg F.

The temperature limit is the average over 15 minutes.

To comply with this condition, the operator shall install and maintain a(n) temperature reading device to accurately indicate the temperature in the combustion chamber and at least 1second downstream of the burner.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C142, C281]

C8.7 The operator shall use this equipment in such a manner that the flow rate being monitored, as indicated below, is not less than 200 gpm.

The flow rate limit is the average over 15 minutes.

To comply with this condition, the operator shall install and maintain a(n) flow meter to accurately indicate the flow rate of the recirculating caustic solution for each stage.

The flow rate measured shall be the scrubber re-circulation flow rate.

The operator shall also install and maintain a device to continuously record the parameter being measured.

The continuous monitoring system shall include visual and audio alarms.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 407, 4-2-1982; RULE 431.1, 6-12-1998]

[Devices subject to this condition : C301]

C8.8 The operator shall use this equipment in such a manner that the flow rate being monitored, as indicated below, is not less than 40 gpm.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

To comply with this condition, the operator shall install and maintain a(n) flow meter to accurately indicate the flow rate of the recirculating caustic solution.

The flow rate measured shall be the scrubber re-circulation flow rate.

The operator shall monitor and record the re-circulation flow rate of the caustic solution at least twice per day.

The operator shall calibrate the flow meter per the manufacturer's specifications.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C137, C138, C139]

C8.11 The operator shall use this equipment in such a manner that the pH being monitored, as indicated below, is not less than 6 of the pH scale.

To comply with this condition, the operator shall install and maintain a(n) pH meter to accurately indicate the pH of the scrubbing solution for each stage.

The operator shall also install and maintain a device to continuously record the parameter being measured.

The continuous monitoring system shall include visual and audio alarms.

The operator shall calibrate the instrument used to measure the pH per the manufacturer's specifications.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

The pH limit is the average over 15 minutes.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 204, 10-8-1993; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C301]

D. Monitoring/Testing Requirements

D12.1 The operator shall install and maintain a(n) non-resettable totalizing fuel meter to accurately indicate the fuel usage of the heater(s).

[RULE 2012, 5-6-2005]

[Devices subject to this condition : D270, D272]

D12.3 The operator shall install and maintain a(n) continuous monitoring system to accurately indicate the open or closed position of the FGR and cold combustion air flow control valves.

Tables or graphs shall be prepared which correlate the valve positions with FGR and cold combustion air flow rates.

These tables or graphs shall be maintained by the operator and shall be made available to District personnel upon request.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D270, D272]

D12.4 The operator shall install and maintain a(n) flow meter to accurately indicate the flow rate at the inlet of the carbon adsorber.

The operator shall verify operation of the blower BL709 (D277) prior to the start of any truck washout/unloading activity.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D274, C276]

- D12.5 The operator shall install and maintain a(n) flow meter to accurately indicate the flow rate being supplied to the combustion chamber.

The operator shall also install and maintain a device to continuously record the parameter being measured.

For the purpose of this condition, the flow rate of natural gas supplied to the combustion chamber shall be indicated and recorded

[RULE 2012, 5-6-2005]

[Devices subject to this condition : C142, C281]

- D12.7 The operator shall install and maintain a(n) stack flow monitor to accurately indicate the flow rate from the afterburner stack to provide continuous and cumulative actual flow volume.

When valid exhaust flow rate of an afterburner is not obtained from the stack flow monitor, substituted data for the exhaust flow rate for the afterburner shall be determined by using procedures in the certification letter for the continuous exhaust flow monitor and the missing data procedures applicable to flow as set forth in Rule 2012 Appendix A, Chapter 3, Section K(2).

[RULE 2012, 5-6-2005]

[Devices subject to this condition : C281]

- D12.8 The operator shall install and maintain a(n) non-resettable elapsed time meter to accurately indicate the elapsed operating time of the engine.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

**[RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996; RULE 1470, 6-1-2007;
RULE 2012, 5-6-2005; 40CFR 60 Subpart III, 7-11-2006]**

[Devices subject to this condition : D298]

D12.9 The operator shall install and maintain a(n) non-resettable totalizing fuel meter to accurately indicate the fuel usage of the boiler.

[RULE 2012, 5-6-2005; 40CFR 60 Subpart Dc, 2-27-2006]

[Devices subject to this condition : D116, D191]

D12.10 The operator shall install and maintain a(n) flow meter to accurately indicate the flow rate at the outlet of the blower.

The operator shall measure the flow rate in standard cubic feet per minute (SCFM).

If a pressure sensing device is used instead of the flow meter, a conversion chart shall be made available to indicate the flow rate (in SCFM) corresponding to the pressure reading.

The operator shall calibrate the flow meter per the manufacturer's specifications.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D555]

D28.1 The operator shall conduct source test(s) in accordance with the following specifications:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The test shall be conducted at least once every three years. For the purposes of determining intervals indicated, the cumulative days between testing during which afterburner C142, afterburner C281 or their associated scrubbers are under repair, maintenance, or construction shall not be counted. The operator shall keep sufficient operating records to demonstrate compliance with the testing intervals and dates counted/not counted..

The test shall be conducted to determine the control efficiency of this equipment for destruction of VOCs.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C142, C281]

D28.3 The operator shall conduct source test(s) in accordance with the following specifications:

The test shall be conducted to determine the control efficiency of the equipment for VOCs.

The District shall be notified of the date and time of the test at least 10 days prior to the test.

The test shall be conducted to determine the CO, NO_x, PM and SO_x emissions at the outlet. Emissions of CO, NO_x and SO_x shall be expressed in lbs/hr and ppmv. Emissions of PM shall be expressed in lbs/hr and gr/scf.

The test shall be conducted at least 90 days after the protocol is approved by the District but no later than 180 days after the initial start-up. Source test report shall be submitted no later than 60 days from the date of the testing.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C281]

D29.5 The operator shall conduct source test(s) for the pollutant(s) identified below.

Pollutant(s) to be tested	Required Test Method(s)	Averaging Time	Test Location
NOX emissions	Approved District method	1 hour	Outlet

The test shall be conducted once every 5-year period with the first 5-year period ending June 30, 2015.

The test shall be conducted to demonstrate compliance with the source testing requirements of Rule 2012 for a Process Unit opting to comply with a NOx concentration limit.

[RULE 2012, 5-6-2005; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D270, D272]

D82.1 The operator shall install and maintain a CEMS to measure the following parameters:

The CEMS shall be installed and maintained to measure exhaust gas SOX emissions.

The exhaust gas SOX emissions shall be in compliance with the District Rule 431.1 requirements.

The CEMS used for monitoring the exhaust gas SOX emissions shall comply with the District Rule 431.1 Attachment A requirements.

The equipment shall be operated in compliance with the applicable District Rule 431.1 Monitoring, Reporting and Recordkeeping Requirements.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 431.1, 6-12-1998]

[Devices subject to this condition : C301]

D90.3 The operator shall periodically monitor the VOC concentration at outlet of the last carbon adsorber according to the following specifications:

The operator shall use EPA Reference Method 21 to monitor the parameter.

The operator shall calibrate the instrument used to monitor the parameter in ppmv methane.

The operator shall monitor once every week.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C34, C35]

D90.4 The operator shall periodically monitor the VOC concentration at the inlet of each carbon canister and at the exit to the atmosphere according to the following specifications:

The operator shall use EPA Reference Method 21 to monitor the parameter.

The operator shall calibrate the instrument used to monitor the parameter in ppmv methane.

The operator shall monitor once every month.

[RULE 1303(a)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C276]

D90.5 The operator shall periodically monitor the VOC concentration at outlet of the last carbon adsorber according to the following specifications:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall monitor once every eight hours whenever the vacuum blower is not running.

The operator shall use EPA Reference Method 21 to monitor the parameter.

The operator shall calibrate the instrument used to monitor the parameter in ppmv methane.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C303, C304, C308, C311, C312, C313]

D90.6 The operator shall periodically monitor the the operation of the vacuum blower according to the following specifications:

The operator shall monitor once every day.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D140, D195, D196, D197, D198, D284, D287, D288, D289]

D90.7 The operator shall periodically monitor the vacuum level at inlet of the carbon adsorber(s) according to the following specifications:

The operator shall monitor once every day.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C303, C304, C308, C311, C312, C313]

D90.10 The operator shall periodically monitor the VOC concentration at outlet of the carbon adsorber according to the following specifications:

The operator shall use EPA Reference Method 21 to monitor the parameter.

The operator shall calibrate the instrument used to monitor the parameter in ppmv methane.

The operator shall monitor once every month.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C335]

D90.11 The operator shall periodically monitor the VOC concentration at outlet of each carbon adsorber according to the following specifications:

The operator shall use EPA Reference Method 21 to monitor the parameter.

The operator shall calibrate the instrument used to monitor the parameter in ppmv methane.

The operator shall monitor once every operating day.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C551]

D90.12 The operator shall periodically monitor the VOC concentration at the outlet of the blower according to the following specifications:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall use EPA Reference Method 21 to monitor the parameter.

The operator shall calibrate the instrument used to monitor the parameter in ppmv methane.

The operator shall monitor once every week.

The operator shall record the blower flow rate, in SCFM, during the above tests.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D555]

D90.13 The operator shall sample and analyze the VOC concentration in ppmv as methane, and speciated for the compounds listed below, at the outlet of the blower according to the following specifications:

Grab samples shall be collected at the outlet of the blower at least once during the first week of operation, and once each quarter thereafter.

The samples shall be analyzed for VOC in ppmv as methane.

The samples shall be speciated for benzene, ethylbenzene, toluene, xylenes, methyl tert-butyl ether (MTBE), and chlorinated compounds in accordance with AQMD approved methods.

Analysis shall be conducted using EPA Method 8015, EPA Method 8260, EPA Method TO-3/TO-15 or other method approved by the AQMD.

The operator shall record the blower flow rate, in SCFM, during the above tests.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1401, 9-10-2010; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D555]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a semi-annual basis, at least, unless the equipment did not operate during the entire semi-annual period. The routine semi-annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D118, D119, D120, C142, C281, D329]

D328.1 The operator shall determine compliance with the CO emission limit(s) either: (a) conducting a source test at least once every five years using AQMD Method 100.1 or 10.1; or (b) conducting a test at least annually using a portable analyzer and AQMD-approved test method. The test shall be conducted when the equipment is operating under normal conditions to demonstrate compliance with Rule 1146 concentration limit. The operator shall comply with all general testing, reporting, and recordkeeping requirements in Sections E and K of this permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D116, D191]

D332.2 The operator shall determine compliance with the CO emission limit(s) by conducting a test at least once every five years using a portable analyzer and AQMD-approved test method or, if not available, a non-AQMD approved test method. The test shall be conducted when the equipment is operating under normal conditions to demonstrate compliance with CO emissions limit. The operator shall comply with all general testing, reporting, and recordkeeping requirements in Sections E and K of this permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D270, D272]

E. Equipment Operation/Construction Requirements

E17.1 The operator shall not use more than 2 of the following items simultaneously:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Device ID: C565 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C566 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C567 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C568 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C569 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C570 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C571 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C572 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C573 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C574 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C575 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C576 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C577 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C578 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C579 [Vapor Return Line, Vacuum Truck Pump Exhaust]

[RULE 204, 10-8-1993]

[Devices subject to this condition : C578, C579]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E71.2 The operator shall only operate this equipment to process waste gas when the natural gas burner is in operation.

[RULE 204, 10-8-1993]

[Devices subject to this condition : C281]

E71.5 The operator shall not operate this equipment to extract vapors from soils contaminated with any Rule 1401 listed carcinogenic air contaminants (as amended on September 10, 2010) with the exception of benzene, ethylbenzene, MTBE, 1,1-dichloroethane, methylene chloride, perchloroethylene, trichloroethylene and vinyl chloride.

[RULE 1401, 9-10-2010]

[Devices subject to this condition : D554, D555, D556]

E128.1 The operator shall keep all spent carbon in a tightly covered container which shall remain closed except when it is being transferred into or out of the container.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C34, C35, C303, C304, C308, C311, C312, C313, C335, C551]

E153.1 The operator shall change over the carbon in the adsorber whenever breakthrough occurs.

For the purpose of this condition, breakthrough occurs when the hydrocarbon monitor reading indicates a concentration of 500 ppmv at the outlet of the last carbon.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C34, C35, C303, C304, C308, C311, C312, C313]

E153.2 The operator shall change over the carbon in the adsorber whenever breakthrough occurs.

For the purpose of this condition, breakthrough occurs when the hydrocarbon monitor reading indicates a concentration of 100 ppmv at the outlet of the first carbon canister. On an annual basis, without regard to whether breakthrough has occurred, DeMenno/Kerdoon shall change over the carbon in the adsorber. Changing over the carbon in the adsorber shall include removal of the first carbon canister, rotating the second canister in series to first, and putting in a new second carbon canister.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C276]

E153.3 The operator shall change over the carbon in the adsorber whenever breakthrough occurs.

For the purpose of this condition, breakthrough occurs when the hydrocarbon monitor reading indicates a concentration of 500 ppmv at the outlet of the carbon adsorber.

Without regard to whether breakthrough has occurred, the operator shall change over the carbon a minimum of once per calendar year.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C335]

E153.4 The operator shall change over the carbon in the adsorber whenever breakthrough occurs.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, breakthrough occurs when the hydrocarbon monitor reading indicates a concentration of 500 ppmv or higher at the outlet of the primary carbon adsorber. The primary adsorber shall be replaced with either 1) a fresh activated carbon adsorber, or 2) the secondary activated carbon adsorber, and the secondary adsorber shall be replaced with a fresh activated carbon adsorber.

Without regard to whether breakthrough has occurred, the operator shall change over the carbon a minimum of once per calendar year.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C551]

E184.1 The operator shall thoroughly clean the filters in the filter vents immediately after each load of material is received.

[RULE 204, 10-8-1993]

[Devices subject to this condition : D329]

E193.2 The operator shall operate and maintain this equipment as follows:

The number of trucks using the enclosed truck washout facility shall be limited to 60 in any one day.

The operator shall verify operation of the blower BL709 (D277) prior to the start of any truck washout/unloading activity.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D274]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E193.3 The operator shall operate and maintain this equipment according to the following specifications:

Upon completion, any vapor extraction well(s) and duct(s) shall be capped to prevent vapors from venting to the atmosphere. Vapors shall not be extracted from the soil unless vented to the facility afterburners (C142 or C281).

There shall be not detectable leak between the wellheads and the connection to the facility afterburners (C142, C281).

Prior to connecting any vapor extraction wells to the soil vapor extraction system, the completed wells shall be capped to prevent vapors from venting to the atmosphere.

[RULE 1166, 7-14-1995; RULE 1166, 5-11-2001; RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D554, D555, D556]

E336.1 The operator shall vent the vent gases from this equipment as follows:

All vent gases shall be vented to the Vapor Recovery System - North Tank Farms (Process 9, System 1).

This equipment shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D75, D76, D77, D78, D99, D100, D101, D103, D104, D105, D106, D107, D108, D109, D110, D111, D112, D113, D309]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E336.2 The operator shall vent the vent gases from this equipment as follows:

All vent gases shall be vented to the Vapor Return Line (Device C18).

This equipment shall not be operated unless the above vapor return line is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D16, D552]

E336.3 The operator shall vent the vent gases from this equipment as follows:

All vent gases shall be vented to at least one Vapor Return Line (Devices C17 and C22).

This equipment shall not be operated unless the above vapor return line(s) is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D20, D227, D229, D233, D338]

E336.4 The operator shall vent the vent gases from this equipment as follows:

All vent gases shall be vented to the Vapor Recovery System - South Tank Farms (Process 9, System 2).

This equipment shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this equipment.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D66, D67, D68, D71, D73, D74, D79, D80, D81, D82, D83, D84, D85, D87, D88, D92, D93, D94, D95, D209, D210, D211, D212, D213, D214, D215, D216, D217, D218, D219, D220, D221, D222, D223, D224, D225]

E336.5 The operator shall vent the vent gases from this equipment as follows:

All vent gases shall be vented to the Vapor Recovery System - RCRA Fuel & Naphtha Tanks (Process 9, System 5).

This equipment shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D65, D69, D70, D72, D89, D90, D91]

E448.1 The operator shall comply with the following requirements:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall operate only one afterburner (Device Nos. C-142 or C-281) at any one time except during afterburner switchover. Switchover time (including but not limited to emergency, maintenance or testing) shall not exceed 6 hours per day and 12 times per year.

These limits shall not apply during the initial start-up period of the SO_x scrubbers (Device Nos. C-300 and C-301) not to exceed 168 hours during a 30 day period or for curing of new refractory when no vapors are processed or as otherwise approved by the AQMD.

Switchover period shall be defined as switching from one afterburner to another and back to the original afterburner.

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002**]

[Devices subject to this condition : C281, C301]

E448.2 The operator shall comply with the following requirements:

The concentration by volume, at the exhaust stack of the scrubbers (dry basis, zero percent O₂), of sulfur compounds in ppmv as SO₂ shall not exceed 12 ppmv averaged over 24 hours.

The mass, at the exhaust stack of the scrubbers, of sulfur compounds as SO₂ shall not exceed 6.7 pounds per day.

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002**]

[Devices subject to this condition : C301]

E448.6 The operator shall comply with the following requirements:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

In the event of a natural gas curtailment or shortage, if the facility afterburners temperature cannot be maintained at 1400 deg F, the operator shall take the following steps to ensure compliance with all the SCAQMD Rules and Regulations and Permit Conditions:

- 1) Close all the inlet valves to the afterburners C281 and C142.
- 2) Stop receiving any waste material to the facility.
- 3) Stop shipping any product from the facility.
- 4) Shutdown all the heating sources, i.e., boilers and heaters.
- 5) Shutdown all the process feed and transfer pumps.
- 6) Prepare a report to record all the above activities.

[RULE 480, 10-7-1977]

[Devices subject to this condition : C281]

H. Applicable Rules

H23.2 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	464

[RULE 464, 12-7-1990]

[Devices subject to this condition : D26, D29, D30, D32, D33, D52, D64, D418]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H23.4 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	1122

[RULE 1122, 10-1-2004; RULE 1122, 5-1-2009]

[Devices subject to this condition : E264]

H23.6 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	463

[RULE 463, 5-6-2005]

[Devices subject to this condition : D65, D66, D68, D69, D70, D71, D72, D73, D74, D75, D76, D79, D80, D81, D82, D83, D84, D85, D87, D88, D89, D90, D91, D93, D94, D95, D103, D106, D107, D108, D109, D110, D111, D112, D113, E328]

H23.7 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	40CFR60, SUBPART	Kb

[40CFR 60 Subpart Kb, 10-15-2003]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D65, D66, D68, D69, D70, D71, D72, D73, D74, D75, D76, D79, D80, D81, D82, D83, D84, D85, D87, D88, D89, D90, D91, D93, D94, D95, D103, D106, D107, D108, D109, D110, D111, D112, D113]

H23.9 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
SOX	40CFR60, SUBPART	Dc
PM	40CFR60, SUBPART	Dc

[40CFR 60 Subpart Dc, 2-27-2006]

[Devices subject to this condition : D116, D191]

H23.10 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
PM	District Rule	1470
CO	40CFR60, SUBPART	III
NOX	40CFR60, SUBPART	III
PM	40CFR60, SUBPART	III
ROG	40CFR60, SUBPART	III
HAPs	40CFR63, SUBPART	ZZZZ

[RULE 1470, 6-1-2007; 40CFR 60 Subpart III, 7-11-2006; 40CFR 63 Subpart ZZZZ, 1-18-2008]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D298]

H23.12 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
Visible Emissions	District Rule	1155

[RULE 1155, 5-2-2014]

[Devices subject to this condition : D329]

H23.13 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	1149

[**RULE 1149, 7-14-1995; RULE 1149, 5-2-2008**]

[Devices subject to this condition : D65, D66, D68, D69, D70, D72, D79, D88, D89, D90, D91, D93, D94, D95]

H23.14 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	462

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 462, 5-14-1999]

[Devices subject to this condition : E343]

H116.1 The operator shall vent all gases, vapors and gas-entrained effluents from this equipment to an afterburner which is in full operation in order to comply with District Rule 470 whenever this equipment is in operation.

[RULE 470, 5-7-1976]

[Devices subject to this condition : D118]

H116.4 The operator shall maintain this equipment to achieve a minimum control efficiency of 98 percent for VOCs in order to comply with District rules and regulations whenever any of the equipment it vents is in operation.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C281]

H116.5 The operator shall , upon completion of construction of a sulfur scrubber and the expiration of the initial start-up period described in Condition E448.1, vent this equipment to a sulfur scrubber that has been issued a permit by the District which is in full operation in order to comply with District Rule 431.1 whenever this equipment is in operation.

[RULE 431.1, 6-12-1998]

[Devices subject to this condition : C281]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H116.6 The operator shall determine the VOC concentration on a monthly basis to demonstrate compliance with the VOC limit at the exhaust of the control equipment in order to comply with offsets requirements whenever the afterburners are in operation. If compliance is demonstrated for three consecutive months, then grab sampling and analysis shall be conducted on a quarterly basis. If the quarterly analysis shows non-compliance, then the grab sampling schedule shall be reverted to monthly basis.

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002**]

[Devices subject to this condition : C281]

I. Administrative

I298.1 This equipment shall not be operated unless the facility holds 12571 pounds of NOx RTCs in its allocation account to offset the annual emissions increase for the first year of operation. The RTCs held to satisfy the first year of operation portion of this condition may be transferred only after one year from the initial start of operation. In addition, this equipment shall not be operated unless the operator demonstrates to the Executive Officer that, at the commencement of each compliance year after the start of operation, the facility holds 12571 pounds of NOx RTCs valid during that compliance year. RTCs held to satisfy the compliance year portion of this condition may be transferred only after the compliance year for which the RTCs are held. If the initial or annual hold amount is partially satisfied by holding RTCs that expire midway through the hold period, those RTCs may be transferred upon their respective expiration dates. This hold amount is in addition to any other amount of RTCs required to be held under other condition(s) stated in this permit.

[**RULE 2005, 6-3-2011**]

[Devices subject to this condition : C281]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

I298.2 This equipment shall not be operated unless the facility holds 97 pounds of NO_x RTCs in its allocation account to offset the annual emissions increase for the first year of operation. The RTCs held to satisfy the first year of operation portion of this condition may be transferred only after one year from the initial start of operation. In addition, this equipment shall not be operated unless the operator demonstrates to the Executive Officer that, at the commencement of each compliance year after the start of operation, the facility holds 97 pounds of NO_x RTCs valid during that compliance year. RTCs held to satisfy the compliance year portion of this condition may be transferred only after the compliance year for which the RTCs are held. If the initial or annual hold amount is partially satisfied by holding RTCs that expire midway through the hold period, those RTCs may be transferred upon their respective expiration dates. This hold amount is in addition to any other amount of RTCs required to be held under other condition(s) stated in this permit.

[RULE 2005, 6-3-2011]

[Devices subject to this condition : D298]

K. Record Keeping/Reporting

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records for all coating consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coatings.

For architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coatings.

[RULE 1113, 11-8-1996; RULE 1113, 7-13-2007; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : E261]

K67.4 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

All materials loaded, unloaded, or stored.

Monthly throughput of materials loaded, unloaded or stored.

True vapor pressure measurements (if required).

Reid vapor pressure measurements (if required).

Temperature measurements (if required).

Material Safety Data Sheets (if required).

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D16, D20, D65, D66, D67, D68, D69, D70, D71, D72, D73, D74, D75, D76, D77, D78, D79, D80, D81, D82, D83, D84, D85, D87, D88, D89, D90, D91, D92, D93, D94, D95, D99, D100, D101, D103, D104, D105, D106, D107, D108, D109, D110, D111, D112, D113, D209, D210, D211, D212, D213, D214, D215, D216, D217, D218, D219, D220, D221, D222, D223, D224, D225, D227, D229, D231, D233, D235, D242, D309, D336, D338, D552, D562]

K67.7 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Number of trucks using the truck washout facility each day

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D274]

K67.8 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

A log of engine operations, including manual and automatic operation, documenting the total time the engine is operated each month and the specific reason for operation as:

- A. Emergency use
- B. Maintenance and testing
- C. Other (Describe the reason for the operation)

In addition, for each time the engine is manually started, the log shall include the date of engine operation, the specific reason for operation, and the totalizing hour meter readings (in hours and tenths of hours) at the beginning and end of the operation.

On or before January 15th of each year, the operator shall record in the engine log:

- A. the total hours of engine operation for the previous calendar year, and
- B. the total hours of engine operation for maintenance and testing for the previous calendar year.

Engine operation log(s) shall be retained on site for a minimum of five calendar years and shall be made available to the Executive Officer or representative upon request.

[RULE 1110.2, 2-1-2008; RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996; RULE 1470, 6-1-2007; RULE 2012, 5-6-2005; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D298]

K67.10 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

VOC monitoring of the carbon adsorber(s).

Vacuum level monitoring of the carbon adsorber(s).

Replacement of the carbon adsorber(s).

Records shall be kept and maintained for at least five years, and shall be made available to the Executive Officer or his authorized representative upon request.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C303, C304, C308, C311, C312, C313]

K67.11 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Monitoring, maintenance and repair of the vacuum blower.

Records shall be kept and maintained for at least five years, and shall be made available to the Executive Officer or his authorized representative upon request.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D140, D195, D196, D197, D198, D284, D287, D288, D289]

K67.12 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Amount of natural gas combusted during each calendar month

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 2012, 5-6-2005; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; 40CFR 60 Subpart Dc, 2-27-2006]

[Devices subject to this condition : D116, D191]

K67.17 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Amount of natural gas combusted during each quarter.

Results of the periodic source tests for NOx and CO.

Records shall be kept and maintained for at least five years, and shall be made available to the Executive Officer or his authorized representative upon request.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 2012, 5-6-2005; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D270, D272]

K67.18 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

All materials stored during each year.

The date(s) any materials are received.

The total weight of materials received.

Records shall be kept and maintained for at least five years, and shall be made available to the Executive Officer or his authorized representative upon request.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D329]

K67.19 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

pH of the scrubbing solution.

Re-circulation flow rate, in gpm, of the scrubbing solution.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C137, C138, C139]

K67.20 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Volume of wastewater discharged to the LACSD sewer connection, in gallons per calendar month.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D468]

K67.21 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Date and hours of operation.

Reason for operation.

Monitoring and replacement of the carbon adsorber(s).

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 402, 5-7-1976]

[Devices subject to this condition : C551]

K67.22 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Monitoring and replacement of the carbon adsorber(s).

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C34, C35, C276, C335]

K67.23 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

VOC measurements.

Grab sample analyses.

Flow rate measurements.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 9-10-2010; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D555]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: DISTILLATION					
System 1: USED OIL DEHYDRATION					S15.1
PUMP, P-002A, 1000-SERIES NORTH TRANSFER, 15 HP A/N: 568962 Permit to Construct Issued: 12/05/14	D426				
PUMP, P-002B, 1000-SERIES SOUTH TRANSFER, 15 HP A/N: 568962 Permit to Construct Issued: 12/05/14	D427				
PUMP, P-215, TANK 2003 CIRCULATION, 25 HP A/N: 568962 Permit to Construct Issued: 12/05/14	D428				
PUMP, P-XX2, SWTF TRANSFER, 15 HP A/N: 568962 Permit to Construct Issued: 12/05/14	D429				
PUMP, P-XX3, SWTF TRANSFER, 15 HP A/N: 568962 Permit to Construct Issued: 12/05/14	D430				
PUMP, AP-412, DRAIN, AIR-POWERED A/N: 568962 Permit to Construct Issued: 12/05/14	D431				
PUMP, P-203A/B/C, EAST/MIDDLE/WEST DEHYDRATION CHARGE, 50 HP EACH, 3 TOTAL A/N: 568962 Permit to Construct Issued: 12/05/14	D326				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: DISTILLATION					
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-406A/B IN SERIES, NORTH PREHEATER, 2 TOTAL; DIAMETER: 3 FT 4 IN; LENGTH: 14 FT 6 IN A/N: 568962 Permit to Construct Issued: 12/05/14	D132				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-405A/B, IN SERIES, SOUTH PREHEATER, 2 TOTAL; DIAMETER: 3 FT 4 IN; LENGTH: 14 FT 6 IN A/N: 568962 Permit to Construct Issued: 12/05/14	D133				
TOWER, FLASH, DEHYDRATION VESSEL, C-201, HEIGHT: 22 FT ; DIAMETER: 5 FT A/N: 568962 Permit to Construct Issued: 12/05/14	D125	D266 D267			
PUMP, P-201A/B IN SERIES, EAST/WEST C-201 BOTTOMS, 50 HP EACH, 2 TOTAL A/N: 568962 Permit to Construct Issued: 12/05/14	D237				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-203, LENGTH: 15 FT 11 IN; DIAMETER: 2 FT 8 IN A/N: 568962 Permit to Construct Issued: 12/05/14	D247				
TOWER, FLASH, DEHYDRATION VESSEL, C-202, HEIGHT: 22 FT ; DIAMETER: 5 FT A/N: 568962 Permit to Construct Issued: 12/05/14	D126	D266 D267			

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: DISTILLATION					
PUMP, P-202A/B IN SERIES, NORTH/SOUTH C-202 BOTTOMS, 50 HP EACH, 2 TOTAL A/N: 568962 Permit to Construct Issued: 12/05/14	D263				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-203A,, LENGTH: 15 FT 11 IN; DIAMETER: 2 FT 8 IN A/N: 568962 Permit to Construct Issued: 12/05/14	D265				
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-202,C-202 OVERHEAD COOLER, LENGTH: 14 FT 6 IN; DIAMETER: 3 FT A/N: 568962 Permit to Construct Issued: 12/05/14	D266	D125 D126 D128			
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-201,C-201 OVERHEAD COOLER, LENGTH: 14 FT 6 IN; DIAMETER: 3 FT A/N: 568962 Permit to Construct Issued: 12/05/14	D267	D125 D126 D128			
TOWER, FLASH, VACUUM DEHYDRATION VESSEL, C-203, HEIGHT: 22 FT ; DIAMETER: 5 FT A/N: 568962 Permit to Construct Issued: 12/05/14	D127	D258			
PUMP, P-203A/B, NORTH/SOUTH C-203 BOTTOMS, 15 HP EACH, 2 TOTAL A/N: 568962 Permit to Construct Issued: 12/05/14	D305				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: DISTILLATION					
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-206, FUELOIL COOLER, LENGTH: 14 FT 6 IN; DIAMETER: 2 FT 2 IN A/N: 568962 Permit to Construct Issued: 12/05/14	D525				
TOWER, FLASH, VACUUM DEHYDRATION VESSEL, C-206, HEIGHT: 10 FT 6 IN; DIAMETER: 5 FT A/N: 568962 Permit to Construct Issued: 12/05/14	D178	D258			
PUMP, P-206A, EAST C-206 BOTTOMS, 10 HP A/N: 568962 Permit to Construct Issued: 12/05/14	D351				
PUMP, P-206B, WEST C-206 BOTTOMS, 20 HP A/N: 568962 Permit to Construct Issued: 12/05/14	D423				
CONDENSER, BAROMETRIC, LENGTH: 10 FT 11 IN; DIAMETER: 10 IN A/N: 568962 Permit to Construct Issued: 12/05/14	D258	D127 D178 D260 D344			
HEAT EXCHANGER, SHELL AND TUBE TYPE, E-205, BAROMETRIC COOLER, LENGTH: 12 FT 4 IN; DIAMETER: 2 FT 6 IN A/N: 568962 Permit to Construct Issued: 12/05/14	D260	D128 D258			

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: DISTILLATION					
ACCUMULATOR, PHASE SEPARATOR, D-204, LENGTH: 20 FT ; DIAMETER: 5 FT A/N: 568962 Permit to Construct Issued: 12/05/14	D128	D9 D31 D121 D176 D177 D260 D266 D267 D361 D373 D380 D383 D385 D394 D395 D417 D559 D560			
PUMP, EAST/WEST BAROMETRIC, P-701A/B, 15 HP EACH, 2 TOTAL A/N: 568962 Permit to Construct Issued: 12/05/14	D255				
PUMP, EAST NAPHTHA, P-702A, 10 HP, SEALLESS A/N: 568962 Permit to Construct Issued: 12/05/14	D256				
PUMP, WEST NAPHTHA, P-702B, 7.5 HP A/N: 568962 Permit to Construct Issued: 12/05/14	D259				
PUMP, EAST/WEST WATER, P-703A/B, 7.5 HP EACH, 2 TOTAL A/N: 568962 Permit to Construct Issued: 12/05/14	D257				
PUMP, AP-205A/B, EAST/WEST SLOP INJECTION, AIR-POWERED A/N: 568962 Permit to Construct Issued: 12/05/14	D508				
PUMP, AP-213, DEHYDRATION CHARGE PUMP DRAIN PUMPS POT, AIR-POWERED A/N: 568962 Permit to Construct Issued: 12/05/14	D509				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
System 2: SLUDGE DEWATERING					S1.2
UNLOADING STATION, TRUCK WASHOUT, LOCATED INSIDE THE TRUCK WASHOUT ENCLOSURE, WITH A 10 HP CONVEYOR, WIDTH: 8 FT ; HEIGHT: 7 FT ; LENGTH: 28 FT A/N:	D52	D322			H23.2
PUMP, AP-301, WASHOUT BOX, AIR-POWERED A/N:	D496				
SCREEN, ROTARY SOLIDS, IPEC, MODEL RSS-1218, 1/3 HP ELECTRIC MOTOR WITH A/N:	D580	D322			H23.2, K171.1
BIN, SOLIDS, PORTABLE, UP TO 4 CUBIC YARDS, COVERED, CONNECTED TO THE ROTARY SCREEN VIA SEALED FLEXIBLE DUCTING	D581				
TANK, HOLDING, V-701, WASTE WATER, 500 BBL A/N:	D60	D322			
PUMP, P-701, CENTRIFUGE FEED, 7.5 HP A/N:	D582				K171.1
GRINDER, SOLIDS, SEALED, 5 HP ELECTRIC MOTOR A/N:	D583				K171.1

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
CENTRIFUGE, SHARPLES, MODEL P-4600 SUPER-D-CANTER, 75 HP ELECTRIC BOWL MOTOR AND 10 HP ELECTRIC SCREW MOTOR WITH A/N:	D64	D324			H23.2, K171.1
BIN, SOLIDS, PORTABLE, UP TO 4 CUBIC YARDS, COVERED	D584				
TANK, HOLDING, WASTEWATER, WIDTH: 6 FT ; HEIGHT: 6 FT ; LENGTH: 7 FT 6 IN	D585				
ENCLOSURE, CENTRIFUGE, SOLIDS BIN, HOLDING TANK, WIDTH: 11 FT ; HEIGHT: 17 FT ; LENGTH: 21 FT					
PUMP, P-700, 5 HP A/N:	D586				K171.1
BIN, SOLIDS, PORTABLE, UP TO 4 CUBIC YARD CAPACITY EACH, COVERED, 10 TOTAL A/N:	D418				H23.2
BIN, ROLLOFF, UP TO 40 CUBIC YARD CAPACITY EACH, COVERED, 10 TOTAL A/N:	D524				
System 3: STORAGE SILO					

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 5: OIL/WATER SEPARATION					
STORAGE SILO, 2800 CU FT CAPACITY, FLY ASH, CEMENT KILN DUST, WITH A SEALED 10" DISCHARGE AUGER AND A 10 HP ELECTRIC MOTOR, HEIGHT: 30 FT ; DIAMETER: 10 FT 10 IN WITH A/N: 530589 Permit to Construct Issued: 04/11/12	D557			PM: (9) [RULE 404, 2-7-1986; RULE 405, 2-7-1986]	C1.13, D323.1, E184.1, H23.12, K67.18, K171.1
FILTER, VENT, 225 SQ FT TOTAL FILTER AREA, WITH 18 FILTER BAGS, EACH, LENGTH: 6 FT ; DIAMETER: 8 IN	C558				
Process 9: AIR POLLUTION CONTROL					
System 1: VAPOR RECOVERY SYSTEM - NORTH TANK FARMS					S15.2, S18.6
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N: 571935 Permit to Construct Issued: 03/27/15	C565	D314			E17.1
CARBON ADSORBER, 150 LBS A/N: 571935 Permit to Construct Issued: 03/27/15	C311			VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.5, D90.7, E128.1, E153.1, K67.10
KNOCK OUT POT, KO-200, HEIGHT: 6 FT 7 IN; DIAMETER: 2 FT 6 IN A/N: 571935 Permit to Construct Issued: 03/27/15	D131				
CARBON ADSORBER, 150 LBS A/N: 571935 Permit to Construct Issued: 03/27/15	C312			VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.5, D90.7, E128.1, E153.1, K67.10

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
KNOCK OUT POT, KO-201, HEIGHT: 7 FT ; DIAMETER: 3 FT 5 IN A/N: 571935 Permit to Construct Issued: 03/27/15	D129				
KNOCK OUT POT, KO-202, HEIGHT: 6 FT 8 IN; DIAMETER: 2 FT A/N: 571935 Permit to Construct Issued: 03/27/15	D130				
POT, SEAL, SP-200, HEIGHT: 5 FT 10 IN; DIAMETER: 2 FT A/N: 571935 Permit to Construct Issued: 03/27/15	D193				
BLOWER, VACUUM, BL-702, 5 HP A/N: 571935 Permit to Construct Issued: 03/27/15	D195	C142 C281			D90.6, K67.11
System 2: VAPOR RECOVERY SYSTEM - SOUTH TANK FARMS					S15.2, S18.4
CARBON ADSORBER, 150 LBS A/N: 571936 Permit to Construct Issued: 03/27/15	C303			VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.5, D90.7, E128.1, E153.1, K67.10
KNOCK OUT POT, KO-500, HEIGHT: 5 FT ; DIAMETER: 2 FT A/N: 571936 Permit to Construct Issued: 03/27/15	D134				
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N: 571936 Permit to Construct Issued: 03/27/15	C572	D283			E17.1
KNOCK OUT POT, KO-505, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N: 571936 Permit to Construct Issued: 03/27/15	D283	C572			

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
CARBON ADSORBER, TWO IN SERIES, EACH 150 LBS A/N: 571936 Permit to Construct Issued: 03/27/15	C313			VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.5, D90.7, E128.1, E153.1, K67.10
KNOCK OUT POT, KO-506, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N: 571936 Permit to Construct Issued: 03/27/15	D286				
CARBON ADSORBER, 150 LBS A/N: 571936 Permit to Construct Issued: 03/27/15	C304			VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.5, D90.7, E128.1, E153.1, K67.10
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N: 571936 Permit to Construct Issued: 03/27/15	C566	D135			E17.1
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N: 571936 Permit to Construct Issued: 03/27/15	C567	D135			E17.1
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N: 571936 Permit to Construct Issued: 03/27/15	C568	D135			E17.1
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N: 571936 Permit to Construct Issued: 03/27/15	C569	D135			E17.1
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N: 571936 Permit to Construct Issued: 03/27/15	C570	D135			E17.1

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N: 571936 Permit to Construct Issued: 03/27/15	C571	D135			E17.1
KNOCK OUT POT, KO-501, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N: 571936 Permit to Construct Issued: 03/27/15	D135	C566 C567 C568 C569 C570 C571			
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N: 571936 Permit to Construct Issued: 03/27/15	C573	D136			E17.1
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N: 571936 Permit to Construct Issued: 03/27/15	C574	D136			E17.1
KNOCK OUT POT, KO-502, HEIGHT: 13 FT 4 IN; DIAMETER: 9 FT 4 IN A/N: 571936 Permit to Construct Issued: 03/27/15	D136	D36 D37 D38 D468 C573 C574			
KNOCK OUT POT, KO-503, HEIGHT: 6 FT 6 IN; DIAMETER: 2 FT A/N: 571936 Permit to Construct Issued: 03/27/15	D291				
KNOCK OUT POT, KO-504, HEIGHT: 3 FT 6 IN; DIAMETER: 3 FT 5 IN A/N: 571936 Permit to Construct Issued: 03/27/15	D292				
BLOWER, VACUUM, BL-701B, 15 HP A/N: 571936 Permit to Construct Issued: 03/27/15	D196	C142 C281			D90.6, K67.11

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
BLOWER, VACUUM, BL-701A, 15 HP A/N: 571936 Permit to Construct Issued: 03/27/15	D284	C142 C281			D90.6, K67.11
System 3: VAPOR RECOVERY SYSTEM - PROCESS WASTE GAS					S15.2, S18.2
KNOCK OUT POT, ,KO-708, HEIGHT: 7 FT ; DIAMETER: 4 FT A/N: 551690 Permit to Construct Issued: 08/20/13	D559	D128			K171.1
KNOCK OUT POT, KO-709, HEIGHT: 7 FT ; DIAMETER: 4 FT A/N: 551690 Permit to Construct Issued: 08/20/13	D560	D128			K171.1
PUMP, KO POT 708/709 DRAIN, P-XXX, 5 HP A/N: 551690 Permit to Construct Issued: 08/20/13	D561				K171.1
KNOCK OUT POT, KO-703, HEIGHT: 7 FT 4 IN; DIAMETER: 1 FT 10 IN A/N: 551690 Permit to Construct Issued: 08/20/13	D295				
KNOCK OUT POT, KO-700, HEIGHT: 7 FT 4 IN; DIAMETER: 2 FT A/N: 551690 Permit to Construct Issued: 08/20/13	D294				
PUMP, KO POT 700/703 DRAIN, P-708, 5 HP A/N: 551690 Permit to Construct Issued: 08/20/13	D250				
KNOCK OUT POT, KO-702, HEIGHT: 13 FT ; DIAMETER: 4 FT 2 IN A/N: 551690 Permit to Construct Issued: 08/20/13	D141	C281			

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
PUMP, KO-702 DRAIN, P-711, 5 HP A/N: 551690 Permit to Construct Issued: 08/20/13	D254				
KNOCK OUT POT, KO-704, HEIGHT: 5 FT 6 IN; DIAMETER: 2 FT 2 IN A/N: 551690 Permit to Construct Issued: 08/20/13	D241	C142			
KNOCK OUT POT, KO-705, HEIGHT: 6 FT 6 IN; DIAMETER: 3 FT A/N: 551690 Permit to Construct Issued: 08/20/13	D226	C142			
System 5: VAPOR RECOVERY SYSTEM - RCRA FUEL & NAPHTHA TANKS					S15.2, S18.5
CARBON ADSORBER, TWO IN SERIES, EACH 150 LBS A/N: 571939 Permit to Construct Issued: 03/27/15	C308			VOC: 500 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	D90.5, D90.7, E128.1, E153.1, K67.10
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N: 571939 Permit to Construct Issued: 03/27/15	C575	D306			E17.1
KNOCK OUT POT, KO-300, HEIGHT: 7 FT ; DIAMETER: 3 FT 5 IN A/N: 571939 Permit to Construct Issued: 03/27/15	D306	C575			
KNOCK OUT POT, KO-301, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N: 571939 Permit to Construct Issued: 03/27/15	D293				
POT, SEAL, SP-300, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N: 571939 Permit to Construct Issued: 03/27/15	D307				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
BLOWER, VACUUM, BL-705, 5 HP A/N: 571939 Permit to Construct Issued: 03/27/15	D140	C142 C281			D90.6, K67.11
System 7: AFTERBURNER					
AFTERBURNER, 23.2 MMBTU/HR (PROCESS GAS AND NAT. GAS), 8.2 MMBTU/HR (NAT. GAS), A/N: 527510 Permit to Construct Issued: 04/11/12	C142	C139 D140 D195 D196 D197 D198 D226 D241 D284 D287 D288 D289 C300 D324 D555	NOX: LARGE SOURCE**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]; SO2: 500 PPMV AT 15 MINS. (5) [RULE 407, 4-2-1982]	C1.14, C4.1, C8.5, D12.5, D12.7, D28.1, D29.4, D323.1, E71.2, E71.3, E448.1, E448.3, E448.4, E448.6, H116.4, H116.5, H116.6, I298.1, K171.1
SCRUBBER, PACKED BED, CAUSTIC, ENVITECH, MODEL RT5-12, SINGLE STAGE, WITH MIST ELIMINATOR, MUNTERS, T-125, AND A QUENCH TOWER. WITH A COMMON STACK WITH DEVICE C301, WIDTH: 8 FT 6 IN; HEIGHT: 13 FT ; LENGTH: 16 FT 6 IN A/N: 544927 Permit to Construct Issued: 05/01/13	C300	C142			C8.6, C8.10, D82.1, E448.1, E448.2, K171.1
System 8: VAPOR RECOVERY SYSTEM - WASTEWATER TREATMENT					S15.2, S18.7
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N: 571940 Permit to Construct Issued: 03/27/15	C576	D205			E17.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
KNOCK OUT POT, KO-600, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N: 571940 Permit to Construct Issued: 03/27/15	D205	D25 D26 D27 D28 D30 D32 D33 D86 D96 D190 D451 C576			
KNOCK OUT POT, KO-601, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N: 571940 Permit to Construct Issued: 03/27/15	D285				
KNOCK OUT POT, KO-602, HEIGHT: 5 FT 4 IN; DIAMETER: 2 FT A/N: 571940 Permit to Construct Issued: 03/27/15	D194	D23			
KNOCK OUT POT, KO-603, HEIGHT: 3 FT 6 IN; DIAMETER: 3 FT 5 IN A/N: 571940 Permit to Construct Issued: 03/27/15	D206				
BLOWER, VACUUM, BL-703A, 15 HP A/N: 571940 Permit to Construct Issued: 03/27/15	D197	C142 C281			D90.6, K67.11
BLOWER, VACUUM, BL-703B, 15 HP A/N: 571940 Permit to Construct Issued: 03/27/15	D287	C142 C281			D90.6, K67.11
System 9: VAPOR RECOVERY SYSTEM - FRONT LOADING RACKS					S13.3, S15.2, S18.8
VAPOR RETURN LINE, TRUCK LOADING, 6 TOTAL A/N: 571941 Permit to Construct Issued: 03/27/15	C17	D315			

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
VAPOR RETURN LINE, TRUCK LOADING, 5 TOTAL A/N: 571941 Permit to Construct Issued: 03/27/15	C22	D314			
KNOCK OUT POT, KO-100, HEIGHT: 3 FT 4 IN; DIAMETER: 1 FT 6 IN A/N: 571941 Permit to Construct Issued: 03/27/15	D315	C17			
KNOCK OUT POT, KO-101, HEIGHT: 3 FT 4 IN; DIAMETER: 1 FT 6 IN A/N: 571941 Permit to Construct Issued: 03/27/15	D314	C22 C565			
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N: 571941 Permit to Construct Issued: 03/27/15	C577	D207			E17.1
KNOCK OUT POT, KO-102, HEIGHT: 6 FT 8 IN; DIAMETER: 2 FT A/N: 571941 Permit to Construct Issued: 03/27/15	D207	C577			
POT, SEAL, SP-100, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N: 571941 Permit to Construct Issued: 03/27/15	D208				
BLOWER, VACUUM, BL-704, 7.5 HP A/N: 571941 Permit to Construct Issued: 03/27/15	D198	C142 C281			D90.6, K67.11
System 12: VAPOR RECOVERY SYSTEM - SLUDGE DEWATERING					S15.2, S18.9
KNOCK OUT POT, KO-800, HEIGHT: 4 FT ; DIAMETER: 2 FT A/N:	D323	D29			

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 9: AIR POLLUTION CONTROL					
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N:	C578	D322			E17.1
KNOCK OUT POT, KO-801, HEIGHT: 13 FT ; DIAMETER: 2 FT A/N:	D322	D52 D60 C578 D580			
KNOCK OUT POT, KO-802, HEIGHT: 4 FT ; DIAMETER: 3 FT A/N:	D321				
VAPOR RETURN LINE, VACUUM TRUCK PUMP EXHAUST, 1 TOTAL A/N:	C579	D320			E17.1
KNOCK OUT POT, KO-803, HEIGHT: 4 FT ; DIAMETER: 3 FT A/N:	D320	C579			
POT, SEAL, SP-800, HEIGHT: 6 FT ; DIAMETER: 2 FT A/N:	D319				
BLOWER, VACUUM, BL-706, 7.5 HP A/N:	D289	C142 C281			D90.6, K67.11
BLOWER, VACUUM, BL-708, 7.5 HP A/N:	D324	D64 C142 C281			D90.14, K67.11

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: DEVICE ID INDEX

Device Index For Section H			
Device ID	Section H Page No.	Process	System
C17	15	9	9
C22	16	9	9
D52	6	5	2
D60	6	5	2
D64	7	5	2
D125	2	1	1
D126	2	1	1
D127	3	1	1
D128	5	1	1
D129	9	9	1
D130	9	9	1
D131	8	9	1
D132	2	1	1
D133	2	1	1
D134	9	9	2
D135	11	9	2
D136	11	9	2
D140	14	9	5
D141	12	9	3
C142	14	9	7
D178	4	1	1
D193	9	9	1
D194	15	9	8
D195	9	9	1
D196	11	9	2
D197	15	9	8
D198	16	9	9
D205	15	9	8
D206	15	9	8
D207	16	9	9
D208	16	9	9
D226	13	9	3
D237	2	1	1
D241	13	9	3

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: DEVICE ID INDEX

Device Index For Section H			
Device ID	Section H Page No.	Process	System
D247	2	1	1
D250	12	9	3
D254	13	9	3
D255	5	1	1
D256	5	1	1
D257	5	1	1
D258	4	1	1
D259	5	1	1
D260	4	1	1
D263	3	1	1
D265	3	1	1
D266	3	1	1
D267	3	1	1
D283	9	9	2
D284	12	9	2
D285	15	9	8
D286	10	9	2
D287	15	9	8
D289	17	9	12
D291	11	9	2
D292	11	9	2
D293	13	9	5
D294	12	9	3
D295	12	9	3
C300	14	9	7
C303	9	9	2
C304	10	9	2
D305	3	1	1
D306	13	9	5
D307	13	9	5
C308	13	9	5
C311	8	9	1
C312	8	9	1
C313	10	9	2

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: DEVICE ID INDEX

Device Index For Section H			
Device ID	Section H Page No.	Process	System
D314	16	9	9
D315	16	9	9
D319	17	9	12
D320	17	9	12
D321	17	9	12
D322	17	9	12
D323	16	9	12
D324	17	9	12
D326	1	1	1
D351	4	1	1
D418	7	5	2
D423	4	1	1
D426	1	1	1
D427	1	1	1
D428	1	1	1
D429	1	1	1
D430	1	1	1
D431	1	1	1
D496	6	5	2
D508	5	1	1
D509	5	1	1
D524	7	5	2
D525	4	1	1
D557	8	5	3
C558	8	5	3
D559	12	9	3
D560	12	9	3
D561	12	9	3
C565	8	9	1
C566	10	9	2
C567	10	9	2
C568	10	9	2
C569	10	9	2
C570	10	9	2

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: DEVICE ID INDEX

Device Index For Section H			
Device ID	Section H Page No.	Process	System
C571	11	9	2
C572	9	9	2
C573	11	9	2
C574	11	9	2
C575	13	9	5
C576	14	9	8
C577	16	9	9
C578	17	9	12
C579	17	9	12
D580	6	5	2
D581	6	5	2
D582	6	5	2
D583	6	5	2
D584	7	5	2
D585	7	5	2
D586	7	5	2

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F2.1 The operator shall limit emissions from this facility as follows:

CONTAMINANT	EMISSIONS LIMIT
VOC	Less than 2550 LBS IN ANY ONE MONTH

The facility afterburners stacks and facility fugitive components shall comply with the above Volatile Organic Compounds (VOC) emission limit.

To ensure compliance with the monthly Volatile Organic Compounds (VOC) emission limit of this condition, the operator shall comply with the following recordkeeping requirements:

(1) Within 14 calendar days after the end of each month, the operator shall total and record VOC emissions for the month from afterburners and fugitive components.

(2) The operator shall retain the VOC emissions records for at least 5 years.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

F2.2 The operator shall limit emissions from this facility as follows:

CONTAMINANT	EMISSIONS LIMIT
SOX	Less than 4 TONS IN ANY ONE YEAR

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

The facility afterburners systems shall comply with the above Sulfur Oxides (SOX) emission limit.

To ensure compliance with the Sulfur Oxides (SOX) emission limit of this condition, the operator shall comply with the following monitoring and recordkeeping requirements:

1. Monitor SOX concentrations at the exhaust stack of the afterburner C281/scrubber C301 or the afterburner C142/scrubber C300 using AQMD certified Continuous Emissions Monitoring System (CEMS), OR
2. If afterburner C281/scrubber C301 is out of operation and scrubber C300 is under construction, monitor the sulfur content of the vapor recovery stream and calculate the SOX emissions from the afterburner C142 on a daily basis.
3. Within 14 calendar days after the end of each month, the operator shall total and record SOX emissions for the month and for the calendar year from the two afterburners C281 and C142.
4. The operator shall retain sulfur content and the SOX emissions records for at least 5 years.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

- (a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or
- (b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

F14.1 The operator shall not use liquid fuel containing sulfur compounds in excess of 500 ppm by weight.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

F14.2 The operator shall not purchase any diesel fuel , for stationary source application as defined in Rule 431.2, containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

F16.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Records of the monthly (and quarterly where applicable) inspection, and subsequent repair and reinspection, of VOC fugitive components subject to District Rule 1173

[RULE 1173, 2-6-2009]

F48.2 The operator shall not operate at this facility any combustion devices burning gaseous fuels (except natural gas) unless total sulfur compounds emissions from the facility are less than 5 pounds per day (calculated as H₂S).

This condition shall no longer apply once this facility has demonstrated to the satisfaction of the District that the operation of all combustion devices at this facility will comply with all applicable requirements of Rule 431.1.

[RULE 431.1, 6-12-1998]

F48.3 The operator shall not operate at this facility any device used to produce gasoline, kerosene, distillate fuel oils, residual fuel oils, lubricants, or other products through distillation of petroleum or through redistillation, cracking or reforming of unfinished petroleum derivatives.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, petroleum shall be defined as the crude oil removed from the earth and the oils derived from tar sands, shale, and coal.

The operator shall submit to the Executive Officer, as a part of an annual compliance certification, a statement that certifies compliance with this condition.

[RULE 204, 10-8-1993]

F48.4 The operator shall not operate at this facility any device used to treat, store, or dispose of benzene-containing hazardous waste from any chemical manufacturing plant, coke by-product recovery plant, or petroleum refinery.

The operator shall submit to the Executive Officer, as a part of an annual compliance certification, a statement that certifies compliance with this condition.

A copy of each manifest, or the manifest data stored in a manifest database, for benzene-containing hazardous waste received at this facility shall be kept and maintained for at least five years, and shall be made available to the Executive Officer or his authorized representative upon request

[RULE 204, 10-8-1993]

F52.1 This facility is subject to the applicable requirements of the following rules or regulation(s):

40 CFR 60 Subpart A

40 CFR 61 Subpart A

40 CFR 63 Subpart A

[40CFR 60 Subpart A, 4-4-2014; 40CFR 61 Subpart A, 2-27-2014; 40CFR 63 Subpart A, 3-27-2014]

SYSTEM CONDITIONS

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

- S1.1 The operator shall limit the loading rate to no more than 6,132,000 gallon(s) in any one calendar month.

This limit shall be based on the total combined throughput of Asphalt Flux Loading Rack No. 4 (Process 7, System 7) and Asphalt Flux Loading Rack No. 7 (Process 7, System 8).

The operator shall monitor the throughput of materials loaded, in gallons, by using certified truck scale records to determine the pounds of material loaded, and a measurement of the specific gravity or API gravity of the material loaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 7 , 8]

- S1.2 The operator shall limit the material processed to no more than 4,320,000 gallon(s) in any one calendar month.

For the purpose of this condition, material processed shall be defined as the total amount of sludge or any other hydrocarbon containing material processed in this system before dewatering.

To comply with this condition, the operator shall install and maintain a non-resettable totalizing flow meter to accurately indicate the total volume of volume of sludge processed in this system before dewatering.

The operator shall determine and record the volume of sludge processed once every calendar month.

The operator shall calibrate the flow meter per the manufacturer's specifications.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 5, System 2]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

- S1.3 The operator shall limit the unloading rate to no more than 1,520,833 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials unloaded, in gallons, by using certified truck scale records to determine the pounds of material unloaded, and a measurement of the specific gravity or API gravity of the material unloaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 3]

- S1.4 The operator shall limit the unloading rate to no more than 6,387,500 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials unloaded, in gallons, by using certified truck scale records to determine the pounds of material unloaded, and a measurement of the specific gravity or API gravity of the material unloaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 1]

- S1.5 The operator shall limit the unloading rate to no more than 3,832,500 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials unloaded, in gallons, by using certified truck scale records to determine the pounds of material unloaded, and a measurement of the specific gravity or API gravity of the material unloaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 2]

- S1.6 The operator shall limit the loading rate to no more than 243,334 gallon(s) in any one calendar month.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, the loading rate shall be defined as the loading rate of Naphtha.

The operator shall monitor the throughput of materials loaded, in gallons, by using certified truck scale records to determine the pounds of material loaded, and a measurement of the specific gravity or API gravity of the material loaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 5]

- S1.7 The operator shall limit the loading rate to no more than 3,193,750 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials loaded, in gallons, by using certified truck scale records to determine the pounds of material loaded, and a measurement of the specific gravity or API gravity of the material loaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 4]

- S1.8 The operator shall limit the loading rate to no more than 6,083,333 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials loaded, in gallons, by using certified truck scale records to determine the pounds of material loaded, and a measurement of the specific gravity or API gravity of the material loaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 6]

- S1.9 The operator shall limit the loading rate to no more than 100,000 gallon(s) in any one calendar month.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, the loading rate shall be defined as the loading rate of RCRA Fuel.

The operator shall monitor the throughput of materials loaded, in gallons, by using certified truck scale records to determine the pounds of material loaded, and a measurement of the specific gravity or API gravity of the material loaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 9]

- S1.10 The operator shall limit the unloading rate to no more than 100,000 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials unloaded, in gallons, by using certified truck scale records to determine the pounds of material unloaded, and a measurement of the specific gravity or API gravity of the material unloaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 9]

- S1.11 The operator shall limit the material processed to no more than 9,060 ton(s) in any one calendar month.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 11, System 1]

- S1.12 The operator shall limit the throughput to no more than 8,500,000 gallon(s) in any one calendar month.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, throughput shall be defined as the volume of wastewater, in gallons, discharged to the LACSD sewer connection (D468).

To comply with this condition, the operator shall install and maintain a non-resettable totalizing flow meter to accurately indicate the total volume of wastewater discharged to the LACSD sewer connection (D468).

The operator shall determine and record the volume of wastewater discharged to the LACSD sewer connection once every calendar month.

The operator shall calibrate the flow meter per the manufacturer's specifications.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 5, System 1]

- S1.13 The operator shall limit the loading rate to no more than 25,000 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials loaded, in gallons, by using certified truck scale records to determine the pounds of material loaded, and a measurement of the specific gravity or API gravity of the material loaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Systems subject to this condition : Process 7, System 10]

- S1.14 The operator shall limit the unloading rate to no more than 100,000 gallon(s) in any one calendar month.

The operator shall monitor the throughput of materials unloaded, in gallons, by using certified truck scale records to determine the pounds of material unloaded, and a measurement of the specific gravity or API gravity of the material unloaded.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 7, System 11]

S13.1 All devices under this system are subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
PM	40CFR60, SUBPART	UU
PM	40CFR63, SUBPART	AAAAAAA

[40CFR 60 Subpart UU, 8-5-1983; 40CFR 63 Subpart AAAAAAA, 12-2-2009]

[Systems subject to this condition : Process 11, System 1]

S13.3 All devices under this system are subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	462

[RULE 462, 5-14-1999]

[Systems subject to this condition : Process 7, System 5 , 9; Process 9, System 9]

S15.1 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases from any process vent of this system shall be vented to the Vapor Recovery System - Process Waste Gas (Process 9, System 3).

This process/system shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 1, System 1, 2, 3; Process 2, System 1; Process 3, System 1; Process 4, System 1]

- S15.2 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases from this system shall be vented to the Afterburners (Process 9, Systems 7 & 13).

This process/system shall not be operated unless at least one of the afterburners is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 1, 2, 3, 4, 5, 8, 9, 11, 12; Process 11, System 4]

- S15.3 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be vented to the Vapor Recovery System - North Tank Farms (Process 9, System 1).

This process/system shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 6, System 5, 6, 7]

- S15.4 The vent gases from all affected devices of this process/system shall be vented as follows:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

All vent gases under normal operating conditions shall be vented to the Vapor Recovery System - South Tank Farms (Process 9, System 2).

This process/system shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 6, System 1 , 2]

S15.5 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be vented to the Vapor Recovery System - RCRA Fuel & Naphtha Tanks (Process 9, System 5).

This process/system shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 6, System 4]

S15.6 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be vented to the Vapor Recovery System - Wastewater Treatment (Process 9, System 8).

This process/system shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 5, System 1]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

S15.7 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be vented to the Caustic Scrubber Serving Asphalt Blowing Stills (Process 9, System 4).

This process/system shall not be operated unless the above caustic scrubber is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 11, System 1]

S15.8 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be vented to the Vapor Recovery System - Asphalt Flux Loading Rack No. 7 (Process 9, System 11).

This process/system shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 7, System 8 , 10]

S15.9 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be vented to the Vapor Recovery System - Front Loading Racks (Process 9, System 9).

This process/system shall not be operated unless the above vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 7, System 4 , 5 , 6 , 7 , 9]

- S18.1 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Asphalt Blowing (Process: 11, System: 1)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Systems subject to this condition : Process 9, System 4]

- S18.2 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Used Oil Dehydration (Process: 1, System: 1)

Vacuum Distillation Unit No. 1 (Process: 1, System: 2)

Vacuum Distillation Unit No. 2 (Process: 1, System: 3)

PRM Stripper (Process: 2, System: 1)

Naphtha Splitter Unit (Process: 3, System: 1)

Ethylene Glycol Distillation (Process: 4, System: 1)

Waste Water Treatment (Process: 5, System: 1)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 9, System 3]

- S18.3 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Asphalt Flux Loading - Rack No. 7 (Process: 7, System: 8)

Used Glycol Loading (Process: 7, System: 10)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 11]

- S18.4 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Fixed Roof Storage Tanks : Southwest Tank Farm (Process: 6, System: 1)

Fixed Roof Storage Tanks - Wastewater Tanks (Process: 6, System: 2)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 2]

- S18.5 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Fixed Roof Storage Tanks : RCRA Fuel & Naphtha Tanks (Process: 6, System: 4)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 9, System 5]

S18.6 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Fixed Roof Storage Tanks : Product Tanks (Process: 6, System: 5)

Fixed Roof Storage Tanks : A-Series Tanks (Process: 6, System: 6)

Fixed Roof Storage Tanks : N-Series Tanks (Process: 6, System: 7)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 1]

S18.7 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Wastewater Treatment (Process: 5, System: 1)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 8]

S18.8 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Fuel Oil Cutter Loading (Process: 7, System: 4)

Naphtha Loading (Process: 7, System: 5)

Marine Diesel Oil Loading (Process: 7, System: 6)

Asphalt Flux Loading - Rack No. 4 (Process: 7, System: 7)

RCRA Fuel Loading and Unloading (Process: 7, System: 9)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 9]

S18.9 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Sludge Dewatering (Process: 5, System: 2)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Systems subject to this condition : Process 9, System 12]

S42.1 The operator shall not use this system for Rule 1149 compliance:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	1149

[RULE 1149, 5-2-2008]

[Systems subject to this condition : Process 11, System 3]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

DEVICE CONDITIONS

C. Throughput or Operating Parameter Limits

C1.13 The operator shall limit the throughput to no more than 200,000 lb(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as the total weight of materials transferred to the silo.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D557]

C1.14 The operator shall limit the operation to no more than 30 day(s) in any one year.

This condition shall no longer apply once the scrubber C300 is constructed and is in full use..

[RULE 204, 10-8-1993]

[Devices subject to this condition : C142]

C4.1 The operator shall limit the residence time to no less than 0.5 seconds.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C142]

C8.5 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, is not less than 1400 Deg F.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

The temperature limit is the average over 15 minutes.

To comply with this condition, the operator shall install and maintain a(n) temperature reading device to accurately indicate the temperature in the combustion chamber and at least 1second downstream of the burner.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C142]

- C8.6 The operator shall use this equipment in such a manner that the flow rate being monitored, as indicated below, is not less than 400 gpm.

The flow rate limit is the average over 15 minutes.

To comply with this condition, the operator shall install and maintain a(n) flow meter to accurately indicate the flow rate of the recirculating caustic solution.

The flow rate measured shall be the scrubber re-circulation flow rate.

The operator shall also install and maintain a device to continuously record the parameter being measured.

The continuous monitoring system shall include visual and audio alarms.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 407, 4-2-1982; RULE 431.1, 6-12-1998]

[Devices subject to this condition : C300]

- C8.10 The operator shall use this equipment in such a manner that the pH being monitored, as indicated below, is not less than 7.8 of the pH scale.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

The pH limit is the average over 15 minutes.

To comply with this condition, the operator shall install and maintain a (n) pH meter to accurately indicate the pH of the scrubbing solution.

The operator shall also install and maintain a device to continuously record the parameter being measured.

The continuous monitoring system shall include visual and audio alarms.

The operator shall calibrate the instrument used to measure the pH per the manufacturer's specifications.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 204, 10-8-1993; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C300]

D. Monitoring/Testing Requirements

D12.5 The operator shall install and maintain a(n) flow meter to accurately indicate the flow rate being supplied to the combustion chamber.

The operator shall also install and maintain a device to continuously record the parameter being measured.

For the purpose of this condition, the flow rate of natural gas supplied to the combustion chamber shall be indicated and recorded

[RULE 2012, 5-6-2005]

[Devices subject to this condition : C142]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D12.7 The operator shall install and maintain a(n) stack flow monitor to accurately indicate the flow rate from the afterburner stack to provide continuous and cumulative actual flow volume.

When valid exhaust flow rate of an afterburner is not obtained from the stack flow monitor, substituted data for the exhaust flow rate for the afterburner shall be determined by using procedures in the certification letter for the continuous exhaust flow monitor and the missing data procedures applicable to flow as set forth in Rule 2012 Appendix A, Chapter 3, Section K(2).

[RULE 2012, 5-6-2005]

[Devices subject to this condition : C142]

D28.1 The operator shall conduct source test(s) in accordance with the following specifications:

The test shall be conducted at least once every three years. For the purposes of determining intervals indicated, the cumulative days between testing during which afterburner C142, afterburner C281 or their associated scrubbers are under repair, maintenance, or construction shall not be counted. The operator shall keep sufficient operating records to demonstrate compliance with the testing intervals and dates counted/not counted..

The test shall be conducted to determine the control efficiency of this equipment for destruction of VOCs.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C142]

D29.4 The operator shall conduct source test(s) for the pollutant(s) identified below.

Pollutant(s) to be tested	Required Test Method(s)	Averaging Time	Test Location

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

NOX emissions	Approved District method	District-approved averaging time	Outlet
---------------	--------------------------	-------------------------------------	--------

The test(s) of NOX emissions shall be conducted to establish a NOX concentration limit at the actual stack condition for NOX mass emission calculations pursuant to Rule 2012, Appendix A , Chapter 3, Section (D)(2)(a) (iii).

A source test protocol shall be submitted to the District no later than 30 days from the date of this permit unless otherwise approved in writing by the District. The test prctocol shall be approved in writing by the District before the test commences.

The source test(s) shall be conducted no later than 90 days from the date of this permit unless otherwise approved in writing by the District.

A written notice of the source test(s) shall be submitted to the District at least 14 days prior to source testing date so that an observer from the District may be present.

[RULE 2012, 5-6-2005; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C142]

D82.1 The operator shall install and maintain a CEMS to measure the following parameters:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

The CEMS shall be installed and maintained to measure exhaust gas SOX emissions.

The exhaust gas SOX emissions shall be in compliance with the District Rule 431.1 requirements.

The CEMS used for monitoring the exhaust gas SOX emissions shall comply with the District Rule 431.1 Attachment A requirements.

The equipment shall be operated in compliance with the applicable District Rule 431.1 Monitoring, Reporting and Recordkeeping Requirements.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 431.1, 6-12-1998]

[Devices subject to this condition : C300]

D90.5 The operator shall periodically monitor the VOC concentration at outlet of the last carbon adsorber according to the following specifications:

The operator shall monitor once every eight hours whenever the vacuum blower is not running.

The operator shall use EPA Reference Method 21 to monitor the parameter.

The operator shall calibrate the instrument used to monitor the parameter in ppmv methane.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C303, C304, C308, C311, C312, C313]

D90.6 The operator shall periodically monitor the the operation of the vacuum blower according to the following specifications:

The operator shall monitor once every day.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D140, D195, D196, D197, D198, D284, D287, D289]

D90.7 The operator shall periodically monitor the vacuum level at inlet of the carbon adsorber(s) according to the following specifications:

The operator shall monitor once every day.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C303, C304, C308, C311, C312, C313]

D90.14 The operator shall periodically monitor the the operation of the vacuum blower according to the following specifications:

The operator shall monitor once every day when the centrifuge [D64] is operating.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D324]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a semi-annual basis, at least, unless the equipment did not operate during the entire semi-annual period. The routine semi-annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C142, D557]

E. Equipment Operation/Construction Requirements

E17.1 The operator shall not use more than 2 of the following items simultaneously:

Device ID: C565 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C566 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C567 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C568 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C569 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C570 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C571 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C572 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C573 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C574 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C575 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C576 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C577 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C578 [Vapor Return Line, Vacuum Truck Pump Exhaust]

Device ID: C579 [Vapor Return Line, Vacuum Truck Pump Exhaust]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[RULE 204, 10-8-1993]

[Devices subject to this condition : C565, C566, C567, C568, C569, C570, C571, C572, C573, C574, C575, C576, C577, C578, C579]

- E71.2 The operator shall only operate this equipment to process waste gas when the natural gas burner is in operation.

[RULE 204, 10-8-1993]

[Devices subject to this condition : C142]

- E71.3 The operator shall only operate this equipment for standby once the new afterburner C281 is commenced operation.

[RULE 204, 10-8-1993]

[Devices subject to this condition : C142]

- E128.1 The operator shall keep all spent carbon in a tightly covered container which shall remain closed except when it is being transferred into or out of the container.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C303, C304, C308, C311, C312, C313]

- E153.1 The operator shall change over the carbon in the adsorber whenever breakthrough occurs.

For the purpose of this condition, breakthrough occurs when the hydrocarbon monitor reading indicates a concentration of 500 ppmv at the outlet of the last carbon.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C303, C304, C308, C311, C312, C313]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

E184.1 The operator shall thoroughly clean the filters in the filter vents immediately after each load of material is received.

[**RULE 204, 10-8-1993**]

[Devices subject to this condition : D557]

E448.1 The operator shall comply with the following requirements:

The operator shall operate only one afterburner (Device Nos. C-142 or C-281) at any one time except during afterburner switchover. Switchover time (including but not limited to emergency, maintenance or testing) shall not exceed 6 hours per day and 12 times per year.

These limits shall not apply during the initial start-up period of the SO_x scrubbers (Device Nos. C-300 and C-301) not to exceed 168 hours during a 30 day period or for curing of new refractory when no vapors are processed or as otherwise approved by the AQMD.

Switchover period shall be defined as switching from one afterburner to another and back to the original afterburner.

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002**]

[Devices subject to this condition : C142, C300]

E448.2 The operator shall comply with the following requirements:

The concentration by volume, at the exhaust stack of the scrubbers (dry basis, zero percent O₂), of sulfur compounds in ppmv as SO₂ shall not exceed 12 ppmv averaged over 24 hours.

The mass, at the exhaust stack of the scrubbers, of sulfur compounds as SO₂ shall not exceed 6.7 pounds per day.

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002**]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C300]

E448.3 The operator shall comply with the following requirements:

When the afterburner C281 or the scrubber C301 are required to be shut down for maintenance or repairs prior to installation and testing of scrubber C300, afterburner C142 shall only be operated when it is vented to storage tanks and loading/unloading racks vapor recovery. In this case, the valves that control gases from the process lines including knock out pots D226 & D241 shall be closed and locked and no gases from the process lines shall be vented to afterburner C142.

These control valves shall also remain closed and locked until scrubber C300 is operational.

The afterburner C142 shall be operated in accordance with the startup procedures approved by the SCAQMD to prevent the release of Volatile Organic Compounds (VOC) emissions.

[RULE 204, 10-8-1993]

[Devices subject to this condition : C142]

E448.4 The operator shall comply with the following requirements:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

The afterburner C142 shall be vented to scrubber C300 whenever in operation, except when all of the following criteria are met:

1. The scrubber C300 is still under construction and full operation has not commenced; and
2. The valves controlling venting from the knock out pots D226 & D241 are closed and blinded; and
3. The afterburner C281 or scrubber C301 are not operable; and
4. The AQMD shall be notified within 10 days prior to a scheduled shutdown of afterburner C281 or scrubber C301. If 10 days cannot be provided, the AQMD shall be notified as soon as practicable.

[RULE 204, 10-8-1993]

[Devices subject to this condition : C142]

E448.6 The operator shall comply with the following requirements:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

In the event of a natural gas curtailment or shortage, if the facility afterburners temperature cannot be maintained at 1400 deg F, the operator shall take the following steps to ensure compliance with all the SCAQMD Rules and Regulations and Permit Conditions:

- 1) Close all the inlet valves to the afterburners C281 and C142.
- 2) Stop receiving any waste material to the facility.
- 3) Stop shipping any product from the facility.
- 4) Shutdown all the heating sources, i.e., boilers and heaters.
- 5) Shutdown all the process feed and transfer pumps.
- 6) Prepare a report to record all the above activities.

[RULE 480, 10-7-1977]

[Devices subject to this condition : C142]

H. Applicable Rules

H23.2 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	464

[RULE 464, 12-7-1990]

[Devices subject to this condition : D52, D64, D418, D580]

H23.12 This equipment is subject to the applicable requirements of the following rules or regulations:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Contaminant	Rule	Rule/Subpart
Visible Emissions	District Rule	1155

[RULE 1155, 5-2-2014]

[Devices subject to this condition : D557]

H116.4 The operator shall maintain this equipment to achieve a minimum control efficiency of 98 percent for VOCs in order to comply with District rules and regulations whenever any of the equipment it vents is in operation.

[**RULE 1303(a)(1)-BACT, 5-10-1996**; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C142]

H116.5 The operator shall , upon completion of construction of a sulfur scrubber and the expiration of the initial start-up period described in Condition E448.1, vent this equipment to a sulfur scrubber that has been issued a permit by the District which is in full operation in order to comply with District Rule 431.1 whenever this equipment is in operation.

[**RULE 431.1, 6-12-1998**]

[Devices subject to this condition : C142]

H116.6 The operator shall determine the VOC concentration on a monthly basis to demonstrate compliance with the VOC limit at the exhaust of the control equipment in order to comply with offsets requirements whenever the afterburners are in operation. If compliance is demonstrated for three consecutive months, then grab sampling and analysis shall be conducted on a quarterly basis. If the quarterly analysis shows non-compliance, then the grab sampling schedule shall be reverted to monthly basis.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C142]

I. Administrative

- I298.1 This equipment shall not be operated unless the facility holds 12571 pounds of NOx RTCs in its allocation account to offset the annual emissions increase for the first year of operation. The RTCs held to satisfy the first year of operation portion of this condition may be transferred only after one year from the initial start of operation. In addition, this equipment shall not be operated unless the operator demonstrates to the Executive Officer that, at the commencement of each compliance year after the start of operation, the facility holds 12571 pounds of NOx RTCs valid during that compliance year. RTCs held to satisfy the compliance year portion of this condition may be transferred only after the compliance year for which the RTCs are held. If the initial or annual hold amount is partially satisfied by holding RTCs that expire midway through the hold period, those RTCs may be transferred upon their respective expiration dates. This hold amount is in addition to any other amount of RTCs required to be held under other condition(s) stated in this permit.

[RULE 2005, 6-3-2011]

[Devices subject to this condition : C142]

K. Record Keeping/Reporting

- K67.10 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

VOC monitoring of the carbon adsorber(s).

Vacuum level monitoring of the carbon adsorber(s).

Replacement of the carbon adsorber(s).

Records shall be kept and maintained for at least five years, and shall be made available to the Executive Officer or his authorized representative upon request.

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C303, C304, C308, C311, C312, C313]

K67.11 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Monitoring, maintenance and repair of the vacuum blower.

Records shall be kept and maintained for at least five years, and shall be made available to the Executive Officer or his authorized representative upon request.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D140, D195, D196, D197, D198, D284, D287, D289, D324]

K67.18 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

All materials stored during each year.

The date(s) any materials are received.

The total weight of materials received.

Records shall be kept and maintained for at least five years, and shall be made available to the Executive Officer or his authorized representative upon request.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D557]

K171.1 The operator shall provide to the District the following items:

FACILITY PERMIT TO OPERATE DEMENNO/KERDOON

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Final drawings and/or specifications of the equipment installed/constructed/modified, including but not limited to PFD, P&ID and revisions/updates, shall be submitted to the SCAQMD within 60 days after completion of the project.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D64, C142, C300, D557, D559, D560, D561, D580, D582, D583, D586]