

Bay Area Air Quality Management District

939 Ellis Street
San Francisco, CA 94109
(415) 771-6000

Proposed

MAJOR FACILITY REVIEW PERMIT

Issued To:

Valero Benicia Asphalt Plant
Facility #B3193

Facility Address:

3001 Park Road
Benicia, CA 90748-1257

Mailing Address:

3001 Park Road
Benicia, CA 90748-1257

Responsible Official

John U. Roach
Refinery Manager
(707) 745-7773

Facility Contact

Clark Hopper,
Environmental Engineering Manager
(707) 745-7385

Type of Facility: Asphalt Refinery
Primary SIC: 2911
Product: Asphalt

BAAQMD Permit Division Contact:
Brenda Cabral

ISSUED BY THE BAY AREA AIR QUALITY MANAGEMENT DISTRICT

Ellen Garvey, Air Pollution Control Officer

Date

TABLE OF CONTENTS

I.	STANDARD CONDITIONS	3
II.	EQUIPMENT	7
III.	GENERALLY APPLICABLE REQUIREMENTS.....	18
IV.	SOURCE-SPECIFIC APPLICABLE REQUIREMENTS.....	20
V.	SCHEDULE OF COMPLIANCE.....	119
VI.	PERMIT CONDITIONS.....	120
VII.	APPLICABLE LIMITS & COMPLIANCE MONITORING REQUIREMENTS.....	148
VIII.	TEST METHODS	202
IX.	PERMIT SHIELD.....	205
X.	GLOSSARY	208
XI.	APPLICABLE STATE IMPLEMENTATION PLAN.....	213

I. STANDARD CONDITIONS

A. Administrative Requirements

The permit holder shall comply with all applicable requirements in the following regulations:

- BAAQMD Regulation 1 - General Provisions and Definitions
(as amended by the District Board on 5/2/01);
- SIP Regulation 1 - General Provisions and Definitions
(as approved by EPA through 8/27/99);
- BAAQMD Regulation 2, Rule 1 - Permits, General Requirements
(as amended by the District Board on 8/1/01);
- SIP Regulation 2, Rule 1 - Permits, General Requirements
(as approved by EPA through 2/25/99);
- BAAQMD Regulation 2, Rule 2 - Permits, New Source Review
(as amended by the District Board on 5/17/00);
- SIP Regulation 2, Rule 2 - Permits, New Source Review and Prevention of Significant Deterioration
(as approved by EPA through 2/25/99);
- BAAQMD Regulation 2, Rule 4 - Permits, Emissions Banking
(as amended by the District Board on 5/17/00);
- SIP Regulation 2, Rule 4 - Permits, Emissions Banking
(as approved by EPA through 2/25/99); and
- BAAQMD Regulation 2, Rule 6 - Permits, Major Facility Review
(as amended by the District Board on 5/2/01).

B. Conditions to Implement Regulation 2, Rule 6, Major Facility Review

1. This Major Facility Review Permit was issued on [] and expires on [when issued, enter 5th anniversary of issue date]. The permit holder shall submit a complete application for renewal of this Major Facility Review Permit no later than [when issued, enter date 6 months prior to permit expiration date] and no earlier than [when issued, enter date 12 months prior to expiration date]. **If a complete application for renewal has not been submitted in accordance with this deadline, the facility may not operate after [when issued, enter 5th anniversary of issue date].** (Regulation 2-6-307, 404.2, & 409.6; MOP Volume II, Part 3, §4.2)
2. The permit holder shall comply with all conditions of this permit. The permit consists of this document and all appendices. Any non-compliance with the terms and conditions of this permit will constitute a violation of the law and will be grounds for enforcement action; permit termination, revocation and re-issuance, or modification; or denial of a permit renewal application. (Regulation 2-6-307; MOP Volume II, Part 3, §4.11)
3. In the event any enforcement action is brought as a result of a violation of any term or condition of this permit, the fact that it would have been necessary for the permittee to halt or reduce the permitted activity in order to maintain compliance with such term or condition shall not be a defense to such enforcement action. (MOP Volume II, Part 3, §4.11)

I. Standard Conditions

4. This permit may be modified, revoked, reopened and reissued, or terminated for cause. (Regulation 2-6-307, 409.8, 415; MOP Volume II, Part 3, §4.11)
5. The filing of a request by the facility for a permit modification, revocation and re-issuance, or termination, or the filing of a notification of planned changes or anticipated non-compliance does not stay the applicability of any permit condition. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
6. This permit does not convey any property rights of any sort, or any exclusive privilege. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
7. The permit holder shall supply within 30 days any information that the District requests in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. (Regulation 1-441, Regulation 2-6-409.4 & 501; MOP Volume II, Part 3, §4.11)
8. Any records required to be maintained pursuant to this permit which the permittee considers to contain proprietary or trade secret information shall be prominently designated as such. Copies of any such proprietary or trade secret information which are provided to the District shall be maintained by the District in a locked confidential file, provided, however, that requests from the public for the review of any such information shall be handled in accordance with the District's procedures set forth in Section 11 of the District's Administrative Code. (Regulation 2-6-419; MOP Volume II, Part 3, §4.11)
9. Proprietary or trade secret information provided to EPA will be subject to the requirements of 40 CFR Part 2, Subpart B - Public Information, Confidentiality of Business Information. (40 CFR Part 2)
10. The emissions inventory submitted with the application for this Major Facility Review Permit is an estimate of actual emissions or the potential to emit for the time period stated and is included only as one means of determining applicable requirements for emission sources. It does not establish, or constitute a basis for establishing, any new emission limitations. (MOP Volume II, Part 3, §4.11)
11. The responsible official shall certify all documents submitted by the facility pursuant to the major facility review permit. The certification shall state that based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. The certifications shall be signed by a responsible official for the facility. (MOP Volume II, Part 3, §4.11)

C. Requirement to Pay Fees

The permit holder shall pay annual fees in accordance with District Regulation 3, including Schedule P. (Regulation 2-6-402 & 409.13, Regulation 3; MOP Volume II, Part 3, §4.12)

D. Inspection and Entry

Access to Facility: The permit holder shall provide reasonable access to the facility and equipment which is subject to this permit to the APCO and/or to his or her designee. (Regulation 1-440, Regulation 2-6-409.3; MOP Volume II, Part 3, §4.14)

I. Standard Conditions

E. Records

1. The permit holder must provide any information, records, and reports requested or specified by the APCO. (Regulation 1-441, Regulation 2-6-409.4)
2. Notwithstanding the specific wording in any requirement, all records for federally enforceable requirements shall be maintained for at least five years from the date of creation of the record. (Regulation 2-6-501, Regulation 3; MOP Volume II, Part 3, §4.7)

F. Monitoring Reports

Reports of all required monitoring must be submitted to the District at least once every six months, except where an applicable requirement specifies more frequent reporting. The first reporting period for this permit shall be [date of issuance] to [six months later]. The report shall be submitted by [one month after end of reporting period]. Subsequent reports shall be for the following periods: [____ 1st through ____ 30th or 31st] and [____ 1st through ____ 30th or 31st], and are due on the last day of the month after the end of the reporting period. All instances of non-compliance shall be clearly identified in these reports. The reports shall be certified by the responsible official as true, accurate, and complete. In addition, all instances of non-compliance with the permit shall be reported in writing to the District's Compliance and Enforcement Division within 10 calendar days of the discovery of the incident. Within 30 calendar days of the discovery of any incident of non-compliance, the facility shall submit a written report including the probable cause of non-compliance and any corrective or preventative actions. The reports shall be sent to the following address:

Director of Compliance and Enforcement
Bay Area Air Quality Management District
939 Ellis Street
San Francisco, CA 94109
Attn: Title V Reports

(Regulation 2-6-502, Regulation 3; MOP Volume II, Part 3, §4.7)

G. Compliance Certification

Compliance certifications shall be submitted annually by the responsible official of this facility to the Bay Area Air Quality Management District and to the Environmental Protection Agency. The certification period will be ____ 1st to ____ 30th or 31st. The certification shall be submitted by ____ 30th or 31st of each year. The certification must list each applicable requirement, the compliance status, whether compliance was continuous or intermittent, the method used to determine compliance, and any other specific information required by the permit. The permit holder may satisfy this requirement through submittal of District-generated Compliance Certification forms. The certification should be directed to the District's Compliance and Enforcement Division at the address above, and a copy of the certification shall be sent to the Environmental Protection Agency at the following address:

Director of the Air Division
USEPA, Region IX
75 Haweighthorne Street
San Francisco, CA 94105

I. Standard Conditions

Attention: Air-3

(MOP Volume II, Part 3, §4.5 and 4.15)

H. Emergency Provisions

1. The permit holder may seek relief from enforcement action in the event of a breakdown, as defined by Regulation 1-208 of the District's Rules and Regulations, by following the procedures contained in Regulations 1-431 and 1-432. The District will thereafter determine whether breakdown relief will be granted in accordance with Regulation 1-433. (MOP Volume II, Part 3, §4.8)
2. The permit holder may seek relief from enforcement action for a violation of any of the terms and conditions of this permit by applying to the District's Hearing Board for a variance pursuant to Health and Safety Code Section 42350. The Hearing Board will determine after notice and hearing whether variance relief should be granted in accordance with the procedures and standards set forth in Health and Safety Code Section 42350 et seq. (MOP Volume II, Part 3, §4.8)
3. The granting by the District of breakdown relief or the issuance by the Hearing Board of a variance will not provide relief from federal enforcement. (MOP Volume II, Part 3, §4.8)

I. Severability

In the event that any provision of this permit is invalidated by a court or tribunal of competent jurisdiction, or by the Administrator of the EPA, all remaining portions of the permit shall remain in full force and effect. (Regulation 2-6-409.5; MOP Volume II, Part 3, §4.10)

J. Miscellaneous Conditions

1. The maximum capacity for each source as shown in Table II-A is the maximum allowable capacity. Exceedance of the maximum allowable capacity for any source is a violation of Regulation 2, Rule 1, Section 301. (Regulation 2-1-301)

II. EQUIPMENT

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301.

S#	Description	Make or Type	Model	Capacity
1	Crude Storage Tank 1A	External Floating Roof		3,419,000 gal
2	Crude Storage Tank 1B	External Floating Roof		3,419,000 gal
3	Gas Oil Storage Tank, TK-1C	Fixed Roof		3,419,000 gal
4	Crude Oil Storage Tank, TK-10A	External Floating Roof		1,382,000 gal
5	Asphalt Storage Tank, TK-2A	Fixed Roof		3,415,000 gal
6	Asphalt Storage Tank, TK-2B	Fixed Roof		3,415,000 gal
7	Asphalt Storage Tank, TK-3	Fixed Roof		1,050,000 gal
8	Asphalt Storage Tank, TK-4	Fixed Roof		1,050,000 gal
9	Naphtha Storage Tank, TK-7	Internal Floating Roof		571,200 gal
12	Tank #6 – Wastewater Tank	Fixed Roof		571,200 gal
13	Tank 8 – Kerosene Tank	Fixed Roof		88,000 gal
14	Loading Racks - Naphtha			1 pump, 2 nozzles
15	Loading Racks - Gas Oil			1 pump, 2 nozzles
16	Loading Racks - Kerosene or Distillate Oil			1 pump, 2 nozzles
17	Loading Racks - Asphalt			3 pumps, 4 nozzles
18	Crude Unit including vacuum tower			18,000 barrels/day
19	Vacuum Heater (natural gas, refinery fuel gas)			33 MMBtu/hr
20	Steam Boiler (natural gas)			14.7 MMBtu/hr
21	Steam Boiler H-2 B (natural gas)			14.7 MMBtu/hr
23	Crude Storage Tank 10B	External Floating Roof		1,382,000 gal
24	Hot Oil Heater, H-3 (natural gas)			9 MMBtu/hr
25	Effluent Water Feed Tank, TK-11A	Fixed Roof		88,200 gal
26	Skimmed Oil Tank, TK-13	Fixed Roof		3800 gal
27	Recovered Oil Tank, TK-12A	Fixed Roof		1260 gal
28	Effluent Water Feed Tank, TK-11B	Fixed Roof		88,000 gal
29	Naphtha Merox Treater, 950 Bbls/Day, UOP			950 bbls/day

II. Equipment

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301.

S#	Description	Make or Type	Model	Capacity
30	Marine Loading Dock (Report ONLY loading ONTO vessels)			2 pumps, 2 nozzles
31	Rail Car Asphalt Loading Rack, five Spots			1 nozzle
32	LGO Stripper, Tower (Column) 301			
34	Tank Heater, H-5 (natural gas)			5.9 MMbtu/hr
37	Rubberized Asphalt Sales Tank, TK-54	Fixed Roof		100,000 gal
38	Rubberized Asphalt Sales Tank, TK-55	Fixed Roof		100,000 gal
39	Lube Oil Tank, Tk-503	CE		18,900 gal
40	Latex Storage Tank, Tk-504	CE		16,800 gal
41	Wemco Hydrocleaner			5,000 bbl/day
51	Sales Tank – Asphalt Liquid, Tank 506	Fixed Roof		152,880 gal
52	Sales Tank – Asphalt Liquid	Fixed Roof		152,880 gal
53	Sales Tank – Asphalt Liquid	Fixed Roof		152,880 gal
54	Asphalt Loading Rack			3 pumps, 4 nozzles
59	Tank #5 – Gas oil Fixed Roof Storage Tank	Fixed Roof		1,050,000 gal
60	Asphalt Tank #505	Fixed Roof		15,000 gal
61	Asphalt Tank 30A	Fixed Roof		995,400 gal
62	Asphalt Tank 30B	Fixed Roof		995,400 gal
63	Tank 31 KERO/LVGO/HVGO/Asphalt Tank	Fixed Roof		1,218,000 gal
65	Asphalt Tank, Tank 32	Fixed Roof		6,920,000 gal
66	Oil Water Separator			210 gal/min
67	Recovered Oil Tank, TK-12B	Fixed Roof		5875 gals
68	Emergency Diesel-powered Firewater Pump (P-4645)			215 hp

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
A1	Koch Mist Eliminator	S5-S8, S41, S59, S65	None	None	None
A2	Mist Eliminator (F-9)	S17	None	None	None
A3	Mist Eliminator F-10	S3, S5-S8, S13, S25, S37, S38, S41, S51- S54, S59, S60-S63, S65, S66	None	None	None
A4	Loading Rack Thermal Oxidizer (6.5 MMbtu/hr)	S14, S15, S17, A2	BAAQMD Condition #1240, Part I.14	temperature	Emissions of NMHC < 49.1 tons per year excluding marine emissions
		S14, S15, S17	BAAQMD 8-6-301	Temperature	0.17 pounds organic compounds per 1,000 gallons
		S14	BAAQMD Condition #1240, Part II.60	Temperature	98.5% destruction
		S15	BAAQMD Condition #1240, Part II.63	Temperature	98.5% destruction
		S17	BAAQMD Condition #1240, Part II.68	Temperature	98.5% destruction

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
A6	Mist Eliminator	S31	None	None	None
A11	Carbon Adsorption Drum	S26	40 CFR 61.349(a)(1)(i)	None	95% control of VOC or 98% control of benzene
A12	Carbon Adsorption Drum	S27	40 CFR 61.349(a)(1)(i)	None	95% control of VOC or 98% control of benzene
A20	Mist Eliminator F500	S3, S13, S37, S38, S51-S53, S54, S60-S63, S65, S66	None	None	None
A21	Carbon Canisters (2)	S26, S27	40 CFR 61.349(a)(1)(i)	None	95% control of VOC or 98% control of benzene
A22	Carbon Canisters (2)	S26, S27	40 CFR 61.349(a)(1)(i)	None	95% control of VOC or 98% control of benzene
A23	Mist Eliminator	S27	None	None	None
A31	Thermal Oxidizer (3.5 MMbtu/hr)	S3, S5-S8, S12, S13, S25, S31, S37, S38, S41, S51-S54, S59, S60-S63, S65, S66, S67, A1, A3, A6, A20	BAAQMD Condition #1240, Part I.14	temperature	Emissions of NMHC < 49.1 tons per year excluding marine emissions

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
A31	Thermal Oxidizer	S3	BAAQMD Condition #1240, Part II.43	Temperature	98.5% destruction
		S5-S8, S37, S38	BAAQMD Condition #1240, Part II.55	Temperature	98.5% destruction
		S5-S8, S37, S38, S51-S53, S60	40 CFR 60.472(c)	temperature	0 percent opacity except for one consecutive 15-min period in any 24-hr period for cleaning
		S12	40 CFR 61.349(a) (2)(i)(A)	temperature	95% control of inlet VOC
		S13, S59, S63	BAAQMD 8-5-311.3	Temperature	95% control of VOC
		S13, S59, S63	40 CFR 60.112b(a) (3)(ii)	Temperature	95% control of inlet VOC
		S13	BAAQMD Condition #1240, Part II.32a	Temperature	98.5% control of inlet VOC by weight
		S59	BAAQMD Condition #1240, Part II.32b	Temperature	98.5% control of inlet VOC by weight
		S63	BAAQMD Condition #1240, Part II.32c	Temperature	98.5% control of inlet VOC by weight

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
A31	Thermal Oxidizer	S25	40 CFR 61.349(a) (2)(i)(A)	temperature	95% control of inlet VOC
		S31	BAAQMD 8-6-301	Temperature	0.17 pounds organic compounds per 1,000 gallons
		S31	BAAQMD Condition 1240, Part II.69	Temperature	98.5% destruction
		S41	BAAQMD 8-8-307		70% combined collection and destruction efficiency
		S41	40 CFR 61.349(a) (2)(i)(A)	temperature	95% control of inlet VOC
		S41			
		S51-S53, S60	BAAQMD Condition #1240, Part II.56	Temperature	98.5% destruction
		S51-S53, S60	40 CFR 60.472(c)	Temperature	0 percent opacity except for one consecutive 15-min period in any 24-hr period for cleaning

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
A31	Thermal Oxidizer	S54	BAAQMD 8-6-301	Temperature	0.17 pounds organic compounds per 1,000 gallons
		S54	BAAQMD Condition #1240, Part II.70	Temperature	98.5% destruction
		S61, S62	40 CFR 60.472(c)	temperature	0 percent opacity except for one consecutive 15-min period in any 24-hr period for cleaning
		S65	BAAQMD Condition #1240, Part II.56	temperature	98.5% destruction
		S65	40 CFR 60.472(c)	temperature	0 percent opacity except for one consecutive 15-min period in any 24-hr period for cleaning
		S66	40 CFR 61.349(a)(2)(i)(A)	temperature	95% control of inlet VOC

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
A31	Thermal Oxidizer	S66	BAAQMD Condition #1240, Part II.85	Temperature	98.5% destruction
44	Off Gas Caustic Scrubber	S18, S32	None	None	None
45	Off Gas Caustic Scrubber	A44	BAAQMD Condition 1240, Part I.11	None	H2S concentration < 163 ppmv, dry, 3 hour average
45	Off Gas Caustic Scrubber	A44	BAAQMD Condition 1240, Part I.12	None	H2S concentration < 10 ppmv, dry, 24 hour average
S19	Vacuum Heater (natural gas, refinery gas)	S18, S32, A44, A45	BAAQMD Condition #1240, Part I.14	None	Emissions of NMHC < 49.1 tons per year excluding marine emissions
		S18	BAAQMD Condition #1240, Part I.3	None	98.5% destruction
		S18, S32	40 CFR 63.643(a)(2)	None	98% destruction of organic HAPs or concentration of 20 ppmv, @ 3% O ₂ , dry

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
S24	Hot Oil Heater	S3, S5-S8, S12, S13, S25, S37, S38, S41, S51-S53, S59, S60- S62, S63, S65, S66, S67, A1, A3, A6, A20	BAAQMD Condition #1240, Part I.14	temperature	Emissions of NMHC < 49.1 tons per year excluding marine emissions
		S3	BAAQMD Condition #1240, Part II.43	Temperature	98.5% destruction
		S5-S8, S37, S38	BAAQMD Condition #1240, Part II.55	Temperature	98.5% destruction
		S5-S8, S37, S38, S51-S53, S60	40 CFR 60.472(c)	Temperature	0 percent opacity except for one consecutive 15-min period in any 24-hr period for cleaning
		S12	40 CFR 61.349(a) (2)(i)(A)	Temperature	95% control of inlet VOC
		S13, S59, S63	BAAQMD 8-5-311.3	Temperature	95% control of VOC
		S13, S59, S63	40 CFR 60.112b(a) (3)(ii)	Temperature	95% control of inlet VOC

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
S24	Hot Oil Heater	S13	BAAQMD Condition #1240, Part II.32a	Temperature	98.5% control of inlet VOC by weight
		S59	BAAQMD Condition #1240, Part II.32b	Temperature	98.5% control of inlet VOC by weight
		S63	BAAQMD Condition #1240, Part II.32c	Temperature	98.5% control of inlet VOC by weight
		S25	40 CFR 61.349(a) (2)(i)(A)	Temperature	95% control of inlet VOC
		S41	40 CFR 61.349(a) (2)(i)(A)	Temperature	95% control of inlet VOC
		S51-S53, S60	BAAQMD Condition #1240, Part II.56	Temperature	98.5% destruction
		S61, S62	40 CFR 60.472(c)	Temperature	0 percent opacity except for one consecutive 15-min period in any 24-hr period for cleaning
		S61, S62	BAAQMD Condition #1240, Part II.57	Temperature	98.5% destruction

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
S24	Hot Oil Heater	S65	BAAQMD Condition #1240, Part II.56	Temperature	98.5% destruction
		S65	40 CFR 60.472(c)	Temperature	0 percent opacity except for one consecutive 15-min period in any 24-hr period for cleaning
		S66	40 CFR 61.349(a) (2)(i)(A)	Temperature	95% control of inlet VOC
		S66	BAAQMD Condition #1240, Part II.85	Temperature	98.5% destruction

III. GENERALLY APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. These requirements apply in a general manner to the facility and/or to sources exempt from the requirement to obtain a District Permit to Operate. The District has determined that these requirements will not be violated under normal, routine operations, and that no additional periodic monitoring or reporting to demonstrate compliance is warranted. In cases where a requirement, in addition to being generally applicable, is also specifically applicable to one or more sources, the requirement and the source are also included in Section IV, Source-Specific Applicable Requirements, of this permit.

The dates in parenthesis in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full language of SIP requirements is on EPA Region 9’s website. The address is included in Appendix A of this permit.

NOTE:

There are differences between the current BAAQMD rules and the version of the rules in the SIP. All sources must comply with both versions of the rule until US EPA has reviewed and approved the District’s revision of the regulation.

**Table III
 Generally Applicable Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)	N
SIP Regulation 1	General Provisions and Definitions (8/27/99)	Y
BAAQMD Regulation 2, Rule 1	General Requirements (5/2/01)	N
SIP Regulation 2, Rule 1	General Requirements (8/27/99)	Y

III. Generally Applicable Requirements

Table III
Generally Applicable Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 4	Air Pollution Episode Plan (3/20/91)	N
SIP Regulation 4	Air Pollution Episode Plan (8/06/90)	Y
BAAQMD Regulation 5	Open Burning (11/2/94)	N
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)	N
SIP Regulation 6	Particulate matter and Visible Emissions (5/3/84)	Y
BAAQMD Regulation 7	Odorous Substances (3/17/82)	N
BAAQMD Regulation 8, Rule 1	Organic Compounds - General Provisions (6/15/94)	Y
BAAQMD Regulation 8, Rule 2	Organic Compounds – Miscellaneous Operations (6/15/94)	Y
BAAQMD Regulation 8, Rule 3	Organic Compounds - Architectural Coatings (12/20/95)	Y
BAAQMD Regulation 8, Rule 4	Organic compounds - General Solvent and Surface Coating Operations (5/15/96)	N
SIP Regulation 8, Rule 4	Organic compounds - General Solvent and Surface Coating Operations (12/23/97)	Y
BAAQMD Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (12/20/95)	N
SIP Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (3/22/95)	Y
BAAQMD Regulation 8, Rule 51	Organic Compounds - Adhesive and Sealant Products (12/20/95)	N
BAAQMD Regulation 11, Rule 2	Hazardous Pollutants - Asbestos Demolition, Renovation and Manufacturing (12/4/91)	Y
BAAQMD Regulation 12, Rule 4	Miscellaneous Standards of Performance - Sandblasting (7/11/90)	N
SIP Regulation 12, Rule 4	Miscellaneous Standards of Performance - Sandblasting (9/2/81)	Y
EPA Regulation 40 CFR 82	Protection of Stratospheric Ozone (2/21/95)	
Subpart F, 40 CFR 82.156	Leak Repair	Y
Subpart F, 40 CFR 82.161	Certification of Technicians	Y
Subpart F, 40 CFR 82.166	Records of Refrigerant	Y

IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. The requirements cited in the following tables apply in a specific manner to the indicated source(s).

The dates in parenthesis in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full text of each permit condition cited is included in Section VI, Permit Conditions, of this permit. The full language of SIP requirements is on EPA Region 9's website. The address is included in Appendix A of this permit. All other text may be found in the regulations themselves.

**Table IV - A
 General Refinery Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD · Regulation 1	General Provisions and Definitions (05/02/2001)		
1-301	Public Nuisance Prohibition	N	
1-510	Area Monitoring	Y	
1-530	Area Monitoring Downtime	Y	
1-540	Area Monitoring Data Examination	Y	
1-542	Area Concentration Excesses	Y	
1-543	Record Maintenance for Two Years	Y	
1-544	Monthly Summary	Y	
BAAQMD Regulation 2, Rule 1	General Requirements (8/1/01)		
2-1-429	Federal Emissions Statement	Y	
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		

IV. Source Specific Applicable Requirements

**Table IV - A
 General Refinery Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-5-404	Certification	Y	
8-5-404.3	For tank degassing equipment	Y	
8-5-502	Tank cleaning annual source test requirement	Y	
8-5-603	Determination of emissions	Y	
8-5-603.2	Source tests for tank cleaning equipment	Y	
BAAQMD Regulation 8, Rule 8	Wastewater (Oil-Water) Separators (6/15/94)		
8-8-308	Junction Box	Y	
BAAQMD Regulation 9 Rule 1	Inorganic Gaseous Pollutants, Sulfur Dioxide Emissions Limitations (3/25/95)		
9-1-110	Conditional Exemption, Area Monitoring	Y	
9-1-301	Limitations on Ground Level Concentrations	Y	
9-1-302	General Emission Limitation (applies only when area monitoring for SO ₂ is not in compliance)	Y	
9-1-313	Sulfur Removal Operations at Petroleum Refineries	N	
9-1-313.2	Sulfur Removal and Recovery System	N	
9-1-501	Area Monitoring Requirements	Y	
9-1-604	Ground Level Monitoring	Y	
SIP Regulation 9 Rule 1	Inorganic Gaseous Pollutants, Sulfur Dioxide Emissions Limitations (6/8/99)		
9-1-313	Sulfur Removal Operations at Petroleum Refineries	Y ¹	
9-1-313.2	Sulfur Removal and Recovery System	Y ¹	
BAAQMD Regulation 9 Rule 2	Inorganic Gaseous Pollutants, Hydrogen Sulfide (10/6/99)		
9-2-110	Exemptions	N	
9-2-301	Limitations on Hydrogen Sulfide	N	
9-2-501	Area Monitoring Requirements	N	
9-2-601	Ground Level Monitoring	N	
40 CFR 60 Subpart A	General Provisions (03/16/1994)		
60.1	Applicability	Y	
60.2	Definitions	Y	
60.3	Units and Abbreviations	Y	

IV. Source Specific Applicable Requirements

**Table IV - A
 General Refinery Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.4	Address	Y	
60.5	Determination of Construction or Modification	Y	
60.6	Review of Plans	Y	
60.7	Notification and Recordkeeping	Y	
60.8	Performance Tests	Y	
60.9	Availability of Information	Y	
60.11	Compliance with Standards and Maintenance Requirements	Y	
60.12	Circumvention	Y	
60.13	Monitoring Requirements	Y	
60.14	Modification	Y	
60.15	Reconstruction	Y	
60.17	Incorporated by Reference	Y	
60.19	General Notification and Reporting Requirements	Y	
40 CFR 61 Subpart A	National Emission Standards for Hazardous Air Pollutants, General Provisions (3/31/71)		
61.01	Lists of Pollutants and Applicability of Part 61	Y	
61.02	Definitions	Y	
61.03	Units and abbreviations	Y	
61.04	Address	Y	
61.05	Prohibited Activities	Y	
61.06	Determination of Construction or Modification	Y	
61.07	Application for Approval of Construction or Modification	Y	
61.08	Approval of construction or modification	Y	
61.09	Notification of startup	Y	
61.10	Source reporting and waiver request	Y	
61.12	Compliance with Standards and Maintenance Requirements	Y	
61.13	Emission Tests and Waiver of Emission Tests	Y	
61.14	Monitoring requirements	Y	
61.15	Modification	Y	
61.18	Incorporation by reference	Y	
61.19	Circumvention	Y	
40 CFR 61 Subpart FF	National Emission Standards for Hazardous Air Pollutants, Benzene Waste Operations (01/07/1993)		
61.340(a)	Applicability: Chemical Manufacturing, Coke by-product recovery, petroleum refineries	Y	

IV. Source Specific Applicable Requirements

Table IV - A
General Refinery Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
61.340(c)	Applicability: Exempt Waste	Y	
61.341	Definitions	Y	
61.342	Standards: General	Y	
61.342(b)	Standards: General; Request for waiver of compliance	Y	
61.342(c)(1)	Standards: General; Treat benzene-containing waste streams in accordance with 61.342(c)(1)(i), 61.342(c)(1)(ii) and 61.342(c)(1)(iii)	Y	
61.342(c)(1)(i)	Standards: General; Remove or destroy benzene in accordance with 61.348.	Y	
61.342(c)(1)(ii)	Standards: General; Comply with 61.343 through 61.347 for treatment units operated in accordance with 61.342(c)(1)(i)	Y	
61.342(c)(1)(iii)	Standards: General; Comply with 61.343 through 61.347 for treatment units for recycled wastes. Recycled wastes subject to 61.342(c)	Y	
61.342(e)	Standards: General; Alternative to 61.342(c) and 61.342(d)	Y	
61.342(e)(1)	Standards: General; Treat waste with a flow-weighted annual average water content of less than 10% per 61.342(c)(1)	Y	
61.342(e)(2)	Standards: General; Treatment of waste with a flow-weighted annual average water content of 10% or more by volume.	Y	
61.342(e)(2)(i)	Standards: General; [Uncontrolled] 61.342(e)(2) Waste shall not contain more than 6.0 Mg/yr benzene.	Y	
61.342(e)(2)(ii)	Standards: General; Determine 61.342(e)(2) benzene quality per 61.355(k).	Y	
61.343(a)(1)(i)(A)	Standards: Tanks; Fixed Roof—Fugitive emissions less than 500 ppmv	Y	
61.345(a)	Standards: Containers	Y	
61.345(a)(1)	Standards: Containers--Covers	Y	
61.345(a)(1)(i)	Standards: Containers--Covers and Openings, no detectable emissions	Y	
61.345(a)(1)(ii)	Standards: Containers--Openings	Y	
61.345(a)(2)	Standards: Containers--Waste Transfer	Y	
61.345(b)	Standards: Containers--Quarterly inspection	Y	
61.345(c)	Standards: Containers--Repairs	Y	
61.346(b)	Alternate compliance provisions for Individual Drain Systems	Y	
61.346(b)(1)	Water seals on drains	Y	
61.346(b)(2)	Cover and vent pipe	Y	
61.346(b)(2)(i)	Tight seals on junction boxes	Y	
61.346(b)(2)(ii)	Control of emissions from junction box vent pipe	Y	

IV. Source Specific Applicable Requirements

**Table IV - A
 General Refinery Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
61.346(b)(2)(ii)(A)	Prevention of flow of vapors from junction box vent pipe	Y	
61.346(b)(3)	No cracks on exposed sewer lines	Y	
61.346(b)(4)	Equipment Inspections	Y	
61.346(b)(4)(i)	Monitor water seals on drains quarterly	Y	
61.346(b)(4)(iii)	Monitor seals on junction boxes quarterly	Y	
61.346(b)(4)(iv)	Monitor for cracks on exposed sewer lines quarterly	Y	
61.346(b)(5)	Repair as soon as practicable but no later than 15 days after identification	Y	
61.355	Test Methods, Procedures, and Compliance Provisions	Y	
61.356	Recordkeeping Requirements	Y	
61.356(a)	Recordkeeping and retention requirements	Y	
61.356(b)	Waste stream records	Y	
61.356(d)	Recordkeeping Requirements: Control equipment engineering design	Y	
61.356(e)	Recordkeeping Requirements: Treatment process or unit per 61.348	Y	
61.356(f)	Recordkeeping Requirements: Closed vent system and control device per 61.349--retain for life of device	Y	
61.356(g)	Recordkeeping Requirements: Visual inspection per 61.343 through 61.347	Y	
61.356(h)	Recordkeeping Requirements: No detectable emissions tests per 61.343 through 61.347, and 61.349	Y	
61.356(i)	Recordkeeping Requirements: Treatment process or unit per 61.348	Y	
61.356(j)	Recordkeeping Requirements: Control device operation	Y	
61.357	Reporting Requirements	Y	
61.357(d)	Reporting Requirements: Facilities with 10 Mg/yr or more total benzene in waste	Y	
61.357(e)	Reporting Requirements for 61.351 and 61.352 equipment	Y	
61.357(f)	Reporting Requirements for 61.351 control equipment	Y	
40 CFR 63 Subpart A	General Provisions of MACT Standards (03/16/1994)		
63.1(a)(1)	Terms used throughout this part are defined in section 63.2	Y	
63.1(a)(2)	This part contains NESHAPS pursuant to Section 112 of Federal Clean Air Act. These NESHAPS are independent of NESHAPS in 40 CFR 61.	Y	
63.1(a)(3)	Emission standard in this part does not replace a more stringent standard in another rule.	Y	
63.1(a)(11)	Submittal postmarked within required timeframe is sufficient.	Y	

IV. Source Specific Applicable Requirements

**Table IV - A
 General Refinery Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
63.1(a)(12)	Time periods may be extended if mutually agreed upon, as allowed under 63.9(i)	Y	
63.1(a)(13)	Special provision in another applicable subpart supercedes conflicting provisions in this subpart.	Y	
63.1(a)(14)	Federal enforceability	Y	
63.1(b)(2)	Sources under this subpart may also be required to obtain local permit.	Y	
63.1(c)(4)	If an extension is obtained for specific provision, all other provisions still apply.	Y	
63.1(c)(5)	Applicability	Y	
63.2	Definitions	Y	
63.4(a)(1)	Sources may not operate in violation, unless an extension or exemption has been obtained	Y	
63.4(a)(2)	Recordkeeping and reporting requirements must be met	Y	
63.4(a)(3)	Source must also comply with local requirements	Y	
63.4(a)(5)	Source must comply with applicable standards even if Title V permit not issued or updated	Y	
63.4(b)	Circumvention	Y	
63.4(c)	Severability	Y	
63.5(a)	Construction and reconstruction applicability	Y	
63.5(a)(1)	Construction and Reconstruction applicability	Y	
63.5(a)(2)	Construction and Reconstruction-effective date	Y	
63.5(b)(1)	Upon construction or reconstruction, subject to standards for new sources	Y	
63.5(b)(3)	Prior written approval of administrator required before constructing or reconstructing	Y	
63.5(b)(4)	Construction and Reconstruction-notification to administrator	Y	
63.5(b)(5)	Construction and Reconstruction-compliance with 40 CFR 63, Subpart A	Y	
63.5(b)(6)	Equipment added to affected source becomes part of affected source, and is subject to relevant standards for source	Y	
63.5(d)(1)(i)	Construction and Reconstruction	Y	
63.5(d)(1)(ii)	Separate applications for each construction or reconstruction	Y	
63.5(d)(3)	Application for approval of construction	Y	
63.5(d)(4)	Additional information	Y	
63.5(e)	Approval of construction or reconstruction	Y	
63.5(f)(1)	Approval of construction or reconstruction based on local pre-construction review	Y	
63.5(f)(2)	Construction and Reconstruction-submittal of request to Administrator	Y	
63.6(a)	Compliance with Standards and Maintenance Requirements-applicability	Y	

IV. Source Specific Applicable Requirements

Table IV - A
General Refinery Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
63.6(b)(3)	Compliance date for sources constructed between proposal and promulgation date for standard	Y	
63.6(c)(5)	Compliance date for source that becomes newly subject to standard	Y	
63.6(e)	Operation and Maintenance Requirements	Y	
63.6(f)(1)	Compliance with non-opacity emission standards - applicability	Y	
63.6(f)(2)(i)	Determination of compliance with non-opacity standard based on performance tests	Y	
63.6(f)(2)(ii)	Determination of compliance with non-opacity standard based on based on conformance with operation and maintenance requirements	Y	
63.6(f)(2)(iii)	Use of startup tests for state requirements	Y	
63.6(f)(2)(iii)(A)	Tests within reasonable time	Y	
63.6(f)(2)(iii)(B)	Tests conducted under representative operating conditions	Y	
63.6(f)(2)(iii)(C)	Use of EPA-approved test procedures	Y	
63.6(f)(2)(iv)	Determine compliance by reviewing records, inspections	Y	
63.6(f)(2)(v)	Determine compliance by evaluation of conformance with operation and maintenance requirements	Y	
63.6(f)(3)	Finding of compliance	Y	
63.6(g)	Use of alternative non-opacity emission standard	Y	
63.6(h)(1)	Compliance with opacity and visible emissions standards-Applicability	Y	
63.6(h)(2)	Methods for determining compliance	Y	
63.6(h)(6)	Availability of records	Y	
63.6(i)	Extension of compliance with emission standards	Y	
63.6(j)	Exemption from compliance with emission standard	Y	
63.7(a)(3)	Administrator may require a performance test	Y	
63.7(d)	Performance testing facilities.	Y	
63.7(e)(1)	Performance Testing Requirements-conduct of performance tests	Y	
63.7(e)(2)	Performance Testing Requirements-use of test methods and procedures in 40 CFR 51, 60, 61, or 63	Y	
63.7(e)(4)	Testing under Section 114 of the Clean Air Act	Y	
63.7(h)(1)	Waiver of performance tests	Y	
63.7(h)(2)	Application for waiver of individual performance test	Y	
63.7(h)(3)	Request to waive a performance test	Y	
63.7(h)(5)	Administrator's authority not abrogated	Y	
63.8(b)(1)	Conducting monitoring	Y	
63.8(b)(3)	Using more than one monitoring system to measure emissions.	Y	

IV. Source Specific Applicable Requirements

Table IV - A
General Refinery Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
63.8(c)(1)	Monitoring Requirements	Y	
63.8(c)(1)(i)	Permit holder shall keep necessary parts to repair “routine” malfunctions, as identified in malfunction plan, per 63.6(e)(3)	Y	
63.8(c)(1)(iii)	Applicable operation and maintenance procedures	Y	
63.8(c)(2)	Monitoring systems shall measure representative emissions, parameters.	Y	
63.8(c)(3)	Monitors shall be installed prior to, or in conjunction with, performance tests under 63.7	Y	
63.8(f)(1)	Use of alternative monitoring method	Y	
63.8(f)(2)	Administrator may approve alternative monitoring upon written request	Y	
63.8(f)(3)	If administrator has reasonable grounds to dispute results of alternative monitoring, the administrator may require specific monitoring	Y	
63.8(f)(4)(ii)	Requirements for application for alternative monitoring	Y	
63.8(f)(5)(i)	Notification of approval of alternative monitoring	Y	
63.8(f)(5)(iii)	Use of alternative monitoring until Administrator approves other monitoring	Y	
63.9(a)	Notification requirements – applicability and general information	Y	
63.9(b)(4)	Notification Requirements for new or reconstructed source with initial startup date after effective date of relevant standard	Y	
63.9(b)(5)	Notification Requirements for construction of new source or reconstruction of existing source subject to standard	Y	
63.9(c)	Request for extension of compliance	Y	
63.9(d)	Notification that source is subject to special compliance requirements	Y	
63.9(i)	Adjustments to time periods or postmark deadlines for submittal and review of required communications	Y	
63.10(a)	Recordkeeping and reporting - applicability and general information.	Y	
63.10(b)(2)(i)	Records of startup, shutdown, or malfunction of operation.	Y	
63.10(b)(2)(ii)	Records of malfunction of air pollution control equipment	Y	
63.10(b)(2)(iv)	Record of actions deviating from startup, shutdown, and malfunction plan.	Y	
63.10(b)(2)(v)	Records to determine conformance with startup, shutdown, and malfunction plan.	Y	
63.10(b)(2)(x)	Records of monitoring system calibration checks.	Y	
63.10(d)(4)	Progress reports for extension of compliance	Y	
63.10(d)(5)(i)	Periodic startup, shutdown, and malfunction reports.	Y	
63.10(d)(5)(ii)	Immediate startup, shutdown, and malfunction reports.	Y	
63.10(f)	Waiver of recordkeeping and reporting requirements	Y	
63.11	Control Device Requirements	Y	

IV. Source Specific Applicable Requirements

Table IV - A
General Refinery Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
63.12	State Authority and Delegation	Y	
63.13	Addresses of EPA Regional Office	Y	
63.14	Incorporation by Reference	Y	
63.15	Availability of Information and Confidentiality	Y	
40 CFR 63 Subpart CC	National Emission Standards for Hazardous Air Pollutants for Petroleum Refineries (06/12/1996)		
63.640(a)	Applicability applies to petroleum refining process units and to related emission points.	Y	
63.640(c)	Applicability and Designation of Affected Source--Includes all emission points at Refinery	Y	
63.640(d)	Applicability and Designation of Affected Source--Exclusions	Y	
63.640(f)	Applicability and Designation of Affected Source--miscellaneous process vents	Y	
63.640(g)	Applicability and Designation of Affected Source--Exempt Processes	Y	
63.640(h)	Applicability and Designation of Affected Source--Compliance dates	Y	
63.640(i)	Applicability and Designation of Affected Source--New petroleum refining process unit requirements	Y	
63.640(j)	Applicability and Designation of Affected Source--Changes to existing petroleum refining process units	Y	
63.640(k)	Applicability and Designation of Affected Source--Additional requirements for new or changed sources	Y	
63.640(l)	Applicability and Designation of Affected Source--Additions of equipment (i.e. process vents, storage vessels, etc) in Group 1 sources not subject to 63.640(i) or (k).	Y	
63.640(m)	Applicability and Designation of Affected Source--Changes causing Group 2 emission points to become Group 1 points	Y	
63.640(q)	For overlap of subpart CC with local or State regulations, the permitting authority for the affected source may allow consolidation of the monitoring, recordkeeping, and reporting requirements under this subpart.	Y	
63.641	Definitions: (arranged alphabetically) Group 1 wastewater stream, Group 2 wastewater stream, miscellaneous process vents (specifically does not include emissions from wastewater collection and conveyance systems).	Y	
63.642	General Standards	Y	
63.642(a)	Apply for a part 70 or part 71 operating permit	Y	
63.642(c)	Table 6 of this subpart specifies the Subpart A provisions that apply.	Y	
63.642(d)	Initial performance tests and compliance determinations shall be required only as specified in this subpart	Y	
63.642(e)	Keep copies of all applicable reports and records for at least 5 years, except as otherwise specified in this subpart.	Y	
63.642(f)	All reports required by this subpart shall be sent to the Administrator	Y	

IV. Source Specific Applicable Requirements

**Table IV - A
 General Refinery Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
63.642(i)	Existing source owners/operators shall demonstrate compliance with (g) by following procedures in (k) or by following emission averaging compliance approach in (l) for specified emission points and the procedures in (k) for other emission points.	Y	
63.642(k)	Existing source owners/operators may comply, and new sources owners/operators shall comply with the wastewater provisions in 63.647 and comply with 63.654 and is exempt from (g)	Y	
63.647(a)	Comply with 61.340-61.355 (Subpart FF). Owners/operators of Group 1 wastewater streams shall comply with sections 61.340 to 61.355 of part 61, subpart FF for each stream that meets the definition of 63.641.	Y	
63.647(b)	Wastewater Provisions	Y	
63.647(c)	Periodic measurement of benzene concentrations	Y	
63.654(a)	Compliance with in recordkeeping in 40 CFR 61, Subpart FF	Y	
63.654(e)	Periodic Reporting and Recordkeeping Requirements	Y	
63.654(g)	Semi-Annual Reporting and Recordkeeping Requirements	Y	
63.654(h)(1)	Reports of startup, shutdown, and malfunction	Y	
63.654(h)(2)	Notifications of inspections for storage vessels	Y	
63.654(i)(1)	Records for storage vessels	Y	
63.654(i)(4)	Information required by 63.654(h)	Y	
Appendix Table 1	Hazardous Air Pollutants	Y	
Appendix Table 6	Hazardous Air Pollutants	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.15	Restriction on use of refinery wastewater for dust control (cumulative increase)	Y	
Part I.20	Notification of startup and shutdown (2-1-403)	N	
Part IV.1	Water seals, P-traps, caps, covers on process water drains (1-301)	N	

¹This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

IV. Source Specific Applicable Requirements

Table IV - B
Source-specific Applicable Requirements
S1, S2, S4, S23- CRUDE STORAGE TANKS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	N	
8-5-112	Limited Exemption, Tanks in Operation	N	
8-5-304	Storage tanks larger than 75 cubic meter	Y	
8-5-304.2	Storage tanks larger than 150 cubic meter storing liquid with a true vapor pressure greater than 25.8 mm Hg	Y	
8-5-311	Vapor loss control device requirements	Y	
8-5-311.1	Primary and secondary seals	Y	
8-5-320	Tank fitting requirements	N	
8-5-320.1	Secondary seal	Y	
8-5-320.2	Openings in the roof	Y	
8-5-320.3	P/V valves	Y	
8-5-320.4	Solid sampling or gauging wells	Y	
8-5-320.5	Slotted sampling or gauging wells	Y	
8-5-320.5.1	The well shall provide a projection below the liquid surface	Y	
8-5-320.5.2	The well requirements	N	
8-5-320.5.3	The gap between the well and the roof	Y	
8-5-320.6	Emergency roof drain	Y	
8-5-321	Primary seal requirements	N	
8-5-321.1	No holes, tears, or other openings in the primary seal fabric	Y	
8-5-321.2	The seal shall be liquid mounted except as provided in 8-5-311.2.2	Y	
8-5-321.3	Metallic shoe type seals	N	
8-5-321.3.1	Geometry of shoe	Y	
8-5-321.3.2	Gaps for welded tanks	Y	
8-5-322	Secondary seal requirements	Y	
8-5-322.1	No holes, tears, or other openings in the secondary seal	Y	
8-5-322.2	Insertion of probes	Y	
8-5-322.3	Gaps for welded tanks	Y	
8-5-322.5	Gap for welded tanks with seal installed after September 4, 1985	Y	
8-5-328	Tank cleaning requirements	Y	
8-5-328.1	Liquid balancing	Y	

IV. Source Specific Applicable Requirements

Table IV - B
Source-specific Applicable Requirements
S1, S2, S4, S23- CRUDE STORAGE TANKS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-5-328.2	An approved Emission Control system	Y	
8-5-329	Ozone excess day prohibition	Y	
8-5-401	Primary seal inspection	Y	
8-5-402	Secondary seal and fitting inspection	Y	
8-5-404	Certification	Y	
8-5-404.2	For secondary seal	Y	
8-5-405	Information required	Y	
8-5-501	Records	Y	
8-5-502	Tank Cleaning Annual Source Test Requirement	Y	
8-5-503	Portable hydrocarbon detector	Y	
8-5-601	Analysis of Samples, Reid Vapor Pressure	Y	
8-5-602	Analysis of Samples, True Vapor Pressure	Y	
8-5-603	Determination of Emissions	Y	
8-5-603.2	Testing of degassing control equipment	Y	
8-5-604	Determinations of Applicability	Y	
8-5-605	P/V Valve Gas Tightness Determination	Y	
SIP Regulation 8, Rule 5	Storage of Organic Liquids (8/25/97)		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	Y ¹	
8-5-112	Limited Exemption, Tanks in Operation	Y ¹	
8-5-320	Tank fitting requirements	Y ¹	
8-5-320.5.2	The well requirements	Y ¹	
8-5-321	Primary seal requirements	Y ¹	
8-5-321.3	Metallic shoe type seals	Y ¹	
NSPS Part 60 Subpart Kb	Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984	Y	
60.110b(a)	Applicability and designation of affected facility	Y	
60.112b(a)	Standard for Volatile Organic Compounds (VOC); Requirement for tanks- > 151 cubic meter with maximum TVP >=5.2 kPa and <76.6; or >= 75 cubic meter and < 151 cubic meter with maximum TVP >= 27.6 kPa and < 76.6 kPa	Y	

IV. Source Specific Applicable Requirements

Table IV - B
Source-specific Applicable Requirements
S1, S2, S4, S23- CRUDE STORAGE TANKS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.112b(a)(2)	Standard for Volatile Organic Compounds (VOC); External floating roof option	Y	
60.112b(a)(2)(i)	Standard for Volatile Organic Compounds (VOC); External floating roof seal requirements	Y	
60.112b(a)(2)(i)(A)	Standard for Volatile Organic Compounds (VOC); External floating roof primary seal requirements	Y	
60.112b(a)(2)(i)(B)	Standard for Volatile Organic Compounds (VOC); External floating roof secondary seal requirements	Y	
60.112b(a)(2)(ii)	Standard for Volatile Organic Compounds (VOC); External floating roof openings requirements	Y	
60.112b(a)(2)(iii)	Standard for Volatile Organic Compounds (VOC); External floating roof floating requirements	Y	
60.113b(b)(1)	Testing and Procedures; External floating roof seal gap measurement frequency	Y	
60.113b(b)(1)(iii)	Testing and Procedures; External floating roof reintroduction of VOL	Y	
60.113b(b)(2)	Testing and Procedures; External floating roof seal gap measurement procedures	Y	
60.113b(b)(2)(i)	Testing and Procedures; External floating roof measure seal gaps when roof is floating	Y	
60.113b(b)(2)(ii)	Testing and Procedures; External floating roof measure seal gaps around entire circumference	Y	
60.113b(b)(2)(iii)	Testing and Procedures; External floating roof seal method to determine surface area of seal gaps	Y	
60.113b(b)(3)	Testing and Procedures; External floating roof method to calculate total surface area ratio	Y	
60.113b(b)(4)	Testing and Procedures; External floating roof seal gap repair requirements	Y	
60.113b(b)(4)(i)	Testing and Procedures; External floating roof primary seal gap limitations	Y	
60.113b(b)(4)(i)(A)	Testing and Procedures; External floating roof mechanical shoe primary seal requirements	Y	
60.113b(b)(4)(i)(B)	Testing and Procedures; External floating roof primary seals no holes, tears, openings	Y	
60.113b(b)(4)(ii)(A)	Testing and Procedures; External floating roof secondary seal installation	Y	
60.113b(b)(4)(ii)(B)	Testing and Procedures; External floating roof secondary seal gap limitations	Y	
60.113b(b)(4)(ii)(C)	Testing and Procedures; External floating roof secondary seals no holes, tears, openings	Y	
60.113b(b)(4)(iii)	Testing and Procedures; External floating roof 30-day extension request for seal gap repairs	Y	
60.113b(b)(5)	Testing and Procedures; External floating roof seal gap inspections 30 day notification	Y	

IV. Source Specific Applicable Requirements

Table IV - B
Source-specific Applicable Requirements
S1, S2, S4, S23- CRUDE STORAGE TANKS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.113b(b)(6)	Testing and Procedures; External floating roof visual inspection when emptied and degassed	Y	
60.113b(b)(6)(i)	Testing and Procedures; External floating roof--roof or seal defect repairs	Y	
60.113b(b)(6)(ii)	Testing and Procedures; External floating roof notification prior to filling	Y	
60.115b	Reporting and Recordkeeping Requirements; 60.112b(a) tanks	Y	
60.115b(b)	Reporting and Recordkeeping Requirements; 60.112b(a) external floating roof	Y	
60.115b(b)(1)	Reporting and Recordkeeping Requirements; 60.112b(a) external floating roof control equipment description and certification	Y	
60.115b(b)(2)	Reporting and Recordkeeping Requirements; 60.112b(a) external floating roof seal gap measurement report	Y	
60.115b(b)(2)(i)	Reporting and Recordkeeping Requirements; 60.112b(a) external floating roof seal gap measurement report--date of measurement	Y	
60.115b(b)(2)(ii)	Reporting and Recordkeeping Requirements; 60.112b(a) external floating roof seal gap measurement report--raw data	Y	
60.115b(b)(2)(iii)	Reporting and Recordkeeping Requirements; 60.112b(a) external floating roof seal gap measurement report--calculations	Y	
60.115b(b)(3)	Reporting and Recordkeeping Requirements; 60.112b(a) external floating roof seal gap measurement records	Y	
60.115b(b)(3)(i)	Reporting and Recordkeeping Requirements; 60.112b(a) external floating roof seal gap measurement records--date of measurement	Y	
60.115b(b)(3)(ii)	Reporting and Recordkeeping Requirements; 60.112b(a) external floating roof seal gap measurement records--raw data	Y	
60.115b(b)(3)(iii)	Reporting and Recordkeeping Requirements; 60.112b(a) external floating roof seal gap measurement records--calculations	Y	
60.115b(b)(4)	Reporting and Recordkeeping Requirements; 60.112b(a) external floating roof seal gap exceedance report	Y	
60.116b(a)	Monitoring of Operations; Record retention	Y	
60.116b(b)	Monitoring of Operations; Permanent record requirements	Y	
60.116b(c)	Monitoring of Operations; VOL storage record requirements	Y	
60.116b(e)(1)	Monitoring of Operations; Determine TVP-temperature selection based on tank operating temperatures	Y	
60.116b(e)(3)(i)	Monitoring of Operations; Determine TVP-other liquids-standard reference texts	Y	
60.116b(e)(3)(ii)	Monitoring of Operations; Determine TVP-other liquids-ASTM method	Y	
60.116b(e)(3)(iii)	Monitoring of Operations; Determine TVP-other liquids-other approved measurement method	Y	
60.116b(e)(3)(iv)	Monitoring of Operations; Determine TVP-other liquids-other approved calculation method	Y	

IV. Source Specific Applicable Requirements

Table IV - B
Source-specific Applicable Requirements
S1, S2, S4, S23- CRUDE STORAGE TANKS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
40 CFR 63 Subpart CC	National Emission Standards for Hazardous Pollutants for Petroleum Refining (8/18/95)		
63.640(n)(1)	Applicability and Designation of Affected Source Overlap for Storage Vessels—Existing Group 1 or Group 2 also subject to Kb only subject to Kb and 63.640(n)(8).	Y	
63.640(n)(8)(i)	Exemption from secondary seal requirements during gap measurements for primary seal	Y	
63.640(n)(8)(ii)	Structurally unsound roofs	Y	
63.640(n)(8)(iii)	Extensions for compliance	Y	
63.640(n)(8)(iv)	Additional reports if extension is used	Y	
63.640(n)(8)(v)	Subpart Kb reports may be submitted for this subpart. Permit holder has 60 days in lieu of Subpart Kb deadline.	Y	
63.640(n)(8)(vi)	Subpart Kb rim seal inspection reports not required if gaps do not exceed limitations.	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18c	Estimates of NMHC emissions from tanks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.12	Specifications for External Floating Roof Tanks (Cumulative Increase, Offsets)	Y	
Part II.13	Quarterly Seal Inspections (Cumulative Increase)	Y	
Part II.14	Throughput Limit (Cumulative Increase)	Y	
Part II.15	Storage of Materials Other than Crude Oil (Cumulative Increase, Toxics)	Y	
Part II.16	Vapor Pressure Limit (Cumulative Increase, Offsets, Toxics)	Y	
Part II.22	Daily Recordkeeping (Cumulative Increase)	Y	
Part II.23	Monthly Recordkeeping (Cumulative Increase)	Y	
Part II.24	Crude Oil Transfers by pipeline only (Cumulative Increase)	Y	

¹This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

IV. Source Specific Applicable Requirements

Table IV – C
Source-specific Applicable Requirements
S3, EXEMPT GAS OIL STORAGE TANK, TK-1C

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Organic Compounds, Storage of Organic Liquids (12/15/99)		
8-5-117	Exemption, Low Vapor Pressure	Y	
8-5-501	Records	Y	
8-5-604	Determination of Applicability	Y	
40 CFR 63 Subpart CC	National Emission Standards for Hazardous Pollutants for Petroleum Refining (8/18/95)		
63.646(b)(1)	Storage Vessel Provisions--Determine stored liquid % OHAP for group determination	Y	
63.646(b)(2)	Storage Vessel Provisions--Determine stored liquid % OHAP-method 18 to resolve disputes	Y	
63.654(i)(1)	Reporting and Recordkeeping Requirements--Recordkeeping for storage vessels	Y	
63.654(i)(1)(iv)	Reporting and Recordkeeping Requirements--Recordkeeping for storage vessels	Y	
63.654(i)(4)	Reporting and Recordkeeping Requirements--Recordkeeping--Record retention	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18c	Estimates of NMHC emissions from tanks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.40	Storage of materials other than gas oil (Cumulative Increase, Toxics)	Y	
Part II.41	Storage of at least 38,400,000 gallons gas oil per yr (Offsets)	Y	
Part II.42	Vapor pressure requirement (Cumulative Increase, NSPS)	Y	
Part II.43	Control Requirement (BACT, Cumulative Increase, offsets)	Y	

IV. Source Specific Applicable Requirements

Table IV – C
Source-specific Applicable Requirements
S3, EXEMPT GAS OIL STORAGE TANK, TK-1C

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part II.44	Vapor recovery and fugitive emission requirement (BACT, Cumulative Increase, offsets)	Y	
Part II.45	Requirement for gasketed tank fittings (BACT)	Y	
Part II.46	Recordkeeping (Cumulative Increase)	Y	

Table IV - D
Source-specific Applicable Requirements
S5, S6, S7, S8, ASPHALT STORAGE TANKS
S37, S38, RUBBERIZED ASPHALT SALES TANKS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 5	Organic Compounds, Storage of Organic Liquids (12/15/99)		
8-5-117	Exemption, Low Vapor Pressure	Y	
8-5-501	Records	Y	
8-5-604	Determination of Applicability	Y	
BAAQMD Regulation 8, Rule 15	Organic Compounds, Emulsified and Liquid Asphalts (9/16/87)		
8-15-305	Prohibition of Manufacture and Sale	Y	
8-15-501	Records	Y	
NSPS Subpart UU	Standards of Performance for Asphalt Processing and Asphalt Roofing Manufacture (8/6/82)		
60.472(c)	Opacity standard	Y	

IV. Source Specific Applicable Requirements

Table IV - D
Source-specific Applicable Requirements
S5, S6, S7, S8, ASPHALT STORAGE TANKS
S37, S38, RUBBERIZED ASPHALT SALES TANKS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.473(c)	Parametric monitoring	Y	
60.473(d)	Exemption from quarterly reports	Y	
40 CFR 63 Subpart CC	National Emission Standards for Hazardous Pollutants for Petroleum Refining (8/18/95)		
63.646(b)(1)	Storage Vessel Provisions--Determine stored liquid % OHAP for group determination	Y	
63.646(b)(2)	Storage Vessel Provisions--Determine stored liquid % OHAP-method 18 to resolve disputes	Y	
63.654(i)(1)	Reporting and Recordkeeping Requirements--Recordkeeping for storage vessels	Y	
63.654(i)(1)(iv)	Reporting and Recordkeeping Requirements--Recordkeeping for storage vessels	Y	
63.654(i)(4)	Reporting and Recordkeeping Requirements--Recordkeeping--Record retention	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18c	Estimates of NMHC emissions from tanks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.48	Throughput Limit (Cumulative Increase, Offsets)	Y	
Part II.49	Prohibition against cutback asphalt (Toxics)	Y	
Part II.50	Vapor Pressure Limit (Cumulative Increase, Offsets)	Y	
Part II.55	Control and Destruction Efficiency Requirements (Cumulative Increase, Offsets)	Y	
Part II.58	Recordkeeping Requirement (Cumulative Increase)	Y	
Part II.58b	Continuous Temperature Monitoring (40 CFR 60.472(c))	Y	
Part II.58c	Allowable Temperature Excursions (2-1-403)	Y	
Part II.58d	Recordkeeping for Allowable Temperature Excursions (2-1-403)	Y	

IV. Source Specific Applicable Requirements

Table IV - D
Source-specific Applicable Requirements
S5, S6, S7, S8, ASPHALT STORAGE TANKS
S37, S38, RUBBERIZED ASPHALT SALES TANKS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part II.58e	Definition of Allowable Temperature Excursions (2-1-403)	Y	

Table IV - E
Source-specific Applicable Requirements
S9, NAPHTHA STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	N	
8-5-112	Limited Exemption, Tanks in Operation	N	
8-5-304	Storage tanks larger than 75 cubic meter	Y	
8-5-304.2	Storage tanks larger than 150 cubic meter storing liquid with a true vapor pressure greater than 25.8 mm Hg	Y	
8-5-311	Vapor loss control device requirements	Y	
8-5-311.2	Internal floating roof tanks	Y	
8-5-311.2.3	A liquid mounted primary and a secondary seal which satisfies the requirement of Section 8-5-321 and 322	Y	
8-5-320	Tank fitting requirements	N	
8-5-320.1	Secondary seal	Y	
8-5-320.2	Openings in the roof	Y	
8-5-320.2.1	Projection below liquid surface	Y	
8-5-320.2.2	Viewports and other openings	Y	
8-5-320.2.3	Inaccessible openings	Y	
8-5-320.3	Pressure vacuum valves	Y	
8-5-320.4	Solid sampling or gauging wells	Y	
8-5-320.4.1	The well shall provide a projection below the liquid surface	Y	
8-5-320.4.2	The well shall be equipped with a cover	Y	

IV. Source Specific Applicable Requirements

Table IV - E
Source-specific Applicable Requirements
S9, NAPHTHA STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-5-320.4.3	The gap between the well and the roof	Y	
8-5-320.5	Slotted sampling or gauging wells	N	
8-5-320.5.1	The well shall provide a projection below the liquid surface	Y	
8-5-320.5.2	The well requirements	N	
8-5-320.5.3	The gap between the well and the roof	Y	
8-5-320.6	Emergency roof drain	Y	
8-5-321	Primary seal requirements	N	
8-5-321.1	No holes, tears, or other openings in the primary seal fabric	Y	
8-5-321.2	The seal shall be liquid mounted except as provided in 8-5-311.2.2	Y	
8-5-321.3	Metallic shoe type seals	N	
8-5-321.3.1	Geometry of shoe	Y	
8-5-321.3.2	Gaps for welded tanks	Y	
8-5-322	Secondary seal requirements	Y	
8-5-322.1	No holes, tears, or other openings in the secondary seal	Y	
8-5-322.2	Insertion of probes	Y	
8-5-322.5	Gaps for welded tanks with seals installed after 2/1/93	Y	
8-5-328	Tank cleaning requirements	Y	
8-5-328.1	Liquid balancing	Y	
8-5-328.2	An approved Emission Control System	Y	
8-5-329	Ozone excess day prohibition	Y	
8-5-330	Viewport Installation	Y	
8-5-401	Primary seal inspection	Y	
8-5-401.2	Once every 10 years	Y	
8-5-402	Secondary seal and fitting inspection	Y	
8-5-402.1	Once every 10 years for tanks subject to the requirements of subsection 8-5-322.5.	Y	
8-5-402.2	Once every 10 years	Y	
8-5-403	Internal Floating Roof Tank Visual Inspection	Y	
8-5-404	Certification	Y	
8-5-404.1	For primary seal	Y	
8-5-404.2	For secondary seal	Y	
8-5-404.2.1	Once every 10 years for tanks subject to the requirements of subsection 8-5-322.5.	Y	

IV. Source Specific Applicable Requirements

Table IV - E
Source-specific Applicable Requirements
S9, NAPHTHA STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-5-404.2.2	Once every 10 years	Y	
8-5-405	Information required	Y	
8-5-405.1	Date of inspection	Y	
8-5-405.2	Actual gap measurements	Y	
8-5-405.3	Data, supported calculation	Y	
8-5-501	Records	Y	
8-5-503	Portable hydrocarbon detector	Y	
SIP Regulation 8, Rule 5	Storage of Organic Liquids (1/20/93)		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	Y ¹	
8-5-112	Limited Exemption, Tanks in Operation	Y ¹	
8-5-320	Tank fitting requirements	Y ¹	
8-5-320.5	Slotted sampling or gauging wells	Y ¹	
8-5-320.5.2	The well requirements	Y ¹	
8-5-321	Primary seal requirements	Y ¹	
8-5-321.3	Metallic shoe type seals	Y ¹	
40 CFR 60 Subpart Kb	New Source Performance Standard for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction or Modification Commenced After July 23, 1984.		
60.110b(a)	Applicability and Designation of Affected Facility; Volatile organic liquid storage vessels > or = to 40 cubic meter, after 7/23/1984	Y	
60.112b(a)	Standard for Volatile Organic Compounds (VOC); Requirement for tanks-- > 151 cubic meter with maximum TVP >=5.2 kPa and <76.6; or >= 75 cubic meter and < 151 cubic meter with maximum TVP >= 27.6 kPa and < 76.6 kPa	Y	
60.112b(a)(1)	Rim Seals Mechanical shoe primary seal with rim mounted secondary	Y	
60.112b(a)(1)(i)	Requirements for internal floating roof resting or floating on liquid surface. Exempt if the floating roof is landed on its support legs. When roof is resting on support legs, filling, emptying, and refilling shall proceed as quickly as possible.	Y	
60.112b(a)(1)(ii)(B)	Requirement for two seals, one mounted above the other	Y	

IV. Source Specific Applicable Requirements

Table IV - E
Source-specific Applicable Requirements
S9, NAPHTHA STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.112b(a)(1)(iii)	Openings except for automatic bleeder vents and rim space vents must provide projection below liquid surface.	Y	
60.112b(a)(1)(iv)	Openings in internal floating roof	Y	
60.112b(a)(1)(v)	Automatic bleeder vents	Y	
60.112b(a)(1)(vi)	Rim space vents	Y	
60.112b(a)(1)(vii)	Sample wells	Y	
60.112b(a)(1)(viii)	Penetrations allowing for passage of columns	Y	
60.112b(a)(1)(ix)	Penetrations allowing for passage of ladders	Y	
60.113b	Testing and procedures	Y	
60.113b(a)	Inspections for internal floating roofs	Y	
60.113b(a)(1)	Testing and Procedures; Internal floating roof visual inspection before filling	Y	
60.113b(a)(2)	Testing and Procedures; Internal floating roof tanks with liquid mounted or mechanical shoe primary seal, annual inspection	Y	
60.113b(a)(3)(ii)	Testing and Procedures; Internal floating roof with double seal system, annual inspection	Y	
60.113b(a)(4)	Testing and Procedures; Internal floating roof inspections after emptied and degassed	Y	
60.113b(a)(5)	Testing and Procedures; Internal floating roof, 30 day notification for filling after inspection	Y	
60.115b	Reporting and Recordkeeping Requirements; 60.112b(a) tanks	Y	
60.115b(a)	Record keeping and reporting requirements	Y	
60.115b(a)(1)	Reporting and Recordkeeping Requirements; 60.112b(a) internal floating roof control equipment description and certification	Y	
60.115b(a)(2)	Reporting and Recordkeeping Requirements; 60.112b(a) internal floating roof inspection records	Y	
60.115b(a)(3)	Reporting and Recordkeeping Requirements; 60.112b(a) internal floating roof annual inspection defects report	Y	

IV. Source Specific Applicable Requirements

Table IV - E
Source-specific Applicable Requirements
S9, NAPHTHA STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.115b(a)(4)	Reporting and Recordkeeping Requirements; 60.112b(a) internal floating roof double seal system inspection defects report	Y	
60.116b	Monitoring of operations	Y	
60.116b(a)	Retention of record for two years	Y	
60.116b(b)	Records of dimensions and capacity	Y	
60.116b(c)	Records of VOL stored, period of storage, and maximum true vapor pressure	Y	
60.116b(e)(1)	Monitoring of Operations; Determine TVP-temperature selection based on tank operating temperatures	Y	
60.116b(e)(3)(i)	Monitoring of Operations; Determine TVP-other liquids-standard reference texts	Y	
60.116b(e)(3)(ii)	Monitoring of Operations; Determine TVP-other liquids-ASTM method	Y	
60.116b(e)(3)(iii)	Monitoring of Operations; Determine TVP-other liquids-other approved measurement method	Y	
60.116b(e)(3)(iv)	Monitoring of Operations; Determine TVP-other liquids-other approved calculation method	Y	
40 CFR 63 Subpart CC	National Emission Standards for Hazardous Pollutants for Petroleum Refining		
63.640(n)(1)	Compliance with 40 CFR Subpart Kb is compliance with this part except as provided in 40 CFR 60.640(n)(8).	Y	
63.640(n)(8)	Applicability and Designation of Affected Source Overlap for Storage Vessels--Additional requirements for Kb storage vessels	Y	
63.640(n)(8)(i)	Exemption from secondary seal requirements during gap measurements for primary seal	Y	
63.640(n)(8)(ii)	Structurally unsound roofs	Y	
63.640(n)(8)(iii)	Extensions for compliance	Y	
63.640(n)(8)(iv)	Additional reports if extension is used	Y	
63.640(n)(8)(v)	Subpart Kb reports may be submitted for this subpart. Permit holder has 60 days in lieu of Subpart Kb deadline.	Y	
63.640(n)(8)	Subpart Kb rim seal inspection reports not required if gaps do not	Y	

IV. Source Specific Applicable Requirements

Table IV - E
Source-specific Applicable Requirements
S9, NAPHTHA STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
(vi)	exceed limitations.		
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18c	Estimates of NMHC emissions from tanks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.25	Storage of Materials Other than Naphtha (Cumulative Increase, Toxics)	Y	
Part II.26	Vapor Pressure Limit (Cumulative Increase, Toxics)	Y	
Part II.27a	Internal Floating Roof Requirements (Cumulative Increase, NSPS)	Y	
Part II.28	Throughput Limit (Cumulative Increase, Toxics)	Y	
Part II.29	Recordkeeping (Cumulative Increase)	Y	

¹This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

IV. Source Specific Applicable Requirements

Table IV - F
Source-specific Applicable Requirements
S12-WASTEWATER TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Organic Compounds, Storage of Organic Liquids (12/15/99)		
8-5-117	Exemption, Low Vapor Pressure	Y	
8-5-501	Records	Y	
8-5-604	Determination of Applicability	Y	
40 CFR 61 Subpart FF	National Emission Standards for Benzene Waste Operations	Y	
61.343(a)	Standards: Tanks; Benzene-containing wastes	Y	
61.343(a)(1)	Standards: Tanks; Fixed Roof--with closed vent system	Y	
61.343(a)(1)(i)(B)	Standards: Tanks; Fixed Roof--No openings	Y	
61.343(a)(1)(ii)	Standards: Tanks; Closed-vent systems are subject to 61.349	Y	
61.343(c)	Standards: Tanks; Fixed roof quarterly inspection	Y	
61.343(d)	Standards: Tanks; Fixed roof repairs	Y	
61.349(a)	Standards: Closed-Vent Systems and Control Devices; Applicability	Y	
61.349(a)(1)	Standards: Closed-Vent Systems and Control Devices; Closed vent system requirements	Y	
61.349(a)(1)(ii)(B)	Car-sealed valves on bypass lines in closed-vent system	Y	
61.349(a)(1)(iii)	Gauging/sampling devices are gas-tight	Y	
61.349(a)(1)(iv)	Safety valve provisions	Y	
61.349(a)(2)	Standards: Closed-Vent Systems and Control Devices; Control device requirements	Y	
61.349(a)(2)(i)	Standards: Closed-Vent Systems and Control Devices; Enclosed combustion device requirements	Y	
61.349(a)(2)(i)(A)	Controlled by enclosed combustion device with greater than 95% control efficiency.	Y	
61.349(b)	Operated at all times.	Y	

IV. Source Specific Applicable Requirements

Table IV - F
Source-specific Applicable Requirements
S12-WASTEWATER TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
61.349(c)	Standards: Closed-Vent Systems and Control Devices; Control Device Performance Demonstration	Y	
61.349(c)(1)	Demonstrate efficiency required in 61.349(a)(2)	Y	
61.349(e)	Administrator may request performance tests	Y	
61.349(f)	Visually inspect for leaks quarterly	Y	
61.349(g)	Repair leaks: 5 days for first attempt; 15 days for complete repair	Y	
61.349(h)	Monitor per 61.354(c)	Y	
61.354(c)	Monitoring of Operations; Closed-vent systems and control devices—Continuously monitor control device operation	Y	
61.354(c)(1)	Monitor thermal vapor incinerator temperature	Y	
61.354(c)(4)	Monitoring of Operations; Boiler or process heaters	Y	
61.354(f)	Monitoring of Operations; Closed vent system with bypass line	Y	
61.354(f)(1)	Visually inspect carseal/valve positions monthly	Y	
61.356(a)	Recordkeeping and retention requirements	Y	
61.356(d)	Engineering design documentation for all control equipment	Y	
61.356(f)	Recordkeeping Requirements: Closed vent system and control device per 61.349--retain for life of device	Y	
61.356(f)(1)	Recordkeeping Requirements: certification of performance level	Y	
61.356(f)(2)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)(i)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)(i)(A)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis thermal vapor incinerator	Y	
61.356(f)(2)(i)(C)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis process heater	Y	
61.356(g)	Recordkeeping Requirements: Visual inspection per 61.343 through 61.347	Y	
61.356(h)	Recordkeeping Requirements: No detectable emissions tests per 61.343 through 61.347, and 61.349	Y	
61.356(j)	Recordkeeping Requirements: Control device operation	Y	
61.356(j)(1)	Recordkeeping Requirements: dates of startup and shutdown	Y	

IV. Source Specific Applicable Requirements

Table IV - F
Source-specific Applicable Requirements
S12-WASTEWATER TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
61.356(j)(2)	Recordkeeping Requirements: description of parameters	Y	
61.356(j)(3)	Recordkeeping Requirements: periods when closed vent system and control device are not operating	Y	
61.356(j)(3)(i)	Recordkeeping Requirements; Bypass Line Controls	Y	
61.356(j)(4)	Recordkeeping Requirements: Control device operation--Thermal vapor incinerator	Y	
61.356(j)(6)	Recordkeeping Requirements: Control device operation- process heater	Y	
61.357(d)(7)	Reporting Requirements: Quarterly report requirements	Y	
61.357(d)(7)(iv)	Reporting Requirements: Quarterly report--Control device monitored per 61.354(c)	Y	
61.357(d)(7)(iv)(A)	Reporting Requirements: Quarterly report--Thermal vapor incinerator	Y	
61.357(d)(7)(iv)(C)	Reporting Requirements: Quarterly report—process heater	Y	
61.357(d)(7)(iv)(G)	Reporting Requirements: change of location where vent stream is introduced into flame zone	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18e	Estimates of NMHC emissions from wastewater sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	

IV. Source Specific Applicable Requirements

Table IV - G
Source-specific Applicable Requirements
S13, KEROSENE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	N	
8-5-112	Limited Exemption, Tanks in Operation	N	
8-5-304	Storage tanks larger than 75 cubic meter	Y	
8-5-304.2	Storage tanks larger than 150 cubic meter storing liquid with a true vapor pressure greater than 25.8 mm Hg	Y	
8-5-311	Vapor Loss Control Device Requirements	Y	
8-5-311.3	An Approved Emission Control System which collects & processes all organic/gases	Y	
8-5-328	Tank Cleaning Requirements	Y	
8-5-328.1	Liquid balancing	Y	
8-5-328.2	An approved Emission Control System	Y	
8-5-329	Ozone Excess Day Prohibition	Y	
8-5-501	Records	Y	
SIP Regulation 8, Rule 5	Storage of Organic Liquids (8/25/97)		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	Y ¹	
8-5-112	Limited Exemption, Tanks in Operation	Y ¹	
40 CFR 60 Subpart Kb	New Source Performance Standard for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction or Modification Commenced After July 23, 1984.		
60.110b(a)	Applicability and Designation of Affected Facility; Volatile organic liquid storage vessels > or = to 40 cubic meter, after 7/23/1984	Y	
60.112b(a)(3)(i)	Standard for Volatile Organic Compounds (VOC); Closed vent system and control device no detectable emissions	Y	
60.112b(a)(3)(ii)	Standard for Volatile Organic Compounds (VOC); Closed vent system and control device >= 95% inlet VOC emission reduction	Y	
60.112b(b)	Standard for Volatile Organic Compounds (VOC); Requirements for tanks >= 75 cubic meter and maximum TVP >= 76.6 kPa	Y	

IV. Source Specific Applicable Requirements

Table IV - G
Source-specific Applicable Requirements
S13, KEROSENE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.112b(b)(1)	Standard for Volatile Organic Compounds (VOC); Closed vent system and control device option	Y	
60.113b(c)	Testing and Procedures; Closed vent system and control device (not flare)	Y	
60.113b(c)(1)	Testing and Procedures; Closed vent system and control device (not flare) operating plan submission	Y	
60.113b(c)(1)(i)	Testing and Procedures; Closed vent system and control device (not flare) operating plan--efficiency demonstration	Y	
60.113b(c)(1)(ii)	Testing and Procedures; Closed vent system and control device (not flare) operating plan--monitoring parameters	Y	
60.113b(c)(2)	Testing and Procedures; Closed vent system and control device (not flare) operate in accordance with operating plan	Y	
60.115b	Reporting and Recordkeeping Requirements; 60.112b(a) tanks	Y	
60.115b(c)(1)	Reporting and Recordkeeping Requirements; Closed vent system and control device (not flare) operating plan copy	Y	
60.115b(c)(2)	Reporting and Recordkeeping Requirements; Closed vent system and control device (not flare) operating records	Y	
60.116b(a)	Monitoring of Operations; Record retention	Y	
60.116b(b)	Monitoring of Operations; Permanent record requirements	Y	
60.116b(e)(1)	Monitoring of Operations; Determine TVP-temperature selection based on tank operating temperatures	Y	
60.116b(e)(2)(i)	Monitoring of Operations; Determine TVP-crude oil or refined petroleum products by API method	Y	
60.116b(e)(2)(ii)	Monitoring of Operations; Determine TVP-crude oil or refined petroleum products other than API method	Y	
60.116b(g)	Monitoring of Operations; Exemption from 116b(c) and 116b(d)	Y	
40 CFR 63 Subpart CC	National Emission Standards for Hazardous Air Pollutants for Petroleum Refineries (06/12/1996)		
63.640(n)(1)	Applicability and Designation of Affected Source Overlap for Storage Vessels--Existing Group 1 or Group 2 also subject to Kb only subject to Kb.	Y	
BAAQMD Condition			

IV. Source Specific Applicable Requirements

Table IV - G
Source-specific Applicable Requirements
S13, KEROSENE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
#1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18c	Estimates of NMHC emissions from tanks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.30	Storage of Materials other than Kerosene, Light or Heavy Vacuum Gas Oil, or Asphalt (Cumulative Increase, Toxics)	Y	
Part II.31	Vapor Pressure Limit (Cumulative Increase, Toxics)	Y	
Part II.32a	Control and Destruction Efficiency Requirement (Regulation 8-5-311.3, NSPS, Cumulative Increase, Toxics)	Y	
Part II.33a	Throughput Limit (Cumulative Increase, Toxics)	Y	
Part II.34	Recordkeeping (Cumulative Increase)	Y	

¹This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

Table IV - H
Source-specific Applicable Requirements
S14-LOADING RACKS, NAPHTHA

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 6	Organic Compounds-Organic Liquid Bulk Terminals and Bulk Plants (2/2/94)		
8-6-114	Maintenance and Repair exemption	Y	
8-6-301	Bulk Terminal Limitations	Y	
8-6-304	Deliveries to Storage Tanks	Y	
8-6-306	Equipment Maintenance	Y	

IV. Source Specific Applicable Requirements

Table IV - H
Source-specific Applicable Requirements
S14-LOADING RACKS, NAPHTHA

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-6-307	Operating Practices	Y	
8-6-501	Records	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18d	Estimates of NMHC emissions from loading racks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part I.19	Temperature monitoring (2-6-503)	Y	
Part I.19a	Allowable temperature excursions (2-1-403)	Y	
Part I.19b	Recordkeeping for allowable temperature excursions (2-1-403)	Y	
Part I.19c	Temperatures above the limit ((2-1-403)	Y	
Part II.59	Submerged fill pipe and abatement requirements <cumulative increase, offsets, BACT, toxics>	Y	
Part II.60	Destruction efficiency requirements <cumulative increase, offsets, BACT, toxics>	Y	
Part II.61a	Vapor pressure limit <cumulative increase, offsets, toxics>	Y	
Part II.61b	Throughput limit<cumulative increase>	Y	

IV. Source Specific Applicable Requirements

Table IV - I
Source-specific Applicable Requirements
S15, LOADING RACK-GAS OIL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 6	Organic Compounds-Organic Liquid Bulk Terminals and Bulk Plants (2/2/94)		
8-6-114	Maintenance and Repair exemption	Y	
8-6-301	Bulk Terminal Limitations	Y	
8-6-304	Deliveries to Storage Tanks	Y	
8-6-306	Equipment Maintenance	Y	
8-6-307	Operating Practices	Y	
8-6-501	Records	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18d	Estimates of NMHC emissions from loading racks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part I.19	Temperature monitoring (2-6-503)	Y	
Part I.19a	Allowable temperature excursions (2-1-403)	Y	
Part I.19b	Recordkeeping for allowable temperature excursions (2-1-403)	Y	
Part I.19c	Temperatures above the limit ((2-1-403)	Y	
Part II.62	Submerged fill pipe and abatement requirement ((BACT, Cumulative Increase, offsets, toxics)	Y	
Part II.63	Requirement for vapor recovery and abatement (BACT, Cumulative Increase, offsets)	Y	
Part II.64a	Vapor pressure limit (Cumulative Increase, offsets)	Y	
Part II.64b	Throughput limit	Y	

IV. Source Specific Applicable Requirements

Table IV - J
Source-specific Applicable Requirements
S16, LOADING RACKS, KEROSENE OR DISTILLATE OIL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18d	Estimates of NMHC emissions from loading racks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.90	Vapor Pressure Limit (Cumulative Increase)	Y	
Part II.91	Throughput Limit (Cumulative Increase)	Y	
Part II.91a	Recordkeeping (Cumulative Increase)	Y	

Table IV - K
Source-specific Applicable Requirements
S17, LOADING RACKS-ASPHALT

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD	Organic Compounds, Emulsified and Liquid Asphalts (9/16/87)		

IV. Source Specific Applicable Requirements

Table IV - K
Source-specific Applicable Requirements
S17, LOADING RACKS-ASPHALT

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Regulation 8, Rule 15			
8-15-305	Prohibition of Manufacture and Sale	Y	
8-15-501	Records	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18d	Estimates of NMHC emissions from loading racks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part I.19	Temperature monitoring (2-6-503)	Y	
Part I.19a	Allowable temperature excursions (2-1-403)	Y	
Part I.19b	Recordkeeping for allowable temperature excursions (2-1-403)	Y	
Part I.19c	Temperatures above the limit ((2-1-403)	Y	
Part II.8	Termination of asphalt loading when blowdown system is venting to A-4, Loading Rack Thermal Oxidizer. (Cumulative Increase)	Y	
Part II.65	Control Requirement (Cumulative Increase)	Y	
Part II.68	Destruction Efficiency Requirement (Cumulative Increase, BACT)	Y	
Part II.71	Vapor Pressure Requirement (Cumulative Increase, offsets)	Y	
Part II.74	Asphalt Throughput Requirement (Cumulative Increase, offsets)	Y	
Part II.75	Recordkeeping Requirement (Cumulative Increase)	Y	
Part IV.2	Asphalt truck inspections. (1-301)	N	
Part IV.3	Notification to trucking companies (1-301)	N	

IV. Source Specific Applicable Requirements

Table IV - L
Source-specific Applicable Requirements
S18, CRUDE UNIT

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 10	Organic Compound – Process Vessel Depressurization (7/20/83)		
8-10-301	Process Vessel Depressurizing. POC emissions shall be vented through a knock-out pot and then abated in one of the following ways, to as low a vessel pressure as possible, but at least until pressure is reduced to less than 1000 mm Hg:	Y	
8-10-301.1	recovery to the fuel gas system	Y	
8-10-301.2	combustion at a firebox or incinerator	Y	
8-10-301.3	combustion at a flare	Y	
8-10-301.4	containment such that emissions to atmosphere do not occur	Y	
8-10-401	Turnaround Records. The following records shall be kept for each process unit turnaround, and retained for at least 2 years and made available to the District on demand during inspections:	Y	
8-10-401.1	date of depressurization event	Y	
8-10-401.2	approximate vessel hydrocarbon concentration when emissions to atmosphere begin	Y	
8-10-401.3	approximate quantity of POC emissions to atmosphere	Y	
40 CFR 63 Subpart CC	National Emission Standards for Hazardous Pollutants for Petroleum Refining (8/18/95)		
63.643(a)	Miscellaneous Process Vent Provisions	Y	
63.643(a)(2)	Control device requirements	Y	
63.643(b)	Boiler or process heater requirements	Y	
63.644(a)	Monitoring Provisions for Miscellaneous Process Vents	Y	
63.644(a)(4)	Boiler or process heater < 44 MW	Y	
63.645(a)	Demonstrations of compliance	Y	
63.645(d)	Replacement of 63.116(b)(2) with 63.645(d)(2)	Y	
63.645(d)(2)	Boiler or process heater in which all vent streams introduced into flame zone	Y	
63.645(i)	Test Methods and Procedures for Miscellaneous Process-- Compliance determination for visible emissions	Y	
BAAQMD Condition #1240		Y	

IV. Source Specific Applicable Requirements

Table IV - L
Source-specific Applicable Requirements
S18, CRUDE UNIT

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part I.1	Annual Throughput Limit (Cumulative Increase, Toxics, <u>Offsets</u>)	Y	
Part I.2	Daily Throughput Limit (Cumulative Increase, Toxics)	Y	
Part I.3	Control Requirement (Cumulative Increase, Toxics)	Y	
Part I.4	Recordkeeping (Cumulative Increase)	Y	
Part I.7	Mechanical seals, packing, and compressor seals (Cumulative Increase)	Y	
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.16	Source Test Requirements for POC destruction (Cumulative Increase, Toxics)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NO _x , and SO ₂ estimates (Cumulative Increase)	Y	
Part I.18b	Estimates of NMHC emissions from sources of fugitive emissions (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.6	Safety Relief System (Cumulative Increase)	Y	

Table IV - M
Source-specific Applicable Requirements
S19, VACUUM HEATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-520	Continuous Emission Monitoring	Y	
1-520.8	Monitors required by Regulations 10, 12, and Section 2-1-403	Y	
1-522	Continuous Emission Monitoring and Recordkeeping Procedures	Y	
1-522.1	approval of plans and specifications	Y	

IV. Source Specific Applicable Requirements

Table IV - M
Source-specific Applicable Requirements
S19, VACUUM HEATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
1-522.2	scheduling requirements	Y	
1-522.3	CEM performance testing	Y	
1-522.4	reporting of inoperative CEMs	Y	
1-522.5	CEM calibration requirements	Y	
1-522.6	CEM accuracy requirements	Y	
1-522.7	emission limit exceedance reporting requirements	Y	
1-522.8	monitoring data submittal requirements	Y	
1-522.9	recordkeeping requirements	Y	
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-310.3	Heat Transfer Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 9, Rule 10	Inorganic Gaseous Pollutants - Nitrogen Oxides and Carbon Monoxide from Boilers, Steam Generators, and Process Heaters in Petroleum Refineries (1/5/94)		
9-10-301	Emission Limit for Facility, NOx: 0.033 lb NOx/MMBTU	Y	7/1/2002
9-10-301.1	...Start-up/Shutdown Contribution	Y	7/1/2002
9-10-301.2	...Out-of-Service Units Contribution	Y	7/1/2002
9-10-305	CO emission limit	Y	7/1/2002
9-10-401	Control Plan Requirements	Y	
9-10-403	Clean-Fuel Extension Compliance Date	Y	7/1/2002
9-10-501	Initial Demonstration of Compliance Schedule	Y	7/1/2002
9-10-502	Monitoring	Y	7/1/2002
9-10-502.1	CEMS for NOx, CO, and O2	Y	7/1/2002
9-10-502.2	Fuel flowmeters	Y	7/1/2002
9-10-504	Recordkeeping	Y	7/1/2002

IV. Source Specific Applicable Requirements

Table IV - M
Source-specific Applicable Requirements
S19, VACUUM HEATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
9-10-505	Reporting	Y	7/1/2002
9-10-601	Determination of Nitrogen Oxides	Y	
9-10-602	Determination of Carbon Monoxide and Stack-Gas Oxygen	Y	
9-10-603	Compliance Determination	Y	
BAAQMD Manual of Procedures, Volume V	Continuous Emission Monitoring Policy and Procedures (1/20/82)	Y	
40 CFR 60 Subpart A	General Provisions (2/12/98)		
60.13	Monitoring requirements	Y	
60.13(a)	Continuous monitoring systems subject to Appendix B, and Appendix F, (if used to demonstrate compliance with continuous emission limits), of Part 60	Y	
60.13(b)	Continuous monitoring systems and devices operational prior to performance tests required by 60.8	Y	
60.13(d)(1)	Continuous monitoring system zero and span calibration requirements	Y	
60.13(e)	Continuous monitoring system minimum frequency of operation	Y	
60.13(e)(2)	Continuous monitoring system minimum frequency of operation for non-opacity-measuring devices	Y	
60.13(f)	Continuous monitoring system installation location requirement	Y	
40 CFR 60 Subpart J	Standards of Performance for Petroleum Refineries (8/17/89)		
60.100(a)	Applicability: Claus Sulfur Recovery Plants, FCCU Catalyst Regenerators at Refineries and Fuel Gas Combustion Devices and Fuel Gas Combustion Devices of Refineries.	Y	
60.100(b)	Applicability: Constructed/modified after 6/11/1973	Y	
60.104	Standards for Sulfur Dioxide	Y	
60.104(a)(1)	fuel gas H2S concentration limited to 230 mg/dscm (0.10 gr/dscf) except for gas burned as a result of process upset or gas burned at flares from relief valve leaks or other emergency malfunctions	Y	
60.105	Monitoring of Emissions and Operations	Y	
60.105(a)(4)	monitoring requirement for H2S (dry basis) in fuel gas prior to	Y	

IV. Source Specific Applicable Requirements

Table IV - M
Source-specific Applicable Requirements
S19, VACUUM HEATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
	combustion (in lieu of separate combustion device exhaust SO2 monitors as required by 60.105(a)(3))		
60.105(e)	Determine and report periods of excess emissions.	Y	
60.105(e)(3)(ii)	Excess H2S in fuel gas	Y	
60.106	Test methods and procedures	Y	
60.106(a)	Test Methods and Procedures	Y	
60.106(e)(1)	Methods to determine compliance with the H2S standard in 60.104(a)(1).	Y	
60.107(e)	Semi-annual compliance report	Y	
60.107(f)	Certification of 60.107(e) report	Y	
40 CFR 60 Appendix B	Performance Specifications		
Performance Specification 3	O2 and CO2 continuous emission monitoring systems	Y	
Performance Specification 5	Total reduced sulfur (TRS) continuous emission monitoring systems	Y	
Performance Specification 7	H2S continuous emission monitoring systems	Y	
40 CFR 60 Appendix F	Quality Assurance Procedures		
Procedure 1	QA requirements for gas continuous emission monitoring systems	Y	
40 CFR 63 Subpart CC	National Emission Standards for Hazardous Pollutants for Petroleum Refining (8/18/95)		
63.643(a)(2)	Control device requirements	Y	
63.643(b)	Boiler or process heater requirements	Y	
63.644(a)	Monitoring Provisions for Miscellaneous Process Vents	Y	
63.644(a)(4)	Boiler or process heater < 44 MW	Y	
BAAQMD Condition #1240			

IV. Source Specific Applicable Requirements

Table IV - M
Source-specific Applicable Requirements
S19, VACUUM HEATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part I.3	Control Requirement (Cumulative Increase, Toxics)	Y	
Part I.5	Refinery Heat Input Limit (Cumulative Increase)	Y	
Part I.5a	S19 Heat Input Limit (Cumulative Increase)	Y	
Part I.5b	CO Concentration Limit (Cumulative Increase)	Y	
Part I.5c	Hourly CO Limit (Cumulative Increase)	Y	
Part I.6	Prohibition against combustion of fuel oil or diesel fuel (cumulative increase)	Y	
Part I.8	Low NOX Burner Requirement, NOX emission limit (Cumulative Increase)	Y	
Part I.10	Requirement for Continuous Recording Oxygen Analyzers (2-1-403)	Y	
Part I.11	H2S Limit for Refinery Fuel Gas, 3-hr average (NSPS)	Y	
Part I.12	H2S Limit for Refinery Fuel Gas, 24-hr average (BACT)	Y	
Part I.13	H2S Monitoring (NSPS, BACT)	Y	
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.16	Source Test Requirements for POC destruction (Cumulative Increase, Toxics)	Y	
Part I.16a	Source Test Requirements for NOX and CO limits (Cumulative Increase, Toxics)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18f	Estimates of NMHC emissions from combustion sources (Cumulative Increase)	Y	
Part I.18h	Estimates of NOx emissions from combustion sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part I.19	Temperature monitoring (2-6-503)	Y	
Part II.60	Destruction efficiency requirements <cumulative increase, offsets, BACT, toxics>	Y	
Part II.63	Requirement for vapor recovery and abatement (BACT, Cumulative Increase, offsets)	Y	
Part III.3	Limitation on H2S in gaseous fuel when vessels are in port (Cumulative Increase)	Y	

IV. Source Specific Applicable Requirements

¹This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

Table IV - N
Source-specific Applicable Requirements
S20, STEAM BOILER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-310.3	Heat Transfer Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 9, Rule 10	Inorganic Gaseous Pollutants - Nitrogen Oxides and Carbon Monoxide from Boilers, Steam Generators, and Process Heaters in Petroleum Refineries (1/5/94)		
9-10-301	Emission Limit for Facility, NOx: 0.033 lb NOx/MMBTU	Y	7/1/2002
9-10-301.1	...Start-up/Shutdown Contribution	Y	7/1/2002
9-10-301.2	...Out-of-Service Units Contribution	Y	7/1/2002
9-10-305	CO emission limit	Y	7/1/2002
9-10-401	Control Plan Requirements	Y	
9-10-403	Clean-Fuel Extension Compliance Date	Y	7/1/2002
9-10-501	Initial Demonstration of Compliance Schedule	Y	7/1/2002
9-10-502	Monitoring	Y	7/1/2002
9-10-502.1	CEMS for NOx, CO, and O2	Y	7/1/2002
9-10-502.2	Fuel flowmeters	Y	7/1/2002
9-10-504	Recordkeeping	Y	7/1/2002
9-10-505	Reporting	Y	7/1/2002
9-10-601	Determination of Nitrogen Oxides	Y	
9-10-602	Determination of Carbon Monoxide and Stack-Gas Oxygen	Y	

IV. Source Specific Applicable Requirements

Table IV - N
Source-specific Applicable Requirements
S20, STEAM BOILER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
9-10-603	Compliance Determination	Y	
BAAQMD Condition #1240			
Part I.5	Refinery Heat Input Limit (Cumulative Increase)	Y	
Part I.6	Prohibition against combustion of fuel oil or diesel fuel (cumulative increase)	Y	
Part I.10	Requirement for Continuous Recording Oxygen Analyzers (2-1-403)	Y	
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18f	Estimates of NMHC emissions from combustion sources (Cumulative Increase)	Y	
Part I.18h	Estimates of NOx emissions from combustion sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	

Table IV - O
Source-specific Applicable Requirements
S21, STEAM BOILER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	

IV. Source Specific Applicable Requirements

Table IV - O
Source-specific Applicable Requirements
S21, STEAM BOILER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-310	Particulate Weight Limitation	Y	
6-310.3	Heat Transfer Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 9, Rule 10	Inorganic Gaseous Pollutants - Nitrogen Oxides and Carbon Monoxide from Boilers, Steam Generators, and Process Heaters in Petroleum Refineries (1/5/94)		
9-10-301	Emission Limit for Facility, NOx: 0.033 lb NOx/MMBTU	Y	7/1/2002
9-10-301.1	...Start-up/Shutdown Contribution	Y	7/1/2002
9-10-301.2	...Out-of-Service Units Contribution	Y	7/1/2002
9-10-305	CO emission limit	Y	7/1/2002
9-10-401	Control Plan Requirements	Y	
9-10-403	Clean-Fuel Extension Compliance Date	Y	7/1/2002
9-10-501	Initial Demonstration of Compliance Schedule	Y	7/1/2002
9-10-502	Monitoring	Y	7/1/2002
9-10-502.1	CEMS for NOx, CO, and O2	Y	7/1/2002
9-10-502.2	Fuel flowmeters	Y	7/1/2002
9-10-504	Recordkeeping	Y	7/1/2002
9-10-505	Reporting	Y	7/1/2002
9-10-601	Determination of Nitrogen Oxides	Y	
9-10-602	Determination of Carbon Monoxide and Stack-Gas Oxygen	Y	
9-10-603	Compliance Determination	Y	
BAAQMD Condition #1240			
Part I.5	Refinery Heat Input Limit (Cumulative Increase)	Y	
Part I.6	Prohibition against combustion of fuel oil or diesel fuel (cumulative increase)	Y	
Part I.10	Requirement for Continuous Recording Oxygen Analyzers (2-1-403)	Y	
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18f	Estimates of NMHC emissions from combustion sources (Cumulative Increase)	Y	

IV. Source Specific Applicable Requirements

Table IV - O
Source-specific Applicable Requirements
S21, STEAM BOILER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part I.18h	Estimates of NOx emissions from combustion sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	

Table IV - P
Source-specific Applicable Requirements
S24, HOT OIL HEATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-310.3	Heat Transfer Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		
8-5-311	Vapor Loss Control Device Requirements	Y	
8-5-311.3	An Approved Emission Control System which collects & processes all organic/gases	Y	
BAAQMD	Inorganic Gaseous Pollutants - Nitrogen Oxides and Carbon		

IV. Source Specific Applicable Requirements

Table IV - P
Source-specific Applicable Requirements
S24, HOT OIL HEATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Regulation 9, Rule 10	Monoxide from Boilers, Steam Generators, and Process Heaters in Petroleum Refineries (1/5/94)		
9-10-111	Limited Exemption: Small Units: Between 1 and 10 MMBTU/hr and capable of firing fuel other than natural gas or LPG	Y	
9-10-217	Definition: Small Unit: Between 1 and 10 MMBTU/hr and capable of firing fuel other than natural gas or LPG	Y	
9-10-306	Small Unit Requirements	Y	7/1/02
9-10-402	Control Plan Requirements, Small Units	Y	7/1/02
9-10-403	Compliance Date, Clean-Fuel Extension Allowance	Y	
9-10-605	Tune-up Procedures	Y	
40 CFR 60 Subpart Kb	New Source Performance Standard for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction or Modification Commenced After July 23, 1984.		
60.110b(a)	Applicability and Designation of Affected Facility; Volatile organic liquid storage vessels > or = to 40 cubic meter, after 7/23/1984	Y	
60.112b(a)(3)(ii)	Standard for Volatile Organic Compounds (VOC); Closed vent system and control device >= 95% inlet VOC emission reduction	Y	
60.112b(b)(1)	Standard for Volatile Organic Compounds (VOC); Closed vent system and control device option	Y	
60.113b(c)	Testing and Procedures; Closed vent system and control device (not flare)	Y	
60.113b(c)(1)	Testing and Procedures; Closed vent system and control device (not flare) operating plan submission	Y	
60.113b(c)(1)(i)	Testing and Procedures; Closed vent system and control device (not flare) operating plan--efficiency demonstration	Y	
60.113b(c)(1)(ii)	Testing and Procedures; Closed vent system and control device (not flare) operating plan--monitoring parameters	Y	
60.113b(c)(2)	Testing and Procedures; Closed vent system and control device (not flare) operate in accordance with operating plan	Y	
60.115b(c)(1)	Reporting and Recordkeeping Requirements; Closed vent system and control device (not flare) operating plan copy	Y	
60.115b(c)(2)	Reporting and Recordkeeping Requirements; Closed vent system and control device (not flare) operating records	Y	

IV. Source Specific Applicable Requirements

Table IV - P
Source-specific Applicable Requirements
S24, HOT OIL HEATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.116b(a)	Monitoring of Operations; Record retention	Y	
NSPS Subpart UU	Standards of Performance for Asphalt Processing and Asphalt Roofing Manufacture (8/6/82)		
60.472(c)	Opacity standard	Y	
60.473(c)	Parametric monitoring	Y	
60.473(d)	Exemption from quarterly reports	Y	
BAAQMD Condition #1240			
Part I.5	Refinery Heat Input Limit (Cumulative Increase)	Y	
Part I.6	Prohibition against combustion of fuel oil or diesel fuel (cumulative increase)	Y	
Part I.10	Requirement for Continuous Recording Oxygen Analyzers (2-1-403)	Y	
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18g	Estimates of NMHC emissions from combustion sources (Cumulative Increase)	Y	
Part I.18i	Estimates of NOx emissions from combustion sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.32a	Requirement for control of S13 (8-5-311.3, NSPS, cumulative increase, toxics)	Y	
Part II.32b	Requirement for control of S59 (8-5-311.3, NSPS, cumulative increase, toxics)	Y	
Part II.32c	Requirement for control of S63 (8-5-311.3, NSPS, cumulative increase, offsets, BACT)	Y	
Part II.43	Control Requirement (BACT, Cumulative Increase, offsets)	Y	
Part II.44	Vapor recovery and fugitive emission requirement (BACT, Cumulative Increase, offsets)	Y	
Part II.55	Control and Destruction Efficiency Requirements (Cumulative Increase, Offsets)	Y	

IV. Source Specific Applicable Requirements

Table IV - P
Source-specific Applicable Requirements
S24, HOT OIL HEATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part II.56	Control and Destruction Efficiency Requirements (Cumulative Increase, Offsets)	Y	
Part II.57	Control and Destruction Efficiency Requirements (Cumulative Increase, Offsets)	Y	
Part II.58b	Continuous Temperature Monitoring (40 CFR 60.472(c))	Y	
Part II.58c	Allowable Temperature Excursions (2-1-403)	Y	
Part II.58d	Recordkeeping for Allowable Temperature Excursions (2-1-403)	Y	
Part II.58e	Definition of Allowable Temperature Excursions (2-1-403)	Y	
Part II.85	Vapor recovery and control requirement (BACT, cumulative increase, contemporaneous emission reductions)	Y	
Part V.1	NOX and CO limits	Y	

¹This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

IV. Source Specific Applicable Requirements

Table IV - Q
Source-specific Applicable Requirements
S25, EFFLUENT WATER FEED TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Organic Compounds, Storage of Organic Liquids (12/15/99)		
8-5-117	Exemption, Low Vapor Pressure	Y	
8-5-501	Records	Y	
8-5-604	Determination of Applicability	Y	
40 CFR 61 Subpart FF	National Emission Standards for Benzene Waste Operations		
61.343(a)	Standards: Tanks; Benzene-containing wastes	Y	
61.343(a)(1)	Standards: Tanks; Fixed Roof--with closed vent system	Y	
61.343(a)(1)(i)(B)	Standards: Tanks; Fixed Roof--No openings	Y	
61.343(a)(1)(ii)	Standards: Tanks; Closed-vent systems are subject to 61.349	Y	
61.343(c)	Standards: Tanks; Fixed roof quarterly inspection	Y	
61.343(d)	Standards: Tanks; Fixed roof repairs	Y	
61.349(a)	Standards: Closed-Vent Systems and Control Devices; Applicability	Y	
61.349(a)(1)	Standards: Closed-Vent Systems and Control Devices; Closed vent system requirements	Y	
61.349(a)(1)(ii)(B)	Car-sealed valves on bypass lines in closed-vent system	Y	
61.349(a)(1)(iii)	Gauging/sampling devices are gas-tight	Y	
61.349(a)(1)(iv)	Safety valve provisions	Y	
61.349(a)(2)	Standards: Closed-Vent Systems and Control Devices; Control device requirements	Y	
61.349(a)(2)(i)	Standards: Closed-Vent Systems and Control Devices; Enclosed combustion device requirements	Y	
61.349(a)(2)(i)(A)	Controlled by enclosed combustion device with greater than 95% control efficiency.	Y	
61.349(b)	Operated at all times.	Y	

IV. Source Specific Applicable Requirements

Table IV - Q
Source-specific Applicable Requirements
S25, EFFLUENT WATER FEED TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
61.349(c)	Standards: Closed-Vent Systems and Control Devices; Control Device Performance Demonstration	Y	
61.349(c)(1)	Demonstrate efficiency required in 61.349(a)(2)	Y	
61.349(e)	Administrator may request performance tests	Y	
61.349(f)	Visually inspect for leaks quarterly	Y	
61.349(g)	Repair leaks: 5 days for first attempt; 15 days for complete repair	Y	
61.349(h)	Monitor per 61.354(c)	Y	
61.354(c)	Monitoring of Operations; Closed-vent systems and control devices--Continuously monitor control device operation	Y	
61.354(c)(1)	Monitor thermal vapor incinerator temperature	Y	
61.354(c)(4)	Monitoring for a boiler or process heater having a design heat input capacity less than 44 MW	Y	
61.354(f)	Monitoring of Operations; Closed vent system with bypass line	Y	
61.354(f)(1)	Visually inspect carseal/valve positions monthly	Y	
61.356(a)	Recordkeeping and retention requirements	Y	
61.356(d)	Engineering design documentation for all control equipment	Y	
61.356(f)	Recordkeeping Requirements: Closed vent system and control device per 61.349--retain for life of device	Y	
61.356(f)(1)	Recordkeeping Requirements: Certification of performance level	Y	
61.356(f)(2)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)(i)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)(i)(A)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis thermal vapor incinerator	Y	
61.356(f)(2)(i)(C)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis process heater	Y	
61.356(g)	Recordkeeping Requirements: Visual inspection per 61.343 through 61.347	Y	
61.356(h)	Recordkeeping Requirements: No detectable emissions tests per 61.343 through 61.347, and 61.349	Y	
61.356(j)	Recordkeeping Requirements: Control device operation	Y	

IV. Source Specific Applicable Requirements

Table IV - Q
Source-specific Applicable Requirements
S25, EFFLUENT WATER FEED TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
61.356(j)(1)	Recordkeeping Requirements: dates of startup and shutdown	Y	
61.356(j)(2)	Recordkeeping Requirements: description of parameters	Y	
61.356(j)(3)	Recordkeeping Requirements: Control device operational upsets	Y	
61.356(j)(3)(i)	Recordkeeping Requirements; Bypass Line Controls	Y	
61.356(j)(4)	Recordkeeping Requirements: Control device operation—Thermal vapor incinerator	Y	
61.356(j)(6)	Recordkeeping Requirements: Control device operation- process heater	Y	
61.357(d)(7)	Reporting Requirements: Quarterly report requirements	Y	
61.357(d)(7)(iv)	Reporting Requirements: Quarterly report--Control device monitored per 61.354(c)	Y	
61.357(d)(7)(iv)(A)	Reporting Requirements: Quarterly report--Thermal vapor incinerator	Y	
61.357(d)(7)(iv)(C)	Reporting Requirements: Quarterly report--Thermal vapor incinerator—Process Heater	Y	
61.357(d)(7)(iv)(G)	Reporting Requirements: change of location where vent stream is introduced into flame zone	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18e	Estimates of NMHC emissions from wastewater sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.10	Control Requirement (Cumulative Increase)	Y	

IV. Source Specific Applicable Requirements

Table IV - R
Source-specific Applicable Requirements
S26, SKIMMED OIL TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Organic Compounds, Storage of Organic Liquids (01/20/1993)		
8-5-117	Exemption, Low Vapor Pressure	Y	
8-5-501	Records	Y	
8-5-604	Determination of Applicability	Y	
40 CFR 61 Subpart FF	National Emission Standards for Benzene Waste Operations		
61.343(a)	Standards: Tanks; Benzene-containing wastes	Y	
61.343(a)(1)	Standards: Tanks; Fixed Roof--with closed vent system	Y	
61.343(a)(1)(i)(B)	Standards: Tanks; Fixed Roof--No openings	Y	
61.343(a)(1)(ii)	Standards: Tanks; Closed-vent systems are subject to 61.349	Y	
61.343(c)	Standards: Tanks; Fixed roof quarterly inspection	Y	
61.343(d)	Standards: Tanks; Fixed roof repairs	Y	
61.349(a)	Standards: Closed-Vent Systems and Control Devices; Applicability	Y	
61.349(a)(1)	Standards: Closed-Vent Systems and Control Devices; Closed vent system requirements	Y	
61.349(a)(1)(ii)(B)	Car-sealed valves on bypass lines in closed-vent system	Y	
61.349(a)(1)(iii)	Gauging/sampling devices are gas-tight	Y	
61.349(a)(1)(iv)	Safety valve provisions	Y	
61.349(a)(2)	Standards: Closed-Vent Systems and Control Devices; Control device requirements	Y	
61.349(a)(2)(ii)	Controlled by vapor recovery: 95% VOC or 98% benzene control efficiency.	Y	
61.349(b)	Operated at all times.	Y	
61.349(e)	Administrator may request performance tests	Y	
61.349(f)	Visually inspect for leaks quarterly	Y	
61.349(g)	Repair leaks: 5 days for first attempt; 15 days for complete repair	Y	
61.349(h)	Monitor per 61.354(c)	Y	
61.354(d)	Non-regenerated carbon adsorption system requirements	Y	
61.354(f)	Monitoring of Operations; Closed vent system with bypass line	Y	
61.354(f)(1)	Visually inspect carseal/valve positions monthly	Y	
61.356(a)	Recordkeeping and retention requirements	Y	
61.356(d)	Engineering design documentation for all control equipment	Y	

IV. Source Specific Applicable Requirements

Table IV - R
Source-specific Applicable Requirements
S26, SKIMMED OIL TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
61.356(f)	Recordkeeping Requirements: Closed vent system and control device per 61.349--retain for life of device	Y	
61.356(f)(1)	Recordkeeping Requirements: Closed vent system and control device engineering calculations-- Certification of performance level	Y	
61.356(f)(2)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)(i)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)(i)(G)	Recordkeeping Requirements: Design analysis carbon absorption system without in-situ regeneration	Y	
61.356(g)	Recordkeeping Requirements: Visual inspection per 61.343 through 61.347	Y	
61.356(h)	Recordkeeping Requirements: No detectable emissions tests per 61.343 through 61.347, and 61.349	Y	
61.356(j)	Recordkeeping Requirements: Control device operation	Y	
61.356(j)(1)	Recordkeeping Requirements: Control device operation--dates of startup and shutdown	Y	
61.356(j)(2)	Recordkeeping Requirements: Control device operation--description of parameters	Y	
61.356(j)(3)	Recordkeeping Requirements: Control device operational upsets	Y	
61.356(j)(3)(i)	Recordkeeping Requirements; Bypass Line Controls	Y	
61.356(j)(10)	Recordkeeping Requirements: Control device operation--Carbon absorber without in situ regeneration	Y	
61.357(d)(7)	Reporting Requirements: Quarterly report requirements	Y	
61.357(d)(7)(iv)	Reporting Requirements: Quarterly report--Control device monitored per 61.354(c)	Y	
61.357(d)(7)(iv)(I)	Reporting Requirements--carbon not replaced at proper interval	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18e	Estimates of NMHC emissions from wastewater sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	

IV. Source Specific Applicable Requirements

Table IV - S
Source-specific Applicable Requirements
S27, RECOVERED OIL TANK-TK-12A ABATED BY CARBON

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Organic Compounds, Storage of Organic Liquids (01/20/1993)		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	Y	
8-5-111.1	Limited Exemption, Tank Removal From and Return to Service, 3 day prior written notice	Y	
8-5-111.2	Limited Exemption, Tank Removal From and Return to Service, Tank in compliance prior to notification	Y	
8-5-111.4	Limited Exemption, Tank Removal From and Return to Service, Vapor recovery-equipped tanks	Y	
8-5-111.5	Limited Exemption, Tank Removal From and Return to Service, Minimize emissions	Y	
8-5-111.6	Limited Exemption, Tank Removal From and Return to Service, Notice of completion not required	Y	
8-5-112	Limited Exemption, Tanks in Operation	Y	
8-5-112.1	Limited Exemption, Tanks in Operation, Tank in compliance prior to start of work. Certified per 8-5-404	Y	
8-5-112.2	Limited Exemption, Tanks in Operation, No product movement, Minimize emissions	Y	
8-5-112.3	Limited Exemption, Tanks in Operation, Not to exceed 7 days	Y	
8-5-301	Storage Tanks Smaller than 150m ³	Y	
8-5-301.3	Storage Tanks Smaller than 150 cubic meter with vapor loss control device in compliance with 8-5-311	Y	
8-5-311	Vapor loss control device requirements	Y	
8-5-311.3	Vapor Loss Control Device Requirements; Approved emission control system	Y	
8-5-501	Records	Y	
8-5-603.1	Determination of Emissions; Organic compounds specified in 8-5-311.3	Y	
40 CFR 61 Subpart FF	National Emission Standards for Benzene Waste Operations		
61.343(a)	Standards: Tanks; Benzene-containing wastes	Y	
61.343(a)(1)	Standards: Tanks; Fixed Roof--with closed vent system	Y	
61.343(a)(1)(i)(B)	Standards: Tanks; Fixed Roof--No openings	Y	
61.343(a)(1)(ii)	Standards: Tanks; Closed-vent systems are subject to 61.349	Y	
61.343(c)	Standards: Tanks; Fixed roof quarterly inspection	Y	
61.343(d)	Standards: Tanks; Fixed roof repairs	Y	

IV. Source Specific Applicable Requirements

Table IV - S
Source-specific Applicable Requirements
S27, RECOVERED OIL TANK-TK-12A ABATED BY CARBON

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
61.349(a)	Standards: Closed-Vent Systems and Control Devices; Applicability	Y	
61.349(a)(1)	Standards: Closed-Vent Systems and Control Devices; Closed vent system requirements	Y	
61.349(a)(1)(ii) (B)	Car-sealed valves on bypass lines in closed-vent system	Y	
61.349(a)(1)(iii)	Gauging/sampling devices are gas-tight	Y	
61.349(a)(1)(iv)	Safety valve provisions	Y	
61.349(a)(2)	Standards: Closed-Vent Systems and Control Devices; Control device requirements	Y	
61.349(a)(2)(ii)	Controlled by vapor recovery: 95% VOC or 98% benzene control efficiency.	Y	
61.349(b)	Operated at all times.	Y	
61.349(c)	Standards: Closed-Vent Systems and Control Devices; Control Device Performance Demonstration	Y	
61.349(c)(1)	Demonstrate efficiency required in 61.349(a)(2)	Y	
61.349(e)	Administrator may request performance tests	Y	
61.349(f)	Visually inspect for leaks quarterly	Y	
61.349(g)	Repair leaks: 5 days for first attempt; 15 days for complete repair	Y	
61.349(h)	Monitor per 61.354(c)	Y	
61.354(d)	Non-regenerated carbon adsorption system requirements	Y	
61.354(f)	Monitoring of Operations; Closed vent system with bypass line	Y	
61.354(f)(1)	Visually inspect carseal/valve positions monthly	Y	
61.356(a)	Recordkeeping and retention requirements	Y	
61.356(d)	Engineering design documentation for all control equipment	Y	
61.356(f)	Recordkeeping Requirements: Closed vent system and control device per 61.349--retain for life of device	Y	
61.356(f)(1)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)(i)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)(i) (G)	Recordkeeping Requirements: Design analysis carbon absorption system without in-situ regeneration	Y	
61.356(g)	Recordkeeping Requirements: Visual inspection per 61.343 through 61.347	Y	
61.356(h)	Recordkeeping Requirements: No detectable emissions tests per 61.343 through 61.347, and 61.349	Y	
61.356(j)	Recordkeeping Requirements: Control device operation	Y	

IV. Source Specific Applicable Requirements

Table IV - S
Source-specific Applicable Requirements
S27, RECOVERED OIL TANK-TK-12A ABATED BY CARBON

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
61.356(j)(1)	Recordkeeping Requirements: Control device operation-dates of startup and shutdown	Y	
61.356(j)(2)	Recordkeeping Requirements: Control device operation-description of parameters	Y	
61.356(j)(3)	Recordkeeping Requirements: Control device operational upsets	Y	
61.356(j)(3)(i)	Recordkeeping Requirements; Bypass Line Controls	Y	
61.356(j)(10)	Recordkeeping Requirements: Control device operation--Carbon absorber without in situ regeneration	Y	
61.357(d)(7)	Reporting Requirements: Quarterly report requirements	Y	
61.357(d)(7)(iv)	Reporting Requirements: Quarterly report--Control device monitored per 61.354(c)	Y	
61.357(d)(7)(iv)(I)	Reporting Requirements	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18e	Estimates of NMHC emissions from wastewater sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	

IV. Source Specific Applicable Requirements

Table IV – T
Source-specific Applicable Requirements
S28, EFFLUENT WATER FEED TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Organic Compounds, Storage of Organic Liquids (01/20/1993)		
8-5-117	Exemption, Low Vapor Pressure	Y	
8-5-501	Records	Y	
8-5-604	Determination of Applicability	Y	
40 CFR 61 Subpart FF	National Emission Standards for Benzene Waste Operations		
61.343(a)	Standards: Tanks; Benzene-containing wastes	Y	
61.343(a)(1)	Standards: Tanks; Fixed Roof--with closed vent system	Y	
61.343(a)(1)(i)(B)	Standards: Tanks; Fixed Roof--No openings	Y	
61.343(a)(1)(ii)	Standards: Tanks; Closed-vent systems are subject to 61.349	Y	
61.343(c)	Standards: Tanks; Fixed roof quarterly inspection	Y	
61.343(d)	Standards: Tanks; Fixed roof repairs	Y	
61.349(a)	Standards: Closed-Vent Systems and Control Devices; Applicability	Y	
61.349(a)(1)	Standards: Closed-Vent Systems and Control Devices; Closed vent system requirements	Y	
61.349(a)(1)(i)(A)	Standards: Closed-Vent Systems and Control Devices--Closed vent systems---No detectable emissions \geq 500 ppmv; annual inspection	Y	
61.349(a)(1)(ii)(B)	Car-sealed valves on bypass lines in closed-vent system	Y	
61.349(a)(1)(iii)	Gauging/sampling devices are gas-tight	Y	
61.349(a)(1)(iv)	Safety valve provisions	Y	
61.349(a)(2)	Standards: Closed-Vent Systems and Control Devices; Control device requirements	Y	
61.349(a)(2)(i)	Standards: Closed-Vent Systems and Control Devices; Enclosed combustion device requirements	Y	
61.349(a)(2)(i)(A)	Controlled by enclosed combustion device with greater than 95% control efficiency.	Y	
61.349(b)	Operated at all times.	Y	
61.349(c)	Standards: Closed-Vent Systems and Control Devices; Control Device Performance Demonstration	Y	
61.349(c)(1)	Demonstrate efficiency required in 61.349(a)(2)	Y	
61.349(e)	Administrator may request performance tests	Y	
61.349(f)	Visually inspect for leaks quarterly	Y	

IV. Source Specific Applicable Requirements

Table IV – T
Source-specific Applicable Requirements
S28, EFFLUENT WATER FEED TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
61.349(g)	Repair leaks: 5 days for first attempt; 15 days for complete repair	Y	
61.349(h)	Monitor per 61.354(c)	Y	
61.354(c)	Monitoring of Operations; Closed-vent systems and control devices--Continuously monitor control device operation	Y	
61.354(c)(1)	Monitor thermal vapor incinerator temperature	Y	
61.354(c)(4)	Monitoring for a boiler or process heater having a design heat input capacity less than 44 MW	Y	
61.354(f)	Monitoring of Operations; Closed vent system with bypass line	Y	
61.354(f)(1)	Visually inspect carseal/valve positions monthly	Y	
61.356(a)	Recordkeeping and retention requirements	Y	
61.356(d)	Engineering design documentation for all control equipment	Y	
61.356(f)	Recordkeeping Requirements: Closed vent system and control device per 61.349--retain for life of device	Y	
61.356(f)(1)	Recordkeeping Requirements: certification of performance level	Y	
61.356(f)(2)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)(i)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)(i)(A)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis thermal vapor incinerator	Y	
61.356(g)	Recordkeeping Requirements: Visual inspection per 61.343 through 61.347	Y	
61.356(h)	Recordkeeping Requirements: No detectable emissions tests per 61.343 through 61.347, and 61.349	Y	
61.356(j)	Recordkeeping Requirements: Control device operation	Y	
61.356(j)(1)	Recordkeeping Requirements: dates of startup and shutdown	Y	
61.356(j)(2)	Recordkeeping Requirements: description of parameters	Y	
61.356(j)(3)	Recordkeeping Requirements: Control device operational upsets	Y	
61.356(j)(3)(i)	Recordkeeping Requirements; Bypass Line Controls	Y	
61.356(j)(4)	Recordkeeping Requirements: Control device operation--Thermal vapor incinerator	Y	
61.357(d)(7)	Reporting Requirements: Quarterly report requirements	Y	
61.357(d)(7)(iv)	Reporting Requirements: Quarterly report--Control device monitored per 61.354(c)	Y	
61.357(d)(7)(iv)(A)	Reporting Requirements: Quarterly report--Thermal vapor incinerator	Y	
61.357(d)(7)(iv)(C)	Reporting Requirements	Y	

IV. Source Specific Applicable Requirements

Table IV – T
Source-specific Applicable Requirements
S28, EFFLUENT WATER FEED TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18e	Estimates of NMHC emissions from wastewater sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	

Table IV - U
Source-specific Applicable Requirements
S29, NAPHTHA MEROX TREATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 10	Organic Compound – Process Vessel Depressurization (7/20/83)		
8-10-301	Process Vessel Depressurizing. POC emissions shall be vented through a knock-out pot and then abated in one of the following ways, to as low a vessel pressure as possible, but at least until pressure is reduced to less than 1000 mm Hg:	Y	
8-10-301.1	recovery to the fuel gas system	Y	
8-10-301.2	combustion at a firebox or incinerator	Y	
8-10-301.3	combustion at a flare	Y	
8-10-301.4	containment such that emissions to atmosphere do not occur	Y	
8-10-401	Turnaround Records. The following records shall be kept for each process unit turnaround, and retained for at least 2 years and made available to the District on demand during inspections:	Y	
8-10-401.1	date of depressurization event	Y	
8-10-401.2	approximate vessel hydrocarbon concentration when emissions to	Y	

IV. Source Specific Applicable Requirements

Table IV - U
Source-specific Applicable Requirements
S29, NAPHTHA MEROX TREATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
	atmosphere begin		
8-10-401.3	approximate quantity of POC emissions to atmosphere	Y	
BAAQMD Condition #1240			
Part I.7	Mechanical seals, packing, and compressor seals (Cumulative Increase)	Y	
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NO _x , and SO ₂ estimates (Cumulative Increase)	Y	
Part I.18b	Estimates of NMHC emissions from sources of fugitive emissions (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	

Table IV - V
Source-specific Applicable Requirements
S30, MARINE LOADING DOCK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
NESHAPS Part 63 Subpart Y	National Emission Standards for Marine Tank Vessel Loading Operations	Y	
63.560(a)	Maximum Achievable Control Technology (MACT) Applicability	Y	
63.560(a)(2)	MACT does not apply to existing sources with emissions < 10 or 25 tons	Y	
63.560(a)(3)	Record keeping in 63.567(j)(4) and emission estimation in 63.565(l) apply to existing sources < 10 and 25 tons of hazardous air pollutants	Y	

IV. Source Specific Applicable Requirements

Table IV - V
Source-specific Applicable Requirements
S30, MARINE LOADING DOCK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
63.560(b)	Applicability and Designation of Affected Source	Y	
63.560(b)(2)	RACT Standards do not Apply to Marine Loading Operations with Throughput Less Than 10 M and 200 M Barrels	Y	
63.565(l)	Emission estimation procedures	Y	
63.567(j)(4)	Retain records of emission estimates per 63.565(l), and actual throughputs, by commodity, for 5 years	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part III.1	Limitation on number of ships and weight (Cumulative Increase)	Y	
Part III.2	Limitation on sulfur content of fuel oil for ship engines. Use of dedicated tanks for ballasting (Cumulative Increase)	Y	
Part III.3	Limitation on H2S in gaseous fuel when vessels are in port (Cumulative Increase)	Y	
Part III.4	Access to tankers (Regulation 1-440)	Y	
Part III.5	Monthly reports (Cumulative Increase)	Y	
Part III.6	Throughput limit and limit on number of barges per month (Cumulative Increase)	Y	
Part III.7	Prohibition against loading organic liquids as defined by Regulation 8-44-204 (Synthetic Minor Condition)	Y	
Part III.8	Prohibition against loading into vessels with a prior cargo of organic liquids as defined by Regulation 8-44-204 (Synthetic Minor Condition)	Y	
Part III.9	Recordkeeping (Cumulative Increase)	Y	

IV. Source Specific Applicable Requirements

Table IV - W
Source-specific Applicable Requirements
S31, RAIL CAR ASPHALT LOADING RACK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 6	Organic Liquid Bulk Terminals And Bulk Plants (2/2/94)		
8-6-114	Exemption, Maintenance and Repair	Y	
8-6-301	Bulk Terminal Limitations	Y	
8-6-305	Delivery Vehicle Requirements	Y	
8-6-306	Equipment Maintenance	Y	
8-6-307	Operating Practices	Y	
8-6-501	Efficiency and Rate Determination	Y	
BAAQMD Regulation 8, Rule 15	Organic Compounds, Emulsified and Liquid Asphalts (9/16/87)		
8-15-305	Prohibition of Manufacture and Sale	Y	
8-15-501	Records	Y	
BAAQMD Condition #1240			
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18d	Estimates of NMHC emissions from loading racks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.66	Control Requirement (Cumulative Increase)	Y	
Part II.69	Destruction Efficiency Requirement (Cumulative Increase, BACT)	Y	
Part II.72	Vapor Pressure Requirement (Cumulative Increase, offsets, toxics)	Y	
Part II.73	Vapor Pressure Requirement for Asphalt (Cumulative Increase, offsets, toxics)		
Part II.74	Asphalt Throughput Requirement	Y	

IV. Source Specific Applicable Requirements

Table IV - W
Source-specific Applicable Requirements
S31, RAIL CAR ASPHALT LOADING RACK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part II.75	Recordkeeping Requirement (Cumulative Increase)	Y	

Table IV - X
Source-specific Applicable Requirements
S32, LGO STRIPPER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 10	Organic Compound – Process Vessel Depressurization (7/20/83)		
8-10-301	Process Vessel Depressurizing. POC emissions shall be vented through a knock-out pot and then abated in one of the following ways, to as low a vessel pressure as possible, but at least until pressure is reduced to less than 1000 mm Hg:	Y	
8-10-301.1	recovery to the fuel gas system	Y	
8-10-301.2	combustion at a firebox or incinerator	Y	
8-10-301.3	combustion at a flare	Y	
8-10-301.4	containment such that emissions to atmosphere do not occur	Y	
8-10-401	Turnaround Records. The following records shall be kept for each process unit turnaround, and retained for at least 2 years and made available to the District on demand during inspections:	Y	
8-10-401.1	date of depressurization event	Y	
8-10-401.2	approximate vessel hydrocarbon concentration when emissions to atmosphere begin	Y	
8-10-401.3	approximate quantity of POC emissions to atmosphere	Y	
40 CFR 63 Subpart CC	National Emission Standards for Hazardous Pollutants for Petroleum Refining (8/18/95)		
63.643(a)	Miscellaneous Process Vent Provisions	Y	
63.643(a)(2)	Control device requirements	Y	
63.643(b)	Boiler or process heater requirements	Y	

IV. Source Specific Applicable Requirements

Table IV - X
Source-specific Applicable Requirements
S32, LGO STRIPPER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
63.644(a)	Monitoring Provisions for Miscellaneous Process Vents	Y	
63.644(a)(4)	Boiler or process heater < 44 MW	Y	
63.645(c)	Organic HAPs in Subpart CC shall be considered	Y	
63.645(d)	This subsection governs instead of 63.116(b)(1) or (b)(2)	Y	
63.645(d)(2)	Any boiler or process heater in which all vent streams are introduced into the flame zone	Y	
63.645(i)	Test Methods and Procedures for Miscellaneous Process-- Compliance determination for visible emissions	Y	
63.654(h)(1)	Reporting and Recordkeeping Requirements--Other reports--Startup, shutdowns and malfunction	Y	
BAAQMD Condition #1240			
Part I.7	Mechanical seals, packing, and compressor seals (Cumulative Increase)	Y	
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.16	Source Test Requirements for POC destruction (Cumulative Increase, Toxics)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18b	Estimates of NMHC emissions from sources of fugitive emissions (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.6	Safety Relief System (Cumulative Increase)	Y	

IV. Source Specific Applicable Requirements

Table IV - Y
Source-specific Applicable Requirements
S34, TANK HEATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-310.3	Heat Transfer Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 9, Rule 10	Inorganic Gaseous Pollutants - Nitrogen Oxides and Carbon Monoxide from Boilers, Steam Generators, and Process Heaters in Petroleum Refineries (1/5/94)		
9-10-110.1	Exemptions	Y	
BAAQMD Condition #1240			
Part I.5	Refinery Heat Input Limit (Cumulative Increase)	Y	
Part I.6	Prohibition against combustion of fuel oil or diesel fuel (cumulative increase)	Y	
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18g	Estimates of NMHC emissions from combustion sources (Cumulative Increase)	Y	
Part I.18i	Estimates of NOx emissions from combustion sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	

IV. Source Specific Applicable Requirements

Table IV - Z
Source-specific Applicable Requirements
S39, LUBE OIL TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Organic Compounds, Storage of Organic Liquids (12/15/99)		
8-5-117	Exemption, Low Vapor Pressure	Y	
8-5-501	Records	Y	
8-5-604	Determination of Applicability	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	

Table IV - AA
Source-specific Applicable Requirements
S40, LATEX STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Organic Compounds, Storage of Organic Liquids (12/15/99)		
8-5-117	Exemption, Low Vapor Pressure	Y	
8-5-501	Records	Y	
8-5-604	Determination of Applicability	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	

IV. Source Specific Applicable Requirements

Table IV - AB
Source-specific Applicable Requirements
S41, WEMCO HYDROTREATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 8	Wastewater (Oil-Water) Separators (6/15/94)		
8-8-303	Gauging and Sampling Devices	Y	
8-8-307	Air Flotation Unit	Y	
8-8-307.2	Combined collection and destruction efficiency of 70% by weight	Y	
8-8-501	API Separator or Air Flotation Bypassed Wastewater Records	Y	
8-8-503	Inspection and Repair Records	Y	
8-8-504	Portable Hydrocarbon Detector	Y	
8-8-603	Inspection Procedures	Y	
40 CFR 61 Subpart FF	National Emission Standards for Benzene Waste Operations		
61.347(a)	Except as provided in 61.352 of this subpart, each oil-water separator shall meet the following standards:	Y	
61.347(a)(1)	Install, operate, and maintain a fixed-roof and closed vent system that routes all organic vapors vented from the oil-water separator to a control device.	Y	
61.347(a)(1)(i)(B)	Standards: Oil-Water Separators; Fixed roof--No openings	Y	
61.347(a)(1)(ii)	Closed-vent systems are subject to 61.349.	Y	
61.347(b)	Cover seals, access hatches , and other openings shall be checked visually initially and quarterly thereafter to ensure no cracks, gaps occur between the cover and wall and that access hatches are closed and gasketed properly.	Y	
61.347(c)	except for delay or repair, when a broken seal or gasket or other problem is identified, or when detectable emissions are measured, first efforts repairs shall be made AS SOON AS POSSIBLE, but not later than 15 calendar days after identification	Y	
61.349(a)	Standards: Closed-Vent Systems and Control Devices; Applicability	Y	
61.349(a)(1)	Standards: Closed-Vent Systems and Control Devices; Closed vent system requirements	Y	
61.349(a)(1)	Car-sealed valves on bypass lines in closed-vent system	Y	

IV. Source Specific Applicable Requirements

Table IV - AB
Source-specific Applicable Requirements
S41, WEMCO HYDROTREATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
(ii)(B)			
61.349(a)(1)(iii)	Gauging/sampling devices are gas-tight	Y	
61.349(a)(1)(iv)	Safety valve provisions	Y	
61.349(a)(2)	Standards: Closed-Vent Systems and Control Devices; Control device requirements	Y	
61.349(a)(2)(i)	Standards: Closed-Vent Systems and Control Devices; Enclosed combustion device requirements	Y	
61.349(a)(2)(i)(A)	Controlled by enclosed combustion device with greater than 95% control efficiency.	Y	
61.349(b)	Operated at all times.	Y	
61.349(c)	Standards: Closed-Vent Systems and Control Devices; Control Device Performance Demonstration	Y	
61.349(c)(1)	Demonstrate efficiency required in 61.349(a)(2)	Y	
61.349(e)	Administrator may request performance tests	Y	
61.349(f)	Visually inspect for leaks quarterly	Y	
61.349(g)	Repair leaks: 5 days for first attempt; 15 days for complete repair	Y	
61.349(h)	Monitor per 61.354(c)	Y	
61.354(c)	Monitoring of Operations; Closed-vent systems and control devices- -Continuously monitor control device operation	Y	
61.354(c)(1)	Monitor thermal vapor incinerator temperature	Y	
61.354(f)	Monitoring of Operations; Closed vent system with bypass line	Y	
61.354(f)(1)	Visually inspect carseal/valve positions monthly	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18e	Estimates of NMHC emissions from wastewater sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance	Y	

IV. Source Specific Applicable Requirements

Table IV - AB
Source-specific Applicable Requirements
S41, WEMCO HYDROTREATER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
	(Cumulative Increase)		
Part II.92	Throughput Limit (Cumulative Increase)	Y	
Part II.92a	Recordkeeping (Cumulative Increase)	Y	

Table IV - AC
Source-specific Applicable Requirements
S51, S52, S53, S60, SALES TANKS-ASPHALT LIQUID

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 5	Organic Compounds, Storage of Organic Liquids (12/15/99)		
8-5-117	Exemption, Low Vapor Pressure	Y	
8-5-501	Records	Y	
8-5-604	Determination of Applicability	Y	
BAAQMD Regulation 8, Rule 15	Organic Compounds, Emulsified and Liquid Asphalts (9/16/87)		
8-15-305	Prohibition of Manufacture and Sale	Y	
8-15-501	Records	Y	
NSPS Subpart UU	Standards of Performance for Asphalt Processing and Asphalt Roofing Manufacture (8/6/82)		
60.472(c)	Opacity standard	Y	
60.473(c)	Parametric monitoring	Y	
60.473(d)	Exemption from quarterly reports	Y	

IV. Source Specific Applicable Requirements

Table IV - AC
Source-specific Applicable Requirements
S51, S52, S53, S60, SALES TANKS-ASPHALT LIQUID

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
40 CFR 63 Subpart CC	National Emission Standards for Hazardous Pollutants for Petroleum Refining (8/18/95)		
63.646(b)(1)	Storage Vessel Provisions--Determine stored liquid % OHAP for group determination	Y	
63.646(b)(2)	Storage Vessel Provisions--Determine stored liquid % OHAP-method 18 to resolve disputes	Y	
63.654(i)(1)	Reporting and Recordkeeping Requirements--Recordkeeping for storage vessels	Y	
63.654(i)(1)(iv)	Reporting and Recordkeeping Requirements--Recordkeeping for storage vessels	Y	
63.654(i)(4)	Reporting and Recordkeeping Requirements--Recordkeeping--Record retention	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18c	Estimates of NMHC emissions from tanks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.48	Throughput Limit (Cumulative Increase, Offsets)	Y	
Part II.49	Prohibition against cutback asphalt (Toxics)	Y	
Part II.50	Vapor Pressure Limit (Cumulative Increase, Offsets, <i>NSPS</i>)	Y	
Part II.56	Control and Destruction Efficiency Requirements (Cumulative Increase, Offsets)	Y	
Part II.58	Recordkeeping Requirement (Cumulative Increase)	Y	
Part II.58b	Continuous Temperature Monitoring (40 CFR 60.472(e))	Y	
Part II.58c	Allowable Temperature Excursions (2-1-403)	Y	
Part II.58d	Recordkeeping for Allowable Temperature Excursions (2-1-403)	Y	
Part II.58e	Definition of Allowable Temperature Excursions (2-1-403)	Y	

IV. Source Specific Applicable Requirements

Table IV - AD
Source-specific Applicable Requirements
S54, ASPHALT LOADING RACK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 6	Organic Liquid Bulk Terminals And Bulk Plants (2/2/94)		
8-6-114	Exemption, Maintenance and Repair	Y	
8-6-301	Bulk Terminal Limitations	Y	
8-6-305	Delivery Vehicle Requirements	Y	
8-6-306	Equipment Maintenance	Y	
8-6-307	Operating Practices	Y	
8-6-501	Efficiency and Rate Determination	Y	
BAAQMD Regulation 8, Rule 15	Organic Compounds, Emulsified and Liquid Asphalts (9/16/87)		
8-15-305	Prohibition of Manufacture and Sale	Y	
8-15-501	Records	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18d	Estimates of NMHC emissions from loading racks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.67	Control Requirement (Cumulative Increase)	Y	
Part II.70	Destruction Efficiency Requirement (Cumulative Increase, BACT)	Y	
Part II.71	Vapor Pressure Requirement (Cumulative Increase, offsets)	Y	
Part II.74	Asphalt Throughput Requirement	Y	

IV. Source Specific Applicable Requirements

Table IV - AD
Source-specific Applicable Requirements
S54, ASPHALT LOADING RACK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part II.75	Recordkeeping Requirement (Cumulative Increase)	Y	
Part IV.2	Asphalt truck inspections. (1-301)	N	
Part IV.3	Notification to trucking companies (1-301)	N	

Table IV - AE
Source-specific Applicable Requirements
S59, TANK #5

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	N	
8-5-112	Limited Exemption, Tanks in Operation	N	
8-5-304	Storage tanks larger than 75 cubic meter	Y	
8-5-304.2	Storage tanks larger than 150 cubic meter storing liquid with a true vapor pressure greater than 25.8 mm Hg	Y	
8-5-311	Vapor Loss Control Device Requirements	Y	
8-5-311.3	An Approved Emission Control System which collects & processes all organic/gases	Y	
8-5-328	Tank Cleaning Requirements	Y	
8-5-328.1	Liquid balancing	Y	
8-5-328.2	An approved Emission Control System	Y	
8-5-329	Ozone Excess Day Prohibition	Y	
8-5-501	Records	Y	
SIP Regulation 8, Rule 5	Storage of Organic Liquids (8/25/97)		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	Y ¹	
8-5-112	Limited Exemption, Tanks in Operation	Y ¹	
40 CFR 60	New Source Performance Standard for Storage Vessels for		

IV. Source Specific Applicable Requirements

Table IV - AE
Source-specific Applicable Requirements
S59, TANK #5

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Subpart Kb	Petroleum Liquids for Which Construction, Reconstruction or Modification Commenced After July 23, 1984.		
60.110b(a)	Applicability and Designation of Affected Facility; Volatile organic liquid storage vessels > or = to 40 cubic meter, after 7/23/1984	Y	
60.112b(a)(3)(i)	Standard for Volatile Organic Compounds (VOC); Closed vent system and control device no detectable emissions	Y	
60.112b(a)(3)(ii)	Standard for Volatile Organic Compounds (VOC); Closed vent system and control device >= 95% inlet VOC emission reduction	Y	
60.112b(b)	Standard for Volatile Organic Compounds (VOC); Requirements for tanks >= 75 cubic meter and maximum TVP >= 76.6 kPa	Y	
60.112b(b)(1)	Standard for Volatile Organic Compounds (VOC); Closed vent system and control device option	Y	
60.113b(c)	Testing and Procedures; Closed vent system and control device (not flare)	Y	
60.113b(c)(1)	Testing and Procedures; Closed vent system and control device (not flare) operating plan submission	Y	
60.113b(c)(1)(i)	Testing and Procedures; Closed vent system and control device (not flare) operating plan--efficiency demonstration	Y	
60.113b(c)(1)(ii)	Testing and Procedures; Closed vent system and control device (not flare) operating plan--monitoring parameters	Y	
60.113b(c)(2)	Testing and Procedures; Closed vent system and control device (not flare) operate in accordance with operating plan	Y	
60.115b	Reporting and Recordkeeping Requirements; 60.112b(a) tanks	Y	
60.115b(c)(1)	Reporting and Recordkeeping Requirements; Closed vent system and control device (not flare) operating plan copy	Y	
60.115b(c)(2)	Reporting and Recordkeeping Requirements; Closed vent system and control device (not flare) operating records	Y	
60.116b(a)	Monitoring of Operations; Record retention	Y	
60.116b(b)	Monitoring of Operations; Permanent record requirements	Y	
60.116b(e)(1)	Monitoring of Operations; Determine TVP-temperature selection based on tank operating temperatures	Y	
60.116b(e)(2)(i)	Monitoring of Operations; Determine TVP-crude oil or refined petroleum products by API method	Y	

IV. Source Specific Applicable Requirements

Table IV - AE
Source-specific Applicable Requirements
S59, TANK #5

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.116b(e)(2)(ii)	Monitoring of Operations; Determine TVP-crude oil or refined petroleum products other than API method	Y	
60.116b(g)	Monitoring of Operations; Exemption from 116b(c) and 116b(d)	Y	
40 CFR 63 Subpart CC	National Emission Standards for Hazardous Air Pollutants for Petroleum Refineries (06/12/1996)		
63.640(n)(1)	Applicability and Designation of Affected Source Overlap for Storage Vessels--Existing Group 1 or Group 2 also subject to Kb only subject to Kb.	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18c	Estimates of NMHC emissions from tanks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.30	Storage of Materials other than Kerosene, Light or Heavy Vacuum Gas Oil, or Asphalt (Cumulative Increase, Toxics)	Y	
Part II.31	Vapor Pressure Limit (Cumulative Increase, Toxics)	Y	
Part II.32b	Control and Destruction Efficiency Requirement (Regulation 8-5-311.3, NSPS, Cumulative Increase, Toxics)	Y	
Part II.33a	Throughput Limit (Cumulative Increase, Toxics)	Y	
Part II.34	Recordkeeping (Cumulative Increase)	Y	

¹This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

IV. Source Specific Applicable Requirements

Table IV - AF
Source-specific Applicable Requirements
S61, S62-ASPHALT STORAGE TANKS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 5	Organic Compounds, Storage of Organic Liquids (01/20/1993)		
8-5-117	Exemption, Low Vapor Pressure		
8-5-501	Records		
8-5-604	Determination of Applicability		
BAAQMD Regulation 8, Rule 15	Organic Compounds, Emulsified and Liquid Asphalts (9/16/87)		
8-15-305	Prohibition of Manufacture and Sale	Y	
8-15-501	Records	Y	
NSPS Subpart UU	Standards of Performance for Asphalt Processing and Asphalt Roofing Manufacture (8/6/82)		
60.472(c)	Opacity standard	Y	
60.473(c)	Parametric monitoring	Y	
60.473(d)	Exemption from quarterly reports	Y	
40 CFR 63 Subpart CC	National Emission Standards for Hazardous Pollutants for Petroleum Refining (8/18/95)		
63.646(b)(1)	Storage Vessel Provisions--Determine stored liquid % OHAP for group determination	Y	
63.646(b)(2)	Storage Vessel Provisions--Determine stored liquid % OHAP-method 18 to resolve disputes	Y	
63.654(i)(1)	Reporting and Recordkeeping Requirements--Recordkeeping for storage vessels	Y	
63.654(i)(1)(iv)	Reporting and Recordkeeping Requirements--Recordkeeping for storage vessels	Y	
63.654(i)(4)	Reporting and Recordkeeping Requirements--Recordkeeping--Record retention	Y	

IV. Source Specific Applicable Requirements

Table IV - AF
Source-specific Applicable Requirements
S61, S62-ASPHALT STORAGE TANKS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18c	Estimates of NMHC emissions from tanks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.48	Throughput Limit (Cumulative Increase, Offsets)	Y	
Part II.49	Prohibition against cutback asphalt (Toxics)	Y	
Part II.51	Vapor Pressure Limit (Cumulative Increase, Offsets, <i>NSPS</i> , BACT)	Y	
Part II.57	Control and Destruction Efficiency Requirements (Cumulative Increase, Offsets)	Y	
Part II.58	Recordkeeping Requirement (Cumulative Increase)	Y	
Part II.58b	Continuous Temperature Monitoring (40 CFR 60.472(c))	Y	
Part II.58c	Allowable Temperature Excursions (2-1-403)	Y	
Part II.58d	Recordkeeping for Allowable Temperature Excursions (2-1-403)	Y	
Part II.58e	Definition of Allowable Temperature Excursions (2-1-403)	Y	

Table IV - AG
Source-specific Applicable Requirements
S63, TANK 31

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	N	
8-5-112	Limited Exemption, Tanks in Operation	N	

IV. Source Specific Applicable Requirements

Table IV - AG
Source-specific Applicable Requirements
S63, TANK 31

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-5-304	Storage tanks larger than 75 cubic meter	Y	
8-5-304.2	Storage tanks larger than 150 cubic meter storing liquid with a true vapor pressure greater than 25.8 mm Hg	Y	
8-5-311	Vapor Loss Control Device Requirements	Y	
8-5-311.3	An Approved Emission Control System which collects & processes all organic/gases	Y	
8-5-328	Tank Cleaning Requirements	Y	
8-5-328.1	Liquid balancing	Y	
8-5-328.2	An approved Emission Control System	Y	
8-5-329	Ozone Excess Day Prohibition	Y	
8-5-501	Records	Y	
SIP Regulation 8, Rule 5	Storage of Organic Liquids (8/25/97)		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	Y ¹	
8-5-112	Limited Exemption, Tanks in Operation	Y ¹	
40 CFR 60 Subpart Kb	New Source Performance Standard for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction or Modification Commenced After July 23, 1984.		
60.110b(a)	Applicability and Designation of Affected Facility; Volatile organic liquid storage vessels > or = to 40 cubic meter, after 7/23/1984	Y	
60.112b(a)(3)(i)	Standard for Volatile Organic Compounds (VOC); Closed vent system and control device no detectable emissions	Y	
60.112b(a)(3)(ii)	Standard for Volatile Organic Compounds (VOC); Closed vent system and control device >= 95% inlet VOC emission reduction	Y	
60.112b(b)	Standard for Volatile Organic Compounds (VOC); Requirements for tanks >= 75 cubic meter and maximum TVP >= 76.6 kPa	Y	
60.112b(b)(1)	Standard for Volatile Organic Compounds (VOC); Closed vent system and control device option	Y	
60.113b(c)	Testing and Procedures; Closed vent system and control device (not flare)	Y	
60.113b(c)(1)	Testing and Procedures; Closed vent system and control device (not flare) operating plan submission	Y	

IV. Source Specific Applicable Requirements

Table IV - AG
Source-specific Applicable Requirements
S63, TANK 31

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.113b(c)(1)(i)	Testing and Procedures; Closed vent system and control device (not flare) operating plan--efficiency demonstration	Y	
60.113b(c)(1)(ii)	Testing and Procedures; Closed vent system and control device (not flare) operating plan--monitoring parameters	Y	
60.113b(c)(2)	Testing and Procedures; Closed vent system and control device (not flare) operate in accordance with operating plan	Y	
60.115b	Reporting and Recordkeeping Requirements; 60.112b(a) tanks	Y	
60.115b(c)(1)	Reporting and Recordkeeping Requirements; Closed vent system and control device (not flare) operating plan copy	Y	
60.115b(c)(2)	Reporting and Recordkeeping Requirements; Closed vent system and control device (not flare) operating records	Y	
60.116b(a)	Monitoring of Operations; Record retention	Y	
60.116b(b)	Monitoring of Operations; Permanent record requirements	Y	
60.116b(e)(1)	Monitoring of Operations; Determine TVP-temperature selection based on tank operating temperatures	Y	
60.116b(e)(2)(i)	Monitoring of Operations; Determine TVP-crude oil or refined petroleum products by API method	Y	
60.116b(e)(2)(ii)	Monitoring of Operations; Determine TVP-crude oil or refined petroleum products other than API method	Y	
60.116b(g)	Monitoring of Operations; Exemption from 116b(c) and 116b(d)	Y	
40 CFR 63 Subpart CC	National Emission Standards for Hazardous Air Pollutants for Petroleum Refineries (06/12/1996)		
63.640(n)(1)	Applicability and Designation of Affected Source Overlap for Storage Vessels--Existing Group 1 or Group 2 also subject to Kb only subject to Kb.	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18c	Estimates of NMHC emissions from tanks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance	Y	

IV. Source Specific Applicable Requirements

Table IV - AG
Source-specific Applicable Requirements
S63, TANK 31

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
	(Cumulative Increase)		
Part II.30	Storage of Materials other than Kerosene, Light or Heavy Vacuum Gas Oil, or Asphalt (Cumulative Increase, Toxics)	Y	
Part II.31	Vapor Pressure Limit (Cumulative Increase, Toxics)	Y	
Part II.32c	Control and Destruction Efficiency Requirement (Regulation 8-5-311.3, NSPS, Cumulative Increase, Toxics)	Y	
Part II.33a	Throughput Limit (Cumulative Increase, Toxics)	Y	
Part II.33b	Prohibition against cutback asphalt materials (Toxics)	Y	
Part II.34	Recordkeeping (Cumulative Increase)	Y	

¹This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

Table IV – AH
Source-specific Applicable Requirements
S65-ASPHALT STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 5	Organic Compounds, Storage of Organic Liquids (12/15/99)		
8-5-117	Exemption, Low Vapor Pressure	Y	
8-5-501	Records	Y	
8-5-604	Determination of Applicability	Y	

IV. Source Specific Applicable Requirements

Table IV – AH
Source-specific Applicable Requirements
S65-ASPHALT STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 15	Organic Compounds, Emulsified and Liquid Asphalts (9/16/87)		
8-15-305	Prohibition of Manufacture and Sale	Y	
8-15-501	Records	Y	
NSPS Subpart UU	Standards of Performance for Asphalt Processing and Asphalt Roofing Manufacture (8/6/82)		
60.472(c)	Opacity standard	Y	
60.473(c)	Parametric monitoring	Y	
60.473(d)	Exemption from quarterly reports	Y	
40 CFR 63 Subpart CC	National Emission Standards for Hazardous Pollutants for Petroleum Refining (8/18/95)		
63.646(b)(1)	Storage Vessel Provisions--Determine stored liquid % OHAP for group determination	Y	
63.646(b)(2)	Storage Vessel Provisions--Determine stored liquid % OHAP-method 18 to resolve disputes	Y	
63.654(i)(1)	Reporting and Recordkeeping Requirements--Recordkeeping for storage vessels	Y	
63.654(i)(1)(iv)	Reporting and Recordkeeping Requirements--Recordkeeping for storage vessels	Y	
63.654(i)(4)	Reporting and Recordkeeping Requirements--Recordkeeping--Record retention	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18c	Estimates of NMHC emissions from tanks (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.48	Throughput Limit (Cumulative Increase, Offsets)	Y	
Part II.49	Prohibition against cutback asphalt (Toxics)	Y	

IV. Source Specific Applicable Requirements

Table IV – AH
Source-specific Applicable Requirements
S65-ASPHALT STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part II.52	Vapor Pressure Limit (Cumulative Increase, Offsets, BACT)	Y	
Part II.53	Fugitive Emission Requirement (BACT, Cumulative Increase)	Y	
Part II.56	Control and Destruction Efficiency Requirements (Cumulative Increase, Offsets)	Y	
Part II.58	Recordkeeping Requirement (Cumulative Increase)	Y	
Part II.58b	Continuous Temperature Monitoring (40 CFR 60.472(c))	Y	
Part II.58c	Allowable Temperature Excursions (2-1-403)	Y	
Part II.58d	Recordkeeping for Allowable Temperature Excursions (2-1-403)	Y	
Part II.58e	Definition of Allowable Temperature Excursions (2-1-403)	Y	

Table IV - AI
Source-specific Applicable Requirements
S66, OIL WATER SEPARATOR

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 8	Wastewater (Oil-Water) Separators (6/15/94)		
8-8-301	Wastewater separators designed rated capacity greater than 760 liters per day (200 gal/day) and smaller than 18.9 liters per second (300 gal/min)	Y	
8-8-301.3	An organic compound vapor recovery system with a combined collection and destruction efficiency of at least 95 percent by weight.	Y	
8-8-303	Gauging and Sampling Devices		
8-8-501	API Separator or Air Flotation Bypassed Wastewater Records		
8-8-503	Inspection and Repair Records		
8-8-504	Portable Hydrocarbon Detector		
8-8-602	Determination of Emissions		
8-8-603	Inspection Procedures		
40 CFR 61	National Emission Standards for Benzene Waste Operations		

IV. Source Specific Applicable Requirements

Table IV - AI
Source-specific Applicable Requirements
S66, OIL WATER SEPARATOR

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Subpart FF			
61.347(a)	Except as provided in 61.352 of this subpart, each oil-water separator shall meet the following standards:		
61.347(a)(1)	Install, operate, and maintain a fixed-roof and closed vent system that routes all organic vapors vented from the oil-water separator to a control device.		
61.347(a)(1)(i)(B)	Standards: Oil-Water Separators; Fixed roof--No openings		
61.347(a)(1)(ii)	Closed-vent systems are subject to 61.349.		
61.347(b)	Cover seals, access hatches , and other openings shall be checked visually initially and quarterly thereafter to ensure no cracks, gaps occur between the cover and wall and that access hatches are closed and gasketed properly.		
61.347(c)	except for delay or repair, when a broken seal or gasket or other problem is identified, or when detectable emissions are measured, first efforts repairs shall be made AS SOON AS POSSIBLE, but not later than 15 calendar days after identification		
61.349(a)	Standards: Closed-Vent Systems and Control Devices; Applicability		
61.349(a)(1)	Standards: Closed-Vent Systems and Control Devices; Closed vent system requirements		
61.349(a)(1)(ii)(B)	Car-sealed valves on bypass lines in closed-vent system		
61.349(a)(1)(iii)	Gauging/sampling devices are gas-tight		
61.349(a)(1)(iv)	Safety valve provisions		
61.349(a)(2)	Standards: Closed-Vent Systems and Control Devices; Control device requirements	Y	
61.349(a)(2)(i)	Standards: Closed-Vent Systems and Control Devices; Enclosed combustion device requirements	Y	
61.349(a)(2)(i)(A)	Controlled by enclosed combustion device with greater than 95% control efficiency.		
61.349(b)	Operated at all times.		

IV. Source Specific Applicable Requirements

Table IV - AI
Source-specific Applicable Requirements
S66, OIL WATER SEPARATOR

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
61.349(c)	Standards: Closed-Vent Systems and Control Devices; Control Device Performance Demonstration		
61.349(c)(1)	Demonstrate efficiency required in 61.349(a)(2)		
61.349(e)	Administrator may request tests	Y	
61.349(f)	Visually inspect for leaks quarterly		
61.349(g)	Repair leaks: 5 days for first attempt; 15 days for complete repair		
61.349(h)	Monitor per 61.354(c)		
61.354(c)	Monitoring of Operations; Closed-vent systems and control devices- -Continuously monitor control device operation		
61.354(c)(1)	Monitor thermal vapor incinerator temperature		
61.354(f)	Monitoring of Operations; Closed vent system with bypass line		
61.354(f)(1)	Visually inspect carseal/valve positions monthly		
63.640(o)(1)	Overlap: Sources subject to National Emission Standards for Hazardous Air Pollutants (MACT) Subpart CC and NSPS Subpart QQQ are only required to comply with Subpart CC provisions		
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18e	Estimates of NMHC emissions from wastewater sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part II.83	Throughput limit (Cumulative Increase)	Y	
Part II.84	Vapor tightness of cover and access opening (Regulation 8-8)	Y	
Part II.85	Vapor recovery and control requirement (BACT, cumulative increase, contemporaneous emission reductions)	Y	
Part II.86	Negative pressure and fugitive emission requirement (BACT, cumulative increase, contemporaneous emission reductions)	Y	
Part II.87	Monitoring and recordkeeping (Cumulative increase)	Y	
Part II.88	Monitoring and recordkeeping (Cumulative increase)	Y	

IV. Source Specific Applicable Requirements

Table IV - AJ
Source-specific Applicable Requirements
S67-RECOVERED OIL TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Organic Compounds, Storage of Organic Liquids (01/20/1993)		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	Y	
8-5-111.1	Limited Exemption, Tank Removal From and Return to Service, 3 day prior written notice	Y	
8-5-111.2	Limited Exemption, Tank Removal From and Return to Service, Tank in compliance prior to notification	Y	
8-5-111.4	Limited Exemption, Tank Removal From and Return to Service, Vapor recovery-equipped tanks	Y	
8-5-111.5	Limited Exemption, Tank Removal From and Return to Service, Minimize emissions	Y	
8-5-111.6	Limited Exemption, Tank Removal From and Return to Service, Notice of completion not required	Y	
8-5-112	Limited Exemption, Tanks in Operation	Y	
8-5-112.1	Limited Exemption, Tanks in Operation, Tank in compliance prior to start of work. Certified per 8-5-404	Y	
8-5-112.2	Limited Exemption, Tanks in Operation, No product movement, Minimize emissions	Y	
8-5-112.3	Limited Exemption, Tanks in Operation, Not to exceed 7 days	Y	
8-5-301	Storage Tanks Smaller than 150m ³	Y	
8-5-301.3	Storage Tanks Smaller than 150 cubic meter with vapor loss control device in compliance with 8-5-311	Y	
8-5-311	Vapor loss control device requirements	Y	
8-5-311.3	Vapor Loss Control Device Requirements; Approved emission control system	Y	
8-5-501	Records	Y	
8-5-603.1	Determination of Emissions; Organic compounds specified in 8-5-311.3	Y	
40 CFR 61 Subpart FF	National Emission Standards for Benzene Waste Operations		
61.343(a)	Standards: Tanks; Benzene-containing wastes	Y	
61.343(a)(1)	Standards: Tanks; Fixed Roof--with closed vent system	Y	
61.343(a)(1)(i)(B)	Standards: Tanks; Fixed Roof--No openings	Y	
61.343(a)(1)(ii)	Standards: Tanks; Closed-vent systems are subject to 61.349	Y	

IV. Source Specific Applicable Requirements

Table IV - AJ
Source-specific Applicable Requirements
S67-RECOVERED OIL TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
61.343(c)	Standards: Tanks; Fixed roof quarterly inspection	Y	
61.343(d)	Standards: Tanks; Fixed roof repairs	Y	
61.349(a)	Standards: Closed-Vent Systems and Control Devices; Applicability	Y	
61.349(a)(1)	Standards: Closed-Vent Systems and Control Devices; Closed vent system requirements	Y	
61.349(a)(1)(i)(A)	Standards: Closed-Vent Systems and Control Devices--Closed vent systems--No detectable emissions \geq 500 ppmv; annual inspection	Y	
61.349(a)(1)(ii)(B)	Car-sealed valves on bypass lines in closed-vent system	Y	
61.349(a)(1)(iii)	Gauging/sampling devices are gas-tight	Y	
61.349(a)(1)(iv)	Safety valve provisions	Y	
61.349(a)(2)	Standards: Closed-Vent Systems and Control Devices; Control device requirements	Y	
61.349(a)(2)(i)	Standards: Closed-Vent Systems and Control Devices; Enclosed combustion device requirements	Y	
61.349(a)(2)(i)(A)	Controlled by enclosed combustion device with greater than 95% control efficiency.	Y	
61.349(b)	Operated at all times.	Y	
61.349(c)	Standards: Closed-Vent Systems and Control Devices; Control Device Performance Demonstration	Y	
61.349(c)(1)	Demonstrate efficiency required in 61.349(a)(2)	Y	
61.349(e)	Administrator may request performance tests	Y	
61.349(f)	Visually inspect for leaks quarterly	Y	
61.349(g)	Repair leaks: 5 days for first attempt; 15 days for complete repair	Y	
61.349(h)	Monitor per 61.354(c)	Y	
61.354(c)	Monitoring of Operations; Closed-vent systems and control devices--Continuously monitor control device operation	Y	
61.354(c)(1)	Monitor thermal vapor incinerator temperature	Y	
61.354(c)(4)	Monitoring for a boiler or process heater having a design heat input capacity less than 44 MW	Y	
61.354(f)	Monitoring of Operations; Closed vent system with bypass line	Y	
61.354(f)(1)	Visually inspect carseal/valve positions monthly	Y	
61.356(a)	Recordkeeping and retention requirements	Y	
61.356(d)	Engineering design documentation for all control equipment	Y	
61.356(f)	Recordkeeping Requirements: Closed vent system and control device per 61.349--retain for life of device	Y	

IV. Source Specific Applicable Requirements

Table IV - AJ
Source-specific Applicable Requirements
S67-RECOVERED OIL TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
61.356(f)(1)	Recordkeeping Requirements: certification of performance level	Y	
61.356(f)(2)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)(i)(A)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis thermal vapor incinerator	Y	
61.356(g)	Recordkeeping Requirements: Visual inspection per 61.343 through 61.347	Y	
61.356(h)	Recordkeeping Requirements: No detectable emissions tests per 61.343 through 61.347, and 61.349	Y	
61.356(j)	Recordkeeping Requirements: Control device operation	Y	
61.356(j)(1)	Recordkeeping Requirements: dates of startup and shutdown	Y	
61.356(j)(2)	Recordkeeping Requirements: description of parameters	Y	
61.356(j)(3)	Recordkeeping Requirements: Control device operational upsets	Y	
61.356(j)(3)(i)	Recordkeeping Requirements; Bypass Line Controls	Y	
61.356(j)(4)	Recordkeeping Requirements: Control device operation--Thermal vapor incinerator	Y	
61.357(d)(7)	Reporting Requirements: Quarterly report requirements	Y	
61.357(d)(7)(iv)	Reporting Requirements: Quarterly report--Control device monitored per 61.354(c)	Y	
61.357(d)(7)(iv)(A)	Reporting Requirements: Quarterly report--Thermal vapor incinerator	Y	
61.357(d)(7)(iv)(C)	Reporting Requirements	Y	
BAAQMD Condition #1240			
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18e	Estimates of NMHC emissions from wastewater sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	

IV. Source Specific Applicable Requirements

Table IV - AK
Source-specific Applicable Requirements
S68-EMERGENCY DIESEL-POWERED FIREWATER PUMP

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD · Regulation 9 Rule 1	Inorganic Gaseous Pollutants, Sulfur Dioxide Emissions Limitations (3/25/95)		
9-1-304	Fuel Burning (Liquid and Solid fuels)	Y	
BAAQMD · Regulation 9, Rule 9	Nitrogen Oxides And Carbon Monoxide From Stationary Internal Combustion Engines		
9-8-330	Emergency Standby Engines, Hours of Operation	N	
9-8-530	Emergency standby engines, monitoring and recordkeeping	N	
BAAQMD Condition #1240			
Part I.5	Refinery Heat Input Limit (Cumulative Increase)	Y	
Part I.6	Prohibition against combustion of fuel oil or diesel fuel except at S68 (cumulative increase)	Y	
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18g	Estimates of NMHC emissions from combustion sources (Cumulative Increase)	Y	
Part I.18i	Estimates of NOx emissions from combustion sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
BAAQMD Condition #18796			

IV. Source Specific Applicable Requirements

Table IV - AK
Source-specific Applicable Requirements
S68-EMERGENCY DIESEL-POWERED FIREWATER PUMP

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 1	Sulfur content of fuel (Cumulative Increase)	N	
Part 2	Emergency use and reliability testing (Cumulative Increase, 9-8-330)	N	
Part 3	Definition of emergency use (9-8-231)	N	
Part 4	Definition of reliability-related activities (9-8-232)	N	
Part 5	Fuel meter or hours of operation meter (9-8-530)	N	
Part 6	Recordkeeping (9-8-530, 1-441)	N	

IV. Source Specific Applicable Requirements

Table IV- AL
Fugitive Sources: Applicable Requirements

(This table is a cross-reference between the refinery equipment and the various fugitive applicable requirements. The actual requirements are in the next table.)

Process Unit	BAAQMD Reg. 8-18	BAAQMD Reg. 8-28 SIP Reg. 8-28	NSPS Part 60, Subpart QQQ; BAAQMD Reg. 10-69	NSPS Part 60, Subpart VV; BAAQMD Reg. 10-52	NESHAP Part 61, Subpart FF; BAAQMD Reg. 11-12	NESHAP Part 63, Subpart CC
S1, S2, S4, and S23 Crude Tankage receipt piping.	X	X				
S1, S2, S4, and S23 Crude Tankage feed piping to S18 Crude Unit.	X	X		X(1)		X
S12, S25-S28, Wastewater sources, S41 WEMCO Hydrocleaner, S66 Oil-Water Separator, Recovered Oil Equipment, and Closed Vent Systems at Wastewater Treatment Plant.	X	X	X (3)		X (2)	
S14 Naphtha Loading Rack, including vapor recovery system and fill line from S9 Naphtha Tank.	X	X				
S15, Loading Racks - Gas Oil	X	X				
S16, Loading Racks - Kerosene or Distillate Oil	X	X				
S17, Loading Racks – Asphalt	X	X				
S18 Crude Unit, including Atmospheric Tower (T-1), crude charge circuit, overhead off-gas system, caustic scrubbers, and naphtha piping to S29 Naphtha Merox Treater and excluding vacuum tower.	X	X		X(1)		X
S18 Vacuum Tower (T-2) overhead gas system	X	X				

IV. Source Specific Applicable Requirements

Table IV- AL
Fugitive Sources: Applicable Requirements

(This table is a cross-reference between the refinery equipment and the various fugitive applicable requirements. The actual requirements are in the next table.)

Process Unit	BAAQMD Reg. 8-18	BAAQMD Reg. 8-28 SIP Reg. 8-28	NSPS Part 60, Subpart QQQ; BAAQMD Reg. 10-69	NSPS Part 60, Subpart VV; BAAQMD Reg. 10-52	NESHAP Part 61, Subpart FF; BAAQMD Reg. 11-12	NESHAP Part 63, Subpart CC
S29 Naphtha Merox Treater, including rundown piping to S9 Naphtha Tank.	X	X		X(1)		X
S30, Marine Loading Dock	X	X				
S31, Rail Car Asphalt Loading Rack	X					
S32 LGO Stripper Tower and associated piping.	X	X		X(1)		X
S54, Asphalt Loading Rack	X					
Fuel gas system, including natural gas piping.	X	X				
All Other Piping	X	X				

Notes:

- (1) Fugitive components which are subject to the equipment leak standards of 40 CFR Part 63 Subpart CC shall comply with the equipment leak standards set forth in 40 CFR Part 60 Subpart VV.
- (2) Wastewater treatment plant equipment which is subject to 40 CFR Part 63 Subpart CC shall comply with the provisions of 40 CFR Part 61 Subpart FF.
- (3) Per 40 CFR Part 63 Section 63.640 (o)(1), the wastewater oil-water separator (S66), which is also subject to 40 CFR Part 60 Subpart QQQ, shall comply only with the wastewater provisions of 40 CFR Part 63 Subpart CC (Part 61 Subpart FF).

IV. Source Specific Applicable Requirements

**Table IV – AM
 Applicable Requirements
 COMPONENTS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8-18	Organic Compounds-Equipment Leaks (3/18/98)		
8-18-110	Exemption, Controlled Seal Systems and Pressure Relief Devices	N	
8-18-113	Limited Exemption, Initial Boiling Point	N	
8-18-115	Limited Exemption, Storage Tanks	N	
8-18-116	Limited Exemption, Vacuum Service	N	
8-18-301	General Standard	N	
8-18-302	Valves	N	
8-18-303	Pumps and compressors	N	
8-18-304	Connections	N	
8-18-304.2	Connections subject to District-approved inspection program	N	
8-18-305	Pressure relief devices	N	
8-18-306	Non-repairable equipment	N	
8-18-306.1	Repair at next scheduled turnaround or five years	N	
8-18-306.2	Percentage of equipment awaiting repair	N	
8-18-307	Liquid Leaks	N	
8-18-401	Inspection	N	
8-18-402	Identification	N	
8-18-403	Visual inspection schedule	N	
8-18-404	Alternate inspection schedule	N	
8-18-501	Portable Hydrocarbon Detector	N	
8-18-502	Records	N	
8-18-601	Analysis of Samples		
8-18-602	Inspection Procedure		
8-18-603	Determination of Control Efficiency		
BAAQMD Regulation 8-28	Episodic Releases From Pressure Relief Devices at Petroleum Refineries and Chemical Plants (3/18/98)	N	
8-28-111	Exemption, Evaporation Point	N	
8-28-112	Exemption, Storage Tanks	N	
8-28-303	Pressure Relief Devices at Existing Sources at Petroleum Refineries	N	
8-28-303.2	Prevention Measures Procedures	N	
8-28-304	Repeat Releases - Pressure Relief Devices at Petroleum Refineries	N	
8-28-401	Reporting at Petroleum Refineries and Chemical Plants	N	

IV. Source Specific Applicable Requirements

**Table IV – AM
 Applicable Requirements
 COMPONENTS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-28-402	Inspection	N	
8-28-403	Records	N	
8-28-404	Identification	N	
8-28-405	Prevention Measures Procedures	N	
8-28-602	Determination of Control Efficiency	N	
SIP Regulation 8, Rule 28	Pressure Relief Valves at Petroleum Refineries and Chemical Plants (6/15/94)	Y	
8-28-301	Pressure Relief Valve	Y ¹	
8-28-401	Reporting	Y ¹	
8-28-402	Inspection	Y ¹	
8-28-403	Records	Y ¹	
8-28-404	Identification	Y ¹	
NSPS Part 60 Subpart VV; BAAQMD Regulation 10-52	Standards of Performance for Equipment Leaks (Fugitive Emission Sources) (8/18/95); BAAQMD Standards of Performance for New Stationary Sources (12/20/95)		
60.480	Applicability and Designation of Affected Facility	Y	
60.482-1	General Standards	Y	
60.482-2	Pump Standards:	Y	
60.482-3	Compressor Standards	Y	
60.482-4	Requirements for Pressure Relief Devices in gas/vapor service	Y	
60.482-5	Requirements for Sampling connecting systems	Y	
60.482-6	Requirements for Open-ended valves or lines	Y	
60.482-7	Valve Standards:	Y	
60.482-7(a)-(c)	Monitor monthly unless 2 successive months <10,000 ppm, then monitor first month of each quarter. If leak >10,000 ppm is detected, resume monthly monitoring	Y	
60.482-7(e)	Methods for first attempts or minimizing valve leaks	Y	
60.482-7(f)	Designated no-emissions (<500 ppm) valves with no external actuating mechanisms in contact with process fluid, may revert to annual monitoring, or that requested by the Administrator	Y	
60.482-8	Standards: Pumps & Valves in Heavy Liquid Service, Pressure Relief Devices in Light Liquid or Heavy Liquid Service, and Flanges & Other Connectors	Y	

IV. Source Specific Applicable Requirements

**Table IV – AM
 Applicable Requirements
 COMPONENTS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.482-9(a)	Delay of repairs	Y	
60.482-9(b)	Repair may be delayed for isolated equipment	Y	
60.482-9(d)	Delay of repairs for pumps	Y	
60.482-9(d)(1)	Only dual-mechanical seal pumps qualify for delay of repair	Y	
60.482-9(d)(2)	Pump leaks must be repaired within 6 months	Y	
60.482-9(c)	Delay of repair for valves is only allowed under certain circumstances	Y	
60.482-10	Requirements for closed-vent systems and control devices	Y	
60.483-1	Alternative standards for valves-allowable percentage of valves leaking	Y	
60.483-2	Alternative standards for valves-skip period leak detection and repair	Y	
60.485	Test Methods and Procedures	Y	
60.486	Record keeping	Y	
60.487	Reporting	Y	
40 CFR 61 Subpart FF	NESHAP, Benzene Waste Operations (01/07/1993)		
61.343(a)(1)(i)(A)	Standards: Tanks; Fixed Roof—Fugitive emissions less than 500 ppmv	Y	
61.345(a)(1)(i)	Standards: Containers--Covers and Openings, no detectable emissions	Y	
61.347(a)(1)(i)(A)	Standards: Oil Water Separators	Y	
61.349(a)(1)(i)	Standards: Closed-vent systems and Control Devices—Closed vent system-no detectable emission \geq 500 ppmv, annual inspection	Y	
BAAQMD Regulation 10-52	Incorporates by reference 40 CFR 60 Subpart VV	Y	
NESHAP Part 63 Subpart CC	National Emission Standards for Hazardous Air Pollutants from Petroleum Refineries		
63.640(a)	Applicability	Y	
63.640(p)	Overlap of subpart CC with other regulations for equipment leaks.	Y	
63.642(e)	Keep records for 5 years	Y	
63.648(a)	Equipment Leak Standards--Existing source comply with 40 CFR 60 Subpart VV and 63.648(b). New source comply with 40 CFR 63 Subpart H	Y	

IV. Source Specific Applicable Requirements

**Table IV – AM
 Applicable Requirements
 COMPONENTS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
63.648(b)	Use of monitoring data from prior to 8/18/95 to qualify for less stringent monitoring frequency	Y	
Part I.14	Facility Limits (cumulative increase)	Y	
Part I.18b	Fugitive NMHC Emission Calculations (cumulative increase)	Y	
Part I.18j	Summary of Emissions Estimates (cumulative increase)	Y	

¹This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

**Table IV - AN
 Source-specific Applicable Requirements
 A4- Loading Rack Thermal Oxidizer**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 6	Organic Compounds-Organic Liquid Bulk Terminals and Bulk Plants (2/2/94)		
8-6-301	Bulk Terminal Limitations	Y	

IV. Source Specific Applicable Requirements

Table IV - AN
Source-specific Applicable Requirements
A4- Loading Rack Thermal Oxidizer

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #1240			
Part I.5	Refinery Heat Input Limit (Cumulative Increase)	Y	
Part I.6	Prohibition against combustion of fuel oil or diesel fuel (cumulative increase)	Y	
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18g	Estimates of NMHC emissions from combustion sources (Cumulative Increase)	Y	
Part I.18i	Estimates of NOx emissions from combustion sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part I.19	Temperature monitoring (2-6-503)	Y	
Part I.19a	Allowable temperature excursions (2-1-403)	Y	
Part I.19b	Recordkeeping for allowable temperature excursions (2-1-403)	Y	
Part I.19c	Temperatures above the limit ((2-1-403)	Y	
Part II.6	Safety Relief System (Cumulative Increase)	Y	
Part II.32a	Requirement for control of S13 (8-5-311.3, NSPS, cumulative increase, toxics)	Y	
Part II.32b	Requirement for control of S59 (8-5-311.3, NSPS, cumulative increase, toxics)	Y	
Part II.32c	Requirement for control of S63 (8-5-311.3, NSPS, cumulative increase, offsets, BACT)	Y	
Part II.60	Destruction efficiency requirements <cumulative increase, offsets, BACT, toxics>	Y	
Part II.63	Requirement for vapor recovery and abatement (BACT, Cumulative Increase, offsets)	Y	
Part II.68	Destruction Efficiency Requirement (Cumulative Increase, BACT)	Y	

¹This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

IV. Source Specific Applicable Requirements

Table IV - AO
Source-specific Applicable Requirements
A31, THERMAL OXIDIZER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		
8-5-311	Vapor Loss Control Device Requirements	Y	
8-5-311.3	An Approved Emission Control System which collects & processes all organic/gases	Y	
BAAQMD Regulation 8, Rule 6	Organic Liquid Bulk Terminals And Bulk Plants (2/2/94)		
8-6-301	Bulk Terminal Limitations	Y	
NSPS Subpart UU	Standards of Performance for Asphalt Processing and Asphalt Roofing Manufacture (8/6/82)		
60.472(c)	Opacity standard	Y	
60.473(c)	Parametric monitoring	Y	
60.473(d)	Exemption from quarterly reports	Y	
40 CFR 60 Subpart Kb	New Source Performance Standard for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction or Modification Commenced After July 23, 1984.		
60.110b(a)	Applicability and Designation of Affected Facility; Volatile organic liquid storage vessels > or = to 40 cubic meter, after 7/23/1984		
60.112b(a)(3)(ii)	Standard for Volatile Organic Compounds (VOC); Closed vent system and control device >= 95% inlet VOC emission reduction		

IV. Source Specific Applicable Requirements

Table IV - AO
Source-specific Applicable Requirements
A31, THERMAL OXIDIZER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.112b(b)(1)	Standard for Volatile Organic Compounds (VOC); Closed vent system and control device option		
60.113b(c)	Testing and Procedures; Closed vent system and control device (not flare)	Y	
60.113b(c)(1)	Testing and Procedures; Closed vent system and control device (not flare) operating plan submission	Y	
60.113b(c)(1)(i)	Testing and Procedures; Closed vent system and control device (not flare) operating plan--efficiency demonstration	Y	
60.113b(c)(1)(ii)	Testing and Procedures; Closed vent system and control device (not flare) operating plan--monitoring parameters	Y	
60.113b(c)(2)	Testing and Procedures; Closed vent system and control device (not flare) operate in accordance with operating plan	Y	
60.115b(c)(1)	Reporting and Recordkeeping Requirements; Closed vent system and control device (not flare) operating plan copy	Y	
60.115b(c)(2)	Reporting and Recordkeeping Requirements; Closed vent system and control device (not flare) operating records	Y	
60.116b(a)	Monitoring of Operations; Record retention	Y	
40 CFR 61 Subpart FF	National Emission Standards for Benzene Waste Operations	Y	
61.343(a)(1)(ii)	Standards: Tanks; Closed-vent systems are subject to 61.349	Y	
61.349(a)	Standards: Closed-Vent Systems and Control Devices; Applicability	Y	
61.349(a)(1)	Standards: Closed-Vent Systems and Control Devices; Closed vent system requirements	Y	
61.349(a)(2)	Standards: Closed-Vent Systems and Control Devices; Control device requirements	Y	
61.349(a)(2)(i)	Standards: Closed-Vent Systems and Control Devices; Enclosed combustion device requirements	Y	
61.349(a)(2)(i)(A)	Controlled by enclosed combustion device with greater than 95% control efficiency.	Y	
61.349(b)	Operated at all times.	Y	
61.349(c)	Standards: Closed-Vent Systems and Control Devices; Control Device Performance Demonstration	Y	

IV. Source Specific Applicable Requirements

Table IV - AO
Source-specific Applicable Requirements
A31, THERMAL OXIDIZER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
61.349(c)(1)	Demonstrate efficiency required in 61.349(a)(2)	Y	
61.349(e)	Administrator may request performance tests	Y	
61.349(f)	Visually inspect for leaks quarterly	Y	
61.349(g)	Repair leaks: 5 days for first attempt; 15 days for complete repair	Y	
61.349(h)	Monitor per 61.354(c)	Y	
61.354(c)	Monitoring of Operations; Closed-vent systems and control devices--Continuously monitor control device operation	Y	
61.354(c)(1)	Monitor thermal vapor incinerator temperature	Y	
61.356(a)	Recordkeeping and retention requirements	Y	
61.356(d)	Engineering design documentation for all control equipment	Y	
61.356(f)	Recordkeeping Requirements: Closed vent system and control device per 61.349--retain for life of device	Y	
61.356(f)(1)	Recordkeeping Requirements: certification of performance level	Y	
61.356(f)(2)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)(i)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis	Y	
61.356(f)(2)(i)(A)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis thermal vapor incinerator	Y	
61.356(f)(2)(i)(C)	Recordkeeping Requirements: Closed vent system and control device engineering calculations--design analysis process heater	Y	
61.356(j)	Recordkeeping Requirements: Control device operation	Y	
61.356(j)(1)	Recordkeeping Requirements: dates of startup and shutdown	Y	
61.356(j)(2)	Recordkeeping Requirements: description of parameters	Y	
61.356(j)(3)	Recordkeeping Requirements: periods when closed vent system and control device are not operating	Y	
61.356(j)(4)	Recordkeeping Requirements: Control device operation--Thermal vapor incinerator	Y	
61.357(d)(7)	Reporting Requirements: Quarterly report requirements	Y	
61.357(d)(7)(iv)	Reporting Requirements: Quarterly report--Control device monitored per 61.354(c)	Y	
61.357(d)(7)	Reporting Requirements: Quarterly report--Thermal vapor	Y	

IV. Source Specific Applicable Requirements

Table IV - AO
Source-specific Applicable Requirements
A31, THERMAL OXIDIZER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
(iv)(A)	incinerator		
BAAQMD Condition #1240			
Part I.5	Refinery Heat Input Limit (Cumulative Increase)	Y	
Part I.6	Prohibition against combustion of fuel oil or diesel fuel (cumulative increase)	Y	
Part I.14	Facility Limits (Cumulative Increase)	Y	
Part I.18	Cumulative Increase Monitoring (Cumulative Increase)	Y	
Part I.18a	NMHC, NOx, and SO2 estimates (Cumulative Increase)	Y	
Part I.18g	Estimates of NMHC emissions from combustion sources (Cumulative Increase)	Y	
Part I.18i	Estimates of NOx emissions from combustion sources (Cumulative Increase)	Y	
Part I.18j	Summary of emissions estimates and reports of non-compliance (Cumulative Increase)	Y	
Part I.19	Temperature monitoring (2-6-503)	Y	
Part II.32a	Control and Destruction Efficiency Requirement (Regulation 8-5-311.3, NSPS, Cumulative Increase, Toxics)	Y	
Part II.32b	Requirement for control of S59 (8-5-311.3, NSPS, cumulative increase, toxics)	Y	
Part II.32c	Requirement for control of S63 (8-5-311.3, NSPS, cumulative increase, offsets, BACT)	Y	
Part II.43	Control Requirement (BACT, Cumulative Increase, offsets)	Y	
Part II.55	Control and Destruction Efficiency Requirements (Cumulative Increase, Offsets)	Y	
Part II.56	Control and Destruction Efficiency Requirements (Cumulative Increase, Offsets)	Y	
Part II.57	Control and Destruction Efficiency Requirements (Cumulative Increase, Offsets)	Y	
Part II.58b	Continuous Temperature Monitoring (40 CFR 60.472(c))	Y	
Part II.58c	Allowable Temperature Excursions (2-1-403)	Y	
Part II.58d	Recordkeeping for Allowable Temperature Excursions (2-1-403)	Y	

IV. Source Specific Applicable Requirements

Table IV - AO
Source-specific Applicable Requirements
A31, THERMAL OXIDIZER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part II.58e	Definition of Allowable Temperature Excursions (2-1-403)	Y	
Part II.69	Destruction Efficiency Requirement (Cumulative Increase, BACT)	Y	
Part II.70	Destruction Efficiency Requirement (Cumulative Increase, BACT)	Y	
Part II.85	Vapor recovery and control requirement (BACT, cumulative increase, contemporaneous emission reductions)	Y	

¹This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

V. SCHEDULE OF COMPLIANCE

The permit holder shall comply with all applicable requirements cited in this permit. The permit holder shall also comply with applicable requirements that become effective during the term of this permit on a timely basis.

VI. PERMIT CONDITIONS

Any condition that is preceded by an asterisk is not federally enforceable.

Condition #1240 For All Sources

Permit Conditions II. 1, 11, 12, and 13; and IV. 1, 2 and 3 were modified or added as part of App. No. 14513.

Pursuant to permit application #17515, permit condition I.8 was modified, conditions I.9 and I.10 were added, and what had been conditions .9 and I.10 were renumbered as I.11 and I.12, respectively.

Pursuant to permit application #17687 the total refinery wide heat input has been corrected from 42 to 66.17 MMBTU/HR, S13 and S59 were permitted, and S12 was exempted from permitting.

Pursuant to permit application #1261 (May, 2000) the total refinery-wide heat input has been corrected from 76.06 to 86.6 MMBTU/HR, and the allowable heat input for S19 was increased from 22.4 to 33 MMbtu/hr.

Pursuant to permit application #1819 (October, 2000), the crude oil throughput to the crude unit, S18, was raised to 5,292,000 barrels/yr.

I. REFINERY CONDITIONS

S18 Crude Unit with Vacuum Distillation Column vented to and abated by S19 Vacuum H-1

1. The total throughput of feed oil to S18 Crude Unit shall not exceed 5,292,000 barrels in any consecutive period. (cumulative increase, toxics, offsets)
2. The total throughput of feed oil to S18 Crude Unit shall not exceed 18,000 barrels in any calendar day. (cumulative increase, toxics)
3. At all times, the vacuum exhaust from the vacuum distillation column at S18 Crude Unit shall be vented to and abated by S19 Vacuum Heater with a destruction efficiency for VOC of at least 98.5%, by weight, as measured across S19. (cumulative increase, toxics)
4. Each day, the permittee shall record, by material name, in a District approved log, the total volume of each and every liquid material

VI. Permit Conditions

throughput to S18 during the preceding calendar day, in gallon units or barrel units. At the conclusion of each month, the permittee shall total the daily log records and record the sum as the monthly throughput of all liquid materials to S18, in a District approved log. Additionally, the permittee shall record in the District approved log the throughput of all liquid materials to S18 for each rolling 12 consecutive month period. This log shall be retained for at least 5 years from date of entry, shall be kept on site, and shall be made available to the District staff on request.
(cumulative increase)

5. The maximum heat input to all refinery combustion units except S68, Emergency Diesel-Powered Firewater Pump, shall not exceed a total of 86.6 MM BTU/Hr. Compliance will be determined from the daily reading of the PG&E natural gas flow meter and the refinery fuel gas meter. These meter readings shall be logged and initialed by the operations coordinator on a daily basis. These readings and the monthly PG&E bills shall be made available to the District upon request.
(cumulative increase)

5a. The maximum heat input to S19, Vacuum Heater, shall not exceed 33 MMbtu/hr. (cumulative increase)

5b. CO emissions in the exhaust of S19, Vacuum Heater, shall not exceed 140 ppm_{dv} at 3% oxygen over any one-hour period. (cumulative increase)

5c. CO emissions in the exhaust of S19, Vacuum Heater, shall not exceed 3.4 lb/hr over any one-hour period. (cumulative increase)

6. Fuel oil and/or diesel fuel shall not be combusted in the refinery's heaters or boilers or other combustion sources except for S68, Emergency Diesel-powered Firewater Pump. (cumulative increase) (modified 8/12/99, 4/24/02)

7. Mechanical seals will be installed on all new rotary pumps and compressors. Mechanical packing of best available design will be installed in new reciprocating pumps. All compressor seals will be vented to an operating firebox or the vapors will otherwise be eliminated by a method; which is satisfactory to the District. (cumulative increase)

8. Vacuum Heater (S19) shall be equipped with a John Zink LoNO_x Burner. Average NO_x emissions from S19 shall not exceed 30 ppm corrected to 3% oxygen on a dry basis (one hour averaging period).
()

VI. Permit Conditions

9. Deleted 06/02/98.

10. Boilers S20 and S21 and heater S19 shall be equipped with individual continuous recording oxygen analyzers. ()

11. The H₂S content in the refinery process gas prior to mixing with another gaseous fluid shall not exceed 163 ppmv, dry, averaged over any consecutive period. (NSPS) (Compliance with this condition will not necessarily ensure compliance with part I.12 of this condition.)

12. The H₂S content in the refinery process gas prior to mixing with another gaseous fluid shall not exceed 10 ppmv, dry, averaged over any consecutive period. (BACT)

13. The permittee shall operate District approved H₂S monitoring and recording instruments which, as set forth in 40 CFR 60 Subpart J, measure and record the content of H₂S in the refinery process gas prior to mixing with another gaseous fluid and which allow the District to determine compliance of the process gas H₂S content with both the applicable standard in 40 CFR 60 Subpart J and parts I.11 and I.12 of this condition. These records shall be retained in a District approved log, retained for at least 5 years from date of record, shall be kept on site, and shall be made available to the District staff upon request. (NSPS, BACT)

14. Total refinery emissions (excluding marine emissions) shall not exceed the limits listed below:

- | | |
|----------------------------------------------|--------------|
| a. Non-Methane Hydrocarbons..... | 49.1 tons/yr |
| b. Sulfur Dioxide, SO ₂ | 28 tons/yr |
| c. Nitrogen Oxides, as NO ₂ | 40 tons/yr |
- (Cumulative Increase)

15. Refinery wastewater shall not be used for dust control at this facility. (Cumulative Increase)

16. The permit holder shall perform a source test at S19, Vacuum Heater, every months to determine compliance with the NO_x and CO standards in Regulation 9, Rule , the CO limit in part 5b of this condition, and the requirement for 98.5% POC destruction efficiency. The source test shall be performed at the maximum capacity of 33 MMbtu/hr. All source testing shall be done in accordance with the District's Manual of Procedures. The facility shall receive approval from the District's Source Test Manager for installation of test ports and source testing procedures.

VI. Permit Conditions

The results shall be delivered to the District no later than 30 days from the date of the source test. (

Cumulative Increase, Toxics)

A/C Condition (to be deleted after completion):

~~17. Within 60 days of issuance of the authority to construct for application #1261, the permit holder shall perform a source test at S19, Vacuum Heater, to determine compliance with the NO_x and CO standards in Regulation 9, Rule 7, the CO limit in part 5b of this condition, and compliance with the requirement for 98.5% POC destruction efficiency. The source test shall be performed at the maximum capacity of 33 MMbtu/hr. All source testing shall be done in accordance with the District's Manual of Procedures. The facility shall receive approval from the District's Source Test Manager for installation of test ports and source testing procedures. The results shall be delivered to the District no later than 30 days from the date of the source test. (~~
~~Cumulative Increase, Toxics)~~

VI. Permit Conditions

hours of operation S68 the actual

hours of operation OX S68 the actual

j

i

The emissions estimates shall be kept on-site for a minimum of five years and be made available to District staff upon request.

VI. Permit Conditions

VI. Permit Conditions

*20. The owner/operator shall notify the District no less than three calendar days in advance of any scheduled startup or shutdown of any source and as soon as feasible for any unscheduled startup or shutdown. The notification shall be sent to the Director of Enforcement and Compliance. (basis:

II. TANKAGE AND LOADING RACK CONDITIONS:

1. Deleted 8/26/00. Modifications to S2 completed.
 2. Deleted 5/01. Redundant with condition 1240 II.26.
 3. Deleted 07/20/99. Redundant with condition 1240 II.27.
 4. Deleted 07/20/99. Redundant with condition 1240 II.54.
 5. Deleted 07/20/99. Redundant with condition 1240 II.60.
 6. The safety relief system
shall vent to the (A4).
 7. Deleted 07/20/99. Redundant with condition 1240 II.51.
 8. Asphalt loading shall be immediately terminated if the
blowdown system is venting to the (A4).
(Cumulative Increase)
 9. Deleted 08/12/99.
 10. Source S25 shall be vented to A3, Mist Eliminator F-10, A31,
, at all times of operation. If A31 is
inoperative, this source shall be vented to source S24, Hot Oil Heater, as a
backup until A31 is operating. (cumulative increase)(Added 10/27/93
)
- S1 Crude Oil Storage Tank 1A, External Floating Roof,
Capacity: 3,419,000 Gallons
S2 Crude Oil Storage Tank, External Floating TK-1B,
Capacity: 3,419,000 Gallons
S4 Crude Oil Storage Tank, External Floating Roof,
TK-10A, Capacity: 1,382,000 Gallons

VI. Permit Conditions

S23 Crude Oil Storage Tank, External Floating Roof,
TK-10B, Capacity: 1,382,000 Gallons

11. Deleted 08/26/00. Tanks S1, S2, S4 and S23 completed.

12. Tanks S1, S2, S4 and S23 shall be external floating roof tanks of welded construction which have liquid mounted mechanical shoe primary seals and zero-gap, rim mounted secondary seals and only the following fittings. There shall be no ungasketed roof fittings.

- (1) Automatic Gauge Float Well/bolted cover, gasketed
 - (1) Access Hatch, 24-inch diameter/bolted cover, gasketed
 - (1) Gauge Hatch Sample Well, 8 inch diameter/weighted mech actuation, gasketed
 - (1) Sample well, 24-inch diameter/slit fabric seal 10% open
 - (1) Vacuum Breaker, 10-inch diameter/weighted mech actuation, gasketed
 - (1) Roof Drain (which does not drain water into product)
 - (18) Roof Legs, 3-inch diameter, adjustable, pontoon area, sock
 - (20) Roof Legs, 3-inch diameter, adjustable, center area, sock
 - (1) Rim Vent, 6-inch diameter/weighted mech actuation, gasketed
- (cumulative increase, offsets)

Note 1: Slotted Guide Pole Control Configuration, per Addendum to API Publication 2517, May 1994, shall include the following components:

- a. Sliding cover;
- b. Well gasket;
- c. Pole sleeve with pole wiper approximately 6 inches above sliding cover, or District approved equivalent;
- d. Float with float wiper approximately 1 inch above the sliding cover, or alternately a float with multiple wipers. (Added per AN 14513, 9/95 or AN 366 1/2000)

VI. Permit Conditions

13. For the four crude tanks S1, S2, S4 and S23,
will inspect the primary and secondary tank seals quarterly, and maintain records of each inspection for five years from the date of the inspection. These records shall be made available to the District upon request. The quarterly inspections will include all items required by Regulations 8-5-401, and 8-5-402, as well as all items required by 40 CFR 60.113b(b)(1)(i) and (ii). (cumulative increase) (Added per AN 14513, 9/95)
14. The sum total crude oil throughput to S1, S2, S4, and S23 shall not exceed 6,235,000 barrels (261,870,000 gallons) in any consecutive 12-month period. (cumulative increase)
15. Material other than crude oil may be throughput to or stored at S1, S2, S4, or S23, if all of the following are satisfied:
 - a the storage of each material complies with all other conditions applicable these sources
 - b the storage of each material complies with all other applicable regulatory requirements
 - c the permittee keeps District approved records which demonstrate to the District's satisfaction that no toxin listed in Table 2-1-316 is emitted from S1, S2, S4, and S23 in an amount in excess of the toxin's respective trigger level set forth in Table 2-1-316.
(cumulative increase, toxics)
16. For S1, S2, S4, and S23, the true vapor pressure of each and all materials stored in each of S1, S2, S4 and S23 shall not exceed 11 psia.
(cumulative increase, offsets, toxics)
17. Deleted 08/26/00. S2 conversion is complete.
18. Part II.18 merged with part II.12.
19. Part II.19 merged with part II.12.
20. Deleted 08/26/00.
21. Deleted per AN 366, converted roof from a fixed roof to an external floating roof.
22. For each of S1, S2, S4, and S23, at the conclusion of each day, the

VI. Permit Conditions

permittee shall record, by material name, in a District approved log, the total volume of each and every liquid material throughput to each of S1, S2, S4, and S23 during that day, in gallon units or barrel units. At the conclusion of each month, the permittee shall total the daily log recordings separately for each of S1, S2, S4, and S23 and record the respective sum as the monthly throughput for each source, in a District approved log.

Additionally, the permittee shall record in a District approved log, the total volume of each and every liquid material throughput to S1, S2, S4, and S23 during each rolling 12 consecutive month period. This log shall be retained for at least 5 years from date of entry, shall be kept on site, and shall be made available to the District staff on request. (cumulative increase)

23. At the conclusion of each month, the permittee shall record in a District approved log, the 12 consecutive month sum total throughput of all liquid materials to S1, S2, S4, and S23 combined. This log shall be retained for at least 5 years from date of entry, it shall be kept on site, and it shall be made available to the District staff on request. (cumulative increase)

24. Material transferred from S1, S2, S4, and/or S23 which is not to be processed at S18 Crude Unit shall only be transferred (out of the) by pipeline and shall not be transferred by marine vessel. (cumulative increase)

S9 Internal Floating Roof Tank, TK-7; Capacity: 571,200 Gallons, White, Storing: Naphtha equipped with a mechanical shoe primary seal, rim mounted secondary seal, and welded deck

25. Material other than Naphtha may be throughput to or stored in S9, if all of the following are satisfied:

a the storage of each material complies with all other conditions applicable to this source

b the storage of each material complies with all other applicable regulatory requirements

c the permittee keeps District approved records which demonstrate to the District's satisfaction that no toxin listed in Table 2-1-316 is emitted from S9 in an amount in excess of the toxin's respective trigger level set forth in Table 2-1-316. (cumulative increase, toxics)

26. The true vapor pressure of each and all material stored in S9 shall not exceed 11 psia. (cumulative increase, toxics)

VI. Permit Conditions

27a. S9 shall not be operated unless it is equipped with a District approved internal floating roof with a mechanical shoe primary seal, a rim mounted secondary seal, and a welded deck. (cumulative increase, NSPS)

~~27b. S9 shall comply with Sections 60.112b(a) (iii) through 60.112b(a) (ix) of the New Source Performance Standards Subpart Kb. (NSPS)~~

28. The total throughput of all liquid materials to S9 shall not exceed 24,019,000 gallons (571,880 barrels) in any rolling 12 consecutive month period. (cumulative increase, toxics)

29. On a monthly basis, the permittee shall record in a District approved log the total volume of each and all liquid materials throughput to S9 each month and each rolling 12 consecutive month period, in gallon units or barrel units. This log shall be retained for at least 5 years from date of entry, shall be kept on site, and shall be made available to the District staff on request. (cumulative increase)

S13 Fixed Roof Storage Tank (TK-8); Capacity: 88,000 Gallons, Storing: Kerosene, Light or Heavy Vacuum Gas Oil, and Asphalt abated by (either) A3 Mist Eliminator F-10 and A31

H-7 (or) A20 Mist Eliminator F-500 and S24 Hot Oil Heater H-3

S59 Fixed Roof Storage Tank (TK-5); Capacity: 1,050,000 Gallons, Storing: Kerosene, Light or Heavy Vacuum Gas Oil and Asphalt, abated by (either) S24 Hot Oil Heater H-3 and A1 Mist Eliminator F-8 (or) A31

H-7 and A3 Mist Eliminator

F-10

S63 Kerosene/Light Vacuum Gas Oil/Heavy Vacuum Gas Oil/Asphalt Storage Tank, Fixed Roof, TK-31, Capacity: 1,218,000 Gallons abated by A3 Mist Eliminator F-10 and A31 H-7

(or) A20 Mist Eliminator F-8 and S24 Hot Oil Furnace H-3

30. Petroleum materials other than Kerosene, Light or Heavy Vacuum Gas Oil, and Asphalt may be stored in S13, S59, and S63 if all of the following are satisfied:

a the storage of each petroleum material complies with all other conditions applicable to S13, S59, or S63.

b the storage of each petroleum material complies with all other applicable regulatory requirements

VI. Permit Conditions

c the permittee keeps District approved records which demonstrate to the District's satisfaction that no toxin listed in Table 2-1-316 is emitted from S13, S59, or S63 in an amount in excess of the toxin's respective trigger level set forth in Table 2-1-316.
(cumulative increase, toxics)

31. The true vapor pressure of each material stored in S13, S59, or S63 shall not exceed 1.5 psia. (cumulative increase, toxics)

31a. To assure compliance with the limit in part 31, the permit holder shall take a sample from each tank on an annual basis and determine the true vapor pressure of the sample. Records of these analyses shall be retained for at least 5 years from the date of the analysis, shall be kept on site, and shall be made available to the District staff on request.
(cumulative increase, toxics)

32a. At all times that S13 stores petroleum materials, S13 shall be operated with a District approved vapor recovery system and S13 shall be abated by (either) A3 Mist Eliminator F-10 and A31
H-7 (or) A20 Mist Eliminator F-500 and S24
Hot Oil Heater H-3; with an overall collection and destruction efficiency of at least 98.5%, by weight. (Regulation 8-5-311.3, NSPS, and cumulative increase, toxics)

32b. At all times that S59 stores organic materials, S59 shall be operated with a District approved vapor recovery system and S59 organic emissions shall be abated by (either) A1 Mist Eliminator F-8 and S24 Hot Oil Heater H-3 (or) A3 Mist Eliminator F-10 and A31

H-7; with an overall collection and destruction efficiency of at least 98.5%, by weight.
(Regulation 8-5-311.3, NSPS, and cumulative increase, toxics)

32c. For S63, at all times that petroleum materials/VOC are in this equipment, S63 shall be operated with a District approved vapor recovery system with emissions ducted to and abated by (either) A3 Mist Eliminator F-10 and A31
H-7 (or) A20
Mist Eliminator F-500 and S24 Hot Oil Heater H-3; with a destruction efficiency of at least 98.5%, by weight, as measured across the combustion device (S24 or A31). (cumulative increase, NSPS, Regulation 8-5-311.3, offsets, BACT)

32d. For S63, the District approved vapor recovery system operated in conjunction with S63 shall operate such that it has no detectable fugitive organic emissions in excess of 100 ppmv, measured as total organic compounds. Total organic compounds is as defined in Regulation 8, Rule

VI. Permit Conditions

18. (BACT)

33a. The total combined throughput of all materials to S13, S59, and S63 shall not exceed 68,208,000 gallons (1,624,600 barrels) in any rolling 12 consecutive month period. (cumulative increase, toxics)

33b. Cutback asphalt materials including but not limited to SC Cutback Asphalt, MC Cutback Asphalt, and FM-1 Cutback Asphalt and other cutback asphalt materials shall NOT be stored in or transferred to S63. (toxics)

34. On a monthly basis, the permittee shall record in a District approved log the total volume of each liquid material throughput to S13, S59, or S63 by material name (e.g., kerosene, light vacuum gas oil, heavy vacuum gas oil, asphalt) each month and each rolling 12 consecutive month period, in gallon units or barrel units. This log shall be retained for at least 5 years from date of entry, shall be kept on site, and shall be made available to the District staff on request. (cumulative increase)

35. Deleted May, 2001

36. Deleted May, 2001

37. Deleted May, 2001

38. Deleted May, 2001

39. Deleted May, 2001

S3 Fixed Roof Storage Tank, TK-1C, Storing: Heavy Vacuum Gas Oil, Capacity: 3,415,000 Gallons operated with a District approved vapor recovery system and abated by (either) A3 Mist Eliminator F-10 and S24 Hot Oil Heater H-3 (or) A20 Mist Eliminator F-500 and A31

H-7

40. Materials other than Heavy Gas Oil may be stored in S3, if all of the following are satisfied:

- a the storage of each petroleum material complies with all other conditions applicable to S3
- b the storage of each petroleum material complies with all other applicable regulatory requirements
- c the permittee keeps District approved records which demonstrate to the District's satisfaction that no toxin listed in Table 2-1-316 is emitted

VI. Permit Conditions

from S3 in an amount in excess of the toxin's respective trigger level set forth in Table 2-1-316. (cumulative increase, toxics)

41. The permittee shall ensure that at least 38,300,000 gallons (the 1996 calendar year baseline throughput to S3) of gas oil is throughput exclusively to S3 for storage during every rolling 12 consecutive month period, prior to transferring/storing gas oil material into another vessel for which VOC emissions are not abated with a destruction efficiency of at least 98.5%, by weight. (offsets)

42. The true vapor pressure of each and all material stored in S3 shall not exceed 0.5 psia. (cumulative increase, NSPS)

43. At all times that S3 stores VOC, S3 shall be operated with a District approved vapor recovery system and S3 volatile organic compound emissions shall be abated by (either) A31

H-7 and A3 Mist Eliminator F-10 (or) S24 Hot Oil Heater H-3 and A20 Mist Eliminator F-500; with a destruction efficiency of at least 98.5%, by weight, as measured across the combustion device (S24 or A31). (cumulative increase, offsets, BACT)

44. The District approved vapor recovery system operated in conjunction with S3 shall operate under negative pressure and ensure that S3, including the District approved vapor recovery system, has no detectable fugitive organic emissions in excess of 100 ppmv, measured as total organic compounds. The vapor recovery system shall be monitored in accordance with BAAQMD Regulation 8, Rule 18. (BACT, cumulative increase, offsets)

45. All tank fittings present at S3 shall be gasketed. (BACT)

46. At the conclusion of each month, the permittee shall record in a District approved log the total volume of each and all liquid materials throughput to S3 during that month and for each rolling 12 consecutive month period, in gallon units or barrel units. This log shall be retained for at least 5 years from date of entry, shall be kept on site, and shall be made available to the District staff on request. (cumulative increase)

47. Deleted 11/29/99. Start-up condition

S5 Asphalt Storage Tank, Fixed Roof, TK-2A, Capacity: 3,415,000 Gallons abated by A3 Mist Eliminator F-10 and A31

VI. Permit Conditions

H-7 (or) A1 Mist Eliminator F-8 and S24 Hot Oil Furnace
H-3

S6 Asphalt Storage Tank, Fixed Roof, TK-2B, Capacity:
3,415,000 Gallons abated by A3 Mist Eliminator F-10 and A31
H-7 (or) A1 Mist Eliminator F-8 and S24 Hot Oil
Furnace H-3

S7 Asphalt Storage Tank, Fixed Roof, TK-3, Capacity:
1,050,000 Gallons abated by A3 Mist Eliminator F-10 and A31
H-7 (or) A1 Mist Eliminator F-8 and S24 Hot Oil
Furnace H-3

S8 Asphalt Storage Tank, Fixed Roof, TK-4, Capacity: 1,050,000
Gallons abated by A3 Mist Eliminator F-10 and A31
H-7 (or) A1 Mist Eliminator F-8 and S24 Hot Oil
Furnace H-3

S37 Asphalt Storage Tank, Fixed Roof, TK 54, Capacity: 100,000
Gallons abated by A3 Mist Eliminator F-10 and A31
H-7 (or) A20 Mist Eliminator F-500 and S24 Hot
Oil Furnace H-3

S38 Asphalt Storage Tank, Fixed Roof, TK-55, Capacity:
100,000 Gallons abated by A3 Mist Eliminator F-10 and A31
H-7 (or) A20 Mist Eliminator F-500 and S24 Hot
Oil Furnace H-3

S51 Asphalt Storage Tank TK-506; Fixed Roof Tank, Capacity: 152,880
Gallons abated by A3 Mist Eliminator F-10 and A31
H-7 (or) A20 Mist Eliminator F-500 and S24 Hot
Oil Furnace H-3

S52 Asphalt Storage Tank TK 507, Fixed Roof Tank, Capacity: 152,880
Gallons abated by A3 Mist Eliminator F-10 and A31
H-7 (or) A20 Mist Eliminator F-500 and S24 Hot
Oil Furnace H-3

S53 Asphalt Storage Tank TK 508, Fixed Roof Tank, Capacity: 152,880
Gallons abated by A3 Mist Eliminator F-10 and A31
H-7 (or) A20 Mist Eliminator F-500 and S24 Hot
Oil Furnace H-3

VI. Permit Conditions

S60 Asphalt Storage Tank TK-505; Fixed Roof, Capacity:
15,000 Gallons abated by (either) A20 Mist
Eliminator F-500 and S24 Hot Oil Heater H-3
(or) A3 Mist Eliminator F-10 and A31
H-7

S61 Asphalt Storage Tank, Fixed Roof, TK-30A, Capacity:
995,400 Gallons abated by A3 Mist Eliminator F-10
and A31 H-7 (or) A20 Mist
Eliminator F-8 and S24 Hot Oil Furnace H-3

S62 Asphalt Storage Tank, Fixed Roof, TK-30B, Capacity:
995,400 Gallons abated by A3 Mist Eliminator F-10
and A31 H-7 (or) A20 Mist
Eliminator F-8 and S24 Hot Oil Furnace H-3

S65 Asphalt Storage Tank, Fixed Roof, TK-32 Tank Capacity: 6,920,000
Gallons abated by A3 Mist Eliminator F-10 and A31
H-7 (or) A1 Mist Eliminator F-8 and S24 Hot Oil
Furnace H-3

48. The sum total asphalt throughput to S5, S6, S7, S8, S37, S38, S51,
S52, S53, S60, S61, S62, and S65 shall not exceed 6,738,349 barrels
(283,010,658 gallons) in any 12 consecutive month period. (cumulative
increase, offsets)

49. For S5, S6, S7, S8, S37, S38, S51, S52, S53, S60, S61, S62, S65:
Cutback asphalt materials including but not limited to SC Cutback
Asphalt, MC Cutback Asphalt, and FM-1 Cutback Asphalt and other
cutback asphalt materials SHALL NOT BE stored in or transferred to any
of the above tanks. (toxics)

50. For S5, S6, S7, S8, S37, S38, S51, S52, S53, and S60: the true vapor
pressure of each and all materials stored in each tank shall not exceed 0.5
psia. (cumulative increase, offsets)

51. For S61 and S62, the true vapor pressure of each and all materials
stored in each tank shall not exceed 0.49 psia. (cumulative increase,
offsets, NSPS, BACT)

52. For S65, the true vapor pressure of each and all materials stored in

VI. Permit Conditions

S65 shall not exceed 0.49 psia. (cumulative increase, offsets, BACT)

53. The District approved vapor recovery system operated in conjunction with S65 shall operate under negative pressure and ensure that S65, including the District approved vapor recovery system, has no detectable fugitive organic emissions in excess of 100 ppmv, measured as total organic compounds. The vapor recovery system shall be monitored in accordance with BAAQMD Regulation 8, Rule 18. (BACT, cumulative increase)

54. Deleted May, 2001.

55. Whenever petroleum materials or VOC are stored at S5, S6, S7, S8, S37, and S38, each source shall be operated with a District approved vapor recovery system with emissions ducted to and abated by (either) A1 Mist Eliminator F-8 and S24 Hot Oil Heater H-3 (or) A31

H-7 and A3 Mist Eliminator F-10 and; with a destruction efficiency of at least 98.5%, by weight, as measured across the combustion device (S24 or A31). (cumulative increase, offsets)

56. Whenever petroleum materials or VOC are stored at S51, S52, S53, S60, and S65, each source shall be operated with a District approved vapor recovery system with emissions ducted to and abated by (either) A3 Mist Eliminator F-10 and A31 H-7 (or) A20 Mist Eliminator F-500 and S24 Hot Oil Heater H-3; with a destruction efficiency of at least 98.5%, by weight, as measured across the combustion device (S24 or A31). (cumulative increase, offsets)

57. Whenever petroleum materials or VOC are stored in S61 and/or S62, each source shall be operated with a District approved vapor recovery system with emissions ducted to and abated by (either) A3 Mist Eliminator F-10 and A31 H-7 (or) A20 Mist Eliminator F-500 and S24 Hot Oil Heater H-3; with a destruction efficiency of at least 98.5%, by weight, as measured across the combustion device (S24 or A31). (cumulative increase, offsets, BACT)

58. Separately, for each of S5, S6, S7, S8, S37, S38, S51, S52, S53, S60, S61, S62 and S65, at the conclusion of each month, the permittee shall record, by material name, in a District approved log, the total volume of each liquid material throughput to each tank during that month and during each rolling 12 consecutive month period, in gallon units or barrel units. This log shall be retained for at least 5 years from date of entry, shall be

VI. Permit Conditions

kept on site, and shall be made available to the District staff on request.
(cumulative increase)

58a.

VI. Permit Conditions

S14 Naphtha Loading Racks abated by A4 Loading
H-6

59. S14 shall be operated with a submerged fill pipe and be abated by A4 Loading H-6 at all times that materials are transferred at S14. (cumulative increase, offsets, BACT, toxics)

60. S14 emissions shall be captured by a District approved vapor recovery system and shall be abated by A4 Loading H-6 with a destruction efficiency of at least 98.5%, by weight, as measured across A4 or S19. (cumulative increase, offsets, BACT, toxics)

61a. The true vapor pressure of the materials transferred at S14 shall not exceed 11 psia. (cumulative increase, offsets, toxics)

61b. The total throughput of naphtha to S14 shall not exceed 25,749,000

VI. Permit Conditions

gallons (613,000 barrels) during any consecutive 12-months. (cumulative increase)

S15 Kerosene and Light Vacuum Gas Oil Loading Rack abated by A4 Loading H-6

62. S15 shall be operated with a submerged fill pipe and be abated by A4 Loading H-6 at all times that materials are transferred at S15. (cumulative increase, offsets, BACT, toxics)

63. S15 emissions shall be captured by a District approved vapor recovery system and shall be abated by A4 Loading H-6 with a destruction efficiency of at least 98.5%, by weight, as measured across A4 or S19. (cumulative increase, offsets, BACT, toxics)

64a. The true vapor pressure of the materials transferred at and/or sampled from S15 shall not exceed 1.5 psia. All materials loaded at S15 must be transferred from Tanks S13, S59, or S63. (cumulative increase, offsets, toxics)

64b. The total combined throughput of Kerosene and Light Vacuum Gas Oil to S15, shall not exceed 283,011,000 gallons (1,483,000 barrels) during any consecutive 12-months. (cumulative increase, offsets, toxics)

S17 Asphalt Loading Racks abated by A2 Mist Eliminator F-9 and A4 Loading H-6

S31 Rail Car Loading Rack; 5 Loading Arms, Loading: Asphalt and Light Vacuum Gas Oil abated by A6 Mist Eliminator F-3 and A31 H-7

S54 Asphalt and Light Vacuum Gas Oil Loading Rack abated by A3 Mist Eliminator F-10 and A31 H-7

65. S17 shall be abated by A2 Mist Eliminator F-9 and A4 Loading H-6 at all times that materials are transferred at S17. (cumulative increase)

66. S31 shall be abated by A6 Mist Eliminator F-3 and A31 H-7 at all times that materials are transferred at

VI. Permit Conditions

S31. (cumulative increase)

67. S54 shall be abated by (either) A3 Mist Eliminator F-10 and A31 H-7 (or) A20 Mist Eliminator F-500 and S24 Hot Oil Heater H-3 at all times that materials are transferred at S54. (cumulative increase)

68. Emissions from S17 shall be captured by a District approved vapor recovery system and shall be abated by A2 Mist Eliminator F-9 and A4 Loading H-6 with a destruction efficiency of at least 98.5%, by weight, as measured across A4. (cumulative increase, BACT)

69. Emissions from S31 shall be captured by a District approved vapor recovery system and shall be abated by A6 Mist Eliminator F-3 and A31 H-7 with a destruction efficiency of at least 98.5%, by weight, as measured across A31. (cumulative increase, BACT)

70. Emissions from S54 shall be captured by a District approved vapor recovery system and shall be abated by (either) A3 Mist Eliminator F-10 and A31 H-7 (or) A20 Mist Eliminator F-500 and S24 Hot Oil Heater H-3 with a destruction efficiency of at least 98.5%, by weight, as measured across that combustion device(s) abating S54 (A31 and/or S24). (cumulative increase, BACT)

71. The true vapor pressure of the materials transferred at or sampled from S17 and/or S 54 shall not exceed 0.5 psia. (cumulative increase, offsets)

72. The true vapor pressure of the materials transferred at or sampled from S31 shall not exceed 1.5 psia, unless the material contains asphalt. (cumulative increase, toxics, offsets)

73. If asphalt or any asphalt containing material or any material blended with asphalt is transferred at or sampled from S31, the true vapor of the material may not exceed 0.5 psia. (cumulative increase, toxics, offsets)

74. The total combined throughput of asphalt and all asphalt containing materials to S17, S31, and S54 shall not exceed 283,011,000 gallons during any consecutive 12-months. (cumulative increase, offsets)

VI. Permit Conditions

75. The permittee shall maintain a District approved log of the monthly throughput of asphalt and all asphalt containing materials to S17, S31, and S54 in gallon units or barrel units during each month and during each rolling 12 consecutive month period, in gallon units or barrel units. This log shall be retained for at least 5 years from date of entry, shall be kept on site, and shall be made available to the District staff on request.

(cumulative increase)

76. Deleted May, 2001.

77. Deleted May, 2001.

78. Deleted May, 2001.

79. Deleted May, 2001.

80. Deleted May, 2001.

81. Deleted May, 2001.

82. Deleted May, 2001.

S66 Oil Water Separator, Physical Capacity: 830 GPM, Permitted Capacity: 210 GPM abated by (either) A3 Mist Eliminator F-10 and A31 H-7 (or) A20 Mist Eliminator F-8 and S24 Hot Oil Furnace H-3

83 The permittee shall ensure that the throughput of liquid material to S66 shall not exceed 110,376,000 gallons per year (210 gallons per minute). (basis: cumulative increase)

84 The cover and each access opening at S66 shall be closed vapor tight (as defined in Regulation 8, Rule 8), and gasketed. (basis: Reg. 8, Rule 8)

85 S66 shall be operated with a District approved vapor recovery system with S66 emissions ducted to and abated by (either) A3 Mist Eliminator F-10 and A31 H-7 (OR) A20 Mist Eliminator F-500 and S24 Hot Oil Heater H-3; with a destruction efficiency of at least 98.5%, by weight, as measured across the combustion device (S24 or A31). (basis: BACT, cumulative increase, contemporaneous emission reductions)

VI. Permit Conditions

86 The District approved vapor recovery system operated in conjunction with S66 shall operate under negative pressure and ensure that S66, including the District approved vapor recovery system, has no detectable fugitive organic emissions in excess of 100 ppmv, measured as total organic compounds. The vapor recovery system shall be monitored in accordance with BAAQMD Regulation 8, Rule 18. (basis: BACT, cumulative increase, contemporaneous emission reductions)

87 Not less frequently than on a monthly basis, the permittee shall measure and record the volume (in gallons) of oil (slop oil) product recovered at S66 and not less frequently than on a monthly basis, the permittee shall measure and record the volume (in gallons) of waste water product recovered at S66 (waste water discharge to City of Benicia). The sum of the volume of slop oil product and the volume of wastewater product shall recorded in a District approved log as the throughput of liquid material to S66. (basis: cumulative increase)

88 On a monthly basis, the permittee shall record in a District approved log the total volume of all liquid materials throughput to S66 each month, in gallon units or barrel units. This log shall be retained for at least 5 years from date of entry, shall be kept on site, and shall be made available to the District staff on request. (basis: cumulative increase)

89

S16 Kerosene and Heavy Vacuum Gas Oil Loading Rack

90. The true vapor pressure of the materials transferred at and/or sampled from S16 shall not exceed 0.49 psia. (cumulative increase)

91. The total throughput of materials transferred through S16 shall not exceed 25,749,000 gallons (613,000 barrels) during any consecutive 12-months. (cumulative increase)

VI. Permit Conditions

()

S41 Wemco Hydrocleaner Induced Air Floatation Machine abated by A1 Mist Eliminator and S24 Hot Oil Furnace H-3 (or) A3 Mist Eliminator F-10 and A31

92. The permittee shall ensure that the throughput of liquid material to S66 shall not exceed 77,263,200 gallons per year (147 gallons per minute). (basis: cumulative increase)

()

III. MARINE OPERATIONS CONDITIONS

1. shall be limited to a total of 12 ships per year at their wharf. These ships shall be exclusively steam vessels less than 49 MDWEIGHT capacity.

2. While operating within District waters, any vessel delivering raw material to the refinery shall use fuel oil with a maximum sulfur content of 2.9% by weight in all combustion units. In addition, all ballasting within District waters shall be accomplished by using dedicated tanks containing no volatile organic compounds. These conditions shall be stipulated in the ~~charter purchase~~ agreement between and the ~~ship owners~~ supplier delivering the raw material to the asphalt plant.
purchase

maintained on-site for District review.

3. While any vessel is in port, all refinery combustion units shall be fired exclusively on natural gas or refinery fuel gas with the maximum H2S content of 10 ppm (by volume).

4. District personnel shall have free access to board the tankers delivering material to while in District waters.

VI. Permit Conditions

5. shall report all marine operations within District waters on a monthly basis. This report shall include all information on ballasting and offloading required by the District in order to determine emissions.

6. Marine loading and shipping of Bunker C fuel oil and gas oil may be done by barges with a capacity less than 100,000 bbls. No more than six barge loadings shall be made in any given month and no more than one barge loading shall be made on any given day. No barge loading shall be made on any day on which a vessel is delivering raw material to

WEIGHT

VI. Permit Conditions

IV. ODOR REDUCTION MEASURES (Added per AN 14513, 9/95)

1. _____ will maintain water seals, P-traps, caps, covers or equivalent on all process water drains.

2. _____ will implement an Asphalt Tank Truck Dome Inspection Program for all asphalt tank trucks that they load. If a truck enters the _____ facility with a leaking or malfunctioning dome lid, _____ will take the following action.
 - a. First occurrence in rolling twelve month period:
_____ will orally notify the truck driver and dispatcher of the faulty dome lid, and request that the lid be repaired prior to the truck re-entering the facility.

 - b. Second occurrence in a rolling twelve month period:
_____ will notify the driver and the trucking company in writing that if the truck enters the facility again with a malfunctioning dome hatch, _____ will not load the truck until the hatch has been repaired.

 - c. Third occurrence in a rolling twelve-month period:
_____ will not load the truck. _____ will also notify the driver and dispatcher, verbally and in writing, that the truck will not be loaded until the hatch has been repaired, and the repair has been inspected or repair documentation has been received by _____ to ensure that the hatch is in proper working order.

- _____ shall keep records of all inspections and notifications. These records shall be made available to the District upon request.

3. _____ shall provide written notification of the Asphalt Tank Truck Dome Inspection Program to any additional trucking company that may do business with _____ in the future, within two weeks of the first asphalt receipt.

V. OTHER SOURCES

VI. Permit Conditions

S24 Hot Oil Heater H-3; Max Firing Rate 9 MM BTU/hr

1. Respective emissions of nitrogen oxides, ~~expressed as NO₂~~, and carbon monoxide (CO) from S24 shall not exceed 30 ppm and 50 ppm at 3% O₂.

Condition #18796

For S68, Emergency Diesel-powered Firewater Pump

- *1. The engine for emergency firewater pump S-68 shall be fired exclusively on diesel fuel having a sulfur content no greater than 0.05% by weight. The sulfur content of the fuel oil shall be certified by the fuel oil vendor. (Basis: Cumulative Increase)
- *2. S-68 shall only be operated to mitigate emergency conditions or for reliability-related activities. Operation for reliability-related activities shall not exceed 100 hours in any calendar year at each engine. Operation while mitigating emergency conditions is unlimited. (Basis: Regulation 9-8-330, Cumulative Increase)
- *3. "Emergency Conditions" is defined as any of the following:
 - a. Loss of regular natural gas supply
 - b. Failure of regular electric power supply
 - c. Flood mitigation
 - d. Sewage overflow mitigation
 - e. Fire
 - f. Failure of a primary motor, but only for such time as needed to repair or replace the primary motor

Condition #18796

For S68, Emergency Diesel-powered Firewater Pump

(Basis: Regulation 9-8-231)

- *4. "Reliability-related activities" is defined as any of the following:
 - a. Operation of an emergency standby engine to test its ability to perform for an emergency use, or
 - b. Operation of an emergency standby engine during maintenance of a primary motor

VI. Permit Conditions

(Basis: Regulation 9-8-232)

- *5. S-68 shall be equipped with either:
- a. a non-resettable totalizing meter that measures and records the hours of operation for the engine
- OR
- b. a non-resettable fuel usage meter (12 gallons of fuel shall be assumed to be equivalent to 1 hour of reliability-related operation)

(Basis: Regulation 9-8-530)

- *6. The following monthly records shall be maintained in a District-approved log for at least 5 years for S-68 and shall be made available for District inspection upon request:
- a. Total hours of operation for the engine
 - b. Hours of operation under emergency conditions for the engine and a description of the nature of each emergency condition
 - c. Fuel usage for the engine

(Basis: Regulation 9-8-530)

VII. APPLICABLE LIMITS & COMPLIANCE MONITORING REQUIREMENTS

This section has been included only to summarize the applicable emission limits contained in Section IV, Source-Specific Applicable Requirements, of this permit. The following tables show the relationship between each emission limit and the associated compliance monitoring provisions, if any. The monitoring frequency indicates whether periodic (P) or continuous (C) monitoring is required. For periodic monitoring, the frequency of the monitoring has also been shown, using the following codes: annual (A), semi-annual (SA), quarterly (Q), monthly (M), weekly (W), daily (D), hourly (H), or on an event basis (E). No monitoring (N) has been required if the current applicable rule or regulation does not require monitoring, and the operation is unlikely to deviate from the applicable emission limit based upon the nature of the operation.

**Table VII – Refinery
 Applicable Limits and Compliance Monitoring Requirements
 REFINERY-WIDE APPLICABILITY**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency	Monitoring Type
NOX	BAAQMD Condition 1240, part I.14	Y		Emissions of NOX < 40 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18h and I.18j	P/A	Calculations
Ambient SO ₂	BAAQMD 9-1-301	Y		Ground level SO ₂ concentrations (0.5 ppm for 3 min; 0.25 ppm for 60 min; 0.05 ppm for 24 hr)	BAAQMD 9-1-501, 9-1-310.3, and 9-1-110	C	SO ₂ GLM
Ambient H ₂ S	BAAQMD 9-2-301	N		Limitations on H ₂ S ground level concentrations	BAAQMD 9-2-501	C	H ₂ S GLM
		Y		Refinery MACT Startup, Shutdown, Malfunction Report	40 CFR 63 Subpart CC 63.654(h)	P/SA	Report
		Y		Refinery MACT Periodic Report	40 CFR 63 Subpart CC 63.654(g)	P/SA	Report
Benzene		Y		Benzene Waste NESHAP Annual Report	40 CFR 61 Subpart FF 61.357(d)(2)	P/A	Report

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – Refinery
 Applicable Limits and Compliance Monitoring Requirements
 REFINERY-WIDE APPLICABILITY**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency	Monitoring Type
Benzene				Benzene Waste NESHAP Quarterly Report	40 CFR 61 Subpart FF 61.357(d)(7)	P/Q	Report
	40 CFR 61 Subpart FF 61.346(b)(1)	Y		Benzene Waste NESHAP quarterly visual inspection of water seals on drains	40 CFR 61 Subpart FF 61.346(b)(4)(i)	P/Q	Visual Inspection
	40 CFR 61 Subpart FF 61.346(b)(2)(i)	Y		Benzene Waste NESHAP quarterly visual inspection of tight seals on junction boxes	40 CFR 61 Subpart FF 61.346(b)(4)(iii)	P/Q	Visual Inspection
	40 CFR 61 Subpart FF 61.346(b)(3)	Y		Benzene Waste NESHAP quarterly visual inspection for cracks in exposed sewer lines	40 CFR 61 Subpart FF 61.346(b)(4)(iv)	P/Q	Visual Inspection
SO2	BAAQMD 9-1-302	Y		General emission standard: < 300 ppm SO2 (applies only to gas-fired equipment when GLMs are not functioning)		N	
	BAAQMD Condition 1240, part I.14	Y		Emissions of SO2 < 28 tons per year excluding marine emissions		N	
H2S	BAAQMD 9-1-313.2	N		Recovery of 95% of H2S in refinery fuel gas	BAAQMD Condition 1240, part I.13	C	H2S CEM
	SIP 9-1-313.2	Y		Recovery of 95% of H2S in refinery fuel gas	BAAQMD Condition 1240, part I.13	C	H2S CEM
	BAAQMD 9-1-313.2	N		Removal of 95% of H2S from process water streams			

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – Refinery
 Applicable Limits and Compliance Monitoring Requirements
 REFINERY-WIDE APPLICABILITY**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency	Monitoring Type
H2S	SIP 9-1-313.2	Y		Removal of 95% of H2S from process water streams			
Benzene in Waste	40 CFR 61 Subpart FF 61.342(e)(2)(i)	Y		Uncontrolled benzene <6 megagrams/year	40 CFR 61 Subpart FF 61.357(d)(5)	P/A	Report
Benzene in Waste	61.345(b)	Y		Visual inspection of container covers	40 CFR 61 Subpart FF 61.345(b)	P/Q	Visual Inspection
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18c and I.18j	P/A	Calculations
VOC	BAAQMD 8-5-328.2	Y		Tank cleaning control device standard; includes 90% abatement efficiency requirement.	8-5-502	P/A	Source test
	BAAQMD 8-5-328.2	Y		Concentration of < 10,000 ppm as methane after cleaning	8-5-503	P/E	Portable hydrocarbon detector

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S1, S2, S4, S23- CRUDE STORAGE TANKS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-5-320	Y		Deck fitting closure standards; includes gasketed covers	BAAQMD 8-5-402.1	P/10 yr interval with "zero-gap" secondary seal	Measurement and visual inspection
	BAAQMD 8-5-321	Y		Primary rim-seal standards; includes gap criteria	BAAQMD Condition 1240, Part II.13 (BAAQMD 8-5-401.1, 8-5-404.1 subsumed by permit condition. See permit shield.)	P/Q	Seal inspection
	BAAQMD 8-5-322	Y		Secondary rim-seal standards; includes gap criteria	BAAQMD Condition 1240, Part II.13 (BAAQMD 8-5-402.1 8-5-404.2.1 subsumed by permit condition. See permit shield.)	P/A	Seal inspection
VOC		Y		Report on seal condition and gap measurements	BAAQMD 8-5-404, 8-5-405	P/E After each tank seal inspection	Inspection report

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S1, S2, S4, S23- CRUDE STORAGE TANKS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC				None	BAAQMD 8-5-501	P/E	Records of liquids stored and TVPs
VOC	60.113b (b)(4)(i)	Y		Primary rim-seal standards; includes gap criteria. Repairs are required if accumulated area of gap exceeds 212 sq. cm/m of vessel diameter, width of any portion of the gap exceeds 3.81 cm, the vertical distance of seal is less than 61 cm above the liquid surface, or there are holes, tears or openings in shoe, seal fabric, or seal envelope.	60.113b (b)(1)-(b)(3)	P/5 yr intervals	Measurement and visual inspection
	60.113b (b)(4)(ii)	Y		Secondary rim-seal standards; includes gap criteria. Repairs are required if accumulated area of gap exceeds 21.2 sq. cm/m of vessel diameter, width of any portion of the gap exceeds 1.27 cm, or there are holes, tears or openings in seal or seal fabric	60.113b (b)(1)-(b)(3)	P/A	Measurement and visual inspection
VOC		Y			60.116b(c)	P/E Upon change of service	Record of liquid stored and true vapor pressure

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S1, S2, S4, S23- CRUDE STORAGE TANKS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC		Y		None	60.113b (b)(6)	P/E (Each time tank is emptied & degassed)	Visual inspection of roof, seals, and fittings
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18c and I.18j	P/A	Calculations

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – B
Applicable Limits and Compliance Monitoring Requirements
S3, GAS OIL STORAGE TANK, TK-1C

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC				None	BAAQMD 8-5-501	P/E	Records of liquids stored and TVPs
VOC	<u>BAAQMD Condition 1240, part I.14</u>	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	<u>BAAQMD Condition 1240, part I.18c and I.18j</u>	P/A	Calculations
	BAAQMD Condition 1240, part II.41	Y		38,300,000 gallons of gas oil must be transferred to S3 every 12-month period before gas oil is stored in a tank without 98.5% control	BAAQMD Condition 1240, part II.46	P/M	Records
	BAAQMD Condition 1240, part II.42	Y		Vapor pressure shall not exceed 0.5 psia	BAAQMD Condition 1240, part II.46	P/M	Records
	BAAQMD Condition 1240, part II.43	Y		98.5% control efficiency	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition 1240, part II.44	Y		Fugitive emissions at vapor recovery system (S24 or A31) shall not exceed 100 ppmv	BAAQMD Condition 1240, part II.44	P/Q or A	Method 21

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - C
Applicable Limits and Compliance Monitoring Requirements
S5, S6, S7, S8, S37, S38-ASPHALT STORAGE TANKS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour	BAAQMD Condition #1240, II.58b	C	Temperature monitoring
	40 CFR 60.472(c)	Y		0 percent opacity except for one consecutive 15-min period in any 24-hr period for cleaning	40 CFR 60.473(c) and BAAQMD Condition #1240, II.58b	C	Temperature monitoring
FP	BAAQMD 6-310	Y		0.15 gr/dscf	BAAQMD Condition #1240, II.58b	C	Temperature monitoring
VOC	BAAQMD 8-15-305			None	BAAQMD 8-15-501	P/E	Records
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18c and I.18j	P/A	Calculations
	BAAQMD Condition #1240, II.50	Y		Vapor pressure may not exceed 0.5 psia	BAAQMD Condition #1240, II.58	P/M	Records
	BAAQMD Condition #1240, II.55	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
Through-put limit	BAAQMD Condition #1240, II.48	Y		6,738,349 barrels/yr total for S5, S6, S7, S8, S37, S38, S51, S52, S53, S60, S61, S62, and S65	BAAQMD Condition #1240, II.58	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – D
Applicable Limits and Compliance Monitoring Requirements
S9, NAPHTHA STORAGE TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-5-320	Y		No gaps > 0.32 cm in viewports or other openings	BAAQMD 8-5-402.2	Internal inspection every 10 years	Measurement and visual inspection
	BAAQMD 8-5-311.2, 8-5-321.1, 8-5-322.1			Primary and secondary seals in accordance with 8-5-311.2. No holes, tears or openings in primary or secondary seal fabric	BAAQMD 8-5-403	P/A	Internal visual inspection from viewports on fixed roof
VOC	BAAQMD 8-5-321.3.1	Y		Maximum gap between shoe and tank shell < 3 in. for a length of 18 in. in vertical plane above liquid surface	BAAQMD 8-5-401	P/every 10 years	Primary seal inspection
	BAAQMD 8-5-321.3.2	Y		No gap between tank shell and primary seal > 1.5 in.	BAAQMD 8-5-401	P/every 10 years	Primary seal inspection
	BAAQMD 8-5-321.3.2	Y		No continuous gap > 0.125 in shall exceed 10% of circumference of tank	BAAQMD 8-5-401	P/every 10 years	Primary seal inspection
	BAAQMD 8-5-321.3.2	Y		Cumulative length of all primary seal gaps > 0.5 in. < 10% of circumference	BAAQMD 8-5-401	P/every 10 years	Primary seal inspection
	BAAQMD 8-5-321.3.2	Y		Cumulative length of all primary seal gaps > 0.125 in. < 40% of circumference	BAAQMD 8-5-401	P/every 10 years	Primary seal inspection
	BAAQMD 8-5-322.3	Y		Cumulative length of all secondary seal gaps > 0.125 in. < 5% of circumference	BAAQMD 8-5-402.2	P/every 10 years	Secondary seal inspection
VOC	BAAQMD 8-5-322.5	Y		No gap between tank shell and secondary seal > 0.06 in.	BAAQMD 8-5-402.1 and 402.2	P/every 10 years	Secondary seal inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – D
Applicable Limits and Compliance Monitoring Requirements
S9, NAPHTHA STORAGE TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-5-322.5	Y		Cumulative length of all secondary seal gaps > 0.02 in. < 5% of circumference excluding gaps < 1.79 in. from vertical seams	BAAQMD 8-5-402.1 and 402.2	P/every 10 years	Secondary seal inspection
				None	BAAQMD 8-5-501	P/E	Records of liquids stored and TVPs
	40 CFR 60.113b(a) (1)	Y		Repair of defects: detached seal, liquid on roof, holes or tears in seal fabric	40 CFR 60.113b(a)(1)	P/E (before filling vessel)	Visual inspection
VOC	40 CFR 60.113b(a) (2)	Y		Repair of defects: detached seal, liquid on roof, holes or tears in seal fabric	40 CFR 60.113b(a)(2)	P/A	Visual inspection
	40 CFR 60.113b(a) (4)	Y		Repair of defects: detached seal, liquid on roof, holes or tears in seal fabric	40 CFR 60.113b(a)(4)	P/E (when tank is emptied and degassed) and at least every 10 years	Visual inspection
				None	40 CFR 60.116b(c)	P/E Upon change of service	Records of maximum true pressure of volatile organic liquids

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – D
Applicable Limits and Compliance Monitoring Requirements
S9, NAPHTHA STORAGE TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18c and I.18j	P/A	calculations
	BAAQMD Condition 1240, part II.26	Y		Vapor pressure shall not exceed 11 psia	BAAQMD Condition 1240, part II.29	P/M	Records
Through-put	BAAQMD Condition 1240, part II.28			< 24,019,000 gallons in any consecutive 12-month period	BAAQMD Condition 1240, part II.29	P/M	Records

Table VII – E
Applicable Limits and Compliance Monitoring Requirements
S12, SKIMMED OIL TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	40 CFR 61.349(a)(1)(I)	Y			40 CFR 61.349(f)	P/Q	Visual inspection
	40 CFR 61.349(a)(1)(ii)(B)	Y		Car-sealed valves on bypass lines	40 CFR 61.354(f)(1)	P/M	Visual inspection
VOC	40 CFR 61.349(a)(2)(i)(A)	Y		95% control (by A31 incinerator)	40 CFR 61.354(c)(1)	C	Temperature measurement

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – E
Applicable Limits and Compliance Monitoring Requirements
S12, SKIMMED OIL TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	40 CFR 61.349(a)(2)(i)(A)	Y		95% control (by S24 process heater)	40 CFR 61.354(c)(4)	C	Temperature measurement
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18e and I.18j	P/A	Calculations

Table VII – F
Applicable Limits and Compliance Monitoring Requirements
S13, KEROSENE TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-5-311.3	Y		95% control of organic vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
VOC				None	BAAQMD 8-5-501	P/E	Records of liquids stored and TVPs
VOC	40 CFR 60.112b(a)(3)(ii)	Y		95% control of inlet VOC	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – F
Applicable Limits and Compliance Monitoring Requirements
S13, KEROSENE TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18c and I.18j	P/A	Calculations
	BAAQMD Condition 1240, part II.31	Y		Vapor pressure shall not exceed 1.5 psia	BAAQMD Condition 1240, part II.31a	P/A	determination of vapor pressure
	BAAQMD Condition 1240, part II.32a	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
Through-put	BAAQMD Condition 1240, part II.33a			< 68,208,000 gallons in any consecutive 12-month period for S13, S59, and S63 total	BAAQMD Condition 1240, part II.34	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – G
Applicable Limits and Compliance Monitoring Requirements
S14, LOADING RACKS, NAPHTHA

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-6-301	Y		21 g/cubic meter (0.17 lb/1000 gallons) (control by A4)	BAAQMD Condition 1240, part I.19	C	Temperature monitoring
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18d and I.18j	P/A	Calculations
	BAAQMD Condition #1240, part II.60	Y		98.5% destruction of vapors by weight	BAAQMD Condition 1240, part I.19	C	Temperature monitoring
	BAAQMD Condition #1240, part II.61a	Y		Vapor pressure < 11 psia	BAAQMD Condition 1240, part II.29	P/M	Records
Through-put limit	BAAQMD Condition #1240, part II.61b	Y		25,749,000 gallons/any consecutive 12 months	BAAQMD 8-6-501.2	P/M	records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – H
Applicable Limits and Compliance Monitoring Requirements
S15, LOADING RACKS, GAS OIL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-6-301	Y		21 g/cubic meter (0.17 lb/1000 gallons) (control by A4)	BAAQMD Condition 1240, part I.19	C	Temperature monitoring
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18d and I.18j	P/A	Calculations
	BAAQMD Condition #1240, part II.63	Y		98.5% destruction of vapors by weight	BAAQMD Condition 1240, part I.19	C	Temperature monitoring
VOC	BAAQMD Condition #1240, part II.64a	Y		Vapor pressure < 1.5 psia		N	
Through-put limit	BAAQMD Condition #1240, part II.64b	Y		283,011,000 gallons/any consecutive 12 months	BAAQMD 8-6-501.2	P/M	records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – I
Applicable Limits and Compliance Monitoring Requirements
S16, LOADING RACKS, KEROSENE OR DISTILLATE OIL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18d and I.18j	P/A	Calculations
VOC	BAAQMD Condition #1240, part II.90	Y		Vapor pressure < 0.49 psia		None	
Through-put limit	BAAQMD Condition #1240, part II.91	Y		25,749,000 gallons/any consecutive 12 months	BAAQMD Condition #1240, part II.91a	P/M	Records

Table– VII - J
Applicable Limits and Compliance Monitoring Requirements
S17, LOADING RACKS-ASPHALT

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-15-305			None	BAAQMD 8-15-501	P/E	Records
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18d and I.18j	P/A	Calculations

VII. Applicable Limits and Compliance Monitoring Requirements

Table– VII - J
Applicable Limits and Compliance Monitoring Requirements
S17, LOADING RACKS-ASPHALT

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition #1240, part II.68	Y		98.5% destruction of vapors by weight	BAAQMD Condition 1240, part I.19	C	Temperature monitoring
	BAAQMD Condition #1240, part II.71	Y		Vapor pressure < 0.5 psia	BAAQMD Condition #1240, part II.75	P/M	Records
Through-put limit	BAAQMD Condition #1240, part II.74	Y		283,011,000 gallons/any consecutive 12 months for S17, S31, and S54 combined	BAAQMD Condition #1240, part II.75	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour	BAAQMD Condition 1240, part I.19	C	Temperature monitoring
FP	BAAQMD 6-310	Y		0.15 gr/dscf	BAAQMD Condition 1240, part I.19	C	Temperature monitoring
Odor		N			BAAQMD Condition #1240, part IV.2	P/E	Asphalt tank truck dome inspection program

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – K
Applicable Limits and Compliance Monitoring Requirements
S18, CRUDE UNIT

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-10-301	Y		Abatement of emissions from process vessel depressurization is required until pressure is reduced to less than 1000 mm Hg	BAAQMD 8-10-401	P/E	Records of hydrocarbon concentration and emissions
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18b and I.18j	P/A	Calculations
	BAAQMD Condition #1240, part I.3	Y		98.5% destruction of vapors by weight	BAAQMD Condition 1240, part I.16	P/every 6 months	Source test
HAP	40 CFR 63 Subpart CC 63.643(a)(2)	Y		Reduce HAPs by 98% or to 20 ppm @ 3% oxygen	40 CFR 63 Subpart CC 63.644(a)(4)	N	N/A
Through-put limit	BAAQMD Condition #1240, part I.1	Y		5,292,000 barrels/any consecutive 12 months	BAAQMD Condition #1240, part I.4	P/M	Records
	BAAQMD Condition #1240, part I.2			18,000 barrels/any calendar day	BAAQMD Condition #1240, part I.4	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table– VII - L
Applicable Limits and Compliance Monitoring Requirements
S19, VACUUM HEATER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
NOX	BAAQMD 9-10-301	Y	7/1/02	Refinery-wide emissions (excluding CO Boilers): 0.033 lb NOx/ MMBTU	BAAQMD 9-10-502	P/every six months	Source test
	BAAQMD Condition 1240, part I.8	Y		30 ppmv (dry, 3% O ₂ , one hour average)	9-10-502 and BAAQMD Condition 1240, part I.16	P/every six months	Source test
NOX	BAAQMD Condition 1240, part I.14	Y		Emissions of NOX < 40 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18h and I.18j	P/A	Calculations
O ₂		Y	7/1/02	No limit	BAAQMD 9-10-502	P/every six months	Source test
CO	BAAQMD 9-10-305	Y		400 ppmv (dry, 3% O ₂)	BAAQMD 9-10-502 and BAAQMD Condition 1240, part I.16a	P/every six months	Source test
	BAAQMD Condition 1240, part I.5b	Y		140 ppmv (dry, 3% O ₂)	BAAQMD Condition 1240, part I.16	P/every 6 months	Source test
	BAAQMD Condition 1240, part I.5c	Y		3.4 lb/hr over any one-hour period	BAAQMD Condition 1240, part I.16	P/every 6 months	Source test

VII. Applicable Limits and Compliance Monitoring Requirements

Table– VII - L
Applicable Limits and Compliance Monitoring Requirements
S19, VACUUM HEATER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
SO2	40 CFR, Subpart J, 60.104(a) (1)	Y		Fuel gas H2S concentration limited to 230 mg/dscm (0.10 gr/dscf) except for gas burned as a result of process upset or gas burned at flares from relief valve leaks or other emergency malfunctions	40 CFR 60.105(a)(4)	C	H2S analyzer
	BAAQMD Condition 1240, part I.11	Y		Fuel gas H2S concentration limited to 163 ppmv, dry, prior to mixing averaged over any consecutive 3-hr period	BAAQMD Condition 1240, part I.13	C	H2S CEM
	BAAQMD Condition 1240, part I.12	Y		Fuel gas H2S concentration limited to 10 ppmv, dry, prior to mixing averaged over any consecutive 24-hr period	BAAQMD Condition 1240, part I.13	C	H2S CEM
	BAAQMD Condition 1240, part I.12	Y		fuel gas H2S concentration limited to 10 ppmv, dry, when any vessel is in port	BAAQMD Condition 1240, part I.13	C	H2S CEM
	BAAQMD Condition 1240, part I.14	Y		Emissions of SO2 < 28 tons per year excluding marine emissions		N	
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour		N	
FP	BAAQMD 6-310.3	Y		0.15 grain/dscf @ 6% oxygen		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table– VII - L
Applicable Limits and Compliance Monitoring Requirements
S19, VACUUM HEATER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition #1240, part I.3	Y		98.5% destruction of vapors by weight	BAAQMD Condition 1240, part I.16	P/every 6 months	Source test
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18f and I.18j	P/A	Calculations
HAP	40 CFR 63 Subpart CC 63.643(a) (2)	Y		Reduce HAPs by 98% or to 20 ppm @ 3% oxygen		None	
Through-put	BAAQMD Condition 1240, part I.5	Y		Maximum heat input to all refinery combustion units < 88.6 MMbtu/hr	BAAQMD Condition 1240, part I.5	C	Fuel meters
	BAAQMD Condition 1240, part I.5a	Y		Maximum heat input to S19 < 33 MMbtu/hr	9-10-502.2	C	Fuel meters

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – M
Applicable Limits and Compliance Monitoring Requirements
S20, STEAM BOILER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
NOX	BAAQMD 9-10-301	Y	7/1/02	Refinery-wide emissions (excluding CO Boilers): 0.033 lb NOx/ MMBTU	BAAQMD 9-10-502	P/A	Source test
NOX	BAAQMD Condition 1240, part I.14	Y		Emissions of NOX < 40 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18h and I.18j	P/A	Calculations
O2		Y	7/1/02	No limit	BAAQMD 9-10-502	P/A	Source test
CO	BAAQMD 9-10-305	Y		400 ppmv (dry, 3% O ₂)	BAAQMD 9-10-502	P/A	Source test
SO2	BAAQMD Condition 1240, part I.14	Y		Emissions of SO2 < 28 tons per year excluding marine emissions		N	
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour (gaseous fuel)		N	
FP	BAAQMD 6-310.3	Y		0.15 grain/dscf @ 6% oxygen		N	
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18f and I.18j	P/A	Calculations
Through-put	BAAQMD Condition 1240, part I.5	Y		Maximum heat input to all refinery combustion units < 88.6 MMbtu/hr	BAAQMD Condition 1240, part I.5	C	Fuel meters

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – N
Applicable Limits and Compliance Monitoring Requirements
S21, STEAM BOILER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
NOX	BAAQMD 9-10-301	Y	7/1/02	Refinery-wide emissions (excluding CO Boilers): 0.033 lb NOx/ MMBTU	BAAQMD 9-10-502	P/A	Source test
NOX	BAAQMD Condition 1240, part I.14	Y		Emissions of NOX < 40 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18h and I.18j	P/A	Calculations
O2		Y	7/1/02	No limit	BAAQMD 9-10-502	P/A	Source test
CO	BAAQMD 9-10-305	Y		400 ppmv (dry, 3% O ₂)	BAAQMD 9-10-502	P/A	Source test
SO2	BAAQMD Condition 1240, part I.14	Y		Emissions of SO2 < 28 tons per year excluding marine emissions		N	
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour		N	
FP	BAAQMD 6-310.3	Y		0.15 grain/dscf @ 6% oxygen		N	
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18f and I.18j	P/A	Calculations
Through-put	BAAQMD Condition 1240, part I.5	Y		Maximum heat input to all refinery combustion units < 88.6 MMBtu/hr	BAAQMD Condition 1240, part I.5	C	Fuel meters

VII. Applicable Limits and Compliance Monitoring Requirements

Table– VII - O
Applicable Limits and Compliance Monitoring Requirements
S24, HOT OIL HEATER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
NOX	BAAQMD Condition 1240, part I.14	Y		Emissions of NOX < 40 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18i and I.18j	P/A	Calculations
SO2	BAAQMD Condition 1240, part I.14	Y		Emissions of SO2 < 28 tons per year excluding marine emissions		N	
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour (gaseous fuel)	BAAQMD Condition #1240, II.58b	C	Temperature monitoring
	40 CFR 60.472(c)	Y		0 percent opacity except for one consecutive 15-min period in any 24-hr period for cleaning	40 CFR 60.473(c) and BAAQMD Condition #1240, II.58b	C	Temperature monitoring
FP	BAAQMD 6-310.3	Y		0.15 grain/dscf @ 6% oxygen	BAAQMD Condition #1240, II.58b	C	Temperature monitoring
VOC	BAAQMD 8-5-311.3	Y		95% control of organic vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	40 CFR 60.112b(a) (3)(ii)	Y		95% control of inlet VOC	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
VOC	40 CFR 61.349(a) (2)(i)(A)	Y		95% control	40 CFR 61.354(c)(4)	C	Temperature measurement

VII. Applicable Limits and Compliance Monitoring Requirements

Table– VII - O
Applicable Limits and Compliance Monitoring Requirements
S24, HOT OIL HEATER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18g and I.18j	P/A	Calculations
	BAAQMD Condition 1240, part II.32a, b, c	Y		98.5% control efficiency	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition 1240, part II.43	Y		98.5% control efficiency	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition 1240, part II.44	Y		Fugitive emissions at vapor recovery system (S24 or A31) shall not exceed 100 ppmv	BAAQMD Condition 1240, part II.44	P/Q or A	Method 21
	BAAQMD Condition #1240, II.55	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition #1240, II.56	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition #1240, II.57	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition 1240, part II.85	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring

VII. Applicable Limits and Compliance Monitoring Requirements

Table– VII - O
Applicable Limits and Compliance Monitoring Requirements
S24, HOT OIL HEATER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Through-put	BAAQMD Condition 1240, part I.5	Y		Maximum heat input to all refinery combustion units < 88.6 MMbtu/hr	BAAQMD Condition 1240, part I.5	C	fuel meters

Table VII – P
Applicable Limits and Compliance Monitoring Requirements
S25, S28, EFFLUENT WATER FEED TANKS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	40 CFR 61.349(a)(2)(i)(A)	Y		95% reduction	40 CFR 61.354(c)(1), 61.354(c)(4)	C	Temperature measurement
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18e and I.18j	P/A	Calculations

Table VII – Q
Applicable Limits and Compliance Monitoring Requirements
S26, SKIMMED OIL TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC					40 CFR 61.349(f)	P/Q	Visual inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – Q
Applicable Limits and Compliance Monitoring Requirements
S26, SKIMMED OIL TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	40 CFR 61.349(a)(1)(ii)(B)	Y		Car-sealed valves on bypass lines	40 CFR 61.354(f)(1)	P/M	Visual inspection
VOC	40 CFR 61.349(a)(2)(ii)	Y		95% control of VOC	40 CFR 61.354(d)	P/D	Measurement of VOC content of outlet
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18e and I.18j	P/A	Calculations

Table VII – R
Applicable Limits and Compliance Monitoring Requirements
S27, RECOVERED OIL TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-5-311.3	Y		95% control of organic vapors	40 CFR 61.354(d)	P/D	Measurement of VOC content of outlet
VOC	40 CFR 61.349(a)(1)(i)	Y		Operation with Fugitive emissions < 500 ppmv	40 CFR 61.349(f)	P/Q	Visual inspection
	40 CFR 61.349(a)(1)(ii)(B)	Y		Car-sealed valves on bypass lines	40 CFR 61.354(f)(1)	P/Q	Visual inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – R
Applicable Limits and Compliance Monitoring Requirements
S27, RECOVERED OIL TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	40 CFR 61.349(a)(2)(ii)	Y		95% control of VOC	40 CFR 61.354(d)	P/D	Measurement of VOC content of outlet
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18e and I.18j	P/A	Calculations

Table VII – S
Applicable Limits and Compliance Monitoring Requirements
S29, NAPHTHA MEROX TREATER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-10-301	Y		abatement of emissions from process vessel depressurization is required until pressure is reduced to less than 1000 mm Hg	BAAQMD 8-10-401	P/E	Records of hydrocarbon concentration and emissions
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18b and I.18j	P/A	Calculations

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – T
Applicable Limits and Compliance Monitoring Requirements
S30, MARINE LOADING DOCK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC				None	40 CFR 63.567(j)(4)	P/E	Records
SO2	BAAQMD Condition 1240, part III.2	Y		2.9% S in fuel oil burned by vessels	BAAQMD Condition 1240, part III.9	P/M	Records
Shipping limits	BAAQMD Condition 1240, part III.1	Y		12 ships per year	BAAQMD Condition 1240, part III.9	P/M	Records
	BAAQMD Condition 1240, part III.1	Y		Vessels less than 49 MDWEIGHT	BAAQMD Condition 1240, part III.9	P/M	Records
	BAAQMD Condition 1240, part III.6	Y		6 barge loadings in any month: 1 barge loading in any day; barge capacity < 100,000 barrels	BAAQMD Condition 1240, part III.9	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – U
Applicable Limits and Compliance Monitoring Requirements
S31, RAIL CAR ASPHALT LOADING RACK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-6-301	Y		0.17 pounds per 1,000 gallons loaded	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD 8-15-305			None	BAAQMD 8-15-501	P/E	Records
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18d and I.18j	P/A	Calculations
	BAAQMD Condition 1240, part II.32	Y		98.5% control efficiency	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition #1240, part II.69	Y		98.5% destruction of vapors by weight	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition #1240, part II.72	Y		Vapor pressure < 1.5 psia	BAAQMD Condition #1240, part II.75	P/M	records
	BAAQMD Condition #1240, part II.73	Y		Vapor pressure of asphalt or asphalt containing materials < 0.5 psia	BAAQMD Condition #1240, part II.75	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour	BAAQMD Condition #1240, II.58b	C	Temperature monitoring

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – U
Applicable Limits and Compliance Monitoring Requirements
S31, RAIL CAR ASPHALT LOADING RACK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD 6-310	Y		0.15 gr/dscf	BAAQMD Condition #1240, II.58b	C	Temperature monitoring
Through-put limit	BAAQMD Condition #1240, part II.74	Y		283,011,000 gallons/any consecutive 12 months for S17, S31, and S54 combined	BAAQMD Condition #1240, part II.75	P/M	Records

Table VII – V
Applicable Limits and Compliance Monitoring Requirements
S32, LGO STRIPPER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-10-301	Y		abatement of emissions from process vessel depressurization is required until pressure is reduced to less than 1000 mm Hg	BAAQMD 8-10-401	P/E	Records of hydrocarbon concentration and emissions
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	<u>BAAQMD Condition 1240, part I.18b and I.18j</u>	P/A	Calculations
	BAAQMD Condition #1240, part I.3	Y		98.5% destruction of vapors by weight	BAAQMD Condition 1240, part I.16	P/every 6 months	Source test

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – W
Applicable Limits and Compliance Monitoring Requirements
S34, TANK HEATER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
NOX	BAAQMD Condition 1240, part I.14	Y		Emissions of NOX < 40 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18I and I.18j	P/A	Calculations
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18g and I.18j	P/A	Calculations
SO2	BAAQMD Condition 1240, part I.14	Y		Emissions of SO2 < 28 tons per year excluding marine emissions		N	
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour (gaseous fuel)		N	
FP	BAAQMD 6-310.3	Y		0.15 grain/dscf @ 6% oxygen		N	
Through-put	BAAQMD Condition 1240, part I.5	Y		Maximum heat input to all refinery combustion units < 88.6 MMbtu/hr	BAAQMD Condition 1240, part I.5	C	fuel meters

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - X
Applicable Limits and Compliance Monitoring Requirements
S39, LUBE OIL TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions		N	

Table VII - Y
Applicable Limits and Compliance Monitoring Requirements
S40, LATEX STORAGE TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions		N	

Table VII - Z
Applicable Limits and Compliance Monitoring Requirements
S41, WEMCO HYDROTREATER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-8-307.2	Y		> 70% combined collection and destruction efficiency by weight	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – Z
Applicable Limits and Compliance Monitoring Requirements
S41, WEMCO HYDROTREATER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	40 CFR 61.349(a)(2)(i)(A)	Y		95% control (by A31 incinerator)	40 CFR 61.354(c)(1)	C	Temperature measurement
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18e and I.18j	P/A	Calculations
Through-put	BAAQMD Condition 1240, part II.92	Y		77,263,000 gallons per year	BAAQMD Condition 1240, part II.92a	P/M	Records

Table VII – AA
Applicable Limits and Compliance Monitoring Requirements
S51, S52, S53, S60, SALES TANKS-ASPHALT

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour	BAAQMD Condition #1240, II.58b	C	Temperature monitoring
	40 CFR 60.472(c)	Y		0 percent opacity except for one consecutive 15-min period in any 24-hr period for clearing	40 CFR 60.473(c) and BAAQMD Condition #1240, II.58b	C	Temperature monitoring
FP	BAAQMD 6-310	Y		0.15 gr/dscf	BAAQMD Condition #1240, II.58b	C	Temperature monitoring

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AA
Applicable Limits and Compliance Monitoring Requirements
S51, S52, S53, S60, SALES TANKS-ASPHALT

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-15-305			None	BAAQMD 8-15-501	P/E	Records
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18c and I.18j	P/A	calculations
	BAAQMD Condition #1240, II.50	Y		Vapor pressure may not exceed 0.50 psia	BAAQMD Condition #1240, II.58	P/M	Records
	BAAQMD Condition #1240, II.56	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
Through-put limit	BAAQMD Condition #1240, II.48	Y		6,738,349 barrels/yr total for S5, S6, S7, S8, S37, S38, S51, S52, S53, S60, S61, S62, and S65	BAAQMD Condition #1240, II.58	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AB
Applicable Limits and Compliance Monitoring Requirements
S54, ASPHALT LOADING RACK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-15-305			None	BAAQMD 8-15-501	P/E	Records
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18d and I.18j	P/A	calculations
	BAAQMD Condition #1240, part II.70	Y		98.5% destruction of vapors by weight	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition #1240, part II.71	Y		Vapor pressure < 0.5 psia	BAAQMD Condition #1240, part II.75	P/M	records
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour	BAAQMD Condition #1240, II.58b	C	Temperature monitoring
FP	BAAQMD 6-310	Y		0.15 gr/dscf	BAAQMD Condition #1240, II.58b	C	Temperature monitoring
Through-put limit	BAAQMD Condition #1240, part II.74	Y		283,011,000 gallons/any consecutive 12 months for S17, S31, and S54 combined	BAAQMD Condition #1240, part II.75	P/M	Records
Odor					BAAQMD Condition #1240, part IV.2	P/E	Asphalt tank truck dome inspection program

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AC
Applicable Limits and Compliance Monitoring Requirements
S59, GAS OIL TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-5-311.3	Y		95% control of organic vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
				None	BAAQMD 8-5-501	P/E	Records of liquids stored and TVPs
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18c and I.18j	P/A	Calculations
	BAAQMD Condition 1240, part II.31	Y		Vapor pressure shall not exceed 1.5 psia	BAAQMD Condition 1240, part II.31a	P/A	determination of vapor pressure
	BAAQMD Condition 1240, part II.32b	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
Through-put	BAAQMD Condition 1240, part II.33a			< 68,208,000 gallons in any consecutive 12-month period for S13, S59, and S63 total	BAAQMD Condition 1240, part II.34	P/M	records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AD
Applicable Limits and Compliance Monitoring Requirements
S61, S62, ASPHALT TANKS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour	BAAQMD Condition #1240, II.58b	C	Temperature monitoring
	40 CFR 60.472(c)	Y		0 percent opacity except for one consecutive 15-min period in any 24-hr period for clearing	40 CFR 60.473(c) and BAAQMD Condition #1240, II.58b	C	Temperature monitoring
FP	BAAQMD 6-310	Y		0.15 gr/dscf	BAAQMD Condition #1240, II.58b	C	Temperature monitoring
VOC	BAAQMD 8-15-305			None	BAAQMD 8-15-501	P/E	Records
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18c and I.18j	P/A	calculations
	BAAQMD Condition #1240, II.51	Y		Vapor pressure may not exceed 0.49 psia	BAAQMD Condition #1240, II.58	P/M	Records
	BAAQMD Condition #1240, II.57	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
Through-put limit	BAAQMD Condition #1240, II.48	Y		6,738,349 barrels/yr total for S5, S6, S7, S8, S37, S38, S51, S52, S53, S60, S61, S62, and S65	BAAQMD Condition #1240, II.58	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AE
Applicable Limits and Compliance Monitoring Requirements
S63, TANK 31

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-5-311.3	Y		95% control of organic vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
				None	BAAQMD 8-5-501	P/E	Records of liquids stored and TVPs
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18c and I.18j	P/A	calculations
	BAAQMD Condition 1240, part II.31	Y		Vapor pressure shall not exceed 1.5 psia	BAAQMD Condition 1240, part II.31a	P/A	determination of vapor pressure
	BAAQMD Condition 1240, part II.32c	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
Through-put	BAAQMD Condition 1240, part II.33a			< 68,208,000 gallons in any consecutive 12-month period for S13, S59, and S63 total	BAAQMD Condition 1240, part II.34	P/M	records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AF
Applicable Limits and Compliance Monitoring Requirements
S65, ASPHALT TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour	BAAQMD Condition #1240, II.58b	C	Temperature monitoring
	40 CFR 60.472(c)	Y		0 percent opacity except for one consecutive 15-min period in any 24-hr period for clearing	40 CFR 60.473(c) and BAAQMD Condition #1240, II.58b	C	Temperature monitoring
FP	BAAQMD 6-310	Y		0.15 gr/dscf	BAAQMD Condition #1240, II.58b	C	Temperature monitoring
VOC	BAAQMD 8-15-305			None	BAAQMD 8-15-501	P/E	Records
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18c and I.18j	P/A	calculations
	BAAQMD Condition #1240, II.52	Y		Vapor pressure may not exceed 0.49 psia	BAAQMD Condition #1240, II.58	P/M	Records
	BAAQMD Condition #1240, II.53	Y		Fugitive emissions shall not exceed 100 ppm	BAAQMD Condition 1240, part II.53	P/Q or A	Method 21
	BAAQMD Condition #1240, II.56	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
Through-put limit	BAAQMD Condition #1240, II.48	Y		6,738,349 barrels/yr total for S5, S6, S7, S8, S37, S38, S51, S52, S53, S60, S61, S62, and S65	BAAQMD Condition #1240, II.58	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AG
Applicable Limits and Compliance Monitoring Requirements
S66, OIL WATER SEPARATOR

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-8-301.3			95% combined collection and destruction efficiency	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	40 CFR 61.349(a)	Y		95% control (by A31 incinerator)	40 CFR 61.354(c)(1)	C	Temperature monitoring
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18e and I.18j	P/A	calculations
	BAAQMD Condition 1240, part II.85	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition 1240, part II.86	Y		No detectable fugitive emissions in excess of 100 ppm, measured as total organic compounds			
Through-put limit	BAAQMD Condition #1240, II.83	Y		11,376,000 gallons/yr	BAAQMD Condition #1240, II.87 and II.88	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AH
Applicable Limits and Compliance Monitoring Requirements
S67-RECOVERED OIL TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-5-311.3	Y		95% control of organic vapors	40 CFR 61.354(c)(1)	C	Temperature measurement
VOC	40 CFR 61.349(a)(1)(i)	Y		Operation with Fugitive emissions < 500 ppmv	40 CFR 61.349(f)	P/Q	Visual inspection
	40 CFR 61.349(a)(1)(ii)(B)	Y		Car-sealed valves on bypass lines	40 CFR 61.354(f)(1)	P/Q	Visual inspection
VOC	40 CFR 61.349(a)(2)(i)(A)	Y		95% control (by A31 incinerator)	40 CFR 61.354(c)(1)	C	Temperature measurement
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18e and I.18j	P/A	Calculations

Table VII - AI
Applicable Limits and Compliance Monitoring Requirements
S68-EMERGENCY DIESEL-POWERED FIREWATER PUMP

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AI
Applicable Limits and Compliance Monitoring Requirements
S68-EMERGENCY DIESEL-POWERED FIREWATER PUMP

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD 6-310	Y		0.15 gr/dscf		N	
Hours of operation	BAAQMD Condition 18796, Part 2			up to 100 hours for reliability testing	BAAQMD Condition 18796, Part 6	P/M	records
	BAAQMD Condition 18796, Part 2			unlimited hours in case of emergency	BAAQMD Condition 18796, Part 6	P/M	records
NOX	BAAQMD Condition 1240, part I.14	Y		Emissions of NOX < 40 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18i and I.18j	P/A	Calculations
SO2	BAAQMD 9-1-304			Fuel Sulfur Limit 0.5% by weight	BAAQMD Condition 18796, Part 1	P/E	fuel certification
	BAAQMD Condition 1240, part I.14	Y		Emissions of SO2 < 28 tons per year excluding marine emissions		N	
	BAAQMD Condition 18796, Part 1			Fuel Sulfur Limit 0.5% by weight	BAAQMD Condition 18796, Part 1	P/E	fuel certification
NHMC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18g and I.18j	P/A	Calculations

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AJ
Applicable Limits and Compliance Monitoring Requirements
COMPONENTS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-18-301	Y		General equipment leak < 100 ppm or minimize in 24 hours, repair in 7 days			
VOC	BAAQMD 8-18-302	Y		Valve leak < 100 ppm or minimize in 24 hours, repair in 7 days	BAAQMD 8-18-401.2 or 8-18-404	P/Q (footnote A)	Method 21 Inspection
VOC	BAAQMD 8-18-302	Y		Inaccessible valve leak < 100 ppm or minimize in 24 hours, repair in 7 days	BAAQMD 8-18-401.3	P/A	Method 21 Inspection
VOC	BAAQMD 8-18-303	Y		Pump and compressor leak < 500 ppm or minimize in 24 hours, repair in 7 days	BAAQMD 8-18-401.2	P/Q	Method 21 Inspection
VOC	BAAQMD 8-18-304.2	Y		Connection leak < 100 ppm or minimize in 24 hours, repair in 7 days	BAAQMD 8-18-401.6	P/every 5 years (see footnote B)	Method 21 Inspection
VOC	BAAQMD 8-18-304.2	Y		Connection leak < 100 ppm or minimize in 24 hours, repair in 7 days (for connectors opened during turnaround)	BAAQMD 8-18-401.1	P/E (within 90 days of turnaround)	Method 21 Inspection
VOC	BAAQMD 8-18-305	Y		Pressure relief valve leak < 500 ppm or minimize in 24 hours, repair in 15 days	BAAQMD 8-18-401.2 and 8-18-401.7	P/Q	Method 21 Inspection
VOC	BAAQMD 8-18-305	Y		Inaccessible pressure relief valve leak < 500 ppm or minimize in 24 hours, repair in 15 days	BAAQMD 8-18-401.3	P/A	Method 21 Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AJ
Applicable Limits and Compliance Monitoring Requirements
COMPONENTS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-18-305	Y		Pressure relief valve leak ≤ 500 ppm or minimize in 24 hours, repair in 15 days	BAAQMD 8-18-401.8	P/E (5 working days after release)	Method 21 Inspection
VOC	BAAQMD 8-18-305	N		Pressure Relief Device with reportable releases ≤ 500 ppm	BAAQMD 8-28-402 & 8-18-401.8	P/E (5 working days after release)	Method 21 Inspection w/Report
VOC	BAAQMD 8-18-306.1	Y		Valve, pressure relief, pump or compressor must be repaired within 5 years or at the next scheduled turnaround	BAAQMD 8-18-502.4	P/Q	Records
VOC	BAAQMD 8-18-306.2	Y		Awaiting repair Valves < 0.5% Pressure Relief < 1% Pump and Connector < 1%	BAAQMD 8-18-502.4	P/Q	Records
VOC	BAAQMD 8-18-307	Y		Pumps and Compressors Evidence of Leak	BAAQMD 8-18-403	P/D	Visual Inspection
VOC	SIP 8-28-301	Y		10,000 ppm (pressure relief devices)	8-28-402	P/Q	Method 21 Inspection
VOC	BAAQMD 8-28-303.2	N		Pressure Relief Devices to meet Prevention Measures Procedures	8-28-405	P/turn-around	
VOC	BAAQMD 8-28-304	N		PHA within 90 days and meet Prevention Measures Procedures. After 2 nd release Vent Pressure Relief Devices to an Abatement Device with at least 95% by weight control efficiency. (pressure relief devices)	BAAQMD 8-28-405	P/release per 5 calendar year	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AJ
Applicable Limits and Compliance Monitoring Requirements
COMPONENTS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-28-304.1	N		Pressure Relief Device with reportable releases in 5-year period.	BAAQMD 8-28-304.1 & 8-28-405	P/E (90 day after release) P/E (120 day after release)	PHA & PMP Report Install tamper-proof indicators
VOC	BAAQMD 8-28-304.2	N		After 2 nd release in 5 years; Vent Pressure Relief Devices to an Abatement Device with 95% destruction efficiency			
40 CFR 60; Subpart VV							
VOC	60.482-2 (b)(1)	Y		LL Pump leak < 10,000 ppm	60.482-2 (a)(1)	P/M	Method 21 Inspection
VOC	60.482-2 (b)(2)	Y		Pump leak Indicated by dripping liquid	60.482-2 (a)(2)	P/W	Visual Inspection
VOC	60.482-2(e)	Y		Pump designated for “No detectable emissions” pursuant to 60.486(e), < 500 ppm	60.482-2(e)(3)	P/A	Method 21 Inspection
	60.482-3(d)	Y		Compressor shall have a sensor to detect failure of seal system, barrier fluid system, or both	60.482-3 (e)(1)	C or P/D	Sensor with audible alarm or checked daily
	60.482-3(i)	Y		Compressor designated for “No detectable emissions” pursuant to 60.486(e), < 500 ppm	60.482-3(i)(2)	P/A	Method 21 Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AJ
Applicable Limits and Compliance Monitoring Requirements
COMPONENTS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	60.482-4(a)	Y		Pressure relief valve (gas/vapor) not vented to abatement □ 500 ppm		N	
	60.482-4(b)(1)	Y		Pressure relief valve (gas/vapor) not vented to abatement < 500 ppm after a pressure release event	60.482-4(b)(2)	P/E (5 days)	Method 21 Inspection
	60.482-7(b)	Y		Valve leak < 10,000 ppm	60.482-7(a)	P/M	Method 21 Inspection
VOC	60.482-7(b)	Y		Valve leak < 10,000 ppm; 2 successive months	60.482-7(c)(i)	P/Q	Method 21 Inspection
	60.482-7(f)	Y		Valve designated “No detectable emissions” leak < 500 ppm	60.482-7(f)(3)	P/A	Method 21 Inspection
VOC	60.482-8(a)	Y		Pumps and valves in heavy liquid service, Pressure Relief devices (light or heavy liquid), Flanges, Connectors leak shall be measured for leak in 5 days if detected by inspection	60.482-8(a)	P/E	Visible, Audible, or olfactory Inspection
VOC	60.482-8(b)	Y		Pumps and Valves (heavy liquid), Pressure Relief Devices (liquid), Flanges, Connectors leak < 10,000 ppm	60.482-8(a)	P/(5 days after leak noted by visual, audible, or olfactory inspection)	Visual, audible, olfactory Inspection; Measure for leaks
VOC	60.482-9(d)	Y		Pumps under “Delay of repair” repaired within 6 months		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AJ
Applicable Limits and Compliance Monitoring Requirements
COMPONENTS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	60.482-10 (g)	Y		Closed-vent systems leak \leq 500 ppm or visible leak indication, or 1 st repair attempt 5 day, repaired 15 days, or turnaround list	60.482-10 (f)	P/A	Method 21 inspection; Visual Inspection
VOC		Y		Individual valve that measures <10,000 ppm for 5 consecutive quarters may be monitored annually, if in a process unit with 5 consecutive quarters <2% valves leaking > 10,000 ppm.	60.483-2(b)(3) (See footnote c)	P/A (if criteria are met)	Method 21 inspection
VOC				Individual valve that measures <10,000 ppm for 2 consecutive quarters may be monitored semiannually, if in a process unit with 2 consecutive quarters <2% valves leaking \geq 10,000 ppm. ^c	60.483-2(b)(2) (footnote c)	SA (if criteria are met)	Method 21 Inspection
NMHC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18b and I.18j	P/M	Calculations
40 CFR 61; Subpart FF (Benzene Waste NESHP)							
VOC	61.343 (a)(1)(i)(A)	Y		Tanks fittings leak \leq 500 ppm	61.343 (a)(1)(i)(A)	P/A	Method 21 Inspection
VOC	63.345 (a)(1)(i)	Y		Container fittings leak \leq to 500 ppm	63.345 (a)(1)(i)	P/A	Method 21 Inspection
VOC	61.347 (a)(1)(i)(A)	Y		O/W Separator fittings leak \leq 500 ppm	61.347 (a)(1)(i)(A)	P/A	Method 21 Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AJ
Applicable Limits and Compliance Monitoring Requirements
COMPONENTS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	61.349 (a)(1)(i)	Y		Closed-vent systems <500 ppm above background	61.349 (a)(1)(I)	P/A	Method 21 Inspection

Footnotes to Table VII-I

^a Valves are inspected pursuant to BAAQMD-approved Alternative Inspection Schedule that satisfies the requirements of 8-18-404. Valves that have not been found to be leaking for the five prior quarters are placed on the annual inspection schedule.

^b Connectors are inspected pursuant to a BAAQMD-approved Connector Inspection Program that satisfies the requirements of 8-18-401.6. Under this program, 20% of all of the refinery’s connectors are inspected each year.

^c The 40 CFR 60.483-2 (Subpart VV) alternative screening schedule for valves is analogous to the Valero Alternative Inspection Schedule (see footnote “a”) with two exceptions: 60.483-2 uses a leak definition of 10,000 ppm VOC rather than 100 ppm TOC, and 60.483-2 requires that the percentage of valves leaking facility-wide (at 10,000 ppm) must have been less than 2% for the five-quarter time period. For process units covered by refinery MACT, 63.648(a)(2) allows the percentage leaking to be determined on a refinery-wide basis. This applies to all process units except NSPS process units except Dimersol, which is not subject to MACT. Finally, any valve subject to Subpart VV must *individually* comply with BAAQMD Rule 8-18-404 (5 quarters with no leaks at 100 ppm) in order to be allowed to be screened less frequently than quarterly. As a practical matter, Subpart VV is effectively less stringent than the Valero Alternative Inspection Schedule.

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AK
Applicable Limits and Compliance Monitoring Requirements
A4, LOADING RACK THERMAL OXIDIZER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
NOX	BAAQMD Condition 1240, part I.14	Y		Emissions of NOX < 40 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18i and I.18j	P/A	Calculations
SO2	BAAQMD Condition 1240, part I.14	Y		Emissions of SO2 < 28 tons per year excluding marine emissions		N	
VOC	BAAQMD 8-6-301	Y		21 g/cubic meter (0.17 lb/1000 gallons)	BAAQMD Condition 1240, part I.19	C	Temperature monitoring
VOC	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18g and I.18j	P/A	Calculations
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.19	C	Temperature monitoring
	BAAQMD Condition #1240, part II.60	Y		98.5% destruction of vapors by weight by A4	BAAQMD Condition 1240, part I.19	C	Temperature monitoring
	BAAQMD Condition #1240, part II.63	Y		98.5% destruction of vapors by weight by A4	BAAQMD Condition 1240, part I.19	C	Temperature monitoring

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AK
Applicable Limits and Compliance Monitoring Requirements
A4, LOADING RACK THERMAL OXIDIZER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition #1240, part II.68	Y		98.5% destruction of vapors by weight	BAAQMD Condition 1240, part I.19	C	Temperature monitoring
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour		N	
FP	BAAQMD 6-310	Y		0.15 grain/dscf	BAAQMD Condition 1240, part I.19	C	Temperature monitoring
Through-put	BAAQMD Condition 1240, part I.5	Y		Maximum heat input to all refinery combustion units < 88.6 MMBtu/hr	BAAQMD Condition 1240, part I.5	C	fuel meters

Table VII – AL
Applicable Limits and Compliance Monitoring Requirements
A31, THERMAL OXIDIZER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
NOX	BAAQMD Condition 1240, part I.14	Y		Emissions of NOX < 40 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18i and I.18j	P/A	Calculations

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AL
Applicable Limits and Compliance Monitoring Requirements
A31, THERMAL OXIDIZER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
SO2	BAAQMD Condition 1240, part I.14	Y		Emissions of SO2 < 28 tons per year excluding marine emissions		N	
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for no more than 3 minutes in any hour	BAAQMD Condition #1240, II.58b	C	Temperature monitoring
Opacity	40 CFR 60.472(c)	Y		0 percent opacity except for one consecutive 15-min period in any 24-hr period for cleaning	40 CFR 60.473(c) and BAAQMD Condition #1240, II.58b	C	Temperature monitoring
FP	BAAQMD 6-310	Y		0.15 gr/dscf	BAAQMD Condition #1240, II.58b	C	Temperature monitoring
VOC	BAAQMD 8-5-311.3	Y		95% control of organic vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
VOC	BAAQMD 8-6-301	Y		21 g/cubic meter (0.17 lb/1000 gallons)	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	40 CFR 60.112b(a) (3)(ii)	Y		95% control of inlet VOC	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	40 CFR 61.349(a) (2)(i)(A)	Y		95% control (by A31 incinerator)	40 CFR 61.354(c)(1)	C	Temperature monitoring

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AL
Applicable Limits and Compliance Monitoring Requirements
A31, THERMAL OXIDIZER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part I.18g and I.18j	P/A	Calculations
	BAAQMD Condition 1240, part I.14	Y		Emissions of NMHC < 49.1 tons per year excluding marine emissions	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition 1240, part II.32a, b, c	Y		98.5% control efficiency	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition 1240, part II.43	Y		98.5% control efficiency	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition #1240, II.55	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition #1240, II.56	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition #1240, II.57	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition #1240, part II.69	Y		98.5% destruction of vapors by weight	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AL
Applicable Limits and Compliance Monitoring Requirements
A31, THERMAL OXIDIZER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition #1240, part II.70	Y		98.5% destruction of vapors by weight	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
	BAAQMD Condition 1240, part II.85	Y		98.5% destruction of vapors	BAAQMD Condition 1240, part II.58b	C	Temperature monitoring
Through-put	BAAQMD Condition 1240, part I.5	Y		Maximum heat input to all refinery combustion units < 88.6 MMbtu/hr	BAAQMD Condition 1240, part I.5	P/D	fuel meters

VIII. TEST METHODS

The test methods associated with the emission limit of a District regulation are generally referenced in Section 600 et seq. of the regulation. The following table indicates only the test methods associated with the emission limits referenced in Section VII, Applicable Emission Limits & Compliance Monitoring Requirements, of this permit.

Table VIII
Test Methods

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD 6-301	Ringelmann No. 1 Limitation	Manual of Procedures, Volume I, Evaluation of Visible Emissions
BAAQMD 6-310	Particulate Weight Limitation	Manual of Procedures, Volume IV, ST-15, Particulates Sampling or EPA Reference Method 5 (40 CFR 60, Appendix A), Determination of Particulate Emissions from Stationary Sources
BAAQMD Regulation 8-5-304	True Vapor Pressure	Manual of Procedures, Volume III, Lab Method 28, Determination of Vapor Pressure of Organic Liquids from Storage Tanks, if organic compound is not listed in Table I
BAAQMD Regulation 8-5-311.3	VOC emissions	Manual of Procedures, Volume IV, ST-34, Bulk Gasoline Distribution Facilities Edwards Refrigeration Unit or Carbon Adsorption Unit
BAAQMD Regulation 8-5-320.3	Pressure vacuum leak concentration	EPA Reference Method 21 (40 CFR 60, Appendix A), Determination of Volatile Organic Compound Leaks
BAAQMD Regulation 8-5-328.2	VOC emissions for tank cleaning	Manual of Procedures, Volume IV, ST-7, Non-Methane Organic Carbon Sampling
BAAQMD Regulation 8-5-603.2	VOC emissions for tank cleaning	Manual of Procedures, Volume IV, ST-7, Non-Methane Organic Carbon Sampling
BAAQMD 8-6-301	Bulk Terminal Limitations	Manual of Procedures, Volume IV, ST-3, Bulk Gasoline Transfer Plants or ST-34, Bulk and Marine Loading Terminals, Vapor Recovery Units Refrigeration Unit or Carbon Adsorption Unit
BAAQMD 8-15-305	Prohibition of Manufacture and Sale	ASTM Distillation Method D402, or ASTM Distillation Method D244

VIII. Test Methods

Table VIII
Test Methods

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD Regulation 8-18-301, 8-18-302, 8-18-303, 8-18-304, 8-18-305	Leak inspection procedures	EPA reference method 21 (40 CFR 60, Appendix A), Determination of Volatile Organic Compound Leaks
BAAQMD Regulation 8-18-306	Determination of mass emissions	EPA Protocol for equipment leak emission estimates, Chapter 4, Mass Emission Sampling, (EPAA-453/R-95-017) November 1995
BAAQMD 9-10-301	Emission Limit for Facility, NOx: 0.033 lb NOx/MMBTU	Manual of Procedures, Volume IV, ST-13A, Oxides of Nitrogen, Continuous Sampling and ST-14, Oxygen, Continuous Sampling
BAAQMD 9-10-305	CO emission limit	Manual of Procedures, Volume IV, ST-6, Carbon Monoxide, Continuous Sampling and ST-14, Oxygen, Continuous Sampling
40 CFR 60.104(a)(1)	Fuel gas H2S concentration limit	EPA Method 11, Determination of Hydrogen Sulfide Content of Fuel Gas Streams in Petroleum Refineries
40 CFR 60.112b	Vapor Pressure	ASTM Method D2879-83
NSPS Part 60 Subpart VV	Standards of Performance for Equipment Leaks (Fugitive Emission Sources) (10/18/83)	
Subpart VV 40 CFR 60.482-2(b)(1), 60.482-7(b), 60.482-8(b), 60.482-10 (g)	Leak inspection procedures	60 Subpart VV, 60.485(b): EPA reference method 21 (40 CFR 60, Appendix A), Determination of Volatile Organic Compound Leaks
Subpart VV 40 CFR 60.482-2(b)(2), 60.482-8(a)	Visual inspection	60 Subpart VV, 60.485(b)

VIII. Test Methods

Table VIII
Test Methods

Applicable Requirement	Description of Requirement	Acceptable Test Methods
Subpart VV 40 CFR 60.482-2(e), 60.482-4(a), 60.482-4(b), 60.482-7(f)	Leak inspection procedures	60 Subpart VV, 60.485(c): EPA reference method 21 (40 CFR 60, Appendix A), Determination of Volatile Organic Compound Leaks
Subpart VV 40 CFR 60.483 and BAAQMD 8-18-404.1	Leak inspection procedures	60 Subpart VV, 60.485(b): EPA reference method 21 (40 CFR 60, Appendix A), Determination of Volatile Organic Compound Leaks
BAAQMD Condition 1240, part II.31a	1.5 psia requirement	Manual of Procedures, Volume III, Lab Method 28, Determination of Vapor Pressure of Organic Liquids from Storage Tanks

IX. PERMIT SHIELD

A. Non-applicable Requirements

Pursuant to District Regulations 2-6-233 and 2-6-409.12, the federally enforceable regulations and/or standards cited in the following table[s] are not applicable to the source or group of sources identified at the top of the table[s]. Enforcement actions and litigation may not be initiated against the source or group of sources covered by this shield based on the regulatory and/or statutory provisions cited, as long as the reasons listed below remain valid for the source or group of sources covered by this shield.

Table IX A – 1
Permit Shield for Non-applicable Requirements
S30, MARINE LOADING DOCK

Citation	Title or Description (Reason not applicable)
BAAQMD Regulation 8, Rule 44	Marine Vessel Loading Terminals (Facility does not load organic liquids as defined by 8-44-204.)

IX. Permit Shield

B. Subsumed Requirements

Pursuant to District Regulations 2-6-233 and 2-6-409.12, as of the date this permit is issued, the federally enforceable “subsumed” monitoring requirements cited in the following table do not apply to the source or group of sources identified at the top of the table. The District has determined that compliance with the requirements listed below and elsewhere in this permit will assure compliance with the substantive requirements of the “subsumed” monitoring requirements. Enforcement actions and litigation may not be initiated against the source or group of sources covered by this shield based on the “subsumed” monitoring requirements cited.

Table IX B - 1
Permit Shield for Subsumed Requirements
S1, S2, S4, AND S23, CRUDE STORAGE TANKS

Subsumed Requirement Citation	Title or Description	Streamlined Requirements	Title or Description
NSPS Subpart Kb, 40 CFR 60.113b(b)(1) (i) and (ii)	Measurement of gaps between tank wall and primary and secondary seals at least once per 5 years and at least once per year, respectively.	BAAQMD Condition # 1240 II.13	Quarterly inspection of primary and secondary tank seals.
BAAQMD 8-5-401.1, 8-5-402.1, 8-5-404.1, and 8-5-404.2.1	Inspection of primary and “zero-gap” secondary seals at least once every 10 years (8-5-401.1 and 8-5-404.1), and at least once per year (8-5-404.2.1).	BAAQMD Condition # 1240 II.13	Quarterly inspection of primary and secondary tank seals.

IX. Permit Shield

Table IX B – 2
Permit Shield for Subsumed Requirements
COMPONENTS

Subsumed Requirement Citation	Title or Description	Streamlined Requirements	Title or Description
NSPS Subpart VV, 40 CFR 60.482-2(c)	Pump Leak above 10,000 ppm or dripping liquid: First repair attempt before 5 days and repair before 15 days.	BAAQMD 8-18-303	Minimization of pump leak > 500 ppm within 24 hours and repair within 7 days.
NSPS Subpart VV, 40 CFR 60.482-7(d)	Valve Leak above 10,000 ppm: First repair attempt before 5 days and repair before 15 days.	BAAQMD 8-18-302	Minimization of valve leak > 100 ppm within 24 hours and repair within 7 days.
NSPS Subpart VV, 40 CFR 60.482-7(g)	Allows relief from 60.482.7(a) monitoring if designated as unsafe-to-monitor.	BAAQMD 8-18-404	BAAQMD Regulation 8-18-404 does not allow this relief.
NSPS Subpart VV, 40 CFR 60.482-7(h)	Allows relief from 60.482.7(a) monitoring if designated as difficult-to-monitor.	BAAQMD 8-18-206	Definition of inaccessible is more stringent. Both 60.482.7(h) and 8-18-401.3 require yearly monitoring for difficult-to-monitor valves.
NSPS Subpart VV, 40 CFR 60.482-9(e)	Allows delay of repair beyond a process unit shutdown under supply circumstances.	BAAQMD 8-18-306	BAAQMD Regulation 8-18-306 does not allow this relief.
NSPS Subpart VV, 40 CFR 60.484	Alternative compliance plan only requires EPA approval.	BAAQMD 8-18-308	Requires public noticing and EPA approval of alternative compliance plan.

X. Glossary

X. GLOSSARY

ACT

Federal Clean Air Act

BAAQMD

Bay Area Air Quality Management District

BACT

Best Available Control Technology

CAA

The federal Clean Air Act

CAAQS

California Ambient Air Quality Standards

CEM

Continuous Emission Monitor

CEQA

California Environmental Quality Act

CFR

The Code of Federal Regulations. 40 CFR contains the implementing regulations for federal environmental statutes such as the Clean Air Act. Parts 50-99 of 40 CFR contain the requirements for air pollution programs.

CO

Carbon Monoxide

Cumulative Increase

The sum of permitted emissions from each new or modified source since a specified date pursuant to BAAQMD Rule 2-1-403, Permit Conditions (as amended by the District Board on 7/17/91) and SIP Rule 2-1-403, Permit Conditions (as approved by EPA on 6/23/95). Used to determine whether threshold-based requirements are triggered.

dscm

dry standard cubic meter

District

The Bay Area Air Quality Management District

EPA

X. Glossary

The federal Environmental Protection Agency.

Excluded

Not subject to any District regulations.

Federally Enforceable, FE

All limitations and conditions which are enforceable by the Administrator of the EPA including those requirements developed pursuant to 40 CFR Part 51, subpart I (NSR), Part 52.21 (PSD), Part 60, (NSPS), Part 61, (NESHAPs), Part 63 (HAP), and Part 72 (Permits Regulation, Acid Rain), including limitations and conditions contained in operating permits issued under an EPA-approved program that has been incorporated into the SIP.

FP

Filterable Particulate as measured by BAAQMD Method ST-15, Particulate.

GLM

Ground Level Monitor

HAP

Hazardous Air Pollutant. Any pollutant listed pursuant to Section 112(b) of the Act. Also refers to the program mandated by Title I, Section 112, of the Act and implemented by both 40 CFR Part 63, and District Regulation 2, Rule 5.

H₂S

Hydrogen Sulfide

Major Facility

A facility with potential emissions of: (1) at least 100 tons per year of regulated air pollutants, (2) at least 10 tons per year of any single hazardous air pollutant, and/or (3) at least 25 tons per year of any combination of hazardous air pollutants, or such lesser quantity of hazardous air pollutants as determined by the EPA administrator.

MDWEIGHT

Thousand Dead Weight Tons

MFR

Major Facility Review. The District's term for the federal operating permit program mandated by Title V of the Federal Clean Air Act and implemented by District Regulation 2, Rule 6.

MOP

The District's Manual of Procedures.

NAAQS

National Ambient Air Quality Standards

X. Glossary

NESHAPS

National Emission Standards for Hazardous Air Pollutants. See in 40 CFR Parts 61 and 63

NH3

Ammonia

NMHC

Non-methane Hydrocarbons

NOx

Oxides of nitrogen.

NSPS

Standards of Performance for New Stationary Sources. Federal standards for emissions from new stationary sources. Mandated by Title I, Section 111 of the Federal Clean Air Act, and implemented by 40 CFR Part 60 and District Regulation 10.

NSR

New Source Review. A federal program for pre-construction review and permitting of new and modified sources of pollutants for which criteria have been established in accordance with Section 108 of the Federal Clean Air Act. Mandated by Title I of the Federal Clean Air Act and implemented by 40 CFR Parts 51 and 52 and District Regulation 2, Rule 2. (Note: There are additional NSR requirements mandated by the California Clean Air Act.)

Offset Requirement

A New Source Review requirement to provide federally enforceable emission offsets for the emissions from a new or modified source. Applies to emissions of POC, NOx, PM10, and SO2.

OHAP

Organic Hazardous Air Pollutant

PHA

Process Hazard Analysis as defined by BAAQMD Regulation 8, Rule 28.

Phase II Acid Rain Facility

A facility that generates electricity for sale through fossil-fuel combustion and is not exempted by 40 CFR 72 from Titles IV and V of the Clean Air Act.

POC

Precursor Organic Compounds

PM

Particulate Matter

X. Glossary

PM10

Particulate matter with aerodynamic equivalent diameter of less than or equal to 10 microns

PSD

Prevention of Significant Deterioration. A federal program for permitting new and modified sources of those air pollutants for which the District is classified "attainment" of the National Air Ambient Quality Standards. Mandated by Title I of the Act and implemented by both 40 CFR Part 52 and District Regulation 2, Rule 2.

RACT

Reasonable Available Control Technology

SIP

State Implementation Plan. State and District programs and regulations approved by EPA and developed in order to attain the National Air Ambient Quality Standards. Mandated by Title I of the Act.

SO2

Sulfur dioxide

Title V

Title V of the federal Clean Air Act. Requires a federally enforceable operating permit program for major and certain other facilities.

TRMP

Toxic Risk Management Plan

TSP

Total Suspended Particulate

TVP

True Vapor Pressure, psia

VOC

Volatile Organic Compounds

VOL

Volatile Organic Liquid

Units of Measure:

Bbl	=	barrel
bhp	=	brake-horsepower

X. Glossary

btu	=	British Thermal Unit
cm	=	centimeter
g	=	grams
gal	=	gallon
hp	=	horsepower
hr	=	hour
lb	=	pound
in	=	inches
max	=	maximum
m	=	meter
m ²	=	square meter
min	=	minute
mm	=	million
ppmv	=	parts per million, by volume
ppmw	=	parts per million, by weight
psia	=	pounds per square inch, absolute
psig	=	pounds per square inch, gauge
scfm	=	standard cubic feet per minute
yr	=	year

XI. APPLICABLE STATE IMPLEMENTATION PLAN

The Bay Area Air Quality Management District's portion of the State Implementation Plan can be found at EPA Region 9's website. The address is:

<http://yosemite1.epa.gov/r9/r9sips.nsf/California?ReadForm&Start=1&Count=30&Expand=3.1>