

FACILITY PERMIT TO OPERATE ROHR,INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 20 : LASER CUTTING					
CUTTER, R & D PROTOTYPE, LASER, MODEL NO. YLP-1/100/20, 220 WATTS MAXIMUM A/N:	D248	C249		PM: (9) [RULE 405,2-7-1986]	B59.10, C1.20, D323.1, E57.1, E147.1, E193.2
DUST COLLECTOR, FUMEX, FA1, WITH ONE POLYESTER PREFILTER, ONE MERV 11 PANEL FILTER, ONE HEPA, & ONE ADSORBER (CARBON AND ALUMINUM IMPRGNATED POTASSIUM PERMANGANATE) A/N:	C249	D248		PM: (9) [RULE 404,2-7-1986]	C6.19, D29.1, D90.2, D322.4, D381.2, E102.1, E193.2, K67.1

* (1)(1A)(1B) Denotes RECLAIM emission factor
 (2)(2A)(2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5)(5A)(5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
ROHR,INC**

SECTION H: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

**FACILITY PERMIT TO OPERATE
ROHR,INC**

SECTION H: DEVICE ID INDEX

Device Index For Section H			
Device ID	Section H Page No.	Process	System
D248	1	20	0
C249	1	20	0

FACILITY PERMIT TO OPERATE ROHR, INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or

(b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[**RULE 401, 3-2-1984**; RULE 401, 11-9-2001]

F14.1 The operator shall not purchase diesel fuel containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

[**RULE 431.2, 9-15-2000**]

F14.2 The operator shall not use diesel fuel containing sulfur compounds in excess of 0.05 percent by weight.

[**RULE 431.2, 5-4-1990**; RULE 431.2, 9-15-2000]

PROCESS CONDITIONS

FACILITY PERMIT TO OPERATE ROHR, INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

P2.1 The operator shall limit emissions from this process as follows

CONTAMINANT	EMISSIONS LIMIT
VOC	Less than or equal to 1179 LBS IN ANY ONE DAY

For the purposes of this condition, the emission limit(s) shall be based on the total combined emissions from process 1(Ovens) and 4 (Surface coating).

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Processes subject to this condition : 1, 4]

DEVICE CONDITIONS

B. Material/Fuel Type Limits

B59.10 The operator shall not use the following material(s) in this device :

Materials containing any toxic air contaminants (TAC) listed in Table 1 of Rule 1401, with an effective date of March 7, 2008, or earlier.

[RULE 1401, 3-7-2008]

[Devices subject to this condition : D248]

C. Throughput or Operating Parameter Limits

FACILITY PERMIT TO OPERATE ROHR, INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

C1.20 The operator shall limit the material processed to no more than 10 in any one day.

For the purpose of this condition, material processed shall be defined as a 12" X 12" Hexcel Hexply 8552 impregnated carbon-fiber test panel.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D248]

C6.19 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 4.5 inches water column.

To comply with this condition, the operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the the filter media.

The operator shall determine and record the parameter being monitored once every 7 days.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C249]

D. Monitoring/Testing Requirements

FACILITY PERMIT TO OPERATE ROHR, INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D29.1 The operator shall conduct source test(s) for the pollutant(s) identified below.

Pollutant(s) to be tested	Required Test Method(s)	Averaging Time	Test Location
PM10 emissions	Approved District method	District-approved averaging time	Outlet
total hydrocarbon emissions	Approved District method	District-approved averaging time	Simultaneous inlet and outlet
Polynuclear Aromatic Hydrocarbons (PAH)	Approved District method	District-approved averaging time	Simultaneous inlet and outlet
Cyanide emissions	Approved District method	District-approved averaging time	Simultaneous inlet and outlet

A speciated analysis shall be conducted for organic compounds using GC/MS.

The speciated analysis shall be conducted for the inlet and outlet

The source test shall be conducted no later than 210 days after the initial start-up of this equipment unless otherwise approved in writing by the District.

The test shall be conducted to determine the emissions of any toxic air contaminants and volatile organic compounds resulting from the laser cutting operation, the collection efficiency, and the control efficiency of the control equipment.

Two complete copies of source test protocol shall be submitted to the District engineer no later than 90 days after the initial start-up of this equipment unless otherwise approved in writing by the District. The test protocol shall be approved in writing by the District before the test commences.

The test protocol shall include, but not limited to, the proposed operating conditions of the equipment during the test, the identity of the testing laboratory, a statement from the testing laboratory certifying it meets the criteria in District Rule 304(k), and a description of the sampling and analytical procedures to be used.

A written notice of the source tests shall be submitted to the District engineer at least 14 days prior to source testing date so that an observer from the District may be present.

Two complete copies of source test reports shall be submitted to the District engineer within 45 days after the source testing date.

The source test report shall also include, exhaust flow rate, moisture content, O2 concentration, the number of panels used during the test, number of holes cut, and diameter and depth of each hole cut

FACILITY PERMIT TO OPERATE ROHR, INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 3-7-2008]

[Devices subject to this condition : C249]

D90.2 The operator shall periodically monitor the hydrocarbon concentration at the inlet and outlet according to the following specifications:

The operator shall use a District approved Organic Vapor Analyzer (OVA) to monitor the parameter.

The operator shall calibrate the instrument used to monitor the parameter in ppmv methane.

The operator shall monitor once every month.

The monitoring frequency shall be reduced to at least quarterly, if three consecutive monthly monitoring show no hydrocarbon readings

The monitoring frequency shall be increased to once every month, no later than 30 days after the discovery of any hydrocarbon readings

The operator shall maintain records to demonstrate compliance with this condition

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : C249]

D322.4 The operator shall perform a monthly inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C249]

FACILITY PERMIT TO OPERATE ROHR, INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D248]

FACILITY PERMIT TO OPERATE ROHR, INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D381.2 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions; and
- 3). Date and time visible emission was abated.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C249]

E. Equipment Operation/Construction Requirements

E57.1 The operator shall vent this equipment to an air pollution control device which is in full use and which has been issued a permit to operate by the Executive officer whenever it is in operation.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D248]

E102.1 The operator shall discharge dust collected in this equipment only into closed containers.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C249]

FACILITY PERMIT TO OPERATE ROHR, INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

E147.1 The operator shall only conduct the processing of resin impregnated carbon fiber in this equipment.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; **RULE 1303(b)(2)-Offset, 12-6-2002**]

[Devices subject to this condition : D248]

E193.2 The operator shall construct this equipment according to the following requirements:

This permit shall expire if the construction of this equipment is not completed within one year from the date of the issuance of this permit unless an extension of time has been approved in writing by a District representative.

The operator shall notify a District representative when construction has been completed.

[**RULE 204, 10-8-1993**]

[Devices subject to this condition : D248, C249]

K. Record Keeping/Reporting

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

the name of the person performing the inspection and/or maintenance of the filter media

the date, time and results of the inspection

the date, time and description of any maintenance or repairs resulting from the inspection

[**RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : C249]