FACILITY PERMIT TO OPERATE

DEFT INC
17451 VON KARMAN AVE
IRVINE, CA 92614

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By_____
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance

FACILITY PERMIT TO OPERATE
DEFT INC

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	DRAFT	05/27/2012
B	RECLAIM Annual Emission Allocation	DRAFT	05/27/2012
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	DRAFT	05/27/2012
E	Administrative Conditions	DRAFT	05/27/2012
F	RECLAIM Monitoring and Source Testing Requirements	DRAFT	05/27/2012
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	DRAFT	05/27/2012
H	Permit To Construct and Temporary Permit to Operate	DRAFT	05/27/2012
I	Compliance Plans & Schedules	DRAFT	05/27/2012
J	Air Toxics	DRAFT	05/27/2012
K	Title V Administration	DRAFT	05/27/2012
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	DRAFT	05/27/2012
B	Rule Emission Limits	DRAFT	05/27/2012

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION A: FACILITY INFORMATION

LEGAL OWNER &/OR OPERATOR:	DEFT INC
LEGAL OPERATOR (if different than owner):	
EQUIPMENT LOCATION:	17451 VON KARMAN AVE IRVINE, CA 92614-6205
MAILING ADDRESS:	17451 VON KARMAN AVE IRVINE, CA 92614-6205
RESPONSIBLE OFFICIAL:	THOMAS R. BOYLAN
TITLE:	VICE PRESIDENT OF OPERATION
TELEPHONE NUMBER:	(949) 476-6737
CONTACT PERSON:	MAHIR BARKHO
TITLE:	PLANT ENGINEER
TELEPHONE NUMBER:	(949) 476-6737
TITLE V PERMIT ISSUED:	August 01, 2007
TITLE V PERMIT EXPIRATION DATE:	July 31, 2012

TITLE V	RECLAIM	
YES	NOx:	NO
	SOx:	NO
	CYCLE:	0
	ZONE:	COASTAL

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

NOT APPLICABLE

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION C: FACILITY PLOT PLAN

(TO BE DEVELOPED)

FACILITY PERMIT TO OPERATE
DEFT INC

Facility Equipment and Requirements
(Section D)

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.

FACILITY PERMIT TO OPERATE
DEFT INC

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

Application number	Permit to Operate number	Equipment description
00535A	S01356	PAINTS BLENDING
437591	F91001	PAINTS BLENDING
00537A	S01358	PAINTS BLENDING
00538A	S01359	PAINTS BLENDING
00539A	S01360	PAINTS BLENDING
02293A	S01361	PAINTS BLENDING
02294A	S01362	PAINTS BLENDING
02295A	S01363	PAINTS BLENDING
02296A	S01364	PAINTS BLENDING
02297A	S01365	PAINTS BLENDING
02298A	S01366	PAINTS BLENDING
02299A	S01367	PAINTS BLENDING
02300A	S01368	PAINTS BLENDING
02301A	S01369	PAINTS BLENDING
02302A	S01370	PAINTS BLENDING
02303A	S01371	PAINTS BLENDING
02304A	S01372	PAINTS BLENDING
05260A	S05996	PAINTS BLENDING
05261A	S05997	PAINTS BLENDING
05262A	S05998	PAINTS BLENDING
05263A	S05999	PAINTS BLENDING
437592	F91002	PAINTS BLENDING
16176X	766176	SPRAY BOOTH PAINT AND SOLVENT
437589	F91000	PAINTS BLENDING
16528X	766528	SPRAY BOOTH OTHER
437593	F91003	BAGHOUSE, AMBIENT TEMP (>100-500 SQ FT)
176724	D05380	STORAGE TANK PLASTICS & RESINS
176725	D05381	STORAGE TANK PLASTICS & RESINS
176726	D05376	STORAGE TANK PLASTICS & RESINS
176727	D05375	STORAGE TANK PLASTICS & RESINS
176728	D05379	STORAGE TANK PLASTICS & RESINS
176729	D05378	STORAGE TANK PLASTICS & RESINS
176730	D05377	STORAGE TANK PLASTICS & RESINS
176731	D05374	STORAGE TANK PLASTICS & RESINS
176732	D05373	STORAGE TANK PLASTICS & RESINS
437571	F90999	PAINTS BLENDING
442784	F91006	BAGHOUSE, AMBIENT TEMP (>500 SQ FT)
437594	F91004	PAINTS BLENDING

FACILITY PERMIT TO OPERATE
DEFT INC

Application number	Permit to Operate number	Equipment description
388844	F48536	PAINTS BLENDING
437595	F91005	PAINTS BLENDING
427276	F71515	PAINT MILLING/BLENDING SYSTEM
491370	G1199	BASKET MILL
519917	G15308	BASKET MILL

NOTE: EQUIPMENT LISTED ABOVE THAT HAVE NO CORRESPONDING PERMITS TO OPERATE NUMBER ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT.

FACILITY PERMIT TO OPERATE
DEFT INC

FACILITY WIDE CONDITION(S)

Condition(s):

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:

   A. AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGLEMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
   B. OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (A) OF THIS CONDITION. [RULE 401]

2. MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST. [RULE 1303(a)(1)-BACT]

3. TO MAINTAIN EXEMPTION FROM THE NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS (NESHAP) REQUIREMENTS, THE TOTAL QUANTITY OF HAZARDOUS AIR POLLUTANT (HAP) EMISSIONS FROM THIS FACILITY SHALL NOT EXCEED 10 TONS (20,000 POUNDS) OF A SINGLE HAP OR 25 TONS (50,000 POUNDS) OF A COMBINATION OF HAPS IN ANY TWELVE CALENDAR MONTH PERIOD.
   [40CFR63 SUBPART HHHHH]

4. TO ENSURE COMPLIANCE WITH THE HAP(S) EMISSION CAPS OF THIS CONDITION, THE FACILITY OPERATOR SHALL:
   (A) IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT AND THIS FACILITY TO VERIFY THE MONTHLY HAP EMISSIONS IN POUNDS AND THE HAP CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS). THE RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT.
   (B) WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, TOTAL AND RECORD HAP EMISSIONS FOR THE MONTH FROM ALL EQUIPMENT AND OPERATIONS THAT ARE REQUIRED TO HAVE WRITTEN PERMITS OR ARE EXEMPT FROM WRITTEN PERMITS PURSUANT TO RULE 219. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.
   (C) MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED HAP-CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.
   (D) RETAIN ALL PURCHASE INVOICES FOR ALL HAP-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE HAP-CONTAINING MATERIAL REMOVED FROM THE FACILITY, FOR FIVE YEARS.
   [RULE 109, 40CFR63 SUBPART HHHHH]

FACILITY PERMIT TO OPERATE
DEFT INC

5. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, RETAINED AT THE FACILITY FOR FIVE YEARS, AND MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.
[RULE 109, 40CFR63 SUBPART HHHHH]

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01356
A/N 00535A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 25 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATIONS NOS. 00537A, 00538A, 00539A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTION OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A) NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B) DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. F91001
A/N 437591

Equipment Description:

POST MIXING STATION #5, MYERS, SERIAL NO. 800-50-128, MAXIMUM 1200 GALLONS MIXING CAPACITY, 50 HP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL NOT BE USED TO PROCESS MORE THAN 1200 GALLONS OF COATING IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC COMPOUNDS IDENTIFIED IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER, WITH THE EXCEPTION OF ACETALDEHYDE (CAS# 75-07-0), AMMONIA (CAS# 7664-41-7), ARSENIC (CAS# 7440-38-2), CADMIUM AND CADMIUM COMPOUNDS (CAS# 7440-43-9), HEXAVALENT CHROMIUM AND CHROMIUM COMPOUNDS (CAS# 18540-29-9), COPPER AND COPPER COMPOUNDS (CAS# 7440-50-8), CRESOL MIXTURES (CAS# 1319-77-3), ETHYL BENZENE (CAS# 100-41-4), GLYCOL ETHERS (CAS# 107-21-1, 111-76-2, 110-80-5, 111-15-9, 109-86-4, 110-49-6), ISOPROPYL ALCOHOL (CAS# 67-63-0), MANGANESE AND MANGANESE COMPOUNDS (CAS# 7439-96-5), METHANOL (CAS# 67-56-1), METHYL ETHYL KETONE (CAS# 78-93-3), NICKEL AND NICKEL COMPOUNDS (CAS# 7440-02-0), PHENOL (CAS# 108-95-2), PHOSPHOROUS AND PHOSPHOROUS COMPOUNDS (CAS# 7723-14-0), PROPYLENE GLYCOL MONOMETHYL ETHER (107-98-2), SELENIUM AND SELENIUM COMPOUNDS (7782-49-2), TOLUENE (108-88-3), VINYLIDINE CHLORIDE (75-35-4) AND XYLENES (1330-20-7).
[RULE 1401]

6. THE MAXIMUM QUANTITY OF HEXAVALENT CHROMIUM CONTAINED IN MATERIALS PROCESSED IN MIXERS UNDER APPLICATION NUMBERS 437571, 437589, 437591, 437592, 437594 AND 437595 COMBINED SHALL NOT EXCEED 187,500 POUNDS IN ANY ONE CALENDAR YEAR.
[RULE 1401]

FACILITY PERMIT TO OPERATE
DEFT INC

7. THE OPERATOR SHALL KEEP ADEQUATE RECORDS OF MATERIALS PROCESSED IN THIS EQUIPMENT IN GALLONS PER DAY, WEIGHT PERCENT HEXAVALENT CHROMIUM, DENSITY, AND POUNDS OF HEXAVALENT CHROMIUM.
[RULE 1303(b)(2)-OFFSET, 1401]

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE MOVEABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

9. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

10. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL “VISIBLE EMISSION EVALUATION”, WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;
B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE
DEFT INC

Emissions And Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 109
    VOC: RULE 1141.1
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS
    PM: RULE 405, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01358
A/N 00537A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 25 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATIONS NOS. 00535A, 00538A, 00539A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01359
A/N 00538A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 25 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATIONS NOS. 00535A, 00537A, 00539A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01360
A/N 00539A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 25 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATIONS NOS. 00535A, 00537A, 00538A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01361
A/N 02293A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 20 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATION NO. 02294A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01362
A/N 02294A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 20 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATION NO. 02293A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01363
A/N 02295A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 20 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATION NO. 02296A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01364
A/N 02296A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 20 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATION NO. 02295A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01365
A/N 02297A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 20 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATION NO. 02298A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01366
A/N 02298A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 20 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATION NO. 02297A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01367
A/N 02299A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 20 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATION NO. 02300A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01368
A/N 02300A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 20 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATION NO. 02299A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01369
A/N 02301A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 20 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATION NO. 02302A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01370
A/N 02302A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 20 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATION NO. 02301A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01371
A/N 02303A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 20 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATION NO. 02304A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S01372
A/N 02304A

Equipment Description:

MIXING TANK, SURFACE COATINGS, 2000 GALLONS CAPACITY, WITH A 20 HP AGITATOR, SHARING COMMON DRIVE WITH APPLICATION NO. 02303A.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S05996
A/N 05260A

Equipment Description:

POST MIXING STATION, COWLES, 25 HP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE MOVEABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

5. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN

FACILITY PERMIT TO OPERATE
DEFT INC

ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S05997
A/N 05261A

Equipment Description:

POST MIXING STATION, COWLES, 25 HP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE MOVEABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

5. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN

FACILITY PERMIT TO OPERATE
DEFT INC

ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S05998
A/N 05262A

Equipment Description:

POST MIXING STATION, COWLES, 30 HP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE MOVEABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

5. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN

FACILITY PERMIT TO OPERATE
DEFT INC

ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. S05999
A/N 05263A

Equipment Description:

POST MIXING STATION, COWLES, 30 HP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE MOVEABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

4. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

5. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN

FACILITY PERMIT TO OPERATE
DEFT INC

ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. F91002
A/N 437592

Equipment Description:

POST MIXING STATION NO. 11, ARMENCO, MODEL NO. 50-7000, SERIAL NO. 38403, 50 HP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL NOT BE USED TO PRODUCE MORE THAN 1200 GALLONS OF COATING IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED DURING THE LOADING OF SOLIDS TO A BAGHOUSE WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC COMPOUNDS IDENTIFIED IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER, WITH THE EXCEPTION OF ACETALDEHYDE (CAS# 75-07-0), AMMONIA (CAS# 7664-41-7), ARSENIC (CAS# 7440-38-2), CADMIUM AND CADMIUM COMPOUNDS (CAS# 7440-43-9), HEXAVALENT CHROMIUM AND CHROMIUM COMPOUNDS (CAS# 18540-29-9), COPPER AND COPPER COMPOUNDS (CAS# 7440-50-8), CRESOL MIXTURES (CAS# 1319-77-3), ETHYL BENZENE (CAS# 100-41-4), GLYCOL ETHERS (CAS# 107-21-1, 111-76-2, 110-80-5, 111-15-9, 109-86-4, 110-49-6), ISOPROPYL ALCOHOL (CAS# 67-63-0), MANGANESE AND MANGANESE COMPOUNDS (CAS# 7439-96-5), METHANOL (CAS# 67-56-1), METHYL ETHYL KETONE (CAS# 78-93-3), NICKEL AND NICKEL COMPOUNDS (CAS# 7440-02-0), PHENOL (CAS# 108-95-2), PHOSPHOROUS AND PHOSPHOROUS COMPOUNDS (CAS# 7723-14-0), PROPYLENE GLYCOL MONOMETHYL ETHER (107-98-2), SELENIUM AND SELENIUM COMPOUNDS (7782-49-2), TOLUENE (108-88-3), VINYLIDINE CHLORIDE (75-35-4) AND XYLENES (1330-20-7).
[RULE 1401]

6. THE MAXIMUM QUANTITY OF HEXAVALENT CHROMIUM CONTAINED IN MATERIALS PROCESSED IN MIXERS UNDER APPLICATION NUMBERS 437571, 437589, 437591, 437592, 437594 AND 437595 COMBINED SHALL NOT EXCEED 187,500 POUNDS IN ANY ONE CALENDAR YEAR.
[RULE 1401]

FACILITY PERMIT TO OPERATE
DEFT INC

7. THE OPERATOR SHALL KEEP ADEQUATE RECORDS OF MATERIALS PROCESSED IN THIS EQUIPMENT IN GALLONS PER DAY, WEIGHT PERCENT HEXAVALENT CHROMIUM, DENSITY, AND POUNDS OF HEXAVALENT CHROMIUM.
[RULE 1303(b)(2)-OFFSET, 1401]

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE MOVEABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

9. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

10. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL “VISIBLE EMISSION EVALUATION”, WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;
B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions And Requirements:

FACILITY PERMIT TO OPERATE
DEFT INC

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. 766176
A/N 16176X

Equipment Description:

SPRAY BOOTH, BRINKS, FLOOR TYPE, MODEL FEC 15-10-T, 15'-0" W. X 9'-6" H. X 4'-2" D., WITH A 7-1/2 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE FILTERING MEDIA.
[RULE 1303(a)(1)-BACT]

4. THE PRESSURE DROP MEASURED ACROSS THE EXHAUST FILTERS SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

5. THE OPERATOR SHALL NOT USE THIS EQUIPMENT UNLESS ALL EXHAUST AIR PASSES THROUGH A FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 3004 (a)(4)]

6. THE OPERATOR SHALL INSTALL AND MAINTAIN A DIFFERENTIAL PRESSURE GAUGE TO ACCURATELY INDICATE THE DIFFERENTIAL PRESSURE ACROSS THE FILTER. THE OPERATOR SHALL DETERMINE AND RECORD THE PARAMETER BEING MONITORED ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

7. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

FACILITY PERMIT TO OPERATE
DEFT INC

[RULE 3004 (a)(4)]

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1107, SEE APPENDIX B FOR EMISSIONS LIMITS
VOC: RULE 1136, SEE APPENDIX B FOR EMISSIONS LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS
PM: RULE 404, SEE APPENDIX B FOR EMISSIONS LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. F91000
A/N 437589

Equipment Description:

POST MIXER #4, ARMENCO, 1500 GALLONS CAPACITY, WITH A TWO SPEED 100 HP DISPERSION AGITATOR.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL NOT BE USED TO PRODUCE MORE THAN 1500 GALLONS OF COATING IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED DURING THE LOADING OF SOLIDS TO A BAGHOUSE WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC COMPOUNDS IDENTIFIED IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER, WITH THE EXCEPTION OF ACETALDEHYDE (CAS# 75-07-0), AMMONIA (CAS# 7664-41-7), ARSENIC (CAS# 7440-38-2), CADMIUM AND CADMIUM COMPOUNDS (CAS# 7440-43-9), HEXAVALENT CHROMIUM AND CHROMIUM COMPOUNDS (CAS# 18540-29-9), COPPER AND COPPER COMPOUNDS (CAS# 7440-50-8), CRESOL MIXTURES (CAS# 1319-77-3), ETHYL BENZENE (CAS# 100-41-4), GLYCOL ETHERS (CAS# 107-21-1, 111-76-2, 110-80-5, 111-15-9, 109-86-4, 110-49-6), ISOPROPYL ALCOHOL (CAS# 67-63-0), MANGANESE AND MANGANESE COMPOUNDS (CAS# 7439-96-5), METHANOL (CAS# 67-56-1), METHYL ETHYL KETONE (CAS# 78-93-3), NICKEL AND NICKEL COMPOUNDS (CAS# 7440-02-0), PHENOL (CAS# 108-95-2), PHOSPHOROUS AND PHOSPHOROUS COMPOUNDS (CAS# 7723-14-0), PROPYLENE GLYCOL MONOMETHYL ETHER (107-98-2), SELENIUM AND SELENIUM COMPOUNDS (7782-49-2), TOLUENE (108-88-3), VINYLIDINE CHLORIDE (75-35-4) AND XYLENES (1330-20-7).
[RULE 1401]

6. THE MAXIMUM QUANTITY OF HEXAVALENT CHROMIUM CONTAINED IN MATERIALS PROCESSED IN MIXERS UNDER APPLICATION NUMBERS 437571, 437589, 437591, 437592, 437594 AND 437595 COMBINED SHALL NOT EXCEED 187,500 POUNDS IN ANY ONE CALENDAR YEAR.
[RULE 1401]

FACILITY PERMIT TO OPERATE
DEFT INC

7. THE OPERATOR SHALL KEEP ADEQUATE RECORDS OF MATERIALS PROCESSED IN THIS EQUIPMENT IN GALLONS PER DAY, WEIGHT PERCENT HEXAVALENT CHROMIUM, DENSITY, AND POUNDS OF HEXAVALENT CHROMIUM.
[RULE 1303(b)(2)-OFFSET, 1401]

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE MOVEABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A) NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B) DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

9. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

10. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL “VISIBLE EMISSION EVALUATION”, WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;
B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

FACILITY PERMIT TO OPERATE
DEFT INC

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. 766528
A/N 16528X

Equipment Description:

DEVILBISS FLOOR BOOTH, MODIFIED FROM A BENCH TYPE, WITH SIX 20" X 24" FILTERS, AND 1 HP FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE FILTERING MEDIA.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL NOT USE THIS EQUIPMENT UNLESS ALL EXHAUST AIR PASSES THROUGH A FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 3004 (a)(4)]

5. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE DIFFERENTIAL PRESSURE ACROSS THE FILTER DOES NOT EXCEED 0.25 INCHES WATER COLUMN. TO COMPLY WITH THIS CONDITION THE OPERATOR SHALL INSTALL AND MAINTAIN A PRESSURE GAUGE TO ACCURATELY INDICATE THE DIFFERENTIAL PRESSURE ACROSS THE FILTER. THE OPERATOR SHALL DETERMINE AND RECORD THE PARAMETER BEING MONITORED ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

6. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM

FACILITY PERMIT TO OPERATE
DEFT INC

THE INSPECTION.
[RULE 3004 (a)(4)]

Emissions And Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1107, SEE APPENDIX B FOR EMISSIONS LIMITS
VOC: RULE 1136, SEE APPENDIX B FOR EMISSIONS LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS
PM: RULE 404, SEE APPENDIX B FOR EMISSIONS LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. F91003
A/N 437593

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. BAGHOUSE, FABRIC MAX, MODEL FJB72-8, SERIAL NO. 1445, PULSE JET TYPE.

2. HEPA FILTRATION BOX, 4’ W. X 2’ L. X 4’ D., WITH TWO PRE-FILTERS, 24" W. X 24" L. X 2" D. EACH, AND TWO HEPA FILTERS, 24” W. X 24” L. X 12" D. EACH.

3. EXHAUST SYSTEM WITH A 15 HP BLOWER, VENTING 13 MIXING VESSELS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL NOT BE USED TO VENT MORE THAN 3 MIXERS AT ANY ONE TIME.
[RULE 1303(a)(1)-BACT]

4. DUSTS COLLECTED IN THE BAGHOUSE SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]

5. SLIDE DAMPERS SHALL BE INSTALLED IN EACH BRANCH DUCT OF THE EXHAUST SYSTEM.
[RULE 1303(a)(1)-BACT]

6. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE BAGS. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DIFFERENTIAL ONCE EVERY WEEK.
[RULE 1303(a)(1)-BACT]

7. A GAUGE SHALL BE INSTALLED AND MAINTAINED TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE HEPA FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 2.5 INCHES OF WATER. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DIFFERENTIAL ONCE EVERY WEEK.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE
DEFT INC

8. THE HEPA FILTERS USED IN THIS EQUIPMENT SHALL BE INDIVIDUALLY DOP (OR EQUIVALENT) TESTED WITH 0.3 MICRON PARTICLES AND CERTIFIED TO HAVE AN EFFICIENCY OF NOT LESS THAN 99.999 PERCENT.
[RULE 1303(a)(1)-BACT, 1401]

Periodic Monitoring:

9. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    PM: RULE 404, SEE APPENDIX B FOR EMISSIONS LIMITS
    PM: 0 PERCENT OPACITY, RULE 1155

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. D05380
A/N 176724

Equipment Description:

PORTABLE TOTE BIN, EPOTUE 98-444 RESIN, 48" L. X 64" H., 550 GALLON CAPACITY.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL BE FILLED BY SUBMERGED FILL PIPE ONLY.
[RULE 1303(a)(1)-BACT]

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. D05381
A/N 176725

Equipment Description:

PORTABLE TOTE BIN, EPOTUE 98-444 RESIN, 48" W. X 48" L. X 64" H., 550 GALLON CAPACITY.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL BE FILLED BY SUBMERGED FILL PIPE ONLY.
[RULE 1303(a)(1)-BACT]

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. D05376
A/N 176726

Equipment Description:

PORTABLE TOTE BIN, EPOTUE 98-444 RESIN, 48" W. X 48" L. X 64" H., 550 GALLON CAPACITY.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL BE FILLED BY SUBMERGED FILL PIPE ONLY.
[RULE 1303(a)(1)-BACT]

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. D05375
A/N 176727

Equipment Description:

PORTABLE TOTE BIN, EPOTUE 98-444 RESIN, 48" W. X 48" L. X 64" H., 550 GALLON CAPACITY.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL BE FILLED BY SUBMERGED FILL PIPE ONLY.
[RULE 1303(a)(1)-BACT]

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. D05379
A/N 176728

Equipment Description:

PORTABLE TOTE BIN, EPOTUE 98-444 RESIN, 48" W. X 48" L. X 64" H., 550 GALLON CAPACITY.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL BE FILLED BY SUBMERGED FILL PIPE ONLY.
[RULE 1303(a)(1)-BACT]

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. D05378
A/N 176729

Equipment Description:

PORTABLE TOTE BIN, EPOTUE 98-444 RESIN, 48" W. X 48" L. X 64" H., 550 GALLON CAPACITY.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL BE FILLED BY SUBMERGED FILL PIPE ONLY.
[RULE 1303(a)(1)-BACT]

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. D05377
A/N 176730

Equipment Description:

PORTABLE TOTE BIN, EPOTUE 98-444 RESIN, 48" W. X 48" L. X 64" H., 550 GALLON CAPACITY.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL BE FILLED BY SUBMERGED FILL PIPE ONLY.
[RULE 1303(a)(1)-BACT]

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. D05374
A/N 176731

Equipment Description:

PORTABLE TOTE BIN, EPOTUE 98-444 RESIN, 48" W. X 48" L. X 64" H., 550 GALLON CAPACITY.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL BE FILLED BY SUBMERGED FILL PIPE ONLY.
[RULE 1303(a)(1)-BACT]

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. D05373
A/N 176732

Equipment Description:

PORTABLE TOTE BIN, EPOTUE 98-444 RESIN, 48" W. X 48" L. X 64" H., 550 GALLON CAPACITY.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL BE FILLED BY SUBMERGED FILL PIPE ONLY.
[RULE 1303(a)(1)-BACT]

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. F90999
A/N 437571

Equipment Description:

PAINT MANUFACTURING SYSTEM #2 CONSISTING OF:

1. DISPERSION TANK, 7'-0" DIA. X 7'-0" H., 2200 GALLON MAXIMUM WORKING CAPACITY WITH A 125 HP HIGH SPEED DISPERSER, ARMENCO.

2. HOLDING TANK, 7'-0" DIA. X 7'-0" H., ARMENCO ENGINEERING, 2200 GALLON MAXIMUM WORKING CAPACITY WITH A 25 HP AGITATOR.

3. MILL, HORIZONTAL BEAD, NETSCH, WITH A 50 HP MOTOR COMMON.

4. HOLDING TANK, ARMENCO ENGINEERING, NO. 13A, 2200 GALLON MAXIMUM WORKING CAPACITY.

5. HOLDING TANK, ARMENCO ENGINEERING, NO. 14A, 2200 GALLON MAXIMUM WORKING CAPACITY.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL NOT BE USED TO PRODUCE MORE THAN 2200 GALLONS OF COATING IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]

4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC COMPOUNDS IDENTIFIED IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER, WITH THE EXCEPTION OF ACETALDEHYDE (CAS# 75-07-0), AMMONIA (CAS# 7664-41-7), ARSENIC (CAS# 7440-38-2), CADMIUM AND CADMIUM COMPOUNDS (CAS# 7440-43-9), HEXAVALENT CHROMIUM AND CHROMIUM COMPOUNDS (CAS# 18540-29-9), COPPER AND COPPER COMPOUNDS (CAS# 7440-50-8), CRESOL MIXTURES (CAS# 1319-77-3), ETHYL BENZENE (CAS# 100-41-4), GLYCOL ETHERS (CAS# 107-21-1, 111-76-2, 110-80-5, 111-15-9, 109-86-4, 110-49-6), ISOPROPYL

FACILITY PERMIT TO OPERATE
DEFT INC

ALCOHOL (CAS# 67-63-0), MANGANESE AND MANGANESE COMPOUNDS (CAS# 7439-96-5), METHANOL (CAS# 67-56-1), METHYL ETHYL KETONE (CAS# 78-93-3), NICKEL AND NICKEL COMPOUNDS (CAS# 7440-02-0), PHENOL (CAS# 108-95-2), PHOSPHOROUS AND PHOSPHOROUS COMPOUNDS (CAS# 7723-14-0), PROPYLENE GLYCOL MONOMETHYL ETHER (107-98-2), SELENIUM AND SELENIUM COMPOUNDS (7782-49-2), TOLUENE (108-88-3), VINYLIDINE CHLORIDE (75-35-4) AND XYLENES (1330-20-7).
[RULE 1401]

6. THE MAXIMUM QUANTITY OF HEXAVALENT CHROMIUM CONTAINED IN MATERIALS PROCESSED IN MIXERS UNDER APPLICATION NUMBERS 437571, 437589, 437591, 437592, 437594 AND 437595 COMBINED SHALL NOT EXCEED 187,500 POUNDS IN ANY ONE CALENDAR YEAR.
[RULE 1401]

7. THE OPERATOR SHALL KEEP ADEQUATE RECORDS OF MATERIALS PROCESSED IN THIS EQUIPMENT IN GALLONS PER DAY, WEIGHT PERCENT HEXAVALENT CHROMIUM, DENSITY, AND POUNDS OF HEXAVALENT CHROMIUM.
[RULE 1303(b)(2)-OFFSET, 1401]

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE MOVEABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A) NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B) DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

9. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

10. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL “VISIBLE

FACILITY PERMIT TO OPERATE
DEFT INC

EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions And Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. F91006
A/N 442784

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. BAGHOUSE, TORIT, MODEL DFT 3-12, TWELVE 13.84" DIA. X 26" L. BAGS, 3048 SQUARE FEET FILTER AREA WITH A PULSE-JET CLEANING SYSTEM.

2. HEPA FILTRATION BOX, WITH THREE PRE-FILTERS, 24" W. X 24" L. X 2" D. EACH, AND THREE HEPA FILTERS, 24” W. X 24” L. X 12" D. EACH.

3. EXHAUST SYSTEM WITH ONE 15 HP BLOWER, VENTING THREE MIXERS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. DUST COLLECTED IN THE BAGHOUSE SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE BAGS. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DIFFERENTIAL ONCE EVERY WEEK.
[RULE 1303(a)(1)-BACT]

5. A GAUGE SHALL BE INSTALLED AND MAINTAINED TO INDICATE, IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE HEPA FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 2.5 INCHES OF WATER. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DIFFERENTIAL ONCE EVERY WEEK.
[RULE 1303(a)(1)-BACT]

6. THE HEPA FILTERS USED IN THIS EQUIPMENT SHALL BE INDIVIDUALLY DOP (OR EQUIVALENT) TESTED WITH 0.3 MICRON PARTICLES AND CERTIFIED TO HAVE AN EFFICIENCY OF NOT LESS THAN 99.999 PERCENT.
[RULE 1303(a)(1)-BACT, 1401]

FACILITY PERMIT TO OPERATE
DEFT INC

7. MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST. [RULE 1303(a)(1)-BACT]

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

Emissions And Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   PM: RULE 404, SEE APPENDIX B FOR EMISSIONS LIMITS
   PM: 0 PERCENT OPACITY, RULE 1155

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. F91004
A/N 437594

Equipment Description:

POST MIXER NO. 10, MOREHOUSE-COWLES, MODEL V-130, 1000 GALLON CAPACITY, WITH A 100 HP AGITATOR.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

4. THIS EQUIPMENT SHALL NOT PROCESS MORE THAN 6000 POUNDS OF POWDER MATERIAL IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

5. MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT]

6. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC COMPOUNDS IDENTIFIED IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER, WITH THE EXCEPTION OF ACETALDEHYDE (CAS# 75-07-0), AMMONIA (CAS# 7664-41-7), ARSENIC (CAS# 7440-38-2), CADMIUM AND CADMIUM COMPOUNDS (CAS# 7440-43-9), HEXAVALENT CHROMIUM AND CHROMIUM COMPOUNDS (CAS# 18540-29-9), COPPER AND COPPER COMPOUNDS (CAS# 7440-50-8), CRESOL MIXTURES (CAS# 1319-77-3), ETHYL BENZENE (CAS# 100-41-4), GLYCOL ETHERS (CAS# 107-21-1, 111-76-2, 110-80-5, 111-15-9, 109-86-4, 110-49-6), ISOPROPYL ALCOHOL (CAS# 67-63-0), MANGANESE AND MANGANESE COMPOUNDS (CAS# 7439-96-5), METHANOL (CAS# 67-56-1), METHYL ETHYL KETONE (CAS# 78-93-3), NICKEL AND NICKEL COMPOUNDS (CAS# 7440-02-0), PHENOL (CAS# 108-95-2), PHOSPHOROUS AND PHOSPHOROUS COMPOUNDS (CAS# 7723-14-0), PROPYLENE GLYCOL MONOMETHYL ETHER (107-98-2), SELENIUM AND SELENIUM COMPOUNDS (7782-49-2), TOLUENE (108-88-3), VINYLIDINE CHLORIDE (75-35-4) AND XYLENES (1330-20-7).
[RULE 1401]

FACILITY PERMIT TO OPERATE
DEFT INC

7. THE MAXIMUM QUANTITY OF HEXAVALENT CHROMIUM CONTAINED IN MATERIALS PROCESSED IN MIXERS UNDER APPLICATION NUMBERS 437571, 437589, 437591, 437592, 437594 AND 437595 COMBINED SHALL NOT EXCEED 187,500 POUNDS IN ANY ONE CALENDAR YEAR. [RULE 1401]

8. THE OPERATOR SHALL KEEP ADEQUATE RECORDS OF MATERIALS PROCESSED IN THIS EQUIPMENT IN GALLONS PER DAY, WEIGHT PERCENT HEXAVALENT CHROMIUM, DENSITY, AND POUNDS OF HEXAVALENT CHROMIUM.
[RULE 1303(b)(2)-OFFSET, 1401]

Periodic Monitoring:

9. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE MOVEABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A) NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B) DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

10. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

11. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL “VISIBLE EMISSION EVALUATION”, WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;
B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

FACILITY PERMIT TO OPERATE
DEFT INC

D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER. [RULE 3004 (a)(4)]

Emissions And Requirements:

12. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171
PM: RULE 405, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. F48536
A/N 388844

Equipment Description:

POST MIXER, PAINT, ARMENCO, 150 H.P., WITH TWO 2,200 GALLON PRE-MIX VESSELS AND TWO 2,200 GALLON HOLDING VESSELS, EACH HOLDING VESSEL WITH A 50 H.P. AGITATOR.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL BE USED ONLY FOR THE MIXING OF WATER REDUCIBLE EPOXY RESIN, EPOXY, AND POLYURETHANE PAINTS.
[RULE 1303(a)(1)-BACT]

4. THIS EQUIPMENT SHALL NOT BE USED TO PROCESS MORE THAN 1 BATCH IN ANY ONE DAY.
[RULE 1303(a)(1)-BACT]

5. WHEN LOADING POWDER MATERIALS, THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH HAS BEEN ISSUED AN OPERATING PERMIT BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

6. RECORDS SHALL BE MAINTAINED TO PROVE COMPLIANCE WITH CONDITIONS 3 AND 4. THE RECORDS SHALL BE KEPT IN A FORMAT APPROVED IN WRITING BY THE DISTRICT. THE RECORDS SHALL BE RETAINED FOR AT LEAST FIVE YEARS AND MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

7. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE MOVEABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A) NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B) DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE
DEFT INC

8. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD. [RULE 3004(a)(4)]

9. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

   IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

   A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

   B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL “VISIBLE EMISSION EVALUATION”, WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

   THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

   A. STACK OR EMISSION POINT IDENTIFICATION;

   B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

   C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

   D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

   [RULE 3004 (a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 109
    VOC: RULE 1141.1
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS
    PM: RULE 405, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. F91005
A/N 437595

Equipment Description:

PAINT MANUFACTURING SYSTEM #3 CONSISTING OF:

1. DISPERSION TANK, 7'-0" DIA. X 7'-0" H., 2200 GALLON MAXIMUM WORKING CAPACITY WITH A 125 HP HIGH SPEED DISPERSER, ARMENCO.

2. HOLDING TANK, 7'-0" DIA. X 7'-0" H., ARMENCO ENGINEERING, 2200 GALLON MAXIMUM WORKING CAPACITY WITH A 25 HP AGITATOR.

3. MILL, HORIZONTAL BEAD, NETSCH, WITH A 50 HP MOTOR COMMON.

4. HOLDING TANK, ARMENCO ENGINEERING, NO. 15A, 2200 GALLON MAXIMUM WORKING CAPACITY.

5. HOLDING TANK, ARMENCO ENGINEERING, NO. 16A, 2200 GALLON MAXIMUM WORKING CAPACITY.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL NOT BE USED TO PRODUCE MORE THAN 2200 GALLONS OF COATING IN ANY ONE DAY.
[RULE 1303(a)(1)-BACT]

4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS THE MIXERS ARE VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC COMPOUNDS IDENTIFIED IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER, WITH THE EXCEPTION OF ACETALDEHYDE (CAS# 75-07-0), AMMONIA (CAS# 7664-41-7), ARSENIC (CAS# 7440-38-2), CADMIUM AND CADMIUM COMPOUNDS (CAS# 7440-43-9), HEXAVALENT CHROMIUM AND CHROMIUM COMPOUNDS (CAS# 18540-29-9), COPPER AND COPPER COMPOUNDS (CAS# 7440-50-8), CRESOL MIXTURES (CAS# 1319-77-3), ETHYL BENZENE (CAS# 100-41-4), GLYCOL ETHERS (CAS# 107-21-1, 111-76-2, 110-80-5, 111-15-9, 109-86-4, 110-49-6), ISOPROPYL

FACILITY PERMIT TO OPERATE
DEFT INC

ALCOHOL (CAS# 67-63-0), MANGANESE AND MANGANESE COMPOUNDS (CAS# 7439-96-5), METHANOL (CAS# 67-56-1), METHYL ETHYL KETONE (CAS# 78-93-3), NICKEL AND NICKEL COMPOUNDS (CAS# 7440-02-0), PHENOL (CAS# 108-95-2), PHOSPHOROUS AND PHOSPHOROUS COMPOUNDS (CAS# 7723-14-0), PROPYLENE GLYCOL MONOMETHYL ETHER (107-98-2), SELENIUM AND SELENIUM COMPOUNDS (7782-49-2), TOLUENE (108-88-3), VINYLIDINE CHLORIDE (75-35-4) AND XYLENES (1330-20-7).
[RULE 1401]

6. THE MAXIMUM QUANTITY OF HEXAVALENT CHROMIUM CONTAINED IN MATERIALS PROCESSED IN MIXERS UNDER APPLICATION NUMBERS 437571, 437589, 437591, 437592, 437594 AND 437595 COMBINED SHALL NOT EXCEED 187,500 POUNDS IN ANY ONE CALENDAR YEAR.
[RULE 1401]

7. THE OPERATOR SHALL KEEP ADEQUATE RECORDS OF MATERIALS PROCESSED IN THIS EQUIPMENT IN GALLONS PER DAY, WEIGHT PERCENT HEXAVALENT CHROMIUM, DENSITY, AND POUNDS OF HEXAVALENT CHROMIUM.
[RULE 1303(b)(2)-OFFSET, 1401]

Periodic Monitoring:

8. OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE MOVEABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A) NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
B) DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

9. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

10. OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL IFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY

FACILITY PERMIT TO OPERATE
DEFT INC

STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO OPERATE

Permit No. F71515
A/N 427276

Equipment Description:

LIQUID MILLING/BLENDING SYSTEM CONSISTING OF:

1. SUBMERSIBLE MILLING MACHINE, MODEL PSM180, 20 H.P. MOTOR.

2. PORTABLE PREMIXED PAINT TANK(s), MAXIMUM DIMENSIONS 2'-7" W. X 5'-6" L. X 5'-3" H., WITH THE MAXIMUM CAPACITY OF 450 GALLON.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE OPERATOR SHALL NOT ADD ANY POWDER MATERIALS TO THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]

4. THE EQUIPMENT SHALL COMPLY WITH ALL APPLICABLE WORK PRACTICE STANDARDS AND RECORDKEEPING REQUIREMENTS SPECIFIED IN RULE 1141.1.
[RULE 1141.1]

5. THE OPERATOR SHALL NOT PROCESS MORE THAN 960 GALLONS OF PRE-MIXED PAINT IN THIS EQUIPMENT IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

6. ALL VOC-CONTAINING MATERIALS, USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401 TABLE I, WITH AN EFFECTIVE DATE OF MAY 2, 2003 OR EARLIER.
[RULE 1401]

7. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO PROVE COMPLIANCE WITH CONDITION NO. 5. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR REPRESENTATIVE.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
DEFT INC

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE MOVEABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
   B. DATE, TIME AND RESULT OF THE INSPECTION.
   [RULE 3004(a)(4)]

9. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD. [RULE 3004(a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 109
    VOC: RULE 1141.1
    VOC: RULE 1171, SEE APPENDIX B FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO CONSTRUCT/OPERATE

Permit No. G1199
A/N 491370

Equipment Description:

BASKET MILL, PREMIER MILL, MODEL PSM-400, 8'-0" L. X 3'-8" W. X 7'-0" H. (OVERALL DIMENSIONS), WITH A 30 H.P. AGITATOR MOTOR, TWO 10 H.P. SIDE AGITATOR MOTORS AND A HYDRAULIC LIFT.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. NO SOLIDS OR LIQUID MATERIALS SHALL BE ADDED TO THE TANK AT THIS MILLING STATION.
[RULE 1303(b)(2)-OFFSET]

4. THE TANK CONTAINING THE COATING SHALL BE KEPT COVERED AT ALL TIMES EXCEPT TO LOWER OR REMOVE THE BASKET MILL.
[RULE 1303(a)(1)-BACT]

5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC COMPOUNDS IDENTIFIED IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 7, 2008 OR EARLIER, WITH THE EXCEPTION OF ACETALDEHYDE (CAS# 75-07-0), AMMONIA (CAS# 7664-41-7), ARSENIC (CAS# 7440-38-2), CADMIUM AND CADMIUM COMPOUNDS (CAS# 7440-43-9), HEXAVALENT CHROMIUM AND CHROMIUM COMPOUNDS (CAS# 18540-29-9), COPPER AND COPPER COMPOUNDS (CAS# 7440-50-8), CRESOL MIXTURES (CAS# 1319-77-3), ETHYL BENZENE (CAS# 100-41-4), GLYCOL ETHERS (CAS# 107-21-1, 111-76-2, 110-80-5, 111-15-9, 109-86-4, 110-49-6), ISOPROPYL ALCOHOL (CAS# 67-63-0), MANGANESE AND MANGANESE COMPOUNDS (CAS# 7439-96-5), METHANOL (CAS# 67-56-1), METHYL ETHYL KETONE (CAS# 78-93-3), NICKEL AND NICKEL COMPOUNDS (CAS# 7440-02-0), PHENOL (CAS# 108-95-2), PHOSPHOROUS AND PHOSPHOROUS COMPOUNDS (CAS# 7723-14-0), PROPYLENE GLYCOL MONOMETHYL ETHER (107-98-2), SELENIUM AND SELENIUM COMPOUNDS (7782-49-2), TOLUENE (108-88-3), VINYLIDINE CHLORIDE (75-35-4) AND XYLENES (1330-20-7).
[RULE 1401]

6. THIS PERMIT SHALL EXPIRE IF CONSTRUCTION OF THIS EQUIPMENT IS NOT COMPLETE BY JANUARY 6, 2010 (WITHIN ONE YEAR FROM THE P/C-P/O ISSUANCE DATE) UNLESS AN EXTENSION IS GRANTED BY THE EXECUTIVE OFFICER.
[RULE 205]

FACILITY PERMIT TO OPERATE
DEFT INC

Periodic Monitoring:

7. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE MOVEABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
   B. DATE, TIME AND RESULT OF THE INSPECTION.
   [RULE 3004(a)(4)]

8. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
   [RULE 3004(a)(4)]

Emissions and Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   VOC: RULE 109
   VOC: RULE 1141.1
   VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO CONSTRUCT/OPERATE

Permit No. G15308
A/N 519917

Equipment Description:

BASKET MILL, PREMIER MILL, MODEL PSM-400, 8'-0" L. X 3'-8" W. X 7'-0" H. (OVERALL DIMENSIONS), WITH A 30 H.P. MAIN AGITATOR MOTOR, TWO 10 H.P. SIDE AGITATOR MOTORS AND A HYDRAULIC LIFT.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. NO SOLIDS OR LIQUID MATERIALS SHALL BE ADDED TO THE TANK AT THIS MILLING STATION.
[RULE 1303(b)(2)-OFFSET]

4. THE TANK CONTAINING THE COATING SHALL BE KEPT COVERED AT ALL TIMES EXCEPT TO LOWER OR REMOVE THE BASKET MILL.
[RULE 1303(a)(1)-BACT]

5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC COMPOUNDS IDENTIFIED IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF SEPTEMBER 10, 2010 OR EARLIER, WITH THE EXCEPTION OF HEXAVALENT CHROMIUM AND CHROMIUM COMPOUNDS (CAS# 18540-29-9), GLYCOL ETHERS (CAS# 107-21-1, 111-76-2, 110-80-5, 111-15-9, 109-86-4, 110-49-6), ISOPROPYL ALCOHOL (CAS# 67-63-0), METHYL ETHYL KETONE (CAS# 78-93-3), NICKEL AND NICKEL COMPOUNDS (CAS# 7440-02-0), TOLUENE (108-88-3) AND XYLENES (1330-20-7).
[RULE 1401]

6. THIS PERMIT SHALL EXPIRE IF CONSTRUCTION OF THIS EQUIPMENT IS NOT COMPLETE BY OCTOBER 11, 2012 (WITHIN ONE YEAR FROM THE P/C-P/O ISSUANCE DATE) UNLESS AN EXTENSION IS GRANTED BY THE EXECUTIVE OFFICER.
[RULE 205]

Periodic Monitoring:

7. THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTIONS OF THE EQUIPMENT TO ENSURE THAT THE MOVEABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.

FACILITY PERMIT TO OPERATE
DEFT INC

B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]

8. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES A STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

Emissions and Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1141.1
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

PERMIT TO CONSTRUCT

NONE

FACILITY PERMIT TO OPERATE
DEFT INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

Periodic Monitoring:

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

   FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (g/l) OF MATERIALS FOR LOW-SOLIDS COATINGS, (c) VOC CONTENT AS SUPPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

   FOR OTHER ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS APPLIED IN GRAMS PER LITER (g/l) OF MATERIALS USED FOR LOW-SOLIDS COATINGS, (c) VOC CONTENT AS APPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

   [RULE 3004 (a) (4)]

Emissions And Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS
   VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

   VOC: RULE 109
   VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION E: ADMINISTRATIVE CONDITIONS

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]

   a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]

   b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]

   c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]

2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]

3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the AQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations, or statutes of other governmental agencies. [204]

4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION E: ADMINISTRATIVE CONDITIONS

5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation. [204]

6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to AQMD personnel upon request and be maintained for at least five years. [204]

7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by AQMD rules or permit conditions: [204]

   a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134]

   b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]

   c. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes; [204]

   d. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compounds which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO2) and be averaged over 15 consecutive minutes; [407]

   e. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent of carbon dioxide (CO2) at standard conditions and averaged over a minimum of 15 consecutive minutes. [409]

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION E: ADMINISTRATIVE CONDITIONS

f. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O2) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]

8. The operator shall, when a source test is required by AQMD, provide a source test protocol to AQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by AQMD. The test protocol shall contain the following information: [204, 304]

a. Brief description of the equipment tested.

b. Brief process description, including maximum and normal operating temperatures, pressures, throughput, etc.

c. Operating conditions under which the test will be performed.

d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).

e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.

f. Description of calibration and quality assurance procedures.

g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (conflict of interest).

9. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by AQMD rules or equipment-specific conditions. The report shall contain the following information: [204]

a. The results of the source test.

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION E: ADMINISTRATIVE CONDITIONS

b. Brief description of the equipment tested.

c. Operating conditions under which the test was performed.

d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).

e. Field and laboratory data forms, strip charts and analyses.

f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.

10. The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of AQMD Source Test Method 1.1 and 1.2. [217]

11. Whenever required to submit a written report, notification or other submittal to the Executive Officer, AQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, AQMD, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182. [204]

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

NOT APPLICABLE

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR RECLAIM SOURCES

NOT APPLICABLE

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

See Section D of this permit for any Permit to Construct issued to this facility.

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION I: PLANS AND SCHEDULES

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules.

NONE

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION J: AIR TOXICS

NOT APPLICABLE

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]

2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

   (B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]

4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION K: TITLE V Administration

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:

   (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.

   (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.

   (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:

   (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or

   (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

   Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:

   (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;

   (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;

   (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and

   (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]

10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]

12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]

13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION K: TITLE V Administration

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]

15. Nothing in this permit or in any permit shield can alter or affect:

    (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;

    (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;

    (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;

    (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;

    (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and

    (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]

16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION K: TITLE V Administration

EMERGENCY PROVISIONS

17. An emergency[1] constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:

    (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:

        (1) An emergency occurred and the operator can identify the cause(s) of the emergency;

        (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;

        (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,

        (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and

    (B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]

18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

---

1 "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION K: TITLE V Administration

RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:

    (A) The date, place as defined in the Title V permit, and time of sampling or measurements;

    (B) The date(s) analyses were performed;

    (C) The company or entity that performed the analyses;

    (D) The analytical techniques or methods used;

    (E) The results of such analyses; and

    (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]

20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]

21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:

    (A) Breakdowns shall be reported as required by Rule 430 – Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION K: TITLE V Administration

(B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.

(C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.

(D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]

23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]

24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:

(A) Identification of each permit term or condition that is the basis of the certification;

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION K: TITLE V Administration

(B) The compliance status during the reporting period;

(C) Whether compliance was continuous or intermittent;

(D) The method(s) used to determine compliance over the reporting period and currently, and

(E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn: Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 109	5-2-2003	Federally enforceable
RULE 1107	1-6-2006	Non federally enforceable
RULE 1107	11-9-2001	Federally enforceable
RULE 1113	11-8-1996	Federally enforceable
RULE 1113	6-3-2011	Non federally enforceable
RULE 1136	6-14-1996	Federally enforceable
RULE 1141.1	11-17-2000	Federally enforceable
RULE 1143	12-3-2010	Non federally enforceable
RULE 1155	12-4-2009	Non federally enforceable
RULE 1171	11-7-2003	Federally enforceable
RULE 1171	5-1-2009	Non federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1401	3-4-2005	Non federally enforceable
RULE 1401	3-7-2008	Non federally enforceable
RULE 1401	5-2-2003	Non federally enforceable
RULE 1401	9-10-2010	Non federally enforceable
RULE 204	10-8-1993	Federally enforceable
RULE 217	1-5-1990	Federally enforceable
RULE 219	6-1-2007	Non federally enforceable
RULE 219	9-4-1981	Federally enforceable

FACILITY PERMIT TO OPERATE
DEFT INC

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 3002	11-14-1997	Federally enforceable
RULE 3002	11-5-2010	Non federally enforceable
RULE 3003	11-14-1997	Federally enforceable
RULE 3003	11-5-2010	Non federally enforceable
RULE 3004	12-12-1997	Federally enforceable
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3005	11-5-2010	Non federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	5-6-2011	Non federally enforceable
RULE 401	11-9-2001	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 405	2-7-1986	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 442	12-15-2000	Federally enforceable
RULE 481	1-11-2002	Federally enforceable
RULE 701	6-13-1997	Federally enforceable
40CFR 63 Subpart HHHHH	10-4-2006	Federally enforceable

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN PERMIT PURSUANT TO RULE 219

NONE

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 01-06-2006]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 01-06-2006]

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates, cont.								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
Extreme Performance	420	420	3.5	3.5	360	360	3.0	3.0
Prefabricated Architectural One-Component	420	275	3.5	2.3	275	275	2.3	2.3
Prefabricated Architectural Multi-Component	420	340	3.5	2.8	275	275	2.3	2.3
Touch Up	420	420	3.5	3.5	360	360	3.0	3.0
Repair	420	420	3.5	3.5	360	360	3.0	3.0
Silicone Release	420	420	3.5	3.5	420	420	3.5	3.5
High-Performance Architectural	420	420	3.5	3.5	420	420	3.5	3.5
Camouflage	420	420	3.5	3.5	420	420	3.5	3.5
Vacuum-Metalizing	420	420	3.5	3.5	420	420	3.5	3.5
Mold-Seal	420	420	3.5	3.5	420	420	3.5	3.5
High-Temperature	420	420	3.5	3.5	420	420	3.5	3.5
Electric-Insulating Varnish	420	420	3.5	3.5	420	420	3.5	3.5
Pan Backing	420	420	3.5	3.5	420	420	3.5	3.5
Pretreatment Coatings	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 01-06-2006]

(2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 11-09-2001]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 11-09-2001]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 11-09-2001]

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates, cont.								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
Extreme Performance	420	420	3.5	3.5	360	360	3.0	3.0
Prefabricated Architectural One-Component	420	275	3.5	2.3	275	275	2.3	2.3
Prefabricated Architectural Multi-Component	420	340	3.5	2.8	275	275	2.3	2.3
Touch Up	420	420	3.5	3.5	360	360	3.0	3.0
Repair	420	420	3.5	3.5	360	360	3.0	3.0
Silicone Release	420	420	3.5	3.5	420	420	3.5	3.5
High-Performance Architectural	420	420	3.5	3.5	420	420	3.5	3.5
Camouflage	420	420	3.5	3.5	420	420	3.5	3.5
Vacuum-Metalizing	420	420	3.5	3.5	420	420	3.5	3.5
Mold-Seal	420	420	3.5	3.5	420	420	3.5	3.5
High-Temperature	420	420	3.5	3.5	420	420	3.5	3.5
Electric-Insulating Varnish	420	420	3.5	3.5	420	420	3.5	3.5
Pan Backing	420	420	3.5	3.5	420	420	3.5	3.5
Pretreatment Coatings	420	420	3.5	3.5	420	420	3.5	3.5

(2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 11-08-1996]

(1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.

(2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

TABLE OF STANDARDS

VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water And Less Exempt Compounds

COATING	Limit*	Effective Date of Adoption	Effective 1/1/1998	Effective 1/1/1999	Effective 7/1/2001	Effective 1/1/2005	Effective 7/1/2008
Bond Breakers	350						
Clear Wood Finishes							
Varnish	350						
Sanding Sealers	350						
Lacquer	680		550			275	
Concrete-Curing Compounds	350						
Dry-Fog Coatings	400						
Fire-proofing Exterior Coatings	350	450		350			
Fire-Retardant Coatings							
Clear	650						
Pigmented	350						
Flats	250				100		50
Graphic Arts (Sign) Coatings	500						

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 11-08-1996]

Industrial Maintenance Primers and Topcoats							
Alkyds	420						
Catalyzed Epoxy	420						
Bituminous Coatings	420						
Materials							
Inorganic Polymers	420						
Vinyl Chloride Polymers	420						
Chlorinated Rubber	420						
Acrylic Polymers	420						
Urethane Polymers	420						
Silicones	420						
Unique Vehicles	420						
Japans/Faux Finishing Coatings	350	700		350			
Magnesite Cement Coatings	600			450			
Mastic Coatings	300						
Metallic Pigmented Coatings	500						
Multi-Color Coatings	420		250				
Pigmented Lacquer	680		550			275	
Pre-Treatment Wash Primers	780						
Primers, Sealers, and Undercoaters	350						
Quick-Dry Enamels	400						
Roof Coatings	300						
Shellac							
Clear	730						
Pigmented	550						
Stains	350						
Swimming Pool Coatings							
Repair	650						
Other	340						
Traffic Coatings	250		150				
Waterproofing Sealers	400						
Wood Preservatives							
Below-Ground	350						
Other	350						

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

TABLE OF STANDARDS (cont.)

VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 06-03-2011]

(1) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6) of Rule 1113, no person shall supply, sell, offer for sale, market, manufacture, blend, repackage, apply, store at a worksite, or solicit the application of any architectural coating within the District:

(A) That is listed in the Table of Standards 1 and contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified; or

(B) That is not listed in the Table of Standards 1, and contains VOC (excluding any colorant added to tint bases) in excess of 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, until January 1, 2014, at which time the limit drops to 50 grams of VOC per liter of coating, less water, less exempt compounds (0.42 pounds per gallon).

(2) No person within the District shall add colorant at the point of sale that is listed in the Table of Standards 2 and contains VOC in excess of the corresponding VOC limit specified in the Table of Standards 2, after the effective date specified.

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 06-03-2011]

TABLE OF STANDARDS 1
VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water and Less Exempt Compounds

COATING CATEGORY	Ceiling Limit[1]	Current Limit[2]	Effective Date		
			7/1/08	1/1/12	1/1/14
Bond Breakers		350			
Clear Wood Finishes		275			
Varnish	350	275			
Sanding Sealers	350	275			
Lacquer		275			
Concrete-Curing Compounds		100			
Concrete-Curing Compounds For Roadways and Bridges[3]		350			
Concrete Surface Retarder		250			50
Driveway Sealer		100		50	
Dry-Fog Coatings		150			50
Faux Finishing Coatings					
Clear Topcoat		350		200	
Decorative Coatings		350			100
Glazes		350			
Japan		350			
Trowel Applied Coatings		350		150	50
Fire-Proofing Coatings		350			150
Flats	250	50	50		
Floor Coatings	100	50			
Form Release Compound		250			100
Graphic Arts (Sign) Coatings		500			150
Industrial Maintenance (IM) Coatings	420	100			
High Temperature IM Coatings		420			
Non-Sacrificial Anti-Graffiti Coatings		100			
Zinc-Rich IM Primers	340	100			
Magnesite Cement Coatings		450			
Mastic Coatings		300			100
Metallic Pigmented Coatings	500	500			150
Multi-Color Coatings		250			
Nonflat Coatings	150	50			
Pre-Treatment Wash Primers		420			
Primers, Sealers, and Undercoaters	200	100			
Reactive Penetrating Sealers		350			
Recycled Coatings		250			
Roof Coatings	250	50			
Roof Coatings, Aluminum		100			

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 06-03-2011]

Roof Primers, Bituminous	350	350			
Rust Preventative Coatings	400	100			
Stone Consolidant		450			
Sacrificial Anti-Graffiti Coatings		100		50	
Shellac					
Clear		730			
Pigmented		550			
Specialty Primers	350	100			
Stains		100			

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 06-03-2011]

COATING CATEGORY	Ceiling Limit[1]	Current Limit[2]	Effective Date		
			7/1/08	1/1/12	1/1/14
Stains, Interior	250	250			
Swimming Pool Coatings					
Repair		340			
Other		340			
Traffic Coatings		100			
Waterproofing Sealers	250	100			
Waterproofing Concrete/Masonry Sealers	400	100			
Wood Preservatives		350			

1. The specified ceiling limits are applicable to products sold under the Averaging Compliance Option.
2. The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.
3. Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

TABLE OF STANDARDS 1 (cont.)
VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

TABLE OF STANDARDS 2
VOC LIMITS FOR COLORANTS

Grams of VOC Per Liter of Colorant
Less Water and Less Exempt Compounds

COLORANT	Limit[4]
Architectural Coatings, excluding IM Coatings	50
Solvent-Based IM	600
Waterborne IM	50

4. Effective January 1, 2014.

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1136 06-14-1996]

Except as otherwise provided in Rule 1136

(a) The operator shall not apply any coating to a wood product which has a VOC content, including any VOC-containing material added to the original coating supplied by the manufacturer, which exceeds the applicable limit specified below:

(1)

VOC LIMITS
Grams Per Liter (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

COATING	Current Limit I	Current Limit II	On and After 7/1/2005
Clear Sealers	550 (4.6) [1.39]	680 (5.7) [3.36]	275 (2.3) [0.36]
Clear Topcoat	550 (4.6) [1.37]	275 (2.3) [0.35]	275 (2.3) [0.35]
Pigmented Primers, Sealers & Undercoats	550 (4.6) [1.06]	600 (5.0) [1.08]	275 (2.3) [0.21]
Pigmented Topcoats	550 (4.6) [1.10]	275 (2.3) [0.25]	275 (2.3) [0.25]

The operator shall use coatings on a wood product that comply with either all VOC limits in column I or all VOC limits in column II. The operator that applies a primer, sealer or undercoat, but not a topcoat, to a wood product, shall be subject to column I for that wood product.

(2) Notwithstanding the requirements of clause (a)(1), an operator that applies a topcoat and a primer, sealer or undercoat to a shutter may, until July 1, 2005, choose to comply with the VOC limits specified below for that shutter:

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1136 06-14-1996]

VOC LIMITS

Grams Per Liter, (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

COATING	
Clear Sealers	275 (2.3) [0.36]
Clear Topcoat	680 (5.7) [2.99]
Pigmented Primers, Sealers & Undercoats	275 (2.3) [0.33]
Pigmented Topcoats	600 (5.0) [1.38]

(3)

VOC LIMITS

Grams Per Liter, (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

COATING	Current Limit	On and After 7/1/2005
Barrier Coat - Plastic Components	760 (6.3) [3.9]	275 (2.3) [0.28]
Composite Wood Edge Filler	550 (4.6) [1.15]	275 (2.3) [0.31]
Extreme Performance Coatings	420 (3.5) [0.51]	275 (2.3) [0.33]
Fillers	500 (4.2) [0.66]	275 (2.3) [0.18]
High-Solid Stains	550 (4.6) [1.23]	350 (2.9) [0.42]
Inks	500 (4.2) [0.96]	500 (4.2) [0.96]
Mold-Seal Coatings	750 (6.3) [4.2]	750 (6.3) [4.2]
Multi-Colored Coatings	685 (5.7) [2.6]	275 (2.3) [0.33]

VOC LIMITS

Grams Per Liter (lb/gal) of Material

COATING	Current Limit	On and After 7/1/2005
Low-Solids Barrier Coat - Plastic Components	760 (6.3)	120 (1.0)
Low-Solid Stains, Toners, and Washcoats	480 (4.0)	120 (1.0)

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1136 06-14-1996]

Any coating subject to this rule that meets any of the three VOC limit formats (grams per liter, lb/gal, or lbs VOC/lb of solids) is in compliance with this subparagraph.

(4) The VOC limit for japan coatings is 700 grams per liter of coatings, less water and exempt compounds, as applied.

(b) A person shall not use a stripper on wood products unless:

(1) it contains less than 350 grams of VOC per liter of material; or

(2) the VOC composite vapor pressure is 2 mm Hg (0.04 psia) or less at 20°C (68°F).

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1143 12-03-2010]

Except as otherwise provided for in Rule 1143

No person shall supply, sell, offer for sale, manufacture, blend, package or repackage any consumer paint thinner or multi-purpose solvent for use in the District unless the consumer paint thinner or multi-purpose solvent complies with the applicable VOC content limits set forth in the table below:

CATEGORY	EFFECTIVE 1/1/2010	EFFECTIVE 1/1/2011
	VOC Content g/L or (lb/Gal)	VOC Content g/L or (lb/Gal)
Consumer Paint Thinner	300 (2.50)	25 (0.21)
Consumer Multi-Purpose Solvent	300 (2.50)	25 (0.21)

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	500 (4.2)
(iii) Medical Devices & Pharmaceuticals	800 (6.7)
(B) Repair and Maintenance Cleaning	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals	
(A) Tools, Equipment, & Machinery	800 (6.7)
(B) General Work Surfaces	600 (5.0)
(C) Cleaning of Coatings or Adhesives Application Equipment	550 (4.6)
(D) Cleaning of Ink Application Equipment	
(i) General	25 (0.21)
(ii) Flexographic Printing	25 (0.21)
(iii) Gravure Printing	
(A) Publication	750 (6.3)
(B) Packaging	25 (0.21)
(iv) Lithographic or Letter Press Printing	

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS VOC g/l (lb/gal)
(A) Roller Wash – Step 1	600 (5.0)
(B) Roller Wash-Step 2, Blanket Wash, & On-Press Components	800 (6.7)
(C) Removable Press Components	25 (0.21)
(v) Screen Printing	750 (6.3)
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	800 (6.7)
(vii) Specialty Flexographic Printing	600 (5.0)
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 05-01-2009]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY	**VOC g/l (lb/gal)**	**VOC g/l (lb/gal)**
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals	800 (6.7)	
(B) Repair and Maintenance Cleaning		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	**VOC g/l (lb/gal)**	**VOC g/l (lb/gal)**
(iii) Medical Devices & Pharmaceuticals		
(A) Tools, Equipment, & Machinery	800 (6.7)	
(B) General Work Surfaces	600 (5.0)	
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)	
(D) Cleaning of Ink Application Equipment		
(i) General	25 (0.21)	
(ii) Flexographic Printing	25 (0.21)	
(iii) Gravure Printing		
(A) Publication	100 (0.83)	
(B) Packaging	25 (0.21)	
(iv) Lithographic (Offset) or Letter Press Printing		
(A) Roller Wash, Blanket Wash, & On-Press Components	100 (0.83)	

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	**VOC g/l (lb/gal)**	**VOC g/l (lb/gal)**
(B) Removable Press Components	25 (0.21)	
(v) Screen Printing	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)	
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)	

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 404 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter"Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter"Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter"Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 405 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
100 or less	220 or less	0.450	0.99	9000	19840	5.308	11.7
150	331	0.585	1.29	10000	22050	5.440	12.0
200	441	0.703	1.55	12500	27560	5.732	12.6
250	551	0.804	1.77	15000	33070	5.982	13.2
300	661	0.897	1.98	17500	38580	6.202	13.7
350	772	0.983	2.17	20000	44090	6.399	14.1
400	882	1.063	2.34	25000	55120	6.743	14.9
450	992	1.138	2.51	30000	66140	7.037	15.5
500	1102	1.209	2.67	35000	77160	7.296	16.1
600	1323	1.340	2.95	40000	88180	7.527	16.6

FACILITY PERMIT TO OPERATE
DEFT INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 405 02-07-1986]

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
700	1543	1.461	3.22	45000	99210	7.738	17.1
800	1764	1.573	3.47	50000	110200	7.931	17.5
900	1984	1.678	3.70	60000	132300	8.277	18.2
1000	2205	1.777	3.92	70000	154300	8.582	18.9
1250	2756	2.003	4.42	80000	176400	8.854	19.5
1500	3307	2.206	4.86	90000	198400	9.102	20.1
1750	3858	2.392	5.27	100000	220500	9.329	20.6
2000	4409	2.563	5.65	125000	275600	9.830	21.7
2250	4960	2.723	6.00	150000	330700	10.26	22.6
2500	5512	2.874	6.34	175000	385800	10.64	23.5
2750	6063	3.016	6.65	200000	440900	10.97	24.2
3000	6614	3.151	6.95	225000	496000	11.28	24.9
3250	7165	3.280	7.23	250000	551200	11.56	25.5
3600	7716	3.404	7.50	275000	606300	11.82	26.1
4000	8818	3.637	8.02	300000	661400	12.07	26.6
4500	9921	3.855	8.50	325000	716500	12.30	27.1
5000	11020	4.059	8.95	350000	771600	12.51	27.6
6000	13230	4.434	9.78	400000	881800	12.91	28.5
7000	15430	4.775	10.5	450000	992100	13.27	29.3
8000	17640	5.089	11.2	500000 or more	1102000 or more	13.60	30.0