



NOV 17 2014

Mr. Ron Knoepfle
Barbosa Cabinets, Inc.
2020 E. Grant Line Rd
Tracy, CA 95304

**Re: Notice of Final Action - Title V Permit
District Facility # N-4065
Project # N-1141238**


Dear Mr. Knoepfle:

The District has issued the Final Title V Permit for Barbosa Cabinets, Inc. The preliminary decision for this project was made on September 25, 2014. No comments were received subsequent to the District preliminary decision. Enclosed are the Final Title V Permit and public notice to be published approximately three days from the date of this letter.

The public notice for issuance of the Final Title V Permit will be published approximately three days from the date of this letter.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,



Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Mike Tollstrup, CARB (w/enclosure) via email
cc: Gerardo C. Rios, EPA (w/enclosure) via email

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



Facility # N-4065
BARBOSA CABINETS, INC.
2020 E GRANT LINE RD
TRACY, CA 95304

Notice of Permit Issuance

The enclosed permit unit requirements authorize the operation of the equipment as described. These permit unit requirements supersede any and all previous permits for the specified equipment.* Please insert these documents into the Facility Permit to Operate, and post copies on or near the equipment as required by District Rule 2010.

Please contact any of our Small Business Assistance (SBA) staff at the numbers below if you have any questions:

Modesto:	(209) 557-6446
Fresno:	(559) 230-5888
Bakersfield:	(661) 392-5665

*Failure to comply with the permit unit requirements may result in enforcement action.

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



Permit to Operate

FACILITY: N-4065

EXPIRATION DATE: 02/28/2019

LEGAL OWNER OR OPERATOR:
MAILING ADDRESS:

BARBOSA CABINETS, INC.
2020 E GRANT LINE RD
TRACY, CA 95304

FACILITY LOCATION:

2020 E GRANT LINE RD
TRACY, CA 95304

FACILITY DESCRIPTION:

MANUFACTURER OF WOODEN CABINETS

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Seyed Sadredin
Executive Director / APCO

Arnaud Marjollet
Director of Permit Services

San Joaquin Valley Air Pollution Control District

FACILITY: N-4065-0-1

EXPIRATION DATE: 02/28/2019

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.9.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: BARBOSA CABINETS, INC.

Location: 2020 E GRANT LINE RD, TRACY, CA 95304

N-4065-0-1 Nov 10 2014 8 42AM - AIVABEU

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
42. Facility-wide VOC emissions shall not exceed 40,000 pounds during any rolling 12-month period. [District Rule 2201] Federally Enforceable Through Title V Permit
43. The combined facility-wide second, third and fourth calendar quarter VOC emissions shall not exceed 32,666 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
44. The facility-wide PM10 emissions shall not exceed 29,200 pounds during any rolling 12-month period. [District Rule 2201] Federally Enforceable Through Title V Permit
45. A record of the facility-wide VOC emissions, on a rolling 12-month period basis, shall be kept. The record shall be updated at least monthly. [District Rule 2201] Federally Enforceable Through Title V Permit
46. Records of the cumulative facility-wide second, third and fourth calendar quarter VOC emissions shall be kept. The records shall be updated at least weekly. [District Rule 2201] Federally Enforceable Through Title V Permit
47. A record of the facility-wide PM10 emissions, on a rolling 12-month period basis, shall be kept. The record shall be updated at least monthly. The PM10 emission contribution from permit units N-4065-5 and N-4065-6 shall each be calculated utilizing the following equation: $[(90,000 \text{ dscfm}) \times (0.003 \text{ gr/dscf}) \times (60 \text{ min/hr}) \times (1 \text{ lb/7000 gr}) \times (\text{hours of operation of the LMC-594-LP baghouses})] + [(4,800 \text{ dscfm}) \times (0.004 \text{ gr/dscf}) \times (60 \text{ min/hr}) \times (1 \text{ lb/7000 gr}) \times (\text{hours of operation of the LMC 360 IRWD 915 RBO 36-15 baghouse})]$. [District Rule 2201] Federally Enforceable Through Title V Permit
48. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
49. On November 10, 2014, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4065-5-3

EXPIRATION DATE: 02/28/2019

EQUIPMENT DESCRIPTION:

WOODWORKING OPERATION CONSISTING OF 19 SAWS, 2 BORING MACHINES, 1 DOWEL INSERTER, 3 HINGE INSERTERS, 5 SANDERS, 2 TENONERS, 1 PLANER, 3 ROUTERS, 13 SHAPERS, 3 MOLDERS AND 3 SHAPE AND SAND MACHINES ALL SERVED BY AN LMC MODEL 594-LP-12 BAGHOUSE. WHEN OPERATING ALONE, THE COUNTERTOP MANUFACTURING PORTION OF THE EQUIPMENT WILL BE SERVED BY THE LMC 594-LP-12 BAGHOUSE OR AN LMC 360 IRWD 915 RBO 36-15 BAGHOUSE. THE COUNTERTOP MANUFACTURING OPERATION CONSISTS OF 8 OF THE ABOVE LISTED SAWS AND TWO OF THE ABOVE LISTED SHAPERS

PERMIT UNIT REQUIREMENTS

1. Visible emissions from the baghouses serving the woodworking equipment shall not equal or exceed 5% opacity for a period or periods aggregating more than three minutes in one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The baghouses serving this permit unit shall not operate simultaneously. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The exhaust flow rate of the LMC 594-LP-12 baghouse shall not exceed 90,000 dscfm. [District Rule 2202] Federally Enforceable Through Title V Permit
4. The PM10 emissions from the LMC 594-LP-12 baghouse shall not exceed 0.003 gr/dscf of exhaust flow. [District Rules 2201 and 4201] Federally Enforceable Through Title V Permit
5. The exhaust flow rate of the LMC 360 IRWD 915 RBO 36-15 baghouse shall not exceed 4,800 dscfm. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The PM10 emissions from the LMC 360 IRWD 915 RBO 36-15 baghouse shall not exceed 0.004 gr/dscf of exhaust flow. [District Rules 2201 and 4201] Federally Enforceable Through Title V Permit
7. The LMC 594-LP-12 baghouse shall be equipped with a pressure differential gauge to indicate the pressure drop across the bags. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
8. The LMC 594-LP-12 baghouse shall operate at all times with a minimum differential pressure of 2 inches of water column and a maximum differential pressure of 4 inches of water column. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
9. The differential operating pressure shall be monitored and recorded on each day that the baghouse operates. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
10. Replacement bags numbering at least 10% of the total number of bags in the largest baghouse using each type of bag shall be maintained on the premises. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The baghouses shall be maintained and operated according to manufacturer's specifications. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The baghouse cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

13. Material removed from the dust collector(s) shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of all maintenance of the baghouse, including all change outs of filter media, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the number of hours of operation of each baghouse, on a rolling 12-month basis, shall be kept. The records shall be kept separately for each baghouse and shall be updated at least monthly. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E=3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E=17.31 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit
18. Visible emissions from the LMC 594-LP-12 baghouse shall be evaluated using EPA Method 22 for a period of at least 6 minutes at least once during each day that this baghouse is operated. Records of visible emissions evaluations shall be maintained. [40 CFR Part 64] Federally Enforceable Through Title V Permit
19. If visible emissions from the LMC 594-LP-12 baghouse are observed, the permittee shall investigate the cause of visible emissions and take corrective action to minimize emissions and prevent recurrence of emissions as expeditiously as practicable. [40 CFR Part 64] Federally Enforceable Through Title V Permit
20. During each day of operation, the permittee shall record the pressure drop of the LMC 594-LP-12 baghouse, and compare the readings to the acceptable range. Upon detecting any excursion from the acceptable pressure drop range, the permittee shall investigate the excursion and take corrective action to minimize excessive emissions and prevent recurrence of the excursion as expeditiously as practicable. [40 CFR Part 64] Federally Enforceable Through Title V Permit
21. The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR part 64.7. [40 CFR Part 64] Federally Enforceable Through Title V Permit
22. The permittee shall comply with the recordkeeping and reporting requirements of 40 CFR part 64.9. [40 CFR Part 64] Federally Enforceable Through Title V Permit
23. If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR part 64.8. [40 CFR Part 64] Federally Enforceable Through Title V Permit
24. Within 6 months of this initial Title V permit being issued, the permittee shall apply for, and fully implement, an Authority to Construct to reduce the pre-control potential to emit for PM10 emissions from the countertop manufacturing operation when controlled by the LMC 360 IRWD 915 RBO 36-15 baghouse to a level not greater than the major source threshold; or submit a Compliance Assurance Monitoring plan for PM10 emissions from the countertop manufacturing operation when controlled by the LMC 360 IRWD 915 RBO 36-15 baghouse pursuant to the requirements of 40 CFR Part 64. [40 CFR Part 64] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4065-6-3

EXPIRATION DATE: 02/28/2019

EQUIPMENT DESCRIPTION:

WOOD WORKING OPERATION CONSISTING OF 39 SAWS, 4 BORING MACHINES, 2 DOWEL INSERTERS, 5 HINGE INSERTERS, 13 SANDERS, 1 PLANER, 1 PLANER/SANDER, 3 DRILLS, 2 DRILL ROUTERS, 1 SHAPER, 1 SHAPER/SANDER, 2 JOINTERS AND 3 EDGE BANDERS AND FILTER CLEANING BOOTH ALL SERVED BY AN LMC MODEL 594-LP-12 BAGHOUSE

PERMIT UNIT REQUIREMENTS

1. Visible emissions from the baghouses serving the woodworking equipment shall not equal or exceed 5% opacity for a period or periods aggregating more than three minutes in one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The exhaust flow rate of the baghouse shall not exceed 90,000 dscfm. [District Rule 2202] Federally Enforceable Through Title V Permit
3. The PM10 emissions from the baghouse shall not exceed 0.003 gr/dscf of exhaust flow. [District Rules 2201 and 4201] Federally Enforceable Through Title V Permit
4. The baghouse shall be equipped with a pressure differential gauge to indicate the pressure drop across the bags. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
5. The baghouse shall operate at all times with a minimum differential pressure of 2 inches of water column and a maximum differential pressure of 4 inches of water column. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
6. The differential operating pressure shall be monitored and recorded on each day that the baghouse operates. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
7. Replacement bags numbering at least 10% of the total number of bags in the largest baghouse using each type of bag shall be maintained on the premises. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The baghouse shall be maintained and operated according to manufacturer's specifications. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The baghouse cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Material removed from the dust collector(s) shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Records of all maintenance of the baghouse, including all change outs of filter media, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the number of hours of operation of each baghouse, on a rolling 12-month basis, shall be kept. The records shall be kept separately for each baghouse and shall be updated at least monthly. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E=3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E=17.31 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit
15. Visible emissions from the baghouse shall be evaluated using EPA Method 22 for a period of at least 6 minutes at least once during each day that the woodworking equipment is are operated. Records of visible emissions evaluations shall be maintained. [40 CFR Part 64] Federally Enforceable Through Title V Permit
16. If visible emissions from the baghouse are observed, the permittee shall investigate the cause of visible emissions and take corrective action to minimize emissions and prevent recurrence of emissions as expeditiously as practicable. [40 CFR Part 64] Federally Enforceable Through Title V Permit
17. During each day of operation, the permittee shall record the pressure drops of the baghouse and compare the readings to the acceptable range. Upon detecting any excursion from the acceptable pressure drop range, the permittee shall investigate the excursion and take corrective action to minimize excessive emissions and prevent recurrence of the excursion as expeditiously as practicable. [40 CFR Part 64] Federally Enforceable Through Title V Permit
18. The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR part 64.7. [40 CFR Part 64] Federally Enforceable Through Title V Permit
19. The permittee shall comply with the recordkeeping and reporting requirements of 40 CFR part 64.9. [40 CFR Part 64] Federally Enforceable Through Title V Permit
20. If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR part 64.8. [40 CFR Part 64] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4065-7-1

EXPIRATION DATE: 02/28/2019

EQUIPMENT DESCRIPTION:

WOOD COATING OPERATION SERVED BY A SPRAY SYSTEMS MODEL I-18107 OPEN FACE BOOTH

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The VOC emissions shall not exceed 99.0 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The PM10 emissions shall not exceed 6.6 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A record of the daily VOC emissions, in pounds, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
5. A record of the daily number of pounds of PM10 emissions, due to coating usage, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
7. VOC content of materials for wood products, as applied, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
8. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
9. Only HVLP, electrostatic, brush, dip, flow, or roll coating application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rule 4606] Federally Enforceable Through Title V Permit
10. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rule 4606] Federally Enforceable Through Title V Permit
11. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning: 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rule 4606] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: BARBOSA CABINETS, INC.

Location: 2020 E GRANT LINE RD, TRACY, CA 95304

N-4065-7-1: Nov 10 2014 8 23AM - AYABEIJ

12. An operator shall store or dispose of fresh or spent solvents, waste solvent cleaning material such as cloth, paper, etc, coating, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4606] Federally Enforceable Through Title V Permit
13. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rule 4606] Federally Enforceable Through Title V Permit
15. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4065-8-1

EXPIRATION DATE: 02/28/2019

EQUIPMENT DESCRIPTION:

WOOD COATING OPERATION SERVED BY A SPRAY SYSTEMS MODEL I-18107 OPEN FACE BOOTH

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The VOC emissions shall not exceed 99.0 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The PM10 emissions shall not exceed 6.6 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A record of the daily VOC emissions, in pounds, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
5. A record of the daily number of pounds of PM10 emissions, due to coating usage, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
7. VOC content of materials for wood products, as applied, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
8. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
9. Only HVLP, electrostatic, brush, dip, flow, or roll coating application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rule 4606] Federally Enforceable Through Title V Permit
10. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rule 4606] Federally Enforceable Through Title V Permit
11. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning: 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rule 4606] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: BARBOSA CABINETS, INC.

Location: 2020 E GRANT LINE RD, TRACY, CA 95304

N-4065-8-1, Nov 10 2014 8:23AM - AIYABELJ

12. An operator shall store or dispose of fresh or spent solvents, waste solvent cleaning material such as cloth, paper, etc, coating, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4606] Federally Enforceable Through Title V Permit
13. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rule 4606] Federally Enforceable Through Title V Permit
15. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4065-9-1

EXPIRATION DATE: 02/28/2019

EQUIPMENT DESCRIPTION:

WOOD COATING OPERATION SERVED BY A SPRAY SYSTEMS MODEL I-18107 OPEN FACE BOOTH

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The VOC emissions shall not exceed 99.0 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The PM10 emissions shall not exceed 6.6 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A record of the daily VOC emissions, in pounds, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
5. A record of the daily number of pounds of PM10 emissions, due to coating usage, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
7. VOC content of materials for wood products, as applied, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
8. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
9. Only HVLP, electrostatic, brush, dip, flow, or roll coating application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rule 4606] Federally Enforceable Through Title V Permit
10. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rule 4606] Federally Enforceable Through Title V Permit
11. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning: 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rule 4606] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. An operator shall store or dispose of fresh or spent solvents, waste solvent cleaning material such as cloth, paper, etc, coating, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4606] Federally Enforceable Through Title V Permit
13. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rule 4606] Federally Enforceable Through Title V Permit
15. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: BARBOSA CABINETS, INC.

Location: 2020 E GRANT LINE RD, TRACY, CA 95304

N-4065-9-1: Nov 10 2014 8:23AM - AJYABEL

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4065-10-1

EXPIRATION DATE: 02/28/2019

EQUIPMENT DESCRIPTION:

WOOD COATING OPERATION SERVED BY A SPRAY SYSTEMS MODEL I-18107 OPEN FACE BOOTH

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The VOC emissions shall not exceed 99.0 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The PM10 emissions shall not exceed 6.6 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A record of the daily VOC emissions, in pounds, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
5. A record of the daily number of pounds of PM10 emissions, due to coating usage, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
7. VOC content of materials for wood products, as applied, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
8. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
9. Only HVLP, electrostatic, brush, dip, flow, or roll coating application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rule 4606] Federally Enforceable Through Title V Permit
10. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rule 4606] Federally Enforceable Through Title V Permit
11. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning: 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rule 4606] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. An operator shall store or dispose of fresh or spent solvents, waste solvent cleaning material such as cloth, paper, etc, coating, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4606] Federally Enforceable Through Title V Permit
13. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rule 4606] Federally Enforceable Through Title V Permit
15. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4065-11-1

EXPIRATION DATE: 02/28/2019

EQUIPMENT DESCRIPTION:

WOOD COATING OPERATION SERVED BY A SPRAY SYSTEMS MODEL I-1287 OPEN FACE BOOTH

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The VOC emissions shall not exceed 99.0 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The PM10 emissions shall not exceed 6.6 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A record of the daily VOC emissions, in pounds, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
5. A record of the daily number of pounds of PM10 emissions, due to coating usage, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
7. VOC content of materials for wood products, as applied, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
8. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
9. Only HVLP, electrostatic, brush, dip, flow, or roll coating application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rule 4606] Federally Enforceable Through Title V Permit
10. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rule 4606] Federally Enforceable Through Title V Permit
11. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning: 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rule 4606] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

12. An operator shall store or dispose of fresh or spent solvents, waste solvent cleaning material such as cloth, paper, etc, coating, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4606] Federally Enforceable Through Title V Permit
13. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rule 4606] Federally Enforceable Through Title V Permit
15. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4065-12-1

EXPIRATION DATE: 02/28/2019

EQUIPMENT DESCRIPTION:

RHODES MANUFACTURING MODEL I-22810C CONVEYORIZED WOOD COATING AND SANDING SYSTEM. THE SYSTEM INCLUDES THREE COATING BOOTHS, ONE SANDING BOOTH SERVED BY A TORIT ECB DUST COLLECTOR AND FOUR PERMIT EXEMPT OVEN/CURING TUNNELS

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Visible emissions from the baghouse serving the sanding booth shall not equal or exceed 5% opacity for a period or periods aggregating more than three minutes in one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The VOC emissions shall not exceed 297.0 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The PM10 emissions, due to coating application, shall not exceed 19.8 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The PM10 emissions from the sanding booth shall not exceed 0.0093 lb/lb of sawdust collected by the dust collector. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The quantity of sawdust collected by the dust collector shall not exceed 100 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The baghouse shall be equipped with a pressure differential gauge to indicate the pressure drop across the bags. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Replacement bags numbering at least 10% of the total number of bags in the largest baghouse using each type of bag shall be maintained on the premises. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Material removed from dust collector(s) shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The baghouse cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
11. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
12. VOC content of materials for wood products, as applied, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Only HVLP, electrostatic, brush, dip, flow, or roll coating application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rule 4606] Federally Enforceable Through Title V Permit
15. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rule 4606] Federally Enforceable Through Title V Permit
16. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning: 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rule 4606] Federally Enforceable Through Title V Permit
17. An operator shall store or dispose of fresh or spent solvents, waste solvent cleaning material such as cloth, paper, etc, coating, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4606] Federally Enforceable Through Title V Permit
18. A record of the daily VOC emissions, in pounds, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
19. A record of the daily number of pounds of PM10 emissions, due to coating usage, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
20. A record of the daily quantity of sawdust collected by the dust collector, in pounds, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
21. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal; and the type of cleaning activity for which each solvent is used. [District Rule 4606] Federally Enforceable Through Title V Permit
22. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rule 4606] Federally Enforceable Through Title V Permit
23. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4606] Federally Enforceable Through Title V Permit
24. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E=3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E=17.31 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4065-13-1

EXPIRATION DATE: 02/28/2019

EQUIPMENT DESCRIPTION:

CEFLA FALCIONI PROFIPPLUS 39 MOLDING COATING UNIT

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The VOC emissions shall not exceed 99.0 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The PM10 emissions shall not exceed 6.6 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
5. VOC content of materials for wood products, as applied, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
6. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
7. Only HVLP, electrostatic, brush, dip, flow, or roll coating application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rule 4606] Federally Enforceable Through Title V Permit
8. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rule 4606] Federally Enforceable Through Title V Permit
9. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning: 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rule 4606] Federally Enforceable Through Title V Permit
10. An operator shall store or dispose of fresh or spent solvents, waste solvent cleaning material such as cloth, paper, etc, coating, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4606] Federally Enforceable Through Title V Permit
11. A record of the daily VOC emissions, in pounds, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: BARBOSA CABINETS, INC.

Location: 2020 E GRANT LINE RD, TRACY, CA 95304

N-4065-13-1: Nov 10 2014 8:24AM - AIYABEIJ

12. A record of the daily number of pounds of PM10 emissions, due to coating usage, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rule 4606] Federally Enforceable Through Title V Permit
15. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4065-14-1

EXPIRATION DATE: 02/28/2019

EQUIPMENT DESCRIPTION:

SANDING BOOTH SERVED BY A TORIT ECB DUST COLLECTOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Visible emissions from baghouse serving the sanding booth shall not equal or exceed 5% opacity for a period or periods aggregating more than three minutes in one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The PM10 emissions from the sanding booth shall not exceed 0.0093 lb/lb of sawdust collected by the dust collector. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The quantity of sawdust collected by the dust collector shall not exceed 100 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The baghouse shall be equipped with a pressure differential gauge to indicate the pressure drop across the bags. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Replacement bags numbering at least 10% of the total number of bags in the largest baghouse using each type of bag shall be maintained on the premises. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Material removed from dust collector(s) shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The baghouse cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
9. A record of the daily quantity of sawdust collected by the dust collector, in pounds, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
11. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E=3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E=17.31 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4065-15-1

EXPIRATION DATE: 02/28/2019

EQUIPMENT DESCRIPTION:

SANDING BOOTH SERVED BY A TORIT ECB DUST COLLECTOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Visible emissions from baghouse serving the sanding booth shall not equal or exceed 5% opacity for a period or periods aggregating more than three minutes in one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The PM10 emissions from the sanding booth shall not exceed 0.0093 lb/lb of sawdust collected by the dust collector. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The quantity of sawdust collected by the dust collector shall not exceed 100 pounds during any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The baghouse shall be equipped with a pressure differential gauge to indicate the pressure drop across the bags. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Replacement bags numbering at least 10% of the total number of bags in the largest baghouse using each type of bag shall be maintained on the premises. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Material removed from dust collector(s) shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The baghouse cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
9. A record of the daily quantity of sawdust collected by the dust collector, in pounds, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
11. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E=3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E=17.31 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4065-16-1

EXPIRATION DATE: 02/28/2019

EQUIPMENT DESCRIPTION:

325 BHP PERKINS MODEL 1306-E87TA DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with either a positive crankcase ventilation (PCV) system that recirculates crankcase emissions into the air intake system for combustion, or a crankcase emissions control device of at least 90% control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed any of the following limits: 4.1 g-NOx/bhp-hr, 0.45 g-CO/bhp-hr, or 0.15 g-VOC/bhp-hr. [District Rule 2201, 13 CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed 0.067 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102, 13 CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
10. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
11. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
13. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
15. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
16. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
17. The permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
18. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
19. The permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions, including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
20. The permittee must maintain records of all required maintenance performed on the air pollution control and monitoring equipment. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
21. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.