SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT
21865 Copley Drive, Diamond Bar, CA 91765

Title Page	
Facility ID:	149235
Revision #:	5
Date:	September 23, 2011

FACILITY PERMIT TO OPERATE

AMF ANAHEIM LLC
2100 E ORANGEWOOD AVE
ANAHEIM, CA 92806

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By Ed Moreno for
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	1	09/23/2011
B	RECLAIM Annual Emission Allocation	1	09/23/2011
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	5	09/23/2011
E	Administrative Conditions	1	09/23/2011
F	RECLAIM Monitoring and Source Testing Requirements	1	09/23/2011
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	1	09/23/2011
H	Permit To Construct and Temporary Permit to Operate	1	09/23/2011
I	Compliance Plans & Schedules	1	09/23/2011
J	Air Toxics	1	09/23/2011
K	Title V Administration	1	09/23/2011
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	1	09/23/2011
B	Rule Emission Limits	1	09/23/2011

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION A: FACILITY INFORMATION

LEGAL OWNER &/OR OPERATOR:	AMF ANAHEIM LLC
LEGAL OPERATOR (if different than owner):	
EQUIPMENT LOCATION:	2100 E ORANGEWOOD AVE ANAHEIM, CA 92806
MAILING ADDRESS:	2100 E ORANGEWOOD AVE ANAHEIM, CA 92806-6193
RESPONSIBLE OFFICIAL:	BOB SICHER
TITLE:	SITE LEADER
TELEPHONE NUMBER:	(562) 596-4740
CONTACT PERSON:	LES WILLIS
TITLE:	FACILITIES MANAGER
TELEPHONE NUMBER:	(714) 363-9206
TITLE V PERMIT ISSUED:	September 23, 2011
TITLE V PERMIT EXPIRATION DATE:	September 22, 2016

TITLE V	RECLAIM	
YES	NOx:	NO
	SOx:	NO
	CYCLE:	0
	ZONE:	COASTAL

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

NOT APPLICABLE

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION C: FACILITY PLOT PLAN

(TO BE DEVELOPED)

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Facility Equipment and Requirements
(Section D)

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

Application number	Permit to Operate number	Equipment description
460284	F92037	OVEN, CURING
460287	F92038	OVEN, BAKING
460289	F92039	OVEN, DRYING
460290	F92044	OVEN, BAKING
460292	F92047	SPRAY BOOTH, PAINT AND SOLVENT
460293	F92048	SPRAY BOOTH, PAINT AND SOLVENT
460295	F92062	SPRAY BOOTH, PAINT AND SOLVENT
460296	F92064	SPRAY BOOTH,,PAINT AND SOLVENT
460297	F92065	SPRAY BOOTH, PAINT AND SOLVENT
460298	F92066	SPRAY BOOTH, PAINT AND SOLVENT
470374	F92067	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
470379	F92068	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
470380	F92069	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
470382	F92070	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
470383	F92071	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
470386	F92074	SPRAY BOOTH, PAINT AND SOLVENT
470387	F92075	SPRAY BOOTH, PAINT AND SOLVENT
470389	F92077	OVEN, POWDER COATING
470390	F92078	OVEN, POWDER COATING
470392	F92079	OVEN, POWDER COATING
470463	F92082	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
473461	F98725	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
473462	F98727	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
492529	G4020	AEROSOL CAN RECYCLING SYSTEM
501204	G7336	LASER CUTTER NO. 1
501206	G7337	DUST COLLECTOR NO. 1
501208	G7338	LASER CUTTER NO. 2
501210	G7339	DUST COLLECTOR NO. 2
501212	G7340	LASER CUTTER NO.3
501214	G7341	DUST COLLECTOR NO. 3
500473	G7349	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
500474	G7350	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
500475	G7351	WASHER
500476	G7352	OVEN, DRYING
500477	G7353	OVEN, CURING
503450	G7354	OVEN, CURING
503451	G7355	OVEN, CURING
518877		SPRAY BOOTH, PAINT AND SOLVENT
518878		SPRAY BOOTH, PAINT AND SOLVENT

NOTE: EQUIPMENT LISTED ABOVE THAT HAVE NO CORRESPONDING PERMITS TO OPERATE NUMBER ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

FACILITY WIDE CONDITION(S)

Condition(s):

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:

   A. AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGELMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
   B. OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (A) OF THIS CONDITION. [RULE 401]

2. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS DISCHARGED TO THE ATMOSPHERE FROM THIS FACILITY SHALL NOT EXCEED 372 POUNDS IN ANY ONE DAY. [RULE 1303(b)(2)-OFFSET]

3. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS FACILITY TO VERIFY THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER COATING SPRAYED SHALL BE USED.
   [RULE 109, 1303(b)(2)-OFFSET]

4. MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY AND SUBJECT TO DISTRICT RULES SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
   [RULE 109, 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]

5. TO MAINTAIN EXEMPTION FROM THE RULE 1132 REQUIREMENTS, THE TOTAL QUANTITY OF VOC EMISSIONS FROM THIS FACILITY SHALL NOT EXCEED 20 TONS (40,000 POUNDS) IN ANY EMISSION INVENTORY YEAR. THE EMISSION INVENTORY YEAR SHALL BE THE ANNUAL EMISSION REPORTING PERIOD BEGINNING FROM JULY 1 OF THE PREVIOUS YEAR THROUGH JUNE 30 OF A GIVEN YEAR. TO ENSURE COMPLIANCE WITH THE EMISSION CAP OF THIS CONDITION, THE FACILITY OPERATOR SHALL:

   A. COMPLY WITH RULE 109 (RECORDKEEPING FOR VOLATILE ORGANIC COMPOUND EMISSIONS).

   B. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH CALENDAR MONTH, TOTAL AND RECORD VOC EMISSIONS FOR THE CALENDAR MONTH FROM ALL EQUIPMENT AND OPERATIONS THAT ARE REQUIRED TO HAVE WRITTEN PERMITS OR ARE EXEMPT FROM WRITTTEN PERMITS PURSUANT TO RULE 219. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

C. BY JULY 15 OF EACH YEAR, TOTAL AND RECORD VOC EMISSIONS FROM THE FACILITY FOR THE EMISSION INVENTORY YEAR.

D. MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC-CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.

E. RETAIN ALL PURCHASE INVOICES FOR ALL VOC-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE VOC-CONTAINING MATERIAL REMOVED FROM THE FACILITY.

IF THE TOTAL FACILITY VOC EMISSIONS FROM THE MONTHLY RECORDS FOR THE EMISSION INVENTORY YEAR EXCEED THE EMISSION CAP OF THIS CONDITION, THE OPERATOR SHALL SUBMIT APPROPRIATE APPLICATIONS AND ACHIEVE COMPLIANCE PURSUANT TO THE REQUIREMENTS SPECIFIED IN RULE 1132.
[RULE 1132]

6. TO MAINTAIN EXMPTION FROM THE NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS (NESHAP) REQUIREMENTS, THE TOTAL QUANTITY OF HAZARDOUS AIR POLLUTANT (HAP) EMISSIONS FROM THIS FACILITY SHALL NOT EXCEED 10 TONS (20,000 POUNDS) OF A SINGLE HAP OR 25 TONS (50,000 POUNDS) OF A COMBINATION OF HAPS IN ANY TWELVE CALENDAR MONTH PERIOD.
[40CFR63 SUBPART MMMM]

7. TO ENSURE COMPLIANCE WITH THE HAP(S) EMISSION CAPS, THE FACILITY OPERATOR SHALL:
(A) IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT AND THIS FACILITY TO VERIFY THE MONTHLY HAP EMISSIONS IN POUNDS AND THE HAP CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS). THE RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT.
(B) WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, TOTAL AND RECORD HAP EMISSIONS FOR THE MONTH FROM ALL EQUIPMENT AND OPERATIONS THAT ARE REQUIRED TO HAVE WRITTEN PERMITS OR ARE EXEMPT FROM WRITTEN PERMITS PURSUANT TO RULE 219. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.
(C) MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED HAP-CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.
(D) RETAIN ALL PURCHASE INVOICES FOR ALL HAP-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE HAP-CONTAINING MATERIAL REMOVED FROM THE FACILITY, FOR FIVE YEARS.
[40CFR63 SUBPART MMMM]

8. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED AT THE PREMISES FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.
[RULE 109, 1303(a)(1)-BACT, 1303(b)(2)-OFFSET, 40CFR63 SUBPART MMMM]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92037
A/N 460284

Equipment Description:

OVEN, CURING, RAMCO, 8'-0" W. X 14'-0" D. X 8'-0" H., 800,000 BTU/HR NATURAL GAS FIRED, WITH A MAXON CYCLOMAX LOW NOx BURNER, A 1/2 H.P. COMBUSTION AIR FAN, A 1/2 H.P. EXHAUST FAN, AND A 7-1/2 RECIRCULATION FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE OXIDES OF NITROGEN (NOx) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NOx, BY VOLUME ON A DRY BASIS @ 3% O2, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

   IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

   A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
   B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO:	2000 PPMV, RULE 407
NOx:	30 PPMV, RULE 1303(a)(1)-BACT
NOx:	30 PPMV, RULE 1147
PM:	0.1 GR/SCF, RULE 409
PM:	RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92038
A/N 460287

Equipment Description

OVEN, BINKS, MODEL BWN 987, 11'-0" W. X 9'-0" L. X 10'-6" H., 350,000 BTU PER HOUR, NATURAL GAS FIRED WITH ONE 3 H.P. CIRCULATING FAN AND ONE 1/2 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 450 DEGREES FAHRENHEIT.
[RULE 401]

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Periodic Monitoring:

5. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE TEMPERATURE OF THE OVEN ONCE EVERY DAY.
[RULE 3004 (a)(4)]

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO:	2000 PPMV, RULE 407
PM:	0.1 GR/SCF, RULE 409
PM:	RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
NOx:	30 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92039
A/N 460289

Equipment Description:

OVEN, BINKS, MODEL BWN 987, 11'-0" W. X 9'-0" L. X 10'-6" H., 350,000 BTU PER HOUR, NATURAL GAS FIRED, WITH ONE 3 H.P. CIRCULATING FAN AND ONE 1/2 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 450 DEGREES FAHRENHEIT.
[RULE 401]

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Periodic Monitoring:

5. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE TEMPERATURE OF THE OVEN ONCE EVERY DAY.
[RULE 3004 (a)(4)]

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO:	2000 PPMV, RULE 407
PM:	0.1 GR/SCF, RULE 409
PM:	RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
NOx:	30 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92044
A/N 460290

Equipment Description:

OVEN, W. MILLER, MODEL NO. 4910, 18'-0" W. X 29'-0" L. X 10'-3" H., CONVEYORIZED, 1,600,000 BTU PER HOUR NATURAL GAS FIRED, WITH ONE 1/3 H.P. COMBUSTION AIR BLOWER, TWO 5 H.P. AIR KNIFE BLOWERS, ONE 10 H.P. CIRCULATING AIR FAN AND ONE 1/3 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 500 DEGREES FAHRENHEIT.
[RULE 401]

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Periodic Monitoring:

5. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE TEMPERATURE OF THE OVEN ONCE EVERY DAY.
[RULE 3004 (a)(4)]

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO:	2000 PPMV, RULE 407
PM:	0.1 GR/SCF, RULE 409
PM:	RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
NOx:	30 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92047
A/N 460292

Equipment Description:

SPRAY BOOTH, BEATTIE, FLOOR DRY FILTER TYPE, 20’-0” W. X 10'-0" D. X 8'-0" H., WITH FOUR 10’-0” W. X 4’-0” H. PREFILTERS, TWO 10’-0” W. X 8’-0” H. BLANKET TYPE FILTERS AND ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]

7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 109
    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
    PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92048
A/N 460293

Equipment Description:

SPRAY BOOTH, BEATTIE, FLOOR DRY FILTER TYPE, 20’-0” W. X 10'-0" D. X 8'-0" H., WITH FOUR 10’-0” W. X 4’-0” H. PREFILTERS, TWO 10’-0” W. X 8’-0” H. BLANKET TYPE FILTERS AND ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]

7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 109
    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
    PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92062
A/N 460295

Equipment Description:

SPRAY BOOTH, BEATTIE, FLOOR DRY FILTER TYPE, 20’-0” W. X 10'-2" D. X 8'-10" H., WITH FOUR 4’-0” W. X 8’-0” H. PREFILTERS, TWO 10’-0” W. X 8’-0” H. BLANKET TYPE FILTERS AND ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]

7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 109
    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
    PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92064
A/N 460296

Equipment Description:

SPRAY BOOTH, BEATTIE, FLOOR DRY FILTER TYPE, 10’-0” W. X 10'-2" D. X 8'-0" H., WITH TWO 10’-0” W. X 4’-0” H. PREFILTERS, ONE 10’-0” W. X 8’-0” H. BLANKET TYPE FILTER AND ONE 2 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]

7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 109
    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
    PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92065
A/N 460297

Equipment Description:

SPRAY BOOTH, BINKS, FLOOR FILTER TYPE, MODEL PFA 10-8-T-LH. 10’-0” W. X 9'-8" L. X 8'-0" H., WITH TWO 10’-0” W. X 4’-0” H. PREFILTERS, ONE 10’-0” W. X 8’-0” H. BLANKET TYPE FILTERS AND ONE 1 ½ HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]

7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 109
    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
    PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92066
A/N 460298

Equipment Description:

SPRAY BOOTH, FLOOR FILTER TYPE, 10'-0" W. X 9'-8" L. X 8'-0" H., WITH TWO 10'-0" W. X 4'-0" H. PREFILTERS, ONE 10'-0" W. X 8'-0" H. BLANKET TYPE FILTER AND ONE 1 ½ HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]

7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 109
    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
    PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92067
A/N 470374

Equipment Description:

POWDER COATING SYSTEM CONSISTING OF:

1. SPRAY BOOTH, BLEEKER, 12'-5" W. X 10'-7" L. X 8'-5" H.
2. TWENTY-EIGHT PRE-FILTERS, 20" W. X 20" L. X 1" D.
3. TWENTY-EIGHT POCKET FILTERS, 20" W. X 20" L. X 12" D.
4. EIGHT FINAL FILTERS, 24" W. X 24" L. X 12" D.
5. ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]

4. TWO GAUGES SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE POCKET-TYPE AND THE FINAL FILTER MEDIA. IN OPERATION, THE PRESSURE DIFFERENTIAL (BETWEEN CLEAN AND DIRTY FILTERS) SHALL NOT EXCEED 2.0 INCHES OF WATER ACROSS POCKET-TYPE FILTERS AND 1.5 INCHES OF WATER ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]

5. CLEAN-UP MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).
[RULE 1303(a)(1)-BACT]

6. NO WET COATINGS SHALL BE APPLIED IN THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

7. THE TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE MONTHLY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

9. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005, OR EARLIER.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

11. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;

    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND

    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

    [RULE 3004 (a)(4)]

12. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

    THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

A. STACK OR EMISSION POINT IDENTIFICATION;

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND

C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

[RULE 3004 (a)(4)]

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92068
A/N 470379

Equipment Description:

POWDER COATING SYSTEM CONSISTING OF:

1. SPRAY BOOTH, BLEEKER, 12'-5" W. X 10'-7" L. X 8'-5" H.
2. TWENTY-EIGHT PRE-FILTERS, 20" W. X 20" L. X 1" D.
3. TWENTY-EIGHT POCKET FILTERS, 20" W. X 20" L. X 12" D.
4. EIGHT FINAL FILTERS, 24" W. X 24" L. X 12" D.
5. ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]

4. TWO GAUGES SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE POCKET-TYPE AND THE FINAL FILTER MEDIA. IN OPERATION, THE PRESSURE DIFFERENTIAL (BETWEEN CLEAN AND DIRTY FILTERS) SHALL NOT EXCEED 2.0 INCHES OF WATER ACROSS POCKET-TYPE FILTERS AND 1.5 INCHES OF WATER ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]

5. CLEAN-UP MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).
[RULE 1303(a)(1)-BACT]

6. NO WET COATINGS SHALL BE APPLIED IN THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

7. THE TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE MONTHLY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED
[RULE 109, 1303(b)(2)-OFFSET]

9. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005, OR EARLIER.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

11. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;

    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND

    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

    [RULE 3004 (a)(4)]

12. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

    THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

A. STACK OR EMISSION POINT IDENTIFICATION;

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND

C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

[RULE 3004 (a)(4)]

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92069
A/N 470380

Equipment Description:

POWDER COATING SYSTEM CONSISTING OF:

1. SPRAY BOOTH, BLEEKER, 12'-5" W. X 11'-2" L. X 8'-5" H.
2. TWENTY-EIGHT PRE-FILTERS, 20" W. X 20" L. X 1" D.
3. TWENTY-EIGHT POCKET FILTERS, 20" W. X 20" L. X 12" D.
4. EIGHT FINAL FILTERS, 24" W. X 24" L. X 12" D.
5. ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]

4. TWO GAUGES SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE POCKET-TYPE AND THE FINAL FILTER MEDIA. IN OPERATION, THE PRESSURE DIFFERENTIAL (BETWEEN CLEAN AND DIRTY FILTERS) SHALL NOT EXCEED 2.0 INCHES OF WATER ACROSS POCKET-TYPE FILTERS AND 1.5 INCHES OF WATER ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]

5. CLEAN-UP MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).
[RULE 1303(a)(1)-BACT]

6. NO WET COATINGS SHALL BE APPLIED IN THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

7. THE TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE MONTHLY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

9. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005, OR EARLIER.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

11. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;

    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND

    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

    [RULE 3004 (a)(4)]

12. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

    THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

A. STACK OR EMISSION POINT IDENTIFICATION;

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND

C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

[RULE 3004 (a)(4)]

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92070
A/N 470382

Equipment Description:

POWDER COATING SYSTEM CONSISTING OF:

1. SPRAY BOOTH, BLEEKER, 12'-5" W. X 10'-7" L. X 8'-5" H.
2. TWENTY-EIGHT PRE-FILTERS, 20" W. X 20" L. X 1" D.
3. TWENTY-EIGHT POCKET FILTERS, 20" W. X 20" L. X 12" D.
4. EIGHT FINAL FILTERS, 24" W. X 24" L. X 12" D.
5. ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]

4. MECHANICAL GAUGES SHALL BE INSTALLED TO INDICATE THE STATIC PRESSURE DIFFERENTIAL ACROSS THE PREFILTERS AND POCKET FILTERS (AS ONE MEASUREMENT) AND THE FINAL FILTERS (AS A SEPARATE MEASUREMENT). IN OPERATION, THE PRESSURE DIFFERENTIAL (BETWEEN CLEAN AND DIRTY FILTERS) SHALL NOT EXCEED 1.0 INCH WATER COLUMN ACROSS THE PREFILTERS/POCKET FILTERS COMBINED AND 1.5 INCHES WATER COLUMN ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 550 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

6. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005, OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

7. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
   [RULE 3004 (a)(4)]

10. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

    THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
    A. STACK OR EMISSION POINT IDENTIFICATION;
    B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
    C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
    [RULE 3004 (a)(4)]

Emissions and Requirements:

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92071
A/N 470383

Equipment Description:

POWDER COATING SYSTEM CONSISTING OF:

1. SPRAY BOOTH, BLEEKER, 12'-5" W. X 10'-7" L. X 8'-5" H.
2. TWENTY-EIGHT PRE-FILTERS, 20" W. X 20" L. X 1" D.
3. TWENTY-EIGHT POCKET FILTERS, 20" W. X 20" L. X 12" D.
4. EIGHT FINAL FILTERS, 24" W. X 24" L. X 12" D.
5. ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]

4. TWO GAUGES SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE POCKET-TYPE AND THE FINAL FILTER MEDIA. IN OPERATION, THE PRESSURE DIFFERENTIAL (BETWEEN CLEAN AND DIRTY FILTERS) SHALL NOT EXCEED 2.0 INCHES OF WATER ACROSS POCKET-TYPE FILTERS AND 1.5 INCHES OF WATER ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]

5. CLEAN-UP MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).
[RULE 1303(a)(1)-BACT]

6. NO WET COATINGS SHALL BE APPLIED IN THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]

7. THE TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE MONTHLY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

9. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005, OR EARLIER.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

11. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;

    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND

    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

    [RULE 3004 (a)(4)]

12. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

    THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

    A. STACK OR EMISSION POINT IDENTIFICATION;

    B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
[RULE 3004 (a)(4)]

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92074
A/N 470386

Equipment Description:

SPRAY BOOTH, BEATTIE, FLOOR DRY FILTER TYPE, 10’-0” W. X 10'-0" D. X 8'-0" H., WITH TWO 10’-0” W. X 4’-0” H. PREFILTERS, ONE 10’-0” W. X 8’-0” H. BLANKET TYPE FILTER AND ONE 2 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]

7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 109
    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
    PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92075
A/N 470387

Equipment Description:

SPRAY BOOTH, BINKS, FLOOR FILTER TYPE, MODEL PFA 10-8-T-LH., 10’-0” W. X 9'-8" L. X 8'-0" H., WITH TWO 10’-0” W. X 4’-0” H. PREFILTERS, ONE 10’-0” W. X 8’-0” H. BLANKET TYPE FILTERS AND ONE 1 ½ HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109
[RULE 109, 1303(b)(2)-OFFSET]

7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 109
    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
    PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92077
A/N 470389

Equipment Description:

OVEN, MILLER, 800,000 BTU/HR NATURAL GAS FIRED, WITH A MAXON CYCLOMAX LOW NOx BURNER, AND ONE 3/4 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURE ABOVE 450 DEGREES FAHRENHEIT.
[RULE 401]

4. THE OXIDES OF NITROGEN (NOx) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NOx, BY VOLUME ON A DRY BASIS @ 3% O2, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)BACT]

Periodic Monitoring:

5. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE TEMPERATURE OF THE OVEN ONCE EVERY DAY.
[RULE 3004 (a)(4)]

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO:	2000 PPMV, RULE 407
NOx:	30 PPMV, RULE 1303(a)(1)-BACT
NOx:	30 PPMV, RULE 1147
PM:	0.1 GR/SCF, RULE 409
PM:	RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92078
A/N 470390

Equipment Description:

OVEN, MILLER, 800,000 BTU/HR NATURAL GAS FIRED, WITH A MAXON CYCLOMAX LOW NOx BURNER, AND ONE 3/4 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE OXIDES OF NITROGEN (NOx) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NOx, BY VOLUME ON A DRY BASIS @ 3% O2, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

   IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

   A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
   B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL “VISIBLE EMISSION EVALUATION”, WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO:	2000 PPMV, RULE 407
NOx:	30 PPMV, RULE 1303(a)(1)-BACT
NOx:	30 PPMV, RULE 1147
PM:	0.1 GR/SCF, RULE 409
PM:	RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92079
A/N 470392

Equipment Description:

POWDER COATING CURING OVEN, MILLER, WITH ONE 800,000 BTU PER HOUR DIRECT NATURAL GAS FIRED MAXON CYCLOMAX 0.8M LOW-NOX BURNER AND ONE 3/4 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE TOTAL QUANTITY OF POWDER COATINGS APPLIED TO ARTICLES PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 550 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

4. THE OXIDES OF NITROGEN (NOx) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NOx, BY VOLUME ON A DRY BASIS @ 3% O2, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)-BACT]

5. MATERIALS USED ON THE ARTICLES PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER.
[RULE 1401]

6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

7. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL “VISIBLE EMISSION EVALUATION”, WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 407
NOx: 30 PPMV, RULE 1303(a)(1)-BACT
NOx: 30 PPMV, RULE 1147
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92082
A/N 470463

Equipment Description:

POWDER COATING SYSTEM CONSISTING OF:

1. SPRAY BOOTH, BLEEKER, 12'-5" W. X 11'-2" L. X 8'-5" H.
2. TWENTY-EIGHT PRE-FILTERS, 20" W. X 20" L. X 1" D.
3. TWENTY-EIGHT POCKET FILTERS, 20" W. X 20" L. X 12" D.
4. EIGHT FINAL FILTERS, 24" W. X 24" L. X 12" D.
5. ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]

4. TWO GAUGES SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE POCKET-TYPE AND THE FINAL FILTER MEDIA. IN OPERATION, THE PRESSURE DIFFERENTIAL (BETWEEN CLEAN AND DIRTY FILTERS) SHALL NOT EXCEED 2.0 INCHES OF WATER ACROSS THE POCKET-TYPE FILTERS AND 1.5 INCHES OF WATER ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]

5. CLEAN-UP MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).
[RULE 1303(a)(1)-BACT]

6. NO WET COATINGS SHALL BE APPLIED IN THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

7. THE TOTAL QUANTITY OF POWDER COATING SPRAYED IN THIS EQUIPMENT SHALL NOT EXCEED 370 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE MONTHLY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

9. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005, OR EARLIER.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

11. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;

    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND

    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

    [RULE 3004 (a)(4)]

12. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

    THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

    A. STACK OR EMISSION POINT IDENTIFICATION;

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND

C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
[RULE 3004 (a)(4)]

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F98725
A/N 473461

Equipment Description:

SPRAY BOOTH, RELCO ENGINEERS, 12'-0" W. X 13'-8" L. X 9'-10" H., WITH THIRTY FIVE 20" X 20" PREFILTERS, THIRTY-FIVE 20" X 20" POCKET FILTERS, EIGHT 24" X 24" X 12" HEPA FINAL FILTERS, AND ONE 5 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]

4. GAUGES SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL ACROSS THE PRE-FILTERS AND THE POCKET FILTERS SHALL NOT EXCEED 1 INCH OF WATER COMBINED, AND THE PRESSURE DIFFERENTIAL ACROSS THE HEPA FINAL FILTERS SHALL NOT EXCEED 1.5 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE HEPA (FINAL) FILTERS USED IN THIS EQUIPMENT SHALL BE INDIVIDUALLY DOP (OR EQUIVALENT) TESTED WITH 0.3 MICRON PARTICLES AND CERTIFIED TO HAVE AN EFFICIENCY OF NOT LESS THAN 99.97%.
[RULE 1303(a)(1)-BACT]

6. THE TOTAL QUANTITY OF POWDER COATING MATERIALS APPLIED IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

7. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

8. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER.
[RULE 1401]

Periodic Monitoring:

9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

10. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
    [RULE 3004 (a)(4)]

11. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

    THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
    A. STACK OR EMISSION POINT IDENTIFICATION;
    B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
    C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
    [RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Emissions and Requirements:

12. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC:	RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC:	RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC:	RULE 109
PM:	RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM:	RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM:	RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F98727
A/N 473462

Equipment Description:

POWDER COATING BOOTH, 8'-0" W. X 10'-0" L. X 8'-0" H., WITH SIXTEEN 20" X 20" PREFILTERS, SIXTEEN 20" X 20 " POCKET FILTERS, SIX 24" X 24" X 12" HEPA FINAL FILTERS AND ONE 3 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]

4. GAUGES SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL ACROSS THE PRE-FILTERS AND THE POCKET FILTERS SHALL NOT EXCEED 1 INCH OF WATER COMBINED, AND THE PRESSURE DIFFERENTIAL ACROSS THE HEPA FINAL FILTERS SHALL NOT EXCEED 1.5 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE HEPA (FINAL) FILTERS USED IN THIS EQUIPMENT SHALL BE INDIVIDUALLY DOP (OR EQUIVALENT) TESTED WITH 0.3 MICRON PARTICLES AND CERTIFIED TO HAVE AN EFFICIENCY OF NOT LESS THAN 99.97%.
[RULE 1303(a)(1)-BACT]

6. THE TOTAL QUANTITY OF POWDER COATING MATERIALS APPLIED IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

7. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

8. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER.
[RULE 1401]

Periodic Monitoring:

9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

10. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
    [RULE 3004 (a)(4)]

11. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

    THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
    A. STACK OR EMISSION POINT IDENTIFICATION;
    B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
    C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
    [RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Emissions and Requirements:

12. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC:	RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC:	RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC:	RULE 109
PM:	RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM:	RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM:	RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G4020
A/N 492529

Equipment Description:

AEROSOL CAN RECYCLING SYSTEM CONSISTING OF:

1. 55 GALLON (MAXIMUM) RECEIVING DRUM.
2. AEROSOL CAN HOUSING SLEEVE AND PUNCTURE UNIT, AEROSOLV, MODEL NO. 7000.
3. CARBON FILTER UNIT, AEROSOLV, MODEL NO. 28228, WITH COALESCING FILTER AND 1.25 LBS ACTIVATED CARBON.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE CARBON FILTER UNIT SHALL BE REPLACED AFTER PUNCTURING 1000 CANS IN THE DRUM OR WITHIN 45 DAYS AFTER FILTER INSTALLATION ON THE DRUM, WHICH EVER IS SOONER.
[RULE 1303(a)(1)-BACT]

4. THIS EQUIPMENT SHALL ONLY BE USED TO PROCESS SPENT AEROSOL PAINT CANS THAT WERE USED AT THIS FACILITY.
[RULE 1303(a)(1)-BACT]

5. THE AEROSOL PAINT CAN SHALL BE LEFT IN THE CAN HOUSING SLEEVE FOR AT LEAST 30 SECONDS AFTER IT IS PUNCTURED FOR COMPLETE DEPLETION OF SOLVENT INSIDE THE CAN.
[RULE 1303(a)(1)-BACT]

6. THE RECEIVING DRUM SHALL BE REPLACED WITH A NEW DRUM AFTER NO MORE THAN 4,200 CANS ARE PUNCTURED IN THIS EQUIPMENT. THE LIQUID WASTE COLLECTED INSIDE THE DRUM SHALL BE DISPOSED OF AS HAZARDOUS WASTE.
[RULE 1303(b)(2)-OFFSET]

7. THE LAST CAN PUNCTURED WITHIN THE AEROSOL CAN HOUSING SHALL BE LEFT IN THE CAN HOUSING SLEEVE UNTIL PUNCTURING IS RESUMED FOR ANOTHER BATCH OF AEROSOL CANS.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THE EQUIPMENT AND FACILITY TO VERIFY THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS), AND THE DAILY VOC EMISSIONS IN POUNDS. ALL RECORDS SHALL BE PREPARED IN A MANNER THAT IS ACCEPTABLE TO THE DISTRICT. RECORDS SHALL BE RETAINED ON THE PREMISES FOR FIVE YEARS AND SHALL BE MADE AVAILABLE TO THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET].

9. MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET].

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 442

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7336
A/N 501204

Equipment Description:

LASER CUTTING SYSTEM NO. 1, BYSTRONIC, ELECTRICALLY POWERED, CONSISTING OF:

1. LASER CUTTING TABLE, DOWNDRAFT TYPE, 12'-2" W. X 33 '-0" L. X 7'-5" H.

2. CHILLLER, 4'-10" W. X 3'-6" L. X 6'-0" H.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT, WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

4. THE MATERIALS PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC/TOXIC COMPOUNDS IDENTIFIED IN RULE 1401, TABLE 1, WITH AN EFFECTIVE DATE OF JUNE 5, 2009 OR EARLIER, EXCEPT CHROMIUM & CHROMIUM COMPOUNDS (CAS # 18540-29-9), NICKEL & NICKEL COMPOUNDS (CAS # 7440-02-0), MANGANESE AND MANGANESE COMPOUNDS (CAS # 7439-96-5), LEAD & LEAD COMPOUNDS (CAS # 7439-92-1) AND COPPER & COPPER COMPOUNDS (CAS # 7440-50-8), AS SPECIFIED IN CONDITION NO. 5.
[RULE 1401]

5. THE METAL PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN MORE THAN THE FOLLOWING:

A.	CHROMIUM & CHROMIUM COMPOUNDS	30% BY WEIGHT
B.	NICKEL & NICKEL COMPOUNDS	27% BY WEIGHT
C.	COPPER & COPPER COMPOUNDS	6% BY WEIGHT
D.	MANGANESE & MANGANESE COMPOUNDS	6% BY WEIGHT
C.	LEAD & LEAD COMPOUNDS	0.25% BY WEIGHT

[RULE 1401]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

6. STAINLESS STEEL CONTAINING CHROMIUM & CHROMIUM COMPOUNDS AND NICKEL & NICKEL COMPOUNDS (EXCEEDING 5% BY WEIGHT EACH) PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 10% OF THE TOTAL METAL PROCESSED IN THIS EQUIPMENT ON A MONTHLY BASIS.
[RULE 1303(b)(2)-OFFSET, 1401]

7. THE SHEET METAL THICKNESS PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 0.15".
[RULE 1303(b)(2)-OFFSET, 1401]

8. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO DEMONSTARTE COMPLIANCE WITH THESE PERMIT CONDITIONS.
[RULE 1303(b)(2)-OFFSET, 1401]

9. RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.
[RULE 1303(b)(2)-OFFSET, 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

    IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

    A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

    B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

    THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

    A. STACK OR EMISSION POINT IDENTIFICATION;

    B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

    C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

    D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
    [RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Emissions and Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    PM RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7337
A/N 501206

Equipment Description:

AIR POLLUTION CONTROL SYSTEM NO. 1, CONSISTING OF:

1. DUST COLLECTOR, TORRIT, MODEL NO. DFT 3-6, 3'-4" W. X 4'-8" D. X 9'-7" H., WITH 6 CARTRIDGE FILTERS, MODEL TORIT ULTRA-WEB, EACH 1'-1" DIA. X 2'-2" L., 1524 SQ. FT. TOTAL FILTER AREA, AND PULSE JET CLEANED.

2. EXHAUST SYSTEM WITH A 10 H.P. BLOWER VENTING LASER CUTTING SYSTEM NO. 1.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. DUST COLLECTED IN THIS EQUIPMENT SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]

4. A MAGNEHELIC GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 5.0 INCH OF WATER AND SHALL NOT BE LOWER THAN 0.5 INCH OF WATER.
[RULE 1303(a)(1)-BACT, 1401]

Periodic Monitoring:

5. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

6. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

   THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

   A. STACK OR EMISSION POINT IDENTIFICATION;

   B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND

   C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

   [RULE 3004 (a)(4)]

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   PM: RULE 1155
   PM: 0 PERCENT OPACITY, RULE 1155
   PM RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7338
A/N 501208

Equipment Description:

LASER CUTTING SYSTEM NO. 2, CINCINNATI, MODEL NO. CL-707 CNC, ELECTRICALLY POWERED, CONSISTING OF:

1. LASER CUTTING TABLE, DOWNDRAFT TYPE, 16'-0" W. X 26'-10" L. X 7'-8" H.

2. CHILLLER, 2'-8" W. X 5'-0" L. X 5'-5" H.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT, WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

4. THE MATERIALS PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC/TOXIC COMPOUNDS IDENTIFIED IN RULE 1401, TABLE 1, WITH AN EFFECTIVE DATE OF JUNE 5, 2009 OR EARLIER, EXCEPT CHROMIUM & CHROMIUM COMPOUNDS (CAS # 18540-29-9), NICKEL & NICKEL COMPOUNDS (CAS # 7440-02-0), MANGANESE AND MANGANESE COMPOUNDS (CAS # 7439-96-5), LEAD & LEAD COMPOUNDS (CAS # 7439-92-1) AND COPPER & COPPER COMPOUNDS (CAS # 7440-50-8), AS SPECIFIED IN CONDITION NO. 5.
[RULE 1401]

5. THE METAL PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN MORE THAN THE FOLLOWING:

A.	CHROMIUM & CHROMIUM COMPOUNDS	30% BY WEIGHT
B.	NICKEL & NICKEL COMPOUNDS	27% BY WEIGHT
C.	COPPER & COPPER COMPOUNDS	6% BY WEIGHT
D.	MANGANESE & MANGANESE COMPOUNDS	6% BY WEIGHT
C.	LEAD & LEAD COMPOUNDS	0.25% BY WEIGHT

[RULE 1401]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

6. STAINLESS STEEL CONTAINING CHROMIUM & CHROMIUM COMPOUNDS AND NICKEL & NICKEL COMPOUNDS (EXCEEDING 5% BY WEIGHT EACH) PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 10% OF THE TOTAL METAL PROCESSED IN THIS EQUIPMENT ON A MONTHLY BASIS.
[RULE 1303(b)(2)-OFFSET, 1401]

7. THE SHEET METAL THICKNESS PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 0.15".
[RULE 1303(b)(2)-OFFSET, 1401]

8. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO DEMONSTARTE COMPLIANCE WITH THESE PERMIT CONDITIONS.
[RULE 1303(b)(2)-OFFSET, 1401]

9. RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.
[RULE 1303(b)(2)-OFFSET, 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

    IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

    A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

    B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

    THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

    A. STACK OR EMISSION POINT IDENTIFICATION;

    B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

    C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

    D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

    [RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Emissions and Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    PM RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7339
A/N 501210

Equipment Description:

AIR POLLUTION CONTROL SYSTEM NO. 2, CONSISTING OF:

1. DUST COLLECTOR, TORRIT, MODEL NO. DFT 3-12, 3'-4" W. X 7'-1" D. X 12'-0" H., WITH 12 CARTRIDGE FILTERS, MODEL TORIT ULTRA-WEB, EACH 1'-1" DIA. X 2'-2" L., 3048 SQ. FT. TOTAL FILTER AREA, AND PULSE JET CLEANED.

2. EXHAUST SYSTEM WITH A 10 H.P. BLOWER VENTING A LASER CUTTING SYSTEM NO. 2.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. DUST COLLECTED IN THIS EQUIPMENT SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]

4. A MAGNEHELIC GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 5.0 INCH OF WATER AND SHALL NOT BE LOWER THAN 0.5 INCH OF WATER.
[RULE 1303(a)(1)-BACT, 1401]

Periodic Monitoring:

5. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

6. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

   THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

   A. STACK OR EMISSION POINT IDENTIFICATION;

   B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND

   C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

   [RULE 3004 (a)(4)]

Emissions And Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   PM: RULE 1155
   PM: 0 PERCENT OPACITY, RULE 1155
   PM RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7340
A/N 501212

Equipment Description:

LASER CUTTING SYSTEM NO. 3, BYSTRONIC, ELECTRICALLY POWERED, CONSISTING OF:

1. LASER CUTTING TABLE, DOWNDRAFT TYPE, 12'-2" W. X 33'-0" L. X 7'-5" H.

2. CHILLLER, 4'-10" W. X 3'-6" L. X 6'-0" H.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT, WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

4. THE MATERIALS PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC/TOXIC COMPOUNDS IDENTIFIED IN RULE 1401, TABLE 1, WITH AN EFFECTIVE DATE OF JUNE 5, 2009 OR EARLIER, EXCEPT CHROMIUM & CHROMIUM COMPOUNDS (CAS # 18540-29-9), NICKEL & NICKEL COMPOUNDS (CAS # 7440-02-0), MANGANESE AND MANGANESE COMPOUNDS (CAS # 7439-96-5), LEAD & LEAD COMPOUNDS (CAS # 7439-92-1) AND COPPER & COPPER COMPOUNDS (CAS # 7440-50-8), AS SPECIFIED IN CONDITION NO. 5.
[RULE 1401]

5. THE METAL PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN MORE THAN THE FOLLOWING:

A.	CHROMIUM & CHROMIUM COMPOUNDS	30% BY WEIGHT
B.	NICKEL & NICKEL COMPOUNDS	27% BY WEIGHT
C.	COPPER & COPPER COMPOUNDS	6% BY WEIGHT
D.	MANGANESE & MANGANESE COMPOUNDS	6% BY WEIGHT
C.	LEAD & LEAD COMPOUNDS	0.25% BY WEIGHT

[RULE 1401]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

6. STAINLESS STEEL CONTAINING CHROMIUM & CHROMIUM COMPOUNDS AND NICKEL & NICKEL COMPOUNDS (EXCEEDING 5% BY WEIGHT EACH) PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 10% OF THE TOTAL METAL PROCESSED IN THIS EQUIPMENT ON A MONTHLY BASIS.
[RULE 1303(b)(2)-OFFSET, 1401]

7. THE SHEET METAL THICKNESS PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 0.15".
[RULE 1303(b)(2)-OFFSET, 1401]

8. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO DEMONSTARTE COMPLIANCE WITH THESE PERMIT CONDITIONS.
[RULE 1303(b)(2)-OFFSET, 1401]

9. RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.
[RULE 1303(b)(2)-OFFSET, 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

    IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

    A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

    B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

    THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

    A. STACK OR EMISSION POINT IDENTIFICATION;

    B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

    C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

    D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

    [RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Emissions and Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    PM RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7341
A/N 501214

Equipment Description:

AIR POLLUTION CONTROL SYSTEM NO. 3, CONSISTING OF:

1. DUST COLLECTOR, TORRIT, MODEL NO. DFT 2-4, 3'-4" W. X 4'-8" D. X 9'-7" H., WITH 4 CARTRIDGE FILTERS, MODEL TORIT ULTRA-WEB, EACH 1'-1" DIA. X 2'-2" L., 1016 SQ. FT. TOTAL FILTER AREA, AND PULSE JET CLEANED.

2. EXHAUST SYSTEM WITH A 10 H.P. BLOWER VENTING A LASER CUTTING SYSTEM NO. 3.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. DUST COLLECTED IN THIS EQUIPMENT SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]

4. A MAGNEHELIC GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 5.0 INCH OF WATER AND SHALL NOT BE LOWER THAN 0.5 INCH OF WATER.
[RULE 1303(a)(1)-BACT, 1401]

Periodic Monitoring:

5. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

6. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

   THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

   A. STACK OR EMISSION POINT IDENTIFICATION;

   B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND

   C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

   [RULE 3004 (a)(4)]

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   PM: RULE 1155
   PM: 0 PERCENT OPACITY, RULE 1155
   PM RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7349
A/N 500473

Equipment Description:

SPRAY BOOTH NO. 1, NORDSON, MODEL CK-7200, 14'-4" W. X 10'-6" L. X 10'-10" H., WITH EXHAUST FILTERS CONSISTING OF EIGHT 3'-0" L. X 1'-0" DIA. PRIMARY CARTRIDGE FILTERS AND FOUR 1'-8" W. X 2'-0" L. SECONDARY BOX-TYPE FILTERS AND ONE 5 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 2.0 INCHES OF WATER ACROSS THE PRIMARY FILTERS AND 1.5 INCHES OF WATER ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]

5. CLEAN-UP MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).
[RULE 1303(a)(1)-BACT]

6. NO WET COATINGS SHALL BE APPLIED IN THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]

7. THE TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 1,500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE MONTHLY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

9. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF JUNE 5, 2009, OR EARLIER.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

11. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;

    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND

    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

    [RULE 3004 (a)(4)]

12. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

    THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

    A. STACK OR EMISSION POINT IDENTIFICATION;

    B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND

    C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

    [RULE 3004 (a)(4)]

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 109

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7350
A/N 500474

Equipment Description:

SPRAY BOOTH NO. 2, NORDSON, MODEL CK-7200, 14'-4" W. X 10'-6" L. X 10'-10" H., WITH EXHAUST FILTERS CONSISTING OF EIGHT 3'-0" L. X 1'-0" DIA. PRIMARY CARTRIDGE FILTERS AND FOUR 1'-8" W. X 2'-0" L. SECONDARY BOX-TYPE FILTERS AND ONE 5 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 2.0 INCHES OF WATER ACROSS THE PRIMARY FILTERS AND 1.5 INCHES OF WATER ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]

5. CLEAN-UP MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).
[RULE 1303(a)(1)-BACT]

6. NO WET COATINGS SHALL BE APPLIED IN THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]

7. THE TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 1,500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE MONTHLY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

9. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF JUNE 5, 2009, OR EARLIER.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

11. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;

    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND

    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

    [RULE 3004 (a)(4)]

12. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

    THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

    A. STACK OR EMISSION POINT IDENTIFICATION;

    B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND

    C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

    [RULE 3004 (a)(4)]

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 109

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7351
A/N 500475

Equipment Description:

SIX STAGE WASHER, INDUSTRIAL PROCESS EQUIPMENT, INC, MODEL 5707-W, 68'-0" L. X 7'-0" W. X 13'-6" H., CONSISTING OF:

1. ONE HEATED PHOSPHATE SPRAY SYSTEM WITH ONE HUNDRED SIXTY SPRAY NOZZLES, ONE 10 H.P. SPRAY TANK, ONE 1,148 GALLONS TANK, WITH ONE 2,000,000 BTU/HOUR ECLIPSE IJ-6 NATURAL GAS FIRED BURNER.

2. ONE HEATED PHOSPHATE SPRAY SYSTEM WITH ONE HUNDRED SIXTY SPRAY NOZZLES, ONE 10 H.P. SPRAY TANK, ONE 1,148 GALLONS TANK, WITH ONE 2,000,000 BTU/HOUR ECLIPSE IJ-6 NATURAL GAS FIRED BURNER.

3. ONE WATER RINSE SPRAY SYSTEM WITH NINETY-SIX SPRAY NOZZLES, ONE 7-1/2 H.P. SPRAY PUMP, ONE 623 GALLONS TANK.

4. ONE PURE WATER RINSE SPRAY SYSTEM WITH NINETY-SIX SPRAY NOZZLES, ONE 7-1/2 H.P. SPRAY PUMP, ONE 623 GALLONS TANK.

5. ONE NON-CHROME SEAL SPRAY SYSTEM WITH FORTY-EIGHT SPRAY NOZZLES, ONE 1 H.P. SPRAY PUMP, ONE 374 GALLONS TANK

6. ONE DEIONIZED WATER RINSE SPRAY SYSTEM WITH FORTY-EIGHT SPRAY NOZZLES, ONE 1 H.P. SPRAY PUMP, ONE 374 GALLONS TANK.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE BURNER IN THIS EQUIPMENT SHALL NOT USE MORE THAN 23,077 CUBIC FEET OF NATURAL GAS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET)

4. A NON-RESETTABLE TOTALIZING FUEL METER SHALL BE INSTALLED AND MAINTAINED TO VERIFY COMPLIANCE WITH THE DAILY NATURAL GAS USAGE LIMIT.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

5. THE OPERATOR SHALL MAINTAIN A NATURAL GAS CONSUMPTION LOG TO VERIFY COMPLIANCE WITH THE NATURAL GAS USAGE LIMIT. THE LOG SHALL INCLUDE, AT A MINIMUM, THE DATE OF OPERATION OF THIS EQUIPMENT, THE GAS METER READING AT THE BEGINNING OF EACH DAY BEFORE THE EQUIPMENT IS OPERATED, AND AT THE END OF EACH DAY AFTER THE EQUIPMENT IS SHUT DOWN.
[RULE 109, 1303(b)(2)-OFFSET]

6. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF JUNE 5, 2009. OR EARLIER.
[RULE 1401]

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM:	0.1 GR/SCF, RULE 109
CO:	2000 PPMV, RULE 407
NOx:	30 PPMV, RULE 1147
VOC:	RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC:	RULE 109
PM:	RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7352
A/N 500476

Equipment Description:

POWDER COATING DRYING OVEN, INDUSTRIAL PROCESS EQUIPMENT, INC, MODEL 5707-DO, 14'-7" W. X 23'-7" L. X 13'-11" H., 1,000,000 BTU/HR ECLIPSE WX0100 WINNOX LOW NOx DIRECT NATURAL GAS FIRED BURNER, WITH ONE 1.5 H.P. COMBUSTION AIR FAN, ONE 1.5 H.P. EXHAUST FAN AND ONE 10 H.P. RECIRCULATION FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURE ABOVE 450 DEGREES FAHRENHEIT.
[RULE 401]

4. THE OXIDES OF NITROGEN (NOx) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NOx, BY VOLUME ON A DRY BASIS @ 3% O2, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)-BACT]

5. MATERIALS USED ON THE ARTICLES PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I WITH AN EFFECTIVE DATE OF JUNE 5, 2009 OR EARLIER.
[RULE 1401]

6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Periodic Monitoring:

7. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

   IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

   A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

   B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL “VISIBLE EMISSION EVALUATION”, WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

   THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

   A. STACK OR EMISSION POINT IDENTIFICATION;

   B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

   C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

   D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
   [RULE 3004 (a)(4)]

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   CO: 2000 PPMV, RULE 407
   NOx: 30 PPMV, RULE 1303(a)(1)-BACT
   NOx: 30 PPMV, RULE 1147
   PM: 0.1 GR/SCF, RULE 409
   PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7353
A/N 500477

Equipment Description:

CURING OVEN, INDUSTRIAL PROCESS EQUIPMENT, INC, MODEL 5707-CO, 17'-3" W. X 43'-0" L. X 13'-8" H., 4,000,000 BTU/HR ECLIPSE WX0400 WINNOX LOW NOx DIRECT NATURAL GAS FIRED BURNER, WITH ONE 5 H.P. COMBUSTION AIR FAN, ONE 3 H.P. EXHAUST FAN AND TWO 25 H.P. RECIRCULATION FANS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 450 DEGREES FAHRENHEIT.
[RULE 401]

4. THE OXIDES OF NITROGEN (NOx) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NOx, BY VOLUME ON A DRY BASIS @ 3% O2, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)-BACT]

5. MATERIALS USED ON THE ARTICLES PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I WITH AN EFFECTIVE DATE OF JUNE 5, 2009 OR EARLIER.
[RULE 1401]

6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS, THE VOC CONTENT OF LIQUID COATINGS IN POUNDS OF VOC PER GALLON OF MATERIAL AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS, AND THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Periodic Monitoring:

7. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

   IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

   A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

   B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL “VISIBLE EMISSION EVALUATION”, WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

   THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

   A. STACK OR EMISSION POINT IDENTIFICATION;

   B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

   C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

   D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

   [RULE 3004 (a)(4)]

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO:	2000 PPMV, RULE 407
NOx:	30 PPMV, RULE 1303(a)(1)-BACT
NOx:	30 PPMV, RULE 1147
PM:	0.1 GR/SCF, RULE 409
PM:	RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7354
A/N 503450

Equipment Description:

OVEN, CURING, RAMCO, 8'-0" W. X 9'-0" D. X 8'-0" H., 800,000 BTU/HR NATURAL GAS FIRED, WITH A MAXON CYCLOMAX LOW NOx BURNER, A 1/2 H.P. COMBUSTION AIR FAN, A 1/2 H.P. EXHAUST FAN AND A 7-1/2 RECIRCULATION FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE OXIDES OF NITROGEN (NOx) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NOx, BY VOLUME ON A DRY BASIS @ 3% O2, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

   IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

   A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

   B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO:	2000 PPMV, RULE 407
NOx:	30 PPMV, RULE 1303(a)(1)-BACT
NOx:	30 PPMV, RULE 1147
PM:	0.1 GR/SCF, RULE 409
PM:	RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7355
A/N 503451

Equipment Description:

OVEN, RAMCO, MODEL 10-10-8, 10'-0" W. X 7'-6" L. X 8'-6" H., 800,000 BTU/HR NATURAL GAS FIRED, WITH ONE 1/3 H.P. COMBUSTION AIR BLOWER, ONE 7 1/2 H.P. CIRCULATING FAN, AND ONE 2 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 450 DEGREES FAHRENHEIT.
[RULE 401]

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Periodic Monitoring:

5. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE TEMPERATURE OF THE OVEN ONCE EVERY DAY.
[RULE 3004 (a)(4)]

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO:	2000 PPMV, RULE 407
NOx:	30 PPMV, RULE 1147
PM:	0.1 GR/SCF, RULE 409
PM:	RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO CONSTRUCT

A/N 518877
Granted as of
April 12, 2011

Equipment Description:

SPRAY BOOTH L-13, CONVEYORIZED, INDUSTRIAL PROCESS EQUIPMENT, 20'-8" W. x 15'-5" D. x 10'-0" H., WITH TWENTY-FIVE 20" x 20" EXHAUST FILTERS AND TWO 3 HP EXHAUST FANS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THE TWO SPRAY BOOTHS UNDER A/Ns 518877 & 518878 COMBINED SHALL NOT EXCEED 850 POUNDS IN ANY CALENDAR MONTH.
[RULE 1303(b)(2)-OFFSET]

6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY AND CALENDAR MONTHLY VOC EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH COATING IN POUNDS PER GALLON OF MATERIAL AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 109, 1303(b)(2)-OFFSET]

7. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 109
    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
    PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PERMIT TO CONSTRUCT

A/N 518878
Granted as of
April 12, 2011

Equipment Description:

SPRAY BOOTH L-15, CONVEYORIZED, INDUSTRIAL PROCESS EQUIPMENT, 20'-8" W. x 15'-5" D. x 10'-0" H., WITH TWENTY-FIVE 20" x 20" FILTERS AND TWO 3 HP EXHAUST FANS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THE TWO SPRAY BOOTHS UNDER A/Ns 518877 & 518878 COMBINED SHALL NOT EXCEED 850 POUNDS IN ANY CALENDAR MONTH.
[RULE 1303(b)(2)-OFFSET]

6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY AND CALENDAR MONTHLY VOC EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH COATING IN POUNDS PER GALLON OF MATERIAL AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 109, 1303(b)(2)-OFFSET]

7. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

   [RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 109
    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
    PM: RULE 481

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

Periodic Monitoring:

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

   FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (g/l) OF MATERIALS FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS SUPPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

   FOR OTHER ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS APPLIED IN GRAMS PER LITER (g/l) OF MATERIALS USED FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS APPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.
   [RULE 3004(a)(4)]

Emissions And Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS
   VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
   VOC: RULE 109

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, LOW USE OR EMISSIONS

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
   VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
   VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
   VOC: RULE 109

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, PRINTING EQUIPMENT, LOW USE OR EMISSIONS, WITH RELATED COATING, LAMINATING AND DRYING EQUIPMENT.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   VOC: RULE 1130.1, SEE APPENDIX B FOR EMISSION LIMITS
   VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
   VOC: RULE 109

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, ABRASIVE BLASTING EQUIPMENT, GLOVE-BOX, < 53 FT3, WITH DUST FILTER.

Periodic Monitoring:

1. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
   [RULE 3004 (a)(4)]

2. THE OPERATOR SHALL DISCHARGE DUST COLLECTED IN THIS EQUIPMENT ONLY INTO CLOSED CONTAINERS.
   [RULE 3004 (a)(4)]

3. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

   THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
   A. STACK OR EMISSION POINT IDENTIFICATION;
   B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
   C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
   [RULE 3004 (a)(4)]

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1140, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   REFRIGERANT: RULE 1415

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COOLING TOWERS

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   CR^{+6}: RULE 1404

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION E: ADMINISTRATIVE CONDITIONS

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]

   a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]

   b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]

   c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]

2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]

3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the AQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations, or statues of other governmental agencies. [204]

4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION E: ADMINISTRATIVE CONDITIONS

5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation. [204]

6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to AQMD personnel upon request and be maintained for at least five years. [204]

7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by AQMD rules or permit conditions: [204]

   a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134]

   b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]

   c. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes; [204]

   d. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compounds which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO2) and be averaged over 15 consecutive minutes; [407]

   e. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent of carbon dioxide (CO2) at standard conditions and averaged over a minimum of 15 consecutive minutes. [409]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION E: ADMINISTRATIVE CONDITIONS

f. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O2) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]

8. The operator shall, when a source test is required by AQMD, provide a source test protocol to AQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by AQMD. The test protocol shall contain the following information: [204, 304]

a. Brief description of the equipment tested.

b. Brief process description, including maximum and normal operating temperatures, pressures, throughput, etc.

c. Operating conditions under which the test will be performed.

d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).

e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.

f. Description of calibration and quality assurance procedures.

g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (conflict of interest).

9. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by AQMD rules or equipment-specific conditions. The report shall contain the following information: [204]

a. The results of the source test.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION E: ADMINISTRATIVE CONDITIONS

b. Brief description of the equipment tested.

c. Operating conditions under which the test was performed.

d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).

e. Field and laboratory data forms, strip charts and analyses.

f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.

10. The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of AQMD Source Test Method 1.1 and 1.2. [217]

11. Whenever required to submit a written report, notification or other submittal to the Executive Officer, AQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, AQMD, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182. [204]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

NOT APPLICABLE

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR RECLAIM SOURCES

NOT APPLICABLE

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

See Section D of this permit for any Permit to Construct issued to this facility.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION I: PLANS AND SCHEDULES

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules.

NONE

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION J: AIR TOXICS

NOT APPLICABLE

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]

2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

   (B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]

4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION K: TITLE V Administration

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:

   (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.

   (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.

   (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:

   (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or

   (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

   Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:

   (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;

   (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;

   (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and

   (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]

10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]

12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]

13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION K: TITLE V Administration

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]

15. Nothing in this permit or in any permit shield can alter or affect:

    (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;

    (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;

    (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;

    (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;

    (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and

    (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]

16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION K: TITLE V Administration

EMERGENCY PROVISIONS

17. An emergency[1] constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:

    (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:

        (1) An emergency occurred and the operator can identify the cause(s) of the emergency;

        (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;

        (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,

        (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and

    (B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]

18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

---

1 "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION K: TITLE V Administration

RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:

    (A) The date, place as defined in the Title V permit, and time of sampling or measurements;

    (B) The date(s) analyses were performed;

    (C) The company or entity that performed the analyses;

    (D) The analytical techniques or methods used;

    (E) The results of such analyses; and

    (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]

20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]

21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:

    (A) Breakdowns shall be reported as required by Rule 430 – Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION K: TITLE V Administration

(B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.

(C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.

(D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]

23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]

24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:

(A) Identification of each permit term or condition that is the basis of the certification;

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION K: TITLE V Administration

(B) The compliance status during the reporting period;

(C) Whether compliance was continuous or intermittent;

(D) The method(s) used to determine compliance over the reporting period and currently, and

(E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn: Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 109	5-2-2003	Federally enforceable
RULE 1107	1-6-2006	Non federally enforceable
RULE 1107	11-9-2001	Federally enforceable
RULE 1113	11-8-1996	Federally enforceable
RULE 1113	6-3-2011	Non federally enforceable
RULE 1130.1	12-13-1996	Federally enforceable
RULE 1132	3-5-2004	Federally enforceable
RULE 1132	5-7-2004	Non federally enforceable
RULE 1140	2-1-1980	Federally enforceable
RULE 1140	8-2-1985	Non federally enforceable
RULE 1145	12-4-2009	Non federally enforceable
RULE 1145	2-14-1997	Federally enforceable
RULE 1147	12-5-2008	Non federally enforceable
RULE 1155	12-4-2009	Non federally enforceable
RULE 1171	11-7-2003	Federally enforceable
RULE 1171	5-1-2009	Non federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303(a)(1)-BACT	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	12-6-2002	Non federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1401	12-7-1990	Non federally enforceable

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 1401	3-4-2005	Non federally enforceable
RULE 1401	6-5-2009	Non federally enforceable
RULE 1404	4-6-1990	Non federally enforceable
RULE 1415	12-3-2010	Non federally enforceable
RULE 204	10-8-1993	Federally enforceable
RULE 217	1-5-1990	Federally enforceable
RULE 219	6-1-2007	Non federally enforceable
RULE 219	9-4-1981	Federally enforceable
RULE 3002	11-14-1997	Federally enforceable
RULE 3002	11-5-2010	Non federally enforceable
RULE 3003	11-14-1997	Federally enforceable
RULE 3003	11-5-2010	Non federally enforceable
RULE 3004	12-12-1997	Federally enforceable
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3005	11-5-2010	Non federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	5-6-2011	Non federally enforceable
RULE 401	11-9-2001	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 405	2-7-1986	Federally enforceable
RULE 407	4-2-1982	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 409	8-7-1981	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 442	12-15-2000	Federally enforceable
RULE 481	1-11-2002	Federally enforceable
RULE 701	6-13-1997	Federally enforceable
40CFR 63 Subpart MMMM	12-22-2006	Federally enforceable

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN PERMIT PURSUANT TO RULE 219

NONE

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 01-06-2006]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 01-06-2006]

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates, cont.								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
Extreme Performance	420	420	3.5	3.5	360	360	3.0	3.0
Prefabricated Architectural One-Component	420	275	3.5	2.3	275	275	2.3	2.3
Prefabricated Architectural Multi-Component	420	340	3.5	2.8	275	275	2.3	2.3
Touch Up	420	420	3.5	3.5	360	360	3.0	3.0
Repair	420	420	3.5	3.5	360	360	3.0	3.0
Silicone Release	420	420	3.5	3.5	420	420	3.5	3.5
High-Performance Architectural	420	420	3.5	3.5	420	420	3.5	3.5
Camouflage	420	420	3.5	3.5	420	420	3.5	3.5
Vacuum-Metalizing	420	420	3.5	3.5	420	420	3.5	3.5
Mold-Seal	420	420	3.5	3.5	420	420	3.5	3.5
High-Temperature	420	420	3.5	3.5	420	420	3.5	3.5
Electric-Insulating Varnish	420	420	3.5	3.5	420	420	3.5	3.5
Pan Backing	420	420	3.5	3.5	420	420	3.5	3.5
Pretreatment Coatings	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 01-06-2006]

(2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 11-09-2001]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 11-09-2001]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 11-09-2001]

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates, cont.								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
Extreme Performance	420	420	3.5	3.5	360	360	3.0	3.0
Prefabricated Architectural One-Component	420	275	3.5	2.3	275	275	2.3	2.3
Prefabricated Architectural Multi-Component	420	340	3.5	2.8	275	275	2.3	2.3
Touch Up	420	420	3.5	3.5	360	360	3.0	3.0
Repair	420	420	3.5	3.5	360	360	3.0	3.0
Silicone Release	420	420	3.5	3.5	420	420	3.5	3.5
High-Performance Architectural	420	420	3.5	3.5	420	420	3.5	3.5
Camouflage	420	420	3.5	3.5	420	420	3.5	3.5
Vacuum-Metalizing	420	420	3.5	3.5	420	420	3.5	3.5
Mold-Seal	420	420	3.5	3.5	420	420	3.5	3.5
High-Temperature	420	420	3.5	3.5	420	420	3.5	3.5
Electric-Insulating Varnish	420	420	3.5	3.5	420	420	3.5	3.5
Pan Backing	420	420	3.5	3.5	420	420	3.5	3.5
Pretreatment Coatings	420	420	3.5	3.5	420	420	3.5	3.5

(2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 11-08-1996]

(1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.

(2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

TABLE OF STANDARDS

VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water And Less Exempt Compounds

COATING	Limit*	Effective Date of Adoption	Effective 1/1/1998	Effective 1/1/1999	Effective 7/1/2001	Effective 1/1/2005	Effective 7/1/2008
Bond Breakers	350						
Clear Wood Finishes							
Varnish	350						
Sanding Sealers	350						
Lacquer	680		550			275	
Concrete-Curing Compounds	350						
Dry-Fog Coatings	400						
Fire-proofing Exterior Coatings	350	450		350			
Fire-Retardant Coatings							
Clear	650						
Pigmented	350						
Flats	250				100		50
Graphic Arts (Sign) Coatings	500						

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 11-08-1996]

Industrial Maintenance Primers and Topcoats							
Alkyds	420						
Catalyzed Epoxy	420						
Bituminous Coatings	420						
Materials							
Inorganic Polymers	420						
Vinyl Chloride Polymers	420						
Chlorinated Rubber	420						
Acrylic Polymers	420						
Urethane Polymers	420						
Silicones	420						
Unique Vehicles	420						
Japans/Faux Finishing Coatings	350	700		350			
Magnesite Cement Coatings	600			450			
Mastic Coatings	300						
Metallic Pigmented Coatings	500						
Multi-Color Coatings	420		250				
Pigmented Lacquer	680		550			275	
Pre-Treatment Wash Primers	780						
Primers, Sealers, and Undercoaters	350						
Quick-Dry Enamels	400						
Roof Coatings	300						
Shellac							
Clear	730						
Pigmented	550						
Stains	350						
Swimming Pool Coatings							
Repair	650						
Other	340						
Traffic Coatings	250		150				
Waterproofing Sealers	400						
Wood Preservatives							
Below-Ground	350						
Other	350						

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

TABLE OF STANDARDS (cont.)

VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 06-03-2011]

(1) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6) of Rule 1113, no person shall supply, sell, offer for sale, market, manufacture, blend, repackage, apply, store at a worksite, or solicit the application of any architectural coating within the District:

(A) That is listed in the Table of Standards 1 and contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified; or

(B) That is not listed in the Table of Standards 1, and contains VOC (excluding any colorant added to tint bases) in excess of 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, until January 1, 2014, at which time the limit drops to 50 grams of VOC per liter of coating, less water, less exempt compounds (0.42 pounds per gallon).

(2) No person within the District shall add colorant at the point of sale that is listed in the Table of Standards 2 and contains VOC in excess of the corresponding VOC limit specified in the Table of Standards 2, after the effective date specified.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 06-03-2011]

TABLE OF STANDARDS 1
VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water and Less Exempt Compounds

COATING CATEGORY	Ceiling Limit[1]	Current Limit[2]	Effective Date		
			7/1/08	1/1/12	1/1/14
Bond Breakers		350			
Clear Wood Finishes		275			
Varnish	350	275			
Sanding Sealers	350	275			
Lacquer		275			
Concrete-Curing Compounds		100			
Concrete-Curing Compounds For Roadways and Bridges[3]		350			
Concrete Surface Retarder		250			50
Driveway Sealer		100		50	
Dry-Fog Coatings		150			50
Faux Finishing Coatings					
Clear Topcoat		350		200	
Decorative Coatings		350			100
Glazes		350			
Japan		350			
Trowel Applied Coatings		350		150	50
Fire-Proofing Coatings		350			150
Flats	250	50	50		
Floor Coatings	100	50			
Form Release Compound		250			100
Graphic Arts (Sign) Coatings		500			150
Industrial Maintenance (IM) Coatings	420	100			
High Temperature IM Coatings		420			
Non-Sacrificial Anti-Graffiti Coatings		100			
Zinc-Rich IM Primers	340	100			
Magnesite Cement Coatings		450			
Mastic Coatings		300			100
Metallic Pigmented Coatings	500	500			150
Multi-Color Coatings		250			
Nonflat Coatings	150	50			
Pre-Treatment Wash Primers		420			
Primers, Sealers, and Undercoaters	200	100			
Reactive Penetrating Sealers		350			
Recycled Coatings		250			
Roof Coatings	250	50			
Roof Coatings, Aluminum		100			

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 06-03-2011]

Roof Primers, Bituminous	350	350			
Rust Preventative Coatings	400	100			
Stone Consolidant		450			
Sacrificial Anti-Graffiti Coatings		100		50	
Shellac					
Clear		730			
Pigmented		550			
Specialty Primers	350	100			
Stains		100			

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 06-03-2011]

COATING CATEGORY	Ceiling Limit[1]	Current Limit[2]	Effective Date		
			7/1/08	1/1/12	1/1/14
Stains, Interior	250	250			
Swimming Pool Coatings					
Repair		340			
Other		340			
Traffic Coatings		100			
Waterproofing Sealers	250	100			
Waterproofing Concrete/Masonry Sealers	400	100			
Wood Preservatives		350			

1. The specified ceiling limits are applicable to products sold under the Averaging Compliance Option.
2. The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.
3. Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

TABLE OF STANDARDS 1 (cont.)
VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

TABLE OF STANDARDS 2
VOC LIMITS FOR COLORANTS

Grams of VOC Per Liter of Colorant
Less Water and Less Exempt Compounds

COLORANT	Limit[4]
Architectural Coatings, excluding IM Coatings	50
Solvent-Based IM	600
Waterborne IM	50

4. Effective January 1, 2014.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1130.1 12-13-1996]

Except as otherwise provided in Rule 1130.1

(1) VOC Content of Screen Printing Materials

The operator shall not apply to any substrate any screen printing material, excluding extreme performance screen printing materials, which contains, as applied, a total amount of VOC in excess of the limits specified in subparagraphs (1)(A), (1)(B), or (1)(C). The applicable VOC limit for a screen printing operation shall be determined by first looking for the product in subparagraph (1)(A). If the product is not listed in subparagraph (1)A), look for the product's substrate in subparagraph (1)(B). If the substrate is not listed in subparagraph (1)(B), look for the applicable limit in subparagraph (1)(C).

In lieu of meeting the requirements in subparagraph (1)(C), the operator may comply with the requirements in paragraph (2) if the screen printing material qualifies for an extreme performance classification under subdivision (e) of Rule 1130.1.

(A) For screen printing coatings and inks used in the production of the following products:

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1130.1 12-13-1996]

PRODUCT	VOC LIMIT grams per Liter of Coating (or Ink), Less water and Less Exempt Compounds On and After December 13, 1996	
	g/L-	lbs/gal-
Chlorine Indicator	500	4.2
Containers	800	6.7
Electronic Circuit	850	7.1
Mechanically-Formed Products	800	6.7
Overlays	800	6.7
Polyethylene Products	800	6.7
Stained Glass Overlay	800	6.7
Sterilization Indicator	600	5.0
Sub-Printed Products	800	6.7
Water Slide Decals:		
Opaque Inks	800	6.7
Clear Inks	800	6.7
Ceramic Decal Inks	800	6.7

(B) For screen printing coatings and inks not regulated by subparagraph (1)(A) and which are applied to the following specified substrates:

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1130.1 12-13-1996]
VOC LIMIT

SUBSTRATE	grams per Liter of Coating (or Ink), Less water and Less Exempt Compounds	
	On and After December 13, 1996	
	g/L	lbs/gal
Ceramic	800	6.7
Fiberglass	600	5.0
Glass or Metal	600	5.0
Man-Made Textile	800	6.7
Unsealed Aluminum	800	6.7

If a substrate is regulated under more than one substrate category listed in subparagraph (1)(B), the category with the highest VOC limit shall apply.

(C) For screen printing materials not regulated by the provisions in subparagraph (1)(A) or (1)(B), which have the following material classifications:

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1130.1 12-13-1996]

SCREEN PRINTING MATERIAL	VOC LIMIT grams per Liter of Coating (or Ink or Adhesive), Less water and Less Exempt Compounds	
	On and After December 13, 1996	
	g/L	lbs/gal
Adhesive	400	3.3
Coating	400	3.3
Fine Detail Loose-leaf Binder Ink	745	6.2
Fluorescent Ink	540	4.5
High-VOC Serigraph Ink	800	6.7
Loose-leaf Binder Metallic Ink	745	6.2
Metallic Ink	400	3.3
Printing Ink	400	3.3
Resists	600	5.0
Scratch-Off Ink	800	6.7
Water-Slide Decal Adhesive	800	6.7

If a screen printing material is regulated under more than one screen printing material category listed in subparagraph (1)(C), the category with the highest VOC limit shall apply.

(2) VOC Content of Extreme Performance Screen Printing Materials

The operator shall not apply any extreme performance screen printing material in excess of the limits specified below:

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1130.1 12-13-1996]

	VOC LIMIT Grams of VOC per Liter of ExtremePerformance Screen Printing Material, Less Water and Less Exempt Compounds	
	g/L	lbs/gal
On and after July 9, 1993	800	6.7
On and after January 1, 2003	400	3.3

(3) Usage of High-VOC Serigraph Inks

The total usage of high-VOC serigraph inks, as defined in paragraph (b)(23) of Rule 1130.1, shall not exceed 10 percent, (by volume), of the total usage of screen printing materials applied on all serigraphs at a facility, on a monthly basis, unless an approved emission control system is used to reduce emissions from high-VOC serigraph inks by an equivalent or greater level to that which would have been achieved by the use of an ink containing 3.3 pounds per gallon VOC (less water and exempt compounds). The required overall control efficiency of the emission control system shall be determined by the equation in paragraph (d)(1) of Rule 1130.1.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1140 02-01-1980]

(1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines, or

(B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).

(2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or

(B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1140 08-02-1985]

(1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines, or

(B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).

(2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or

(B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1145 12-04-2009]

Except as otherwise provided in Rule 1145, no person shall apply on plastics, rubber, leather, or glass any coatings which are applied with a VOC content in excess of the limits listed in the Table of Standards.

TABLE OF STANDARDS

VOC LIMITS LESS WATER AND LESS EXEMPT COMPOUNDS		
COATING CATEGORIES	g/L	lbs/gal
Electrical dissipating and shock free coatings	360	3.0
Extreme performance two-component coatings	420	3.5
General one-component coatings	120	1.0
General two-component coatings	120	1.0
Leather antique coatings	156	1.3
Leather color coatings	60	0.5
Leather sealer coatings	60	0.5
Leather stain coatings	216	1.8
Leather top coatings	120	1.0
Metallic coatings	420	3.5
Military specification one-component coatings	340	2.8
Military specification two-component coatings	420	3.5
Mirror backing curtain coated coatings	500	4.2
Mirror backing rolled coated coatings	312	2.6
Mold seal coatings	750	6.3
Multi-color coatings	680	5.7
Refrigerated glass door coatings	480	4.0
Optical coatings	50	0.4
Vacuum metalizing coatings	800	6.7

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1145 02-14-1997]

Except as otherwise provided in Rule 1145, the operator shall not apply on plastics, glass, or rubber any coatings which are applied with a VOC content in excess of the limits specified below:

COATING	VOC LIMITS Less Water and Less Exempt Compounds			
	Current		On and After 1-1-98	
	g/L	lbs/gal	g/L	lbs/gal
General Coatings				
One-component	275	2.3	275	2.3
Two-component	420	3.5	420	3.5
Military Spec. Coating				
One-component	340	2.8	340	2.8
Two-component	420	3.5	420	3.5
Multi-Colored Coatings	685	5.7	685	5.7
Mold Seal Coatings	750	6.3	750	6.3
Vacuum Metalizing Coatings	800	6.7	800	6.7
Mirror Backing				
Curtain Coated	500	4.2	500	4.2
Roll Coated	430	3.6	430	3.6
Optical Coatings	800	6.7	800	6.7
Electric Dissipating Coatings and Shock-Free Coatings	800	6.7	360	3.0
Metallic Coatings	420	3.5	420	3.5

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	500 (4.2)
(iii) Medical Devices & Pharmaceuticals	800 (6.7)
(B) Repair and Maintenance Cleaning	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals	
(A) Tools, Equipment, & Machinery	800 (6.7)
(B) General Work Surfaces	600 (5.0)
(C) Cleaning of Coatings or Adhesives Application Equipment	550 (4.6)
(D) Cleaning of Ink Application Equipment	
(i) General	25 (0.21)
(ii) Flexographic Printing	25 (0.21)
(iii) Gravure Printing	
(A) Publication	750 (6.3)
(B) Packaging	25 (0.21)
(iv) Lithographic or Letter Press Printing	

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS VOC g/l (lb/gal)
(A) Roller Wash – Step 1	600 (5.0)
(B) Roller Wash-Step 2, Blanket Wash, & On-Press Components	800 (6.7)
(C) Removable Press Components	25 (0.21)
(v) Screen Printing	750 (6.3)
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	800 (6.7)
(vii) Specialty Flexographic Printing	600 (5.0)
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 05-01-2009]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY	**VOC g/l (lb/gal)**	**VOC g/l (lb/gal)**
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals	800 (6.7)	
(B) Repair and Maintenance Cleaning		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	**VOC g/l (lb/gal)**	**VOC g/l (lb/gal)**
(iii) Medical Devices & Pharmaceuticals		
(A) Tools, Equipment, & Machinery	800 (6.7)	
(B) General Work Surfaces	600 (5.0)	
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)	
(D) Cleaning of Ink Application Equipment		
(i) General	25 (0.21)	
(ii) Flexographic Printing	25 (0.21)	
(iii) Gravure Printing		
(A) Publication	100 (0.83)	
(B) Packaging	25 (0.21)	
(iv) Lithographic (Offset) or Letter Press Printing		
(A) Roller Wash, Blanket Wash, & On-Press Components	100 (0.83)	

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	**VOC g/l (lb/gal)**	**VOC g/l (lb/gal)**
(B) Removable Press Components	25 (0.21)	
(v) Screen Printing	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)	
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)	

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 404 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter"Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter"Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter"Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 405 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
100 or less	220 or less	0.450	0.99	9000	19840	5.308	11.7
150	331	0.585	1.29	10000	22050	5.440	12.0
200	441	0.703	1.55	12500	27560	5.732	12.6
250	551	0.804	1.77	15000	33070	5.982	13.2
300	661	0.897	1.98	17500	38580	6.202	13.7
350	772	0.983	2.17	20000	44090	6.399	14.1
400	882	1.063	2.34	25000	55120	6.743	14.9
450	992	1.138	2.51	30000	66140	7.037	15.5
500	1102	1.209	2.67	35000	77160	7.296	16.1
600	1323	1.340	2.95	40000	88180	7.527	16.6

FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC

APPENDIX B: RULE EMISSION LIMITS
[RULE 405 02-07-1986]

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
700	1543	1.461	3.22	45000	99210	7.738	17.1
800	1764	1.573	3.47	50000	110200	7.931	17.5
900	1984	1.678	3.70	60000	132300	8.277	18.2
1000	2205	1.777	3.92	70000	154300	8.582	18.9
1250	2756	2.003	4.42	80000	176400	8.854	19.5
1500	3307	2.206	4.86	90000	198400	9.102	20.1
1750	3858	2.392	5.27	100000	220500	9.329	20.6
2000	4409	2.563	5.65	125000	275600	9.830	21.7
2250	4960	2.723	6.00	150000	330700	10.26	22.6
2500	5512	2.874	6.34	175000	385800	10.64	23.5
2750	6063	3.016	6.65	200000	440900	10.97	24.2
3000	6614	3.151	6.95	225000	496000	11.28	24.9
3250	7165	3.280	7.23	250000	551200	11.56	25.5
3600	7716	3.404	7.50	275000	606300	11.82	26.1
4000	8818	3.637	8.02	300000	661400	12.07	26.6
4500	9921	3.855	8.50	325000	716500	12.30	27.1
5000	11020	4.059	8.95	350000	771600	12.51	27.6
6000	13230	4.434	9.78	400000	881800	12.91	28.5
7000	15430	4.775	10.5	450000	992100	13.27	29.3
8000	17640	5.089	11.2	500000 or more	1102000 or more	13.60	30.0