



FACILITY PERMIT TO OPERATE


ULTRAMAR INC (NSR USE ONLY)
961 LA PALOMA AVE
WILMINGTON, CA 90744

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By 
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC (NSR USE ONLY)**

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	0	04/06/2009
B	RECLAIM Annual Emission Allocation	0	04/06/2009
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	2	07/06/2012
E	Administrative Conditions	0	04/06/2009
F	RECLAIM Monitoring and Source Testing Requirements	0	04/06/2009
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	0	04/06/2009
H	Permit To Construct and Temporary Permit to Operate	2	07/06/2012
I	Compliance Plans & Schedules	0	04/06/2009
J	Air Toxics	0	04/06/2009
K	Title V Administration	0	04/06/2009
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	0	04/06/2009
B	Rule Emission Limits	0	04/06/2009



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

**Facility Equipment and Requirements
(Section D)**

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements. Also included are the rule origin and authority of each emission limit and permit condition.

**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO OPERATE AT THIS FACILITY:

Application Number	Permit to Operate Number	Equipment Description	Page Number
178046	D07198	MARINE BULK LOADING/UNLOADING PETROLEUM MIDDLE DISTILLATE	4
178051	D07203	WASTEWATER TREATING	6
178053	D07205	RAILCAR LOADING/UNLOADING CRUDE OIL	8
178055	D07207	TANK TRUCK UNLOADING PETROLEUM MIDDLE DISTILLATE	10
328976	F11333	ICE (50-500 HP) EM FIRE FIGHT - DIESEL	12
328977	F11335	ICE (50-500 HP) EM FIRE FIGHT - DIESEL	14
433789	F70668	STORAGE TANK FX RF W/ INT FLT GAS-OIL (NO. 99-TK-120001)	16
433791	F70669	STORAGE TANK FX RF W/ INT FLT GAS-OIL (NO. 99-TK-120002)	18
433792	F70670	STORAGE TANK FX RF W/ INT FLT GAS-OIL (NO. 99-TK-120003)	20
433793	F70671	STORAGE TANK FX RF W/ INT FLT GAS-OIL (NO. 99-TK-120004)	22
433794	F70672	STORAGE TANK FX RF W/ INT FLT GAS-OIL (NO. 99-TK-42501)	24
433795	F70673	STORAGE TANK FX RF W/ INT FLT GAS-OIL (NO. 99-TK-42502)	26
443859	G18976	STORAGE TANK , DOMED EXT FLOAT ROOF, GAS-OIL (NO. 99-TK-67001)	28
443860	G18977	STORAGE TANK, DOMED EXT FLOAT ROOF, GAS-OIL (NO. 99-TK-67002)	30
443861	G18978	STORAGE TANK, DOMED EXT FLOAT ROOF, GAS-OIL (NO. 99-TK-67003)	32
443862	G18979	STORAGE TANK, DOMED EXT FLOAT ROOF, GAS-OIL (NO. 99-TK-67004)	34
448253	G18980	STORAGE TANK FX RF W/ INT FLT GAS-OIL (NO. 99-TK-7301)	36
448254	G18981	STORAGE TANK FX RF W/ INT FLT GAS-OIL (NO. 99-TK-7302)	38
448255	G18982	STORAGE TANK FX RF W/ INT FLT GAS-OIL (NO. 99-TK-11001)	40
448256	G18983	STORAGE TANK FX RF W/ INT FLT GAS-OIL (NO. 99-TK-21001)	42

NOTE: ANY APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

FACILITY WIDE CONDITION(S)

Condition(s):

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:
 - A. AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGELMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
 - B. OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (A) OF THIS CONDITION.
[RULE 401]

2. MATERIAL SAFETY DATA SHEETS FOR ALL COATINGS AND SOLVENTS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

3. THIS FACILITY SHALL COMPLY WITH THE APPLICABLE REQUIREMENTS OF RULE 431.1 AND RULE 431.2.
[RULE 431.1, RULE 431.2]

4. THIS FACILITY SHALL COMPLY WITH THE APPLICABLE REQUIREMENTS OF RULE 1173.
[RULE 1173]

**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. D07198
A/N 178046**

Equipment Description:

MARINE TERMINAL BULK LOADING/UNLOADING FACILITY CONSISTING OF :

1. TWO LOADING/UNLOADING ARMS AT HARBOR BERTH 164, ONE WITH FOUR 8 INCH PIPELINE RISERS, AND ONE WITH SIX 8 INCH PIPELINE RISERS, EACH EQUIPPED WITH GATE VALVE, FLANGES AND FLEXIBLE HOSES CONNECTING TO SHIP MANIFOLDS.
2. ONE LOADING/UNLOADING ARM AT HARBOR BERTH 163, WITH SIX 8 INCH PIPELINE RISERS, EQUIPPED WITH GATE VALVE, FLANGES AND FLEXIBLE HOSES CONNECTING TO SHIP MANIFOLDS.
3. COLLECTION SUMP, 4'-0" W. X 4'0" L. X 6'0" D.
4. LOADING PUMPS NOS. 2 AND 15, EACH CENTRIFUGAL TYPE, WITH MECHANICAL SEALS AND A 200 HP MOTOR
5. LOADING PUMP NO. 4, POSITIVE DISPLACEMENT TYPE, WITH PACKING GLAND AND A 125 HP MOTOR
6. LOADING PUMP NO. 14, CENTRIFUGAL TYPE, WITH MECHANICAL SEALS AND A 150 HP MOTOR
7. LOADING PUMPS NOS. 21 AND 22, EACH CENTRIFUGAL TYPE, WITH MECHANICAL SEALS AND A 300 HP MOTOR
8. SUMP PUMP, CENTRIFUGAL TYPE, WITH A MECHANICAL SEAL AND A 7-1/2 HP MOTOR
9. TRANSFER LINE DRAIN PUMP, POSITIVE DISPLACEMENT TYPE, WITH A PACKING GLAND AND A 15 HP MOTOR.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.

[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.

[RULE 204]



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID AQMD PERMIT.
[RULE 1303(a)(1) - BACT]

4. THIS EQUIPMENT SHALL ONLY USE GAS OIL, DECANT OIL, DIESEL OIL AND LIGHT CYCLE OIL, EACH WITH A TRUE VAPOR PRESSURE OF 0.4 PSIA OR LESS UNDER ACTUAL OPERATING CONDITIONS DURING LOADING OPERATION.
[RULE 1303(b)(2) - OFFSET, RULE 1401, RULE 431.1]

5. THE OPERATOR SHALL LIMIT THE COMBINED THROUGHPUT OF BARGE AND SHIP LOADING TO NO MORE THAN 300,000 BARRELS IN ANY ONE CALENDAR MONTH.
[RULE 1303(b)(2) - OFFSET]

6. THE OPERATOR SHALL LOAD NO MORE THAN 9 SHIPS IN ANY ONE CALENDAR YEAR.
[RULE 1303(b)(2) - OFFSET]

7. THE OPERATOR SHALL LOAD NO MORE THAN 10 BARGES IN ANY ONE CALENDAR MONTH.
[RULE 1303(b)(2) - OFFSET]

8. RECORDS SHALL BE MAINTAINED AND KEPT AVAILABLE FOR INSPECTION TO DEMONSTRATE COMPLIANCE WITH THE SPECIFIED CONDITIONS.
[RULE 204, RULE 1303(b)(2) - OFFSET]

Periodic Monitoring: NONE

Emissions and Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: 2 LBS VOC PER 1000 BARRELS ORGANIC LIQUID LOADED, RULE 1142

**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. D07203
A/N 178051**

Equipment Description:

OILY WATER GATHERING AND SEPARATING SYSTEM CONSISTING OF:

1. OIL-WATER SEPARATOR TANK, CAPACITY 19,950 GALLONS, 11'-3" DIA. X 27'-0" H.
2. SLOP OIL ACCUMULATOR TANK, CAPACITY 19,950 GALLONS, 11'-3" DIA. X 27'-0" H.
3. DOCK SUMP PUMP, WELL-TYPE VERTICAL CENTRIFUGAL WITH A 7-1/2 HP MOTOR
4. HATER AREA SUMP PUMP, WELL-TYPE VERTICAL CENTRIFUGAL WITH A 1 HP MOTOR
5. PARCEL NO. 1 TANK FARM API GRAVITY SEPARATOR
6. PARCEL NO. 1 TANK FARM SUMP PUMP, WELL-TYPE VERTICAL CENTRIFUGAL WITH A 7-1/2 HP MOTOR
7. PUMP HOUSE AREA SUMP PUMP, WELL-TYPE VERTICAL CENTRIFUGAL WITH A 7-1/2 HP MOTOR
8. PUMP P-15, WELL-TYPE, VERTICAL CENTRIFUGAL WITH A 7-1/2 HP MOTOR
9. NEW TANKAGE AREA API GRAVITY SEPARATOR
10. NEW TANKAGE AREA SUMP PUMP, SUBMERGED WITH A 7-1/2 HP MOTOR
11. TRUCK LOADING RACK AREA SUMP PUMP, WELL-TYPE VERTICAL CENTRIFUGAL, WITH A 7-1/2 HP MOTOR
12. PARCEL NO. 3 TANK FARM API GRAVITY SEPARATOR.
13. SLOPS HANDLING PUMP, RECIPROCATING WITH A 10 HP MOTOR

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.

[RULE 204]



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.

[RULE 204]

3. THIS EQUIPMENT MUST NOT BE USED TO RECOVER 7,600 LITERS (201 GALLONS) OR MORE PER DAY OF PETROLEUM PRODUCTS FROM ANY EQUIPMENT WHICH PROCESSES, REFINES, STORES OR HANDLES HYDROCARBONS WITH A REID VAPOR PRESSURE OF 25 MMHG (0.5 PSIA) OR GREATER.

[RULE 1303(b)(2) - OFFSET]

Periodic Monitoring: NONE

Emissions and Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 464



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. D07205
A/N 178053**

Equipment Description:

SOUTH TRUCK LOADING/UNLOADING FACILITY CONSISTING OF:

1. ONE 4" LOADING SPOUT
2. TWO 4" UNLOADING CONNECTIONS.
3. ONE METER, A. O. SMITH
4. LOADING/UNLOADING PUMP, VIKING WITH PACKED GLAND AND 30 HP MOTOR

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE TOTAL COMBINED LOADING LIMIT FOR EQUIPMENT LOADING ORGANIC LIQUIDS HAVING A VAPOR PRESSURE OF 77.5 MM HG (1.5 PSIA) OR GREATER UNDER ACTUAL LOADING CONDITIONS SHALL NOT EXCEED 19999 GALLONS PER DAY.
[RULE 462, RULE 1303(b)(2) - OFFSET]
4. THIS EQUIPMENT SHALL NOT BE USED FOR LOADING GASOLINE.
[RULE 1303(b)(2) - OFFSET]



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 462



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. D07207
A/N 178055**

Equipment Description:

TANK TRUCK UNLOADING FACILITY (NORTH RACK) CONSISTING OF:

1. FOUR 4" UNLOADING CONNECTIONS.
2. ONE METER, A. O. SMITH.
3. UNLOADING PUMP, PEERLESS, CENTRIFUGAL, WITH MECHANICAL SEAL AND A 40 HP MOTOR
4. LOADING/UNLOADING PUMP, INGERSOLL-RAND, CHEMLINER WITH MECHANICAL SEAL AND 40 HP MOTOR (COMMON TO TANK CAR LOADING FACILITY AND R.R./TANK TRUCK LOADING/UNLOADING FACILITY)

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE TOTAL COMBINED LOADING LIMIT FOR EQUIPMENT LOADING ORGANIC LIQUIDS HAVING A VAPOR PRESSURE OF 77.5 MM HG (1.5 PSIA) OR GREATER UNDER ACTUAL LOADING CONDITIONS SHALL NOT EXCEED 19999 GALLONS PER DAY.

[RULE 462, RULE 1303(b)(2) - OFFSET]



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

Emissions and Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 462

**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. F11333
A/N 328976**

Equipment Description:

INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, 99-P-40, DIESEL FUEL, CUMMINS, MODEL NO. V-378-F2, SERIAL NO. 20230035. 137 HP @ 3300 RPM

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL LIMIT THE OPERATING TIME TO NO MORE THAN 199 HOURS IN ANY ONE YEAR.
[RULE 1304(a)(4) - MODELING AND OFFSET EXEMPTION]
4. THE OPERATOR SHALL INSTALL AND MAINTAIN A NON-RESETTABLE ELAPSED TIME METER TO ACCURATELY INDICATE THE ELAPSED OPERATING TIME OF THE ENGINE.
[[RULE 1304(a)(4) - MODELING AND OFFSET EXEMPTION]
5. THE OPERATOR SHALL INSPECT, ADJUST, AND CERTIFY THE IGNITION OR FUEL INJECTION TIMING OF THIS ENGINE A MINIMUM OF ONCE EVERY THREE YEARS OF OPERATION. INSPECTIONS, ADJUSTMENTS, AND CERTIFICATIONS SHALL BE PERFORMED BY A QUALIFIED MECHANIC AND PERFORMED IN ACCORDANCE WITH THE ENGINE MANUFACTURER'S SPECIFICATIONS AND PROCEDURES.
[RULE 1303(a)(1) - BACT]



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

6. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETERS:

THE DATE OF OPERATION, THE ELAPSED TIME IN HOURS AND THE REASONS FOR OPERATION.

[RULE 204]

Periodic Monitoring: NONE

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 1470

**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. F11335
A/N 328977**

Equipment Description:

INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, 99-P-41, DIESEL FUEL, CUMMINS, MODEL NO. NT-855-F2, SERIAL NO. 10307631, 285 HP @ 1750 RPM, TURBOCHARGED

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL LIMIT THE OPERATING TIME TO NO MORE THAN 199 HOURS IN ANY ONE YEAR.
[RULE 1304(a)(4) - MODELING AND OFFSET EXEMPTION]
4. THE OPERATOR SHALL INSTALL AND MAINTAIN A NON-RESETTABLE ELAPSED TIME METER TO ACCURATELY INDICATE THE ELAPSED OPERATING TIME OF THE ENGINE.
[RULE 1304(a)(4) - MODELING AND OFFSET EXEMPTION]
5. THE OPERATOR SHALL INSPECT, ADJUST, AND CERTIFY THE IGNITION OR FUEL INJECTION TIMING OF THIS ENGINE A MINIMUM OF ONCE EVERY THREE YEARS OF OPERATION. INSPECTIONS, ADJUSTMENTS, AND CERTIFICATIONS SHALL BE PERFORMED BY A QUALIFIED MECHANIC AND PERFORMED IN ACCORDANCE WITH THE ENGINE MANUFACTURER'S SPECIFICATIONS AND PROCEDURES.
[RULE 1303(a)(1) - BACT]



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

6. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETERS:

THE DATE OF OPERATION, THE ELAPSED TIME IN HOURS AND THE REASONS FOR OPERATION.

[RULE 204]

Periodic Monitoring: NONE

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 1470

**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. F70668
A/N 433789**

Equipment Description:

STORAGE TANK, INTERNAL FLOATING ROOF, NO 99-TK-120001, WELDED SHELL, 120000 BBL, 134'-0" DIA. X 50'-0" H., WITH FLOATING ROOF, PONTOON, WITH METALLIC SHOE-TYPE PRIMARY SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 50 PERCENT OF THE LOWER EXPLOSIVE LIMIT. THE OPERATOR SHALL USE AN EXPLOSIMETER TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE A YEAR AT A 4 TO 8 MONTH INTERVAL TO ENSURE COMPLIANCE WITH THIS CONDITION.
[RULE 463, RULE 1178]
4. THE OPERATOR SHALL KEEP RECORDS, IN MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

TYPE OF LIQUID STORED, THROUGHPUT, AND TRUE VAPOR PRESSURE OF LIQUIDS UNDER ACTUAL STORAGE CONDITIONS.

[RULE 463, 40 CFR 60 SUBPART K]



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

Periodic Monitoring: NONE

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC/TOC: 40 CFR 60 SUBPART K
VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. F70669
A/N 433791**

Equipment Description:

STORAGE TANK, INTERNAL FLOATING ROOF, NO. 99-TK-120002, WELDED SHELL, 120000 BBL; 134'-0" DIA. X 50'-0" H., WITH FLOATING ROOF, PONTOON, WITH A METALLIC SHOE-TYPE PRIMARY SEAL AND A WIPER TYPE SECONDARY SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 50 PERCENT OF THE LOWER EXPLOSIVE LIMIT. THE OPERATOR SHALL USE AN EXPLOSIMETER TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE A YEAR AT A 4 TO 8 MONTH INTERVAL TO ENSURE COMPLIANCE WITH THIS CONDITION.
[RULE 463, RULE 1178]
4. THE OPERATOR SHALL KEEP RECORDS, IN MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

TYPE OF LIQUID STORED, THROUGHPUT, AND TRUE VAPOR PRESSURE OF LIQUIDS UNDER ACTUAL STORAGE CONDITIONS.

[RULE 463, 40 CFR 60 SUBPART K]



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

Periodic Monitoring: NONE

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC/TOC: 40 CFR 60 SUBPART K
VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. F70670
A/N 433792**

Equipment Description:

STORAGE TANK, INTERNAL FLOATING ROOF, NO 99-TK-120003, WELDED SHELL, 120000 BBL, 134'-0" DIA. X 50'-0" H., WITH FLOATING ROOF, PONTOON, WITH A METALLIC SHOE-TYPE PRIMARY SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 50 PERCENT OF THE LOWER EXPLOSIVE LIMIT. THE OPERATOR SHALL USE AN EXPLOSIMETER TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE A YEAR AT A 4 TO 8 MONTH INTERVAL TO ENSURE COMPLIANCE WITH THIS CONDITION.
[RULE 463, RULE 1178]
4. THE OPERATOR SHALL KEEP RECORDS, IN MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

TYPE OF LIQUID STORED, THROUGHPUT, AND TRUE VAPOR PRESSURE OF LIQUIDS UNDER ACTUAL STORAGE CONDITIONS.

[RULE 463, 40 CFR 60 SUBPART K]



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

Periodic Monitoring: NONE

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC/TOC: 40 CFR 60, SUBPART K
VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178

**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. F70671
A/N 433793**

Equipment Description:

STORAGE TANK, INTERNAL FLOATING ROOF, NO 99-TK-120004, WELDED SHELL, 120000 BBL, 134'-0" DIA. X 50'-0" H., WITH FLOATING ROOF, PONTOON, WITH A METALLIC SHOE-TYPE PRIMARY SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 50 PERCENT OF THE LOWER EXPLOSIVE LIMIT. THE OPERATOR SHALL USE AN EXPLOSIMETER TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE A YEAR AT A 4 TO 8 MONTH INTERVAL TO ENSURE COMPLIANCE WITH THIS CONDITION.
[RULE 463, RULE 1178]
4. THE OPERATOR SHALL KEEP RECORDS, IN MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

TYPE OF LIQUID STORED, THROUGHPUT, AND TRUE VAPOR PRESSURE OF LIQUIDS UNDER ACTUAL STORAGE CONDITIONS.

[RULE 463, 40 CFR 60 SUBPART K]



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

Periodic Monitoring: NONE

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC/TOC: 40 CFR 60 SUBPART K
VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. F70672
A/N 433794**

Equipment Description:

STORAGE TANK, INTERNAL FLOATING ROOF, NO 99-TK-42501, WELDED SHELL, 42500 BBL, 80'-0" DIA. X 50'-0" H., WITH FLOATING ROOF, PONTOON, WITH A METALLIC SHOE-TYPE PRIMARY SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 50 PERCENT OF THE LOWER EXPLOSIVE LIMIT. THE OPERATOR SHALL USE AN EXPLOSIMETER TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE A YEAR AT A 4 TO 8 MONTH INTERVAL TO ENSURE COMPLIANCE WITH THIS CONDITION.
[RULE 463, RULE 1178]

4. THE OPERATOR SHALL KEEP RECORDS, IN MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

TYPE OF LIQUID STORED, THROUGHPUT, AND TRUE VAPOR PRESSURE OF LIQUIDS UNDER ACTUAL STORAGE CONDITIONS.

[RULE 463, 40 CFR 60 SUBPART K]



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

Periodic Monitoring: NONE

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC/TOC: 40 CFR 60 SUBPART K
VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. F70673
A/N 433795**

Equipment Description:

STORAGE TANK, INTERNAL FLOATING ROOF, NO. 99-TK-42502, WELDED SHELL, 42500 BBL; 80'-0" DIA. X 50'-0" H., WITH FLOATING ROOF, PONTOON, WITH METALLIC SHOE-TYPE PRIMARY SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 50 PERCENT OF THE LOWER EXPLOSIVE LIMIT. THE OPERATOR SHALL USE AN EXPLOSIMETER TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE A YEAR AT A 4 TO 8 MONTH INTERVAL TO ENSURE COMPLIANCE WITH THIS CONDITION.
[RULE 463, RULE 1178]
4. THE OPERATOR SHALL KEEP RECORDS, IN MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

TYPE OF LIQUID STORED, THROUGHPUT, AND TRUE VAPOR PRESSURE OF LIQUIDS UNDER ACTUAL STORAGE CONDITIONS.

[RULE 463, 40 CFR 60 SUBPART K]



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

Periodic Monitoring: NONE

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC/TOC: 40 CFR 60 SUBPART K
VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. G18976
A/N 443859**

Equipment Description:

TANK NO. 99-TK-67001, DOMED EXTERNAL FLOATING ROOF, CAPACITY 67,000 BARRELS, 100'-0" DIA X 48'-0" H, PONTOON, WELDED SHELL, WITH MECHANICAL SHOE PRIMARY SEAL, WIPER TYPE SECONDARY SEAL, AND A GEODESIC DOME COVER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.

[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.

[RULE 204]

3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE FLOATING ROOF DOES NOT EXCEED 30 PERCENT OF THE LOWER EXPLOSIVE LIMIT (LEL). AN EXPLOSIMETER SHALL BE USED TO MONITOR THE HYDROCARBON CONCENTRATION TWICE PER YEAR AT 4 TO 8 MONTH INTERVALS. ADEQUATE RECORDS SHALL BE KEPT TO SHOW COMPLIANCE WITH THIS CONDITION.

[RULE 463, 1178]

4. THE OPERATOR SHALL LIMIT THE USE AND THROUGHPUT TO NO MORE THAN 2,037,917 BARRELS PER CALENDAR MONTH OF ORGANIC LIQUIDS NOT TO EXCEED A TRUE VAPOR PRESSURE OF 11 PSIA UNDER ACTUAL STORAGE CONDITIONS.

RULE 1303(b)(2)-OFFSETS

5. THE OPERATOR SHALL KEEP RECORDS, IN MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

TYPE OF LIQUID STORED, THROUGHPUT, AND TRUE VAPOR PRESSURE OF LIQUIDS UNDER ACTUAL STORAGE CONDITIONS.

[RULE 463]



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

Periodic Monitoring: NONE

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. G18977
A/N 443860**

Equipment Description:

TANK NO. 99-TK-67002, DOMED EXTERNAL FLOATING ROOF, CAPACITY 67,000 BARRELS, 100'-0" DIA X 48'-0" H, PONTOON, WELDED SHELL, WITH MECHANICAL SHOE PRIMARY SEAL, WIPER TYPE SECONDARY SEAL AND A GEODESIC DOME COVER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE FLOATING ROOF DOES NOT EXCEED 30 PERCENT OF THE LOWER EXPLOSIVE LIMIT (LEL). AN EXPLOSIMETER SHALL BE USED TO MONITOR THE HYDROCARBON CONCENTRATION TWICE PER YEAR AT 4 TO 8 MONTH INTERVALS. ADEQUATE RECORDS SHALL BE KEPT TO SHOW COMPLIANCE WITH THIS CONDITION.
[RULE 463, 1178]
4. THE OPERATOR SHALL LIMIT THE USE AND THROUGHPUT TO NO MORE THAN 2,037,917 BARRELS PER CALENDAR MONTH OF ORGANIC LIQUIDS NOT TO EXCEED A TRUE VAPOR PRESSURE OF 11 PSIA UNDER ACTUAL STORAGE CONDITIONS.
RULE 1303(b)(2)-OFFSETS
5. THE OPERATOR SHALL KEEP RECORDS, IN MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
TYPE OF LIQUID STORED, THROUGHPUT, AND TRUE VAPOR PRESSURE OF LIQUIDS UNDER ACTUAL STORAGE CONDITIONS.
[RULE 463]

Periodic Monitoring: NONE



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. G18978
A/N 443861**

Equipment Description:

TANK NO. 99-TK-67003, DOMED EXTERNAL FLOATING ROOF, CAPACITY 67,000 BARRELS, 100'-0" DIA X 48'-0" H, PONTOON, WELDED SHELL, WITH MECHANICAL SHOE PRIMARY SEAL, WIPER TYPE SECONDARY SEAL AND A GEODESIC DOME COVER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE FLOATING ROOF DOES NOT EXCEED 30 PERCENT OF THE LOWER EXPLOSIVE LIMIT (LEL). AN EXPLOSIMETER SHALL BE USED TO MONITOR THE HYDROCARBON CONCENTRATION TWICE PER YEAR AT 4 TO 8 MONTH INTERVALS. ADEQUATE RECORDS SHALL BE KEPT TO SHOW COMPLIANCE WITH THIS CONDITION.
[RULE 463, 1178]
4. THE OPERATOR SHALL LIMIT THE USE AND THROUGHPUT TO NO MORE THAN 2,037,917 BARRELS PER CALENDAR MONTH OF ORGANIC LIQUIDS NOT TO EXCEED A TRUE VAPOR PRESSURE OF 11 PSIA UNDER ACTUAL STORAGE CONDITIONS.
RULE 1303(b)(2)-OFFSETS
5. THE OPERATOR SHALL KEEP RECORDS, IN MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
TYPE OF LIQUID STORED, THROUGHPUT, AND TRUE VAPOR PRESSURE OF LIQUIDS UNDER ACTUAL STORAGE CONDITIONS.
[RULE 463]



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

Periodic Monitoring: NONE

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178

**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. G18979
A/N 443862**

Equipment Description:

TANK NO. 99-TK-67004, DOMED EXTERNAL FLOATING ROOF, CAPACITY 67,000 BARRELS, 100'-0" DIA X 48'-0" H, PONTOON, WELDED SHELL, WITH MECHANICAL SHOE PRIMARY SEAL, WIPER TYPE SECONDARY SEAL AND A GEODESIC DOME COVER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE FLOATING ROOF DOES NOT EXCEED 30 PERCENT OF THE LOWER EXPLOSIVE LIMIT (LEL). AN EXPLOSIMETER SHALL BE USED TO MONITOR THE HYDROCARBON CONCENTRATION TWICE PER YEAR AT 4 TO 8 MONTH INTERVALS. ADEQUATE RECORDS SHALL BE KEPT TO SHOW COMPLIANCE WITH THIS CONDITION.
[RULE 463, 1178]
4. THE OPERATOR SHALL LIMIT THE USE AND THROUGHPUT TO NO MORE THAN 2,037,917 BARRELS PER CALENDAR MONTH OF ORGANIC LIQUIDS NOT TO EXCEED A TRUE VAPOR PRESSURE OF 11 PSIA UNDER ACTUAL STORAGE CONDITIONS.
RULE 1303(b)(2)-OFFSETS
5. THE OPERATOR SHALL KEEP RECORDS IN MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
TYPE OF LIQUID STORED, THROUGHPUT, AND TRUE VAPOR PRESSURE OF LIQUIDS UNDER ACTUAL STORAGE CONDITIONS.
[RULE 463]



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

Periodic Monitoring: NONE

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. G18980
A/N 448253**

Equipment Description:

TANK NO. 99-TK-7301, INTERNAL FLOATING ROOF, CAPACITY 7300 BARRELS, 36'-0" DIA X 41'-0" H, WELDED SHELL, WITH MECHANICAL SHOE TYPE PRIMARY SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 30 PERCENT OF THE LOWER EXPLOSIVE LIMIT (LEL). AN EXPLOSIMETER SHALL BE USED TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE PER YEAR AT A 4 TO 8 MONTHS INTERVAL. ADEQUATE RECORDS SHALL BE KEPT TO SHOW COMPLIANCE WITH THIS CONDITION.
[RULE 463, 1178]
4. THE OPERATOR SHALL LIMIT THE USE AND THROUGHPUT TO NO MORE THAN 222,042 BARRELS PER CALENDAR MONTH OF ORGANIC LIQUIDS NOT TO EXCEED A TRUE VAPOR PRESSURE OF 11 PSIA UNDER ACTUAL STORAGE CONDITIONS.
[RULE 1303(b)(2)-OFFSETS]
5. THE OPERATOR SHALL KEEP RECORDS, IN MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

TYPE OF LIQUID STORED, THROUGHPUT, AND TRUE VAPOR PRESSURE OF LIQUIDS UNDER
[RULE 463]

Periodic Monitoring: NONE



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178

**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. G18981
A/N 448254**

Equipment Description:

TANK NO. 99-TK-7302, INTERNAL FLOATING ROOF, CAPACITY 7300 BARRELS, 36'-0" DIA X 41'-0" H, WELDED SHELL, WITH MECHANICAL SHOE TYPE PRIMARY SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 30 PERCENT OF THE LOWER EXPLOSIVE LIMIT (LEL). AN EXPLOSIMETER SHALL BE USED TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE PER YEAR AT A 4 TO 8 MONTHS INTERVAL. ADEQUATE RECORDS SHALL BE KEPT TO SHOW COMPLIANCE WITH THIS CONDITION.
[RULE 463, 1178]
4. THE OPERATOR SHALL LIMIT THE USE AND THROUGHPUT TO NO MORE THAN 222,042 BARRELS PER CALENDAR MONTH OF ORGANIC LIQUIDS NOT TO EXCEED A TRUE VAPOR PRESSURE OF 11 PSIA UNDER ACTUAL STORAGE CONDITIONS.
[RULE 1303(b)(2)-OFFSETS]
5. THE OPERATOR SHALL KEEP RECORDS IN MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

TYPE OF LIQUID STORED, THROUGHPUT, AND TRUE VAPOR PRESSURE OF LIQUIDS UNDER ACTUAL STORAGE CONDITIONS.
[RULE 463]

Periodic Monitoring: NONE



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. G18982
A/N 448255**

Equipment Description:

TANK NO. 99-TK-11001, INTERNAL FLOATING ROOF, CAPACITY 11000 BARRELS, 48'-0" DIA X 35'-6" H, WELDED SHELL, WITH MECHANICAL SHOE TYPE PRIMARY SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 30 PERCENT OF THE LOWER EXPLOSIVE LIMIT (LEL). AN EXPLOSIMETER SHALL BE USED TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE PER YEAR AT A 4 TO 8 MONTHS INTERVAL. ADEQUATE RECORDS SHALL BE KEPT TO SHOW COMPLIANCE WITH THIS CONDITION.
[RULE 463, 1178]
4. THE OPERATOR SHALL LIMIT THE USE AND THROUGHPUT TO NO MORE THAN 334,583 BARRELS PER CALENDAR MONTH OF ORGANIC LIQUIDS NOT TO EXCEED A TRUE VAPOR PRESSURE OF 11 PSIA UNDER ACTUAL STORAGE CONDITIONS.
[RULE 1303(b)(2)-OFFSETS]
5. THE OPERATOR SHALL KEEP RECORDS, IN MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

TYPE OF LIQUID STORED, THROUGHPUT, AND TRUE VAPOR PRESSURE OF LIQUIDS UNDER ACTUAL STORAGE CONDITIONS.

[RULE 463]

Periodic Monitoring: NONE



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178

**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO OPERATE

**Permit No. G18983
A/N 448256**

Equipment Description:

TANK NO. 99-TK-21001, INTERNAL FLOATING ROOF, CAPACITY 20700 BARRELS, 60'-0" DIA X 41'-0" H, WELDED SHELL, WITH MECHANICAL SHOE TYPE PRIMARY SEAL

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE HYDROCARBON CONCENTRATION BEING MONITORED, AS INDICATED BELOW, DOES NOT EXCEED 30 PERCENT OF THE LOWER EXPLOSIVE LIMIT (LEL). AN EXPLOSIMETER SHALL BE USED TO MONITOR THE HYDROCARBON CONCENTRATION IN THE VAPOR SPACE ABOVE THE INTERNAL FLOATING ROOF TWICE PER YEAR AT A 4 TO 8 MONTHS INTERVAL. ADEQUATE RECORDS SHALL BE KEPT TO SHOW COMPLIANCE WITH THIS CONDITION.
[RULE 463, 1178]
4. THE OPERATOR SHALL LIMIT THE USE AND THROUGHPUT TO NO MORE THAN 629,625 BARRELS PER CALENDAR MONTH OF ORGANIC LIQUIDS NOT TO EXCEED A TRUE VAPOR PRESSURE OF 11 PSIA UNDER ACTUAL STORAGE CONDITIONS.
[RULE 1303(b)(2)-OFFSETS]
5. THE OPERATOR SHALL KEEP RECORDS, IN MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

TYPE OF LIQUID STORED, THROUGHPUT, AND TRUE VAPOR PRESSURE OF LIQUIDS UNDER ACTUAL STORAGE CONDITIONS.

[RULE 463]

Periodic Monitoring: NONE



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 463
VOC: RULE 1149
VOC: RULE 1178

**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

Conditions:

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (A) COATING TYPE, (B) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (g/l) OF MATERIALS FOR LOW-SOLIDS COATINGS. (C) VOC CONTENT AS SUPPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT. FOR OTHER COATING.

FOR OTHER ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (A) COATING TYPE, (B) VOC CONTENT AS APPLIED IN GRAMS PER LITER (g/l) OF MATERIALS USED FOR LOW-SOLIDS COATINGS (C) VOC CONTENT AS APPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT. FOR OTHER COATING.
[RULE 1113, RULE 109]

Emissions And Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

REFRIGERANTS: RULE 1415

REFRIGERANTS: 40 CFR 82 SUBPART F



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, STORAGE AND TRANSFER EQUIPMENT FOR UNHEATED ORGANIC LIQUIDS

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 463



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

**Facility Equipment and Requirements
(Section H)**

This section consists of a table listing all individual Permits to Construct issued to various equipment at the facility. Each permit will list operating conditions, including periodic monitoring requirements and applicable emission limits and requirements. Also included are the rule origin and authority of each emission limit and permit condition.



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AT THIS FACILITY:

Application Number	Equipment Description	Page Number
433733	GAS OIL BULK LOADING/UNLOADING BERTHS 163 AND 164	3
430537	MARINE TERMINAL WASTE GAS COLLECTION SYSTEM/INCINERATION	5

NOTE: EQUIPMENT LISTED ABOVE ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT WILL NOT BE FOUND IN THIS TITLE V PERMIT.



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

PERMIT TO CONSTRUCT

A/N 433733
Granted 9/16/2005

Equipment Description:

MARINE TERMINAL BULK LOADING/UNLOADING FACILITY CONSISTING OF :

1. LOADING/UNLOADING ARM, HARBOR BERTH 164-1, ONE WITH FOUR 8 INCH PIPELINE RISERS, WITH GATE VALVE, FLANGES AND FLEXIBLE HOSES CONNECTING TO SHIP MANIFOLDS.
2. LOADING/UNLOADING ARM, HARBOR BERTH 164-2, ONE WITH SIX 8 INCH PIPELINE RISERS, EACH EQUIPPED WITH GATE VALVE, FLANGES AND FLEXIBLE HOSES CONNECTING TO SHIP MANIFOLDS.
3. ONE LOADING/UNLOADING ARM AT HARBOR BERTH 163, WITH SIX 8 INCH PIPELINE RISERS, EQUIPPED WITH GATE VALVE, FLANGES AND FLEXIBLE HOSES CONNECTING TO SHIP MANIFOLDS.
4. COLLECTION SUMP, 4'-0" W. X 4'-0" L. X 6'-0" D.
5. TWO LOADING PUMPS NOS. 99-P-2 AND 99-P-3, EACH CENTRIFUGAL TYPE, WITH MECHANICAL SEALS AND A 250 HP MOTOR
6. LOADING PUMP NO. 99-P-4, POSITIVE DISPLACEMENT TYPE, WITH PACKING GLAND AND A 125 HP MOTOR
7. LOADING PUMP NO. 99-P-14, CENTRIFUGAL TYPE, WITH MECHANICAL SEALS AND A 150 HP MOTOR.
8. TRANSFER PUMP, 99-P-15, WITH MECHANICAL SEALS AND A 200 HP MOTOR
9. LOADING PUMP NO. 99-P-1, CENTRIFUGAL TYPE, WITH MECHANICAL SEALS AND A 200 HP MOTOR
10. TWO LOADING PUMPS NOS. 99-P-21 AND 99-P-22, EACH CENTRIFUGAL TYPE, WITH MECHANICAL SEALS AND A 300 HP MOTOR
11. TRANSFER LINE DRAIN PUMP NO. 99-P-6, POSITIVE DISPLACEMENT TYPE, WITH A PACKING GLAND AND A 15 HP MOTOR.


Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.

[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.

[RULE 204]



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AN AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT BY THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT.
[RULE 1142, RULE 1303(b)(2) - OFFSET]
4. THE OPERATOR SHALL ONLY USE THE FOLLOWING MATERIALS IN THE MARINE LOADING/UNLOADING FACILITY:
GAS OIL, DECANT OIL, DIESEL OIL, AND LIGHT CYCLE OIL, EACH WITH A TRUE VAPOR PRESSURE OF 0.4 PSIA OR LESS UNDER ACTUAL; OPERATING CONDITIONS DURING LOADING OPERATION.
[RULE 1303(b)(2) - OFFSET, RULE 1401, RULE 431.1]
5. THE OPERATOR SHALL LIMIT THE THROUGHPUT FROM BOTH BARGE AND SHIP LOADING TO 300,000 BARRELS IN ANY ONE CALENDAR MONTH.
[RULE 1303(b)(2) - OFFSET]
6. A FLOWMETER SHALL BE INSTALLED AND MAINTAINED TO ACCURATELY INDICATE THE THROUGHPUT FROM BOTH BARGE AND SHIP LOADING.
[RULE 204, RULE 1303(b)(2) - OFFSET]
7. THE OPERATOR SHALL LIMIT THE NUMBER OF SHIPS LOADED TO NO MORE THAN NINE (9) IN ANY ONE CALENDAR YEAR.
[RULE 1303(b)(2) - OFFSET]
8. THE OPERATOR SHALL LIMIT THE NUMBER OF BARGES LOADED TO NO MORE THAN TEN (10) IN ANY ONE CALENDAR MONTH.
[RULE 1303(b)(2) - OFFSET]
9. THE OPERATOR SHALL LIMIT THE TOTAL COMBINED FLOW RATE FROM ALL LOADING ARMS IN OPERATION AT THE SAME TIME LOADING PRODUCT INTO A MARINE VESSEL TO 3740 GALLONS PER MINUTE. THE PURPOSE OF THIS CONDITION IS TO ENSURE THAT THE VENT GAS DISPLACEMENT RATE DOES NOT EXCEED 500 CUBIC FEET PER MINUTE.
[RULE 1303(b)(2) - OFFSET]

Periodic Monitoring: NONE

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:
VOC: 2 LBS VOC PER 1000 BARRELS ORGANIC LIQUID LOADED, RULE 1142



**FACILITY PERMIT TO OPERATE
ULTRAMAR INC. MARINE TERMINAL**

PERMIT TO CONSTRUCT

**A/N 430537
Granted 9/16/2005**


Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. DETONATION ARRESTOR, DOCK SAFETY UNIT, 99-ME-01 WITH PARTICULATE FILTER 99-F-01 AND DETONATION ARRESTOR A-MV101
2. SUMP, 99-SMP-01, LOW POINT LIQUID COLLECTION
3. KNOCK OUT POT, 99-V-09, HEIGHT: 6FT; DIAMETER: 1 FT 6 IN
4. BLOWER, 99-BL-02, VAPOR SERVICE, 25 HP, 1762 SCFM
5. BLOWER, 99-BL-03, COMBUSTOR AIR, 7.5 HP, 4200 SCFM
6. INCINERATOR, A-MV202, NATURAL GAS FIRED PILOTS, CALLIDUS, 136 MMBTU/HR WITH ONE BURNER IN PRIMARY STAGE AND FOUR BURNERS IN SECONDARY STAGE, AND DETONATION ARRESTOR, COMBUSTOR, A-MV201

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL BE IN FULL OPERATION WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.
[RULE 1142]
4. THE OPERATOR SHALL LIMIT THE FUEL USAGE TO NO MORE THAN 225 CUBIC FEET PER MINUTE.
[RULE 1303(b)(2) - OFFSET]



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

5. A NON-RESETTABLE TOTALIZING FUEL FLOW METER SHALL BE INSTALLED AND MAINTAINED TO ACCURATELY INDICATE THE FUEL USAGE BEING SUPPLIED TO THE INCINERATOR.
[RULE 1303(b)(2) - OFFSET]
6. THE OPERATOR SHALL LIMIT THE EXHAUST FLOW TO NO MORE THAN 725 CUBIC FEET PER MINUTE.
[RULE 1303(b)(2) - OFFSET]
7. A FLOW METER SHALL BE INSTALLED AND MAINTAINED TO ACCURATELY INDICATE THE FLOW RATE FROM THE VAPOR SERVICE BLOWER.
[RULE 1303(b)(2) - OFFSET]

Periodic Monitoring:

8. WHENEVER THE INCINERATOR IS IN OPERATION, THE TEMPERATURE IN THE FIREBOX SHALL NOT BE LESS THAN 1400 DEGREES FAHRENHEIT.
[RULE 1303(b)(2) - OFFSET, RULE 1142, RULE 3004(a)(4) - PERIODIC MONITORING]
9. A CONTINUOUS TEMPERATURE MEASUREMENT AND RECORDING DEVICE SHALL BE INSTALLED AND MAINTAINED TO ACCURATELY INDICATE THE TEMPERATURE IN THE FIREBOX.
[RULE 1303(b)(2) - OFFSET, RULE 1142, RULE 3004(a)(4) - PERIODIC MONITORING]
10. A SOURCE TEST SHALL BE PERFORMED ONCE EVERY THREE YEARS TO DETERMINE THE POUNDS OF VOC EMITTED PER 1000 BARRELS OF ORGANIC LIQUID LOADED.
[RULE 1142, RULE 3004(a)(4) - PERIODIC MONITORING]
11. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A DAILY BASIS WHENEVER FUEL IS BURNED. THE ROUTINE DAILY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:



FACILITY PERMIT TO OPERATE ULTRAMAR INC. MARINE TERMINAL

1). TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

2). HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- 1). STACK OR EMISSION POINT IDENTIFICATION;
- 2). DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- 3). DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- 4). ALL VISIBLE EMISSION OBSERVATION RECORDS BY OPERATOR OR A CERTIFIED SMOKE READER.

[RULE 401]

Emissions and Requirements:

12. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: 2 LBS/1000 BARRELS ORGANIC LIQUID LOADED, RULE 1142
CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404 (SEE APPENDIX B FOR EMISSION LIMITS)
SOX: 500 PPMV, RULE 407