



South Coast Air Quality Management District

21865 Copley Drive, Diamond Bar, CA 91765-4178
(909) 396-2000 • www.aqmd.gov

August 8, 2012

Mr. Andy Andreoli
Vice President
Baker Commodities, Inc.
4020 Bandini Blvd
Vernon, CA 90058

Dear Mr. Andreoli:

Subject: Final Title V Renewal Permit, I.D. No. 800016

Enclosed is your final Title V Renewal Facility Permit for Baker Commodities, Inc., issued by the South Coast Air Quality Management District (AQMD) under Application No. 527384 for your facility located at 4020 Bandini Blvd., Vernon, CA 90058. This final Title V renewal permit will become effective today, August 8, 2012.


Please review all sections of your Title V renewal permit carefully and make sure that you comply with all requirements including, but not limited to, the monitoring, recordkeeping, and reporting requirements (i.e. semi-annual monitoring report, annual compliance certification report, etc.) specified in this Title V permit. All reporting forms can be downloaded from the AQMD website at <http://www.aqmd.gov/titlev/apply.html>.

This Title V Permit renewal includes updated changes made to the permit that reflect change of conditions and equipment modifications requested by you as follows:

Equipment	Application No.	Device No.	Process	Permit Type
Air Cooled Condenser	509114	C391	5	PO
Storage Tank No. 5	532948	D395	7,5	PO
Storage Tank No. 6	532949	D396	7,5	PO
Storage Tank No. 7	532950	D397	7,5	PO
Storage Tank No. 8	532951	D398	7,5	PO
Air Pollution Control	532952	C300-C302	10	PO

Thank you for providing the necessary information that allowed the AQMD to complete the renewal of your Title V permit. If you have any questions, determine that there are administrative errors in the permit, or need additional information concerning this permit, please contact Ms. Monica Fernandez-Neild, Air Quality Engineer, at 909.396.2202.

Sincerely,


Brian L. Yeh
Senior Manager
Mechanical, Chemical and Public Services

BLY:mfn
Enclosure
Certified Mail/Return Receipt Requested

c: Mr. Gerardo C. Rios, U.S. EPA, Region IX

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	21	08/08/2012
B	RECLAIM Annual Emission Allocation	20	07/01/2012
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	16	08/08/2012
E	Administrative Conditions	8	04/19/2007
F	RECLAIM Monitoring and Source Testing Requirements	5	04/19/2007
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	5	04/19/2007
H	Permit To Construct and Temporary Permit to Operate	14	10/19/2010
I	Compliance Plans & Schedules	3	04/19/2007
J	Air Toxics	2	08/08/2012
K	Title V Administration	2	08/08/2012
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	3	08/08/2012
B	Rule Emission Limits	3	08/08/2012

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION A: FACILITY INFORMATION

LEGAL OWNER &/OR OPERATOR: BAKER COMMODITIES INC
LEGAL OPERATOR (if different than owner):
EQUIPMENT LOCATION: 4020 BANDINI BLVD
VERNON, CA 90058
MAILING ADDRESS: 4020 BANDINI BLVD
VERNON, CA 90058-4532
RESPONSIBLE OFFICIAL: ANDY ANDREOLI
TITLE: VICE PRESIDENT
TELEPHONE NUMBER: (323) 268-2801
CONTACT PERSON: ADAM LOTA
TITLE: ENGINEER
TELEPHONE NUMBER: (323) 268-2801
TITLE V PERMIT ISSUED: August 07, 2012
TITLE V PERMIT EXPIRATION DATE: August 06, 2017

TITLE V	RECLAIM
----------------	----------------

YES	NOx:	YES
	SOx:	NO
	CYCLE:	2
	ZONE:	COASTAL

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

The annual allocation of NOx RECLAIM Trading Credits (RTCs) for this facility is calculated pursuant to Rule 2002. Total NOx emission shall not exceed such annual allocations unless the operator obtains RTCs corresponding to the facility's increased emissions in compliance with Rules 2005 and 2007.

The level of Starting Allocation plus Non-Tradable Credits used to determine compliance with Rule 2005(c)(4) and applicability of Rule 2005(e) - Trading Zone Restrictions is listed on the last page of this Section.

The following table lists the annual allocations that were issued to this facility and the amounts of RTCs held by this facility on the day of printing this Section.

RECLAIM POLLUTANT ANNUAL ALLOCATION (POUNDS)

Year Begin End (month/year)	Zone	NOx RTC Initially Allocated	NOx RTC ¹ Holding as of 07/01/2012 (pounds)	Non-Tradable ² Non-Usable RTCs (pounds)
7/2009 6/2010	Coastal	17007	3210	918
1/2010 12/2010	Coastal	0	0	567
7/2010 6/2011	Coastal	17007	4143	1378
1/2011 12/2011	Coastal	0	5425	756
7/2011 6/2012	Coastal	17007	13180	1837
1/2012 12/2012	Coastal	0	5425	756
7/2012 6/2013	Coastal	17007	13180	1837
1/2013 12/2013	Coastal	0	5425	756
7/2013 6/2014	Coastal	17007	13180	1837
1/2014 12/2014	Coastal	0	5425	756
7/2014 6/2015	Coastal	17007	13180	1837
1/2015 12/2015	Coastal	0	5425	756
7/2015 6/2016	Coastal	17007	13180	1837
1/2016 12/2016	Coastal	0	5425	756
7/2016 6/2017	Coastal	17007	13180	1837
1/2017 12/2017	Coastal	0	5425	756
7/2017 6/2018	Coastal	17007	13180	1837

Footnotes:

1. This number may change due to pending trades, emissions reported under Quarterly Certification of Emissions Report (QCER) and Annual Permit Emission Program (APEP) Report required pursuant to Rule 2004, or deductions made pursuant to Rule 2010(b). The most recent total RTC information can be obtained from the District's RTC Listing.

2. The use of such credits is subject to restrictions set forth in paragraph (f)(1) of Rule 2002.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

The annual allocation of NOx RECLAIM Trading Credits (RTCs) for this facility is calculated pursuant to Rule 2002. Total NOx emission shall not exceed such annual allocations unless the operator obtains RTCs corresponding to the facility's increased emissions in compliance with Rules 2005 and 2007.

The level of Starting Allocation plus Non-Tradable Credits used to determine compliance with Rule 2005(c)(4) and applicability of Rule 2005(e) - Trading Zone Restrictions is listed on the last page of this Section.

The following table lists the annual allocations that were issued to this facility and the amounts of RTCs held by this facility on the day of printing this Section.

RECLAIM POLLUTANT ANNUAL ALLOCATION (POUNDS)

Year Begin End (month/year)	Zone	NOx RTC Initially Allocated	NOx RTC ¹ Holding as of 07/01/2012 (pounds)	Non-Tradable ² Non-Usable RTCs (pounds)
1/2018 12/2018	Coastal	0	5425	756
7/2018 6/2019	Coastal	17007	13180	1837
1/2019 12/2019	Coastal	0	5425	756
7/2019 6/2020	Coastal	17007	13180	1837
1/2020 12/2020	Coastal	0	5425	756
7/2020 6/2021	Coastal	17007	13180	1837
1/2021 12/2021	Coastal	0	5425	756
7/2021 6/2022	Coastal	17007	13180	1837
1/2022 12/2022	Coastal	0	5425	756
7/2022 6/2023	Coastal	17007	13180	1837
1/2023 12/2023	Coastal	0	5425	756
7/2023 6/2024	Coastal	17007	13180	1837
1/2024 12/2024	Coastal	0	5425	756
7/2024 6/2025	Coastal	17007	13180	1837
1/2025 12/2025	Coastal	0	5425	756
7/2025 6/2026	Coastal	17007	13180	1837
1/2026 12/2026	Coastal	0	5425	756

Footnotes:

1. This number may change due to pending trades, emissions reported under Quarterly Certification of Emissions Report (QCER) and Annual Permit Emission Program (APEP) Report required pursuant to Rule 2004, or deductions made pursuant to Rule 2010(b). The most recent total RTC information can be obtained from the District's RTC Listing.
2. The use of such credits is subject to restrictions set forth in paragraph (f)(1) of Rule 2002.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

The annual allocation of NO_x RECLAIM Trading Credits (RTCs) for this facility is calculated pursuant to Rule 2002. Total NO_x emission shall not exceed such annual allocations unless the operator obtains RTCs corresponding to the facility's increased emissions in compliance with Rules 2005 and 2007.

The level of Starting Allocation plus Non-Tradable Credits used to determine compliance with Rule 2005(c)(4) and applicability of Rule 2005(e) - Trading Zone Restrictions is listed on the last page of this Section.

The following table lists the annual allocations that were issued to this facility and the amounts of RTCs held by this facility on the day of printing this Section.

RECLAIM POLLUTANT ANNUAL ALLOCATION (POUNDS)

Year Begin End (month/year)	Zone	NO _x RTC Initially Allocated	NO _x RTC ¹ Holding as of 07/01/2012 (pounds)	Non-Tradable ² Non-Usable RTCs (pounds)
7/2026 6/2027	Coastal	17007	13180	1837
1/2027 12/2027	Coastal	0	5425	756

Footnotes:

1. This number may change due to pending trades, emissions reported under Quarterly Certification of Emissions Report (QCER) and Annual Permit Emission Program (APEP) Report required pursuant to Rule 2004, or deductions made pursuant to Rule 2010(b). The most recent total RTC information can be obtained from the District's RTC Listing.
2. The use of such credits is subject to restrictions set forth in paragraph (f)(1) of Rule 2002.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

The annual allocation of RECLAIM Trading Credits (RTCs) for this facility is calculated pursuant to Rule 2002. If the facility submits a permit application to increase in an annual allocation to a level greater than the facility's starting Allocation plus Non-Tradable credits as listed below, the application will be evaluated for compliance with Rule 2005 (c)(4). Rule 2005 (e) - Trading Zone Restrictions applies if an annual allocation is increased to a level greater than the facility's Starting Allocation plus Non-Tradable Credits:

Year		Zone	NOx RTC	Non-Tradable
Begin	End		Starting Allocation	Credits(NTC)
(month/year)			(pounds)	(pounds)
7/1994	6/1995	Coastal	68291	0

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION C: FACILITY PLOT PLAN

(TO BE DEVELOPED)

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: RENDERING, BAKER COMMODITIES					P13.1
System 1: RAW MATERIAL HANDLING					
PIT, ANIMAL MATTER, RECEIVING A/N: 166990	D1				E187.1
PIT, ANIMAL MATTER, RECEIVING A/N: 166990	D2				E187.1
CONVEYOR, SCREW, ANIMAL MATTER, RECEIVING PIT A/N: 166990	D3				E187.1
CONVEYOR, SCREW, ANIMAL MATTER, RECEIVING PIT A/N: 166990	D4				E187.1
CONVEYOR, SCREW, ANIMAL MATTER, RECEIVING PIT A/N: 166990	D5				E187.1
CONVEYOR, SCREW, ANIMAL MATTER, RECEIVING PIT A/N: 166990	D6				E187.1
CONVEYOR, SCREW, ANIMAL MATTER, RECEIVING PIT A/N: 166990	D7				E187.1
CONVEYOR, SCREW, ANIMAL MATTER, RECEIVING PIT A/N: 166990	D8				E187.1
CONVEYOR, SCREW, ANIMAL MATTER, RECEIVING PIT A/N: 166990	D9				E187.1
CONVEYOR, SCREW, ANIMAL MATTER, RECEIVING PIT A/N: 166990	D10				E187.1
CONVEYOR, SCREW, ANIMAL MATTER, MAGNETS FEED A/N: 166990	D11				E187.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: RENDERING: BAKER COMMODITIES					P13.1
TANK, ANIMAL MATTER, MAGNET, ELECTRO-PLATE TYPE A/N: 166990	D12				E187.1
TANK, ANIMAL MATTER, MAGNET, ELECTRO-PLATE TYPE A/N: 166990	D13				E187.1
CONVEYOR, SCREW, ANIMAL MATTER, INCLINE, 24 INCH DIAMETER A/N: 166990	D14				E187.1
BIN, SURGE, COMPARTMENTED A/N: 166990	D15				E187.1
CONVEYOR, SCREW, SURGE BIN A/N: 166990	D16				E187.1
CONVEYOR, SCREW, SURGE BIN A/N: 166990	D17				E187.1
CONVEYOR, SCREW, SURGE BIN A/N: 166990	D18				E187.1
CONVEYOR, SCREW, SURGE BIN A/N: 166990	D19				E187.1
GRINDER, DUPPS HOGGER A/N: 166990	D20				E187.1
GRINDER, DUPPS HOGGER A/N: 166990	D21				E187.1
GRINDER A/N: 166990	D22				E187.1
CONVEYOR, SCREW, ANIMAL MATTER A/N: 166990	D23				E187.1
System 2: RENDERING SYSTEM NO. 3					

* (1) (1A) (1B) Denotes RECLAIM emission factor
(2) (2A) (2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5) (5A) (5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: RENDERING: BAKER COMMODITIES					P13.1
RENDERING COOKER, NO.1, PRECOOKER A/N: 155019	D24	C212 C391			E187.1
CONVEYOR, COOKER NO. 1 FEED A/N: 155019	D25				E187.1
CONVEYOR, SCREW, RATE CONTROL A/N: 155019	D26				E187.1
RENDERING COOKER, NO.2, PRECOOKER A/N: 155019	D27	C212 C391			E187.1
CONVEYOR, SCREW, PRECOOKED TRANSFER A/N: 155019	D28				E187.1
CONVEYOR, SCREW, INCLINED PRECOOKER FEED A/N: 155019	D29				E187.1
CONVEYOR, SCREW, PRECOOKER UNLOADING A/N: 155019	D30				E187.1
CONVEYOR, SCREW, INCLINED, PRECOOKER RECYCLE A/N: 155019	D31				E187.1
System 3: COOKING					
RENDERING COOKER, NO. 2, STEAM HEATED A/N: 118821	D32	C214 C391			
VESSEL, SEPARATOR, ENTRAINMENT A/N: 118821	D33	C214 C391			

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: RENDERING: BAKER COMMODITIES					P13.1
VESSEL, SEPARATOR, ENTRAINMENT A/N: 118821	D34	C214 C391			
FEEDER, ROTARY CONTROL METERING A/N: 118821	D35	C214 C391			
System 4: SCREENING, WASHING AND SEPARATING					
CONVEYOR, SCREW A/N: 491629	D37	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, FLOOR SCREW A/N: 491629	D38	C213 C391			C1.7, C1.8, C1.11
SCREEN, CLASSIFYING, NORTH CLARIFIER A/N: 491629	D39	C213 C391			C1.7, C1.8, C1.11
VESSEL, DRAINOR SCREW A/N: 491629	D41	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, DRAINOR SCREW A/N: 491629	D42	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW, FEED A/N: 491629	D43	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW, FEED A/N: 491629	D44	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW, FEED A/N: 491629	D45	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW, FEED A/N: 491629	D46	C213 C391			C1.7, C1.8, C1.11
VESSEL, SCREW PRESS NO. 4 A/N: 491629	D47	C213 C391			C1.7, C1.8, C1.11
VESSEL, SCREW PRESS NO. 3 A/N: 491629	D48	C213 C391			C1.7, C1.8, C1.11
VESSEL, SCREW PRESS NO. 2 A/N: 491629	D49	C213 C391			C1.7, C1.8, C1.11

- * (1) (1A) (1B) Denotes RECLAIM emission factor
(2) (2A) (2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5) (5A) (5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: RENDERING: BAKER COMMODITIES					P13.1
VESSEL, SCREW PRESS NO. 1 A/N: 491629	D50	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW PRESS NO. 5 A/N: 491629	D381	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, OVERPRESS RETURN SCREW A/N: 491629	D382	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW A/N: 491629	D51	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW A/N: 491629	D52	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW A/N: 491629	D53	C213 C391			C1.7, C1.8, C1.11
CYCLONE A/N: 491629	D383	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW A/N: 491629	D54	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW A/N: 491629	D55	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW A/N: 491629	D56	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW, INCLINE A/N: 491629	D57	D68			C1.7, C1.8, C1.11
BIN, DRY CRAX A/N: 491629	D58	C213 C391			C1.7, C1.8, C1.11
TANK, DECANTER, SURGE TANK A/N: 491629	D60	C213 C391			C1.7, C1.8, C1.11
TANK, CENTRIFUGE, SURGE TANK A/N: 491629	D61	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, RETURN SCREW A/N: 491629	D63	D68			C1.7, C1.8, C1.11

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: RENDERING: BAKER COMMODITIES					P13.1
CONVEYOR, DRYER NO. 1 FEED SCREW A/N: 491629	D64	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, DRYER NO. 1, RETURN SCREW A/N: 491629	D65	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, DRYER NO. 1, DISCHARGE CONTROL SCREW A/N: 491629	D66	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW A/N: 491629	D67	C213 C391			C1.7, C1.8, C1.11
DRYER, NO. 1, STEAM HEATED A/N: 491629	D68	D57 D63 C213 C391			C1.7, C1.8, C1.11
TANK, DECANTER A/N: 491629	D70	C213 C391			C1.7, C1.8, C1.11
VESSEL, SEPARATOR A/N: 491629	D71	C213 C391			C1.7, C1.8, C1.11
VESSEL, SEPARATOR A/N: 491629	D72	C213 C391			C1.7, C1.8, C1.11
VESSEL, SEPARATOR A/N: 491629	D384	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, CENTRIFUGE SOILDS SCREEN A/N: 491629	D385	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW A/N: 491629	D73	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, SCREW A/N: 491629	D74	C213 C391			C1.7, C1.8, C1.11
VESSEL, SEPARATOR A/N: 491629	D303	C213 C391			C1.7, C1.8, C1.11
VESSEL, SEPARATOR A/N: 491629	D304	C213 C391			C1.7, C1.8, C1.11

* (1) (1A) (1B) Denotes RECLAIM emission factor
(2) (2A) (2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5) (5A) (5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: RENDERING: BAKER COMMODITIES					P13.1
VESSEL, SEPARATOR A/N: 491629	D305	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, DRYER NO. 2, FEED SCREW A/N: 491629	D386	C213 C391			C1.7, C1.8, C1.11
DRYER, NO. 2, STEAM HEATED A/N: 491629	D306	C214			C1.7, C1.8, C1.11
CONVEYOR, DRYER NO. 2, RETURN SCREW A/N: 491629	D387	C213 C391			C1.7, C1.8, C1.11
DRYER, NO. 2, DISCHARGE CONTROL SCREW A/N: 491629	D388	C213 C391			C1.7, C1.8, C1.11
CONVEYOR, DRYER BYPASS SCREW A/N: 491629	D389	C213 C391			C1.7, C1.8, C1.11
TANK, STICK WATER, HEIGHT: 19 FT 8 IN; DIAMETER: 9 FT A/N: 491629	D307	C213 C391			C1.7, C1.8, C1.11
System 5: TALLOW PROCESSING					
TANK, NO. 7, HEIGHT: 14 FT ; DIAMETER: 10 FT 3 IN A/N: 290985	D76	C212 C391			
CENTRIFUGE, 75 HP A/N: 290985	D372	C212 C391			
CENTRIFUGE, 75 HP A/N: 290985	D373	C212 C391			
TANK, SURGE, NO. 3, TALLOW, STEAM HEATED, HEIGHT: 19 FT ; DIAMETER: 9 FT A/N: 290985	D81	C212 C391			

- * (1) (1A) (1B) Denotes RECLAIM emission factor
(2) (2A) (2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5) (5A) (5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: RENDERING: BAKER COMMODITIES					P13.1
TANK, SURGE, NO. 4, TALLOW, STEAM HEATED, HEIGHT: 19 FT ; DIAMETER: 9 FT A/N: 290985	D82	C212 C391			
CONVEYOR, SCREW, BLEACHING CLAY A/N: 290985	D374	C212 C391		PM: (9) [RULE 404, 2-7-1986; RULE 405, 2-7-1986]	D322.1
TANK, SLURRY, WITH FILTER SOCK, HEIGHT: 9 FT ; DIAMETER: 5 FT A/N: 290985	D84	D90 C214 C391		PM: (9) [RULE 404, 2-7-1986; RULE 405, 2-7-1986]	D322.1, D381.1, K67.2
DRYER, VACUUM, PICK HEATER A/N: 290985	D85	C212 C391			
TANK, SURGE, VACUUM DRYER OVERFLOW, HEIGHT: 5 FT 9 IN; DIAMETER: 4 FT A/N: 290985	D86	C212 C391			
TANK, PRECOAT, STEAM HEATED A/N: 290985	D87	C214 C391			
TANK, SURGE, CENTRIFUGED TALLOW, HEIGHT: 24 FT ; DIAMETER: 11 FT 6 IN A/N: 290985	D90	D84			
VESSEL, VERTICAL SEPARATOR, EAST A/N: 290985	D91	C214 C391			
VESSEL, VERTICAL SEPARATOR, EAST A/N: 290985	D92	C214 C391			
System 6: BLOOD PROCESSING					
TANK, RECEIVING, HEIGHT: 13 FT ; DIAMETER: 10 FT A/N: C31592	D93				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
(2) (2A) (2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5) (5A) (5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: RENDERING: BAKER COMMODITIES					P13.1
MIXER, HEIGHT: 5 FT ; DIAMETER: 5 FT A/N: C31592	D94				
COOKER, COAGULATOR, STEAM HEATED A/N: C31592	D95				
CONVEYOR, SCREW, INCLINED SCREEN DRAINER A/N: C31592	D96	C212 C391			
CONVEYOR, SCREW A/N: C31592	D97	C212 C391			
TANK, HOLDING, SERUM A/N: C31592	D98	C212 C391			
SCREEN, CLASSIFYING, CLASSIFYING, SEPARATOR, VIBRATING A/N: C31592	D99	C212 C391			
System 7: MEAT MEAL GRINDING SCREENING					
CONVEYOR, SCREW, SILO A/N: C33905	D100			PM: (9) [RULE 405, 2-7-1986]	D323.1
BUCKET ELEVATOR A/N: C33905	D101			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW A/N: C33905	D102			PM: (9) [RULE 405, 2-7-1986]	D323.1
BIN, BLENDING, PET FOOD GRADE, WIDTH: 20 FT ; HEIGHT: 24 FT ; LENGTH: 20 FT A/N: C33905	D103			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, DISTRIBUTION A/N: C33905	D104			PM: (9) [RULE 405, 2-7-1986]	D323.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5) (5A) (5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: RENDERING: BAKER COMMODITIES					P13.1
CONVEYOR, SCREW, UNLOADING A/N: C33905	D105			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, UNLOADING A/N: C33905	D106			PM: (9) [RULE 405, 2-7-1986]	D323.1
BUCKET ELEVATOR A/N: C33905	D107			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW A/N: C33905	D108			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW A/N: C33905	D109			PM: (9) [RULE 405, 2-7-1986]	D323.1
VESSEL, MAGNETIC SEPARATOR A/N: C33905	D110			PM: (9) [RULE 405, 2-7-1986]	D323.1
VESSEL, MAGNETIC SEPARATOR A/N: C33905	D111			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, MAGNETS DISCHARGE A/N: C33905	D112			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, BELT, MAGNET A/N: C33905	D113			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, CROSS A/N: C33905	D114			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, GRINDERS FEED A/N: C33905	D115			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, GRINDERS FEED A/N: C33905	D116			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, GRINDERS FEED A/N: C33905	D117			PM: (9) [RULE 405, 2-7-1986]	D323.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5) (5A) (5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2) (2A) (2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: RENDERING- BAKER COMMODITIES					P13.1
GRINDER, HAMMERMILL TYPE A/N: C33905	D118			PM: (9) [RULE 405, 2-7-1986]	D323.1, E166.1, E202.1
GRINDER, HAMMERMILL TYPE A/N: C33905	D119			PM: (9) [RULE 405, 2-7-1986]	D323.1, E166.1, E202.1
GRINDER, HAMMERMILL TYPE A/N: C33905	D120			PM: (9) [RULE 405, 2-7-1986]	D323.1, E166.1, E202.1
GRINDER, HAMMERMILL TYPE A/N: C33905	D121			PM: (9) [RULE 405, 2-7-1986]	D323.1, E166.1, E202.1
GRINDER, HAMMERMILL TYPE A/N: C33905	D122			PM: (9) [RULE 405, 2-7-1986]	D323.1, E166.1, E202.1
CONVEYOR, SCREW A/N: C33905	D123			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, CLASSIFIER FEED A/N: C33905	D124			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, INCLINED, DISTRIBUTION A/N: C33905	D125			PM: (9) [RULE 405, 2-7-1986]	D323.1
SCREEN, CLASSIFYING, CLASSIFYING A/N: C33905	D126			PM: (9) [RULE 405, 2-7-1986]	D323.1
SCREEN, CLASSIFYING, CLASSIFYING A/N: C33905	D127			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, OVERS A/N: C33905	D128			PM: (9) [RULE 405, 2-7-1986]	D323.1

- | | |
|---|---|
| <p>* (1) (1A) (1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5) (5A) (5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits</p> | <p>(2) (2A) (2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See section J for NESHAP/MACT requirements</p> |
|---|---|

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: RENDERING: BAKER COMMODITIES					P13.1
CONVEYOR, SCREW, OVERS RETURN A/N: C33905	D129			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, FINISHED MEAL A/N: C33905	D130			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, ELEVATOR FEED A/N: C33905	D131			PM: (9) [RULE 405, 2-7-1986]	D323.1
BUCKET ELEVATOR A/N: C33905	D132			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, OVER BIN A/N: C33905	D133			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW A/N: C33905	D134			PM: (9) [RULE 405, 2-7-1986]	D323.1
BIN, STORAGE, FINISHED MEAL A/N: C33905	D135			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW A/N: C33905	D136			PM: (9) [RULE 405, 2-7-1986]	D323.1, E175.1
CONVEYOR, SCREW A/N: C33905	D137			PM: (9) [RULE 405, 2-7-1986]	D323.1, E175.1
System 8: PET FOOD BIN					
CONVEYOR, SCREW, BIN UNLOADING A/N: C02142	D138			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, BIN UNLOADING A/N: C02142	D139			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, ELEVATOR FEED A/N: C02142	D140			PM: (9) [RULE 405, 2-7-1986]	D323.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 - (3) Denotes RECLAIM concentration limit
 - (5) (5A) (5B) Denotes command and control emission limit
 - (7) Denotes NSR applicability limit
 - (9) See App B for Emission Limits
 - (2) (2A) (2B) Denotes RECLAIM emission rate
 - (4) Denotes BACT emission limit
 - (6) Denotes air toxic control rule limit
 - (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 - (10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: RENDERING: BAKER COMMODITIES					P13.1
BUCKET ELEVATOR, TRUCK LOADING A/N: C02142	D141			PM: (9) [RULE 405, 2-7-1986]	D323.1, E175.1
System 9: MEAT-MEAL LOADING					
HOPPER, UNDERGROUND, UNLOADING A/N: A12144	D142			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW A/N: A12144	D143			PM: (9) [RULE 405, 2-7-1986]	D323.1
BUCKET ELEVATOR A/N: A12144	D144			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, BOTTOM CROSS A/N: A12144	D145			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, BOTTOM CROSS A/N: A12144	D146			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, TOP CROSS A/N: A12144	D147			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW, UNLOADING A/N: A12144	D148			PM: (9) [RULE 405, 2-7-1986]	D323.1
System 10: COCONUT OIL REFINING					
MIXER, CAUSTIC A/N: 145491	D149				
MIXER, CAUSTIC A/N: 145491	D150				
VESSEL, REFINING SEPARATOR A/N: 145491	D151				
VESSEL, REFINING SEPARATOR A/N: 145491	D152				
MIXER, WATER WASH A/N: 145491	D153				

* (1) (1A) (1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5) (5A) (5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2) (2A) (2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: RENDERING: BAKER COMMODITIES					P13.1
VESSEL, WATER WASH SEPARATOR A/N: 145491	D154				
HOPPER, DUMP A/N: 145491	D155			PM: (9) [RULE 405, 2-7-1986]	C1.1, C1.2, C1.3, D323.1, E166.2
CONVEYOR, SCREW A/N: 145491	D156			PM: (9) [RULE 405, 2-7-1986]	D323.1
TANK, FILTROL HOPPER A/N: 145491	D157			PM: (9) [RULE 405, 2-7-1986]	D323.1
TANK, FILTROL HOPPER A/N: 145491	D158			PM: (9) [RULE 405, 2-7-1986]	D323.1
DRYER, VACCUM A/N: 145491	D159				D323.1, E166.2
CONDENSER, DRIER A/N: 145491	D160				
TANK, SURGE, OIL A/N: 145491	D161				
TANK, FILTER PRECOAT, HEIGHT: 8 FT ; DIAMETER: 5 FT A/N: 145491	D162				
CONVEYOR, SCREW A/N: 145491	D163			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW A/N: 145491	D164			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW A/N: 145491	D165			PM: (9) [RULE 405, 2-7-1986]	D323.1
CONVEYOR, SCREW A/N: 145491	D166			PM: (9) [RULE 405, 2-7-1986]	D323.1
TANK, EMERGENCY A/N: 145491	D167				

* (1) (1A) (1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5) (5A) (5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2) (2A) (2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: RENDERING: BAKER COMMODITIES					P13.1
TANK, SOAP ACIDULATION, HEIGHT: 12 FT ; DIAMETER: 12 FT A/N: 145491	D168				
TANK, SOAP ACIDULATION, HEIGHT: 12 FT ; DIAMETER: 12 FT A/N: 145491	D169				
TANK, SOAP STOCK, HEIGHT: 14 FT 6 IN; DIAMETER: 8 FT A/N: 145491	D170				
TANK, SOAP DILUTION, HEIGHT: 9 FT 6 IN; DIAMETER: 6 FT 6 IN A/N: 145491	D171				
MIXER A/N: 145491	D172				
MIXER, RESIDENCE A/N: 145491	D173				
VESSEL, SEPARATOR, FATTY ACID A/N: 145491	D174				
TANK, SLUDGE A/N: 145491	D175				
TANK, DISPOSAL A/N: 145491	D176				
TANK, ACID OIL SKIM, WIDTH: 1 FT 6 IN; HEIGHT: 2 FT ; LENGTH: 5 FT 6 IN A/N: 145491	D177				
Process 2: STORAGE: BAKER COMMODITIES					
System 1: MEAT-MEAL STORAGE					
STORAGE TANK, NO. 1, MEAT MEAL, HEIGHT: 36 FT ; DIAMETER: 31 FT A/N: A12498	D178			PM: (9) [RULE 405, 2-7-1986]	D323.1

* (1) (1A) (1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5) (5A) (5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2) (2A) (2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2: STORAGE: BAKER COMMODITIES					
STORAGE TANK, NO. 2, MEAT MEAL, HEIGHT: 36 FT ; DIAMETER: 31 FT A/N: A12499	D179			PM: (9) [RULE 405, 2-7-1986]	D323.1
STORAGE SILO, MEAT MEAL, HEIGHT: 40 FT ; DIAMETER: 25 FT A/N: 355016	D323			PM: (9) [RULE 405, 2-7-1986]	D323.2
STORAGE SILO, MEAT MEAL, HEIGHT: 40 FT ; DIAMETER: 25 FT A/N: 355013	D324			PM: (9) [RULE 405, 2-7-1986]	D323.2
System 2: TALLOW STORAGE					S13.1
STORAGE TANK, STEAM HEATED, SCALE, FINISHED TALLOW, 48200 GALS; DIAMETER: 17 FT ; HEIGHT: 37 FT A/N: A42445	D180				C6.1, D12.1, E147.1
STORAGE TANK, STEAM HEATED, NO.1, TALLOW, 10155 GALS; DIAMETER: 9 FT ; HEIGHT: 26 FT A/N: A42441	D181	C212 C391			C6.2, D12.1, E147.1
STORAGE TANK, STEAM HEATED, NO.2, TALLOW, 10155 GALS; DIAMETER: 9 FT ; HEIGHT: 26 FT A/N: A42442	D182	C212 C391			C6.2, D12.1, E147.1
STORAGE TANK, STEAM HEATED, NO.6, TALLOW, 10155 GALS; DIAMETER: 9 FT ; HEIGHT: 26 FT A/N: A42443	D183	C212 C391			C6.2, D12.1, E147.1
STORAGE TANK, STEAM HEATED, NO. 8, SCALE, FINISHED TALLOW, HEIGHT: 30 FT ; DIAMETER: 16 FT A/N: C28563	D184	C212 C391			C6.3, D12.1, E54.1, E147.2

* (1) (1A) (1B) Denotes RECLAIM emission factor
(2) (2A) (2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5) (5A) (5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2: STORAGE: BAKER COMMODITIES					
STORAGE TANK, STEAM HEATED, NO. 2, TALLOW, RECEIVING, 12294 GALS; DIAMETER: 9 FT 4 IN; HEIGHT: 24 FT A/N: A79126	D185	C214 C391			C6.3, D12.1, E54.2, E147.2, E147.3
STORAGE TANK, STEAM HEATED, NO. 1, TALLOW, RECEIVING, 12294 GALS; DIAMETER: 9 FT 4 IN; HEIGHT: 24 FT A/N: A79127	D186	C214 C391			C6.3, D12.1, E54.2, E147.2, E147.3
STORAGE TANK, STEAM HEATED, NO. 4, TALLOW, RECEIVING, 12294 GALS; DIAMETER: 9 FT 4 IN; HEIGHT: 24 FT A/N: A79128	D187	C214 C391			C6.3, D12.1, E54.2, E147.2, E147.3
STORAGE TANK, STEAM HEATED, NO. 3, TALLOW, RECEIVING, 12294 GALS; DIAMETER: 9 FT 4 IN; HEIGHT: 24 FT A/N: A79129	D188	C214 C391			C6.3, D12.1, E54.2, E147.2, E147.3
STORAGE TANK, STEAM HEATED, NO. 5, TALLOW, RECEIVING, 19903 GALS; DIAMETER: 11 FT ; HEIGHT: 28 FT A/N: A82598	D189	C214 C391			C6.3, D12.1, E54.2, E147.2, E147.3
System 3: TALLOW OR RAINWATER STORAGE					S13.1
STORAGE TANK, STEAM HEATED, NO. 2, TALLOW OR RAINWATER, HEIGHT: 36 FT ; DIAMETER: 30 FT A/N: C28562	D190	C214 C391			C6.3, D12.1, E54.2, E147.2

* (1) (1A) (1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5) (5A) (5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2) (2A) (2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2: STORAGE BAKER COMMODITIES					
STORAGE TANK, STEAM HEATED, NO. 3, TALLOW OR RAINWATER, HEIGHT: 36 FT ; DIAMETER: 30 FT A/N: C28564	D191	C214 C391			C6.3, D12.1, E54.2, E147.2
System 5: FUEL DISPENSING AND STORAGE					
STORAGE TANK, UNDERGROUND, GASOLINE, NOT METHANOL COMPATIBLE, WITH PHASE I VAPOR RECOVERY SYSTEM OPW (VR-102-E/I), 10000 GALS A/N: 491623	D194			ROG: (9) [RULE 461, Universal Conditions, 1-9-2004]	D330.1, E193.2, J109.1, J373.3
FUEL DISPENSING NOZZLE, GASOLINE, BELLOWS-LESS, WITH PHASE II VAPOR RECOVERY SYSTEM, GASOLINE, HEALY PHASE II EVR NOT INCLUDING ISD (VR-201-H) A/N: 491623	D195			ROG: (9) [RULE 461, Healy Conditions, 1-9-2004; RULE 461, Universal Conditions, 1-9-2004]	D330.1, E193.2, J110.1, J373.3
System 6: FINISHED PRODUCTS STORAGE					
STORAGE TANK, FIXED ROOF, STEAM HEATED, STAR 11, BLEND OF ANIMAL FAT AND VEGETABLE OIL, 26000 GALS; DIAMETER: 12 FT 6 IN; HEIGHT: 32 FT A/N: 310984	D313				
STORAGE TANK, FIXED ROOF, STEAM HEATED, STAR 12, BLEND OF ANIMAL FAT AND VEGETABLE OIL, 26000 GALS; DIAMETER: 12 FT 6 IN; HEIGHT: 32 FT A/N: 310985	D314				

* (1) (1A) (1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5) (5A) (5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2) (2A) (2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2: STORAGE: BAKER COMMODITIES					
STORAGE TANK, FIXED ROOF, STEAM HEATED, STAR 13, BLEND OF ANIMAL FAT AND VEGETABLE OIL, 26000 GALS; DIAMETER: 12 FT 6 IN; HEIGHT: 32 FT A/N: 310986	D315				
Process 4: WASTEWATER TREATMENT: BAKER COMMODITIES					
TANK, WASTE WATER, MECHANICAL CATCH BASIN NO. 1, 8000 GALS A/N: 478995	D201				E166.3
TANK, SURGE NO. 1, WASTE WATER, 17000 GALS A/N: 478995	D202				
TANK, STORAGE NO. 6, WASTE WATER, 33000 GALS A/N: 478995	D203				
TANK, STORAGE NO. 7, WASTE WATER, 44000 GALS A/N: 478995	D204				
TANK, SLUDGE STORAGE NO. 4, 850 GALS A/N: 478995	D206				
TANK, REACTANT STORAGE NO. 2, 700 GALS A/N: 478995	D208				
TANK, CATCH BASIN NO. 1 DISCHARGE, 700 GALS A/N: 478995	D210				
PIT, LIQUID RECEIVING, WASTE WATER A/N: 478995	D328				

* (1) (1A) (1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5) (5A) (5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2) (2A) (2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 4: WASTEWATER TREATMENT: BAKER COMMODITIES					
CONVEYOR, DISCHARGE SCREW, LIQUID RECEIVING PIT A/N: 478995	D329				
TANK, STORAGE NO. T-1, WASTE WATER, 36800 GALS A/N: 478995	D349				
TANK, STORAGE NO. 2, WASTE WATER, 36500 GALS A/N: 478995	D331				
TANK, STORAGE NO. 3, WASTE WATER, 18000 GALS A/N: 478995	D332				
TANK, STORAGE NO. 4, WASTE WATER, 20600 GALS A/N: 478995	D333				
TANK, STORAGE NO. T-5, WASTE WATER, 36800 GALS A/N: 478995	D350				
TANK, SLUDGE STORAGE NO. 5, 22000 GALS A/N: 478995	D334				
TANK, SKIMMER, WASTE WATER, 11400 GALS A/N: 478995	D335				
TANK, HYDROCAL NO. 1, WASTE WATER, 7250 GALS A/N: 478995	D336				
TANK, HYDROCAL DISCHARGE, 700 GALS A/N: 478995	D337				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 - (3) Denotes RECLAIM concentration limit
 - (5) (5A) (5B) Denotes command and control emission limit
 - (7) Denotes NSR applicability limit
 - (9) See App B for Emission Limits
 - (2) (2A) (2B) Denotes RECLAIM emission rate
 - (4) Denotes BACT emission limit
 - (6) Denotes air toxic control rule limit
 - (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 - (10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 4: WASTEWATER TREATMENT, BAKER COMMODITIES					
TANK, MECHANICAL CATCH BASIN NO. 2, WASTE WATER, 8000 GALS A/N: 478995	D338				
TANK, CATCH BASIN NO. 2 DISCHARGE, 700 GALS A/N: 478995	D339				
TANK, SLUDGE STORAGE NO. 2, 7700 GALS A/N: 478995	D340				
TANK, SLUDGE STORAGE NO. 3, 17000 GALS A/N: 478995	D341				
TANK, REACTANT NO. 3, 4000 GALS A/N: 478995	D346				
TANK, MEASUREMENT NO. 1, 400 GALS A/N: 478995	D347				
TANK, MEASUREMENT NO. 1, 450 GALS A/N: 478995	D348				
TANK, STORAGE NO. S-1, SLUDGE, 21000 GALS A/N: 478995	D351				
TANK, MIXING, WASTE WATER, 10000 GALS A/N: 478995	D352				
FILTER PRESS, NO. 1, PACIFIC PRESS, WASTE WATER, MODEL P12N132A-150R A/N: 478995	D353				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits

- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
 BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 4: WASTEWATER TREATMENT: BAKER COMMODITIES					
FILTER PRESS, NO. 2, PACIFIC PRESS, WASTE WATER, MODEL P12N132A-150R A/N: 478995	D354				
TANK, STORAGE NO. T-6, SLUDGE, 36800 GALS A/N: 478995	D355				
CENTRIFUGE, NO.1, MODEL CS 21-4HC, 225 GPM CAPACITY A/N: 465910	D368	C300			E187.1
CENTRIFUGE, NO.2, MODEL CS 21-4HC, 225 GPM CAPACITY A/N: 465910	D369	C300			E187.1
Process 5: AIR POLLUTION CONTROL: BAKER COMMODITIES					
CONDENSER, SHELL AND TUBE, NO. 1, 3800 SQ.FT. A/N: 378517	C212	D24 D27 D76 D81 D82 D85 D86 D96 D97 D98 D99 D181 D182 D183 D184 C200 C215 C216 D372 D373 D374			C6.4, D12.3

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 5: AIR POLLUTION CONTROL: BAKER COMMODITIES					
CONDENSER, SHELL AND TUBE, NO. 2, 3800 SQ.FT. A/N: 378517	C213	D37 D38 D39 D41 D42 D43 D44 D45 D46 D47 D48 D49 D50 D51 D52 D53 D54 D55 D56 D58 D60 D61 D64 D65 D66 D67 D68 D70 D71 D72 D73 D74 C200 C215 C216 D303 D304 D305 D307 C370 D381 D382 D383 D384 D385 D386 D387 D388 D389			C6.4, D12.3
CONDENSER, SHELL AND TUBE, NO. 3, 3500 SQ.FT. A/N: 378517	C214	D32 D33 D34 D35 D84 D87 D91 D92 D185 D186 D187 D188 D189 D190 D191 C200 C215 C216 D306 C370			C6.4, D12.3

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 5: AIR POLLUTION CONTROL, BAKER COMMODITIES					
SCRUBBER, PACKED BED, VERTICAL, 4000 CFM, WIDTH: 4 FT ; HEIGHT: 12 FT 6 IN; LENGTH: 3 FT WITH A/N: 324827 TANK, SCRUBBER SOLUTION (WASTEWATER), HEIGHT: 6 FT ; DIAMETER: 5 FT TANK, SULFURIC ACID	C370	C200 C213 C214 C215 C216 C391			C6.11, C10.1, C12.1, D12.11, D12.12, K67.4
BOILER, INCINERATOR, WITH HEAT RECOVERY, NO. 1 SOUTH, FUEL OIL, NATURAL GAS, YELLOW GREASE, BABCOCK AND WILCOX, MODEL VC-CD, 39.9 MMBTU/HR WITH A/N: 378514 BURNER, TODD, NATURAL GAS, FUEL OIL, & YELLOW GREASE, WITH FLUE GAS RECIRCULATION, 3 TOTAL; 13.3 MMBTU/HR	C200	C212 C213 C214 C370 C391	NOX: LARGE SOURCE**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 56 PPMV NATURAL GAS (3) [RULE 2012, 5-6-2005]; NOX: 56 PPMV FUEL OIL (3) [RULE 2012, 5-6-2005]; NOX: 56 PPMV YELLOW GREASE (3) [RULE 2012, 5-6-2005]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]; SOX: 500 PPMV (5) [RULE 407, 4-2-1982]	B59.1, B59.6, C6.7, C8.1, D12.6, D328.1, D371.1, K67.3

* (1) (1A) (1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5) (5A) (5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2) (2A) (2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 5: AIR POLLUTION CONTROL: BAKER COMMODITIES					
BOILER, INCINERATOR, WITH HEAT RECOVERY, NO. 3 NORTH, FUEL OIL, NATURAL GAS, YELLOW GREASE, BABCOCK AND WILCOX, MODEL EC 2, 39.313 MMBTU/HR WITH A/N: 378517 BURNER, FUEL OIL, NATURAL GAS, YELLOW GREASE, TODD, WITH FLUE GAS RECIRCULATION, 3 TOTAL; 39.313 MMBTU/HR	C215	C212 C213 C214 C370 C391	NOX: LARGE SOURCE**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 56 PPMV NATURAL GAS (3) [RULE 2012, 5-6-2005]; NOX: 56 PPMV YELLOW GREASE (3) [RULE 2012, 5-6-2005]; NOX: 56 PPMV FUEL OIL 2 (3) [RULE 2012, 5-6-2005]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]; SOX: 500 PPMV FUEL OIL (5) [RULE 407, 4-2-1982]	B59.6, C6.7, C8.1, D12.6, D328.1, D371.1, K67.3
BOILER, INCINERATOR, WITH HEAT RECOVERY, NO. 2 CENTER, FUEL OIL, NATURAL GAS, YELLOW GREASE, BABCOCK AND WILCOX, MODEL VC CD, 39.387 MMBTU/HR WITH A/N: 378516 BURNER, FUEL OIL, NATURAL GAS, YELLOW GREASE, TODD, WITH FLUE GAS RECIRCULATION, 3 TOTAL; 39.387 MMBTU/HR	C216	C212 C213 C214 C370 C391	NOX: LARGE SOURCE**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 56 PPMV NATURAL GAS (3) [RULE 2012, 5-6-2005]; NOX: 56 PPMV YELLOW GREASE (3) [RULE 2012, 5-6-2005]; NOX: 56 PPMV FUEL OIL 2 (3) [RULE 2012, 5-6-2005]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]; SOX: 500 PPMV FUEL OIL (5) [RULE 407, 4-2-1982]	B59.6, C6.7, C8.1, D12.6, D328.1, D371.1, K67.3

* (1) (1A) (1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5) (5A) (5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2) (2A) (2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 5: AIR POLLUTION CONTROL: BAKER COMMODITIES					
CONDENSER, AIR COOLED, 77,508 SQ. FT. SURFACE AREA WITH A/N: 509114	C391	D24 D27 D32 D33 D34 D35 D37 D38 D39 D41 D42 D43 D44 D45 D46 D47 D48 D49 D50 D51 D52 D53 D54 D55 D56 D58 D60 D61 D64 D65 D66 D67 D68 D70 D71 D72 D73 D74 D76 D81 D82 D84 D85 D86 D87 D91 D92 D96 D97 D98 D99 D181 D182 D183 D184 D185 D186 D187 D188 D189 D190 D191 C200 C215 C216 D303 D304 D305 D307 C370 D372 D373 D374 D381 D382 D383 D384 D385 D386 D387 D388 D389			C6.13
BLOWER, FAN NO. 1, 50 HP					

* (1) (1A) (1B) Denotes RECLAIM emission factor
(2) (2A) (2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5) (5A) (5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 5: AIR POLLUTION CONTROL: BAKER COMMODITIES					
BLOWER, FAN NO. 2, 50 HP					
Process 6: RENDERING: J & M					
System 1: HIGH TEMPERATURE RENDERING					
BIN, ANIMAL MATTER, RECEIVING, WIDTH: 10 FT ; DEPTH: 6 FT ; LENGTH: 31 FT 6 IN A/N: A60640	D217				E187.1
CONVEYOR, SCREW, TWIN A/N: A60640	D218				E187.1
CONVEYOR, SCREW, INCLINED A/N: A60640	D219				E187.1
VESSEL, ELECTRO MAGNET A/N: A60640	D220				E187.1
CONVEYOR, SCREW, TWIN, EAST HOGGER FEED A/N: A60640	D221				E187.1
SHREDDER, EAST HOGGER A/N: A60640	D222	C300			E187.1
CONVEYOR, SCREW, COOKER FEED A/N: A60640	D223				E187.1
RENDERING COOKER, CONTINUOUS RENDERING A/N: A60640	D224	C300			C6.5, D12.4, E187.1
VESSEL, TRAP, CYCLONIC ENTRAINMENT A/N: A60640	D225				E187.1
VESSEL, CONTROL WHEEL, COOKER DISCHARGE A/N: A60640	D226				E187.1
System 2: RENDERED PRODUCTS HANDLING					

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 6: RENDERING: J & M					P13.1
CONVEYOR, SCREW A/N: C10336	D227	C300			E187.1
CONVEYOR, SCREW, COOKER DISCHARGE A/N: C10336	D228	C300			E187.1
CONVEYOR, SCREW, TALLOW A/N: C10336	D229	C300			E187.1
BUCKET ELEVATOR, TALLOW A/N: C10336	D230	C300			E187.1
VESSEL, PRE-PRESS A/N: C10336	D231	C300			E187.1
CLARIFIER A/N: C10336	D232	C300			E187.1
SCREEN, CLASSIFYING, CLASSIFYING A/N: C10336	D233	C300			E187.1
CENTRIFUGE, HORIZONTAL DRUM A/N: C10336	D234	C300			E187.1
VESSEL, PRESS A/N: C10336	D235	C300			E187.1
CONVEYOR, SCREW, PRESS FEED A/N: C10336	D236	C300			E187.1
VESSEL, PRESS A/N: C10336	D237	C300			E187.1
CONVEYOR, SCREW, COOKER RETURN A/N: C10336	D238	C300			E187.1
CONVEYOR, SCREW, TEST A/N: C10336	D239	C300			E187.1
CONVEYOR, SCREW, CRAX DISCHARGE A/N: C10336	D240	C300			E187.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 - (3) Denotes RECLAIM concentration limit
 - (5) (5A) (5B) Denotes command and control emission limit
 - (7) Denotes NSR applicability limit
 - (9) See App B for Emission Limits
 - (2) (2A) (2B) Denotes RECLAIM emission rate
 - (4) Denotes BACT emission limit
 - (6) Denotes air toxic control rule limit
 - (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 - (10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 6: RENDERING: J & M					P13.1
CONVEYOR, SCREW, INCLINED A/N: C10336	D241	C300			E187.1
CONVEYOR, SCREW, INCLINED A/N: C10336	D242	C300			E187.1
CONVEYOR, SCREW, EMERGENCY COOKER UNLOADING A/N: C10336	D243	C300			E187.1
BUCKET ELEVATOR, CRAX BIN UNLOADING A/N: C10336	D244				E187.1
BIN, CRAX A/N: C10336	D245				E187.1
System 3: PET FOOD BLENDING					
HOPPER, MEAT-MEAL, RECEIVING A/N: C34012	D246			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
CONVEYOR, SCREW A/N: C34012	D247			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
CONVEYOR, SCREW, INCLINED A/N: C34012	D248			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
SCREEN, CLASSIFYING, CLASSIFYING A/N: C34012	D249			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
SCREEN, CLASSIFYING, CLASSIFYING, OVERS A/N: C34012	D250			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
CONVEYOR, SCREW, OVERS A/N: C34012	D251			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
BIN, OVERS A/N: C34012	D252			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
BUCKET ELEVATOR A/N: C34012	D253			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
 BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 6: RENDERING: J & M					P13.1
CONVEYOR, SCREW, FEED A/N: C34012	D254			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
CONVEYOR, SCREW, OVERBINS A/N: C34012	D255			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
BIN, SURGE, 7800 GALS A/N: C34012	D256			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
CONVEYOR, SCREW, DISTRIBUTION A/N: C34012	D257			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
CONVEYOR, SCREW, UNLOADING A/N: C34012	D258			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
BIN, SURGE, 7800 GALS A/N: C34012	D259			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
CONVEYOR, SCREW, DISTRIBUTION A/N: C34012	D260			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
CONVEYOR, SCREW, UNLOADING A/N: C34012	D261			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
CONVEYOR, SCREW, CROSS A/N: C34012	D262			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
CONVEYOR, SCREW, INCLINED A/N: C34012	D263			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
HOPPER, MEAT-MEAL, BAGGING A/N: C34012	D264			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
CONVEYOR, SCREW, UNLOADING A/N: C34012	D265			PM: (9) [RULE 405, 2-7-1986]	D323.1, E187.1
System 4: TRAP GREASE PROCESSING					
COOKER, STEAM HEATED A/N: A75423	D268	C300			
SCREEN, CLASSIFYING, CLASSIFYING A/N: A75423	D269				

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 6: RENDERING: J & M					P13.1
CONVEYOR, SCREW A/N: A75423	D270				
DRYER A/N: A75423	D271	C300			
System 5: GREASE DRYING					
TANK, GREASE, DRYING, STEAM HEATED, 8450 GALS; DIAMETER: 7 FT 7 IN; HEIGHT: 25 FT A/N: 127555	D272	C300			
TANK, VERTICAL DRYING, HEATED, 10000 GALS; DIAMETER: 7 FT 8 IN; HEIGHT: 31 FT 2 IN A/N: 273917	D273	C300			
System 6: GLYCEROLYSIS					
REACTOR, TANK, 8200 GAL A/N: 477180	D361				B59.4, C6.9
TANK, STORAGE, CRUDE GLYCERIN A/N: 477180	D362				
HEAT EXCHANGER, THERMAL OIL A/N: 477180	D363				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 6: RENDERING: J & M					P13.1
HEATER, NATURAL GAS, PARKER BOILER, MODEL HT-1920L, 1.92 MMBTU/HR A/N: 477180	D364			CO: 100 PPMV NATURAL GAS (4) [RULE 1303, 5-10-1996; RULE 1303, 12-6-2002]; CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982]; NOX: 20 PPMV NATURAL GAS (4) [RULE 2005, 5-6-2005]; NOX: 130 LBS/MMBTU NATURAL GAS (1) [RULE 2012(e)(1)(A)(ii) -NOx Process Unit, 4-11-1997]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	
TANK, ACCUMULATOR, THERMAL OIL, 200 GAL A/N: 477180	D365				
TANK, EXPANSION, THERMAL OIL, 500 GAL A/N: 477180	D366				
CONDENSER, VAPOR A/N: 477180	D367				E71.1
Process 7: STORAGE: J & M					
System 1: TALLOW					S13.1
STORAGE TANK, STEAM HEATED, NO. A, TALLOW, HEIGHT: 30 FT ; DIAMETER: 19 FT A/N: C27161	D274	C300			C6.3, D12.1, E54.3, E147.2
STORAGE TANK, STEAM HEATED, NO. B, TALLOW, HEIGHT: 30 FT ; DIAMETER: 19 FT A/N: C27162	D275	C300			C6.3, D12.1, E54.3, E147.2
System 2: GREASE					S13.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor (2) (2A) (2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5) (5A) (5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 7: STORAGE: J & M					
STORAGE TANK, NO. 1, TRAP GREASE, RECEIVING, HEIGHT: 25 FT ; DIAMETER: 11 FT A/N: A75428	D278	C300			
STORAGE TANK, NO. 2, TRAP GREASE, RECEIVING, HEIGHT: 25 FT ; DIAMETER: 11 FT A/N: A75429	D279	C300			
STORAGE TANK, NO. 3, TRAP GREASE, RECEIVING, HEIGHT: 25 FT ; DIAMETER: 11 FT A/N: A75430	D280	C300			
STORAGE TANK, NO. 4, TRAP GREASE, RECEIVING, HEIGHT: 16 FT ; DIAMETER: 9 FT A/N: A75431	D281	C300			
STORAGE TANK, STEAM HEATED, NO. 8, YELLOW GREASE, 12794 GALS; DIAMETER: 11 FT ; HEIGHT: 23 FT 4 IN A/N: 232418	D282	C300			B59.3
STORAGE TANK, STEAM HEATED, NO. 2, GREASE, HEIGHT: 20 FT ; DIAMETER: 11 FT A/N: C20824	D283	C300			C6.3, D12.1, E54.3, E147.2
System 3: FEED-FAT: STAR GREASE					
STORAGE TANK, STEAM HEATED, NO. 5, FEED-FAT, HEIGHT: 18 FT ; DIAMETER: 20 FT A/N: C01368	D284	C300			E187.1
System 5: GREASE, TALLOW, OR WASTEWATER					

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 7: STORAGE: J & M					
STORAGE TANK, STEAM HEATED, WASTE WATER, GREASE, TALLOW, HEIGHT: 27 FT ; DIAMETER: 12 FT A/N: 367129	D320	C300			C6.3, D12.1, E54.3, E147.2
STORAGE TANK, STEAM HEATED, WASTEWATER, GREASE, TALLOW, HEIGHT: 29 FT ; DIAMETER: 10 FT A/N: 367130	D321	C300			C6.3, D12.1, E54.3, E147.2
STORAGE TANK, STEAM HEATED, WASTEWATER, GREASE, TALLOW, HEIGHT: 27 FT ; DIAMETER: 10 FT A/N: 367131	D322	C300			C6.3, D12.1, E54.3, E147.2
STORAGE TANK, NO. A-1, STEAM HEATED, WASTE WATER, GREASE, TALLOW, 21432 GALS; DIAMETER: 12 FT ; HEIGHT: 22 FT 6 IN A/N: 491622	D377	C300			C6.3, E54.3, E147.2, E166.3
STORAGE TANK, NO. A-2, STEAM HEATED, WASTE WATER, GREASE, TALLOW, 21432 GALS; DIAMETER: 12 FT ; HEIGHT: 22 FT 6 IN A/N: 491624	D378	C300			C6.3, E54.3, E147.2, E166.3
STORAGE TANK, NO. A-3, STEAM HEATED, WASTE WATER, GREASE, TALLOW, 21432 GALS; DIAMETER: 12 FT ; HEIGHT: 22 FT 6 IN A/N: 491625	D379	C300			C6.3, E54.3, E147.2, E166.3
STORAGE TANK, NO. A-4, STEAM HEATED, WASTE WATER, GREASE, TALLOW, 21432 GALS; DIAMETER: 12 FT ; HEIGHT: 22 FT 6 IN A/N: 491626	D380	C300			C6.3, E54.3, E147.2, E166.3

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 7: STORAGE: J & M					
STORAGE TANK, NO. A-5, STEAM HEATED, WASTE WATER, GREASE, TALLOW, 21432 GALS; DIAMETER: 12 FT ; HEIGHT: 22 FT 6 IN A/N: 532948	D395	C300			C6.14, E54.4, E147.2, E166.3
STORAGE TANK, NO. A-6, STEAM HEATED, WASTE WATER, GREASE, TALLOW, 21432 GALS; DIAMETER: 12 FT ; HEIGHT: 22 FT 6 IN A/N: 532949	D396	C300			C6.14, E54.4, E147.2, E166.3
STORAGE TANK, NO. A-7, STEAM HEATED, WASTE WATER, GREASE, TALLOW, 21432 GALS; DIAMETER: 12 FT ; HEIGHT: 22 FT 6 IN A/N: 532950	D397	C300			C6.14, E54.4, E147.2, E166.3
STORAGE TANK, NO. A-8, STEAM HEATED, WASTE WATER, GREASE, TALLOW, 21432 GALS; DIAMETER: 12 FT ; HEIGHT: 22 FT 6 IN A/N: 532951	D398	C300			C6.14, E54.4, E147.2, E166.3
Process 8: GREASE RECEIVING: STAR GREASE PROCESSING					P13.1
BULK MATERIAL LOAD/UNLOAD STATION, BARREL DUMPER A/N: 478349	D290				E187.1

* (1) (1A) (1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5) (5A) (5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2) (2A) (2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 8: GREASE RECEIVING: STAR GREASE PROCESSING					P13.1
HOT POT/KETTLE, NATURAL GAS, GREASE, MELTING, 1.3 MMBTU/HR WITH A/N: 478349 BURNER, NATURAL GAS, MAXON, MODEL TYPE 13, 52 TOTAL: 1.3 MMBTU/HR	D356	C300	NOX: PROCESS UNIT**	CO: 100 PPMV NATURAL GAS (4) [RULE 1303, 5-10-1996; RULE 1303, 12-6-2002]; CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982]; NOX: 20 PPMV (4) [RULE 2005, 5-6-2005]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5A) [RULE 409, 8-7-1981]	C6.12, D323.1, E187.1
CONVEYOR, DRAG A/N: 478349	D292				E187.1
DRUM, WASHER, 10 FT L., 4 FT W., 4.5 FT H., SPRAY NOZZLE WITH A/N: 478349 PUMP, RECIRCULATION, WASH WATER, 10 HP	D358				E187.1
TANK, SURGE, 1269 GAL A/N: 478349	D360				
SCREEN, CLASSIFYING A/N: 478349	D295				E187.1
SCREEN, CLASSIFYING A/N: 478349	D357				E187.1
CONVEYOR, SCREW A/N: 478349	D293				E187.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 - (3) Denotes RECLAIM concentration limit
 - (5) (5A) (5B) Denotes command and control emission limit
 - (7) Denotes NSR applicability limit
 - (9) See App B for Emission Limits
 - (2) (2A) (2B) Denotes RECLAIM emission rate
 - (4) Denotes BACT emission limit
 - (6) Denotes air toxic control rule limit
 - (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 - (10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 8: GREASE RECEIVING: STAR GREASE PROCESSING					P13.1
CONVEYOR, SCREW, REJECT A/N: 478349	D294				E187.1
Process 9: GREASE STORAGE: STAR GREASE PROCESSING					P13.1
STORAGE TANK, STEAM HEATED, NO. 1, GREASE, HEIGHT: 17 FT ; DIAMETER: 11 FT 6 IN A/N: C03551	D296	C300			E187.1
STORAGE TANK, STEAM HEATED, NO. 3, GREASE WASHINGS, HEIGHT: 17 FT ; DIAMETER: 6 FT A/N: A44580	D297	C300			B59.2, C6.6, D12.1, E147.1, E147.3
STORAGE TANK, STEAM HEATED, NO. 4, GREASE, HEIGHT: 18 FT ; DIAMETER: 9 FT A/N: C03358	D298	C300			E187.1
STORAGE TANK, STEAM HEATED, NO. 9, YELLOW GREASE, 22000 GALS; DIAMETER: 11 FT 7 IN; HEIGHT: 34 FT 4 IN A/N: 250985	D299	C300			B59.3
Process 10: APC SYSTEM: J & M/STAR GREASE PROCESSING					

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
 BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 10: APC SYSTEM: J & M/STAR GREASE PROCESSING					
CONDENSER, SHELL AND TUBE, VERTICAL, HEIGHT: 26 FT ; 2800 SQ.FT., DIAMETER: 3 FT A/N: 532952	C300	D222 D224 D227 D228 D229 D230 D231 D232 D233 D234 D235 D236 D237 D238 D239 D240 D241 D242 D243 D268 D271 D272 D273 D274 D275 D278 D279 D280 D281 D282 D283 D284 D296 D297 D298 D299 C301 D320 D321 D322 D356 D368 D369 D377 D378 D379 D380 D395 D396 D397 D398			
CONDENSER, SHELL AND TUBE, CYCLONE, WIDTH: 1 FT 4 IN; HEIGHT: 2 FT 4 IN; LENGTH: 3 FT A/N: 532952	C301	C300 C302			

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 10: APC SYSTEM: J & M/STAR GREASE PROCESSING					
AFTERBURNER, NATURAL GAS, 8 MMBTU/HR WITH A/N: 532952 BOILER, ECLIPSE, MODEL 3 HR, WASTE HEAT	C302	C301	NOX: PROCESS UNIT**	CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5A) [RULE 409, 8-7-1981]	C8.2, D323.1
Process 13: Rule 219 Exempt Equipment Subject to Source-Specific Requirements					
System 1: RULE 219 EXEMPT EQUIPMENT					
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS	E316			ROG: (9) [RULE 1113, 11-8-1996; RULE 1113, 6-3-2011; RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	K67.1

* (1) (1A) (1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5) (5A) (5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2) (2A) (2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

**FACILITY PERMIT TO OPERATE
 BAKER COMMODITIES INC**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D1	1	1	1
D2	1	1	1
D3	1	1	1
D4	1	1	1
D5	1	1	1
D6	1	1	1
D7	1	1	1
D8	1	1	1
D9	1	1	1
D10	1	1	1
D11	1	1	1
D12	2	1	1
D13	2	1	1
D14	2	1	1
D15	2	1	1
D16	2	1	1
D17	2	1	1
D18	2	1	1
D19	2	1	1
D20	2	1	1
D21	2	1	1
D22	2	1	1
D23	2	1	1
D24	3	1	2
D25	3	1	2
D26	3	1	2
D27	3	1	2
D28	3	1	2
D29	3	1	2
D30	3	1	2
D31	3	1	2
D32	3	1	3
D33	3	1	3
D34	4	1	3
D35	4	1	3

**FACILITY PERMIT TO OPERATE
 BAKER COMMODITIES INC**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D37	4	1	4
D38	4	1	4
D39	4	1	4
D41	4	1	4
D42	4	1	4
D43	4	1	4
D44	4	1	4
D45	4	1	4
D46	4	1	4
D47	4	1	4
D48	4	1	4
D49	4	1	4
D50	5	1	4
D51	5	1	4
D52	5	1	4
D53	5	1	4
D54	5	1	4
D55	5	1	4
D56	5	1	4
D57	5	1	4
D58	5	1	4
D60	5	1	4
D61	5	1	4
D63	5	1	4
D64	6	1	4
D65	6	1	4
D66	6	1	4
D67	6	1	4
D68	6	1	4
D70	6	1	4
D71	6	1	4
D72	6	1	4
D73	6	1	4
D74	6	1	4
D76	7	1	5

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D81	7	1	5
D82	8	1	5
D84	8	1	5
D85	8	1	5
D86	8	1	5
D87	8	1	5
D90	8	1	5
D91	8	1	5
D92	8	1	5
D93	8	1	6
D94	9	1	6
D95	9	1	6
D96	9	1	6
D97	9	1	6
D98	9	1	6
D99	9	1	6
D100	9	1	7
D101	9	1	7
D102	9	1	7
D103	9	1	7
D104	9	1	7
D105	10	1	7
D106	10	1	7
D107	10	1	7
D108	10	1	7
D109	10	1	7
D110	10	1	7
D111	10	1	7
D112	10	1	7
D113	10	1	7
D114	10	1	7
D115	10	1	7
D116	10	1	7
D117	10	1	7
D118	11	1	7

**FACILITY PERMIT TO OPERATE
 BAKER COMMODITIES INC**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D119	11	1	7
D120	11	1	7
D121	11	1	7
D122	11	1	7
D123	11	1	7
D124	11	1	7
D125	11	1	7
D126	11	1	7
D127	11	1	7
D128	11	1	7
D129	12	1	7
D130	12	1	7
D131	12	1	7
D132	12	1	7
D133	12	1	7
D134	12	1	7
D135	12	1	7
D136	12	1	7
D137	12	1	7
D138	12	1	8
D139	12	1	8
D140	12	1	8
D141	13	1	8
D142	13	1	9
D143	13	1	9
D144	13	1	9
D145	13	1	9
D146	13	1	9
D147	13	1	9
D148	13	1	9
D149	13	1	10
D150	13	1	10
D151	13	1	10
D152	13	1	10
D153	13	1	10

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D154	14	1	10
D155	14	1	10
D156	14	1	10
D157	14	1	10
D158	14	1	10
D159	14	1	10
D160	14	1	10
D161	14	1	10
D162	14	1	10
D163	14	1	10
D164	14	1	10
D165	14	1	10
D166	14	1	10
D167	14	1	10
D168	15	1	10
D169	15	1	10
D170	15	1	10
D171	15	1	10
D172	15	1	10
D173	15	1	10
D174	15	1	10
D175	15	1	10
D176	15	1	10
D177	15	1	10
D178	15	2	1
D179	16	2	1
D180	16	2	2
D181	16	2	2
D182	16	2	2
D183	16	2	2
D184	16	2	2
D185	17	2	2
D186	17	2	2
D187	17	2	2
D188	17	2	2

**FACILITY PERMIT TO OPERATE
 BAKER COMMODITIES INC**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D189	17	2	2
D190	17	2	3
D191	18	2	3
D194	18	2	5
D195	18	2	5
C200	24	5	0
D201	19	4	0
D202	19	4	0
D203	19	4	0
D204	19	4	0
D206	19	4	0
D208	19	4	0
D210	19	4	0
C212	22	5	0
C213	23	5	0
C214	23	5	0
C215	25	5	0
C216	25	5	0
D217	27	6	1
D218	27	6	1
D219	27	6	1
D220	27	6	1
D221	27	6	1
D222	27	6	1
D223	27	6	1
D224	27	6	1
D225	27	6	1
D226	27	6	1
D227	28	6	2
D228	28	6	2
D229	28	6	2
D230	28	6	2
D231	28	6	2
D232	28	6	2
D233	28	6	2

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D234	28	6	2
D235	28	6	2
D236	28	6	2
D237	28	6	2
D238	28	6	2
D239	28	6	2
D240	28	6	2
D241	29	6	2
D242	29	6	2
D243	29	6	2
D244	29	6	2
D245	29	6	2
D246	29	6	3
D247	29	6	3
D248	29	6	3
D249	29	6	3
D250	29	6	3
D251	29	6	3
D252	29	6	3
D253	29	6	3
D254	30	6	3
D255	30	6	3
D256	30	6	3
D257	30	6	3
D258	30	6	3
D259	30	6	3
D260	30	6	3
D261	30	6	3
D262	30	6	3
D263	30	6	3
D264	30	6	3
D265	30	6	3
D268	30	6	4
D269	30	6	4
D270	31	6	4

**FACILITY PERMIT TO OPERATE
 BAKER COMMODITIES INC**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D271	31	6	4
D272	31	6	5
D273	31	6	5
D274	32	7	1
D275	32	7	1
D278	33	7	2
D279	33	7	2
D280	33	7	2
D281	33	7	2
D282	33	7	2
D283	33	7	2
D284	33	7	3
D290	35	8	0
D292	36	8	0
D293	36	8	0
D294	37	8	0
D295	36	8	0
D296	37	9	0
D297	37	9	0
D298	37	9	0
D299	37	9	0
C300	38	10	0
C301	38	10	0
C302	39	10	0
D303	6	1	4
D304	6	1	4
D305	7	1	4
D306	7	1	4
D307	7	1	4
D313	18	2	6
D314	18	2	6
D315	19	2	6
E316	39	13	1
D320	34	7	5
D321	34	7	5

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D322	34	7	5
D323	16	2	1
D324	16	2	1
D328	19	4	0
D329	20	4	0
D331	20	4	0
D332	20	4	0
D333	20	4	0
D334	20	4	0
D335	20	4	0
D336	20	4	0
D337	20	4	0
D338	21	4	0
D339	21	4	0
D340	21	4	0
D341	21	4	0
D346	21	4	0
D347	21	4	0
D348	21	4	0
D349	20	4	0
D350	20	4	0
D351	21	4	0
D352	21	4	0
D353	21	4	0
D354	22	4	0
D355	22	4	0
D356	36	8	0
D357	36	8	0
D358	36	8	0
D360	36	8	0
D361	31	6	6
D362	31	6	6
D363	31	6	6
D364	32	6	6
D365	32	6	6

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D366	32	6	6
D367	32	6	6
D368	22	4	0
D369	22	4	0
C370	24	5	0
D372	7	1	5
D373	7	1	5
D374	8	1	5
D377	34	7	5
D378	34	7	5
D379	34	7	5
D380	34	7	5
D381	5	1	4
D382	5	1	4
D383	5	1	4
D384	6	1	4
D385	6	1	4
D386	7	1	4
D387	7	1	4
D388	7	1	4
D389	7	1	4
C391	27	5	0
D395	35	7	5
D396	35	7	5
D397	35	7	5
D398	35	7	5

FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or

(b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

F14.1 The operator shall not burn liquid fuel containing sulfur compounds in excess of 500 ppm by weight.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

F14.2 The operator shall not purchase diesel fuel containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

PROCESS CONDITIONS

P13.1 All devices under this process are subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Odor	District Rule	472
------	---------------	-----

[RULE 472, 5-7-1976]

[Processes subject to this condition : 1, 6, 8, 9]

SYSTEM CONDITIONS

S13.1 All devices under this system are subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
Odor	District Rule	472

[RULE 472, 5-7-1976]

[Systems subject to this condition : Process 2, System 2 , 3; Process 7, System 1 , 2 , 3]

DEVICE CONDITIONS

B. Material/Fuel Type Limits

B59.1 The operator shall only use the following material(s) in this device :

fuel that has been fully atomized before the combustion of fuel oil

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C200]

B59.2 The operator shall not use the following material(s) in this device :

Tallow

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002**]

[Devices subject to this condition : D297]

B59.3 The operator shall only use the following material(s) in this device :

Yellow Grease

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002**]

[Devices subject to this condition : D282, D299]

B59.4 The operator shall only use the following material(s) in this device :

Brown grease and glycerin

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1401,
3-7-2008**]

[Devices subject to this condition : D361]

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

B59.6 The operator shall not use the following material(s) in this device :

Yellow Grease with an ash content greater than 0.02 percent by weight.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[**RULE 1303, 5-10-1996; RULE 1303, 12-6-2002; RULE 401, 3-2-1984; RULE 401, 11-9-2001**]

[Devices subject to this condition : C200, C215, C216]

C. Throughput or Operating Parameter Limits

C1.1 The operator shall limit the throughput to no more than 18000 lb(s)/hr.

For the purpose of this condition, throughput shall be defined as coconut oil processed.

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002**]

[Devices subject to this condition : D155]

C1.2 The operator shall limit the material processed to no more than 2400 lb(s) in any one day.

For the purpose of this condition, material processed shall be defined as filter clay processed.

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002**]

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D155]

C1.3 The operator shall limit the material processed to no more than 300 lb(s) in any one day.

For the purpose of this condition, material processed shall be defined as carbon black processed.

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002**]

[Devices subject to this condition : D155]

C1.7 The operator shall limit the material processed to no more than 800 ton(s) in any one day.

For the purpose of this condition, material processed shall be defined as raw material.

This limit shall be based on the total combined limit for equipment of this system.

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002**]

[Devices subject to this condition : D37, D38, D39, D41, D42, D43, D44, D45, D46, D47, D48, D49, D50, D51, D52, D53, D54, D55, D56, D57, D58, D60, D61, D63, D64, D65, D66, D67, D68, D70, D71, D72, D73, D74, D303, D304, D305, D306, D307, D381, D382, D383, D384, D385, D386, D387, D388, D389]

C1.8 The operator shall limit the material processed to no more than 400 ton(s) in any one day.

For the purpose of this condition, material processed shall be defined as tallow.

This limit shall be based on the total combined limit for equipment of this system.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D37, D38, D39, D41, D42, D43, D44, D45, D46, D47, D48, D49, D50, D51, D52, D53, D54, D55, D56, D57, D58, D60, D61, D63, D64, D65, D66, D67, D68, D70, D71, D72, D73, D74, D303, D304, D305, D306, D307, D381, D382, D383, D384, D385, D386, D387, D388, D389]

C1.11 The operator shall limit the material processed to no more than 240 ton(s) in any one day.

For the purpose of this condition, material processed shall be defined as solid meal.

This limit shall be based on the total combined limit for equipment of this system.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D37, D38, D39, D41, D42, D43, D44, D45, D46, D47, D48, D49, D50, D51, D52, D53, D54, D55, D56, D57, D58, D60, D61, D63, D64, D65, D66, D67, D68, D70, D71, D72, D73, D74, D303, D304, D305, D306, D307, D381, D382, D383, D384, D385, D386, D387, D388, D389]

C6.1 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 220 Deg F.

To comply with this condition, the operator shall monitor the temperature as specified in condition number 12-1.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472, 5-7-1976]

[Devices subject to this condition : D180]

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C6.2 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 190 Deg F.

To comply with this condition, the operator shall monitor the temperature as specified in condition number 12-1.

**[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472,
5-7-1976]**

[Devices subject to this condition : D181, D182, D183]

C6.3 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 150 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature in the tank.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

**[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472,
5-7-1976]**

[Devices subject to this condition : D184, D185, D186, D187, D188, D189, D190,
D191, D274, D275, D283, D320, D321, D322, D377, D378, D379, D380]

C6.4 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 120 Deg F.

To comply with this condition, the operator shall monitor the temperature as specified in condition number 12-3.

**[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472,
5-7-1976]**

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C212, C213, C214]

- C6.5 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 290 Deg F.

To comply with this condition, the operator shall monitor the temperature as specified in condition number 12-4.

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472, 5-7-1976**]

[Devices subject to this condition : D224]

- C6.6 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 180 Deg F.

To comply with this condition, the operator shall monitor the temperature as specified in condition number 12-1.

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472, 5-7-1976**]

[Devices subject to this condition : D297]

- C6.7 The operator shall use this equipment in such a manner that the pressure being monitored, as indicated below, does not exceed 3.75 Psig.

The operator shall install and maintain a pressure gauge to accurately indicate the pressure of the natural gas feed to the boiler.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002**]

FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C200, C215, C216]

- C6.9 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 500 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature of the reactor.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D361]

- C6.11 The operator shall use this equipment in such a manner that the pH being monitored, as indicated below, does not exceed 8 of the pH scale.

[RULE 1303, 5-10-1996; RULE 1303, 12-6-2002]

[Devices subject to this condition : C370]

- C6.12 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 500 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature in the hot pot/kettle.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D356]

- C6.13 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 125 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature of the water discharge from the condenser.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472, 5-7-1976]

[Devices subject to this condition : C391]

- C6.14 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 140 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature in the tank.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472, 5-7-1976]

[Devices subject to this condition : D395, D396, D397, D398]

- C8.1 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, is not less than 1202 Deg F.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall install and maintain a temperature gauge to accurately indicate and continuously record the temperature in the combustion chamber of the boiler within one foot of the wall opposite of the burner plane.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

**[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472,
5-7-1976]**

[Devices subject to this condition : C200, C215, C216]

C8.2 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, is not less than 1202 Deg F.

To comply with this condition, the operator shall install and maintain a(n) continuous monitoring system to accurately indicate the temperature in the combustion chamber of the afterburner.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

**[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472,
5-7-1976]**

[Devices subject to this condition : C302]

C10.1 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, is maintained between 3 and 6 inches water column.

[RULE 1303, 5-10-1996; RULE 1303, 12-6-2002]

[Devices subject to this condition : C370]

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- C12.1 The operator shall use this equipment in such a manner that the scrubber solution flow rate being monitored as indicated below is greater than or equal to 25 gpm.

[RULE 1303, 5-10-1996; RULE 1303, 12-6-2002]

[Devices subject to this condition : C370]

D. Monitoring/Testing Requirements

- D12.1 The operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature in the tank.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472, 5-7-1976]

[Devices subject to this condition : D180, D181, D182, D183, D184, D185, D186, D187, D188, D189, D190, D191, D274, D275, D283, D297, D320, D321, D322]

- D12.3 The operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature of the water discharge from the condenser.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C212, C213, C214]

- D12.4 The operator shall install and maintain a(n) gauge to accurately indicate the temperature of the material discharged from the cooker.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472, 5-7-1976]



FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D224]

D12.6 The operator shall install and maintain a(n) non-resettable totalizing fuel meter to accurately indicate the fuel usage of the equipment.

[RULE 2012, 5-6-2005]

[Devices subject to this condition : C200, C215, C216]

D12.11 The operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the scrubber.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C370]

D12.12 The operator shall install and maintain a(n) pH meter to accurately indicate the pH of the scrubber solution.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C370]

D322.1 The operator shall perform annual inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D84, D374]

FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D100, D101, D102, D103, D104, D105, D106,
D107, D108, D109, D110, D111, D112, D113, D114, D115, D116, D117, D118,
D119, D120, D121, D122, D123, D124, D125, D126, D127, D128, D129, D130,
D131, D132, D133, D134, D135, D136, D137, D138, D139, D140, D141, D142,
D143, D144, D145, D146, D147, D148, D155, D156, D157, D158, D159, D163,
D164, D165, D166, D178, D179, D246, D247, D248, D249, D250, D251, D252,
D253, D254, D255, D256, D257, D258, D259, D260, D261, D262, D263, D264,
D265, C302, D356]

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.2 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a daily basis whenever fuel oil is burned. The routine daily inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.
In addition, the operator shall have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within 72 hours of conversion to fuel oil firing and on a weekly basis thereafter, until the equipment stops firing fuel oil.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- 4). All visible emission observation records by operator or a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D323, D324]

- D328.1 The operator shall determine compliance with the CO emission limit(s) either: (a) conducting a source test at least once every five years using AQMD Method 100.1 or 10.1; or (b) conducting a test at least annually using a portable analyzer and AQMD-approved test method. The test shall be conducted when the equipment is operating under normal conditions to demonstrate compliance with Rule 1146 concentration limit. The operator shall comply with all general testing, reporting, and recordkeeping requirements in Sections E and K of this permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C200, C215, C216]

- D330.1 The operator shall have a person that has been trained in accordance with Rule 461 conduct a semi-annual inspection of the gasoline transfer and dispensing equipment. The first inspection shall be in accordance with Rule 461, Attachment B, the second inspection shall be in accordance with Rule 461, Attachment C, and the subsequent inspections shall alternate protocols. The operator shall keep records of the inspection and the repairs in accordance to Rule 461 and Section K of this Permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D194, D195]

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D371.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever this equipment has combusted one million gallons of diesel fuel, to be counted cumulatively over a five year period. The inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall:

Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three working days (or during the next fuel oil firing period if the unit ceases firing on fuel oil within the three working day time frame) and report any deviations to AQMD.

In addition, the operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- a). Stack or emission point identification;
- b). Description of any corrective actions taken to abate visible emissions;
- c). Date and time visible emission was abated; and
- d). Visible emission observation record by a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C200, C215, C216]

FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D381.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions; and
- 3). Date and time visible emission was abated.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D84]

E. Equipment Operation/Construction Requirements

E54.1 The operator is not required to vent this equipment to the following equipment if all of the requirements listed below are met:

Device ID: C212 [CONDENSER, NO. 1]

Requirement number 1: complies with condition C6.3

Requirement number 2: complies with condition E147.2

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472, 5-7-1976]

[Devices subject to this condition : D184]

E54.2 The operator is not required to vent this equipment to the following equipment if all of the requirements listed below are met:

Device ID: C214 [CONDENSER, NO. 3]

Requirement number 1: complies with condition C6.3

Requirement number 2: complies with condition E147.2

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472, 5-7-1976]

[Devices subject to this condition : D185, D186, D187, D188, D189, D190, D191]

E54.3 The operator is not required to vent this equipment to the following equipment if all of the requirements listed below are met:

Device ID: C300 [CONDENSER, VERTICAL]

Requirement number 1: complies with condition C6.3

Requirement number 2: complies with condition E147.2

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472, 5-7-1976]

[Devices subject to this condition : D274, D275, D283, D320, D321, D322, D377, D378, D379, D380]

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E54.4 The operator is not required to vent this equipment to the following equipment if all of the requirements listed below are met:

Device ID: C300 [CONDENSER, VERTICAL]

Requirement number 1: complies with condition C6.14

Requirement number 2: complies with condition E147.2

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D395, D396, D397, D398]

E71.1 The operator shall not vent this equipment to atmosphere.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D367]

E147.1 The operator shall not conduct forced air drying or heating by injection of live-steam in this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472,
5-7-1976]

[Devices subject to this condition : D180, D181, D182, D183, D297]

E147.2 The operator shall not conduct drying operations in this equipment.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472, 5-7-1976]

[Devices subject to this condition : D184, D185, D186, D187, D188, D189, D190, D191, D274, D275, D283, D320, D321, D322, D377, D378, D379, D380, D395, D396, D397, D398]

E147.3 The operator shall not conduct operations which allow steam to be vented to the atmosphere in this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 472, 5-7-1976]

[Devices subject to this condition : D185, D186, D187, D188, D189, D297]

E166.1 The operator shall keep all openings from this equipment closed when in use except during inspection and cleaning.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D118, D119, D120, D121, D122]

E166.2 The operator shall keep all openings from this equipment closed when in use except during loading.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D155, D159]

E166.3 The operator shall keep all openings from this equipment closed when in use except during equipment maintenance to prevent any odor escaping.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 402, 5-7-1976]

[Devices subject to this condition : D201, D377, D378, D379, D380, D395, D396, D397, D398]

E175.1 The operator shall not use this equipment unless all exhaust air passes through the following:

Flexible socks must be maintained on all loading spouts.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D136, D137, D141]

E187.1 The operator shall wash all exposed surfaces free of animal matter at least once each working day.

[RULE 402, 5-7-1976]

[Devices subject to this condition : D1, D2, D3, D4, D5, D6, D7, D8, D9, D10, D11, D12, D13, D14, D15, D16, D17, D18, D19, D20, D21, D22, D23, D24, D25, D26, D27, D28, D29, D30, D31, D217, D218, D219, D220, D221, D222, D223, D224, D225, D226, D227, D228, D229, D230, D231, D232, D233, D234, D235, D236, D237, D238, D239, D240, D241, D242, D243, D244, D245, D246, D247, D248, D249, D250, D251, D252, D253, D254, D255, D256, D257, D258, D259, D260, D261, D262, D263, D264, D265, D284, D290, D292, D293, D294, D295, D296, D298, D356, D357, D358, D368, D369]

E193.2 The operator shall construct, operate, and maintain this equipment as follows:

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

All phase I and phase II vapor recovery equipment at this facility shall be installed, operated and maintained to meet all California Air Resources Board certification requirements.

[RULE 461, 6-3-2005; RULE 461, 3-7-2008; RULE 461, Healy Conditions, 1-9-2004]

[Devices subject to this condition : D194, D195]

E202.1 The operator shall clean and maintain this equipment according to the following specifications:

Filters socks on the grinders must be properly maintained.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D118, D119, D120, D121, D122]

J. Rule 461

J109.1 The operator shall use, except for diesel transfer, the phase I vapor recovery system in full operation whenever this equipment is in use. This system shall be installed, operated and maintained to meet all CARB certification requirements.

[RULE 461, 6-3-2005; RULE 461, 3-7-2008; RULE 461, Healy Conditions, 1-9-2004]

[Devices subject to this condition : D194]

J110.1 The operator shall use, except for diesel transfer, the phase II vapor recovery system in full operation whenever gasoline from this equipment is dispensed to motor vehicles as defined in Rule 461. This system shall be installed, operated and maintained to meet all CARB certification requirements.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 461, 6-3-2005; RULE 461, 3-7-2008; RULE 461, Healy Conditions, 1-9-2004]

[Devices subject to this condition : D195]

J373.3 The operator shall comply with the following gasoline transfer and dispensing requirements:

FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

New equipment installations and subsequent service and repairs for any certified component for which this permit was issued, shall only be performed by a current and certified person who has successfully completed the manufacturer's training course and appropriate International Code Council (ICC) certification. Completion of any AQMD training course does not constitute as a substitute for this requirement. Proof of successful completion of any manufacturer training course shall be with the manufacturer.

Depending on the system configuration, a leak rate test of drop tube/drain valve assembly shall be conducted to quantify the pressure integrity of both the drop tube and drain valve seal or a leak rate test of drop tube overflow prevention device and drain valve shall be conducted to quantify the pressure integrity of the drop tube overflow prevention device and the pressure integrity of the spill container drain valve. Either test shall be conducted as a performance test and as a reverification test.

The above test shall be conducted in accordance with test procedure method TP-201.1C (October 8, 2003) or TP-201.1D (October 8, 2003) respectively. Result shall be submitted to the AQMD, Office of Engineering and Compliance, within seventy-two (72) hours of test.

A leak rate and cracking pressure test of pressure/vacuum relief vent valves shall be conducted within ten (10) days after the start of operation of the OPW phase I EVR equipment and at least once every three (3) years thereafter to determine the pressure and vacuum at which the pressure/vacuum vent valve actuates, and to determine the volumetric leak rate at a given pressure. The test shall be conducted in accordance with the test procedure method TP-201.1E (October 8, 2003).

The result of the above test shall be submitted to the AQMD, Office of Engineering and Compliance, within seventy-two (72) hours of test. This test result shall be kept on site for three (3) years and made available to District representatives upon request.

A static torque test of portable phase I adaptors shall be conducted to quantify the amount of static torque required to start the rotation of the rotatable phase I adaptors. The test shall be conducted in accordance with the test procedure method outlined in



FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

TP-201.1B (October 8, 2003) as a performance test and as a reverification test. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within seventy-two (72) hours of test.

The phase II vapor recovery system shall be installed, operated, and maintained such that the maximum allowable pressure through the riser, and underground piping does not exceed the dynamic back pressure described by the California Air Resources Board (CARB) Executive Order by which the system was certified as Nitrogen flowrates: 60 CFH, and Dynamic backpressure : 0.5 inches of water column.

The above dynamic backpressure tests shall be conducted to determine the phase II system vapor recovery back pressures. The tests shall be conducted in accordance with CARB test procedure TP-201.4, methodology 4 and 6 (July 3, 2002); as a performance test. This test shall be a one-time test and the results kept permanently on site. A copy of the results shall be submitted to the AQMD, Office of Engineering and Compliance, within seventy-two (72) hours of test.

A static pressure leak decay test shall be conducted to demonstrate that the storage tanks, the remote and/or nozzle vapor recovery check valves, associated vapor return piping and fittings are free from vapor leaks. The test shall be conducted in accordance with CARB test procedure method TP-201.3 (March 17, 1999) as performance test and as a reverification test. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within seventy-two (72) hours of test.

A static pressure performance test for the Healy Clean Air Separator using both the vacuum decay procedure and the positive pressure procedure shall be conducted to quantify the vapor tightness of the Healy Clean Air Separator Tank Pressure Management System. These tests shall be conducted in accordance with exhibit 4 of CARB Executive Order VR-201-H as a performance test and as a reverification test. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within seventy-two (72) hou

A vapor to liquid volume ratio test shall be conducted to quantify the vapor to liquid (V/L) volumetric ratio of the Healy Clean Air Separator System. The test shall be

FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

conducted in accordance with exhibit 5 of CARB Executive Order VR-201-H as a performance test and as a reverification test. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within seventy-two (72) hours of test.

A nozzle bag test shall be conducted on the Healy phase II EVR nozzles to verify the integrity of the vapor valve. The test shall be conducted on any newly installed or replaced Healy phase II EVR nozzles and in accordance with exhibit 7 of CARB Executive Order VR-201-H. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within seventy-two (72) hours of test.

The static pressure leak decay test TP-201.3, shall be conducted in accordance with exhibit 8 of CARB of CARB Executive Order VR-201-H. Verification of completing each step as outlined shall be documented by submitting a copy of exhibit 8 to the AQMD, Office of Engineering and Compliance, within seventy-two (72) hours of test.

Unless AQMD Rule 461 requires a more frequent testing or inspection schedule, the owner/operator shall be responsible to perform the scheduled weekly, quarterly, and annual inspections as outlined in the ARB approved installation, operation, and maintenance manual for the Healy phase II EVR systems, as well as all the required vapor recovery system tests as per the current and appropriate ARB Executive Order.

The AQMD shall be notified by e-mail at r461testing@aqmd.gov or by facsimile at telephone number (909) 396-3606 at least seventy-two (72) hours prior to any of the above mentioned testing requirements. Such notification shall include the name of the owner or operator; the name of the contractor; the location of the facility; and the scheduled start and completion dates of the tests to be performed.

The testing for the above mentioned tests shall be conducted in accordance with most recent Rule 461 amendment or CARB Executive Order requirements, whichever is more stringent.

All records and test results that are required to be maintained by Rule 461 shall be kept on site for four years and made available to district representatives upon request.



FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Should the facility dispense more than 600,000 gallons of gasoline in a calendar year; the operator shall file an application for a new permit to construct/operate to install a CARB Certified In-Station Diagnostic (ISD) System. The ISD System shall be fully installed, tested, and operative within 90 (ninety) days from the date the permit was issued.

[RULE 461, 6-3-2005; RULE 461, 3-7-2008; RULE 461, Healy Conditions, 1-9-2004]

[Devices subject to this condition : D194, D195]

K. Record Keeping/Reporting

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records for all coating consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coatings.

For architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coatings.

[RULE 1113, 11-8-1996; RULE 1113, 6-3-2011]

[Devices subject to this condition : E316]

K67.2 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

the name of the person performing the inspection and/or maintenance of the filter media

the date, time and results of the inspection

the date, time and description of any maintenance or repairs resulting from the inspection

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D84]

K67.3 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Dates of operation when yellow grease is fired

Amount of natural gas usage in cubic feet per day

Amount of fuel oil usage in gallons per day

Amount of yellow grease usage in gallons per day

Daily sum of the parameters based on the equation stated in condition no. 303-1

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1304(c)-Offset Exemption, 6-14-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C200, C215, C216]

K67.4 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):



**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

pressure differential across the scrubber

the pH of the scrubbing solution

scrubber solution flowrate

The operating parameters shall be read and recorded at least once every operating day.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C370]

FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION E: ADMINISTRATIVE CONDITIONS

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]
 - a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]
 - b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]
 - c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]
2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]
3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the AQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations or statutes of other governmental agencies. [204]
4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]



FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION E: ADMINISTRATIVE CONDITIONS

5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation. [204]
6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to AQMD personnel upon request and be maintained for at least: [204]
 - a. Three years for a facility not subject to Title V; or
 - b. Five years for a facility subject to Title V.
7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by AQMD rules or permit conditions: [204]
 - a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134, 204]
 - b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]
 - c. For a large NO_x source, compliance with a RECLAIM concentration limit shall be measured over a continuous 60 minutes for that source; [2012]
 - d. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes. [204]

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION E: ADMINISTRATIVE CONDITIONS

- e. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compound which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO₂) and be averaged over 15 consecutive minutes; [407]
 - f. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent carbon dioxide (CO₂) at standard conditions and averaged over 15 consecutive minutes. [409]
 - g. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O₂) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]
8. All equipment operating under the RECLAIM program shall comply concurrently with all provisions of AQMD Rules and Regulation, except those listed in Table 1 of Rule 2001 for NO_x RECLAIM sources and Table 2 of Rule 2001 for SO_x RECLAIM sources. Those provisions listed in Tables 1 or 2 shall not apply to NO_x or SO_x emissions after the date the facility has demonstrated compliance with all monitoring and reporting requirements of Rules 2011 or 2012, as applicable. Provisions of the listed AQMD rules in Tables 1 or 2 which have initial implementation dates in 1994 shall not apply to a RECLAIM NO_x or SO_x source, respectively. [2001]
9. The operator shall, when a source test is required by AQMD, provide a source test protocol to AQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by AQMD. The test protocol shall contain the following information: [204, 304]
- a. Brief description of the equipment tested.



FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION E: ADMINISTRATIVE CONDITIONS

- b. Brief process description, including maximum and normal operating temperatures, pressures, through-put, etc.
 - c. Operating conditions under which the test will be performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts/stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.
 - f. Description of calibration and quality assurance procedures.
 - g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (no conflict of interest).
10. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by AQMD Rules or equipment-specific conditions. The report shall contain the following information: [204]
- a. The results of the source test.
 - b. Brief description of the equipment tested.
 - c. Operating conditions under which the test will be performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts/stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Field and laboratory data forms, strip charts and analyses.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION E: ADMINISTRATIVE CONDITIONS

- f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.
- 11. The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of AQMD Source Test Method 1.1 and 1.2. [217]
- 12. Whenever required to submit a written report, notification or other submittal to the Executive Officer, AQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, AQMD, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182. [204]



FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

The Facility shall comply with all applicable monitoring and source testing requirements in Regulation XX. These requirements may include but are not limited to the following:

I. NO_x Monitoring Conditions

A. The Operator of a NO_x Major Source, as defined in Rule 2012, shall, as applicable:

Not Applicable

B. The Operator of a NO_x large Source, as defined in Rule 2012, shall, as applicable:

1. Install, maintain, and operate a totalizing fuel meter and any device specified by the Executive Officer as necessary to determine monthly fuel usage or other applicable variables specified in Rule 2012, Appendix A, Table 3-A. The sharing of totalizing fuel meter may be allowed by the Executive Officer if the fuel meter serves large sources which have the same emission factor, concentration limit, or emission rate. The sharing of totalizing fuel meters shall not be allowed for large sources which are required to comply with an annual heat input limit. [2012]
2. Comply at all times with the specified NO_x concentration limit in PPM measured over any continuous 60 minutes for that source or establish an equipment-specific emission rate that is reliable, accurate, representative of that sources emissions, and in accordance with the requirements specified in Rule 2012, Appendix A, Chapter 5. [2012]

C. The Operator of a NO_x Process Unit, as defined in Rule 2012, shall, as applicable:

1. Install, maintain, and operate a totalizing fuel meter or any device approved by the Executive Officer to measure quarterly fuel usage or other applicable variables specified in Rule 2012, Table 2012-1, and Rule 2012, Appendix A, Table 4-A. The sharing of totalizing fuel meters may be allowed by the Executive Officer if the fuel meter serves process units which have the same emission factor or emission rate. The sharing of totalizing meter shall not be allowed for process units which are required to comply with an annual heat input limit. [2012]

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

II. NOx Source Testing and Tune-up conditions

1. The operator shall conduct all required NOx source testing in compliance with an AQMD-approved source test protocol. [2012]
2. The operator shall, as applicable, conduct source tests for every large NOx source no later than June 30, 1997 and every 3 years thereafter. The source test shall include the determination of NOx concentration and a relative accuracy audit of the exhaust stack flow determination (e.g. in-stack flow monitor or fuel flow monitor based F-factor calculation). Such source test results shall be submitted per the schedule described by APEP. In lieu of submitting the first source test report, the facility permit holder may submit the results of a source test not more than 3 years old which meets the requirements when conducted. [2012]
3. All NOx large sources and NOx process units shall be tuned-up in accordance with the schedule specified in Rule 2012, Appendix A, Chapter 5, Table 5-B. [2012]



**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR
RECLAIM SOURCES**

The Facility shall comply with all applicable reporting and recordkeeping requirements in Regulation XX. These requirements may include but are not limited to the following:

I. Recordkeeping Requirements for all RECLAIM Sources

1. The operator shall maintain all monitoring data required to be measured or reported pursuant to Rule 2011 and Rule 2012, whichever is applicable. All records shall be made available to AQMD staff upon request and be maintained for at least:
 - a. Three years after each APEP report is submitted to AQMD for a facility not subject to Title V, unless a different time period is required in Rule 2011 or Rule 2012 [2011 & 2012]; or
 - b. Five years after each APEP report is submitted to AQMD for a facility subject to Title V. [3004(a)(4)(E)]
 - c. Notwithstanding the above, all data gathered or computed for intervals of less than 15 minutes shall only be maintained a minimum of 48 hours. [2011 & 2012]
2. The operator shall store on site and make available to the Executive Officer upon request: records used to determine emissions, maintenance records, sources test reports, relative accuracy test audit reports, relative accuracy audit reports and fuel meter calibration records. [2011 & 2012]

II. Reporting Requirements for all RECLAIM Sources

1. The operator shall submit a quarterly certification of emissions including the facility's total NOx or SOx emissions, whichever is applicable, for the quarter within 30 days after the end of the first three quarters and 60 days after the end of the fourth quarter of a compliance year. [2011 & 2012]

NOx Reporting Requirements

- A. The Operator of a NOx Major Source, as defined in Rule 2012, shall, as applicable:

Not Applicable

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR
RECLAIM SOURCES**

B. The Operator of a NOx Large Source, as defined in Rule 2012, shall:

1. Install, maintain and operate a modem or any reporting device approved by the Executive Officer to report, to the AQMD, the total monthly NOx mass emissions from each large NOx source. The Operator shall comply with this requirement within 12 months of the date of entry to the RECLAIM Program. Such data shall be reported within 15 days after the end of each calendar month. [2012]

C. The Operator of a NOx Process Unit, as defined in Rule 2012, shall:

1. Electronically report the calculated quarterly NOx emissions for each NOx process unit. The Operator shall comply with this requirement within 12 months of the date of entry to the RECLAIM Program. [2012]



**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

NONE

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION I: PLANS AND SCHEDULES

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules specified below. The operator shall comply with all conditions specified in the approval of these plans, with the following exceptions:

- a. The operator does not have to comply with NO_x or SO_x emission limits from rules identified in Table 1 or Table 2 of Rule 2001(j) which become effective after December 31, 1993.
- b. The operator does not have to comply with NO_x or SO_x emission limits from rules identified in Table 1 or Table 2 of Rule 2001(j) after the facility has received final certification of all monitoring and reporting requirements specified in Section F and Section G.

Documents pertaining to the plan applications listed below are available for public review at AQMD Headquarters. Any changes to plan applications will require permit modification in accordance with Title V permit revision procedures.

List of approved plans:

Application	Rule
276409	1146.1

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.



**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION J: AIR TOXICS

NOT APPLICABLE

FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION K: TITLE V Administration

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
- (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.
 - (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
 - (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
- (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]

10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]

12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]

13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]



FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION K: TITLE V Administration

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]
15. Nothing in this permit or in any permit shield can alter or affect:
- (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]
16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**SECTION K: TITLE V Administration
EMERGENCY PROVISIONS**

17. An emergency¹ constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:

(A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:

- (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
- (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
- (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
- (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and

(B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]

18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

¹ "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.



FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION K: TITLE V Administration RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
- (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
 - (B) The date(s) analyses were performed;
 - (C) The company or entity that performed the analyses;
 - (D) The analytical techniques or methods used;
 - (E) The results of such analyses; and
 - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:
- (A) Breakdowns shall be reported as required by Rule 430 – Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.

FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION K: TITLE V Administration

- (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.
- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
- (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;



**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION K: TITLE V Administration

- (B) The compliance status during the reporting period;
- (C) Whether compliance was continuous or intermittent;
- (D) The method(s) used to determine compliance over the reporting period and currently, and
- (E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn:
Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 1113	11-8-1996	Federally enforceable
RULE 1113	6-3-2011	Non federally enforceable
RULE 1171	11-7-2003	Federally enforceable
RULE 1171	5-1-2009	Non federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303	5-10-1996	Federally enforceable
RULE 1303(a)(1)-BACT	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	12-6-2002	Non federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1304(c)-Offset Exemption	6-14-1996	Federally enforceable
RULE 1401	3-7-2008	Non federally enforceable
RULE 2001	5-6-2005	Federally enforceable
RULE 2004	5-11-2001	Federally enforceable
RULE 2005	5-6-2005	Federally enforceable
RULE 2012	5-6-2005	Federally enforceable
RULE 2012(e)(1)(A)(ii) -NOx Process Unit	4-11-1997	Non federally enforceable
RULE 204	10-8-1993	Federally enforceable
RULE 217	1-5-1990	Federally enforceable
RULE 219	7-14-2006	Non federally enforceable



FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 219	9-4-1981	Federally enforceable
RULE 3002	11-14-1997	Federally enforceable
RULE 3003	11-14-1997	Federally enforceable
RULE 3003	3-16-2001	Non federally enforceable
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3005	3-16-2001	Non federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	6-9-2006	Non federally enforceable
RULE 401	11-9-2001	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 403	4-2-2004	Federally enforceable
RULE 403	6-3-2005	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 405	2-7-1986	Federally enforceable
RULE 407	4-2-1982	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 409	8-7-1981	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 431.2	5-4-1990	Federally enforceable
RULE 431.2	9-15-2000	Non federally enforceable
RULE 461	3-7-2008	Non federally enforceable
RULE 461	6-3-2005	Federally enforceable
RULE 461, Balance Conditions	1-9-2004	Non federally enforceable
RULE 461, Healy Conditions	1-9-2004	Non federally enforceable
RULE 461, Universal Conditions	1-9-2004	Non federally enforceable
RULE 472	5-7-1976	Federally enforceable
RULE 480	10-7-1977	Federally enforceable
RULE 701	6-13-1997	Federally enforceable

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN
PERMIT PURSUANT TO RULE 219**

1. I.C. ENGINES, GASOLINE
2. I.C. ENGINES, DIESEL
3. SPACE HEATERS, NATURAL GAS
4. WATER HEATERS, NATURAL GAS
5. PRE-WELD WARMER, NATURAL GAS



**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 11-08-1996]**

- (1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.
- (2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

TABLE OF STANDARDS

VOC LIMITS

**Grams of VOC Per Liter of Coating,
Less Water And Less Exempt Compounds**

COATING	Limit*	Effective Date of Adoption	Effective 1/1/1998	Effective 1/1/1999	Effective 7/1/2001	Effective 1/1/2005	Effective 7/1/2008
Bond Breakers	350						
Clear Wood Finishes							
Varnish	350						
Sanding Sealers	350						
Lacquer	680		550			275	
Concrete-Curing Compounds	350						
Dry-Fog Coatings	400						
Fire-proofing Exterior Coatings	350	450		350			
Fire-Retardant Coatings							
Clear	650						
Pigmented	350						
Flats	250				100		
Graphic Arts (Sign) Coatings	500						50

**FACILITY PERMIT TO OPERATE
 BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1113 11-08-1996]**

Industrial Maintenance						
Primers and Topcoats						
Alkyds	420					
Catalyzed Epoxy	420					
Bituminous Coatings	420					
Materials						
Inorganic Polymers	420					
Vinyl Chloride Polymers	420					
Chlorinated Rubber	420					
Acrylic Polymers	420					
Urethane Polymers	420					
Silicones	420					
Unique Vehicles	420					
Japans/Faux Finishing	350	700		350		
Coatings						
Magnesite Cement Coatings	600			450		
Mastic Coatings	300					
Metallic Pigmented Coatings	500					
Multi-Color Coatings	420		250			
Pigmented Lacquer	680		550		275	
Pre-Treatment Wash Primers	780					
Primers, Sealers, and	350					
Undercoaters						
Quick-Dry Enamels	400					
Roof Coatings	300					
Shellac						
Clear	730					
Pigmented	550					
Stains	350					
Swimming Pool Coatings						
Repair	650					
Other	340					
Traffic Coatings	250		150			
Waterproofing Sealers	400					
Wood Preservatives						
Below-Ground	350					
Other	350					

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

TABLE OF STANDARDS (cont.)

VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120



**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 06-03-2011]**

- (1) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6) of Rule 1113, no person shall supply, sell, offer for sale, market, manufacture, blend, repackage, apply, store at a worksite, or solicit the application of any architectural coating within the District:
 - (A) That is listed in the Table of Standards 1 and contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified; or
 - (B) That is not listed in the Table of Standards 1, and contains VOC (excluding any colorant added to tint bases) in excess of 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, until January 1, 2014, at which time the limit drops to 50 grams of VOC per liter of coating, less water, less exempt compounds (0.42 pounds per gallon).
- (2) No person within the District shall add colorant at the point of sale that is listed in the Table of Standards 2 and contains VOC in excess of the corresponding VOC limit specified in the Table of Standards 2, after the effective date specified.

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 06-03-2011]**

**TABLE OF STANDARDS 1
VOC LIMITS**

**Grams of VOC Per Liter of Coating,
Less Water and Less Exempt Compounds**

COATING CATEGORY	Ceiling Limit ¹	Current Limit ²	Effective Date		
			7/1/08	1/1/12	1/1/14
Bond Breakers		350			
Clear Wood Finishes		275			
Varnish	350	275			
Sanding Sealers	350	275			
Lacquer		275			
Concrete-Curing Compounds		100			
Concrete-Curing Compounds For Roadways and Bridges ³		350			
Concrete Surface Retarder		250			50
Driveway Sealer		100		50	
Dry-Fog Coatings		150			50
Faux Finishing Coatings					
Clear Topcoat		350		200	
Decorative Coatings		350			100
Glazes		350			
Japan		350			
Trowel Applied Coatings		350		150	50
Fire-Proofing Coatings		350			150
Flats	250	50	50		
Floor Coatings	100	50			
Form Release Compound		250			100
Graphic Arts (Sign) Coatings		500			150
Industrial Maintenance (IM) Coatings	420	100			
High Temperature IM Coatings		420			
Non-Sacrificial Anti-Graffiti Coatings		100			
Zinc-Rich IM Primers	340	100			
Magnesite Cement Coatings		450			
Mastic Coatings		300			100
Metallic Pigmented Coatings	500	500			150
Multi-Color Coatings		250			
Nonflat Coatings	150	50			
Pre-Treatment Wash Primers		420			
Primers, Sealers, and Undercoaters	200	100			
Reactive Penetrating Sealers		350			
Recycled Coatings		250			
Roof Coatings	250	50			
Roof Coatings, Aluminum		100			



**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 06-03-2011]**

Roof Primers, Bituminous	350	350		
Rust Preventative Coatings	400	100		
Stone Consolidant		450		
Sacrificial Anti-Graffiti Coatings		100	50	
Shellac				
Clear		730		
Pigmented		550		
Specialty Primers	350	100		
Stains		100		

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 06-03-2011]**

COATING CATEGORY	Ceiling Limit ¹	Current Limit ²	Effective Date		
			7/1/08	1/1/12	1/1/14
Stains, Interior	250	250			
Swimming Pool Coatings					
Repair		340			
Other		340			
Traffic Coatings		100			
Waterproofing Sealers	250	100			
Waterproofing Concrete/Masonry Sealers	400	100			
Wood Preservatives		350			

1. The specified ceiling limits are applicable to products sold under the Averaging Compliance Option.
2. The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.
3. Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

**TABLE OF STANDARDS 1 (cont.)
VOC LIMITS**

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

**TABLE OF STANDARDS 2
VOC LIMITS FOR COLORANTS**

**Grams of VOC Per Liter of Colorant
Less Water and Less Exempt Compounds**

COLORANT	Limit ⁴
Architectural Coatings, excluding IM Coatings	50
Solvent-Based IM	600
Waterborne IM	50

4. Effective January 1, 2014.



FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 11-07-2003]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	500 (4.2)
(iii) Medical Devices & Pharmaceuticals	800 (6.7)
(B) Repair and Maintenance Cleaning	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]**

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals	
(A) Tools, Equipment, & Machinery	800 (6.7)
(B) General Work Surfaces	600 (5.0)
(C) Cleaning of Coatings or Adhesives Application Equipment	550 (4.6)
(D) Cleaning of Ink Application Equipment	
(i) General	25 (0.21)
(ii) Flexographic Printing	25 (0.21)
(iii) Gravure Printing	
(A) Publication	750 (6.3)
(B) Packaging	25 (0.21)
(iv) Lithographic or Letter Press Printing	



**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]**

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(A) Roller Wash – Step 1	600 (5.0)
(B) Roller Wash-Step 2, Blanket Wash, & On-Press Components	800 (6.7)
(C) Removable Press Components	25 (0.21)
(v) Screen Printing	750 (6.3)
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	800 (6.7)
(vii) Specialty Flexographic Printing	600 (5.0)
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 05-01-2009]**

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals	800 (6.7)	
(B) Repair and Maintenance Cleaning		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	



FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals		
(A) Tools, Equipment, & Machinery	800 (6.7)	
(B) General Work Surfaces	600 (5.0)	
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)	
(D) Cleaning of Ink Application Equipment		
(i) General	25 (0.21)	
(ii) Flexographic Printing	25 (0.21)	
(iii) Gravure Printing		
(A) Publication	100 (0.83)	
(B) Packaging	25 (0.21)	
(iv) Lithographic (Offset) or Letter Press Printing		
(A) Roller Wash, Blanket Wash, & On-Press Components	100 (0.83)	

**FACILITY PERMIT TO OPERATE
 BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 05-01-2009]**

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(B) Removable Press Components	25 (0.21)	
(v) Screen Printing	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)	
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)	

* The specified limits remain in effect unless revised limits are listed in subsequent columns.



**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 404 02-07-1986]**

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 404 02-07-1986]**

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148



**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 404 02-07-1986]**

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 405 02-07-1986]**

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process)		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process)	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
100 or less	220 or less	0.450	0.99	9000	19840	5.308	11.7
150	331	0.585	1.29	10000	22050	5.440	12.0
200	441	0.703	1.55	12500	27560	5.732	12.6
250	551	0.804	1.77	15000	33070	5.982	13.2
300	661	0.897	1.98	17500	38580	6.202	13.7
350	772	0.983	2.17	20000	44090	6.399	14.1
400	882	1.063	2.34	25000	55120	6.743	14.9
450	992	1.138	2.51	30000	66140	7.037	15.5
500	1102	1.209	2.67	35000	77160	7.296	16.1
600	1323	1.340	2.95	40000	88180	7.527	16.6



**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 405 02-07-1986]**

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
700	1543	1.461	3.22	45000	99210	7.738	17.1
800	1764	1.573	3.47	50000	110200	7.931	17.5
900	1984	1.678	3.70	60000	132300	8.277	18.2
1000	2205	1.777	3.92	70000	154300	8.582	18.9
1250	2756	2.003	4.42	80000	176400	8.854	19.5
1500	3307	2.206	4.86	90000	198400	9.102	20.1
1750	3858	2.392	5.27	100000	220500	9.329	20.6
2000	4409	2.563	5.65	125000	275600	9.830	21.7
2250	4960	2.723	6.00	150000	330700	10.26	22.6
2500	5512	2.874	6.34	175000	385800	10.64	23.5
2750	6063	3.016	6.65	200000	440900	10.97	24.2
3000	6614	3.151	6.95	225000	496000	11.28	24.9
3250	7165	3.280	7.23	250000	551200	11.56	25.5
3600	7716	3.404	7.50	275000	606300	11.82	26.1
4000	8818	3.637	8.02	300000	661400	12.07	26.6
4500	9921	3.855	8.50	325000	716500	12.30	27.1
5000	11020	4.059	8.95	350000	771600	12.51	27.6
6000	13230	4.434	9.78	400000	881800	12.91	28.5
7000	15430	4.775	10.5	450000	992100	13.27	29.3
8000	17640	5.089	11.2	500000 or more	1102000 or more	13.60	30.0

**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 461, Healy Conditions 01-09-2004]**

GASOLINE TRANSFER AND DISPENSING, HEALY CONDITIONS

1. Equipment subject to Executive Orders G-70-165, G-70-186, and G-70-187 shall comply with the following:

A vapor return line vacuum integrity test shall be conducted as outlined in Exhibit 4 of CARB Executive Order G-70-165, G-70-186, or G-70-187, as applicable. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within seventy-two (72) hours of test.

The AQMD shall be notified by e-mail at r461testing@aqmd.gov or by facsimile at telephone number (909) 396-3606 at least seventy-two (72) hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractor; the location of the facility; and the scheduled start and completion dates of the vapor return line integrity test.

2. Equipment subject to Executive Orders G-70-186 and G-70-187 shall comply with the following:

A fillneck vapor pressure regulation fueling test shall be conducted as outlined in Exhibit 4 of CARB Executive Order G-70-186 or G-70-187, as applicable. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within seventy-two (72) hours of test.

The AQMD shall be notified by e-mail at r461testing@aqmd.gov or by facsimile at telephone number (909) 396-3606 at least seventy-two (72) hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractor; the location of the facility; and the scheduled start and completion dates of the fillneck vapor pressure regulation fueling test.

3. The Phase II vapor recovery system shall be installed, operated, and maintained such that the maximum allowable pressure through the system including nozzle, vapor hose, swivels, and underground piping does not exceed the dynamic back pressures described by the California Air Resources Board Executive Order by which the system was certified:

Nitrogen Flowrates (CFH)	Dynamic Back Pressure (Inches of Water)
60	0.35
80	0.62



**FACILITY PERMIT TO OPERATE
BAKER COMMODITIES INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 461, Healy Conditions 01-09-2004]**

Dynamic back pressure tests shall be conducted to determine the phase ii system vapor recovery back pressures. The tests shall be conducted in accordance with CARB Test Procedure TP-201.4, Methodology 5. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within seventy-two (72) hours of tests.

The AQMD shall be notified by e-mail at r461testing@aqmd.gov or by facsimile at telephone number (909) 396-3606 at least seventy-two (72) hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractor; the location of the facility; and the scheduled start and completion dates of the dynamic back pressure tests.

FACILITY PERMIT TO OPERATE BAKER COMMODITIES INC

APPENDIX B: RULE EMISSION LIMITS [RULE 461, Universal Conditions 01-09-2004]

GASOLINE TRANSFER AND DISPENSING, UNIVERSAL CONDITIONS

1. Operation of this equipment shall be in compliance with all data and specifications submitted with the application under which this permit was issued, unless otherwise noted below.
2. This equipment shall be properly maintained and kept in good operating condition at all times.
3. Except for diesel transfers, Phase I vapor recovery systems shall be in full operation whenever fuel is being transferred into storage tanks.
4. Except for diesel transfers, Phase II vapor recovery systems shall be in full operation whenever fuel is being transferred into motor vehicles, as defined in Rule 461.
5. All Phase I and Phase II vapor recovery equipment at this facility shall be installed, operated and maintained to meet all California Air Resources Board certification requirements.
6. Except for HIRT VCS 400-7 equipment, a static pressure leak decay test shall be conducted to demonstrate that the storage tanks, the remote and/or nozzle vapor recovery check valves, associated vapor return piping and fittings are free from vapor leaks. The test shall be conducted in accordance with CARB Test Procedure Method TP-201.3. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within seventy-two (72) hours of test.

The AQMD shall be notified by e-mail at r461testing@aqmd.gov or by facsimile at telephone number (909) 396-3606 at least seventy-two (72) hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractor; the location of the facility; and the scheduled start and completion dates of the static pressure leak decay test.

7. The testing for the above mentioned tests shall be conducted in accordance with the most recent Rule 461 amendment or CARB Executive Order requirements, whichever is more stringent.
8. All records and test results that are required to be maintained by Rule 461 shall be kept on site and made available to district representatives upon request.