San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

JUL 30 2013

Mr. Phil Acosta
Vintage Production California Inc
9600 Ming Avenue, Suite 300
Bakersfield, CA 93311

Re: Notice of Minor Title V Permit Modification
District Facility # S-1738
Project # 1122464

Dear Mr. Acosta:

Enclosed is the District's analysis of your application for minor Title V permit modification for the facility identified above. You proposed a Title V minor permit modification to incorporate recently issued Authorities to Construct (ATCs) S-1738-2-7, '-22-5, '-38-5, '-49-6, '-240-6, '-288-6, '-354-2, '-354-3, '-417-2, and '-443-5, '-431-0 and '-451-0 through '-454-0 into the Title V operating permit. The ATC projects authorized installation of up to four (4) 500 bbl crude oil storage tanks connected to at any of nine (9) possible existing vapor control systems (VCSs) (project 1120689) and installation of an organic liquid loading rack connected to existing tank vapor control system S-1738-354 (project 1094479).

Enclosed is the engineering evaluation with the following attachments: proposed modified Title V permit, recently issued Authorities to Construct (ATCs) S-1738-2-7, '-22-5, '-38-5, '-49-6, '-240-6, '-288-6, '-354-2, '-354-3, '-417-2, and '-443-5, '-431-0 and '-451-0 through '-454-0, application, and previous Title V permit. This project will be subject to a 45-day EPA commenting period prior to the District taking final action.

If you have any questions, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

www.valleyair.org www.healthyairliving.com

Printed on recycled paper.

JUL 30 2013

Thank you for your cooperation in this matter.

Sincerely,

David Warner
Director of Permit Services

Enclosures

cc: Gerardo C. Rios, EPA (w/enclosure) via email

TITLE V APPLICATION REVIEW

Minor Modification
Project #: S-1122464

Engineer: Richard Edgehill
Date: July 25, 2013

Reviewed by AP SWR AQE
JUL 25 2013

Facility Number: S-1738
Facility Name: Vintage Production California Inc
Mailing Address: 9600 Ming Avenue, Suite 300
Bakersfield, CA 93311

Contact Name: Joey Barulich and Phil Acosta
Phone: (661) 869-8075
Title: HES Consultant
Lead Engineer: Alan Phillips

Responsible Official: Stephen Bartz, Operations Team Lead

I. PROPOSAL

Vintage Production California (VPC) is proposing a Title V minor permit modification to incorporate the recently issued Authorities to Construct (ATCs) S-1738-354-2 and '-431-0 (project 1094479) and ATCs S-1738-2-7, '-22-5, '-38-5, '-49-6, '-240-6, '-288-6, '-354-3, '-417-2, and '-443-5, and '-451-0 through '-454-0 (project 1120689) into the Title V operating permit. Project 1120689 authorizes installation of up to four (4) 500 bbl crude oil storage tanks connected to at any of nine (9) possible existing vapor control systems (VCSs). Project 1094479 authorizes installation of an organic liquid loading rack connected to existing tank vapor control system S-1738-354.

The purpose of this evaluation is to identify all applicable requirements, determine if the facility will comply with the applicable requirements and to provide the legal and factual basis for the proposed revisions.

II. FACILITY LOCATION

The authorized equipment is located at the following locations within VPCs Light Oil Western Stationary Source.

Facility	PTO	Location
Rio Viejo [86x-33]	S-1738-2-6	Section 33, T12N, R21W
Pleito	S-1738-22-4	Section 25, T11N, R21W
G-North [Wheeler Ridge]	S-1738-38-4	Section 24, T11N, R20W
G-South [Wheeler Ridge]	S-1738-49-5	SE Section 22, T11N, R20W
Paloma	S-1738-240-5	SW Section 03, T32S, R28W
M&M	S-1738-288-5	NW Section 30, T30S, R22W
Yowlumne	S-1738-354-1, '-431	Section 04, T11N, R22W
McDonald Anticline [Layman]	S-1738-417-1	SE Section 18, T28S, R20W
Monument Junction [Hopkins]	S-1738-443-4	Section 10, T29S, R21W

III. EQUIPMENT DESCRIPTION

Existing Permit Units

S-1738-2-8 42,000 GALLON FIXED ROOF PETROLEUM TANK #TOC WITH VAPOR RECOVERY SYSTEM SHARED WITH PERMITS S-1738-30, '-31, '-53, AND '-226 INCLUDING 7.5 HP VAPOR COMPRESSOR AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (RIO VIEJO FIELD 86X-33)

S-1738-22-6: 84,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #5029 WITH VAPOR RECOVERY SYSTEM SERVING PERMITS S-1738-22 THROUGH '-26, AND '-267 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (PLIETO HILLS RANCH)

S-1738-38-6: 42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK WITH VAPOR RECOVERY SYSTEM INCLUDING 7.5 HP COMPRESSOR SERVING PERMIT UNITS S-1738-50 THROUGH '-52 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (G NORTH – WHEELER RIDGE)

S-1738-49-7: 42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK WITH VAPOR RECOVERY SYSTEM INCLUDING ONE 30 HP COMPRESSOR SERVING PERMIT UNITS S-1738-50 THROUGH '-52 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (G SOUTH)

S-1738-240-8: 16,926 GALLON FIXED ROOF PETROLEUM STORAGE TANK #5335 WITH VAPOR RECOVERY SYSTEM INCLUDING 12 HP COMPRESSOR SERVING PERMITS S-1738-241 THROUGH '-246 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (PALOMA PROJECT)

S-1738-288-7: 84,000 GALLON FIXED ROOF SHIPPING TANK WITH CONTROL SYSTEM SHARED WITH S-1738-289, '-290, '-340, AND '-341 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (M&M LEASE)

S-1738-354-4: 126,000 GALLON (3,000 BBL) FIXED WASH TANK #5335 WITH VAPOR RECOVERY INCLUDING VAPOR COMPRESSORS AND ONE EMERGENCY FLARE. V/R SYSTEM SHARED WITH TANKS S-1738-354 THROUGH '-358 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 AND LOADING RACK S-1738-431 LOCATED IN THE YOWLUMNE TANK BATTERY

S-1738-431-1: CLASS 1 ORGANIC LIQUID (CRUDE OIL) LOADING RACK WITH ONE BOTTOM LOADING DRY-BREAK COUPLER FILL HOSE AND VAPOR COLLECTION HOSE SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1738-354

S-1738-417-3: 42,000 GALLON PETROLEUM STORAGE TANK (#5) EQUIPPED WITH VAREC VAPOR CONTROL SYSTEM INCLUDING VAPOR COMPRESSOR SHARED WITH S-1738-418, '-419, '-420 AND '-521 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (LAYMAN)

S-1738-443-6: 2,000 BBL (29.7' DIA X 16' HIGH) FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM SHARED WITH S-1738-444, '-445, '-446 AND '-447 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (HOPKINS LEASE)

<u>New Permit Units</u>

S-1738-431-1: CLASS 1 ORGANIC LIQUID (CRUDE OIL) LOADING RACK WITH ONE BOTTOM LOADING DRY-BREAK COUPLER FILL HOSE AND VAPOR COLLECTION HOSE SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1738-354

S-1738-451-1: 500 BBL CAPACITY CRUDE OIL PRODUCTION TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON

PERMIT S-1738-2, '-22, '-38, '-49, '-240, '-288, '-354, '-417, OR '-443

S-1738-452-1: 500 BBL CAPACITY CRUDE OIL PRODUCTION TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1738-2, '-22, '-38, '-49, '-240, '-288, '-354, '-417, OR '-443

S-1738-453-1: 500 BBL CAPACITY CRUDE OIL PRODUCTION TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1738-2, '-22, '-38, '-49, '-240, '-288, '-354, '-417, OR '-443

S-1738-454-1: 500 BBL CAPACITY CRUDE OIL PRODUCTION TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1738-2, '-22, '-38, '-49, '-240, '-288, '-354, '-417, OR '-443

IV. SCOPE OF EPA AND PUBLIC REVIEW

This change to a Title V permit is considered to be a minor modification and, as such, requires no public review.

V. APPLICABLE REQUIREMENTS

District Rule 2520, Federally Mandated Operating Permits (Adopted June 21, 2001)

VI. DESCRIPTION OF PROPOSED MODIFICATIONS

A condition match between draft PTO and current PTO is provided below.

Draft PTOs S-1738-2-8, '-22-6, '-38-6, '-49-7, '-240-8, '-288-7, '-354-4, '-417-3, and '-443-6 include all conditions listed on the current Title V PTOs

S-1738-431-0 and '-451-0 through '-454-0

As the permit units, are new there are no proposed modifications to ATC conditions except for deletion of the requirement to submit a Title V Minor Modification application which has been satisfied with this project.

VII. COMPLIANCE

In accordance with Rule 2520, 3.20, these modifications:

1. Do not violate requirements of any applicable federally enforceable local or federal requirement;

2. Do not relax monitoring, reporting, or recordkeeping requirements in the permit and are not significant changes in existing monitoring permit terms or conditions;
3. Do not require or change a case-by-case determination of an emission limitation or other standard, or a source-specific determination for temporary sources of ambient impacts, or a visibility or increment analysis;
4. Do not seek to establish or change a permit term or condition for which there is no corresponding underlying applicable requirement and that the source has assumed to avoid an applicable requirement to which the source would otherwise be subject. Such terms and conditions include;
    a. A federally enforceable emission cap assumed to avoid classification as a modification under any provisions of Title I of the Federal Clean Air Act; and
    b. An alternative emissions limit approved pursuant to regulations promulgated under section 112(i)(5) of the Federal Clean Air Act; and
5. Are not Title I modifications as defined in District Rule 2520 or modifications as defined in section 111 or 112 of the Federal Clean Air Act; and
6. Do not seek to consolidate overlapping applicable requirements.

In accordance with Rule 2520, the application meets the procedural requirements of section 11.4 by including;

1. A description of the change, the emissions resulting from the change, and any new applicable requirements that will apply if the change occurs;
2. The source's suggested draft permit; and
3. Certification by a responsible official that the proposed modification meets the criteria for use of minor permit modification procedures and a request that such procedures be used.

VIII. ATTACHMENTS

A. Proposed Title V PTOs S-1246-179-15 and '-370-1
B. Authorities to Construct S-1246-179-14 and '-370-0
C. Permit Application
D. Previous Title V (draft) PTO S-1246-179-10

ATTACHMENT A
Proposed Title V PTOs

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-2-8 **EXPIRATION DATE:** 02/28/2014

SECTION: 33 **TOWNSHIP:** 12N **RANGE:** 21W

EQUIPMENT DESCRIPTION:
42,000 GALLON FIXED ROOF PETROLEUM TANK #TOC WITH VAPOR RECOVERY SYSTEM SHARED WITH PERMITS S-1738-30, '-31, '-53, AND '-226 INCLUDING 7.5 HP VAPOR COMPRESSOR AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (RIO VIEJO FIELD 86X-33)

DRAFT

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
2. All piping valves and fittings shall be constructed and maintained in a leak-free condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. {2606} The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. {2591} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. {2608} This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
9. Vapors shall vent only through gas line compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Storage tank p/v caps shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR Rule] Federally Enforceable Through Title V Permit
11. Storage tank p/v caps shall be leak-free (except for in breathing) during normal operation. [District NSR Rule] Federally Enforceable Through Title V Permit
12. Liquids from knockout vessel shall be disposed of in a manner preventing emissions to the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Vapor compressor shall activate whenever tank internal pressure exceeds 1 oz./sq. in. [District NSR Rule] Federally Enforceable Through Title V Permit
14. VOC emission rate shall not exceed 0.17 lb/hr for this permit unit and permit units S-1738-30, '-31, '-53 and '-226 combined. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
16. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
17. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
18. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
19. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
20. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
21. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
22. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

24. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-22-6 **EXPIRATION DATE:** 02/28/2014

SECTION: 25 **TOWNSHIP:** 11N **RANGE:** 21W

EQUIPMENT DESCRIPTION:
84,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #5029 WITH VAPOR RECOVERY SYSTEM SERVING PERMITS S-1738-22 THROUGH '-26, AND '-267 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (PLIETO HILLS RANCH)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
2. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. {2606} The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. {2591} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. {2608} This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
9. Vapors shall vent only through gas line compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

10. Storage tank p/v caps shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

11. Storage tank p/v caps shall be leak-free (except for inbreathing) during normal operation. [District NSR Rule] Federally Enforceable Through Title V Permit

12. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

13. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

14. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

15. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

16. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

17. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

18. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

19. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-38-6 **EXPIRATION DATE:** 02/28/2014

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 20W

EQUIPMENT DESCRIPTION:
42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK WITH VAPOR RECOVERY SYSTEM INCLUDING 7.5 HP COMPRESSOR SERVING PERMIT UNITS S-1738-50 THROUGH '-52 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (G NORTH - WHEELER RIDGE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
2. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. {2606} The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. {2591} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. {2608} This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
9. Vapors shall vent only through gas line compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

10. Storage tank p/v caps shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR Rule] Federally Enforceable Through Title V Permit
11. Storage tank p/v caps shall be leak-free (except for inbreathing) during normal operation. [District NSR Rule] Federally Enforceable Through Title V Permit
12. Liquids from knockout vessel shall be disposed of in a manner preventing emissions to the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
14. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
15. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
16. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
17. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
18. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
19. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
20. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit
22. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
23. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-49-7 **EXPIRATION DATE:** 02/28/2014

SECTION: SE22 **TOWNSHIP:** 11N **RANGE:** 20W

EQUIPMENT DESCRIPTION:
42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK WITH VAPOR RECOVERY SYSTEM INCLUDING ONE 30 HP COMPRESSOR SERVING PERMIT UNITS S-1738-50 THROUGH '-52 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (G SOUTH)

PERMIT UNIT REQUIREMENTS

1. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
4. {2606} The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. {2591} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. {2608} This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Vapor control system shall operate between 0.5 in. w.c. and 1.5 in. w.c. [District NSR Rule] Federally Enforceable Through Title V Permit
10. True vapor pressure of stored liquid shall not exceed 14.0 psia. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

23. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
24. Operator shall maintain records of daily tank throughput. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-240-8 **EXPIRATION DATE:** 02/28/2014

SECTION: SW03 **TOWNSHIP:** 32S **RANGE:** 26E

EQUIPMENT DESCRIPTION:
16,926 GALLON FIXED ROOF PETROLEUM STORAGE TANK #5335 WITH VAPOR RECOVERY SYSTEM INCLUDING 12 HP COMPRESSOR SERVING PERMITS S-1738-241 THROUGH '-246 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (PALOMA PROJECT)

PERMIT UNIT REQUIREMENTS

1. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
4. {2606} The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. {2591} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. {2608} This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Tank shall not be used to store or process liquids if the vapor control system is inoperable. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Vapor recovery system shall vent to gas plant (permit S-39-1) only. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

11. Average tank throughput shall not exceed 25,200 gallons/day (calculated on a calendar quarter basis). [District NSR Rule] Federally Enforceable Through Title V Permit

12. True vapor pressure of liquid stored shall not exceed 9.8 psia. [District NSR Rule] Federally Enforceable Through Title V Permit

13. VOC emission rate shall not exceed 0.2 lb/hr and 0.59 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit

14. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

15. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

16. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

17. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

18. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

19. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

20. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit
23. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
24. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
25. Operator shall maintain records of average daily tank throughput. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-288-7 **EXPIRATION DATE:** 02/28/2014

SECTION: NW30 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
84,000 GALLON FIXED ROOF SHIPPING TANK WITH CONTROL SYSTEM SHARED WITH S-1738-289, '-290, '-340, AND '-341 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (M&M LEASE)

DRAFT

PERMIT UNIT REQUIREMENTS

1. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
4. {2606} The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. {2591} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. {2608} This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Vapor recovery system shall include 6" dia. piping connecting tank vapor spaces to 8" dia. gas boot, 2" dia. piping (from 6" dia. piping) serving vapor compressor switches & dry gas regulator, and connecting 3" dia. compressor intake piping. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Vapor recovery system shall include 1" dia. dry gas piping regulated by dry gas regulator & feeding to 8" dia. gas boot, one Varec dry gas regulator, and one back pressure check valve on 3" dia. compressor intake piping. [District NSR Rule] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Vapor recovery system shall include two dryer explosion proof pressure switches, one activating & one de-activating vapor compressor, and one 20 hp Santa Fe Systems Co. vapor compressor. [District NSR Rule] Federally Enforceable Through Title V Permit
12. Prior to breaking the vapor-tight seal on any tank, the dry gas supply line to the system shall be closed. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Liquid condensates from gas boot shall be handled in a manner to prevent emissions to atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
14. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
15. VOC content of total organic hydrocarbons in gas shall not exceed 29% by weight. [District NSR Rule] Federally Enforceable Through Title V Permit
16. Permittee shall perform and record annual gas analysis for VOC content and make such records available for District inspection upon request. [District NSR Rule] Federally Enforceable Through Title V Permit
17. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
18. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
19. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
20. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
21. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
22. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
23. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

26. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. VOC shall be tested using EPA Method 25 or EPA Method 18 referenced as methane. [District Rules 1081 and District NSR Rule] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-354-4 **EXPIRATION DATE:** 02/28/2014

SECTION: 04 **TOWNSHIP:** 11N **RANGE:** 22W

EQUIPMENT DESCRIPTION:
126,000 GALLON (3,000 BBL) FIXED WASH TANK #5335 WITH VAPOR RECOVERY INCLUDING VAPOR COMPRESSORS AND ONE EMERGENCY FLARE. V/R SYSTEM SHARED WITH TANKS S-1738-354 THROUGH '-358 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 AND LOADING RACK S-1738-431 LOCATED IN THE YOWLUMNE TANK BATTERY

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Vapors shall vent only through gas line compressor. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All piping, valves and fittings shall be maintained in a leak-free condition as defined in Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Liquids from the knockout vessel shall be disposed of in a manner preventing VOC emissions. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Storage tank p/v caps shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Storage tank p/v caps shall be leak-free (except for inbreathing) during normal operation. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
8. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
9. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
10. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
16. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
19. Formerly permit number S-1136-47-0.
20. Formerly permit number S-1548-186-2.
21. Formerly permit number S-3898-5.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-417-3 **EXPIRATION DATE:** 02/28/2014

SECTION: SE18 **TOWNSHIP:** 28S **RANGE:** 20E

EQUIPMENT DESCRIPTION:
42,000 GALLON PETROLEUM STORAGE TANK (#5) EQUIPPED WITH VAREC VAPOR CONTROL SYSTEM INCLUDING VAPOR COMPRESSOR SHARED WITH S-1738-418, '-419, '-420 AND '-521 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (LAYMAN)

PERMIT UNIT REQUIREMENTS

1. Formerly S-2804-1.
2. Vapor recovery system shall be shared with permit unit S-1738-418, -419, -420, & -421. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Vapor recovery system shall be maintained in a leak-free (as defined in Rule 4623) condition and shall consist of a closed vent system that collects all VOCs from the storage tank and discharges to an open flare (permit unit S-1738-427) that reduces the inlet VOC emissions by at least 95 percent by weight as determined by the test method specified in District Rule 4623, Section 6.4.6. [District Rule 4623, 5.6.1 & District NSR Rule] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on this tank shall be equipped with a leak-free (as defined in Rule 4623) cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. All piping valves, flanges, connectors, and fittings shall be constructed and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 4623, 5.6.3 & District NSR Rule] Federally Enforceable Through Title V Permit
6. There shall be no leaks in excess of 10,000 ppmv when measured with an portable hydrocarbon detection instrument calibrated with methane in accordance with EPA Method 21. Emissions in excess of this is considered a violation of this permit. [District NSR Rule & 4623] Federally Enforceable Through Title V Permit
7. Fugitive VOC emissions rate, calculated using EPA Publication 453/R-95-017," Table 2-4 Oil and Gas Operations Average Emission Factors, from the total number of components in liquid service, tank vapor space, vapor piping to vapor recovery system manifold, and vapor recovery system shall not exceed 19.7 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

14. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-431-1 **EXPIRATION DATE:** 02/28/2014

SECTION: NE 4 **TOWNSHIP:** 11N **RANGE:** 22W

EQUIPMENT DESCRIPTION:
CLASS 1 ORGANIC LIQUID (CRUDE OIL) LOADING RACK WITH BOTTOM LOADING DRY-BREAK COUPLER FILL HOSE AND VAPOR COLLECTION HOSE SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1738-354

PERMIT UNIT REQUIREMENTS

1. All vapors displaced during liquid transfer shall be directed to vapor control system listed on S-1738-354 [District Rule 2201] Federally Enforceable Through Title V Permit
2. The loading rack shall vent to a vapor control system with a vapor collection efficiency exceeding 95%. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that VOC emissions do not exceed 0.08 pounds per 1000 gallons of organic liquid with greatest vapor pressure loaded. [District Rule 4621 and 4624] Federally Enforceable Through Title V Permit
4. VOC emission rate from petroleum product piping and components in natural gas and light liquid service shall not exceed 0.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. VOC emissions rate from liquid loss during hose disconnection shall not exceed 0.004 lb-VOC/disconnect. [District Rule 2201] Federally Enforceable Through Title V Permit
6. There shall be no more than 60 hose disconnects per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Total liquid drainage from hose disconnects shall not exceed 2 mL per average of 3 consecutive disconnects. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The operator shall keep a copy of the APCO-approved Operator Management Plan (OMP) at the facility and make it available to the APCO, ARB and US EPA upon request. By January 30 of each year, the operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing approved OMP. [District Rule 4409] Federally Enforceable Through Title V Permit
9. In accordance with the approved OMP, the operator shall meet all applicable operating, inspection and re-inspection, maintenance, process pressure relief device (PRD), component identification, recordkeeping and notification requirements of Rule 4409 for all components containing or contacting VOC at the this gas liquids processing facility, except for those components specifically exempted in Sections 4.1 and 4.2. [District Rule 4409] Federally Enforceable Through Title V Permit
10. All records required by Rule 4409 shall be retained for a minimum period of 5 years and shall be made available to the APCO, ARB and US EPA upon request. [District Rule 4409] Federally Enforceable Through Title V Permit
11. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624 5.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Loading and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at a distance of one centimeter from the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624.5.6] Federally Enforceable Through Title V Permit

13. Equipment under vapor control shall not vent to atmosphere. [District NSR Rule and 4624] Federally Enforceable Through Title V Permit

14. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

15. Permittee shall maintain an accurate fugitive component count of components in natural gas and light liquid service, and resultant emissions calculated using emissions factors from California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon leaks at Petroleum Facilities Table IV-2c. 1995 EPA Protocol Oil and Gas Production Screening Value Ranges Emission Factors. Permit holder shall update such records when new components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit

16. The permittee shall maintain an inspection log containing at least the following: A) dates of leak and drainage inspections, B) leak determination method, C) findings, D) corrective action (including date each leak or excess drainage condition repaired), and E) inspector name and signature. [District Rule 1070] Federally Enforceable Through Title V Permit

17. Permittee shall maintain accurate daily records of liquid throughput,number of disconnects, and liquid type and make such records readily available for District inspection upon request for a period of five years. [District Rule 2201 and 4624] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-443-6 **EXPIRATION DATE:** 02/28/2014

SECTION: 10 **TOWNSHIP:** 29S **RANGE:** 21E

EQUIPMENT DESCRIPTION:
2,000 BBL (29.7' DIA X 16' HIGH) FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM SHARED WITH S-1738-444, '-445, '-446 AND '-447 AND PORTABLE STORAGE TANKS S-1738-451, '-452, '-453, AND/OR '-454 (HOPKINS LEASE)

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The vapor control system shall include vapor compressor, flare S-1738-449 and connection to sales line. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Vapors shall be collected and discharged only into pipeline for sale or to flare S-1738-449. [District NSR Rule] Federally Enforceable Through Title V Permit
4. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
8. VOC fugitive emissions from the components in gas service on tank shall not exceed 18.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Permittee shall maintain accurate component count for tank and the vapor recovery system according to EPAs "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emission Factors. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operator shall visually inspect the vapor recovery system, tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

15. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

16. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rules 4623, Table 3] Federally Enforceable Through Title V Permit

17. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit

18. This tank shall be degassed before commencing interior cleaning by following one of the following options: 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit

19. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit
21. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
22. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
23. If the tank holds an organic liquid having a TVP of 1.5 psia or greater, then, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
24. If the tank holds an organic liquid having a TVP of 1.5 psia or greater, then operator shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit
25. If the tank holds an organic liquid having a TVP of 1.5 psia or greater, then operator shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
26. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit
27. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
28. Facilities S-1216, S-382, and S-1738 constitute one stationary source. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-451-1 **EXPIRATION DATE:** 02/28/2014

DRAFT

EQUIPMENT DESCRIPTION:
500 BBL CAPACITY CRUDE OIL PRODUCTION TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1738-2, '-22, '-38, '-49, '-240, '-288, '-354, '-417, OR '-443

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Storage tank shall be equipped with a vapor recovery system consisting of a closed vent system that routes all VOCs from the storage tank to a field gas gathering system. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. [District Rules 2201and 4623] Federally Enforceable Through Title V Permit
3. Storage tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv) for tank components and for components in piping from the tank to vapor control system truck line. The ppmv readings, as methane above background, shall be taken using a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. A gas or liquid leak is a violation of this permit and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. VOC fugitive emissions from tank and from components in piping from tank to vapor control system trunk line shall not exceed 0.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions from tank components and from components in piping from the tank to vapor control system truck line calculated using screening value emissions factors of CARB/CAPCOA "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" included in EPA, "Protocol for Estimating Leak Emissions" (EPA - 453/R-95-017, November 1995). [District Rule 2201] Federally Enforceable Through Title V Permit
7. Gas-leak concentration shall be determined by EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on storage tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect storage tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Upon detection of a liquid leak from storage tank, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 parts per million by volume (ppmv) for the tank and 2,000 parts per million by volume (ppmv) for the tank vapor control system measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

13. If a component type for storage tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

15. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-452-1 **EXPIRATION DATE:** 02/28/2014

DRAFT

EQUIPMENT DESCRIPTION:
500 BBL CAPACITY CRUDE OIL PRODUCTION TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1738-2, '-22, '-38, '-49, '-240, '-288, '-354, '-417, OR '-443

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Storage tank shall be equipped with a vapor recovery system consisting of a closed vent system that routes all VOCs from the storage tank to a field gas gathering system. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. [District Rules 2201and 4623] Federally Enforceable Through Title V Permit
3. Storage tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv) for tank components and for components in piping from the tank to vapor control system truck line. The ppmv readings, as methane above background, shall be taken using a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. A gas or liquid leak is a violation of this permit and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. VOC fugitive emissions from tank and from components in piping from tank to vapor control system trunk line shall not exceed 0.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions from tank components and from components in piping from the tank to vapor control system truck line calculated using screening value emissions factors of CARB/CAPCOA "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" included in EPA, "Protocol for Estimating Leak Emissions" (EPA - 453/R-95-017, November 1995). [District Rule 2201] Federally Enforceable Through Title V Permit
7. Gas-leak concentration shall be determined by EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on storage tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect storage tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Upon detection of a liquid leak from storage tank, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 parts per million by volume (ppmv) for the tank and 2,000 parts per million by volume (ppmv) for the tank vapor control system measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

13. If a component type for storage tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

15. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-453-1 **EXPIRATION DATE:** 02/28/2014

DRAFT

EQUIPMENT DESCRIPTION:
500 BBL CAPACITY CRUDE OIL PRODUCTION TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1738-2, '-22, '-38, '-49, '-240, '-288, '-354, '-417, OR '-443

PERMIT UNIT REQUIREMENTS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Storage tank shall be equipped with a vapor recovery system consisting of a closed vent system that routes all VOCs from the storage tank to a field gas gathering system. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. [District Rules 2201and 4623] Federally Enforceable Through Title V Permit
4. Storage tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv) for tank components and for components in piping from the tank to vapor control system truck line. The ppmv readings, as methane above background, shall be taken using a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. A gas or liquid leak is a violation of this permit and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. VOC fugitive emissions from tank and from components in piping from tank to vapor control system trunk line shall not exceed 0.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions from tank components and from components in piping from the tank to vapor control system truck line calculated using screening value emissions factors of CARB/CAPCOA "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" included in EPA, "Protocol for Estimating Leak Emissions" (EPA - 453/R-95-017, November 1995). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Gas-leak concentration shall be determined by EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Any tank gauging or sampling device on storage tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall visually inspect storage tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

11. Upon detection of a liquid leak from storage tank, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 parts per million by volume (ppmv) for the tank and 2,000 parts per million by volume (ppmv) for the tank vapor control system measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

14. If a component type for storage tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

16. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-454-1 **EXPIRATION DATE:** 02/28/2014

DRAFT

EQUIPMENT DESCRIPTION:
500 BBL CAPACITY CRUDE OIL PRODUCTION TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1738-2, '-22, '-38, '-49, '-240, '-288, '-354, '-417, OR '-443

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Storage tank shall be equipped with a vapor recovery system consisting of a closed vent system that routes all VOCs from the storage tank to a field gas gathering system. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. [District Rules 2201and 4623] Federally Enforceable Through Title V Permit
3. Storage tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv) for tank components and for components in piping from the tank to vapor control system truck line. The ppmv readings, as methane above background, shall be taken using a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. A gas or liquid leak is a violation of this permit and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. VOC fugitive emissions from tank and from components in piping from tank to vapor control system trunk line shall not exceed 0.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions from tank components and from components in piping from the tank to vapor control system truck line calculated using screening value emissions factors of CARB/CAPCOA "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" included in EPA, "Protocol for Estimating Leak Emissions" (EPA - 453/R-95-017, November 1995). [District Rule 2201] Federally Enforceable Through Title V Permit
7. Gas-leak concentration shall be determined by EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on storage tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect storage tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Upon detection of a liquid leak from storage tank, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 parts per million by volume (ppmv) for the tank and 2,000 parts per million by volume (ppmv) for the tank vapor control system measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

13. If a component type for storage tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

15. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

DRAFT

ATTACHMENT B

Authorities to Construct

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-2-7 **ISSUANCE DATE:** 05/02/2012

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

SECTION: 33 **TOWNSHIP:** 12N **RANGE:** 21W

EQUIPMENT DESCRIPTION:
MODIFICATION OF 42,000 GALLON FIXED-ROOF PETROLEUM STORAGE TANK #TOC 1046 WITH VAPOR RECOVERY SYSTEM SHARED WITH PERMITS S-1738-30, '-31, '-53 AND '-226 INCLUDING 7.5 HP VAPOR COMPRESSOR (RIO VIEJO FIELD 86X-33): CONNECT UP TO FOUR (4) 500 BBL TANKS (S-1738-451 THROUGH '-454) TO VAPOR CONTROL SYSTEM

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping valves and fittings shall be constructed and maintained in a leak-free condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-2-7 : Jul 19 2013 8:10AM -- EDGEHILR : Joint Inspection NOT Required

4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit

5. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

6. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

7. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

8. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. Vapors shall vent only through gas line compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

11. Storage tank p/v caps shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

12. Storage tank p/v caps shall be leak-free (except for in breathing) during normal operation. [District NSR Rule] Federally Enforceable Through Title V Permit

13. Liquids from knockout vessel shall be disposed of in a manner preventing emissions to the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit

14. Vapor compressor shall activate whenever tank internal pressure exceeds 1 oz./sq. in. [District NSR Rule] Federally Enforceable Through Title V Permit

15. VOC emission rate shall not exceed 0.17 lb/hr for this permit unit and permit units S-1738-30, '-31, '-53 and '-226 combined. [District NSR Rule] Federally Enforceable Through Title V Permit

16. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

17. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

18. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

20. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

21. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

22. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

23. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

25. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-22-5 **ISSUANCE DATE:** 05/02/2012

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

SECTION: 25 **TOWNSHIP:** 11N **RANGE:** 21W

EQUIPMENT DESCRIPTION:
MODIFICATION OF 84,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #5029 WITH VAPOR RECOVERY SYSTEM SERVING PERMITS S-1738-22 THROUGH '-26 AND '-267 (PLEITO HILLS RANCH): CONNECT UP TO FOUR (4) 500 BBL TANKS (S-1738-451 THROUGH '-454) TO VAPOR CONTROL SYSTEM

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-22-5 : Jul 19 2013 8:10AM -- EDGEHILR : Joint Inspection NOT Required

4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit

5. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

6. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

7. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

8. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. Vapors shall vent only through gas line compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

11. Storage tank p/v caps shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

12. Storage tank p/v caps shall be leak-free (except for inbreathing) during normal operation. [District NSR Rule] Federally Enforceable Through Title V Permit

13. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

14. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

15. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

16. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

17. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

18. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

19. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

22. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-38-5 **ISSUANCE DATE:** 05/02/2012

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 20W

EQUIPMENT DESCRIPTION:
MODIFICATION OF 42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #1846 WITH VAPOR RECOVERY SYSTEM INCLUDING 7.5 HP COMPRESSOR (WHEELER RIDGE): CONNECT UP TO FOUR (4) 500 BBL TANKS (S-1738-451 THROUGH '-454) TO VAPOR CONTROL SYSTEM

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-38-5 : Jul 19 2013 8:10AM -- EDGEHILR : Joint Inspection NOT Required

4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit

5. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

6. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

7. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

8. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. Vapors shall vent only through gas line compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

11. Storage tank p/v caps shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

12. Storage tank p/v caps shall be leak-free (except for inbreathing) during normal operation. [District NSR Rule] Federally Enforceable Through Title V Permit

13. Liquids from knockout vessel shall be disposed of in a manner preventing emissions to the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit

14. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

15. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

16. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

17. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

18. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

19. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

20. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

23. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-49-6 **ISSUANCE DATE:** 05/02/2012

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

SECTION: SE22 **TOWNSHIP:** 11N **RANGE:** 20W

EQUIPMENT DESCRIPTION:
MODIFICATION OF 42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK WITH VAPOR RECOVERY SYSTEM INCLUDING ONE 15 HP COMPRESSOR AND/OR ONE 30 HP COMPRESSOR SERVING PERMIT UNITS S-1738-50 THROUGH '-52 (G SOUTH): CONNECT UP TO FOUR (4) 500 BBL TANKS (S-1738-451 THROUGH '-454) TO VAPOR CONTROL SYSTEM

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-49-6 : Jul 19 2013 8:10AM -- EDGEHILR : Joint Inspection NOT Required

5. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

6. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

7. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

8. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit

10. Vapor control system shall operate between 0.5 in. w.c. and 1.5 in. w.c. [District NSR Rule] Federally Enforceable Through Title V Permit

11. True vapor pressure of stored liquid shall not exceed 14.0 psia. [District NSR Rule] Federally Enforceable Through Title V Permit

12. Tank throughput shall not exceed 333 bbl/day. [District NSR Rule] Federally Enforceable Through Title V Permit

13. VOC emission rate shall not exceed 0.06 lb/hr. [District NSR Rule] Federally Enforceable Through Title V Permit

14. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

15. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

16. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

17. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

18. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

20. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

23. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. Operator shall maintain records of daily tank throughput. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-240-6 **ISSUANCE DATE:** 05/02/2012

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

SECTION: SW03 **TOWNSHIP:** 32S **RANGE:** 26E

EQUIPMENT DESCRIPTION:
MODIFICATION OF 16,926 GALLON FIXED ROOF PETROLEUM STORAGE TANK #5335 WITH VAPOR RECOVERY SYSTEM INCLUDING 12 HP COMPRESSOR SERVING PERMITS S-1738-241 THROUGH '-246 (PALOMA PROJECT): CONNECT UP TO FOUR (4) 500 BBL TANKS (S-1738-451 THROUGH '-454) TO VAPOR CONTROL SYSTEM

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-240-6 : Jul 19 2013 8:10AM -- EDGEHILR : Joint Inspection NOT Required

5. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

6. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

7. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

8. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit

10. Tank shall not be used to store or process liquids if the vapor control system is inoperable. [District NSR Rule] Federally Enforceable Through Title V Permit

11. Vapor recovery system shall vent to gas plant (permit S-39-1) only. [District NSR Rule] Federally Enforceable Through Title V Permit

12. Average tank throughput shall not exceed 25,200 gallons/day (calculated on a calendar quarter basis). [District NSR Rule] Federally Enforceable Through Title V Permit

13. True vapor pressure of liquid stored shall not exceed 9.8 psia. [District NSR Rule] Federally Enforceable Through Title V Permit

14. VOC emission rate shall not exceed 0.2 lb/hr and 0.59 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit

15. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

16. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

17. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

18. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

20. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

21. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

22. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

24. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Operator shall maintain records of average daily tank throughput. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-288-6 **ISSUANCE DATE:** 05/02/2012

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

SECTION: NW30 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
MODIFICATION OF 84,000 GALLON FIXED-ROOF SHIPPING TANK WITH VAPOR CONTROL SHARED WITH S-1738-289, '290, '340, & '341 - M&M LEASE: CONNECT UP TO FOUR (4) 500 BBL TANKS (S-1738-451 THROUGH '-454) TO VAPOR CONTROL SYSTEM

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-288-6 : Jul 19 2013 8:10AM -- EDGEHILR : Joint Inspection NOT Required

5. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

6. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

7. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

8. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit

10. Vapor recovery system shall include 6" dia. piping connecting tank vapor spaces to 8" dia. gas boot, 2" dia. piping (from 6" dia. piping) serving vapor compressor switches & dry gas regulator, and connecting 3" dia. compressor intake piping. [District NSR Rule] Federally Enforceable Through Title V Permit

11. Vapor recovery system shall include 1" dia. dry gas piping regulated by dry gas regulator & feeding to 8" dia. gas boot, one Varec dry gas regulator, and one back pressure check valve on 3" dia. compressor intake piping. [District NSR Rule] Federally Enforceable Through Title V Permit

12. Vapor recovery system shall include two dryer explosion proof pressure switches, one activating & one de-activating vapor compressor, and one 20 hp Santa Fe Systems Co. vapor compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

13. Prior to breaking the vapor-tight seal on any tank, the dry gas supply line to the system shall be closed. [District NSR Rule] Federally Enforceable Through Title V Permit

14. Liquid condensates from gas boot shall be handled in a manner to prevent emissions to atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit

15. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit

16. VOC content of total organic hydrocarbons in gas shall not exceed 29% by weight. [District NSR Rule] Federally Enforceable Through Title V Permit

17. Permittee shall perform and record annual gas analysis for VOC content and make such records available for District inspection upon request. [District NSR Rule] Federally Enforceable Through Title V Permit

18. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

19. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

20. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

21. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

22. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

23. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

24. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

25. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

27. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. VOC shall be tested using EPA Method 25 or EPA Method 18 referenced as methane. [District Rules 1081 and District NSR Rule] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-354-2 **ISSUANCE DATE:** 03/25/2010

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

SECTION: NE 04 **TOWNSHIP:** 11N **RANGE:** 22W

EQUIPMENT DESCRIPTION:
MODIFICATION OF 126,000 GALLON (3,000 BBL) FIXED ROOF WASH TANK WITH VAPOR RECOVERY, INCLUDING: VAPOR COMPRESSORS, SEPARATORS, AND ONE EMERGENCY FLARE. V/R SYSTEM SHARED WITH TANKS S-1738-354 THROUGH '358, LOCATED IN THE YOWLUMNE TANK BATTERY: TIE LOADING RACK S-1738-431 TO VAPOR CONTROL SYSTEM

CONDITIONS

1. This ATC shall be implemented concurrently with ATC S-1738-431-0. [District Rule 2201]
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
3. Vapors shall vent only through gas line compressor. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All piping, valves and fittings shall be maintained in a gas-tight condition as defined in Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Liquids from the knockout vessel shall be disposed of in a manner preventing VOC emissions. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Storage tank p/v caps shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-354-2 : Jul 19 2013 4:02PM -- EDGEHILR : Joint Inspection NOT Required

7. Storage tank p/v caps shall be vapor tight (except for inbreathing) during normal operation. [District Rule 4623] Federally Enforceable Through Title V Permit

8. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit

9. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, on a portable hydrocarbon detection instrument. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit

10. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

11. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

12. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

13. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

16. Formerly permit number S-1136-47-0.

17. Formerly permit number S-1548-186-2.

18. Formerly permit number S-3898-5.

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-354-3 **ISSUANCE DATE:** 05/02/2012

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

SECTION: 04 **TOWNSHIP:** 11N **RANGE:** 22W

EQUIPMENT DESCRIPTION:
MODIFICATION OF 126,000 GALLON (3,000 BBL) FIXED ROOF WASH TANK WITH VAPOR RECOVERY, INCLUDING: VAPOR COMPRESSORS, SEPARATORS, AND ONE EMERGENCY FLARE. V/R SYSTEM SHARED WITH TANKS S-1738-354 THROUGH '358, LOCATED IN THE YOWLUMNE TANK BATTERY: CONNECT UP TO FOUR (4) 500 BBL TANKS (S-1738-451 THROUGH '-454) TO VAPOR CONTROL SYSTEM

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
3. Vapors shall vent only through gas line compressor. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All piping, valves and fittings shall be maintained in a leak-free condition as defined in Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Liquids from the knockout vessel shall be disposed of in a manner preventing VOC emissions. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Storage tank p/v caps shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-354-3 : Jul 19 2013 8:10AM -- EDGEHILR : Joint Inspection NOT Required

7. Storage tank p/v caps shall be leak-free (except for inbreathing) during normal operation. [District Rule 4623] Federally Enforceable Through Title V Permit

8. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit

9. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit

10. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

11. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

12. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

13. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

14. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

15. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

16. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

17. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

18. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
20. Formerly permit number S-1136-47-0.
21. Formerly permit number S-1548-186-2.
22. Formerly permit number S-3898-5.

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-417-2 **ISSUANCE DATE:** 05/02/2012

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

SECTION: SE18 **TOWNSHIP:** 28S **RANGE:** 20E

EQUIPMENT DESCRIPTION:
MODIFICATION OF 42,000 GALLON PETROLEUM STORAGE TANK (#5) EQUIPPED WITH VAREC VAPOR CONTROL SYSTEM INCLUDING VAPOR COMPRESSOR SHARED WITH S-1738-418, '-419, '-420 & '-421 (LAYMAN): CONNECT UP TO FOUR (4) 500 BBL TANKS (S-1738-451 THROUGH '-454) TO VAPOR CONTROL SYSTEM

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. Formerly S-2804-1.
3. Vapor recovery system shall be shared with permit unit S-1738-418, -419, -420, & -421. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Vapor recovery system shall be maintained in a leak-free (as defined in Rule 4623) condition and shall consist of a closed vent system that collects all VOCs from the storage tank and discharges to an open flare (permit unit S-1738-427) that reduces the inlet VOC emissions by at least 95 percent by weight as determined by the test method specified in District Rule 4623, Section 6.4.6. [District Rule 4623, 5.6.1 & District NSR Rule] Federally Enforceable Through Title V Permit
5. Any tank gauging or sampling device on this tank shall be equipped with a leak-free (as defined in Rule 4623) cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-417-2 : Jul 19 2013 8:11AM – EDGEHILR : Joint Inspection NOT Required

6. All piping valves, flanges, connectors, and fittings shall be constructed and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 4623, 5.6.3 & District NSR Rule] Federally Enforceable Through Title V Permit

7. There shall be no leaks in excess of 10,000 ppmv when measured with an portable hydrocarbon detection instrument calibrated with methane in accordance with EPA Method 21. Emissions in excess of this is considered a violation of this permit. [District NSR Rule & 4623] Federally Enforceable Through Title V Permit

8. Fugitive VOC emissions rate, calculated using EPA Publication 453/R-95-017," Table 2-4 Oil and Gas Operations Average Emission Factors, from the total number of components in liquid service, tank vapor space, vapor piping to vapor recovery system manifold, and vapor recovery system shall not exceed 19.7 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit

9. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

10. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

15. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

16. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-443-5 **ISSUANCE DATE:** 05/02/2012

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

SECTION: 10 **TOWNSHIP:** 29S **RANGE:** 21E

EQUIPMENT DESCRIPTION:
MODIFICATION OF 2000 BBL (29.7' DIA. X 16' HIGH) FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM SHARED WITH S-1738-444, '-445, '-446, AND '-447 (HOPKINS LEASE): CONNECT UP TO FOUR (4) 500 BBL TANKS (S-1738-451 THROUGH '-454) TO VAPOR CONTROL SYSTEM, RECALCULATE FUGITIVE EMISSIONS USING CAPCOA SCREENING VALUE EMISSIONS FACTORS

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The vapor control system shall include vapor compressor, flare S-1738-449 and connection to sales line. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Vapors shall be collected and discharged only into pipeline for sale or to flare S-1738-449. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-443-5 : Jul 19 2013 8:11AM -- EDGEHILR : Joint Inspection NOT Required

6. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit

7. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 4623] Federally Enforceable Through Title V Permit

8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit

9. VOC fugitive emissions from the components in gas and light oil service on tank shall not exceed 0.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Permittee shall maintain accurate component count for tank and the vapor recovery system according to EPAs screening value emissions factors of CARB/CAPCOA "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities." Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Operator shall visually inspect the vapor recovery system, tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

12. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

13. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

14. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

16. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

17. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rules 4623, Table 3] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

18. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit

19. This tank shall be degassed before commencing interior cleaning by following one of the following options: 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit

20. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit

21. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit

22. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit

23. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit

24. If the tank holds an organic liquid having a TVP of 1.5 psia or greater, then, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit

25. If the tank holds an organic liquid having a TVP of 1.5 psia or greater, then operator shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit

26. If the tank holds an organic liquid having a TVP of 1.5 psia or greater, then operator shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

27. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit

28. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

29. Facilities S-1216, S-382, and S-1738 constitute one stationary source. [District Rule 2201] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-431-0 **ISSUANCE DATE:** 03/25/2010

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

SECTION: NE 4 **TOWNSHIP:** 11N **RANGE:** 22W

EQUIPMENT DESCRIPTION:
CLASS 1 ORGANIC LIQUID (CRUDE OIL) LOADING RACK WITH BOTTOM LOADING DRY-BREAK COUPLER FILL HOSE AND VAPOR COLLECTION HOSE SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1738-354

CONDITIONS

1. This ATC shall be implemented concurrently with ATC S-1738-354-2 [District Rule 2201]
2. All vapors displaced during liquid transfer shall be directed to vapor control system listed on S-1738-354 [District Rule 2201]
3. The loading rack shall vent to a vapor control system with a vapor collection efficiency exceeding 95%. [District NSR Rule]
4. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that VOC emissions do not exceed 0.08 pounds per 1000 gallons of organic liquid with greatest vapor pressure loaded. [District Rule 4621 and 4624]
5. VOC emission rate from petroleum product piping and components in natural gas and light liquid service shall not exceed 0.1 lb/day. [District Rule 2201]
6. VOC emissions rate from liquid loss during hose disconnection shall not exceed 0.004 lb-VOC/disconnect. [District Rule 2201]
7. There shall be no more than 60 hose disconnects per day. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-431-0 : Jul 19 2013 9:02AM – EDGEHILR : Joint Inspection NOT Required

8. Total liquid drainage from hose disconnects shall not exceed 2 mL per average of 3 consecutive disconnects. [District Rule 2201]

9. The operator shall keep a copy of the APCO-approved Operator Management Plan (OMP) at the facility and make it available to the APCO, ARB and US EPA upon request. By January 30 of each year, the operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing approved OMP. [District Rule 4409]

10. In accordance with the approved OMP, the operator shall meet all applicable operating, inspection and re-inspection, maintenance, process pressure relief device (PRD), component identification, recordkeeping and notification requirements of Rule 4409 for all components containing or contacting VOC at the this gas liquids processing facility, except for those components specifically exempted in Sections 4.1 and 4.2. [District Rule 4409]

11. All records required by Rule 4409 shall be retained for a minimum period of 5 years and shall be made available to the APCO, ARB and US EPA upon request. [District Rule 4409]

12. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624 5.4]

13. Loading and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at a distance of one centimeter from the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624.5.6]

14. Equipment under vapor control shall not vent to atmosphere. [District NSR Rule and 4624]

15. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624]

16. Permittee shall maintain an accurate fugitive component count of components in natural gas and light liquid service, and resultant emissions calculated using emissions factors from California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon leaks at Petroleum Facilities Table IV-2c. 1995 EPA Protocol Oil and Gas Production Screening Value Ranges Emission Factors. Permit holder shall update such records when new components are installed. [District Rule 2201]

17. The permittee shall maintain an inspection log containing at least the following: A) dates of leak and drainage inspections, B) leak determination method, C) findings, D) corrective action (including date each leak or excess drainage condition repaired), and E) inspector name and signature. [District Rule 1070]

18. Permittee shall maintain accurate daily records of liquid throughput,number of disconnects, and liquid type and make such records readily available for District inspection upon request for a period of five years. [District Rule 2201 and 4624]

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-451-0 **ISSUANCE DATE:** 05/02/2012

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

EQUIPMENT DESCRIPTION:
500 BBL CAPACITY CRUDE OIL PRODUCTION TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1738-2, '-22, '-38, '-49, '-240, '-288, '-354, '-417, OR '-443

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Storage tank shall be equipped with a vapor recovery system consisting of a closed vent system that routes all VOCs from the storage tank to a field gas gathering system. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. [District Rules 2201and 4623] Federally Enforceable Through Title V Permit
4. Storage tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv) for tank components and for components in piping from the tank to vapor control system truck line. The ppmv readings, as methane above background, shall be taken using a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. A gas or liquid leak is a violation of this permit and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-451-0 : Jul 19 2013 8:11AM -- EDGEHILR : Joint Inspection NOT Required

6. VOC fugitive emissions from tank and from components in piping from tank to vapor control system trunk line shall not exceed 0.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

7. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions from tank components and from components in piping from the tank to vapor control system truck line calculated using screening value emissions factors of CARB/CAPCOA "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" included in EPA, "Protocol for Estimating Leak Emissions" (EPA - 453/R-95-017, November 1995). [District Rule 2201] Federally Enforceable Through Title V Permit

8. Gas-leak concentration shall be determined by EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit

9. Any tank gauging or sampling device on storage tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

10. Operator shall visually inspect storage tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

11. Upon detection of a liquid leak from storage tank, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 parts per million by volume (ppmv) for the tank and 2,000 parts per million by volume (ppmv) for the tank vapor control system measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

14. If a component type for storage tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

16. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-452-0 **ISSUANCE DATE:** 05/02/2012

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

EQUIPMENT DESCRIPTION:
500 BBL CAPACITY CRUDE OIL PRODUCTION TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1738-2, '-22, '-38, '-49, '-240, '-288, '-354, '-417, OR '-443

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Storage tank shall be equipped with a vapor recovery system consisting of a closed vent system that routes all VOCs from the storage tank to a field gas gathering system. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. [District Rules 2201and 4623] Federally Enforceable Through Title V Permit
4. Storage tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv) for tank components and for components in piping from the tank to vapor control system truck line. The ppmv readings, as methane above background, shall be taken using a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. A gas or liquid leak is a violation of this permit and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-452-0 : Jul 19 2013 8:11AM -- EDGEHILR : Joint Inspection NOT Required

6. VOC fugitive emissions from tank and from components in piping from tank to vapor control system trunk line shall not exceed 0.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

7. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions from tank components and from components in piping from the tank to vapor control system truck line calculated using screening value emissions factors of CARB/CAPCOA "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" included in EPA, "Protocol for Estimating Leak Emissions" (EPA - 453/R-95-017, November 1995). [District Rule 2201] Federally Enforceable Through Title V Permit

8. Gas-leak concentration shall be determined by EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit

9. Any tank gauging or sampling device on storage tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

10. Operator shall visually inspect storage tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

11. Upon detection of a liquid leak from storage tank, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 parts per million by volume (ppmv) for the tank and 2,000 parts per million by volume (ppmv) for the tank vapor control system measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

14. If a component type for storage tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

16. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-453-0 **ISSUANCE DATE:** 05/02/2012

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

EQUIPMENT DESCRIPTION:
500 BBL CAPACITY CRUDE OIL PRODUCTION TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1738-2, '-22, '-38, '-49, '-240, '-288, '-354, '-417, OR '-443

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Storage tank shall be equipped with a vapor recovery system consisting of a closed vent system that routes all VOCs from the storage tank to a field gas gathering system. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. [District Rules 2201and 4623] Federally Enforceable Through Title V Permit
4. Storage tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv) for tank components and for components in piping from the tank to vapor control system truck line. The ppmv readings, as methane above background, shall be taken using a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. A gas or liquid leak is a violation of this permit and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-453-0 : Jul 19 2013 8:11AM -- EDGEHILR : Joint Inspection NOT Required

6. VOC fugitive emissions from tank and from components in piping from tank to vapor control system trunk line shall not exceed 0.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

7. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions from tank components and from components in piping from the tank to vapor control system truck line calculated using screening value emissions factors of CARB/CAPCOA "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" included in EPA, "Protocol for Estimating Leak Emissions" (EPA - 453/R-95-017, November 1995). [District Rule 2201] Federally Enforceable Through Title V Permit

8. Gas-leak concentration shall be determined by EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit

9. Any tank gauging or sampling device on storage tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

10. Operator shall visually inspect storage tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

11. Upon detection of a liquid leak from storage tank, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 parts per million by volume (ppmv) for the tank and 2,000 parts per million by volume (ppmv) for the tank vapor control system measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

14. If a component type for storage tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

16. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-454-0 **ISSUANCE DATE:** 05/02/2012

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

EQUIPMENT DESCRIPTION:
500 BBL CAPACITY CRUDE OIL PRODUCTION TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1738-2, '-22, '-38, '-49, '-240, '-288, '-354, '-417, OR '-443

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Storage tank shall be equipped with a vapor recovery system consisting of a closed vent system that routes all VOCs from the storage tank to a field gas gathering system. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. [District Rules 2201and 4623] Federally Enforceable Through Title V Permit
4. Storage tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv) for tank components and for components in piping from the tank to vapor control system truck line. The ppmv readings, as methane above background, shall be taken using a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. A gas or liquid leak is a violation of this permit and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-454-0 : Jul 19 2013 8:11AM – EDGEHILR : Joint Inspection NOT Required

6. VOC fugitive emissions from tank and from components in piping from tank to vapor control system trunk line shall not exceed 0.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

7. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions from tank components and from components in piping from the tank to vapor control system truck line calculated using screening value emissions factors of CARB/CAPCOA "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" included in EPA, "Protocol for Estimating Leak Emissions" (EPA - 453/R-95-017, November 1995). [District Rule 2201] Federally Enforceable Through Title V Permit

8. Gas-leak concentration shall be determined by EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit

9. Any tank gauging or sampling device on storage tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

10. Operator shall visually inspect storage tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

11. Upon detection of a liquid leak from storage tank, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 parts per million by volume (ppmv) for the tank and 2,000 parts per million by volume (ppmv) for the tank vapor control system measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

14. If a component type for storage tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

16. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

ATTACHMENT C
Permit Application

San Joaquin Valley
Unified Air Pollution Control District

TITLE V MODIFICATION - COMPLIANCE CERTIFICATION FORM

I. TYPE OF PERMIT ACTION (Check appropriate box)

[ ] SIGNIFICANT PERMIT MODIFICATION
[X] MINOR PERMIT MODIFICATION
[ ] ADMINISTRATIVE AMENDMENT

COMPANY NAME: **Vintage Production California LLC**	FACILITY ID: - **S – 1738**
1. Type of Organization: [X]Corporation [ ]Sole Ownership [ ]Government [ ]Partnership [ ]Utility	
2. Owner's Name: **Vintage Production California LLC**	
3. Agent to the Owner: **Stephen Bartz**	

II. COMPLIANCE CERTIFICATION (Read each statement carefully and initial **all** circles for confirmation):

(SS) Based on information and belief formed after reasonable inquiry, the source identified in this application will continue to comply with the applicable federal requirement(s) which the source is in compliance.

(SS) Based on information and belief formed after reasonable inquiry, the source identified in this application will comply with applicable federal requirement(s) that will become effective during the permit term, on a timely basis.

(SS) Corrected information will be provided to the District when I become aware that incorrect or incomplete information has been submitted.

(SS) Based on information and belief formed after reasonable inquiry, information and statements in the submitted application package, including all accompanying reports, and required certifications are true accurate and complete.

I declare, under penalty of perjury under the laws of the state of California, that the forgoing is correct and true:

Signature of Responsible Official

July 19, 2013
Date

Stephen Bartz
Name of Responsible Official (please print)

Operations Team Lead (Central)
Title of Responsible Official (please print)

Incorporate multiple ATCs into Title V permit

S-1738-2-8, 22-6, 38-6, 49-7, 240-8, 288-7, 354-4, 417-3, 431-1, 443-6, 451-1, 452-1, 453-1, 454-1

San Joaquin Valley Air Pollution Control District

www.valleyair.org

Permit Application For:

[ ] ADMINISTRATIVE AMENDMENT [X] MINOR MODIFICATION [ ] SIGNIFICANT MODIFICATION

1. PERMIT TO BE ISSUED TO: **Vintage Production California LLC (VPC)**

2. MAILING ADDRESS:

STREET/P.O. BOX: **9600 Ming Avenue, Suite 300**

CITY: **Bakersfield** STATE: **CA** 9-DIGIT ZIP CODE: **93311**

3. LOCATION WHERE THE EQUIPMENT WILL BE OPERATED:

STREET: **Multiple Locations** CITY: **LOW**

_____ ¼ SECTION _____ TOWNSHIP _____ RANGE _____

INSTALLATION DATE:

4. GENERAL NATURE OF BUSINESS: **Crude Oil and Natural Gas Production**

5. DESCRIPTION OF EQUIPMENT OR MODIFICATION FOR WHICH APPLICATION IS MADE
(include Permit #'s if known, and use additional sheets if necessary)

Incorporate ATC S-1738-354-2, '-431-0, '-2-7, '-22-5, '-38-5, '-49-6, '-240-6, '-288-6, '-354-3, '-417-2, '-443-5, '-451-0, '-452-0, '-453-0 and '-454-0 into Title V permit S-1738 – Vintage Production California LLC, Light Oil Western stationary source.

6. TYPE OR PRINT NAME OF APPLICANT:
Phil Acosta – Vintage Production California LLC

TITLE OF APPLICANT:
HES Advisor

7. SIGNATURE OF APPLICANT:

DATE: **07/19/13**

PHONE: **(661) 869-8065**
FAX: **(661) 869-8170**
EMAIL: **Phil_Acosta@oxy.com**

For APCD Use Only:

DATE STAMP	*FILING FEE RECEIVED :* $ _____ *CHECK#:* _____
	DATE PAID: _____
	PROJECT NO: _____ *FACILITY ID:* _____

ATTACHMENT D

Previous Title V PTO

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-2-6 **EXPIRATION DATE:** 02/28/2014

SECTION: 33 **TOWNSHIP:** 12N **RANGE:** 21W

EQUIPMENT DESCRIPTION:
42,000 GALLON FIXED-ROOF PETROLEUM STORAGE TANK #TOC 1046 WITH VAPOR RECOVERY SYSTEM SHARED WITH PERMITS S-1738-30, '-31, '-53 AND '-226 INCLUDING 7.5 HP VAPOR COMPRESSOR (RIO VIEJO FIELD 86X-33)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
2. All piping valves and fittings shall be constructed and maintained in a leak-free condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
9. Vapors shall vent only through gas line compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Storage tank p/v caps shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR Rule] Federally Enforceable Through Title V Permit
11. Storage tank p/v caps shall be leak-free (except for in breathing) during normal operation. [District NSR Rule] Federally Enforceable Through Title V Permit
12. Liquids from knockout vessel shall be disposed of in a manner preventing emissions to the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Vapor compressor shall activate whenever tank internal pressure exceeds 1 oz./sq. in. [District NSR Rule] Federally Enforceable Through Title V Permit
14. VOC emission rate shall not exceed 0.17 lb/hr for this permit unit and permit units S-1738-30, '-31, '-53 and '-226 combined. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
16. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
17. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
18. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
19. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
20. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
21. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
22. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit
24. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
25. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-22-4 **EXPIRATION DATE:** 02/28/2014

SECTION: 25 **TOWNSHIP:** 11N **RANGE:** 21W

EQUIPMENT DESCRIPTION:
84,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #5029 WITH VAPOR RECOVERY SYSTEM SERVING PERMITS S-1738-22 THROUGH '-26 AND '-267 (PLEITO HILLS RANCH)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
2. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
9. Vapors shall vent only through gas line compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Storage tank p/v caps shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

11. Storage tank p/v caps shall be leak-free (except for inbreathing) during normal operation. [District NSR Rule] Federally Enforceable Through Title V Permit

12. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

13. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

14. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

15. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

16. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

17. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

18. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

19. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-38-4 **EXPIRATION DATE:** 02/28/2014

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 20W

EQUIPMENT DESCRIPTION:
42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #1846 WITH VAPOR RECOVERY SYSTEM INCLUDING 7.5 HP COMPRESSOR (WHEELER RIDGE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
2. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
9. Vapors shall vent only through gas line compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Storage tank p/v caps shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR Rule] Federally Enforceable Through Title V Permit
11. Storage tank p/v caps shall be leak-free (except for inbreathing) during normal operation. [District NSR Rule] Federally Enforceable Through Title V Permit
12. Liquids from knockout vessel shall be disposed of in a manner preventing emissions to the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
14. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
15. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
16. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
17. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
18. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
19. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
20. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit
22. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
23. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-49-5 **EXPIRATION DATE:** 02/28/2014

SECTION: SE22 **TOWNSHIP:** 11N **RANGE:** 20W

EQUIPMENT DESCRIPTION:
42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK WITH VAPOR RECOVERY SYSTEM INCLUDING ONE 15 HP COMPRESSOR AND/OR ONE 30 HP COMPRESSOR SERVING PERMIT UNITS S-1738-50 THROUGH '-52 (G SOUTH)

PERMIT UNIT REQUIREMENTS

1. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
4. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Vapor control system shall operate between 0.5 in. w.c. and 1.5 in. w.c. [District NSR Rule] Federally Enforceable Through Title V Permit
10. True vapor pressure of stored liquid shall not exceed 14.0 psia. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Tank throughput shall not exceed 333 bbl/day. [District NSR Rule] Federally Enforceable Through Title V Permit
12. VOC emission rate shall not exceed 0.06 lb/hr. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
14. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
15. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
16. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
17. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
18. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
19. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
20. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit
22. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. Operator shall maintain records of daily tank throughput. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-240-5 **EXPIRATION DATE:** 02/28/2014

SECTION: SW03 **TOWNSHIP:** 32S **RANGE:** 26E

EQUIPMENT DESCRIPTION:
16,926 GALLON FIXED ROOF PETROLEUM STORAGE TANK #5335 WITH VAPOR RECOVERY SYSTEM INCLUDING 12 HP COMPRESSOR SERVING PERMITS S-1738-241 THROUGH '-246 (PALOMA PROJECT)

PERMIT UNIT REQUIREMENTS

1. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
4. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Tank shall not be used to store or process liquids if the vapor control system is inoperable. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Vapor recovery system shall vent to gas plant (permit S-39-1) only. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Average tank throughput shall not exceed 25,200 gallons/day (calculated on a calendar quarter basis). [District NSR Rule] Federally Enforceable Through Title V Permit
12. True vapor pressure of liquid stored shall not exceed 9.8 psia. [District NSR Rule] Federally Enforceable Through Title V Permit
13. VOC emission rate shall not exceed 0.2 lb/hr and 0.59 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
14. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
15. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
16. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
17. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
18. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
19. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
20. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit
23. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
24. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
25. Operator shall maintain records of average daily tank throughput. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-288-5 **EXPIRATION DATE:** 02/28/2014

SECTION: NW30 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
84,000 GALLON FIXED-ROOF SHIPPING TANK WITH VAPOR CONTROL SHARED WITH S-1738-289, '290, '340, & '341 - M&M LEASE

PERMIT UNIT REQUIREMENTS

1. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
4. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Vapor recovery system shall include 6" dia. piping connecting tank vapor spaces to 8" dia. gas boot, 2" dia. piping (from 6" dia. piping) serving vapor compressor switches & dry gas regulator, and connecting 3" dia. compressor intake piping. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Vapor recovery system shall include 1" dia. dry gas piping regulated by dry gas regulator & feeding to 8" dia. gas boot, one Varec dry gas regulator, and one back pressure check valve on 3" dia. compressor intake piping. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Vapor recovery system shall include two dryer explosion proof pressure switches, one activating & one de-activating vapor compressor, and one 20 hp Santa Fe Systems Co. vapor compressor. [District NSR Rule] Federally Enforceable Through Title V Permit
12. Prior to breaking the vapor-tight seal on any tank, the dry gas supply line to the system shall be closed. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Liquid condensates from gas boot shall be handled in a manner to prevent emissions to atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
14. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
15. VOC content of total organic hydrocarbons in gas shall not exceed 29% by weight. [District NSR Rule] Federally Enforceable Through Title V Permit
16. Permittee shall perform and record annual gas analysis for VOC content and make such records available for District inspection upon request. [District NSR Rule] Federally Enforceable Through Title V Permit
17. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
18. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
19. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
20. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
21. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
22. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
23. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

26. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. VOC shall be tested using EPA Method 25 or EPA Method 18 referenced as methane. [District Rules 1081 and District NSR Rule] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-354-1 **EXPIRATION DATE:** 02/28/2014

SECTION: 04 **TOWNSHIP:** 11N **RANGE:** 22W

EQUIPMENT DESCRIPTION:
126,000 GALLON (3,000 BBL) FIXED ROOF WASH TANK WITH VAPOR RECOVERY, INCLUDING: VAPOR COMPRESSORS, SEPARATORS, AND ONE EMERGENCY FLARE. V/R SYSTEM SHARED WITH TANKS S-1738-354 THROUGH '358, LOCATED IN THE YOWLUMNE TANK BATTERY

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Vapors shall vent only through gas line compressor. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All piping, valves and fittings shall be maintained in a leak-free condition as defined in Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Liquids from the knockout vessel shall be disposed of in a manner preventing VOC emissions. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Storage tank p/v caps shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Storage tank p/v caps shall be leak-free (except for inbreathing) during normal operation. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
8. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
9. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
10. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
16. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
19. Formerly permit number S-1136-47-0.
20. Formerly permit number S-1548-186-2.
21. Formerly permit number S-3898-5.

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1738-354-2 **ISSUANCE DATE:** 03/25/2010

LEGAL OWNER OR OPERATOR: VINTAGE PRODUCTION CALIFORNIA LLC
MAILING ADDRESS: 9600 MING AVE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: LIGHT OIL WESTERN STATIONARY SOURCE
WESTERN KERN COUNTY
KERN COUNTY, CA

SECTION: NE 04 **TOWNSHIP:** 11N **RANGE:** 22W

EQUIPMENT DESCRIPTION:
MODIFICATION OF 126,000 GALLON (3,000 BBL) FIXED ROOF WASH TANK WITH VAPOR RECOVERY, INCLUDING: VAPOR COMPRESSORS, SEPARATORS, AND ONE EMERGENCY FLARE. V/R SYSTEM SHARED WITH TANKS S-1738-354 THROUGH '358, LOCATED IN THE YOWLUMNE TANK BATTERY: TIE LOADING RACK S-1738-431 TO VAPOR CONTROL SYSTEM

CONDITIONS

1. This ATC shall be implemented concurrently with ATC S-1738-431-0. [District Rule 2201]
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
3. Vapors shall vent only through gas line compressor. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All piping, valves and fittings shall be maintained in a gas-tight condition as defined in Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Liquids from the knockout vessel shall be disposed of in a manner preventing VOC emissions. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Storage tank p/v caps shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
S-1738-354-2 : Jul 19 2013 9:02AM -- EDGEHILR : Joint Inspection NOT Required

7. Storage tank p/v caps shall be vapor tight (except for inbreathing) during normal operation. [District Rule 4623] Federally Enforceable Through Title V Permit

8. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit

9. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, on a portable hydrocarbon detection instrument. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit

10. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

11. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

12. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

13. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

16. Formerly permit number S-1136-47-0.

17. Formerly permit number S-1548-186-2.

18. Formerly permit number S-3898-5.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-417-1 **EXPIRATION DATE:** 02/28/2014

SECTION: SE18 **TOWNSHIP:** 28S **RANGE:** 20E

EQUIPMENT DESCRIPTION:
42,000 GALLON PETROLEUM STORAGE TANK (#5) EQUIPPED WITH VAREC VAPOR CONTROL SYSTEM INCLUDING VAPOR COMPRESSOR SHARED WITH S-1738-418, '-419, '-420 & '-421 (LAYMAN)

PERMIT UNIT REQUIREMENTS

1. Formerly S-2804-1.
2. Vapor recovery system shall be shared with permit unit S-1738-418, -419, -420, & -421. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Vapor recovery system shall be maintained in a leak-free (as defined in Rule 4623) condition and shall consist of a closed vent system that collects all VOCs from the storage tank and discharges to an open flare (permit unit S-1738-427) that reduces the inlet VOC emissions by at least 95 percent by weight as determined by the test method specified in District Rule 4623, Section 6.4.6. [District Rule 4623, 5.6.1 & District NSR Rule] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on this tank shall be equipped with a leak-free (as defined in Rule 4623) cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. All piping valves, flanges, connectors, and fittings shall be constructed and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 4623, 5.6.3 & District NSR Rule] Federally Enforceable Through Title V Permit
6. There shall be no leaks in excess of 10,000 ppmv when measured with an portable hydrocarbon detection instrument calibrated with methane in accordance with EPA Method 21. Emissions in excess of this is considered a violation of this permit. [District NSR Rule & 4623] Federally Enforceable Through Title V Permit
7. Fugitive VOC emissions rate, calculated using EPA Publication 453/R-95-017," Table 2-4 Oil and Gas Operations Average Emission Factors, from the total number of components in liquid service, tank vapor space, vapor piping to vapor recovery system manifold, and vapor recovery system shall not exceed 19.7 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

14. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1738-443-4 **EXPIRATION DATE:** 02/28/2014

SECTION: 10 **TOWNSHIP:** 29S **RANGE:** 21E

EQUIPMENT DESCRIPTION:
2000 BBL (29.7' DIA. X 16' HIGH) FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM SHARED WITH S-1738-444, '-445, '-446, AND '-447 (HOPKINS LEASE)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The vapor control system shall include vapor compressor, flare S-1738-449 and connection to sales line. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Vapors shall be collected and discharged only into pipeline for sale or to flare S-1738-449. [District NSR Rule] Federally Enforceable Through Title V Permit
4. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
8. VOC fugitive emissions from the components in gas service on tank shall not exceed 18.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Permittee shall maintain accurate component count for tank and the vapor recovery system according to EPAs "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emission Factors. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operator shall visually inspect the vapor recovery system, tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

15. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rules 2201 and 4623, Table 3] Federally Enforceable Through Title V Permit

16. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rules 4623, Table 3] Federally Enforceable Through Title V Permit

17. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit

18. This tank shall be degassed before commencing interior cleaning by following one of the following options: 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit

19. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit
21. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
22. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
23. If the tank holds an organic liquid having a TVP of 1.5 psia or greater, then, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
24. If the tank holds an organic liquid having a TVP of 1.5 psia or greater, then operator shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit
25. If the tank holds an organic liquid having a TVP of 1.5 psia or greater, then operator shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
26. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit
27. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
28. Facilities S-1216, S-382, and S-1738 constitute one stationary source. [District Rule 2201] Federally Enforceable Through Title V Permit