San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

NOV 01 2011

Larry Landis
Chevron U.S.A., Inc.
P.O. Box 1392
Bakersfield, CA 93301

Re: Notice of Preliminary Decision - Title V Permit Renewal
District Facility # S-1131
Project # S-1063775

Dear Mr. Landis:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Chevron U.S.A., Inc. for its heavy oil production operation located within the Heavy Oil Central Stationary Source of Kern County, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Sincerely,

David Warner
Director of Permit Services

DW: KR/cm

Attachments

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

www.valleyair.org www.healthyairliving.com

Printed on recycled paper.

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

NOV 0 1 2011

Gerardo C. Rios, Chief
Permits Office (AIR-3)
U.S. EPA - Region IX
75 Hawthorne St.
San Francisco, CA 94105

Re: Notice of Preliminary Decision – Title V Permit Renewal
District Facility # S-1131
Project # S-1063775

Dear Mr. Rios:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Chevron U.S.A., Inc. for its heavy oil production operation located within the Heavy Oil Central Stationary Source of Kern County, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 45-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Sincerely,

David Warner
Director of Permit Services

DW: KR/cm

Attachments

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

www.valleyair.org www.healthyairliving.com

Printed on recycled paper.

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

NOV 01 2011

Mike Tollstrup, Chief
Project Assessment Branch
Air Resources Board
P O Box 2815
Sacramento, CA 95812-2815

Re: Notice of Preliminary Decision - Title V Permit Renewal
District Facility # S-1131
Project # S-1063775

Dear Mr. Tollstrup:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Chevron U.S.A., Inc. for its heavy oil production operation located within the Heavy Oil Central Stationary Source of Kern County, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Sincerely,

David Warner
Director of Permit Services

DW: KR/cm

Attachments

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

www.valleyair.org www.healthyairliving.com

Printed on recycled paper.

Bakersfield Californian

NOTICE OF PRELIMINARY DECISION
FOR THE PROPOSED RENEWAL OF
THE FEDERALLY MANDATED OPERATING PERMIT

NOTICE IS HEREBY GIVEN that the San Joaquin Valley Air Pollution Control District solicits public comment on the proposed renewal of the Federally Mandated Operating Permit to Chevron U.S.A., Inc. for its heavy oil production operation located within the Heavy Oil Central Stationary Source of Kern County, California.

The District's analysis of the legal and factual basis for this proposed action, project #S-1063775, is available for public inspection at http://www.valleyair.org/notices/public_notices_idx.htm and the District office at the address below. There are no emission changes associated with this proposed action. This will be the public's only opportunity to comment on the specific conditions of the proposed renewal of the Federally Mandated Operating permit. If requested by the public, the District will hold a public hearing regarding issuance of this renewed permit. For additional information, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500. Written comments on the proposed renewed permit must be submitted within 30 days of the publication date of this notice to DAVID WARNER, DIRECTOR OF PERMIT SERVICES, SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT, 34946 FLYOVER COURT, BAKERSFIELD, CALIFORNIA 93308.

SAN JOAQUIN VALLEY
AIR POLLUTION CONTROL DISTRICT

Proposed Title V Permit Renewal Evaluation
Chevron USA Inc.
S-1131

TABLE OF CONTENTS

I. PROPOSAL 2
II. FACILITY LOCATION 2
III. EQUIPMENT LISTING 3
IV. GENERAL PERMIT TEMPLATE USAGE 3
V. SCOPE OF EPA AND PUBLIC REVIEW 3
VI. FEDERALLY ENFORCEABLE REQUIREMENTS 3
VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE 7
VIII. PERMIT REQUIREMENTS 7
IX. PERMIT SHIELD 111
X. PERMIT CONDITIONS 112
XI. ATTACHMENTS 112

A. DRAFT RENEWED TITLE V OPERATING PERMIT
B. PREVIOUS TITLE V OPERATING PERMIT
C. DETAILED FACILITY LIST
D. COMPLIANCE CERTIFICATION FORM

TITLE V PERMIT RENEWAL EVALUATION
Heavy Oil Central Production

Engineer: Kris Rickards
Date: October 27, 2011

Facility Number: S-1131
Facility Name: Chevron U.S.A., Inc.
Mailing Address: PO Box 1392
Bakersfield CA 93302

Reviewed by AP SUPRADE

OCT 27 2011

Contact Name: Lance Erickson
Phone: 661-654-7145

Responsible Official: William Fall
Title: Health, Environment, & Safety Manager

Project # : S-1063775
Deemed Complete: September 21, 2006

I. PROPOSAL

Chevron U.S.A., Inc. (hereafter referred to as CUSA) was issued a Title V permit on December 31, 2002. As required by District Rule 2520, the applicant is requesting a permit renewal. The existing Title V permit shall be reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the issuance of the initial Title V permit.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

II. FACILITY LOCATION

CUSA's operation is located within the Heavy Oil Central Stationary Source in Kern County.

III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as Attachment C.

IV. GENERAL PERMIT TEMPLATE USAGE

The applicant does not propose to use any model general permit templates.

V. SCOPE OF EPA AND PUBLIC REVIEW

The applicant is not requesting any model general permit templates. Therefore, all federally enforceable conditions in this current Title V permit will be subject to EPA and public review.

VI. FEDERALLY ENFORCEABLE REQUIREMENTS

A. Rules Updated

- District Rule 2020, Exemptions
  (amended August 18, 2011)
- District Rule 2201, New and Modified Stationary Source Review Rule
  (amended April 21, 2011)
- District Rule 4101, Visible Emissions
  (amended February 17, 2005)
- District Rule 4305, Boilers, Steam Generators, and Process Heaters–Phase 2
  (amended August 21, 2003)
- District Rule 4306, Boilers, Steam Generators, and Process Heaters–Phase 3
  (amended October 16, 2008)
- District Rule 4307, Boilers, Steam Generators, and Process Heaters– 2.0 MMBtu/hr to 5.0 MMBtu/hr
  (amended May 19, 2011)
- District Rule 4311, Flares
  (amended June 18, 2009)
- District Rule 4351, Boilers, Steam Generators, and Process Heaters–Phase 1
  (amended August 21, 2003)

- District Rule 4401, Steam-Enhanced Crude Oil Production Wells (amended December 14, 2006)
- District Rule 4601, Architectural Coatings (amended December 17, 2009)
- District Rule 4621, Gasoline Transfer into Stationary Storage Containers, Delivery Vessels and Bulk Plants (amended December 20, 2007)
- District Rule 4622, Gasoline Transfer into Motor Vehicle Fuel Tanks (amended December 20, 2007)
- District Rule 4623, Storage of Organic Liquids (amended May 19, 2005)
- District Rule 4701, Internal Combustion Engines – Phase 1 (amended August 21, 2003)
- District Rule 4702, Internal Combustion Engines – Phase 2 (amended August 18, 2011)
- District Rule 4703, Stationary Gas Turbines (amended September 20, 2007)
- District Rule 8011, General Requirements (amended August 19, 2004)
- District Rule 8021, Construction, Demolition, Excavation, Extraction, and Other Earthmoving Activities (amended August 19, 2004)
- District Rule 8031, Bulk Materials (amended August 19, 2004)
- District Rule 8041, Carryout and Trackout (amended August 19, 2004)
- District Rule 8051, Open Areas (amended August 19, 2004)
- District Rule 8061, Paved and Unpaved Roads (amended August 19, 2004)

- District Rule 8071, Unpaved Vehicle/Equipment Traffic Areas (amended September 16, 2004)

- 40 CFR Part 60, Subpart GG, Standards of Performance for Stationary Gas Turbines (amended February 24, 2006)

- 40 CFR Part 60, Subpart IIII, Standards of Performance for Stationary Compression Ignition Internal Combustion Engines (adopted July 11, 2006)

- 40 CFR 82, Subpart B, Stratospheric Ozone (amended June 18, 2008)

- 40 CFR 82, Subpart F, Stratospheric Ozone (amended June 18, 2008)

B. Rules No Longer Referenced on PTOs

- 40 CFR 60 Subpart Dc - Standards of Performance for Small Industrial - Commercial - Institutional Steam Generating Units

- 40 CFR 60 Subpart K - Standards of Performance for Storage Vessels for Petroleum Liquids for which Construction, Reconstruction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978

- 40 CFR 60 Subpart Ka - Standards of Performance for Storage Vessels for Petroleum Liquids for which Construction, Reconstruction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984

C. Rules Adopted

- District Rule 4320, Advanced Emission reduction Options for Boilers, Steam Generators, and Process Heaters Greater than 5.0 MMBtu/hr (adopted October 16, 2008)

- 40 CFR 60 Subpart KKKK - Standards of Performance for Stationary Combustion Turbines (adopted July 6, 2006 and amended March 20, 2009)

- 40 CFR 63, Subpart ZZZZ - National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (adopted June 15, 2004 and amended March 9, 2011)

- 40 CFR 63, Subpart DDDDD - National Emission Standards for Hazardous Air Pollutants for Industrial, Commercial, and Institutional Boilers and Process Heaters (adopted May 20, 2011)

- 40 CFR Part 64 - Compliance Assurance Monitoring (CAM) (adopted October 22, 1997)

D. Rules Not Updated

- District Rule 1080, Stack Monitoring (amended December 17, 1992)

- District Rule 1081, Source Sampling (amended December 16, 1993)

- District Rule 2010, Permits Required (amended December 17, 1992)

- District Rule 2031, Transfer of Permits (amended December 17, 1992)

- District Rule 2070, Standards for Granting Applications (amended December 17, 1992)

- District Rule 2080, Conditional Approval (amended December 17, 1992)

- District Rule 2520, Federally Mandated Operating Permits (amended June 21, 2001)

- District Rule 4201, Particulate Matter Concentration (amended December 17, 1992)

- District Rule 4301, Fuel Burning Equipment (amended December 17, 1992)

- District Rule 4402, Crude Oil Production Sumps (amended December 17, 1992)

- District Rule 4407, In-Situ Combustion Well Vents (amended May 19, 1994)

- 40 CFR 60 Subpart Kb - Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for which Construction, Reconstruction, or Modification Commenced After July 23, 1984

- 40 CFR Part 61, Subpart M, National Emissions Standard for Asbestos (amended February 12, 1999)

VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit."

For this facility, the following are not federally enforceable and will not be discussed in further detail:

District Rule 4102, Nuisance

Condition 42 of permit unit S-1131-0-2 is based on District Rule 4102 and will therefore not be discussed any further.

VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of the initial Title V permit.

A. District Rule 2020 – Exemptions

District Rule 2020 lists equipment, which is specifically exempt from obtaining permits, and specifies recordkeeping requirements to verify such exemptions. The rule was amended in December 20, 2007. The amendments to this rule do not have any affect on current permit requirements and will therefore not be addressed in this evaluation.

B. District Rule 2201 - New and Modified Stationary Source Review Rule

District Rule 2201 has been amended since this facility's initial Title V permit was issued. This Title V permit renewal does not constitute a modification per section 3.25, defined as an action including at least one of the following items:

1) Any change in hours of operation, production rate, or method of operation of an existing emissions unit, which would necessitate a change in permit conditions.
2) Any structural change or addition to an existing emissions unit which would necessitate a change in permit conditions. Routine replacement shall not be considered to be a structural change.
3) An increase in emissions from an emissions unit caused by a modification of the Stationary Source when the emissions unit is not subject to a daily emissions limitation.

4) Addition of any new emissions unit which is subject to District permitting requirements.
5) A change in a permit term or condition proposed by an applicant to obtain an exemption from an applicable requirement to which the source would otherwise be subject.

Therefore, the updated requirements of this rule are not applicable at this time; however, there were changes made to the requirements of some permit units to update permit language.

The term "gas-tight" or "gas tight" on several permits were updated to read "leak-free" since "gas-tight" has been replaced by "leak-free" in District Rule 4623 (though Rule 4623 will address this change there are several permits that use this definition out of the rule but are exempt from the rule and cite Rule 2201 instead).

C. District Rule 4101 - Visible Emissions

District Rule 4101 prohibits the discharge of any air contaminant for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker in shade as that designated as No. 1 on the Ringelmann Chart; or is of such opacity as to obscure an observer's view to a degree equal to or greater than the smoke described in Section 5.1 of Rule 4101. The rule was amended in February 17, 2005.

The following condition will ensure compliance with this rule (all redundant Rule 4101 conditions have been removed from other permits):

- No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01), by using EPA method 9. If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101]

Permit Unit(s)	Condition Number(s)
S-1131-0	23

D. District Rule 4305 - Boilers, Steam Generators, and Process Heaters – Phase 2

This rule applies to any boiler, steam generator or process heater, with a rated heat input greater than 5 million Btu per hour that is fired with gaseous and/or liquid fuels.

This rule was updated recently to incorporate allowances for increased emissions due to start-up and shutdown periods.

All units this rule applies to are also either compliant with or dormant for District Rule 4306, *Boilers, Steam Generators, and Process Heaters – Phase 3*. Since emissions limits of District Rule 4306 and all other requirements are equivalent or more stringent than District Rule 4305 requirements, compliance with District Rule 4306 requirements will satisfy requirements of District Rule 4305 (rule citations for all Rule 4305 conditions are added to permits where applicable).

E. District Rule 4306 - Boilers, Steam Generators, and Process Heaters – Phase 3

This rule applies to any boiler, steam generator or process heater, with a rated heat input greater than 5 million Btu per hour that is fired with gaseous and/or liquid fuels.

Steam generators listed in the table below are designated non-compliant dormant, as such, they will not be operated; therefore, emission limits, monitoring provisions, and testing requirements of this rule will be satisfied when the units are modified to operate in compliance with this rule. The conditions below will be listed on the permits to ensure that compliance with this rule is achieved prior to operation:

- No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010]
- The fuel supply line shall be physically disconnected from this unit. [District Rule 4306].
- This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306]

Permit Unit(s)	Condition Number(s)
S-1131-65, '-77, '-94, '-858, '-941, '-943, '-966, '-976, '-992, '-993, '-994, '-998, '-1000, '-1001, '-1002, '-1003, '-1004, and '-1016	1-3

The following units are compliant with Rule 4306 and with Rule 4320, *Advanced Emission reduction Options for Boilers, Steam Generators, and Process Heaters Greater than 5.0 MMBtu/hr.* Since emissions limits of District Rule 4320 and all other requirements are equivalent or more stringent than District Rule 4306 requirements, compliance with District Rule 4320 requirements will satisfy requirements of District Rule 4306 (rule citations for all Rule 4306 conditions are added to permits where applicable).

Permit Unit(s)
S-1131-62, '-63, '-64, '-66, '-67, '-68, '-69, '-70, '-73, and '-912

Rule 4306 applies to the remaining steam generators, which have also received ATCs to comply with District Rule 4320 (no streamlining or reordering of conditions has been performed for these ATCs as Chevron will implement the Rule 4320 compliant ATCs shortly after this renewal is completed), that will be implemented according to the compliance schedule listed in that rule. Currently Rule 4306 is the most stringent rule that is applicable to these units and will be evaluated as follows.

Section 5.1 requires that except for units subject to Sections 5.2, NOx and carbon monoxide (CO) emissions shall not exceed the limits specified in the following table. All ppmv emission limits specified in this section are referenced at dry stack gas conditions and 3.00 percent by volume stack gas oxygen. Emission concentrations shall be corrected to 3.00 percent oxygen in accordance with Section 8.1.

With a maximum heat input of 62.5 MMBtu/hr for the oilfield steam generators, the applicable emission limit category is listed in Section 5.1.1, Table 1, Category C, from District Rule 4306.

Rule 4306 Emissions Limits				
Category	**Operated on gaseous fuel**		**Operated on liquid fuel**	
	NO_X Limit	**CO Limit**	**NO_X Limit**	**CO Limit**
C. Oilfield Steam Generators	15 ppmv or 0.018 lb/MMBtu	400 ppmv	40 ppmv or 0.052 lb/MMBtu	400 ppmv

For these units:

- the proposed NO_x emission factor is 15 ppmvd @ 3% O_2 (0.0182 lb/MMBtu), and
- the proposed CO emission factors are between 27 ppmvd @ 3% O_2 (0.02 lb/MMBtu) and 51.4 ppmvd @ 3% O_2 (0.038 lb/MMBtu).

Therefore, compliance with Section 5.1 of District Rule 4306 is expected. The following condition will ensure compliance with this section:

- Except during start-up and shutdown, emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 (or 0.0182 lb-NOx/MMBtu), or XX ppmvd CO @ 3% O2 (or X.XXX lb-CO/MMBtu). [District Rules 2201; 4305, 5.1; and 4306, 5.1]

Permit Unit(s)	Condition Number(s)
S-1131-78, '-859, and '-908	7
S-1131-82, '-95, and '-881	8
S-1131-99	9
S-1131-877	13
S-1131-879, '-883, and '-884	6
S-1131-880	12
S-1131-987 and '-997	5
S-1131-999	4

Section 5.2 applies to units with an annual fuel use less than 9 billion Btu heat input per calendar year. No units are limited this way; therefore, this section is not applicable.

Section 5.3 requires that on and after the full compliance schedule specified in Section 7.1, the applicable emission limits of Sections 5.1, 5.2.2 and 5.2.3 shall not apply during start-up or shutdown provided an operator complies with the requirements specified below.

1) The duration of each start-up or each shutdown shall not exceed two hours, except as provided in Section 5.3.3.
2) The emission control system shall be in operation and emissions shall be minimized insofar as technologically feasible during start-up or shutdown.
3) Notwithstanding the requirement of Section 5.3.1, an operator may submit an application for a Permit to Operate condition to allow more than two hours for each start-up or each shutdown provided the operator meets all of the conditions in specified in Sections 5.3.3.1 through 5.3.3.3.

The following conditions will be listed on the permits to ensure compliance:

- Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3]

- Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25]

Permit Unit(s)	Condition Number(s)
S-1131-78, '-82, and '-881	10 and 11
S-1131-95 and '-99	11 and 12
S-1131-859 and '-908	9 and 10
S-1131-877	14 and 15
S-1131-879, '-883, and '-884	8 and 9
S-1131-880	13 and 14
S-1131-987 and '-997	7 and 8
S-1131-999	6 and 7

Section 5.4.1 applies to units that simultaneously fire on gaseous and liquid fuels. These units are fired exclusively on gaseous fuel; therefore this section is not applicable.

Section 5.4.2 requires that permit units subject to District Rule 4306, Section 5.1 emissions limits shall either install and maintain Continuous Emission Monitoring (CEM) equipment for NO_X, CO and O_2, or install and maintain APCO-approved alternate monitoring.

In order to satisfy the requirements of District Rule 4306, Chevron periodically monitors NO_X, CO, and O_2 exhaust emissions concentrations, using a portable analyzer. The following conditions are listed on the permits to ensure compliance with this section:

- The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4]

- If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4]

- All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4]

Permit Unit(s)	Condition Number(s)
S-1131-78, '-877, and '-880	1-3
S-1131-82 and '-881	20-22
S-1131-95	19-21
S-1131-99	14-16
S-1131-859	12-14
S-1131-879 and '-997	17-19
S-1131-883, '-884, and '-908	18-20
S-1131-987 and '-999	16-18

Since the units are not subject to the requirements listed in Section 5.2.1 or 5.2.2, they are not subject to **Section 5.4.3** requirements.

Since the units are not subject to the requirements of category H (maximum annual heat input between 9 billion and 30 billion Btu/year) listed in Section 5.1.1, they are not subject to **Section 5.4.4** requirements.

Section 5.5.1 requires that the operator of any unit shall have the option of complying with either the applicable heat input (lb/MMBtu) emission limits or the concentration (ppmv) emission limits specified in Section 5.1. The emission limits selected to demonstrate compliance shall be specified in the source test proposal pursuant to Rule 1081 (Source Sampling).

Therefore, the following condition will be listed on the permits to ensure compliance:

- The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1; and 4306, 5.5.1]

Permit Unit(s)	Condition Number(s)
S-1131-78 and '-99	19
S-1131-82	24
S-1131-95 and '-908	23
S-1131-859	17
S-1131-877	16
S-1131-879	21
S-1131-880	15
S-1131-881	25
S-1131-883, '-884, and '-997	22
S-1131-987 and '-999	20

Section 5.5.2 requires that all emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0.

Therefore, the following permit condition will be listed on as follows:

- All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5]

Permit Unit(s)	Condition Number(s)
S-1131-78	20
S-1131-82	25
S-1131-95	24
S-1131-99, '-883, '-884, and '-997	23
S-1131-859, '-987, and '-999	21
S-1131-877 and '-880	17
S-1131-879	22
S-1131-881	26
S-1131-908	27

Section 5.5.3 applies to units equipped with CEMS. None of these units are equipped with CEMS; therefore, this section is not applicable.

Section 5.5.4 requires that for emissions monitoring pursuant to Sections 5.4.2, 5.4.2.1, and 6.3.1 using a portable NO_X analyzer as part of an APCO approved Alternate Emissions Monitoring System, emission readings shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15-consecutive-minute sample reading or by taking at least five (5) readings evenly spaced out over the 15-consecutive-minute period.

The following condition will be listed on the permits to ensure compliance:

- All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4]

Permit Unit(s)	Condition Number(s)
S-1131-78, '-877, and '-880	3
S-1131-82 and '-881	22
S-1131-95	21
S-1131-99	16
S-1131-859	14
S-1131-879 and '-997	19
S-1131-883, '-884, and '-908	20
S-1131-987 and '-999	18

Section 5.5.5 requires that for emissions source testing performed pursuant to Section 6.3.1 for the purpose of determining compliance with an applicable standard or numerical limitation of this rule, the arithmetic average of three (3) 30-consecutive-minute test runs shall apply. If two (2) of three (3) runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit.

This requirement is identical to that described in Rule 1081, Section 6.1. The following condition is listed on the facility-wide permit and will ensure compliance with this section:

- All required source testing shall conform to the compliance testing procedures described in District Rule 1081. [District Rule 1081]

Permit Unit(s)	Condition Number(s)
S-1131-0	3

Section 6.1 requires that the records required by Sections 6.1.1 through 6.1.3 shall be maintained for five calendar years and shall be made available to the APCO upon request. Failure to maintain records or information contained in the records that demonstrate noncompliance with the applicable requirements of this rule shall constitute a violation of this rule.

The following condition will be listed on the permits to ensure compliance:

- All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; 4305, 6.1; and 4306, 6.1]

Permit Unit(s)	Condition Number(s)
S-1131-78	40
S-1131-82, '-859, '-883, and '-884	36
S-1131-95	35
S-1131-99, '-877, and '-880	38
S-1131-879	33
S-1131-881	39
S-1131-908	37
S-1131-987	31
S-1131-997	34
S-1131-999	32

Section 6.1.2 requires that the operator of a unit subject to Section 5.2 shall record the amount of fuel use at least on a monthly basis. Since these units are not subject to the requirements listed in Section 5.2, this section is not applicable.

Section 6.1.3 requires that the operator of a unit subject to Section 5.2.1 or 6.3.1 shall maintain records to verify that the required tune-up and the required monitoring of the operational characteristics have been performed. The units are not subject to Sections 5.2.1 or 6.3.1; therefore, the requirements of this section do not apply.

Section 6.2 identifies the following test methods as District-approved source testing methods for the pollutants listed:

Pollutant	Units	Test Method Required
Fuel HHV	Btu/scf	ASTM D 1826 or D 1945 in conjunction with D 3588
NO_X	ppmv	EPA Method 7E or ARB Method 100
NO_X	lb/MMBtu	EPA Method 19
CO	ppmv	EPA Method 10 or ARB Method 100
Stack Gas O_2	%	EPA Method 3 or 3A, or ARB Method 100
Stack Gas Velocities	ft/min	EPA Method 2
Stack Gas Moisture Content	%	EPA Method 4

Chevron has requested additional test methods as allowed by District Policy APR-1710 for testing of SO_X (EPA method 19), fuel gas sulfur content (ASTM D1072, D3246, D4084 or grab sample analysis by double GC), and PM (EPA Methods 5 – both filterable and condensable[1], 201A and 202, or CARB Method 5).

The following permit condition will ensure compliance with this section:

- The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content – EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensable), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-78, '-95, '-877, and '-880	22
S-1131-82 and '-881	23
S-1131-99, '-883, and '-884	21
S-1131-859, '-987, and '-999	19
S-1131-879 and '-997	20
S-1131-908	25

[1] District policy, APR-1715, requires both filterable and condensable PM to be considers and clarifies that EPA also requires this.

Section 6.3.1 requires that this unit be tested to determine compliance with the applicable requirements of section 5.1 and 5.2.3 not less than once every 12 months. Upon demonstrating compliance on two consecutive compliance source tests, the following source test may be deferred for up to thirty-six months.

The following permit condition will ensure compliance with this section:

- Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3, 4306, 6.3, and 4351, 6.3.1]

Permit Unit(s)	Condition Number(s)
S-1131-78	16
S-1131-82, '-95, and '-881	13
S-1131-99	17
S-1131-859	15
S-1131-877 and '-880	18
S-1131-879, '-883, and '-884	11
S-1131-908	21
S-1131-987 and '-997	10
S-1131-999	9

In addition, since the applicant has proposed to use pre-approved Alternate Monitoring Scheme "A" using a portable analyzer, the tune-up requirements listed in Section 6.3.1 are not applicable to the steam generator. Section 6.3.1 also requires that, during the 36-month source testing interval, the owner/operator shall monthly monitor the operational characteristics recommended by the unit manufacturer. Since the pre-approved Alternate Monitoring Scheme "A" using a portable analyzer requires monthly monitoring of NO_X, CO, and O_2 exhaust emissions concentrations, operational characteristics monitoring requirement is satisfied, and no further discussion is required.

Section 6.3.2 allows that in lieu of compliance with Section 6.3.1, compliance with the applicable emission limits in Sections 5.1 or 5.2.3 shall be demonstrated by submittal of annual emissions test results to the District from a unit or units that represents a group of units, provided:

1) All units in the group are initially source tested. The emissions from all test runs from units within the group are less than 90% of the permitted value, and the emissions do not vary greater than 25% from the average of all test runs; and
2) All units in a group are similar in terms of rated heat input, make and series, operational conditions, fuel used, and control method. No unit with a rated heat input greater than 100 MMBtu shall be considered as part of the group; and
3) The group is owned by a single owner and is located at a single stationary source; and
4) Selection of the representative unit(s) is approved by the APCO prior to testing; and
5) The number of representative units source tested shall be at least 30% of the total number of units in the group. The representative tests shall rotate each year so that within three years all units in the group have been tested at least once.
6) All units in the group shall have received the similar maintenance and tune-up procedures as the representative unit(s) as listed in the Permit to Operate. The operator shall submit to the APCO the specific maintenance procedures to be performed on each unit that will be included in the group for representative testing. Such maintenance procedures shall be specified in the Permit to Operate for units that are included in the group for representative testing. Any maintenance work on a unit which has no effect on emissions standards and which is not specified in the maintenance procedures shall be submitted to the APCO for approval before such unit can be included as part of the group for representative testing. Any unit that necessitates any maintenance work which has an effect on emission standards and is beyond the maintenance procedures identified in the Permit to Operate, shall not be included as part of the group for representative testing. The unit shall be source tested in accordance with the provisions of Section 6.3.1; and
7) Should any of the representative units exceed the required emission limits, each of the units in the group shall demonstrate compliance by emissions testing. Failure to complete emissions testing within 90 days of the failed test shall result in the untested units being in violation of this rule. After compliance with the requirements of Section 6.3.2.7 has been demonstrated, subsequent source testing shall be performed pursuant to Sections 6.3.1 or 6.3.2.

The following permit conditions will ensure compliance with this section:

- Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative un(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 4305, 6.3.2.4; 4306, 6.3.2.4 ; and 4351, 6.3]

- The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 4305, 6.3.2.1 and 4306, 6.3.2.1]

- All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 4305, 6.3.2.6 and 4306, 6.3.2.6]

- All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 4305, 6.3.2.2 and 4306, 6.3.2.2]

- The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 4305, 6.3.2.5 and 4306, 6.3.2.5]

Permit Unit(s)	Condition Number(s)
S-1131-78	35-39
S-1131-82	28-32
S-1131-95	27-31
S-1131-99, '-987, and '-999	24-28
S-1131-859	22-26
S-1131-877 and '-880	33-37
S-1131-879	25-29
S-1131-881 and '-908	29-33
S-1131-883, '-884, and '-997	26-30

Section 6.4, Emission Control Plan (ECP)

Section 6.4.1 requires that the operator of any unit shall submit to the APCO for approval an Emissions Control Plan according to the compliance schedule in Section 7.0 of District Rule 4306. Chevron has already submitted an ECP for these units. Therefore compliance with this section is expected.

F. District Rule 4307 - Boilers, Steam Generators, and Process Heaters – 2.0 MMBtu/hr to 5.0 MMBtu/hr

This rule limits NOx, CO, SO2 and PM10 emissions from boilers, steam generators and process heaters with heat rating of 2.0 MMBtu/hr up to and including 5.0 MMBtu/hr that are fired with gaseous and/or liquid fuels.
Since the emissions unit listed on permit S-1131-1019 is designated non-compliant dormant, it will not be operated and emission limits, monitoring provisions, and testing requirements of this rule will be satisfied when the unit is modified to operate in compliance with this rule. The conditions below will be listed on the permit to ensure that compliance with this rule is achieved prior to operation:

- No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010]
- The fuel supply line shall be physically disconnected from this unit. [District Rule 4307].
- This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4307 and all other applicable District regulations. [District Rule 4307]

Permit Unit(s)	Condition Number(s)
S-1131-1019	1-3

G. District Rule 4311 – Flares

Rule 4311 limits the emissions of volatile organic compounds (VOCs) and oxides of nitrogen (NOx), and sulfur from the operation of flares.

Section 5.1 states flares permitted to operate only during an emergency are not subject to the requirements of Section 5.6 and 5.7.

No flares in this project are designated emergency flares; therefore this section is not applicable.

Section 5.2 requires that the flame be present at all times when combustible gases are vented through the flare. The following condition will be listed on the ATCs to ensure compliance:

- A flame shall be present at all times when combustible gases are vented through the flare. [District Rule 4311, 5.2]

Permit Unit(s)	Condition Number(s)
S-1131-1085	3
S-1131-1086 and '-1087	5
S-1131-1108	6

Section 5.3 requires that the flare outlet be equipped with an automatic ignition system, or operate with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares. The following condition will be listed on the ATCs to ensure compliance:

- Flare shall be equipped with a natural gas or propane fired pilot and an automatic re-ignition system. [District Rules 2201; and 4311, 5.3]

Permit Unit(s)	Condition Number(s)
S-1131-1085	4
S-1131-1086 and '-1087	6

- Flare shall be equipped with a natural gas-fired pilot and an automatic re-ignition system. [District Rules 2201; and 4311, 5.3]

Permit Unit(s)	Condition Number(s)
S-1131-1108	7

Section 5.4 requires that except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an alternative equivalent device, capable of continuously detecting at least one pilot flame or the flare flame is present shall be installed and operated. The following condition will be listed on the ATCs to ensure compliance:

- Flare shall be equipped with a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an equivalent device capable of continuously detecting at least one pilot flame or the flare flame is present. The flame detection device shall be kept operational at all times except during flare maintenance when the flare is isolated from gas flow. During essential planned power outages when the flare is operating, the pilot monitor is allowed to be non-functional if the flare flame is clearly visible to onsite operators. Effective on and after July 1, 2012, all pilot monitor downtime shall be reported annually pursuant to Rule 4311, section 6.2.3.6. [District Rule 4311, 5.4]

Permit Unit(s)	Condition Number(s)
S-1131-1085	5
S-1131-1086 and '-1087	7
S-1131-1108	8

Section 5.5 requires flares that use flow-sensitive automatic ignition systems and which do not use a continuous pilot flame to use purge gas for purging. The following condition will be listed on the ATCs to ensure compliance:

- If the flare uses a flow-sensing automatic ignition system and does not use a continuous flame pilot, the flare shall use purge gas for purging. [District Rule 4311, 5.5]

Permit Unit(s)	Condition Number(s)
S-1131-1085	11
S-1131-1086 and '-1087	12
S-1131-1108	13

Section 5.6 states that open flares (air-assisted, steam-assisted, or non-assisted) in which the flare gas pressure is less than 5 psig shall be operated in such a manner that meets the provisions of 40 CFR 60.18. The requirements of this section shall not apply to Coanda effect flares. Since no flares at this stationary source are Coanda effect flares, this section applies to all flares.

The following condition will ensure compliance with this section:

- Open flares in which the flare gas pressure is less than 5 psig shall be operated in such a manner that meets the provisions of 40 CFR 60.18. [District Rule 4311, 5.6]

Permit Unit(s)	Condition Number(s)
S-1131-1085	12
S-1131-1086 and '-1087	13
S-1131-1108	14

Section 5.7 states that ground-level enclosed flares meet the defined emission standards. The flares involved with this project are not ground-level enclosed flares; therefore, this section does not apply.

Section 5.8 states that flaring is prohibited unless it is consistent with an approved flare minimization plan (FMP), pursuant to Section 6.5, and all commitments listed in that plan have been met. Subsection 6.5.1 requires the operator of a petroleum refinery flare or any flare that has a flaring capacity of greater than or equal to 5.0 MMBtu per hour to submit a flare minimization plan (FMP) to the APCO for approval.

The operator has submitted a flare minimization plan that has been approved by the APCO.

Section 5.9 applies to petroleum refinery SO_2 performance targets. These flares do not serve a petroleum refinery; therefore this section is not applicable to the flares at this stationary source.

Section 5.10 requires the operator of a flare subject to flare minimization requirements pursuant to Section 5.8 to monitor the vent gas flow to the flare with a flow measuring device or other parameters as specified in the Permit to Operate.

- Thermally Enhanced Oil Recovery (TEOR)/ vapor control gas, natural gas, pilot gas, and purge gas lines to flare shall be equipped with volumetric flow rate indicator. [District Rules 2201; and 4311, 5.10, 6.7]

Permit Unit(s)	Condition Number(s)
S-1131-1085	2
S-1131-1086 and '-1087	4
S-1131-1108	3

Section 5.11 requires the operator of a petroleum refinery or a flare with a flaring capacity equal to or greater than 50 MMBtu/hr to monitor the flare pursuant to Sections 6.6, 6.7, 6.8, 6.9, and 6.10.

- **Section 6.6** requires operators to monitor vent gas composition using one of the methods listed in 6.6.1 through 6.6.5.
- **Section 6.7** requires operators to monitor the volumetric flows of purge and pilot gases with flow measuring devices or other parameters as specified on the Permit to Operate so that volumetric flows of pilot and purge gas may be calculated based on pilot design and the parameters monitored.
- **Section 6.8** requires that operators of any flare with a water seal to monitor and record the water level and pressure of the water seal that services each flare daily or as specified on the Permit to Operate. This stationary source does not operate any flares with a water seal; therefore this section is not applicable.
- **Section 6.9** requires that an operator comply with sections 6.9.1 through 6.9.4 as applicable.
- **Section 6.10** requires refinery flares be monitored by video. Since this stationary source does not engage in refining operations, this section is not applicable.

The following conditions will be listed on the permits to ensure compliance:

- Operator shall monitor vent gas composition using one of the five following methods: 1) Sampling vent gas pursuant to Rule 4311 Section 6.6.1, 2) Integrated sampling pursuant to Rule 4311 Section 6.6.2, 3) Operate continuous analyzers that meet the requirements of Rule 4311 Section 6.6.3, 4) Operate continuous analyzers employing gas chromatography pursuant to Rule 4311 Section 6.6.4, or 5) Monitor sulfur content using a colorimetric tube system, and monitor vent gas hydrocarbons pursuant to Rule 4311 Section 6.6.5. [District Rule 4311, 5.11, 6.6]

- If flares share a common header, a sample from the header will be deemed representative of vent gas composition for all flares served by the header. The operator shall provide the APCO with access to the monitoring system to collect vent gas samples to verify the analysis required by Rule 4311 Section 5.11. [District Rule 4311, 5.11, 6.6]

- Operator shall monitor the volumetric flows of purge and pilot gases. [District Rule 4311, 5.11, 6.7]

- Operator shall report periods of monitor inoperation greater than 24 continuous hours by the following working day, followed by notification of resumption of monitoring. Periods of inoperation of monitoring equipment shall not exceed 14 days per any 18-consecutive-month period. Periods of flare monitoring system inoperation do not include the periods when the system feeding the flare is not operating. [District Rule 4311, 5.11, 6.9]

- During periods of inoperation of continuous analyzers or auto-samplers installed pursuant to Section 6.6, operators responsible for monitoring shall take one sample within 30 minutes of the commencement of flaring, from the flare header or from an alternate location at which samples are representative of vent gas composition and have samples analyzed pursuant to Rule 4311 Section 6.3.4. During periods of inoperation of flow monitors, flow shall be calculated using good engineering practices. [District Rule 4311, 5.11, 6.9]

- Operator shall maintain and calibrate all required monitors and recording devices in accordance with the applicable manufacturer's specifications. In order to claim that a manufacturer's specification is not applicable, the person responsible for emissions must have, and follow, a written maintenance policy that was developed for the device. The written policy must explain and justify the difference between the written procedure and the manufacturer's procedure. [District Rule 4311, 5.11, 6.9]

- All in-line continuous analyzer and flow monitoring data must be continuously recorded by an electronic data acquisition system capable of one-minute averages. Flow monitoring data shall be recorded as one-minute averages. [District Rule 4311, 5.11, 6.9]

Permit Unit(s)	Condition Number(s)
S-1131-1085	13-19
S-1131-1086 and '-1087	14-20
S-1131-1108	15-21

Section 6.1 requires the following records to be retained on-site for a minimum of five years:

- Copy of the compliance determination conducted pursuant to Section 6.4.1
- Copy of the source testing result conducted pursuant to Section 6.4.2
- For flares used during an emergency, record of the duration of flare operation, amount of gas burned, and the nature of the emergency situation
- Operators claiming an exemption pursuant to Section 4.3 shall record annual throughput, material usage, or other information necessary to demonstrate an exemption under that section
- Effective on and after July 1, 2011, a copy of the approved flare minimization plan pursuant to Section 6.5
- Effective on and after July 1, 2011, where applicable, monitoring data collected pursuant to Sections 5.10, 6.6, 6.7, 6.8, 6.9, and 6.10

The following condition will ensure compliance with this section:

- All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4311, 6.1]

Permit Unit(s)	Condition Number(s)
S-1131-1085	28
S-1131-1086	30
S-1131-1087	31
S-1131-1108	35

Section 6.2.1 requires the operator to notify the District of an unplanned flaring event within 24 hours after the start of the next business day or within 24 hours of their discovery, whichever occurs first. The notification shall include the flare source identification, the start date and time, and the end date and time.

The following condition will ensure compliance with this section:

- The operator shall notify the District of an unplanned flaring event within 24 hours after the start of the next business day or within 24 hours of their discovery, whichever occurs first. The notification shall include the flare source identification, the start date and time, and the end date and time. [District Rule 4311, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-1085	21
S-1131-1086 and '-1087	23
S-1131-1108	28

Section 6.2.2, effective on and after July 1, 2012, and annually thereafter, requires the operator of a flare subject to flare minimization plans pursuant to Section 5.8 to submit an annual report to the District that summarizes all Reportable Flaring Events as defined in Section 3.0 that occurred during the previous 12 month period. The report shall be submitted within 30 days following the end of the twelve month period of the previous year. The report shall include, but is not limited to all of the following:

- The results of an investigation to determine the primary cause and contributing factors of the flaring event;
- Any prevention measures considered or implemented to prevent recurrence together with a justification for rejecting any measures that were considered but not implemented;
- If appropriate, an explanation of why the flaring was an emergency and necessary to prevent accident, hazard or release of vent gas to the atmosphere, or where, due to a regulatory mandate to vent a flare, it cannot be recovered, treated and used as a fuel gas at the facility; and
- The date, time, and duration of the flaring event.

The following condition will ensure compliance with this section:

- Effective on and after July 1, 2012, and annually thereafter, an operator shall submit a report to the District within 30 days following the end of each 12-month period that summarizes all reportable flaring events during the previous 12-month period. The report shall include the following: 1) The results of an investigation to determine the primary cause and contributing factors of the flaring event; 2) Any prevention measures considered or implemented to prevent recurrence together with a justification for rejecting any measures that were considered but not implemented; 3) If appropriate, an explanation of why the flaring was an emergency and necessary to prevent accident, hazard or release of vent gas to the atmosphere, or where, due to a regulatory mandate to vent a flare, it cannot be recovered, treated and used as a fuel gas at the facility; and 4) The date, time, and duration of the flaring event. [District Rule 4311, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-1085	22
S-1131-1086	24
S-1131-1087	25
S-1131-1108	29

Section 6.2.3 effective on and after July 1, 2012, and annually thereafter, the operator of a flare subject to flare monitoring requirements pursuant to Sections 5.10, 6.6, 6.7, 6.8, 6.9, and 6.10, as appropriate, shall submit an annual report to the APCO within 30 days following the end of each 12 month period.

The report shall include the following:

- The total volumetric flow of vent gas in standard cubic feet for each day.
- Hydrogen sulfide content, methane content, and hydrocarbon content of vent gas composition pursuant to Section 6.6.
- If vent gas composition is monitored by a continuous analyzer or analyzers pursuant to Section 5.11, average total hydrocarbon content by volume, average methane content by volume, and depending upon the analytical method used pursuant to Section 6.3.4, total reduced sulfur content by volume or hydrogen sulfide content by volume of vent gas flared for each hour of the month.
- If the flow monitor used pursuant to Section 5.10 measures molecular weight, the average molecular weight for each hour of each month.
- For any pilot and purge gas used, the type of gas used, the volumetric flow for each day and for each month, and the means used to determine flow.
- Flare monitoring system downtime periods, including dates and times.
- For each day and for each month provide calculated sulfur dioxide emissions.
- A flow verification report for each flare subject to this rule. The flow verification report shall include flow verification testing pursuant to Section 6.3.5.

The following condition will ensure compliance with this section:

- Effective on and after July 1, 2012, and annually thereafter, an operator shall submit a report to the District within 30 days following the end of each 12-month period that includes the following: 1) The total volumetric flow of vent gas in standard cubic feet for each day; 2) Hydrogen sulfide content, methane content, and hydrocarbon content of vent gas composition pursuant to Section 6.6; 3) If vent gas composition is monitored by a continuous analyzer or analyzers pursuant to Section 5.11, average total hydrocarbon content by volume, average methane content by volume, and depending upon the analytical method used pursuant to Section 6.3.4, total reduced sulfur content by volume or hydrogen sulfide content by volume of vent gas flared for each hour of the month; 4) If the flow monitor used pursuant to Section 5.10 measures molecular weight, the average molecular weight for each hour of each month; 5) For any pilot and purge gas used, the type of gas used, the volumetric flow for each day and for each month, and the means used to determine flow; 6) Flare monitoring system downtime periods, including dates and times; 7) For each day and for each month provide calculated sulfur dioxide emissions; and 8) A flow verification report for each flare subject to this rule. The flow verification report shall include flow verification testing pursuant to Section 6.3.5. [District Rule 4311, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-1085	23
S-1131-1086	25
S-1131-1087	26
S-1131-1108	30

Section 6.3 lists test methods an operator can use to demonstrate compliance with this rule. Compliance with this section is expected.

Section 6.4 requires records of compliance with 5.6 to be provided to the District upon request and lists further requirement for enclosed flares, which Chevron does not operate at this stationary source. Compliance with this section is expected.

Section 6.5 requires operators of flares >5.0 MMBtu/hr to submit a flare minimization plan (FMP) by July 1, 2010. Chevron has submitted a FMP; therefore compliance with this section has been made.

Section 6.6 requires the operator to monitor vent gas composition using one of the following five methods as appropriate:

- Sampling that meets the following requirements:
  - If the flow rate of vent gas flared in any consecutive 15-minute period continuously exceeds 330 standard cubic feet per minute (SCFM), a sample shall be taken within 15 minutes. The sampling frequency thereafter shall be one sample every three hours and shall continue until the flow rate of vent gas flared in any consecutive 15-minute period is continuously 330 SCFM or less. In no case shall a sample be required more frequently than once every 3 hours.
  - Samples shall be analyzed pursuant to Section 6.3.4.
- Integrated sampling that meets the following requirements:
  - If the flow rate of vent gas flared in any consecutive 15 minute period continuously exceeds 330 SCFM, integrated sampling shall begin within 15 minutes and shall continue until the flow rate of vent gas flared in any consecutive 15 minute period is continuously 330 SCFM or less.
  - Integrated sampling shall consist of a minimum of one aliquot for each 15-minute period until the sample container is full. If sampling is still required pursuant to Section 6.6.2.1, a new sample container shall be placed in service within one hour after the previous sample was filled. A sample container shall not be used for a sampling period that exceeds 24 hours.
  - Samples shall be analyzed pursuant to Section 6.3.4.
- Continuous analyzers that meet the following requirements:
  - The analyzers shall continuously monitor for total hydrocarbon methane, and depending upon the analytical method used pursuant to Section 6.3.4, hydrogen sulfide or total reduced sulfur.
  - The hydrocarbon analyzer shall have a full-scale range of 100% total hydrocarbon.
  - Each analyzer shall be maintained to be accurate to within 20% when compared to any field accuracy tests or to within 5% of full scale.

- Continuous analyzers employing gas chromatography that meet the following requirements:
  - The gas chromatography system shall monitor for total hydrocarbon, methane, and hydrogen sulfide.
  - The gas chromatography system shall be maintained to be accurate within 5% of full scale.
- Monitor sulfur content using a colorimetric tube system on a daily basis, and monitor vent gas hydrocarbon on a weekly basis by collecting samples and having them tested pursuant to a method in Section 6.3.4.

Additionally, if flares share a common header, a sample from the header will be deemed representative of vent gas composition for all flares served by the header.

The following condition will ensure compliance with this section:

- Vent gas composition shall be monitored using one of the methods outlined in Rule 4311, Section 6.6.1 through 6.6.5. If flares share a common header, a sample from the header will be deemed representative of vent gas composition for all flares served by the header. [District Rule 4311, 6.6]

Permit Unit(s)	Condition Number(s)
S-1131-1085	24
S-1131-1086	26
S-1131-1087	27
S-1131-1108	31

Section 6.7 requires the operator to monitor the volumetric flows of purge and pilot gases with flow measuring devices. The following condition will ensure compliance with this section:

- Thermally Enhanced Oil Recovery (TEOR)/vapor control gas, natural gas, pilot gas, and purge gas lines to flare shall be equipped with volumetric flow rate indicator. [District Rules 2201; and 4311, 5.10, 6.7]

Permit Unit(s)	Condition Number(s)
S-1131-1085	2
S-1131-1086 and '-1087	4
S-1131-1108	3

Section 6.8 requires operators of flares with water seals to monitor water level and pressure. This stationary source does not operate any flares with a water seal; therefore this section is not applicable.

Section 6.9 requires operators of flares to comply with the following as applicable:

- Periods of flare monitoring system inoperation greater than 24 continuous hours shall be reported by the following working day, followed by notification of resumption of monitoring. Periods of inoperation of monitoring equipment shall not exceed 14 days per any 18-consecutive-month period. Periods of flare monitoring system inoperation do not include the periods when the system feeding the flare is not operating.
- During periods of inoperation of continuous analyzers or auto-samplers installed pursuant to Section 6.6, operators responsible for monitoring shall take one sample within 30 minutes of the commencement of flaring, from the flare header or from an alternate location at which samples are representative of vent gas composition and have samples analyzed pursuant to Section 6.3.4. During periods of inoperation of flow monitors required by Section 5.10, flow shall be calculated using good engineering practices.
- Maintain and calibrate all required monitors and recording devices in accordance with the applicable manufacturer's specifications. In order to claim that a manufacturer's specification is not applicable, the person responsible for emissions must have, and follow, a written maintenance policy that was developed for the device in question. The written policy must explain and justify the difference between the written procedure and the manufacturer's procedure.
- All in-line continuous analyzer and flow monitoring data must be continuously recorded by an electronic data acquisition system capable of one-minute averages. Flow monitoring data shall be recorded as one-minute averages.

The following conditions will ensure compliance with this section:

- Periods of flare monitoring system inoperation greater than 24 continuous hours shall be reported by the following working day, followed by notification of resumption of monitoring. Periods of inoperation of monitoring equipment shall not exceed 14 days per any 18-consecutive-month period. Periods of flare monitoring system inoperation do not include the periods when the system feeding the flare is not operating. [District Rule 4311, 6.9]

- During periods of inoperation of continuous analyzers or auto-samplers installed pursuant to Section 6.6, operators responsible for monitoring shall take one sample within 30 minutes of the commencement of flaring, from the flare header or from an alternate location at which samples are representative of vent gas composition and have samples analyzed pursuant to Section 6.3.4. During periods of inoperation of flow monitors required by Section 5.10, flow shall be calculated using good engineering practices. [District Rule 4311, 6.9]

- Operator shall maintain and calibrate all required monitors and recording devices in accordance with the applicable manufacturer's specifications. In order to claim that a manufacturer's specification is not applicable, the person responsible for emissions must have, and follow, a written maintenance policy that was developed for the device in question. The written policy must explain and justify the difference between the written procedure and the manufacturer's procedure. [District Rule 4311, 6.9]

- All in-line continuous analyzer and flow monitoring data must be continuously recorded by an electronic data acquisition system capable of one-minute averages. Flow monitoring data shall be recorded as one-minute averages. [District Rule 4311, 5.11, 6.9]

Permit Unit(s)	Condition Number(s)
S-1131-1085	25-27
S-1131-1086	27-29
S-1131-1087	28-30
S-1131-1108	32-34

Section 6.10 applies to operators of petroleum refinery flares. This stationary source does not refine petroleum products; therefore this section is not applicable.

H. District Rule 4320 – Advanced Emission reduction Options for Boilers, Steam Generators, and Process Heaters Greater than 5.0 MMBtu/hr

This rule limits NO_X, CO, SO_2 and PM_{10} emissions from boilers, steam generators and process heaters rated greater than 5 MMBtu/hr. This rule also provides a compliance option of payment of fees in proportion to the actual amount of NOx emitted over the previous year.

All steam generators at this facility are rated greater than 5 MMBtu/hr heat input. Therefore this rule applies to all steam generators that are not non-compliant dormant or those discussed under Rule 4306 (units that have Rule 4320 compliant ATCs issued and are awaiting conversion to PTO).

Section 5.1 states that an operator of a unit(s) subject to this rule shall comply with all applicable requirements of the rule and one of the following, on a unit-by-unit basis:

- Operate the unit to comply with the emission limits specified in Sections 5.2 and 5.4; or
- Pay an annual emissions fee to the District as specified in Section 5.3 and comply with the control requirements specified in Section 5.4; or
- Comply with the applicable Low-use Unit requirements of Section 5.5.

Chevron complies with Section 5.3 by paying an emissions fee; therefore the emission limits of Section 5.2 are not applicable.

Section 5.3 specifies the schedule and calculation method that is used to comply with Section 5.1.

The following conditions will be listed on the permits to ensure compliance with these sections:

- Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.1, 5.3]

- Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3]

Permit Unit(s)	Condition Number(s)
S-1131-62, '-63, '-64, '-66, '-67, '-68, '-69, '-70, and '-73	31 and 32
S-1131-912	29 and 30

Section 5.4.1 To limit particulate matter emissions, an operator shall comply with one of the following requirements:

- On and after the applicable NOx Compliance Deadline specified in Section 5.2 Table 1, operators shall fire units exclusively on PUC-quality natural gas, commercial propane, butane, or liquefied petroleum gas, or a combination of such gases;
- On and after the applicable NOx Compliance Deadline specified in Section 5.2 Table 1, operators shall limit fuel sulfur content to no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet; or
- On and after the applicable NOx Compliance Deadline specified in Section 5.2 Table 1, operators shall install and properly operate an emission control system that reduces SO_2 emissions by at least 95% by weight; or limit exhaust SO_2 to less than or equal to 9 ppmv corrected to 3.0% O2.
- Notwithstanding the compliance deadlines indicated in Sections 5.4.1.1 through 5.4.1.3, refinery units, which require modification of refinery equipment to reduce sulfur emissions, shall be in compliance with the applicable requirement in Section 5.4.1 no later than July 1, 2013.

These units are all limited to 1.0 gr-S/100 scf. The following condition will ensure compliance with this section:

- The operator shall fire the unit only on natural gas. The combined sulfur content of all fuels supplied to this steam generator shall not exceed 1.0 gr S/100 scf. [District Rules 2201; and 4320, 5.4]

Permit Unit(s)	Condition Number(s)
S-1131-62, '-63, '-64, '-66, '-67, '-68, '-69, '-70, '-73, and '-912	1

Section 5.4.2 applies to liquid fuel firing units. These units are not permitted to burn liquid fuels; therefore, this section is not applicable.

Section 5.5 applies to units that burn less than 1.8 billion Btu/year. These units are not restricted to 1.8 billion Btu/year; therefore, this section is not applicable.

Section 5.6 states that the applicable emission limits of Sections 5.2 Table 1 and 5.5.2 shall not apply during start-up or shutdown provided an operator complies with the requirements specified in Sections 5.6.1 through 5.6.5.

The following conditions will ensure compliance with this section:

- Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown. [District Rules 4305, 5.5, 6.1; 4306, 5.3, 6.1; and 4320, 5.6, 6.1]

- Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; 4306, 3.22, 3.25; and 4320, 3.25, 3.29]

Permit Unit(s)	Condition Number(s)
S-1131-62, '-63, '-64, '-66, '-67, '-68, '-69, '-70, '-73, and '-912	7 and 8

Section 5.7.1 requires that permit units subject to District Rule 4320, Section 5.2 shall both install and maintain an operational APCO approved Continuous Emission Monitoring System (CEMS) for NO_X, CO and O_2, or implement an APCO-approved alternate monitoring program. These units are not required to comply with Section 5.2; therefore this section is not applicable.

Section 5.7.6 requires operators complying with Sections 5.4.1.1 or 5.4.1.2 to provide an annual fuel analysis to the District unless a more frequent sampling and reporting period is included in the Permit to Operate.
The following conditions are listed on the permits to ensure compliance with this section:

- If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320, 5.2 and 5.7]

- If the unit is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. Each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 4320, 5.2 and 5.7]

- Permittee shall maintain daily records of volume of fuel gas burned, sulfur content as determined by analytical testing or fuel supplier invoices/certifications, and permit number(s) of systems providing gas for incineration. [District Rules 2201; and 4320, 5.2, 5.7]

Permit Unit(s)	Condition Number(s)
S-1131-62, '-63, '-64, '-66, '-67, '-68, '-69, '-70, '-73, and '-912	12, 13, and 25

Section 5.8.1 requires that the operator of any unit shall have the option of complying with either the applicable heat input (lb/MMBtu), emission limits or the concentration (ppmv) emission limits specified in Section 5.2. The emission limits selected to demonstrate compliance shall be specified in the source test proposal pursuant to Rule 1081 (Source Sampling).

Therefore, the following condition will be listed on the ATCs as follows:

- The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8]

Permit Unit(s)	Condition Number(s)
S-1131-62, '-63, '-64, '-66, '-67, '-68, '-69, '-70, '-73, and '-912	9

Section 5.8.2 requires that all emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0. Therefore, the following permit condition will be listed on the ATCs as follows:

- All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8]

Permit Unit(s)	Condition Number(s)
S-1131-62, '-63, '-64, '-66, '-67, '-68, '-69, '-70, '-73, and '-912	10

Section 5.8.3 applies to units equipped with CEMS. No units for which Rule 4320 is applicable are equipped with CEMS; therefore the requirements of this section are not applicable.

Section 5.8.4 lists requirements for units complying with Section 5.7.1. These units are not required to comply with this section; therefore, this section is not applicable.

Section 5.8.5 lists requirements for units complying with Section 6.3.1, which applies to units subject to Section 5.2. These units are not required to comply with Section 5.2; therefore, this section is not applicable.

Section 6.1 requires that the records required by Sections 6.1.1 through 6.1.5 shall be maintained for five calendar years and shall be made available to the APCO and EPA upon request. Failure to maintain records or information contained in the records that demonstrate noncompliance with the applicable requirements of this rule shall constitute a violation of this rule.

A permit condition will be listed on the permit as follows:

- All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; 2520, 9.4.2; 4305, 6.1; 4306, 6.1; and 4320, 6.1]

Permit Unit(s)	Condition Number(s)
S-1131-62, '-63, '-64, '-66, '-67, '-68, '-69, '-70, '-73, and '-912	26

Section 6.2 identifies the following test methods as District-approved source testing methods for the pollutants listed:

Pollutant	Units	Test Method Required
Fuel HHV	Btu/scf	ASTM D 1826 or D 1945 in conjunction with D 3588
NO_X	ppmv	EPA Method 7E or ARB Method 100
NO_X	lb/MMBtu	EPA Method 19
CO	ppmv	EPA Method 10 or ARB Method 100
Stack Gas O_2	%	EPA Method 3 or 3A, or ARB Method 100
Stack Gas Velocities	ft/min	EPA Method 2
Stack Gas Moisture Content	%	EPA Method 4
SO_X	lb/MMBtu	EPA Method 6, 6C, 8 or ARB Method 100
H_2S in Fuel	ppmv	EPA Method 11 or 15

Chevron has requested additional test methods as allowed by District Policy APR-1710 for testing of SO_X (EPA method 19), fuel gas sulfur content (ASTM D1072, D3246, D4084 or grab sample analysis by double GC), and PM (EPA Methods 5 – both filterable and condensable[2], 201A and 202, or CARB Method 5).

The following permit condition will be listed to ensure compliance with this section:

- The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensable), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; 4306, 6.2; and 4320, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-62, '-63, '-64, '-66, '-67, '-68, '-69, '-70, '-73, and '-912	15

[2] District policy, APR-1715, requires both filterable and condensable PM to be considers and clarifies that EPA also requires this.

Section 6.3.1 requires that this unit be tested to determine compliance with the applicable requirements of Section 5.2. These units are not subject to the requirements of section 5.2; therefore this section is not applicable.

Section 6.3.2 allows that in lieu of compliance with Section 6.3.1, compliance with the applicable emission limits in Sections 5.1 or 5.2.3 shall be demonstrated by submittal of annual emissions test results to the District from a unit or units that represent a group of units. Chevron does not use representative testing on any of these steam generators; therefore, this section is not applicable.

Section 6.4 requires the permittee to submit an emissions control plan. Chevron has already submitted a plan; therefore the requirements of this section are not applicable.

I. District Rule 4351 – Boilers, Steam Generators, and Process Heaters – Phase 1

This rule applies to any boiler, steam generator or process heater, with a rated heat input greater than 5 million Btu per hour that is fired with gaseous and/or liquid fuels, and is included in a major NOx source. This rule does not apply to any unit located west of Interstate Highway 5 located in Fresno, Kern, or Kings county.

All steam generators at this facility (no boilers exist and one process heater is operated by Chevron but is <5.0 MMBtu/hr, so this rule does not apply) are rated greater than 5 MMBtu/hr and are located East of Highway 5; therefore, these units are subject to District Rule 4351, Boilers, Steam Generators and Process Heaters – Phase 1.

In addition, these units are also subject to District Rule 4305, Boilers, Steam Generators and Process Heaters – Phase 2.

All units this rule applies to are compliant with District Rule 4305, *Boilers, Steam Generators, and Process Heaters – Phase 2*. Since emissions limits of District Rule 4305 and all other requirements are equivalent or more stringent than District Rule 4351 requirements, compliance with District Rule 4305 requirements will satisfy requirements of District Rule 4351 (rule citations for all Rule 4351 conditions are added to permits where applicable).

J. District Rule 4401 – Steam-Enhanced Crude Oil Production Wells

The purpose of this rule is to limit the VOC emissions from steam-enhanced crude oil production well vents. This rule is applicable to all steam-enhanced crude oil production wells and any associated vapor collection and control systems.

The following condition will ensure compliance with this rules leak definition:

- Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20]

All condition mapping will appear at the end of the Rule 4401 compliance discussion.

Section 4.1 exempts any steam-enhanced crude oil production well from this rule when undergoing service or repair during the time the well is not producing. The following condition will ensure compliance with this exemption:

- During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1]

Section 4.7 states that the requirements of Section 5.4.1 through Section 5.4.7 of this rule shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight or less (≤10 wt.%), as determined by the test methods in Section 6.3.4.:

- The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7]

Section 5.1 prohibits an operator from operating a steam-enhanced crude oil production well unless either of the following two conditions are met: 1) The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids is connected to a VOC collection and control system as defined in Section 3.0 of this Rule, or 2) the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system that has a VOC collection and control system as defined in Section 3.0 of this Rule.

- An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1]

Section 5.2 states that an operator shall be in violation of this rule if any District inspection or operator inspection conducted pursuant to Section 5.4 demonstrates that one or more of the following conditions exist at the facility:

- Existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere; or,
- Existence of a component with a major liquid leak as defined in Section 3.0; or,
- Existence of a component with a gas leak greater than 50,000 ppmv; or,
- Existence of a component leak described in Section 5.2.2.4.1 through Section 5.2.2.4.3 in excess of the allowable number of leaks specified in Table 2.

The following conditions will ensure compliance with this section:

- An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2]

- An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2]

Section 5.3 requires operators to comply with the following requirements:

- An operator shall not use any component with a leak as defined in Section 3.0, or that is found to be in violation of the provisions of Section 5.2.2. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of this rule; or,
- Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere; or,

- An operator shall comply with the requirements of Section 6.7 if there is any change in the description of major components or critical components.

The following conditions will ensure compliance with this section:

- An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3]

- Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3]

- An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3]

Section 5.4 an operator shall perform all component inspections and gas leak measurements pursuant to the requirements of Section 6.3.3 with the following exceptions and additions:

- Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year; or,
- An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of this rule; or,
- In addition to the inspections required by Section 5.4.1, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows:
  - An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week; or,
  - Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of this rule.

- In addition to the inspections required by Section 5.4.1, Section 5.4.2 and Section 5.4.3, an operator shall perform the following inspections:
  - An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection; or,
  - An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service; or,
  - Except for PRDs subject to the requirements of Section 5.4.4.1, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced.
- An operator shall inspect all unsafe-to-monitor components during each turnaround; or,
- A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator.

The following conditions will ensure compliance with this section:

- Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1]

- An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2]

- In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3]

- In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4]

- An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.7]

- District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.8]

Section 5.5 outlines leak repair requirements as follows:

- An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak. An operator shall include the following information on the tag:
  - The date and time of leak detection.
  - The date and time of leak measurement.
  - For a gaseous leak, the leak concentration in ppmv.
  - For a liquid leak, whether it is a major liquid leak or a minor liquid leak.
  - Whether the component is an essential component, an unsafe-to monitor component, or a critical component.
- An operator shall keep the tag affixed to the component until an operator has met all of the following conditions:
  - Repaired or replaced the leaking component, and
  - Re-inspected the component using the test method in Section 6.3.3, and
  - The component is found to be in compliance with the requirements of this rule.
- An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak.
- Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0, an operator shall comply with at least one of the following requirements as soon as practicable, but not later than the time period specified in Table 3.
  - Repair or replace the leaking component; or
  - Vent the leaking component to a VOC collection and control system as defined in Section 3.0; or
  - Remove the leaking component from operation

- The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3.
- The time of the initial leak detection shall be the start of the repair period specified in Table 3.
- If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier.

The following conditions will ensure compliance with this section:

- An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5]

- An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5]

- An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5]

- Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5]

- The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5]

- The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5]

- The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5]

- If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5]

Section 6.1 requires operators to maintain records required by Section 6.1 and Section 6.2 for a period of five (5) years. These records shall be made available to the APCO, California Air Resources Board (ARB), and EPA upon request. The following records shall be maintained:

- The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs.
- A small producer shall maintain monthly records of county-specific crude oil production. For the purpose of this rule, the monthly crude oil production records required by the California Division of Oil, Gas, and Geothermal Resources may be used to satisfy Section 6.1.2.
- An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0.
- The inspection log maintained pursuant to Section 6.4.
- Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration.
- An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5.
- An operator shall keep a copy of the APCO-approved Operator Management Plan at the facility.
- An operator shall keep a list of all gauge tanks, as defined in Section 3.0. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment.
- The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing.

- An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year of the release to the APCO no later than 60 days after the end of the calendar year.

The following conditions will ensure compliance with this section:

- The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1]
- An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1]
- Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1]
- Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1]
- An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1 and 6.5]
- Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.6]
- Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1]
- The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1]
- An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1]

- All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1]

Section 6.2 requires source testing to meet the following requirements:

- An operator shall source test annually all VOC collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system is not subject to compliance source testing requirements.
- If approved by the APCO, a VOC collection and control system is not subject to Section 6.2.1 if all uncondensed VOC emissions collected by the system are controlled by a device meeting one of the following requirements:
  - An internal combustion engine subject to District Rule 4702 (Internal Combustion Engines – Phase 2); or
  - A combustion device subject to District Rule 4320 (Advanced Emission Reduction Options for Boilers, Steam Generators, and Process Heaters Greater than 5.0 MMBtu/hr); District Rule 4307 (Boilers, Steam Generators, and Process Heaters – 2.0 MMBtu/hr to 5.0 MMBtu/hr); or District Rule 4308 (Boilers, Steam Generators, and Process Heaters – 0.075 MMBtu/hr to 2.0 MMBtu/hr); or
  - A unit subject to District Rule 4311 (Flares).
- An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0:
  - An operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July – September), and whenever there is a change in the source or type of produced fluid in the gauge tank.
  - The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9.

The following conditions will ensure compliance with this section:

- An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2]

- If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2]

- An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2]

Section 6.3 lists test methods that may be used to show compliance. The following conditions will ensure compliance with this section:

- The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3]

- VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3]

- Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3]

- The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3]

Section 6.4 requires operators to maintain an inspection log that records, at a minimum, all of the following information for each inspection performed:

- The total number of components inspected, and the total number and percentage of leaking components found by component type.
- The location, type, and name or description of each leaking component and description of any unit where the leaking component is found.
- The date of leak detection and the method of leak detection.
- For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak.
- The date of repair, replacement, or removal from operation of leaking components.
- The identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier.
- The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier.
- The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced.
- The inspector's name, business mailing address, and business telephone number.
- The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log.

The following conditions will ensure compliance with this section:

- Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4]

Section 6.5 requires operators to establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. The following condition will ensure compliance with this section:

- An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1 and 6.5]

Section 6.6 requires an operator to prepare and submit an Operator Management Plan for approval by the APCO. An operator may use diagrams, charts, spreadsheets, or other methods approved by the APCO to describe the information required by Section 6.6.4 through Section 6.6.7. The following condition will ensure compliance with this section:

- Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.6]

Section 6.7 requires that by January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan.

The following conditions will ensure compliance with this section:

- By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7]

Permit Unit(s)	Condition Number(s)
S-1131-716	15-56
S-1131-903 and '-909	9-50
S-1131-917, '-932, '-944, '-958, '-1014, '-1035, and '-1048	5-46
S-1131-995	7-48
S-1131-996	8-49
S-1131-1007, '-1010, '-1011, '-1012, '-1013, and '-1033	6-47
S-1131-1017	14-55
S-1131-1031 and '-1032	11-52
S-1131-1036	4-45
S-1131-1106	10-51

K. District Rule 4601 - Architectural Coatings

This rule limits the emissions of VOCs from architectural coatings. It requires limiting the application of any architectural coating to no more than what is listed in the Table of Standards (Section 5.0). The rule was amended in December 17, 2009. Since the following changes included in the latest rule amendment did not result in adding new requirements and/or revising current requirements in the facility-wide permit S-2010-0-2, no further evaluation is needed.

Section 5.1 requires that, except as provided for in Section 5.2 and 5.3, no person shall: manufacture, blend, or repackage for use within the District; or supply, sell, or offer for sale within the District; or solicit for application or apply within the District any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards 1 or the Table of Standards 2, after the specified effective date in the Table of Standards 1 or the Table of Standards 2. Limits are expressed as VOC Regulatory, thinned to the manufacturer's maximum thinning recommendation, excluding any colorant added to tint bases.

Section 5.2 allows coatings that meet the definition in Section 3.0 for one or more specialty coating categories listed in the Table of Standards 1 or the Table of Standards 2 to meet the VOC limit for the applicable specialty coating listed in the Table of Standards 1 or the Table of Standards 2.

The following condition will ensure compliance with this section of the rule:

- No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1, 5.2, 5.5, and 5.7]

Permit Unit(s)	Condition Number(s)
S-1131-0	24

Section 5.3 allows a coating manufactured prior to the effective date specified for that coating in the Table of Standards 1 or the Table of Standards 2, and that complied with the standards in effect at the time the coating was manufactured, to be sold, supplied, or offered for sale for up to three years after the specified effective date. In addition, a coating manufactured before the effective date specified for that coating in the Table of Standards 1 or the Table of Standards 2 may be applied at any time, both before and after the specified effective date, so long as the coating complied with the standards in effect at the time the coating was manufactured. Section 5.3 does not apply to any coating that does not display the date or date-code required by Section 6.1.1.

The facility had not requested this allowance in the previous Title V permit nor in the application for this permit.

Section 5.4 requires that all architectural coating containers used to apply the contents therein to a surface directly from the container by pouring, siphoning, brushing, rolling, padding, ragging or other means, shall be closed when not in use. These architectural coating containers include, but are not limited to, drums, buckets, cans, pails, trays or other application containers. Containers of any VOC-containing materials used for thinning and cleanup shall also be closed when not in use.

- All VOC-containing materials for architectural coatings subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4]

Permit Unit(s)	Condition Number(s)
S-1131-0	25

Section 5.5 requires that no person who applies or solicits the application of any architectural coating shall apply a coating that is thinned to exceed the applicable VOC limit specified in the Table of Standards 1 or the Table of Standards 2.

The following condition will ensure compliance with this section of the rule:

- No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1, 5.2, 5.5, and 5.7]

Permit Unit(s)	Condition Number(s)
S-1131-0	24

Section 5.6 is effective only through December 31, 2010.

Section 5.7 requires that coatings not listed in the Table of Standards 1 or the Table of Standards 2 that do not meet any of the definitions for the specialty coatings categories listed in the Table of Standards 1 or the Table of Standards 2, the VOC content limit shall be determined by classifying the coating as a Flat, Nonflat, or Nonflat – High Gloss coating, based on its gloss, and the corresponding Flat, Nonflat, or Nonflat – High Gloss VOC limit in the Table of Standards 1 or the Table of Standards 2 shall apply.

The following condition will ensure compliance with this section of the rule:

- No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1, 5.2, 5.5, and 5.7]

Permit Unit(s)	Condition Number(s)
S-1131-0	24

Section 5.8 is effective only through December 31, 2010.

Section 6.1 requires each manufacturer of any architectural coating subject to this rule to display the information listed in Sections 6.1.1 through 6.1.14 on the coating container (or label) in which the coating is sold or distributed.

The following condition will ensure compliance with this section of the rule:

- The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3]

Permit Unit(s)	Condition Number(s)
S-1131-0	26

Section 6.2 lists sales data requirements. This source does not engage in architectural coating sales; therefore, this section is not applicable.

Section 6.3 lists test methods. The following condition will ensure compliance with this section of the rule:

- The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3]

Permit Unit(s)	Condition Number(s)
S-1131-0	26

L. District Rule 4621 - Gasoline Transfer into Stationary Storage Containers, Delivery Vessels and Bulk Plants

This rule applies to storage containers located at bulk plants with capacities greater than 250 gallons and less than 19,800 gallons; to other stationary storage containers with capacities greater than 250 gallons; and to those storage containers that are not subject to the control requirements of Rule 4623 (Storage of Organic Liquids) Section 5.0. The rule also applies to gasoline delivery vessels.

Section 5.1 states "loading equipment and vapor collection equipment shall be installed, maintained, and operated such that it is leak-free, with no excess organic liquid drainage at disconnect."

Section 3.19 defines a leak as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration or total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with the test method in Section 6.4.3. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component or equipment into a container is not considered sampling of a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere.

Therefore, the following permit conditions will be placed on the permit to ensure cornpliance with these requirements:

- Vapor recovery systems and gasoline dispensing equipment shall be maintained leak-free as verified using EPA Test Method 21 and visual inspection. Leak testing shall be performed at least annually and within 60 days of all major modifications. For this condition, a major modification is considered to be replacing, repairing, or upgrading 75% or more of the certified system. A leak is defined as the dripping at a rate of more than three (3) drops per minute of liquid containing VOCs or a reading as methane in excess of 10,000 ppm as determined using EPA Method 21. [District Rules 4621, 3.19, 5.1, 5.6; and 4622, 3.17, 5.1, 5.6, 6.5]

Permit Unit(s)	Condition Number(s)
S-1131-724	31

Section 5.2.1 states "no person shall transfer, or permit the transfer, of gasoline from any delivery vessel into any stationary storage container subject to the requirements of this rule unless such container is equipped with an ARB certified permanent submerged fill pipe and utilizes an ARB certified Phase I vapor recovery system that is maintained and operated according to manufacturer specifications and the applicable ARB Executive Order." Since the facility has installed ARB certified Phase I vapor recovery system, requirements of this section are satisfied and compliance is expected.

In addition, ARB has the additional certification requirements, including applicable rules and regulations of the Division of Measurement Standards, the Department of Food and Agriculture, the Office of the State Fire Marshal, the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health, the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification.

Therefore, the following conditions will be listed on the permit to ensure compliance with this requirement:

- The vapor recovery systems and their components shall be installed, operated, and maintained in accordance with the State certification requirements. [District Rules 4621, 5.2; and 4622, 5.1]
- The Phase I and Phase II vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621, 5.2; and 4622, 5.1]
- Each gasoline storage tank shall be equipped with a permanent submerged fill pipe. [District Rule 4621, 5.2]
- Each storage tank subject to this permit shall be equipped with an ARB certified Phase I vapor recovery system, which shall prevent at least 95% by weight of all gasoline vapors displaced during the filling of storage tanks from entering the atmosphere. The transfer of gasoline from any delivery vessel to any stationary storage container with 250 gallon capacity or more shall not be allowed unless the container is equipped with an ARB certified Phase 1 system and maintained and operated according to manufacturers specifications. [District Rule 4621, 5.2]

Permit Unit(s)	Condition Number(s)
S-1131-724	2, 3, 8, and 9

Section 5.2.4 states "operators shall have all underground storage container installations and all underground piping configurations inspected by the APCO prior to backfilling. The operator shall notify the District by telephone or other District-approved method and obtain a confirmation number at least three business days prior to the backfilling."
As this equipment is already installed, notification prior to backfilling is not required.

Section 5.3.3 states "for an underground storage container not located at a bulk plant and a container that does not contain aviation gasoline, the container shall be equipped with an ARB certified Phase I vapor recovery system that has a minimum volumetric control efficiency of 98 percent." The facility has proposed the installation of a Phase I vapor recovery system that meets the requirements of this section. Therefore, no further discussion is required.

Section 5.3.5 states "operators of underground storage containers not located at bulk plants shall conduct and pass the applicable performance tests specified in Sections 6.4.5 through 6.4.8 to determine compliance at least once every 36 months, (no more than 30 days before or after the required performance test date) unless otherwise required under ARB Executive Order or Rule 4622 (Gasoline Transfer into Motor Vehicle Fuel Tanks)."

Therefore, the following conditions will be listed on the permit to ensure compliance with this requirement:

- The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621, 5.3; and 4622, 6.4]
- The permittee shall perform and pass a Static Leak Test for Underground Tanks using ARB TP-201.3 in accordance with the Executive Order specified in this permit for the Phase II Vapor Recovery System at least once every 12 months. [District Rules 4621, 5.3; and 4622, 6.4]
- The permittee shall perform and pass a Pressure Integrity of Drop Tube Drain Valve Assembly Test using ARB TP-201.1C or a Pressure Integrity of Drop Tube Overfill Protection Devices Test using ARB TP-201.1D if an overfill protection device is installed, at least once every 36 months. [District Rule 4621, 5.3]
- The permittee shall perform and pass a Static Torque of Rotatable Phase I Adaptors test using ARB procedure TP-201.1B at least once every 36 months. [District Rule 4621, 5.3]

Permit Unit(s)	Condition Number(s)
S-1131-724	20, 23, 27, and 28

Section 5.5 states "all Phase I vapor recovery systems shall be inspected according to the frequency specified in Table 1. The person conducting the inspections shall, at a minimum, verify that the fill caps and vapor caps are not missing, damaged, or loose, that the fill cap gasket and vapor cap gaskets are not missing or damaged, that the fill adapter and vapor adapter are securely attached to the risers, that, where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing, and the dry break (poppet-valve) is not missing or damaged and that the submerged fill tube is not missing or damaged." Therefore, the following conditions will be listed on the permit to ensure compliance with this requirement:

- The operator shall conduct periodic maintenance inspections based on the amount of gasoline dispensed by the facility in a calendar month as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621, 5.5; and 4622, 5.3]

- Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621, 5.5]

Permit Unit(s)	Condition Number(s)
S-1131-724	35 and 36

Section 5.7.2 states "no person shall operate, or allow the operation of a delivery vessel unless valid State of California decals which attest to the vapor integrity of the container are displayed." Therefore, the following condition will be listed on the permit to ensure compliance with this requirement:

- No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo tank which attest to the vapor integrity of the tank. [District Rule 4621, 5.7]

Permit Unit(s)	Condition Number(s)
S-1131-724	12

Section 6.1.4 states "all records required to demonstrate compliance with the requirements of this rule shall be retained on the premises for a minimum of five years and made available on site during normal business hours to the APCO, ARB, or EPA, and submitted to the APCO, ARB, or EPA upon request."

Therefore, the following conditions will be listed on the permit to ensure compliance with this requirement:

- The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rules 4621, 6.1; and 4622, 6.2]
- Operator shall maintain all records of required monitoring data and support information for inspection for a period of five years. [District Rules 4621, 6.1; and 4622, 6.1, 6.2]
- The operator shall maintain monthly and annual gasoline throughput records. [District Rules 4621, 6.1; and 4622, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-724	30, 33, and 40

Section 6.2.3 states "Operators shall notify the District at least seven days prior to any performance testing."

Section 6.2.4 states "Operators shall submit all performance test results to the District within 30 days of test completion."

Therefore, the following condition will be listed on the permit to ensure compliance with this requirement:

- The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-724	21

Section 6.3.1 states "on and after June 20, 2008, installation and maintenance contractors shall be certified by the ICC for Vapor Recovery System Installation and Repair (VI) and make available onsite proof of ICC certification for VI, and have and make available on site proof of any and all certifications required by the Executive Order and installation and operation manual in order to install or maintain specific systems, or work under the direct and personal supervision of an individual physically present at the work site who possesses and makes available onsite a current certificate from the ICC, indicating he or she has passed the VI exam and all certifications required by the applicable Executive Order."

Section 6.3.2 states "All ICC certifications shall be renewed every 24 months by passing the appropriate exam specific to the certification being sought."

Therefore, the following conditions will be listed on the permit to ensure compliance with this requirement:

- A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621, 6.3; and 4622, 5.2]
- Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621, 6.3; and 4622, 5.2]

Permit Unit(s)	Condition Number(s)
S-1131-724	17 and 18

Section 6.3.3 states "Effective on and after March 21, 2008, Gasoline Dispensing Facility Testers wishing to conduct vapor recovery system testing and repair at facilities located within the District, shall be in full compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification)."

Therefore, the following permit condition will be placed on the ATC to ensure compliance with these requirements:

- A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621, 6.3 and 4622, 6.4]

Permit Unit(s)	Condition Number(s)
S-1131-724	19

M. District Rule 4622 - Gasoline Transfer into Motor Vehicle Fuel Tanks

This rule applies to any gasoline storage and dispensing operation or mobile fueler from which gasoline is transferred into motor vehicle fuel tanks, except as provided in Section 4.0.

Section 3.17 defines leak as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration or total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with the test method in Section 6.5.4. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component or equipment into a container is not considered sampling of a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere.

Therefore, the following condition will be listed on the permit to ensure compliance with this requirement:

- Vapor recovery systems and gasoline dispensing equipment shall be maintained leak-free as verified using EPA Test Method 21 and visual inspection. Leak testing shall be performed at least annually and within 60 days of all major modifications. For this condition, a major modification is considered to be replacing, repairing, or upgrading 75% or more of the certified system. A leak is defined as the dripping at a rate of more than three (3) drops per minute of liquid containing VOCs or a reading as methane in excess of 10,000 ppm as determined using EPA Method 21. [District Rules 4621, 3.19, 5.1, 5.6; and 4622, 3.17, 5.1, 5.6, 6.5]

Permit Unit(s)	Condition Number(s)
S-1131-724	31

Section 3.25 defines a retail gasoline outlet as an establishment at which gasoline is sold or offered for sale to the general public for use in motor vehicles. Therefore, the following condition will be listed on the permit to ensure compliance with this requirement:

- This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rules 4622, 3.25; and 2520, 9.1]

Permit Unit(s)	Condition Number(s)
S-1131-724	11

Section 5.1 states "a person shall not transfer or permit the transfer of gasoline from any stationary storage container, or from any mobile fueler with a capacity greater than 120 gallons, into a motor vehicle fuel tank with a capacity greater than 5 gallons, unless the gasoline dispensing unit used to transfer the gasoline is equipped with and has in operation an ARB certified Phase II vapor recovery system."

Section 5.1.1 states "all ARB certified Phase II vapor recovery systems shall be maintained according to ARB certifications and the manufacturer specifications applicable to the system." Since the facility is proposing to install ARB certified Phase II vapor recovery system, requirements of this section are satisfied and compliance is expected.

In addition, ARB has the additional certification requirements, including applicable rules and regulations of the Division of Measurement Standards, the Department of Food and Agriculture, the Office of the State Fire Marshal, the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health, the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification.

Therefore, the following conditions will be listed on the permit to ensure compliance with this requirement:

- The vapor recovery systems and their components shall be installed, operated, and maintained in accordance with the State certification requirements. [District Rules 4621, 5.2; and 4622, 5.1]
- The Phase I and Phase II vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621, 5.2; and 4622, 5.1]
- All nozzles shall be equipped with coaxial hose configurations. [District Rule 4622, 5.1]
- Each dispensing system shall be equipped with an ARB certified Phase II vapor recovery system which shall prevent at least 95% by weight of all gasoline vapors displaced during refueling of vehicles from entering the atmosphere. [District Rule 4622, 5.1]
- The permittee shall perform and pass a Dispenser vapor Line Tightness test for each dispenser using the test procedure defined in the Installation, Operation and Maintenance manual of the Executive Order specified in this permit for the Phase II Vapor Recovery System at least once every 12 months. [District Rule 4622, 5.1]

Permit Unit(s)	Condition Number(s)
S-1131-724	2, 3, 7, 10, and 26

Section 5.1.2 states "all ARB certified Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method in Section 6.5.4."

The following condition will be listed on the permit to ensure compliance with this requirement:

- Vapor recovery systems and gasoline dispensing equipment shall be maintained leak-free as verified using EPA Test Method 21 and visual inspection. Leak testing shall be performed at least annually and within 60 days of all major modifications. For this condition, a major modification is considered to be replacing, repairing, or upgrading 75% or more of the certified system. A leak is defined as the dripping at a rate of more than three (3) drops per minute of liquid containing VOCs or a reading as methane in excess of 10,000 ppm as determined using EPA Method 21. [District Rules 4621, 3.19, 5.1, 5.6; and 4622, 3.17, 5.1, 5.6, 6.5]

Permit Unit(s)	Condition Number(s)
S-1131-724	31

Section 5.2.1 states "any gasoline dispensing system subject to this rule shall comply with the provisions of this rule at the time of installation."

Section 5.2.2 states "operators shall have all underground storage container installations and all underground piping configurations inspected by the APCO prior to backfilling. The operator shall notify the District by telephone or other District-approved method and obtain a confirmation number at least three business days prior to the backfilling."

As this equipment is already installed, notification prior to backfilling is not required.

Section 5.2.3 states "installation and maintenance contractors shall, be certified by the ICC (International Code Council) for Vapor Recovery System Installation and Repair by June 20, 2008, renew the ICC certification for Vapor Recovery System Installation and Repair every 24 months, make available onsite proof of ICC certification, and have and make available on site proof of any and all certifications required by the Executive Order and installation and operation manual in order to install or maintain specific systems."

Section 5.2.4 states "in lieu of complying with Sections 5.2.3.1 through 5.2.3.4, installation and maintenance contractors may work under the direct and personal supervision of an individual physically present at the work site who possesses and makes available on site current certifications from the ICC, indicating he or she has passed the ICC Vapor Recovery System Installation and Repair exam and all other certifications required by the applicable Executive Order." The following conditions will be listed on the permit to ensure compliance with this requirement:

- The ARB certified vapor recovery system and all of its components shall be maintained in good repair. Any ARB certified gasoline vapor recovery system, which has been installed and has been issued a permit to operate, shall not be removed regardless of the amount of gasoline dispensed or how the gasoline is delivered to the facility. [District Rule 4622, 5.2]
- A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621, 6.3; and 4622, 5.2]
- Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621, 6.3; and 4622, 5.2]
- The gasoline throughput for this permit unit shall not exceed 600,000 gallons in any one calendar year. [District Rule 4622, 5.2]

Permit Unit(s)	Condition Number(s)
S-1131-724	5, 17, 18, and 39

Section 5.3.1 states "the owner or operator of an ARB certified Phase II vapor recovery system shall conduct periodic maintenance inspections to ensure that components of the vapor recovery system are in proper operating condition."

Section 5.3.2 states "the frequency of inspections shall be based on the operation's largest monthly gasoline throughput from the previous calendar year as indicated in Table 1."

Section 5.3.4 states "the frequency of vapor path inspections shall be based on the amount of gasoline dispensed by the operation in a calendar month as indicated in Table 1."

Section 5.3.5 states "the person conducting the inspections shall at a minimum, verify that the fueling instructions required by Section 5.5 are clearly displayed with the appropriate toll-free complaint phone number and toxic warning signs, that the following nozzle components are in place and in good condition as specified in ARB Executive Orders: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, hold open latch, that the hoses are not torn, flattened or crimped, that the vapor path of coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid and that the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit."

The following conditions will be listed on the permit to ensure compliance with these requirements:

- The operator shall conduct periodic maintenance inspections based on the amount of gasoline dispensed by the facility in a calendar month as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621, 5.5; and 4622, 5.3]

- Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the fueling instructions required by this permit are clearly displayed with the appropriate toll-free complaint phone number and toxic warning signs; 2) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 3) the hoses are not torn, flattened or crimped; 4) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 5) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622, 5.3]

Permit Unit(s)	Condition Number(s)
S-1131-724	35 and 37

Section 5.4.1 states "no person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order, until: The defect has been repaired, replaced, or adjusted as necessary to correct the defect; The District has been notified, and the District has reinspected the system or authorized the system for use. Such authorization shall not include the authority to operate the equipment prior to the correction of the defective components; and all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual." The following condition will be listed on the permit to ensure compliance with this requirement:

- No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622, 5.4]

Permit Unit(s)	Condition Number(s)
S-1131-724	15

Section 5.4.2 states "upon identification of any major defects, the owner or operator shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired."

Section 5.4.2.1 states "tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary."

Section 5.4.2.2 states "in the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use." The following condition will be listed on the permit to ensure compliance with this requirement:

- Any defects identified shall be tagged "Out of Order"; the tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defect has been repaired, replaced or adjusted. In the case of defects identified by the District, tagged equipment shall be rendered inoperable and the tag shall not be removed until the District has been notified of the repairs, and/or the District has inspected and authorized the tagged equipment for use. A log containing at least the following shall be maintained: date and type of defect identified and date repaired, replaced or corrected. [District Rules 4622, 5.4]

Permit Unit(s)	Condition Number(s)
S-1131-724	16

Section 5.4.4 states "in the event of a separation due to a drive off, the owner or operator shall complete one of the following, unless otherwise specified in the applicable ARB Executive Order, and document the activities in accordance with Section 6.2, before placing the affected equipment back in service:

1) Conduct a visual inspection of the affected equipment, perform qualified repairs on any damaged components, and conduct applicable re-verification tests pursuant to Sections 6.5.1.1 and 6.5.1.4, or
2) Conduct a visual inspection of the affected equipment and replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified, before placing affected equipment back in service."

The following condition will be listed on the permit to ensure compliance with this requirement:

- In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622, 5.4]

Permit Unit(s)	Condition Number(s)
S-1131-724	38

Section 6.2.1 states "operators shall retain the test result verification that each ARB certified Phase II vapor recovery system meets or exceeds the requirements of the tests specified in Section 6.5. These verifications shall be maintained for at least five years. These test results shall be dated and shall contain the names, addresses, and telephone numbers of the companies responsible for system installation and testing."

Therefore, the following permit condition will be placed on the ATC to ensure compliance with this requirement:

- The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rules 4621, 6.1; and 4622, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-724	30

Section 6.2.2 states "a person who performs repairs on any ARB certified Phase I or Phase II vapor recovery system shall provide to the owner or operator a repair log, which the owner or operator shall maintain on the premises for at least five years and which shall include all of the following:

1) Date and time of each repair;
2) The name and applicable certification numbers of the person(s) who performed the repair, and, if applicable, the name, address and phone number of the person's employer;
3) Description of service performed;
4) Each component that was repaired, serviced, or removed;
5) Each component that was installed as replacement, if applicable;
6) Receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs."

The following condition will be listed on the permit to ensure compliance with this requirement:

- The operator shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-724	41

Section 6.2.3 states "each operator who is required to perform periodic maintenance inspections under Section 5.3 shall maintain monthly gasoline throughput records on the premises for a minimum of five years, make them available on site during normal business hours to the APCO, ARB, or EPA, and submit them to the APCO, ARB, or EPA upon request." The following conditions will be listed on the permit to ensure compliance with this requirement:

- The operator shall maintain monthly and annual gasoline throughput records. [District Rules 4621, 6.1; and 4622, 6.2]
- All records required by this permit shall be retained on-site for a period of at least five years, and shall be made available for inspection upon request. [District Rule 4622, 6.1, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-724	40 and 43

Section 6.3.1 states "the owner or operator of a gasoline dispensing operation shall maintain an O&M Manual in accordance with Section 6.3."

Section 6.3.2 states "the O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request."

Section 6.3.3 states "the O&M manual shall, at a minimum, include the following current information:
1) copies of all vapor recovery performance tests,
2) all applicable ARB Executive Orders, Approval Letters, and District Permits,

3) manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer,
4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests listed in Section 6.0. The owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements, and
5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components."

Section 6.3.4 states "owners or operators of gasoline dispensing operations shall document the periodic maintenance inspection program in the O&M manual."

The following conditions will be listed on the permit to ensure compliance with this requirement:

- The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622, 6.3]

- The operator shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with Section 5.4 of Rule 4622. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) All applicable ARB Executive Orders, Approval Letters, and District Permits; 2) The manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 3) System and/or component testing ,requirements, including test schedules and passing criteria for each of the standard tests. The owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements; 4) Protocol for performing periodic maintenance inspections including the components to be inspected and the defects requiring repair; and 5) Additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622, 6.3]

Permit Unit(s)	Condition Number(s)
S-1131-724	34 and 42

Section 6.4.1 states "operators shall comply with the ARB certified Phase II vapor recovery system performance tests specified in Sections 6.4.1.1 through 6.4.1.4 and shall conduct all applicable performance tests at start up and thereafter (no more than 30 days before or after the required compliance testing date) as required by ARB Executive Order and installation and operation manuals."

Section 6.4.1.1 states "conduct and pass a Static Leak Test of the ARB certified Phase II vapor recovery system at least once every twelve months."

Section 6.4.1.2 states "conduct and pass a Dynamic Back-Pressure Test of the ARB certified Phase II vapor recovery system at least once every twelve months except for those aboveground storage tanks that have integral dispensers (non-remote), unless otherwise required under ARB Executive Order."

Section 6.4.1.3 states "for ARB certified Phase II vapor recovery systems with bellows-less nozzles, conduct and pass, as applicable, an Air-to-Liquid Volume Ratio Test or a Vapor-to-Liquid Ratio Test at least once every six months."

Section 6.4.1.4 states "for ARB certified Phase II vapor recovery systems with a liquid removal device required by ARB Executive Orders, conduct and pass a Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid. The amount of liquid in the vapor path shall be determined in accordance with the procedure specified in Section 5.3.5.4."

Section 6.4.2 states "the person responsible for conducting the tests specified in Section 6.4 shall use calibrated equipment meeting the calibration range and calibration intervals specified by the manufacturer, ARB Executive Order, or ARB test procedure."

Section 6.4.4 states "effective on and after March 21, 2008, persons responsible for conducting the tests specified in Section 6.5 shall be in full compliance with all provisions of Rule 1177 (Gasoline Dispensing Facility Tester Certification)."

The following condition will be listed on the permit to ensure compliance with this requirement:

- A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621, 6.3 and 4622, 6.4]

Permit Unit(s)	Condition Number(s)
S-1131-724	19

Section 6.4.5 states "each gasoline dispensing operation shall notify the District at least seven days prior to any performance testing."

Section 6.4.6 states "each ARB certified Phase II vapor recovery system shall be tested within 60 days of completion of installation or modification."

Section 6.5.1 states "tests shall be conducted in accordance with the latest version of the following ARB and EPA approved test methods, or their equivalents as approved by the EPA, and the APCO."

Section 6.5.1.1 states "Static Leak Test for Underground Tanks, ARB TP-201.3"

Section 6.5.1.2 states "Dynamic Back-Pressure Test, ARB TP-201.4"

Section 6.5.1.3 states "Air-to-Liquid Volume Ratio Test, ARB TP-201.5"

Section 6.5.1.4 states "Liquid Removal Test, ARB TP-201.6C"

Section 6.5.1.5 states "Static Leak Test for Aboveground Tanks, ARB TP-206.3 or TP-201.3B as applicable."

The following conditions will be listed on the permit to ensure compliance with these requirements:

- The permittee shall perform and pass a Dynamic Back Pressure Test using ARB TP-201.4 at least once every 12 months. [District Rule 4622, 6.4, 6.5]
- The permittee shall perform and pass a Static Leak Test for Underground Tanks using ARB TP-201.3 in accordance with the Executive Order specified in this permit for the Phase II Vapor Recovery System at least once every 12 months. [District Rules 4621, 5.3; and 4622, 6.4, 6.5]
- The permittee shall perform and pass a Vapor-to-Liquid Volume Ratio Test using the test procedure defined in the Executive Order specified in this permit for the Phase II Vapor Recovery System at least once every six (6) months. [District Rule 4622, 6.4, 6.5]
- The permittee shall perform and pass a Static Pressure Test for the Healy Clean Air Separator using the test procedure defined in the Executive Order specified in this permit for the Phase II Vapor Recovery System at least once every 12 months. [District Rule 4622, 6.4, 6.5]
- The permittee shall perform and pass a Dispenser vapor Line Tightness test for each dispenser using the test procedure defined in the Installation, Operation and Maintenance manual of the Executive Order specified in this permit for the Phase II Vapor Recovery System at least once every 12 months. [District Rule 4622, 6.4, 6.5]

Permit Unit(s)	Condition Number(s)
S-1131-724	22-26

Section 6.5.4 states "detection of leaks shall be in accordance with EPA Test Method 21."

The following condition will be listed on the permit to ensure compliance with this requirement:

- Vapor recovery systems and gasoline dispensing equipment shall be maintained leak-free as verified using EPA Test Method 21 and visual inspection. Leak testing shall be performed at least annually and within 60 days of all major modifications. For this condition, a major modification is considered to be replacing, repairing, or upgrading 75% or more of the certified system. A leak is defined as the dripping at a rate of more than three (3) drops per minute of liquid containing VOCs or a reading as methane in excess of 10,000 ppm as determined using EPA Method 21. [District Rules 4621, 3.19, 5.1, 5.6; and 4622, 3.17, 5.1, 5.6, 6.5]

Permit Unit(s)	Condition Number(s)
S-1131-724	31

N. District Rule 4623 - Storage of Organic Liquids

This rule limits volatile organic compound (VOC) emissions from the storage of organic liquids. It applies to any tank with a capacity of 1,100 gallons or greater in which any organic liquid is placed, held, or stored.

Pursuant to **Section 4.4** of this rule, tanks exclusively receiving and/or storing an organic liquid with a TVP less than 0.5 psia are exempt from all requirements of this rule except for the following:

- TVP and API Gravity Testing provisions pursuant to Section 6.2,
- Recordkeeping provisions pursuant to Section 6.3.6,
- Test Methods provisions pursuant to Section 6.4, and
- Compliance schedules pursuant to Section 7.2.

The following conditions will ensure compliance with this exemption:

- This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4]

- Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2]

- The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2]

- Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3]

- The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3]

- All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3]

- The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4]

- For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4]

Permit Unit(s)	Condition Number(s)
S-1131-448, '-460, '-509, '-529, '-530, '-531, '-586, '-592, '-594, '-599, '-600, '-601, '-602, '-603, '-606, '-610, '-615, '-619, '-620, '-621, '-622, '-623, '-625, '-626, '-627, '-628, '-631, '-632, '-633, '-634, '-635, '-636, '-652, '-663, '-670, '-671, '-702, '-961, '-962, '-963, and '-964	1-8
S-1131-861 and '-862	6-12

Tanks listed below are both connected to vapor control and are limited to a TVP of less than 0.5 psia. Therefore the previously listed conditions will ensure compliance with this exemption:

Permit Unit(s)	Condition Number(s)
S-1131-598	6 and 22-28
S-1131-608, '-613, '-629, '-630, '-638, '-641, '-650, '-651, and '-1097	4 and 13-21
S-1131-885	32-41
S-1131-886, '-891, and '-892	24-32 and 35

Section 5.1 requires that no organic liquid shall be placed, held, or stored in any tank unless the tank is equipped with a VOC control system identified in Table 1. This section also requires that tanks operate in a leak-free condition except as allowed in Section 5.2.

Chevron is not a small producer and all tanks that are not exempt pursuant to Section 4.4 comply with this rule by being equipped with vapor control systems.

Section 5.2 lists requirements for pressure relief valves. No tanks, except those that are exempt, are operated with a PV valve; therefore this section is not applicable.

Section 5.3 lists requirements for external floating roof tanks. No tanks are classified as an external floating roof tank; therefore this section is not applicable.

Section 5.4 lists requirements for internal floating roof tanks. No tanks are classified as an internal floating roof tank; therefore this section is not applicable.

Section 5.5 lists requirements for floating roof deck fittings. No tanks are equipped with floating roof decks; therefore this section is not applicable.

Section 5.6 lists requirements for vapor recovery systems. Fixed roof tanks shall be fully enclosed and shall be maintained in a leak-free condition. An APCO-approved vapor recovery system shall consist of a closed system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be maintained in a leak-free condition.

The VOC control device shall be one of the following:

- A condensation or vapor return system that connects to one of the following: a gas processing plant, a field gas pipeline, a pipeline distributing Public Utility Commission quality gas for sale, an injection well for disposal of vapors as approved by the California Department of Conservation, Division of Oil Gas, and Geothermal Resources, or
- A VOC control device that reduces the inlet VOC emissions by at least 95 percent by weight as determined by the test method specified in Section 6.4.6.

Additionally any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition.

The following conditions will ensure compliance with this section of the rule:

- When the vent line is open free water knockout vessel, water stand vessel (V-190), and sand jet (V-200) vessel shall only vent to Mecca-Rambler casing vapor recovery system permit unit #S-1131-1008. [District Rules 2201; and 4623, 5.6]
- When the vent line for this permit unit is closed, produced fluids shall only be introduced to vapor controlled tanks S-1131-598, '629, '630, '638, '641, '650, '651, and '1097. [District Rules 2201; and 4623, 5.6]
- The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 95%. [District Rules 2201; and 4623, 5.6]
- Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. Leak-free shall be defined as emitting no more than 10,000 ppm of methane measured at a distance of one centimeter from the potential source with an instrument calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 5.6.2]

Permit Unit(s)	Condition Number(s)
S-1131-1049 and '-1050	1, 2, and 3

Section 5.7 lists voluntary tank preventive inspection and maintenance, and tank interior cleaning requirements. Chevron has not requested any additional I&M or tank cleaning allowances; therefore this section is not applicable.

Section 6.2 lists TVP and API gravity testing for uncontrolled fixed roof tanks. As mentioned previously, Chevron does not operate any tanks that are not exempt from the rule and do not have vapor control; therefore this section of the rule is not applicable.

Section 6.3 requires that all records be retained for a period of five years. The following condition will be listed on the permits to ensure compliance:

- All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3]

Permit Unit(s)	Condition Number(s)
S-1131-1049 and '-1050	30

O. District Rule 4701 - Internal Combustion Engines – Phase 1

Pursuant to Section 7.5.2.3 of District Rule 4702, as of June 1, 2006 District Rule 4701 is no longer applicable to engines subject to Rule 4701 §4.1, 4.2, 4.3, or 5.1. All engines permitted at this stationary source could be subject to one of these sections; therefore, these internal combustion engines will comply with the requirements of District Rule 4702 and no further discussion is required.

P. District Rule 4702 - Internal Combustion Engines – Phase 2

The purpose of this rule is to limit the emissions of nitrogen oxides (N0x), carbon monoxide (CO), and volatile organic compounds (VOC) from internal combustion engines.

The rule was amended January 18, 2007 to address the following:

- The definition of Certified Compression-Ignited Engine was modified to include a Code of Federal Regulation citation.
- An exemption was added for engines used in retracting arresting gear cables used to stop military naval aircraft after landing.
- A compliance deadline for engines used exclusively in agricultural operation was extended for one year.
- Engines operated with an APCO certified exhaust control system were exempted from submitting an emission control plan.
- Certified compression ignition engines were exempted from compliance testing.
- A portable NOx analyzer was allowed for Agriculture Operation (AO) spark-ignited engines to initially show compliance with the emission standards until a source test can be arranged.
- Representative testing for spark-ignited engines were allowed.
- A District certification program was established to verify the control efficiency of exhaust control systems.

Pursuant to **Section 4.2**, except for the requirements of Sections 5.7 and 6.2.3, the requirements of this rule shall not apply to an internal combustion engine that meets the following condition:

An emergency standby engine as defined in Section 3.0 of this rule, and provided that it is operated with a nonresettable elapsed operating time meter. In lieu of a nonresettable time meter, the owner of an emergency engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions.

Section 3.15 defines an "Emergency Standby Engine" as an internal combustion engine which operates as a temporary replacement for primary mechanical or electrical power during an unscheduled outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the operator. An engine shall be considered to be an emergency standby engine if it is used only for the following purposes: (1) periodic maintenance, periodic readiness testing, or readiness testing during and after repair work; (2) unscheduled outages, or to supply power while maintenance is performed or repairs are made to the primary power supply; and (3) if it is limited to operate 100 hours or less per calendar year for non-emergency purposes. An engine shall not be considered to be an emergency standby engine if it is used: (1) to reduce the demand for electrical power when normal electrical power line service has not failed, or (2) to produce power for the utility electrical distribution system, or (3) in conjunction with a voluntary utility demand reduction program or interruptible power contract.

Therefore, engines listed on permits S-1131-1084 and '-1117 qualify as emergency standby engines and will only have to meet the requirements of Sections 5.7 and 6.2.3 of this Rule. The engine listed on permit S-1131-1119 does not qualify as an emergency standby engine.

The following definition will be placed on the emergency standby engines to ensure compliance:

- An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702, 3.15]
- This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702, 3.15]
- This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702, 3.15]

Permit Unit(s)	Condition Number(s)
S-1131-1084	3, 5, and 6
S-1131-1117	4, 6, and 7

Section 5.7 of this Rule requires that the owner of an emergency standby engine comply with the requirements specified in Section 5.7.2 through Section 5.7.5 below:

1) Properly operate and maintain each engine as recommended by the engine manufacturer or emission control system supplier.

2) Monitor the operational characteristics of each engine as recommended by the engine manufacturer or emission control system supplier.
3) Install and operate a nonresettable elapsed operating time meter. In lieu of installing a nonresettable time meter, the owner of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO and is allowed by Permit-to-Operate or Stationary Equipment Registration condition. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions.

The following conditions ensure compliance with this section:

- This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 5.7; and 17 CCR 93115]

- During or before periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702, 5.7]

- This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702, 5.7]

Permit Unit(s)	Condition Number(s)
S-1131-1084	2, 4, and 7
S-1131-1117	2, 5, and 10

Section 6.2.3 requires that an owner claiming an exemption under Section 4.2 maintain annual operating records. This information shall be retained for at least five years, shall be readily available, and submitted to the APCO upon request.

The following conditions ensure compliance with this section:

- The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 6.2]

- All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-1084	8 and 9
S-1131-1117	13 and 15

The engine listed on permit S-1131-1119 is a non-emergency use compression ignition engine limited to 300 hours per year.

Section 5.1.2 requires compression-ignited engines to comply with the applicable emission limits/standards pursuant to Section 5.1.2 or Section 8.0. Pursuant to Table 2 *Emission Limits/Standards and Compliance Schedule for a Compression-Ignited Internal Combustion Engine*, Section 2.B, any EPA certified TIER 3 or TIER 4 engine shall meet the certified compression-ignited engine standard in effect at the time of installation.

Since the proposed engine is a certified Tier 3 engine, and the requirement at the time of ATC issuance was Tier 3 certification, this engine complies with Section 5.1.2.

Section 5.7 of this Rule requires that the owner of an engine comply with the requirements specified in Section 5.7.2 through Section 5.7.5 below:

1) Properly operate and maintain each engine as recommended by the engine manufacturer or emission control system supplier.
2) Monitor the operational characteristics of each engine as recommended by the engine manufacturer or emission control system supplier.
3) Install and operate a nonresettable elapsed operating time meter. In lieu of installing a nonresettable time meter, the owner of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO and is allowed by Permit-to-Operate or Stationary Equipment Registration condition. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions.

The following conditions ensure compliance with this section:

- Any IC engine utilized for this permit unit shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702, 5.7]

- During or before periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702, 5.7]

- Any IC engine utilized for this permit unit shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 5.7; and 17 CCR 93115]

Permit Unit(s)	Condition Number(s)
S-1131-1119	11, 12, and 13

Section 6.1 requires the owner of an engine subject to the requirements of Section 5.1 or Section 8.0, except for an engine specified in Section 6.1.1, of this rule to submit to the APCO an APCO-approvable emission control plan of all actions to be taken to satisfy the emission requirements of Section 5.1 and the compliance schedules of Section 7.0.

Since this engine already complies with the requirements of Section 5.1, no emission control plan is necessary.

Section 6.2.1 requires the owner of an engine subject to the requirements of Section 5.1 to maintain an engine operating log to demonstrate compliance with this rule. This information shall be retained for a period of at least five years, shall be readily available, and be made available to the APCO upon request. The engine operating log shall include, on a monthly basis, the following information:

6.2.1.1 Total hours of operation,
6.2.1.2 Type of fuel used,
6.2.1.3 Maintenance or modifications performed,
6.2.1.4 Monitoring data,
6.2.1.5 Compliance source test results, and
6.2.1.6 Any other information necessary to demonstrate compliance with this rule.
6.2.1.7 For an engine subject to Section 8.0, the quantity (cubic feet of gas or gallons of liquid) of fuel used on a daily basis.

Therefore, the following condition will be listed on the permit to ensure compliance.

- The permittee shall maintain a permit unit operating log that shall include the following: a record of the cumulative annual hours of operation of the engine, the quantity of diesel fuel used, and a record of maintenance or modifications performed on any IC engine utilized for this permit unit. These records shall be updated on a monthly basis. [District Rule 4702, 6.2; and 17 CCR 93115]

Permit Unit(s)	Condition Number(s)
S-1131-1119	11, 12, and 13

Section 6.3 specifies source testing requirements.

Pursuant to Section 6.3.1.1, source testing is not required for a certified compression-ignited engine that has not been retrofitted with an exhaust control and is not subject to the requirements of Section 8.0 (Alternative Emission Control Plan). This permit applies only to an engine that is a certified compression-ignited engine with an exhaust control that has not been retrofitted and is not subject to the requirements of Section 8.0, therefore source testing is not required.

Section 6.5 specifies the requirements for the Inspection and Monitoring (I&M) Plan.

Pursuant to Section 6.5.1.1, an I&M plan is not required for any certified spark-ignited engine that has not been retro-fitted with an exhaust control and is not subject to the requirements of Section 8.0 (Alternative Emission Control Plan). This permit applies only to an engine that is a certified compression-ignited engine with an exhaust control that has not been retrofitted and is not subject to the requirements of Section 8.0, therefore source testing is not required.

Section 7.5 identifies the compliance schedule for non-AO compression-ignited engine.

Pursuant to Section 7.5.2.2, this engine shall be in full compliance with Rule 4702 by the indicated dates. Since this engine is already in compliance with Rule 4702, further action is not required.

Q. District Rule 4703 - Stationary Gas Turbines

This rule applies to all stationary gas turbine systems with ratings equal to or greater than 0.3 megawatt (MW) or a maximum heat input rating of more than 3 MMBtu/hr.

Turbines listed on permits S-1131-1038 and '-1039 are designated non-compliant dormant, as such, they will not be operated; therefore, emission limits, monitoring provisions, and testing requirements of this rule will be satisfied when the units are modified to operate in compliance with this rule. The conditions below will be listed on the permits to ensure that compliance with this rule is achieved prior to operation:

- No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010]

- The fuel supply line shall be physically disconnected from this unit. [District Rule 4703].
- This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4703 and all other applicable District regulations. [District Rule 4703]

Permit Unit(s)	Condition Number(s)
S-1131-1038 and '-1039	1-3

The gas turbine listed on S-1131-1037 has a heat input rate greater than 3 MMBtu/hour. Therefore, this turbine is subject to the requirements of this rule.

Section 5.1 requires turbines to comply with NO_X limits according to which Tier is applicable. According to Section 7 this turbine must comply with Tier 2 emission limits. NO_X emissions shall be managed over a 3-hour period.

Section 5.2 requires turbines to comply with CO limits according to table 5-4. Rule 4703 does not include a specific averaging period requirement for demonstrating compliance with the CO emission limit. The District practice is to require CO emissions compliance demonstration on a 3-hour rolling average period.

Section 5.3 states that NO_X and CO emission limits shall not apply during a transitional operation period, which includes bypass transition period, primary re-ignition period, reduced load period, start-up or shutdown (each term is defined in Section 3.0 of Rule 4703), provided an operator shall meet the following conditions:

- The duration of each startup or each shutdown shall not exceed two hours.
- For each bypass transition period, the requirements specified in Section 3.2 shall be met.
- For each primary re-ignition period, the requirements specified in Section 3.20 shall be met (this condition applies to dry low NO_X combustor technology, which this turbine is not equipped with, therefore this requirement does not apply).
- Each reduced load period shall not exceed one hour.
- The emissions control system shall be in operation and emissions shall be minimized insofar as technologically feasible during these periods.

The following conditions will ensure compliance with these sections:

- Except during periods of startup/shutdown, emission rates (3-hour rolling average) shall not exceed any of the following: NOx (as NO2): 0.018 lb/MMBTU or 5 ppmvd @ 15% O2, or CO: 12 ppmvd @ 15% O2. [District Rules 2201; and 4703, 5.1, 5.2, 5.3]

- Results of continuous emission monitoring must be averaged in accordance with the requirements of 40 CFR 60.13. [40 CFR 60.334(j),(j)(5); 40 CFR 64; and District Rule 4703, 5.1]

- The operator shall provide source test information annually regarding the exhaust gas NOx concentration corrected to 15% O2 (dry). [40 CFR 60.335(a) and (b)(7) and District Rule 4703, 5.1]
- The duration of each startup or shutdown shall not exceed two hours. [40 CFR 60.2; and District Rule 4703, 5.3]
- Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rule 4703, 3.29]
- Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4703, 3.26]
- Bypass transition period is defined as the duration of time that a gas turbine's operation transitions between the heat recovery steam generator and bypass exhaust stacks, provided that the SCR catalyst is not within the required temperature range or the required ammonia saturation level has not yet been achieved; and NOx emissions shall not exceed 15 ppmvd @ 15% O2 averaged over 2 hours; and the duration of a bypass transition period shall not exceed two hours except during black start period. [District Rule 4703, 3.2]
- Reduced load period is defined as the time during which a gas turbine is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. Each reduced load period shall not exceed one hour. [District Rule 4703, 3.23]
- The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup and shutdown. [District Rule 4703, 5.3]

Permit Unit(s)	Condition Number(s)
S-1131-1037	12, 28, 43, 16-21

Section 6.1 requires the submission of an emissions control plan. Chevron has already submitted an emissions control plan; therefore this section is not applicable.

Section 6.2.1 requires the owner to operate and maintain continuous emissions monitoring equipment for NO_X and oxygen, or install and maintain APCO-approved alternate monitoring.

This unit is equipped with a Continuous Emissions Monitoring System (CEMS) that will monitor NO_X, CO and O_2 in the exhaust gas. Therefore, the requirements of this section have been satisfied.

Section 6.2.2 specifies monitoring requirements for turbines without exhaust-gas NO_X control devices. This gas turbine will be equipped with an SCR system that is

designed to control NO_X emissions. Therefore, the requirements of this section are not applicable and no further discussion is required.

Section 6.2.3 requires that for units 10 MW and greater that operated an average of more than 4,000 hours per year over the last three years before August 18, 1994, the owner or operator shall monitor the exhaust gas NO_X emissions. Chevron operates CEMS on this unit that meets the requirements of this section.

The following condition will ensure ongoing compliance with these sections:

- The owner or operator shall certify, maintain, operate, and quality-assure a continuous emission monitor system (CEMS) which continuously measures and records the exhaust gas NOx, CO, and O2 concentrations. Continuous emissions monitors shall be capable of monitoring emissions during normal operating conditions and during startups and shutdowns, provided that CEMS pass the relative accuracy requirements and performance specifications of: 40 CFR Part 60, Appendix B and F; 40 CFR Part 51, Appendix P; Performance Specification 2 (PS-2); and District approved protocol for startups. If relative accuracy of CEMS cannot be demonstrated during the startup, CEMS results during startup and shutdown events shall be replaced with startup emission rates obtained from the source test conducted by the facility to determine compliance with emission limits contained in this document. [40 CFR 60.334(b)(1); 40 CFR 64; and District Rules 1080, 6.7; and 4703, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-1037	22

Section 6.2.4 requires the facility to maintain all records for a period of five years from the date of data entry and shall make such records available to the APCO upon request.

The following condition will placed on each permit:

- The owner or operator shall maintain all records of required monitoring data and support information for a period of five years from the date of data entry and shall make such records available to the District upon request. [District Rule 4703, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-1037	23

Section 6.2.5 requires the operator to submit to the APCO, before issuance of the Permit to Operate, information correlating the control system operating to the associated measure NO_X output. This information may be used by the APCO to determine compliance when there is no continuous emission monitoring system for NO_X available or when the continuous emissions monitoring system is not operating properly. CEMS have already been installed and correlating factors have been submitted to the District; therefore, this section is not applicable.

Section 6.2.6 requires the operator to maintain a stationary gas turbine system operating log that includes, on a daily basis, the actual local startup and stop time, length and reason for reduced load periods, total hours of operation, and the type and quantity of fuel used.

Section 6.2.7 requires the operator to maintain a stationary gas turbine system log for units exempt under Section 4.2 of this Rule. This turbine is not exempt under Section 4.2 of this Rule. Therefore, no further discussion is required.

Section 6.2.8 requires the operator performing start-up or shutdown of a unit to keep records of the duration of start-up or shutdown.

The following condition will ensure compliance with these sections:

- The owner or operator shall maintain a stationary gas turbine system operating log that includes, on a daily basis, the actual local startup and stop time, length and reason for reduced load periods, total hours of operation, the type and quantity of fuel used, duration of each start-up (or black start), shutdown, and bypass transition time period. [District Rule 4703, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-1037	24

Section 6.2.9 requires additional recordkeeping for Tier 3 units. This turbine is not subject to Tier 3 emission limits; therefore, this section is not applicable.

Section 6.2.10 requires additional recordkeeping for public service units. This turbine is not a public service unit; therefore, this section is not applicable.

Section 6.2.11 requires an operator to keep records of the date, time, and duration of each bypass transition and primary re-ignition period. This unit is not equipped with dry low-NO_X combustors, so will not have reignition periods.

Section 6.2.12 requires additional recordkeeping for Tier 3 units. This turbine is not subject to Tier 3 emission limits; therefore, this section is not applicable.

Section 6.3.1 requires that the owner or operator of any stationary gas turbine system subject to the provisions of Section 5.0 of this rule provide source test information annually regarding the exhaust gas NO_X and CO concentrations.

The gas turbine is required to be tested annually to ensure compliance with NO_X and CO concentrations. The following condition will ensure compliance with this section:

- Compliance source testing for NOx, CO, VOC, NH3 and fuel gas sulfur content shall be conducted at least once every 12 months. [40 CFR 60.335(a) and District Rules 1081; and 4703, 3.6, 6.3]

Permit Unit(s)	Condition Number(s)
S-1131-1037	25

Section 6.3.2 specifies source testing requirements for units operating less than 877 hours per year. This turbine is not limited by permit condition to operate less than 877 hours per year. Therefore, the requirements of this section are not applicable and no further discussion is required.

Section 6.3.3 states that units with intermittently operated auxiliary burners shall demonstrate compliance with the auxiliary burner in both "on" and "off" configurations. This turbine is not equipped with auxiliary burners; therefore, the requirements of this section are not applicable.

Section 6.4 lists the following test measures to be used unless otherwise approved by the APCO and EPA:

- Oxides of nitrogen emissions for compliance tests shall be determined by using EPA Method 7E or EPA Method 20.

- Carbon monoxide emissions for compliance tests shall be determined by using EPA Test Methods 10 or 10B.

- Oxygen content of the exhaust gas shall be determined by using EPA Methods 3, 3A, or 20.

- HHV and LHV of gaseous fuels shall be determined by using ASTM D3588-91, ASTM 1826-88, or ASTM 1945-81.

The following condition will ensure compliance with the test method requirements of this section:

- The following test methods shall be used: NOx - EPA Method 7E or 20; CO - EPA Method 10 or 10B; Ammonia - BAAQMD ST-1B; O2 - EPA Method 3, 3A, or 20; and HHV and LHV – ASTM D3588-91, ASTM 1826-88, or ASTM 1945-81. EPA approved alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [40 CFR 60.335(a) and (b)(1) and District Rules 1081; and 4703, 6.4]

Permit Unit(s)	Condition Number(s)
S-1131-1037	26

R. District Rule 8011 - General Requirements

The provisions of this rule are applicable to specified outdoor fugitive dust sources. The definitions, exemptions, requirements, administrative requirements, recordkeeping requirements, and test methods set forth in this rule are applicable to all Rules under Regulation VIII (Fugitive PM10 Prohibitions) of the Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. The rule was amended in August 19, 2004.

The following conditions will ensure compliance with this rule:

- Disturbances of soil related to any construction, demolition, excavation, extraction, or water mining activities shall comply with the requirements for fugitive dust control in SJVUAPCD District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 or Rule 8011. [District Rules 8021 and 8011]
- Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 or Rule 8011. [District Rules 8031 and 8011]
- An owner/operator shall prevent or cleanup any carryout and trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 or Rule 8011. [District Rules 8041 and 8011]
- Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 or Rule 8011. [District Rules 8051 and 8011]
- Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 or Rule 8011. [District Rules 8061 and 8011]
- Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 or Rule 8011. [District Rules 8071 and 8011]

Permit Unit(s)	Condition Number(s)
S-1131-0	30 - 35

S. District Rule 8021 - Construction, Demolition, Excavation, Extraction, and Other Earthmoving Activities

The purpose of this rule is to limit fugitive dust emissions from construction, demolition, excavation, extraction, and other earthmoving activities. The rule was amended in August 19, 2004.

This rule applies to any construction, demolition, excavation, extraction, and other earthmoving activities, including, but not limited to, land clearing, grubbing, scraping, travel on site, and travel on access roads to and from the site. This rule also applies to the construction of new landfill disposal sites or modification to existing landfill disposal sites prior to commencement of landfilling activities.

Section 5.0 requires that no person shall perform any construction, demolition, excavation, extraction, or other earthmoving activities unless the appropriate requirements in sections 5.1 and 5.2 are sufficiently implemented to limit VDE to 20% opacity. In addition to the requirements of this rule, a person shall comply with all other applicable requirements of Regulation VIII.

The following condition will ensure compliance with this rule:

- Disturbances of soil related to any construction, demolition, excavation, extraction, or water mining activities shall comply with the requirements for fugitive dust control in SJVUAPCD District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 or Rule 8011. [District Rules 8021 and 8011]

Permit Unit(s)	Condition Number(s)
S-1131-0	30

T. District Rule 8031 - Bulk Materials

The purpose of this rule is to limit fugitive dust emissions from the outdoor handling, storage, and transport of bulk materials. The rule was amended in August 19, 2004.

This rule applies to the outdoor handling, storage, and transport of any bulk material.

Section 5.0 requires that no person shall perform any outdoor handling, storage, and transport of bulk materials unless the appropriate requirements in Table 8031-1 of this rule are sufficiently implemented to limit VDE to 20% opacity or to comply with the conditions for a stabilized surface as defined in Rule 8011. In addition to the requirements of this rule, a person shall comply with all other applicable requirements of Regulation VIII.

The following condition will ensure compliance with this rule:

- Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 or Rule 8011. [District Rules 8031 and 8011]

Permit Unit(s)	Condition Number(s)
S-1131-0	31

U. District Rule 8041 - Carryout and Trackout

The purpose of this rule is to limit fugitive dust emissions from carryout and trackout. The rule was amended in August 19, 2004.

This rule applies to all sites that are subject to Rules 8021 (Construction, Demolition, Excavation, Extraction, and other Earthmoving Activities), 8031 (Bulk Materials), and 8071 (Unpaved Vehicle and Equipment Traffic Areas) where carryout or trackout has occurred or may occur.

Section 5.0 requires that an owner/operator shall sufficiently prevent or cleanup carryout and trackout as specified in sections 5.1 through 5.8. In addition to the requirements of this rule, a person shall comply with all other applicable requirements of Regulation VIII. The use of blower devices, or dry rotary brushes or brooms, for removal of carryout and trackout on public roads is expressly prohibited. The removal of carryout and trackout from paved public roads does not exempt an owner/operator from obtaining state or local agency permits which may be required for the cleanup of mud and dirt on paved public roads.

The following condition will ensure compliance with this rule:

- An owner/operator shall prevent or cleanup any carryout and trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 or Rule 8011. [District Rules 8041 and 8011]

Permit Unit(s)	Condition Number(s)
S-1131-0	32

V. District Rule 8051 - Open Areas

The purpose of this rule is to limit fugitive dust emissions from open areas. The rule was amended in August 19, 2004.

This rule applies to any open area having 3.0 acres or more of disturbed surface area that has remained undeveloped, unoccupied, unused, or vacant for more than seven days.

Section 5.0 requires that whenever open areas are disturbed or vehicles are used in open areas, the owner/operator shall implement one or a combination of control measures indicated in Table 8051-1 to comply with the conditions of a stabilized surface at all times and to limit VDE to 20% opacity. In addition to the requirements of this rule, a person shall comply with all other applicable requirements of Regulation VIII.

The following condition will ensure compliance with this rule:

- Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 or Rule 8011. [District Rules 8051 and 8011]

Permit Unit(s)	Condition Number(s)
S-1131-0	33

W. District Rule 8061 - Paved and Unpaved Roads

The purpose of this rule is to limit fugitive dust emissions from paved and unpaved roads by implementing control measures and design criteria. The rule was amended in August 19, 2004.

This rule applies to any new or existing public or private paved or unpaved road, road construction project, or road modification project.

The following condition will ensure compliance with this rule:

- Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 or Rule 8011. [District Rules 8061 and 8011]

Permit Unit(s)	Condition Number(s)
S-1131-0	34

X. District Rule 8071 - Unpaved Vehicle/Equipment Traffic Area

The purpose of this rule is to limit fugitive dust emissions from unpaved vehicle and equipment traffic areas by implementing control measures and design criteria.

This rule applies to any unpaved vehicle/equipment traffic area of 1.0 acre or larger.

The following condition will ensure compliance with this rule:

- Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 or Rule 8011. [District Rules 8071 and 8011]

Permit Unit(s)	Condition Number(s)
S-1131-0	35

Y. 40 CFR Part 60, Subpart GG, Standards of Performance for Stationary Gas Turbines

40 CFR Part 60 Subpart GG applies to all stationary gas turbines with a heat input greater than 10.7 gigajoules per hour (10 MMBtu/hr), that commence construction, modification, or reconstruction after 10/03/77. The stationary gas turbines listed on permits S-1131-1037, '-1038, and '-1039 have a heat input greater than 10.2 MMBtu/hr and were issued permits to construct by the Kern County APCD 6/19/86; therefore this subpart is applicable to these turbines.

§60.332 Standard for NOx:

This section lists standards for NO_X. Section 60.332(b) and (e) thru (l) do not apply to any of the units at this stationary source. Turbines listed on permits S-1131-1038 and '-1039 are required to comply with the NO_X calculation method listed under §60.332(a)(2) per §60.332(d) and §60.332(c). The turbine listed on permit S-1131-1037 has the option of complying with either §60.332(a)(1) or (a)(2).

NO_X limits will therefore be calculated using the method outlined in §60.332(a)(2) as follows:

$$STD = 0.0150\frac{(14.4)}{Y} + F \text{; where}$$

STD = allowable ISO corrected NO_X emission concentration in % by volume @ 15% O_2 on dry basis

Y = manufacturer's rated heat rate at manufacturer's rated peak load (kilojoules per watt hour), or actual measured heat rate based on lower heating value of fuel as measured at actual peak load for the facility. The value of Y shall not exceed 14.4 kilojoules per watt hour, and

F = NO_X emission allowance for fuel-bound nitrogen as defined in paragraph (a)(4) of this section (Chevron has elected to not use this optional F value).

For example, unit under permit S-1131-1037,

Heat input rate = 249×10^6 Btu/hr
Power Rating = 20 MW

$$Y = \left(249\times10^6\,\frac{Btu}{hr}\right)\times\left(\frac{1\,kJ}{0.9478\,Btu}\right)\times\left(\frac{1}{3.725\times10^6\,w}\right) = 70.5\,\frac{kJ}{w\text{-}hr}$$

Since Y exceeds 14.4 kJ/w-hr, Y is set equal to 14.4 kJ/w-hr. Completing the calculation yields:

$$STD = 0.0150\frac{(14.4)}{14.4} + 0 = 0.015\ \%\ \text{by volume @ 15\% } O_2\ (150\ \text{ppmv @ 15\% } O_2)$$

Similarly, NOx emissions standards for other units will be identical. NOx standards are summarized in the following table.

NSPS NO_X Limits			
Permit #	**Y**	**F**	**STD (ppmv @ 15% O_2)**
S-1131-1037	4.4	0	150
S-1131-1038	14.4	0	150
S-1131-1039	14.4	0	150

Chevron is required to demonstrate compliance with 5 ppmvd @ 15% O_2 for permit S-1131-1037 and 35 ppmvd @ 15% O_2 for permits '-1038 and '-1039 (currently dormant for Rule 4703). Therefore, each unit is expected to operate in compliance with the NOx standards.

The following conditions will be listed on the permits to ensure compliance:

- NOx emission rate (one hour average) shall not exceed the NSPS standard of 150 ppmvd @ 15% O2. [40 CFR 60.332(a)]

Permit Unit(s)	Condition Number(s)
S-1131-1037	13
S-1131-1038 and '-1039	14

§60.333 Standard for SOx:

Section 60.333(a) requires that emissions of sulfur dioxide shall not exceed 0.015 percent by volume dry @ 15% O_2 (150 ppmvd @ 15% O_2).

The 150 ppmvd @ 15% O_2 limit specified in §60.333(a) is converted to lb-SO_2/MMBtu as follows:

$$\frac{\left(150\times10^{-6}\right)\times\left(8{,}578\frac{ft^3}{MMBtu}\right)\times\left(64\frac{lb-SO_2}{lb-mol}\right)\times\left(\frac{20.95}{20.95-15}\right)}{\left(379.5\frac{ft^3}{lb-mol}\right)} = 0.764\frac{lb-SO_2}{MMBtu}$$

The current emission factor for SO_X is compared with the NSPS limit in the following table for these units:

NSPS SO_X Limits		
Permit #	**Emission Factor (lb-SOx/MMBtu)**	**NSPS Limit (lb-SO_2/MMBtu)**
S-1131-1037	0.005	0.764
S-1131-1038	0.006	0.764
S-1131-1039	0.006	0.764

For each unit, the permitted emission factors are significantly less than that of the maximum allowable emission standards.

Section 60.333(b) requires that no turbine subject to this subpart burn fuel that contains sulfur in excess of 0.8 percent by weight (8,000 ppmw). Since any sulfur introduced into the turbine will result in SO_X emissions (there is no sulfur control on any of these permits) the lb-SO_X/MMBtu limit will ensure compliance with this section (startup and shut down periods are not expected to affect sulfur emissions or fuel sulfur levels as the same fuel will be used).

The following conditions will ensure compliance with these sections:

- Except during periods of startup/shutdown, emission rates shall not exceed any of the following: PM10: 0.013 lb/MMBTU, SOx (as SO2): 0.005 lb/MMBTU, or VOC: 0.040 lb/MMBTU. [40 CFR 60.333(a) and (b) and District Rules 2201]

Permit Unit(s)	Condition Number(s)
S-1131-1037	12

- Except during periods of startup/shutdown, emission rates (3-hour rolling average) shall not exceed any of the following: PM10: 0.0128 lb/MMBTU, SOx (as SO2): 0.006 lb/MMBTU, NOx (as NO2): 0.129 lb/MMBTU or 38 ppmvd @ 15% O2, VOC: 0.035 lb/MMBTU, or CO: 40 ppmvd @ 15% O2. [40 CFR 60.333(a) and (b) and District Rules 2201; and 4703]

Permit Unit(s)	Condition Number(s)
S-1131-1038 and '-1039	13

§60.334 Monitoring of Operations

Section 60.334(a) does not apply to units following §60.334(b). These unit have CEMs installed to monitor NO_X and O_2; therefore this section does not apply.

Section 60.334(b) states that the owner or operator of a stationary gas turbine constructed between October 3, 1977 and July 8, 2004 and using water or steam to control NO_X emissions may, as an alternative to operating the continuous emissions

monitoring system to monitor and record the fuel consumption and the ratio of water or steam to fuel being fired in the turbine, can install, calibrate, certify, maintain, operate, and quality-assure a continuous monitoring system (CEMS) consisting of NO_X and O_2 monitors.

These turbines were constructed between October 3, 1977 and July 8, 2004 and have CEMS installed to measure NO_X, CO, and O_2 concentrations. The following conditions will be listed on the permits to ensure compliance with this section:

- The owner or operator shall certify, maintain, operate, and quality-assure a continuous emission monitor system (CEMS) which continuously measures and records the exhaust gas NOx, CO, and O2 concentrations. Continuous emissions monitors shall be capable of monitoring emissions during normal operating conditions and during startups and shutdowns, provided that CEMS pass the relative accuracy requirements and performance specifications of: 40 CFR Part 60, Appendix B and F; 40 CFR Part 51, Appendix P; Performance Specification 2 (PS-2); and District approved protocol for startups. If relative accuracy of CEMS cannot be demonstrated during the startup, CEMS results during startup and shutdown events shall be replaced with startup emission rates obtained from the source test conducted by the facility to determine compliance with emission limits contained in this document. [40 CFR 60.334(b)(1); 40 CFR 64; and District Rules 1080, 6.7; and 4703, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-1037	22
S-1131-1038 and '-1039	36

Section 60.334(b)(1) requires that CEMs be maintained and calibrated according to 40 CFR 60 Appendix B. The following conditions will ensure compliance with this section:

- The owner or operator shall certify, maintain, operate, and quality-assure a continuous emission monitor system (CEMS) which continuously measures and records the exhaust gas NOx, CO, and O2 concentrations. Continuous emissions monitors shall be capable of monitoring emissions during normal operating conditions and during startups and shutdowns, provided that CEMS pass the relative accuracy requirements and performance specifications of: 40 CFR Part 60, Appendix B and F; 40 CFR Part 51, Appendix P; Performance Specification 2 (PS-2); and District approved protocol for startups. If relative accuracy of CEMS cannot be demonstrated during the startup, CEMS results during startup and shutdown events shall be replaced with startup emission rates obtained from the source test conducted by the facility to determine compliance with emission limits contained in this document. [40 CFR 60.334(b)(1); 40 CFR 64; and District Rules 1080, 6.7; and 4703, 6.2]

Permit Unit(s)	Condition Number(s)
S-1131-1037	22
S-1131-1038 and '-1039	36

Section 60.334(b)(2) and (3) requires that CEMS be operated according to 40 CFR 60.13. The following condition will ensure compliance with this section:

- CEMS shall complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each 15-minute quadrant of the hour or shall meet equivalent specifications established by mutual agreement of the District, the ARB and the EPA. [40 CFR 60.334(b)(2); 40 CFR 64; and District Rule 1080]

- Results of continuous emission monitoring shall be averaged in accordance with the requirements of 40 CFR 60.13. [40 CFR 60.334(b)(3) and 40 CFR 64]

Permit Unit(s)	Condition Number(s)
S-1131-1037	27, 28
S-1131-1038 and '-1039	41, 44

Section 60.334(c) is an optional requirement to use CEMS. The turbines are already equipped with CEMS; therefore this requirement is not applicable.

Section 60.334(d), (e), and (f) apply to turbines constructed after July 8, 2004. These turbines were all constructed before this date; therefore this section is not applicable.

Section 60.334(g) applies to steam or water to fuel ratio parameter continuous monitors. These turbines do not continuously monitor these parameters as they are equipped with CEMS; therefore this section is not applicable.

Section 60.334(h)(3)(i) and (ii) requires the owner or operator to keep sulfur content records using valid purchase contract, tariff sheet or transportation contract for the gaseous fuel, specifying that the maximum sulfur content of the fuel is 20 grains/100 scf or less or perform a representative fuel sampling to show the sulfur content of gaseous fuel does not exceed 20 grains/100 scf.

Section 60.334(i) allows operators to monitor sulfur on custom schedules.

The following condition will ensure compliance with these sections:

- If the turbine is not fired on PUC-regulated or FERC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334(h)(3) and (i)(3)(i)]

Permit Unit(s)	Condition Number(s)
S-1131-1037	29
S-1131-1038 and '-1039	30

Section 60.334(i)(3)(D) requires daily monitoring of fuel sulfur content when it exceeds 0.8 percent by weight (8,000 ppmw). The following condition will ensure compliance with this section:

- Operator shall submit a semiannual report listing any daily period during which the sulfur content of the fuel being fired in the gas turbine exceeds 0.8% by weight. [40 CFR 60.334(i)(3)(D)]

Permit Unit(s)	Condition Number(s)
S-1131-1037	48
S-1131-1038 and '-1039	43

Section 60.334(j)(1)(i) and (ii) list requirements for turbines using water or steam to fuel ratio monitoring and for turbines using an F value for the equation used in §60.332. This facility uses neither; therefore these section are not applicable.

Section 60.334(j)(1)(iii)(A) defines excess NO_X emissions as any unit-operating hour in which the 4-hour rolling average NO_X concentration exceeds the NO_X emission limit calculated in §60.332.

These units are all required to operate well under this 150 ppmvd limit; therefore the following conditions will ensure compliance:

Chevron has proposed to demonstrate compliance with NO_X emissions of 5 ppmvd @ 15% O_2 on 3-hour rolling average basis, which is considered to be more stringent than the NSPS limit (given above under §60.332 Standard for NO_X for each turbine) over 4-hour rolling average period. Therefore, it is not necessary to define excess NO_X emissions separately.

Section 60.334(j)(1)(iii)(B) defines a period of monitor downtime shall be any operating hour in which sufficient data are not obtained to validate the hour for either NO_X concentration or diluent (or both).

- Monitor downtime for NOx shall be any unit operating hour in which sufficient data are not obtained to validate the hour for either NO_X concentration or diluent O2 (or both). [40 CFR 60.334(j)1)(iii)(B)]

Permit Unit(s)	Condition Number(s)
S-1131-1037	31
S-1131-1038 and '-1039	38

Section 60.334(j)(2)(i) states for samples of gaseous fuel and for oil samples obtained using daily sampling, flow proportional sampling, or sampling for the unit's storage tank, excess sulfur dioxide emissions occur each unit operating hour included in the period beginning on the date and hour of any sample for which sulfur content of the fuel fired in the gas turbine exceeds 0.8% (by weight) and ending on the date and hour that a subsequent sample is taken that demonstrate compliance with the sulfur limit.

These permits have a SO_X emissions rate of 0.005 lb/MMBtu and 0.006 lb/MMBtu, which are less than 0.702 lb/MMBtu (0.8 lb-S/100 lb-fuel x 64 lb-SO_2/32 lb-S x 0.0439 lb-fuel/ft^3 x ft3/1,000 Btu x 10^6 Btu/MMBtu). Therefore, it is not necessary to define a less stringent limit.

Section 60.334(j)(2)(ii) defines excess sulfur dioxide emissions when each delivery of fuel oil has been selected. These turbines are fired exclusively on gaseous fuel. Thus, requirements of this section are not applicable.

Section 60.334(j)(2)(iii) defines monitor downtime for sulfur dioxide emissions occur when a required sample is not taken by its due date. Monitor downtime also begins if invalid results are obtained for a fuel sample.

Chevron is not using sulfur dioxide monitors, and the turbines are exclusively fired on natural gas fuel. Therefore, it is not necessary to define monitor down for sulfur dioxide emissions.

Section 60.334(j)(5) requires the owner or operator to postmark the reports required under §60.7(c) by the 30^{th} day following the end of each 6-month period. The permittee is required to submit quarterly reports, as it is required by District Rule 1080. Thus, compliance is expected with this section.

- The owner or operator shall submit a written report of CEMS operations for each calendar quarter to the District. The report is due on the 30th day following the end of the calendar quarter and shall include the following: Time intervals, data and magnitude of excess NOx emissions, nature and the cause of excess (if known), corrective actions taken and preventive measures adopted; Averaging period used for data reporting corresponding to the averaging period specified in the emission test period used to determine compliance with an emission standard; Applicable time and date of each period during which the CEM was inoperative, except for zero and span checks, and the nature of system repairs and adjustments; A negative declaration when no excess emissions occurred. [40 CFR 60.334(j)(5); 40 CFR 64; and District Rule 1080]

Permit Unit(s)	Condition Number(s)
S-1131-1037	32
S-1131-1038 and '-1039	45

§60.335 Test Methods and Procedure

Section 60.335(a) states that the owner or operator shall conduct the performance tests required in §60.8 using EPA Method 20, ASTM D6522-00 or EPA Method 7E and either EPA Method 3 or 3A to determine NO_X and diluent concentration. Sampling traverse points are to be selected following Method 20 or Method 1.

Section 60.335(b)(1) states that for each run of the performance test, the mean nitrogen oxide emission concentration @ 15% O_2 shall be corrected to ISO standard conditions using the equation listed in this section to demonstrate compliance with NSPS NO_X standard. NO_X correction to ISO standard is optional for units equipped with add-on emissions control devices. Therefore, ISO correction is required.

The following condition will ensure compliance with these sections:

- The following test methods shall be used: NOx - EPA Method 7E or 20; CO - EPA Method 10 or 10B; Ammonia - BAAQMD ST-1B; O2 - EPA Method 3, 3A, or 20; and HHV and LHV – ASTM D3588-91, ASTM 1826-88, or ASTM 1945-81. EPA approved alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [40 CFR 60.335(a) and (b)(1) and District Rules 1081; and 4703, 6.4]

Permit Unit(s)	Condition Number(s)
S-1131-1037	26
S-1131-1038 and '-1039	32

Section 60.335(b)(2) applies to initial performance testing as required by §60.8. These permit units are in operation; therefore, initial source testing is not required and this section is not applicable.

Section 60.335(b)(3) states that for a combined cycle turbine system with duct burner, the owner may elect to measure turbine NO_X emissions after the duct burner rather than directly after turbine. The turbines under this project are not equipped with supplemental heat or duct burner. Therefore, no further discussion is required.

Section 60.335(b)(4) states that if water or steam injection is used to control NO_X with no additional post-combustion NO_X control and the owner or operator chooses to monitor the steam or water to fuel ratio then that monitoring system must be operated with each performance test run to determine the fuel consumption and the steam or water to fuel ratio to demonstrate on-going compliance with the NO_X standard.

The turbine listed on S-1131-1037 is is equipped with an SCR system, and turbines listed on S-1131—1037, '-1038, and '-1039 have operational CEMS to directly measure NO_X, CO and O_2 concentrations. Therefore, the permittee is not required to monitor fuel consumption and water or steam injection during a performance test.

Section 60.335(b)(5) states that if the owner elects to claim an emission allowance for fuel bound nitrogen, then concurrently with each reference method run, a representative sample of the fuel used shall be collected and analyzed following the applicable procedure described in §60.335(b)(9). These data shall be used to determine the maximum fuel nitrogen content for which the established water or steam to fuel ratio will be valid. The operator has not claimed any allowance for fuel bound nitrogen; therefore this section is not applicable.

Section 60.335(b)(6) states that if the owner or operator elects to install a CEMS, the performance evaluation of CEMS may either be conducted separately or as part of the initial performance test of the affected unit as described in paragraph (b)(7). These permit units are in operation; therefore, initial source testing is not required and this section is not applicable.

Section 60.335(b)(7), (b)(8), and (b)(9) are not applicable to the turbines in this project.

Section 60.335(b)(10) if the owner or operator is required to determine the sulfur content of the fuel combusted in the turbine then a minimum of three fuel samples shall be collected during the performance test.

Section 60.335(b)(11) allows the fuel analysis to be performed by the owner or operator, service contractor, fuel vendor, or any other qualified agency.

The following conditions will be placed on the permit:

- If the turbine is not fired on PUC-regulated or FERC-regulated natural gas, then a fuel sample shall be collected during the source test to determine the sulfur content of the fuel combusted in the turbine. The fuel sample shall be analyzed for the total sulfur content using ASTM D1072; D3246; D4084; D4468; D6228; or D6667; or double GC for H2S and mercaptans. The applicable ranges of some ASTM methods are not adequate to measure the levels of sulfur in some fuel gases. Dilution of samples before analysis (with verification of dilution ratio) may be used after getting a prior approval from the District [40 CFR 60.335(b)(10)]

Permit Unit(s)	Condition Number(s)
S-1131-1037	30
S-1131-1038 and '-1039	31

Section 60.335(c) allows the operator to develop an ambient condition correction factor instead of using the equation in paragraph (b)(1) of this section. The operator has not requested any correction factor be developed; therefore this section is not applicable.

Z. 40 CFR Part 60, Subpart IIII, Standards of Performance for Stationary Compression Ignition Internal Combustion Engines

The purpose of 40 CFR 60 Subpart IIII is to establish New Source Performance Standards (NSPS) to reduce emissions of NO_X, SO_X, PM, CO, and VOC from new stationary compression ignition (CI) internal combustion (IC) engines.

Pursuant to **Section 60.4200**, these standards apply to stationary CI engines that were manufactured after April 1, 2006 and stationary CI engines that were modified (as defined in 40 CFR 60.2) or reconstructed after July 11, 2005.

The engines listed on permits S-1131-833 and '-1084 were manufactured prior to April 1, 2006. These engines have not been modified or reconstructed since July 11, 2005. Therefore, 40 CFR 60 Subpart IIII does not apply to these engines.

Engines listed on permits S-1131-1117 and '-1119 were manufactured after April 1, 2006 and are subject to this subpart.

Section 60.4202 of this subpart requires that Engine(s) meet the appropriate Subpart IIII emission standards for new engines, based on the model year, size, and number of liters per cylinder.

These engines are all certified to the latest EPA Tier Certification level for the applicable horsepower range, guaranteeing compliance with the emission standards of Subpart IIII.

The following conditions will ensure compliance with this section:

- Emissions from this IC engine shall not exceed any of the following limits: X.XX g-NOx/bhp-hr, X.XX g-CO/bhp-hr, or X.XX g-VOC/bhp-hr. [District Rule 2201; 13 CCR 2423; 17 CCR 93115; and 40 CFR 60 Subpart IIII]

- Emissions from this IC engine shall not exceed X.XX g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201; 4102; 13 CCR 2423; 17 CCR 93115; and 40 CFR 60 Subpart IIII]

Permit Unit(s)	Condition Number(s)
S-1131-1117	11 and 12
S-1131-1119	6 and 7

Section 60.4207 of this subpart requires that Engine(s) be fired on 500 ppm sulfur content fuel or less, and fuel with a minimum centane index of 40 or a maximum aromatic content of 35 percent by volume. Starting in October 1, 2010, the maximum allowable sulfur fuel content will be lowered to 15 ppm.

These engines are restricted to CARB certified diesel fuel, which meets all of the fuel requirements listed in Subpart IIII.

The following condition will ensure compliance with this section:

- Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201; 4801, 3.1; 17 CCR 93115; and 40 CFR 60 Subpart IIII]

Permit Unit(s)	Condition Number(s)
S-1131-1117	9
S-1131-1119	5

Section 60.4209 of this subpart requires that The operator/owner must install a non-resettable hour meter prior to startup of the engine(s).

These engines are equipped with a non-resettable hour meter.

The following condition will ensure compliance with this section:

- This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 5.7; 17 CCR 93115; and 40 CFR 60 Subpart IIII]

Permit Unit(s)	Condition Number(s)
S-1131-1117	2
S-1131-1119	13

Section 60.4211(f) of this subpart requires that Emergency engine(s) may be operated for the purpose of maintenance and testing up to 100 hours per year. There is no limit on emergency use.

Engine S-1131-1117 is an emergency engine, '-1119 is not; therefore this section is applicable to the engine listed on S-1131-1117. The Air Toxic Control Measure for Stationary Compression Ignition Engines (Stationary ATCM) limits this engine maintenance and testing to 50 hours/year.

The following condition will ensure compliance with this section:

- This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702, 3.15; 17 CCR 93115; and 40 CFR 60 Subpart IIII]

Permit Unit(s)	Condition Number(s)
S-1131-1117	6

Section 60.4211(g) of this subpart requires the owner/operator to operate and maintain the engine(s) and any installed control devices according to the manufacturers written instructions.

The following condition will ensure compliance with this section:

- This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702, 5.7; and 40 CFR 60 Subpart IIII]

Permit Unit(s)	Condition Number(s)
S-1131-1117	10
S-1131-1119	11

AA. 40 CFR Part 60, Subpart KKKK, Standards of Performance for Stationary Combustion Turbines

The EPA promulgated this new NSPS that would apply to new stationary combustion turbines greater than or equal to 1 MW that commence construction, modification or reconstruction after February 18, 2005. Gas turbines listed on permits S-1131-1037, '-1038, and '-1039 were constructed before February 18, 2005 and have not been modified (as defined in 40 CFR Part 60, Subpart A, Section 14) or reconstructed since this date. Therefore requirements of this NSPS are not applicable.

BB. 40 CFR 63, Subpart ZZZZ - National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines

Engines are subject to this subpart if they are operated at a major or area source of Hazardous Air Pollutant (HAP) emissions. A major source of HAP emissions is a facility that has the potential to emit any single HAP at a rate of 10 tons/year or greater or any combinations of HAPs at a rate of 25 tons/year or greater. This stationary source is considered a major source of HAP emissions; therefore engines listed on permits S-1131-833, '-1084, '-1117, and '-1119 are subject to this subpart.

40 CFR 63 Subpart ZZZZ requires the following engines to comply with 40 CFR 60 Subpart IIII:

1. New emergency engines located at area sources of HAPs
2. Emergency engines rated less than or equal to 500 bhp and located at major sources of HAPs

Engines listed on permits S-1131-833, '-1084, and '-1117 are stationary RICE rated less than or equal to 500 bhp and are located at a major area source of HAP emissions; therefore, these engines must comply with 40 CFR 60 Subpart IIII (discussed separately in the corresponding section).

Additionally, 40 CFR 63 Subpart ZZZZ requires engines rated greater 500 bhp and located at major sources of HAPs to meet the notification requirements of §63.6645(h); however, that section only applies if an initial performance test is required. The engine listed on permit S-1131-1119 is rated greater than 500 bhp and located at a major HAP source; however, an initial performance test was not required for this engine, the notification requirement is not applicable.

CC. 40 CFR 63, Subpart DDDDD — National Emission Standards for Hazardous Air Pollutants for Industrial, Commercial, and Institutional Boilers and Process Heaters

This subpart applies to major HAP sources as defined in either 40 CFR 63.2 or 63.761.

A major HAP Source is defined in 40 CFR Part 63.2 as a source emitting hazardous pollutants (as defined in 112b) in excess of 10 tons per year of any hazardous air pollutant or 25 tons per year of any combination of hazardous air pollutants.

40 CFR 63.761 defines a Major Source as the same as in Section 63.2 except that, for production field facilities only HAP emissions from glycol dehydration units and

storage vessels with the potential for flash emissions shall be aggregated for a major source determination.

Chevron does not have the potential to emit from glycol dehydration units and storage vessels (only Rule 4623 exempt front-line tanks would have the capacity to flash).

DD. 40 CFR Part 82, Subpart B and F — Stratospheric Ozone

These regulations apply to servicing motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC). Sections of this regulation were amended in 2004 and 2008.

The following conditions assure compliance with these requirements:

- If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B]

- If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F]

Permit Unit(s)	Condition Number(s)
S-1131-0	28 and 29

EE. 40 CFR Part 64 — Compliance Assurance Monitoring (CAM)

40 CFR Part 64 requires Compliance Assurance Monitoring (CAM) for units that meet the following three criteria:

1) the unit must have an emission limit for the pollutant;
2) the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
3) the unit must have a pre-control potential to emit of greater than the major source thresholds.

Major Source Thresholds (4/21/11 Revision of Rule 2201)

Pollutant	lb/year	ton/year
NO_X	20,000	10
SO_X	140,000	70
PM_{10}	140,000	70
$PM_{2.5}$	200,000	100
CO	200,000	100
VOC	20,000	10

a. S-1131-598 — Fixed Roof Tank with Vapor Recovery System and Sulfur Removal System

This permit unit has an emissions limit for fugitive VOC but it does not have add-on controls for this criteria pollutant. Therefore, this permit unit is not subject to CAM for VOC.

This unit has add-on controls in the form of a sulfur removal system but does not have an emissions limit for SOx. Therefore, this unit is not subject to CAM for SOx, nor is it subject to CAM for any other pollutant.

b. S-1131-608, '-613, '-629, '-630, '-638, '-641, '-650, '-651, '-885, '-886, '-891, '-892, '-1049, '-1050, and '-1097 — Fixed Roof Tanks with Vapor Recovery System

§64.1 defines a control device as equipment, other than inherent process equipment, that is used to destroy or remove air pollutants prior to discharge to the atmosphere.

These permit units are not subject to CAM since the vapor recovery system does not meet CAM's definition of a control device. The vapor recovery system consists of a vapor return or condensation system that connects to a gas pipeline distribution system which does not destroy or remove air pollutants prior to discharge to the atmosphere.

c. S-1131-448, '-460, '-509, '-529, '-530, '-531, '-586, '-592, '-594, '-599, '-600, '-601, '-602, '-603, '-606, '-610, '-615, '-619, '-620, '-621, '-622, '-623, '-625, '-626, '-627, '-628, '-631, '-632, '-633, '-634, '-635, '-636, '-652, '-663, '-670, '-671, '-702, '-861, '-862, '-961, '-962, '-963, '-964, and '-1091 — Fixed Roof Tanks

These permit units are not subject to CAM since the units do not have add-on controls.

a. S-1131-943 — 62.5 MMBtu/hr Gas-Fired Steam Generator

This permit unit has emissions limits for NO_X, SO_X, PM_{10}, CO, and VOC but does not have add-on controls for these criteria pollutants. Additionally, this unit is dormant. Therefore, this permit unit is not subject to CAM for NO_X, SO_X, PM_{10}, CO, and VOC.

e. S-1131-1019 — 2.7 MMBtu/hr Gas-Fired Heater Treater

This permit unit has emissions limits for NO_X, SO_X, PM_{10}, CO, and VOC but does not have add-on controls for these criteria pollutants. Therefore, this permit unit is not subject to CAM for NO_X, SO_X, PM_{10}, CO, and VOC.

f. S-1131-941 — 27.5 MMBtu/hr Steam Generator with Low NOx burner and FGR

This is a dormant emission unit and will be required to comply with all current district and federal rules upon any modifications resulting in the dormant status being removed.

g. S-1131-62, '-63, '-64, '-65, '-66, '-67, '-68, '-69, '-70, '-73, '-77, '-78, '-82, '-94, '-95, '-98, '-99, '-858, '-859, '-877, '-879, '-880, '-881, '-884, '-908, '-912, '-966, '-976, '-987, '-992, '-993, '-994, '-997, '-998, '-998, '-999, '-1000, '-1001, '-1002, '-1003, '-1004, '-1016, — 62.5 MMBtu/hr Steam Generators with Low NOx burners and FGR

Except for dormant emission units S-1131-65, '-77, '-94, '-858, '-966, '-976, '-992, '-993, '-994, '-998, '-1000, '-1001, '-1002, '-1003, '-1004, and '-1016 these steam generators are equipped with FGR, are currently operating in compliance with Rule 4603, and are therefore required to meet the NOx emissions limit of 0.018 lb/MMBtu. To assess whether CAM is triggered the emissions factor corresponding to pre add-on (FGR) was calculated.

AP-42 Table 1.4-1 (7/98) lists the following emissions factors for small boilers < 100 MMBtu/hr:

	Emissions Factor ($lb/10^6$ scf)
Uncontrolled	100
Controlled – low NOx burners	50
Controlled – Low NOx burners/Flue gas recirculation	32

The control efficiency of FGR and corresponding emissions factors are

$$100\%\ x\ \frac{\left(\frac{50\ lb}{10^6}-\frac{32\ lb}{10^6}\right)}{\frac{50\ lb}{10^6}}=36\%$$

$$\frac{\left(\frac{0.018\ lb\cdot NO_X}{MMBtu}\right)}{\left(1-\frac{0.036\ lb\cdot NO_X}{MMBtu}\right)}=\frac{0.028\ lb\cdot NO_X}{MMBtu}$$

Using these factors, the pre add-on control emissions can be calculated as:

$$\frac{0.028\ lb\cdot NO_X}{MMBtu}\left(\frac{62.5\ MMBtu}{hr}\right)\frac{8{,}760\ hr}{yr}\left(\frac{ton}{2{,}000\ lb}\right)=7.7\ \frac{tons}{yr}<10\ \frac{tons}{yr}$$

As pre-control annual emissions are less than 10 tons/yr enhanced CAM monitoring is not required.

Dormant emission units will be required to comply with all current district and federal rules (including Rule 4306 that will ensure compliance with this section) upon any modifications resulting in the dormant status being removed.

h. S-1131-716, '-903, '-909, '-917, '-932, '-944, '-958, '-995, '-996, '-1007, '-1010, '-1011, '-1012, '-1013, '-1014, '-1017, '-1031, '-1032, '-1033, '-1035, '-1036, '-1048, '-1106 — Thermally Enhanced Oil Recovery Operations

§64.1 defines a control device as equipment, other than inherent process equipment, that is used to destroy or remove air pollutants prior to discharge to the atmosphere.

These permit units are not subject to CAM since the casing gas collection system, where one is installed, does not meet CAM's definition of a control device. The casing gas collection system consists of piping that connects to a gas pipeline distribution system which does not destroy or remove air pollutants prior to discharge to the atmosphere.

i. S-1131-1008 — Thermally Enhanced Oil Recovery Operation with H2S Scrubbing System

This permit unit has an emissions limit for fugitive VOC but it does not have add-on controls for this criteria pollutant. Therefore, this permit unit is not subject to CAM for VOC.

This unit has add-on controls in the form of a sulfur removal system but does not have an emissions limit for SOx. Therefore, this unit is not subject to CAM for SOx, nor is it subject to CAM for any other pollutant.

j. S-1131-1037 — 249.0 MMBtu/hr Gas-Fired Turbine Engine Cogeneration System

This permit unit has emissions limits for SO_X, VOC, and PM_{10} but it does not have add-on controls for these criteria pollutants. Therefore, this permit unit is not subject to CAM for SO_X, VOC or PM_{10}.

This permit unit has an emissions limit for NO_X, has an add-on control for this criteria pollutant, and with post control emissions greater than major source thresholds pre-control emissions will be greater than these thresholds as well; therefore, these permits are subject to CAM for NO_X emissions.

This permit unit complies with CAM for NO_X with the use of a continuous emission monitor (CEM) for NO_X. The following conditions will be listed on the permit to ensure compliance:

- Cogeneration system shall include General Electric model LM-2500PE gas turbine, generator set rated at 22.89 MW, turbine combustor and compressor water injection systems, SCR, CO catalyst, and CEM's for NOx, CO, & O2. [40 CFR 64 and District Rule 2201]
- CEM equipment shall be maintained and calibrated according to EPA guidelines specified in CFR Part 60, Appendix B. [40 CFR 60.334 (b); 40 CFR 60; and District Rule 1080]
- The owner or operator shall certify, maintain, operate, and quality-assure a continuous emission monitor system (CEMS) which continuously measures and records the exhaust gas NOx, CO, and O2 concentrations. Continuous emissions monitors shall be capable of monitoring emissions during normal operating conditions and during startups and shutdowns, provided that CEMS pass the relative accuracy requirements and performance specifications of: 40 CFR Part 60, Appendix B and F; 40 CFR Part 51, Appendix P; Performance Specification 2 (PS-2); and District approved protocol for startups. If relative accuracy of CEMS cannot be demonstrated during the startup, CEMS results during startup and shutdown events shall be replaced with startup emission rates obtained from the source test conducted by the facility to determine compliance with emission limits contained in this document. [40 CFR 60.334(b)(1); 40 CFR 64; and District Rules 1080, 6.7; and 4703, 6.2]
- CEMS shall complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each 15-minute quadrant of the hour or shall meet equivalent specifications established by mutual agreement of the District, the ARB and the EPA. [40 CFR 60.334(b)(2); 40 CFR 64; and District Rule 1080]

- Results of continuous emission monitoring shall be averaged in accordance with the requirements of 40 CFR 60.13. [40 CFR 60.334(b)(3) and 40 CFR 64]

- The owner or operator shall submit a written report of CEMS operations for each calendar quarter to the District. The report is due on the 30th day following the end of the calendar quarter and shall include the following: Time intervals, data and magnitude of excess NOx emissions, nature and the cause of excess (if known), corrective actions taken and preventive measures adopted; Averaging period used for data reporting corresponding to the averaging period specified in the emission test period used to determine compliance with an emission standard; Applicable time and date of each period during which the CEM was inoperative, except for zero and span checks, and the nature of system repairs and adjustments; A negative declaration when no excess emissions occurred. [40 CFR 60.334(j)(5); 40 CFR 64; and District Rule 1080]

- The continuous NOx monitoring system shall meet the performance specification requirements in 40 CFR 60, Appendix F, 40 CFR 51, Appendix P, and Part 60, Appendix B, or shall meet equivalent specifications established by mutual agreement of the District, the ARB, and the EPA. [40 CFR 64 and District Rule 1080, 6.7]

- Results of continuous emissions monitoring must be reduced according to the procedure established in 40 CFR, Part 51, Appendix P, paragraphs 5.0 through 5.3.3, or by other methods deemed equivalent by mutual agreement with the District, the ARB, and the EPA. [40 CFR 64 and District Rule 1080]

- Results of continuous emission monitoring must be averaged in accordance with the requirements of 40 CFR 60.13. [40 CFR 60.334(j),(j)(5); 40 CFR 64; and District Rule 4703, 5.1]

- Records shall be maintained and shall contain: the occurrence and duration of any start-up, shutdown or malfunction, performance testing, evaluations, calibrations, checks, adjustments, maintenance of any CEM's that have been installed pursuant to District Rule 1080, and emission measurements. [40 CFR 60.7 (b); 40 CFR 64; and District Rule 1080]

- The APCO shall be notified no later than eight hours after the detection of a breakdown of the CEM. The operator shall inform the APCO of the intent to shut down the CEM at least 24 hours prior to the event. [40 CFR 64 and District Rule 1080, 10.0]

Permit Unit(s)	Condition Number(s)
S-1131-1037	1, 8, 22, 27, 28, 32, 34, 41, 42, 44, and 50

k. S-1131-1038 and '-1039 — 58.2 MMBtu/hr Gas-Fired Turbine Engine Cogeneration Systems

These permit units have emissions limits for SO_X, VOC, and PM_{10} but do not have add-on controls for these criteria pollutants. Therefore, these permit units are not subject to CAM for SO_X, VOC or PM_{10}.

These permit units have an emissions limit for NO_X, have add-on controls for this criteria pollutant, and with post control emissions greater than major source thresholds pre-control emissions will be greater than these thresholds as well; therefore, these permits are subject to CAM for NO_X emissions.

This permit unit complies with CAM for NO_X with the use of a continuous emission monitor (CEM) for NO_X. The following conditions will be listed on the permit to ensure compliance:

- CEM equipment shall be maintained and calibrated according to EPA guidelines specified in CFR Part 60, Appendix B. [40 CFR 60.334 (b); 40 CFR 60; and District Rule 1080]
- The owner or operator shall certify, maintain, operate, and quality-assure a continuous emission monitor system (CEMS) which continuously measures and records the exhaust gas NOx, CO, and O2 concentrations. Continuous emissions monitors shall be capable of monitoring emissions during normal operating conditions and during startups and shutdowns, provided that CEMS pass the relative accuracy requirements and performance specifications of: 40 CFR Part 60, Appendix B and F; 40 CFR Part 51, Appendix P; Performance Specification 2 (PS-2); and District approved protocol for startups. If relative accuracy of CEMS cannot be demonstrated during the startup, CEMS results during startup and shutdown events shall be replaced with startup emission rates obtained from the source test conducted by the facility to determine compliance with emission limits contained in this document. [40 CFR 60.334(b)(1); 40 CFR 64; and District Rules 1080, 6.7; and 4703, 6.2]
- CEMS shall complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each 15-minute quadrant of the hour or shall meet equivalent specifications established by mutual agreement of the District, the ARB and the EPA. [40 CFR 60.334(b)(2); 40 CFR 64; and District Rule 1080]
- Results of continuous emission monitoring shall be averaged in accordance with the requirements of 40 CFR 60.13. [40 CFR 60.334(b)(3) and 40 CFR 64]

- The owner or operator shall submit a written report of CEMS operations for each calendar quarter to the District. The report is due on the 30th day following the end of the calendar quarter and shall include the following: Time intervals, data and magnitude of excess NOx emissions, nature and the cause of excess (if known), corrective actions taken and preventive measures adopted; Averaging period used for data reporting corresponding to the averaging period specified in the emission test period used to determine compliance with an emission standard; Applicable time and date of each period during which the CEM was inoperative, except for zero and span checks, and the nature of system repairs and adjustments; A negative declaration when no excess emissions occurred. [40 CFR 60.334(j)(5); 40 CFR 64; and District Rule 1080]

- The continuous NOx monitoring system shall meet the performance specification requirements in 40 CFR 60, Appendix F, 40 CFR 51, Appendix P, and Part 60, Appendix B, or shall meet equivalent specifications established by mutual agreement of the District, the ARB, and the EPA. [40 CFR 64 and District Rule 1080, 6.7]

- Results of continuous emissions monitoring must be reduced according to the procedure established in 40 CFR, Part 51, Appendix P, paragraphs 5.0 through 5.3.3, or by other methods deemed equivalent by mutual agreement with the District, the ARB, and the EPA. [40 CFR 64 and District Rule 1080]

- Records shall be maintained and shall contain: the occurrence and duration of any start-up, shutdown or malfunction, performance testing, evaluations, calibrations, checks, adjustments, maintenance of any CEM's that have been installed pursuant to District Rule 1080, and emission measurements. [40 CFR 60.7 (b); 40 CFR 64; and District Rule 1080]

- The APCO shall be notified no later than eight hours after the detection of a breakdown of the CEM. The operator shall inform the APCO of the intent to shut down the CEM at least 24 hours prior to the event. [40 CFR 64 and District Rule 1080, 10.0]

Permit Unit(s)	Condition Number(s)
S-1131-1037	1, 8, 22, 27, 28, 32, 34, 41, 42, 44, and 50
S-1131-1038 and '-1039	9, 35, 36, 39, 40, 41, 44, 45, and 47

I. S-1131-833 — 240 bhp Diesel-Fired Emergency Internal Combustion Engine

This engine does not have any add-on controls for any pollutant that would cause the unit to be subject to these requirements. Therefore, CAM is not required.

m. S-1131-1084 — 83 bhp Gas-Fired Emergency Internal Combustion Engine

This engine does not have any add-on controls for any pollutant that would cause the unit to be subject to these requirements. Therefore, CAM is not required.

n. S-1131-1084 — 480 bhp Diesel-Fired Emergency Internal Combustion Engine

This engine does not have any add-on controls for any pollutant that would cause the unit to be subject to these requirements. Therefore, CAM is not required.

o. S-1131-1084 — 532 bhp Diesel-Fired Transportable Internal Combustion Engine

This engine does not have any add-on controls for any pollutant that would cause the unit to be subject to these requirements. Therefore, CAM is not required.

p. S-1131-724 — Gasoline Dispensing Operation

This unit lists no emissions limits for NO_X, SO_X, PM_{10}, CO or VOC. Therefore, CAM is not applicable to this operation.

q. S-1131-1085, '-1086, and '-1087 — 83.3 MMBtu/hr Transportable Standby Flares

These flares have no add-on controls for any pollutant that would cause these units to be subject to these requirements. Therefore, CAM is not required.

r. S-1131-1108 — 83.0 MMBtu/hr Transportable Low-Use Flare

This flare has no add-on controls for any pollutant that would cause the unit to be subject to these requirements. Therefore, CAM is not required.

IX. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

An updated permit shield for Rules 4201, 4301, 4351, 4406, and 4801 has been added to the revised Steam Generator Permits as follows:

- Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of District Rule 4201 (as amended December 17, 1992), 4301 (as amended December 17, 1992), 4351 (as amended August 21, 2003), 4406 (as amended December 17, 1992), and 4801 (as amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2]

Permit Unit(s)	Condition Number(s)
S-1131-62, '-63, '-64, '-66, '-67, '-68, '-69, '-70, '-73, and '-912	29

All other applicable permit shields have been retained, no other permit shields were requested or added.

X. PERMIT CONDITIONS

See Attachment A - Draft Renewed Title V Operating Permit.

XI. ATTACHMENTS

A. Draft Renewed Title V Operating Permit
B. Previous Title V Operating Permit
C. Detailed Facility List

ATTACHMENT A

Draft Renewed Title V Operating Permit

San Joaquin Valley
Air Pollution Control District

FACILITY: S-1131-0-2 **EXPIRATION DATE:** 02/28/2007

DRAFT

FACILITY-WIDE REQUIREMENTS

1. {1255} The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. {1256} The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. All required source testing shall conform to the compliance testing procedures described in District Rule 1081. [District Rule 1081] Federally Enforceable Through Title V Permit
4. {1257} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
5. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020. [District Rules 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
6. {1259} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
7. {1260} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
8. {1261} Every application for a permit required under Rule 2010 (12/17/92) (Permits Required) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

10. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

11. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

12. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with Section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

13. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit . [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

14. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

15. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

16. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

17. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

18. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

22. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

23. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01), by using EPA method 9. If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101] Federally Enforceable Through Title V Permit
24. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1, 5.2, 5.5, and 5.7] Federally Enforceable Through Title V Permit
25. All VOC-containing materials for architectural coatings subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
26. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
27. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
28. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
29. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit
30. Disturbances of soil related to any construction, demolition, excavation, extraction, or water mining activities shall comply with the requirements for fugitive dust control in SJVUAPCD District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 or Rule 8011. [District Rules 8021 and 8011] Federally Enforceable Through Title V Permit
31. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 or Rule 8011. [District Rules 8031 and 8011] Federally Enforceable Through Title V Permit
32. An owner/operator shall prevent or cleanup any carryout and trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 or Rule 8011. [District Rules 8041 and 8011] Federally Enforceable Through Title V Permit
33. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 or Rule 8011. [District Rules 8051 and 8011] Federally Enforceable Through Title V Permit
34. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 or Rule 8011. [District Rules 8061 and 8011] Federally Enforceable Through Title V Permit
35. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 or Rule 8011. [District Rules 8071 and 8011] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

36. {1288} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

37. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

38. {1290} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

39. {1291} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permit shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92);2070 , section 7.0 (12/17/92); 2080 (12/17/92); 4101 (12/17/92); 4601, sections 5.1, 5.2, 5.4, 5.5, 6.1, and 6.2 (9/17/97); 8020 (4/25/96); 8030 (4/25/96); 8060 (4/25/96); A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

43. When applicable to 40 CFR Part 68, a subject facility shall submit to the proper authority a Risk Management Plan when mandated by the regulation. [40 CFR Part 68] Federally Enforceable Through Title V Permit

44. All permits for facilities S-88, S-511, S-1127, and S-1131 are included in ChevronTexaco Inc.'s Heavy Oil Central stationary source. [District Rule 2201] Federally Enforceable Through Title V Permit

45. On December 31, 2002, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin January 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-62-29 **EXPIRATION DATE:** 02/28/2007

SECTION: 05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS FIRED C.E. NATCO STEAM GENERATOR (HSG# 60-38; DIS# 20630-79) WITH FLUE GAS RECIRCULATION, NORTH AMERICAN MODEL GLE LOW-NOX BURNER, AND NORTH AMERICAN OPTIMIZER

DRAFT

PERMIT UNIT REQUIREMENTS

1. The operator shall fire the unit only on natural gas. The combined sulfur content of all fuels supplied to this steam generator shall not exceed 1.0 gr S/100 scf. [District Rules 2201; and 4320, 5.4] Federally Enforceable Through Title V Permit
2. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rules 2201; and 4320, 5.2] Federally Enforceable Through Title V Permit
3. Emissions from the steam generator shall not exceed any of the following limits: 0.005 lb-PM10/MMBtu or 0.007 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Except during startup and shutdown, emissions shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.018 lb-NOx/MMBtu and 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201; 4305, 5.1; 4306, 5.1; and 4320, 5.2] Federally Enforceable Through Title V Permit
5. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum emissions from the steam generator, including start-up and shutdown periods, shall not exceed any of the following limits: 54.0 lb-NOx/day, 9,855 lb-NOx/year, 55.5 lb-CO/day, and 20,258 lb-CO/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown. [District Rules 4305, 5.5, 6.1; 4306, 5.3, 6.1; and 4320, 5.6, 6.1] Federally Enforceable Through Title V Permit
8. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; 4306, 3.22, 3.25; and 4320, 3.25, 3.29] Federally Enforceable Through Title V Permit
9. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

11. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; and 4306, 6.3] Federally Enforceable Through Title V Permit

12. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

13. If the unit is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. Each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

14. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by test methods referenced in this permit. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; 4306, 6.2; and 4320, 6.2] Federally Enforceable Through Title V Permit

16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

19. Source testing shall be conducted using the methods and procedures approved by the District. Source testing for compliance demonstration shall be conducted by independent testing laboratories, and shall be witnessed, or authorized by District personnel. Sample collection shall be by ARB certified testing laboratory. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

21. Permittee shall submit an analysis to the District demonstrating compliance with the fuel sulfur content and higher heating value within 60 days of startup and at least once every 12 months. The sulfur content and higher heating value of the fuel shall be determined using the test methods referenced in this permit or certified by a third party fuel supplier. [District Rule 4320, 6.2] Federally Enforceable Through Title V Permit

22. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 1081; 2201; 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1; and 4306, 6.1] Federally Enforceable Through Title V Permit

24. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

25. Permittee shall maintain daily records of volume of fuel gas burned, sulfur content as determined by analytical testing or fuel supplier invoices/certifications, and permit number(s) of systems providing gas for incineration. [District Rules 2201; and 4320, 5.2, 5.7] Federally Enforceable Through Title V Permit

26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; 2520, 9.4.2; 4305, 6.1; 4306, 6.1; and 4320, 6.1] Federally Enforceable Through Title V Permit

27. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

28. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of District Rule 4201 (as amended December 17, 1992), 4301 (as amended December 17, 1992), 4351 (as amended August 21, 2003), 4406 (as amended December 17, 1992), and 4801 (as amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.1, 5.3] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-63-24 **EXPIRATION DATE:** 02/28/2007

SECTION: 05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED C.E. NATCO STEAM GENERATOR (HSG#60-39, DIS#20631-79) WITH NORTH AMERICAN GLE LOW-NOX BURNER, FLUE GAS RECIRCULATION (SAN JOAQUIN LOWER)

PERMIT UNIT REQUIREMENTS

1. The operator shall fire the unit only on natural gas. The combined sulfur content of all fuels supplied to this steam generator shall not exceed 1.0 gr S/100 scf. [District Rules 2201; and 4320, 5.4] Federally Enforceable Through Title V Permit
2. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rules 2201; and 4320, 5.2] Federally Enforceable Through Title V Permit
3. Emissions from the steam generator shall not exceed any of the following limits: 0.005 lb-PM10/MMBtu or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Except during startup and shutdown, emissions shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.018 lb-NOx/MMBtu and 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201; 4305, 5.1; 4306, 5.1; and 4320, 5.2] Federally Enforceable Through Title V Permit
5. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum emissions from the steam generator, including start-up and shutdown periods, shall not exceed any of the following limits: 54.0 lb-NOx/day, 9,855 lb-NOx/year, 55.5 lb-CO/day, and 20,258 lb-CO/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown. [District Rules 4305, 5.5, 6.1; 4306, 5.3, 6.1; and 4320, 5.6, 6.1] Federally Enforceable Through Title V Permit
8. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; 4306, 3.22, 3.25; and 4320, 3.25, 3.29] Federally Enforceable Through Title V Permit
9. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

11. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; and 4306, 6.3] Federally Enforceable Through Title V Permit

12. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

13. If the unit is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. Each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

14. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by test methods referenced in this permit. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; 4306, 6.2; and 4320, 6.2] Federally Enforceable Through Title V Permit

16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

19. Source testing shall be conducted using the methods and procedures approved by the District. Source testing for compliance demonstration shall be conducted by independent testing laboratories, and shall be witnessed, or authorized by District personnel. Sample collection shall be by ARB certified testing laboratory. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

21. Permittee shall submit an analysis to the District demonstrating compliance with the fuel sulfur content and higher heating value within 60 days of startup and at least once every 12 months. The sulfur content and higher heating value of the fuel shall be determined using the test methods referenced in this permit or certified by a third party fuel supplier. [District Rule 4320, 6.2] Federally Enforceable Through Title V Permit

22. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 1081; 2201; 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1; and 4306, 6.1] Federally Enforceable Through Title V Permit

24. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

25. Permittee shall maintain daily records of volume of fuel gas burned, sulfur content as determined by analytical testing or fuel supplier invoices/certifications, and permit number(s) of systems providing gas for incineration. [District Rules 2201; and 4320, 5.2, 5.7] Federally Enforceable Through Title V Permit

26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; 2520, 9.4.2; 4305, 6.1; 4306, 6.1; and 4320, 6.1] Federally Enforceable Through Title V Permit

27. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

28. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of District Rule 4201 (as amended December 17, 1992), 4301 (as amended December 17, 1992), 4351 (as amended August 21, 2003), 4406 (as amended December 17, 1992), and 4801 (as amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.1, 5.3] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-64-24 **EXPIRATION DATE:** 02/28/2007

SECTION: 05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED C.E. NATCO STEAM GENERATOR (HSG# 60-40; DIS# 20632-79) WITH FLUE GAS RECIRCULATION, NORTH AMERICAN GLE LOW-NOX BURNER AND NORTH AMERICAN OPTIMIZER

DRAFT

PERMIT UNIT REQUIREMENTS

1. The operator shall fire the unit only on natural gas. The combined sulfur content of all fuels supplied to this steam generator shall not exceed 1.0 gr S/100 scf. [District Rules 2201; and 4320, 5.4] Federally Enforceable Through Title V Permit
2. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rules 2201; and 4320, 5.2] Federally Enforceable Through Title V Permit
3. Emissions from the steam generator shall not exceed any of the following limits: 0.005 lb-PM10/MMBtu or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Except during startup and shutdown, emissions shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.018 lb-NOx/MMBtu and 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201; 4305, 5.1; 4306, 5.1; and 4320, 5.2] Federally Enforceable Through Title V Permit
5. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum emissions from the steam generator, including start-up and shutdown periods, shall not exceed any of the following limits: 54.0 lb-NOx/day, 9,855 lb-NOx/year, 55.5 lb-CO/day, and 20,258 lb-CO/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown. [District Rules 4305, 5.5, 6.1; 4306, 5.3, 6.1; and 4320, 5.6, 6.1] Federally Enforceable Through Title V Permit
8. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; 4306, 3.22, 3.25; and 4320, 3.25, 3.29] Federally Enforceable Through Title V Permit
9. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

11. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; and 4306, 6.3] Federally Enforceable Through Title V Permit

12. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

13. If the unit is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. Each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

14. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by test methods referenced in this permit. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; 4306, 6.2; and 4320, 6.2] Federally Enforceable Through Title V Permit

16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

19. Source testing shall be conducted using the methods and procedures approved by the District. Source testing for compliance demonstration shall be conducted by independent testing laboratories, and shall be witnessed, or authorized by District personnel. Sample collection shall be by ARB certified testing laboratory. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

21. Permittee shall submit an analysis to the District demonstrating compliance with the fuel sulfur content and higher heating value within 60 days of startup and at least once every 12 months. The sulfur content and higher heating value of the fuel shall be determined using the test methods referenced in this permit or certified by a third party fuel supplier. [District Rule 4320, 6.2] Federally Enforceable Through Title V Permit

22. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 1081; 2201; 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1; and 4306, 6.1] Federally Enforceable Through Title V Permit

24. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

25. Permittee shall maintain daily records of volume of fuel gas burned, sulfur content as determined by analytical testing or fuel supplier invoices/certifications, and permit number(s) of systems providing gas for incineration. [District Rules 2201; and 4320, 5.2, 5.7] Federally Enforceable Through Title V Permit

26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; 2520, 9.4.2; 4305, 6.1; 4306, 6.1; and 4320, 6.1] Federally Enforceable Through Title V Permit

27. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

28. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of District Rule 4201 (as amended December 17, 1992), 4301 (as amended December 17, 1992), 4351 (as amended August 21, 2003), 4406 (as amended December 17, 1992), and 4801 (as amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.1, 5.3] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-65-25 **EXPIRATION DATE:** 02/28/2007

SECTION: 05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR NATURAL GAS-FIRED C.E. NATCO STEAM GENERATOR (HSG# 60-41; DIS# 20633-79) WITH FLUE GAS RECIRCULATION, NORTH AMERICAN, MODEL #5131-HGCR-62.5, BURNER AND NORTH AMERICAN OPTIMIZER (SAN JOAQUIN LOWER)

DRAFT

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using District approved portable analyzers in any calendar month in which the unit operates. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
5. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
6. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
7. Emission rates shall not exceed the following PM10: 0.005 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2, VOC: 0.006 lb/MMBtu, and CO: 0.029 lb/MMBtu or 39 ppmv @ 3% O2. [District NSR Rule, Rules 4305, and 4351] Federally Enforceable Through Title V Permit
8. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months, except as provided below. [District Rules 2201, 4305, 4306, and 4351] Federally Enforceable Through Title V Permit
9. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305 and 4351] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rules 4305 and 4351] Federally Enforceable Through Title V Permit
11. Compliance demonstration (source testing) shall be conducted by independent testing laboratories and shall be witnessed, or authorized by the District. Sample collection shall be done by ARB certified testing laboratory. [District Rules 1081 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
12. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
13. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
14. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4305 and 4351] Federally Enforceable Through Title V Permit
15. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District NSR Rule] Federally Enforceable Through Title V Permit
16. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District NSR Rule] Federally Enforceable Through Title V Permit
17. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3 and Kern County Rules 404 and 408] Federally Enforceable Through Title V Permit
19. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
20. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
22. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

23. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

24. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

28. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rule 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

29. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

30. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

31. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301 and 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

33. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

35. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-66-23 **EXPIRATION DATE:** 02/28/2007

SECTION: 05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED C.E. NATCO STEAM GENERATOR (HSG# 60-42; DIS# 20634-79) WITH FLUE GAS RECIRCULATION, NORTH AMERICAN GLE LOW-NOX BURNER AND NORTH AMERICAN OPTIMIZER. (SAN JOAQUIN LOWER)

PERMIT UNIT REQUIREMENTS

1. The operator shall fire the unit only on natural gas. The combined sulfur content of all fuels supplied to this steam generator shall not exceed 1.0 gr S/100 scf. [District Rules 2201; and 4320, 5.4] Federally Enforceable Through Title V Permit
2. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rules 2201; and 4320, 5.2] Federally Enforceable Through Title V Permit
3. Emissions from the steam generator shall not exceed any of the following limits: 0.005 lb-PM10/MMBtu or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Except during startup and shutdown, emissions shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.018 lb-NOx/MMBtu and 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201; 4305, 5.1; 4306, 5.1; and 4320, 5.2] Federally Enforceable Through Title V Permit
5. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum emissions from the steam generator, including start-up and shutdown periods, shall not exceed any of the following limits: 54.0 lb-NOx/day, 9,855 lb-NOx/year, 55.5 lb-CO/day, and 20,258 lb-CO/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown. [District Rules 4305, 5.5, 6.1; 4306, 5.3, 6.1; and 4320, 5.6, 6.1] Federally Enforceable Through Title V Permit
8. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; 4306, 3.22, 3.25; and 4320, 3.25, 3.29] Federally Enforceable Through Title V Permit
9. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

11. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; and 4306, 6.3] Federally Enforceable Through Title V Permit

12. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

13. If the unit is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. Each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

14. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by test methods referenced in this permit. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; 4306, 6.2; and 4320, 6.2] Federally Enforceable Through Title V Permit

16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit
19. Source testing shall be conducted using the methods and procedures approved by the District. Source testing for compliance demonstration shall be conducted by independent testing laboratories, and shall be witnessed, or authorized by District personnel. Sample collection shall be by ARB certified testing laboratory. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
21. Permittee shall submit an analysis to the District demonstrating compliance with the fuel sulfur content and higher heating value within 60 days of startup and at least once every 12 months. The sulfur content and higher heating value of the fuel shall be determined using the test methods referenced in this permit or certified by a third party fuel supplier. [District Rule 4320, 6.2] Federally Enforceable Through Title V Permit
22. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 1081; 2201; 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit
23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1; and 4306, 6.1] Federally Enforceable Through Title V Permit
24. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
25. Permittee shall maintain daily records of volume of fuel gas burned, sulfur content as determined by analytical testing or fuel supplier invoices/certifications, and permit number(s) of systems providing gas for incineration. [District Rules 2201; and 4320, 5.2, 5.7] Federally Enforceable Through Title V Permit
26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; 2520, 9.4.2; 4305, 6.1; 4306, 6.1; and 4320, 6.1] Federally Enforceable Through Title V Permit
27. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit
28. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit
29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of District Rule 4201 (as amended December 17, 1992), 4301 (as amended December 17, 1992), 4351 (as amended August 21, 2003), 4406 (as amended December 17, 1992), and 4801 (as amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.1, 5.3] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-67-24 **EXPIRATION DATE:** 02/28/2007

SECTION: 05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR C.E. NATCO NATURAL GAS-FIRED STEAM GENERATOR (HSG# 60-43; DIS# 20635-79) WITH FLUE GAS RECIRCULATION AND A NORTH AMERICAN GLE LOW-NOX BURNER (SAN JOAQUIN LOWER)

DRAFT

PERMIT UNIT REQUIREMENTS

1. The operator shall fire the unit only on natural gas. The combined sulfur content of all fuels supplied to this steam generator shall not exceed 1.0 gr S/100 scf. [District Rules 2201; and 4320, 5.4] Federally Enforceable Through Title V Permit
2. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rules 2201; and 4320, 5.2] Federally Enforceable Through Title V Permit
3. Emissions from the steam generator shall not exceed any of the following limits: 0.005 lb-PM10/MMBtu or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Except during startup and shutdown, emissions shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.018 lb-NOx/MMBtu and 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201; 4305, 5.1; 4306, 5.1; and 4320, 5.2] Federally Enforceable Through Title V Permit
5. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum emissions from the steam generator, including start-up and shutdown periods, shall not exceed any of the following limits: 54.0 lb-NOx/day, 9,855 lb-NOx/year, 55.5 lb-CO/day, and 20,258 lb-CO/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown. [District Rules 4305, 5.5, 6.1; 4306, 5.3, 6.1; and 4320, 5.6, 6.1] Federally Enforceable Through Title V Permit
8. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; 4306, 3.22, 3.25; and 4320, 3.25, 3.29] Federally Enforceable Through Title V Permit
9. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

11. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; and 4306, 6.3] Federally Enforceable Through Title V Permit

12. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

13. If the unit is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. Each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

14. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by test methods referenced in this permit. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; 4306, 6.2; and 4320, 6.2] Federally Enforceable Through Title V Permit

16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

19. Source testing shall be conducted using the methods and procedures approved by the District. Source testing for compliance demonstration shall be conducted by independent testing laboratories, and shall be witnessed, or authorized by District personnel. Sample collection shall be by ARB certified testing laboratory. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

21. Permittee shall submit an analysis to the District demonstrating compliance with the fuel sulfur content and higher heating value within 60 days of startup and at least once every 12 months. The sulfur content and higher heating value of the fuel shall be determined using the test methods referenced in this permit or certified by a third party fuel supplier. [District Rule 4320, 6.2] Federally Enforceable Through Title V Permit

22. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 1081; 2201; 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1; and 4306, 6.1] Federally Enforceable Through Title V Permit

24. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

25. Permittee shall maintain daily records of volume of fuel gas burned, sulfur content as determined by analytical testing or fuel supplier invoices/certifications, and permit number(s) of systems providing gas for incineration. [District Rules 2201; and 4320, 5.2, 5.7] Federally Enforceable Through Title V Permit

26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; 2520, 9.4.2; 4305, 6.1; 4306, 6.1; and 4320, 6.1] Federally Enforceable Through Title V Permit

27. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

28. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of District Rule 4201 (as amended December 17, 1992), 4301 (as amended December 17, 1992), 4351 (as amended August 21, 2003), 4406 (as amended December 17, 1992), and 4801 (as amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.1, 5.3] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-68-23 **EXPIRATION DATE:** 02/28/2007

SECTION: 05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR C.E. NATCO NATURAL GAS-FIRED STEAM GENERATOR (HSG# 60-44; DIS# 20636-79) WITH FLUE GAS RECIRCULATION AND A NORTH AMERICAN GLE LOW-NOX BURNER (SAN JOAQUIN LOWER)

DRAFT

PERMIT UNIT REQUIREMENTS

1. The operator shall fire the unit only on natural gas. The combined sulfur content of all fuels supplied to this steam generator shall not exceed 1.0 gr S/100 scf. [District Rules 2201; and 4320, 5.4] Federally Enforceable Through Title V Permit
2. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rules 2201; and 4320, 5.2] Federally Enforceable Through Title V Permit
3. Emissions from the steam generator shall not exceed any of the following limits: 0.005 lb-PM10/MMBtu or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Except during startup and shutdown, emissions shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.018 lb-NOx/MMBtu and 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201; 4305, 5.1; 4306, 5.1; and 4320, 5.2] Federally Enforceable Through Title V Permit
5. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum emissions from the steam generator, including start-up and shutdown periods, shall not exceed any of the following limits: 54.0 lb-NOx/day, 9,855 lb-NOx/year, 55.5 lb-CO/day, and 20,258 lb-CO/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown. [District Rules 4305, 5.5, 6.1; 4306, 5.3, 6.1; and 4320, 5.6, 6.1] Federally Enforceable Through Title V Permit
8. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; 4306, 3.22, 3.25; and 4320, 3.25, 3.29] Federally Enforceable Through Title V Permit
9. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

11. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; and 4306, 6.3] Federally Enforceable Through Title V Permit

12. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

13. If the unit is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. Each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

14. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by test methods referenced in this permit. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; 4306, 6.2; and 4320, 6.2] Federally Enforceable Through Title V Permit

16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit.

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

19. Source testing shall be conducted using the methods and procedures approved by the District. Source testing for compliance demonstration shall be conducted by independent testing laboratories, and shall be witnessed, or authorized by District personnel. Sample collection shall be by ARB certified testing laboratory. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

21. Permittee shall submit an analysis to the District demonstrating compliance with the fuel sulfur content and higher heating value within 60 days of startup and at least once every 12 months. The sulfur content and higher heating value of the fuel shall be determined using the test methods referenced in this permit or certified by a third party fuel supplier. [District Rule 4320, 6.2] Federally Enforceable Through Title V Permit

22. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 1081; 2201; 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1; and 4306, 6.1] Federally Enforceable Through Title V Permit

24. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

25. Permittee shall maintain daily records of volume of fuel gas burned, sulfur content as determined by analytical testing or fuel supplier invoices/certifications, and permit number(s) of systems providing gas for incineration. [District Rules 2201; and 4320, 5.2, 5.7] Federally Enforceable Through Title V Permit

26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; 2520, 9.4.2; 4305, 6.1; 4306, 6.1; and 4320, 6.1] Federally Enforceable Through Title V Permit

27. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

28. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of District Rule 4201 (as amended December 17, 1992), 4301 (as amended December 17, 1992), 4351 (as amended August 21, 2003), 4406 (as amended December 17, 1992), and 4801 (as amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.1, 5.3] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-69-23 **EXPIRATION DATE:** 02/28/2007

SECTION: 05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED C.E. NATCO STEAM GENERATOR (HSG# 60-45; DIS# 20637-79) WITH FLUE GAS RECIRCULATION, NORTH AMERICAN GLE LOW-NOX BURNER AND NORTH AMERICAN OPTIMIZER. (SAN JOAQUIN LOWER)

PERMIT UNIT REQUIREMENTS

1. The operator shall fire the unit only on natural gas. The combined sulfur content of all fuels supplied to this steam generator shall not exceed 1.0 gr S/100 scf. [District Rules 2201; and 4320, 5.4] Federally Enforceable Through Title V Permit
2. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rules 2201; and 4320, 5.2] Federally Enforceable Through Title V Permit
3. Emissions from the steam generator shall not exceed any of the following limits: 0.005 lb-PM10/MMBtu or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Except during startup and shutdown, emissions shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.018 lb-NOx/MMBtu and 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201; 4305, 5.1; 4306, 5.1; and 4320, 5.2] Federally Enforceable Through Title V Permit
5. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum emissions from the steam generator, including start-up and shutdown periods, shall not exceed any of the following limits: 54.0 lb-NOx/day, 9,855 lb-NOx/year, 55.5 lb-CO/day, and 15,858 lb-CO/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown. [District Rules 4305, 5.5, 6.1; 4306, 5.3, 6.1; and 4320, 5.6, 6.1] Federally Enforceable Through Title V Permit
8. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; 4306, 3.22, 3.25; and 4320, 3.25, 3.29] Federally Enforceable Through Title V Permit
9. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

11. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; and 4306, 6.3] Federally Enforceable Through Title V Permit

12. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

13. If the unit is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. Each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

14. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by test methods referenced in this permit. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; 4306, 6.2; and 4320, 6.2] Federally Enforceable Through Title V Permit

16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

19. Source testing shall be conducted using the methods and procedures approved by the District. Source testing for compliance demonstration shall be conducted by independent testing laboratories, and shall be witnessed, or authorized by District personnel. Sample collection shall be by ARB certified testing laboratory. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

21. Permittee shall submit an analysis to the District demonstrating compliance with the fuel sulfur content and higher heating value within 60 days of startup and at least once every 12 months. The sulfur content and higher heating value of the fuel shall be determined using the test methods referenced in this permit or certified by a third party fuel supplier. [District Rule 4320, 6.2] Federally Enforceable Through Title V Permit

22. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 1081; 2201; 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1; and 4306, 6.1] Federally Enforceable Through Title V Permit

24. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

25. Permittee shall maintain daily records of volume of fuel gas burned, sulfur content as determined by analytical testing or fuel supplier invoices/certifications, and permit number(s) of systems providing gas for incineration. [District Rules 2201; and 4320, 5.2, 5.7] Federally Enforceable Through Title V Permit

26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; 2520, 9.4.2; 4305, 6.1; 4306, 6.1; and 4320, 6.1] Federally Enforceable Through Title V Permit

27. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

28. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of District Rule 4201 (as amended December 17, 1992), 4301 (as amended December 17, 1992), 4351 (as amended August 21, 2003), 4406 (as amended December 17, 1992), and 4801 (as amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.1, 5.3] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-70-23 **EXPIRATION DATE:** 02/28/2007

SECTION: 05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED C.E. NATCO STEAM GENERATOR (HSG# 60-46; DIS# 20638-79) WITH A NORTH AMERICAN MAGNA FLAME GLE LOW-NOX BURNER AND FLUE GAS RECIRCULATION (SAN JOAQUIN LOWER)

DRAFT

PERMIT UNIT REQUIREMENTS

1. The operator shall fire the unit only on natural gas. The combined sulfur content of all fuels supplied to this steam generator shall not exceed 1.0 gr S/100 scf. [District Rules 2201; and 4320, 5.4] Federally Enforceable Through Title V Permit
2. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rules 2201; and 4320, 5.2] Federally Enforceable Through Title V Permit
3. Emissions from the steam generator shall not exceed any of the following limits: 0.005 lb-PM10/MMBtu or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Except during startup and shutdown, emissions shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.018 lb-NOx/MMBtu and 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201; 4305, 5.1; 4306, 5.1; and 4320, 5.2] Federally Enforceable Through Title V Permit
5. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum emissions from the steam generator, including start-up and shutdown periods, shall not exceed any of the following limits: 54.0 lb-NOx/day, 9,855 lb-NOx/year, 55.5 lb-CO/day, and 20,258 lb-CO/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown. [District Rules 4305, 5.5, 6.1; 4306, 5.3, 6.1; and 4320, 5.6, 6.1] Federally Enforceable Through Title V Permit
8. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; 4306, 3.22, 3.25; and 4320, 3.25, 3.29] Federally Enforceable Through Title V Permit
9. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

11. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; and 4306, 6.3] Federally Enforceable Through Title V Permit

12. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

13. If the unit is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. Each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

14. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by test methods referenced in this permit. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; 4306, 6.2; and 4320, 6.2] Federally Enforceable Through Title V Permit

16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

19. Source testing shall be conducted using the methods and procedures approved by the District. Source testing for compliance demonstration shall be conducted by independent testing laboratories, and shall be witnessed, or authorized by District personnel. Sample collection shall be by ARB certified testing laboratory. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

21. Permittee shall submit an analysis to the District demonstrating compliance with the fuel sulfur content and higher heating value within 60 days of startup and at least once every 12 months. The sulfur content and higher heating value of the fuel shall be determined using the test methods referenced in this permit or certified by a third party fuel supplier. [District Rule 4320, 6.2] Federally Enforceable Through Title V Permit

22. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 1081; 2201; 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1; and 4306, 6.1] Federally Enforceable Through Title V Permit

24. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

25. Permittee shall maintain daily records of volume of fuel gas burned, sulfur content as determined by analytical testing or fuel supplier invoices/certifications, and permit number(s) of systems providing gas for incineration. [District Rules 2201; and 4320, 5.2, 5.7] Federally Enforceable Through Title V Permit

26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; 2520, 9.4.2; 4305, 6.1; 4306, 6.1; and 4320, 6.1] Federally Enforceable Through Title V Permit

27. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

28. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of District Rule 4201 (as amended December 17, 1992), 4301 (as amended December 17, 1992), 4351 (as amended August 21, 2003), 4406 (as amended December 17, 1992), and 4801 (as amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.1, 5.3] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-1131-73-23 **EXPIRATION DATE:** 02/28/2007

SECTION: 05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED C.E. NATCO STEAM GENERATOR (HSG# 60-49; DIS# 20641-79) WITH A NORTH AMERICAN MAGNA FLAME GLE LOW-NOX BURNER AND FLUE GAS RECIRCULATION (SAN JOAQUIN LOWER)

PERMIT UNIT REQUIREMENTS

1. The operator shall fire the unit only on natural gas. The combined sulfur content of all fuels supplied to this steam generator shall not exceed 1.0 gr S/100 scf. [District Rules 2201; and 4320, 5.4] Federally Enforceable Through Title V Permit
2. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rules 2201; and 4320, 5.2] Federally Enforceable Through Title V Permit
3. Emissions from the steam generator shall not exceed any of the following limits: 0.005 lb-PM10/MMBtu or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Except during startup and shutdown, emissions shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.018 lb-NOx/MMBtu and 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201; 4305, 5.1; 4306, 5.1; and 4320, 5.2] Federally Enforceable Through Title V Permit
5. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum emissions from the steam generator, including start-up and shutdown periods, shall not exceed any of the following limits: 54.0 lb-NOx/day, 9,855 lb-NOx/year, 55.5 lb-CO/day, and 20,258 lb-CO/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown. [District Rules 4305, 5.5, 6.1; 4306, 5.3, 6.1; and 4320, 5.6, 6.1] Federally Enforceable Through Title V Permit
8. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; 4306, 3.22, 3.25; and 4320, 3.25, 3.29] Federally Enforceable Through Title V Permit
9. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

11. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; and 4306, 6.3] Federally Enforceable Through Title V Permit

12. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

13. If the unit is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. Each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

14. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by test methods referenced in this permit. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; 4306, 6.2; and 4320, 6.2] Federally Enforceable Through Title V Permit

16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit
19. Source testing shall be conducted using the methods and procedures approved by the District. Source testing for compliance demonstration shall be conducted by independent testing laboratories, and shall be witnessed, or authorized by District personnel. Sample collection shall be by ARB certified testing laboratory. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
21. Permittee shall submit an analysis to the District demonstrating compliance with the fuel sulfur content and higher heating value within 60 days of startup and at least once every 12 months. The sulfur content and higher heating value of the fuel shall be determined using the test methods referenced in this permit or certified by a third party fuel supplier. [District Rule 4320, 6.2] Federally Enforceable Through Title V Permit
22. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 1081; 2201; 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit
23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1; and 4306, 6.1] Federally Enforceable Through Title V Permit
24. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
25. Permittee shall maintain daily records of volume of fuel gas burned, sulfur content as determined by analytical testing or fuel supplier invoices/certifications, and permit number(s) of systems providing gas for incineration. [District Rules 2201; and 4320, 5.2, 5.7] Federally Enforceable Through Title V Permit
26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; 2520, 9.4.2; 4305, 6.1; 4306, 6.1; and 4320, 6.1] Federally Enforceable Through Title V Permit
27. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit
28. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit
29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of District Rule 4201 (as amended December 17, 1992), 4301 (as amended December 17, 1992), 4351 (as amended August 21, 2003), 4406 (as amended December 17, 1992), and 4801 (as amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.1, 5.3] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-77-23 **EXPIRATION DATE:** 02/28/2007

SECTION: 19 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS-FIRED C.E. NATCO STEAM GENERATOR (HSG# 60-67; DIS# 20611-79) WITH FLUE GAS RECIRCULATION, NORTH AMERICAN, MODEL #5131-HGCR-62. 5, BURNER AND NORTH AMERICAN OPTIMIZER. (CANFIELD LEASE)

DRAFT

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
5. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
6. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
7. Emission rates shall not exceed the following PM10: 0.108 lb/MMBtu, SOx (as SO2): 1.026 lb/MMBtu, NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2, VOC: 0.006 lb/MMBtu, and CO: 0.029 lb/MMBtu or 39 ppmv @ 3% O2. [District Rules 2201, 4305, and 4351] Federally Enforceable Through Title V Permit
8. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rules 2201 and 4406] Federally Enforceable Through Title V Permit
9. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4406] Federally Enforceable Through Title V Permit
10. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

11. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months, except as provided below. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit

12. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit

13. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit

14. Compliance demonstration (source testing) shall be conducted by independent testing laboratories and shall be witnessed or authorized by the District. Sample collection shall be done by an ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

15. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

16. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

17. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans, or other test methods approved by the District. [District Rules 1081, 4305, and 4351] Federally Enforceable Through Title V Permit

18. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

19. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

20. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3 and Kern County Rules 404 and 408] Federally Enforceable Through Title V Permit

22. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit

23. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

27. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

31. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rule 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. All units in a group for which representative units are source for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). These tune-up procedures shall be completed according to District Rule 4304 (Adopted October 19, 1995) and tune-up test results shall show comparable results for each unit in the group. Records shall be maintained for the each unit of the group including all preventative and corrective maintenance work done. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

33. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301 and 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

36. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

37. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

38. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-78-23 **EXPIRATION DATE:** 02/28/2007

SECTION: 19 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS-FIRED C.E. NATCO STEAM GENERATOR (HSG# 60-69; DIS# 20610-79) WITH A NORTH AMERICAN MAGNA FLAME GLE LOW-NOX BURNER AND FLUE GAS RECIRCULATION (CANFIELD LEASE)

DRAFT

PERMIT UNIT REQUIREMENTS

1. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
2. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
3. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
4. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit
5. The portable analyzer shall be calibrated prior to each use with a two-point calibration method (zero and span). Calibration shall be performed with certified calibration gases. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. Emissions from the steam generator shall not exceed any of the following limits: 0.108 lb-PM10/MMBtu, 1.026 lb-SOx (as SO2)/MMBtu, 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

7. Except during start-up and shutdown, emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 (or 0.0182 lb-NOx/MMBtu), or 50 ppmvd CO @ 3% O2 (or 0.037 lb-CO/MMBtu). [District Rules 2201, 4305, 5.1, and 4306, 5.1] Federally Enforceable Through Title V Permit

8. During start-up and shutdown, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

9. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 54.0 lb-NOx/day, 9,965 lb-NOx/yr, or 55.5 lb-CO/day. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit

11. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit

12. Permittee shall maintain records of duration of each start-up and shutdown for a period of five years and make such records readily available for District inspection upon request. [District Rule 4306, 6.1] Federally Enforceable Through Title V Permit

13. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rules 2201 and 4406] Federally Enforceable Through Title V Permit

14. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4406] Federally Enforceable Through Title V Permit

15. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit

17. Compliance demonstration (source testing) shall be conducted by independent testing laboratories and shall be witnessed or authorized by the District. Sample collection shall be done by an ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

18. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit

20. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

22. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit

23. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

24. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

25. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3 and Kern County Rules 404 and 408] Federally Enforceable Through Title V Permit

27. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit

28. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D1072, D4084, D3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D1826 or D1945 in conjunction with ASTM D3588 for gaseous fuels. [District Rules 2520, 9.3.2; 4305, 6.2.1; 4306, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative un(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 4305, 6.3.2.4; 4306, 6.3.2.4 ; and 4351, 6.3] Federally Enforceable Through Title V Permit

36. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 4305, 6.3.2.1 and 4306, 6.3.2.1] Federally Enforceable Through Title V Permit

37. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 4305, 6.3.2.6 and 4306, 6.3.2.6] Federally Enforceable Through Title V Permit

38. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 4305, 6.3.2.2 and 4306, 6.3.2.2] Federally Enforceable Through Title V Permit

39. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 4305, 6.3.2.5 and 4306, 6.3.2.5] Federally Enforceable Through Title V Permit

40. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; 4305, 6.1; and 4306, 6.1] Federally Enforceable Through Title V Permit

41. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301 and 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-82-26 **EXPIRATION DATE:** 02/28/2007

SECTION: SE05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS-FIRED C.E. NATCO STEAM GENERATOR (HSG# 60-88; DIS# 20643-79) WITH A NORTH AMERICAN MODEL GLE MAGNA-FLAME LOW NOX BURNER, A FLUE GAS RECIRCULATION FGR SYSTEM AND NORTH AMERICAN OPTIMIZER - SJ LOWER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rule 4406, 4.0] Federally Enforceable Through Title V Permit
3. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rule 4406, 4.0] Federally Enforceable Through Title V Permit
4. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Flue gas recirculation shall be utilized, as needed, in conjunction with low-NOx burner to maintain ongoing compliance with permitted emission limits. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Emissions from the steam generator shall not exceed any of the following limits: 1.026 lb-SOx/MMBtu, 0.108 lb-PM10/MMBtu, or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.0182 lb-NOx/MMBtu or 39 ppmvd CO @ 3% O2 or 0.029 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4351, 5.1] Federally Enforceable Through Title V Permit
9. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit

12. Emissions from the steam generator shall not exceed either of the following limits: 54.0 lb-NOx/day or 43.5 lb-CO/day. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit

14. Whenever the flue gas recirculation (FGR) system on this unit is switched from the open to the closed position, or from the closed to the open position, compliance source testing for NOx and CO emissions shall be conducted within 60 days of change of FGR operation date unless source testing with FGR system in both the open and closed position has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

15. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

16. {2417} Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [County Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus)] Federally Enforceable Through Title V Permit

17. If the steam generator is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. If the steam generator is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM D 1072, D 3031, D 4084, D 3246, double GC for H2S and mercaptans, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. If the steam generator is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

22. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

23. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit

24. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit

25. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit

26. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5 and 4306, 5.5.5] Federally Enforceable Through Title V Permit

27. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

28. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx and CO emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

29. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

30. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

31. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

32. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

33. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit

34. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District Rule 2201] Federally Enforceable Through Title V Permit

35. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, and 4306, 6.1] Federally Enforceable Through Title V Permit

37. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301 and 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

38. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-94-27 **EXPIRATION DATE:** 02/28/2007

SECTION: 29 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS-FIRED STRUTHERS STEAM GENERATOR (HSG# 70-08; DIS# 20627-81) WITH FLUE GAS RECIRCULATION, NORTH AMERICAN, MODEL #5131-HGCR-62. 5, BURNER AND NORTH AMERICAN OPTIMIZER (CANFIELD LEASE)

DRAFT

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
5. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
6. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
7. Emission rates shall not exceed the following PM10: 0.108 lb/MMBtu, SOx (as SO2): 1.026 lb/MMBtu, NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2, VOC: 0.006 lb/MMBtu, and CO: 0.029 lb/MMBtu or 39 ppmv @ 3% O2. [District Rules 2201, 4305, 4351] Federally Enforceable Through Title V Permit
8. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rules 2201 and 4406] Federally Enforceable Through Title V Permit
9. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4406] Federally Enforceable Through Title V Permit
10. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

11. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months, except as provided below. [District Rules 2201, 4305, 4306, and 4351] Federally Enforceable Through Title V Permit

12. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit

13. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit

14. Compliance demonstration (source testing) shall be conducted by independent testing laboratories and shall be witnessed or authorized by the District. Sample collection shall be done by an ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

15. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

16. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

17. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans, or other test methods approved by the District. [District Rules 1081, 4305, and 4351] Federally Enforceable Through Title V Permit

18. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

19. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

20. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3 and Kern County Rules 404 and 408] Federally Enforceable Through Title V Permit

22. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit

23. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

27. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

31. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rule 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

33. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

34. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

35. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301 and 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

36. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

37. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

38. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-95-23 **EXPIRATION DATE:** 02/28/2007

SECTION: SE05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS/GAS FIRED STRUTHERS STEAM GENERATOR (HSG# 70-31; DIS# 20642-79) WITH A NORTH AMERICAN MODEL GLE MAGNA-FLAME LOW NOX BURNER, FLUE GAS RECIRCULATION (FGR) SYSTEM AND NORTH AMERICAN OPTIMIZER - SJ LOWER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rule 4406, 4.0] Federally Enforceable Through Title V Permit
3. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rule 4406, 4.0] Federally Enforceable Through Title V Permit
4. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Flue gas recirculation shall be utilized, as needed, in conjunction with low-NOx burner to maintain ongoing compliance with permitted emission limits. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Emissions from the steam generator shall not exceed any of the following limits: 1.026 lb-SOx/MMBtu, 0.108 lb-PM10/MMBtu, or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.0182 lb-NOx/MMBtu or 39 ppmvd CO @ 3% O2 or 0.029 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4351, 5.1] Federally Enforceable Through Title V Permit
9. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Emissions from the steam generator shall not exceed either of the following limits: 54.0 lb-NOx/day or 43.5 lb-CO/day. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit

13. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit

14. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

15. {2417} Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [County Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus)] Federally Enforceable Through Title V Permit

16. If the steam generator is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. If the steam generator is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM D 1072, D 3031, D 4084, D 3246, double GC for H2S and mercaptans, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. If the steam generator is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

20. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

22. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit

23. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit

24. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit

25. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5 and 4306, 5.5.5] Federally Enforceable Through Title V Permit

26. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

27. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx and CO emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

28. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

29. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

30. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

32. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit

33. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District Rule 2201] Federally Enforceable Through Title V Permit

34. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, and 4306, 6.1] Federally Enforceable Through Title V Permit

36. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301 and 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

37. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-1131-98-26 **EXPIRATION DATE:** 02/28/2007

SECTION: SE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR STRUTHERS NATURAL GAS/VAPOR RECOVERY GAS-FIRED STEAM GENERATOR (HSG# 70-44; DIS# 20608-82) WITH A NORTH AMERICAN MODEL #GLE-4231 LOW NOX BURNER AND FLUE GAS RECIRCULATION

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rule 4406, 4.0] Federally Enforceable Through Title V Permit
3. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rule 4406, 4.0] Federally Enforceable Through Title V Permit
4. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Emissions from the natural gas/vapor recovery gas-fired steam generator shall not exceed any of the following limits: 1.026 lb-SOx/MMBtu, 0.108 lb-PM10/MMBtu, or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Except during start-up and shutdown periods emissions from the natural gas/vapor recovery gas-fired steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.0182 lb-NOx/MMBtu or 39 ppmvd CO @ 3% O2 or 0.029 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4351, 5.1] Federally Enforceable Through Title V Permit
8. During start-up and shutdown periods emissions from the natural gas/vapor recovery gas-fired steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4306, 3.25 and 3.22] Federally Enforceable Through Title V Permit
10. Emissions from the natural gas/vapor recovery gas-fired steam generator shall not exceed either of the following limits: 54.0 lb-NOx/day or 43.5 lb-CO/day. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3.1, 4306, 6.3.1, and 4351, 6.3.1] Federally Enforceable Through Title V Permit

12. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

13. {2417} Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [County Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus)] Federally Enforceable Through Title V Permit

14. If the steam generator is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. If the steam generator is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM D 1072, D 3031, D 4084, D 3246, double GC for H2S and mercaptans, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. If the steam generator is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

18. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

20. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 6.2 and 4306, 6.2] Federally Enforceable Through Title V Permit

21. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 6.2 and 4306, 6.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. Stack gas oxygen (O2) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 6.2 and 4306, 6.2] Federally Enforceable Through Title V Permit

23. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit

24. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 5.5.2 and 4306, 5.5.2] Federally Enforceable Through Title V Permit

25. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5 and 4306, 5.5.5] Federally Enforceable Through Title V Permit

26. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

27. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

28. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

29. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

30. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

31. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

32. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit

33. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, and 4306, 6.1] Federally Enforceable Through Title V Permit

36. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

37. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

38. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-99-26 **EXPIRATION DATE:** 02/28/2007

SECTION: SE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR STRUTHERS NATURAL GAS/VAPOR RECOVERY GAS-FIRED STEAM GENERATOR (HSG# 70-45; DIS# 20609-82) WITH A NORTH AMERICAN MODEL #GLE-4231 LOW NOX BURNER AND FLUE GAS RECIRCULATION

DRAFT

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Kern County Rule 407] Federally Enforceable Through Title V Permit
7. Emissions from the steam generator shall not exceed any of the following limits: 1.026 lb-SOx/MMBtu, 0.108 lb-PM10/MMBtu, or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Emissions from the steam generator shall not exceed either of the following limits: 54.0 lb-NOx/day or 43.5 lb-CO/day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.0182 lb-NOx/MMBtu or 39 ppmvd CO @ 3% O2 or 0.029 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4351, 5.1] Federally Enforceable Through Title V Permit
10. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rules 2201 and 4351] Federally Enforceable Through Title V Permit
11. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit

13. Flue gas recirculation shall be utilized, as needed, in conjunction with low-NOx burner to maintain ongoing compliance with permitted emission limits. [District Rules 2201, 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

14. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

15. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

16. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

17. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit

18. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit

22. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5 and 4306, 5.5.5] Federally Enforceable Through Title V Permit

23. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit

24. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

25. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

26. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

27. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

28. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

29. If the steam generator is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. If the steam generator is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM D 1072, D 3031, D 4084, D 3246, double GC for H2S and mercaptans, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

31. If the steam generator is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rule 4406, 4.0] Federally Enforceable Through Title V Permit

33. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rule 4406, 4.0] Federally Enforceable Through Title V Permit

34. The fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 4305, 6.2, 4306, 6.2, and 4351, 6.2] Federally Enforceable Through Title V Permit

35. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit

36. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District Rule 2201] Federally Enforceable Through Title V Permit

37. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, and 4306, 6.1] Federally Enforceable Through Title V Permit

39. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. {4194} Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-262-5 **EXPIRATION DATE:** 02/28/2007

EQUIPMENT DESCRIPTION:
720 STEAM-ENHANCED CRUDE-OIL PRODUCTION WELLS WITH CLOSED CASING VENTS

DRAFT

PERMIT UNIT REQUIREMENTS

1. Well casing vents shall remain closed at all times except during periods of actual service or repair when wells are not producing. [District NSR Rule and 4401] Federally Enforceable Through Title V Permit
2. Fluids produced from these steam-enhanced wells with closed well casing vents shall be introduced only to front line production equipment vented to a District-approved vapor collection and control system that has a VOC destruction or removal efficiency of at least 99%, or to gauge tanks as defined by Rule 4401 Section 3.17. [District Rule 4401] Federally Enforceable Through Title V Permit
3. Permittee shall maintain a current listing of all steam-enhanced wells in the central Kern County fields heavy oil production stationary source with closed casing vents that direct fluids to uncontrolled storage tanks and a current listing of all permit numbers of front-line equipment receiving produced fluids from the wells; shall update the list whenever a well or front-line equipment is added, replaced or deleted; and shall make such listing readily available for District inspection upon request. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Any increase to the maximum number of steam enhanced oil production wells with closed casing vents shall require prior authorization by Authority to Construct or APCO approval of application for transfer of ownership of Permit to Operate. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The crude oil production from wells associated with this permit unit shall not lie within 1,000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
6. {4272} Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401 3.20] Federally Enforceable Through Title V Permit
7. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
8. {4273} An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. {4274} An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.8 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.6.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401 5.6.2] Federally Enforceable Through Title V Permit

10. {4275} An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.8 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 3 of Rule 4401. [District Rule 4401 5.6.2] Federally Enforceable Through Title V Permit

11. {4276} An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.6.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.9 of Rule 4401. [District Rule 4401 5.7.1] Federally Enforceable Through Title V Permit

12. {4277} Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401 5.7.2] Federally Enforceable Through Title V Permit

13. {4278} An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401 5.7.3] Federally Enforceable Through Title V Permit

14. {4279} Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401 5.8.1] Federally Enforceable Through Title V Permit

15. {4280} An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of Rule 4401. [District Rule 4401 5.8.2] Federally Enforceable Through Title V Permit

16. {4281} In addition to the inspections required by Section 5.8.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of Rule 4401. [District Rule 4401 5.8.3] Federally Enforceable Through Title V Permit

17. {4282} In addition to the inspections required by Sections 5.8.1, 5.8.2 and 5.8.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.8.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401 5.8.4] Federally Enforceable Through Title V Permit

18. {4283} An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401 5.8.5] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. {4284} District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401 5.8.6] Federally Enforceable Through Title V Permit

20. {4285} An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401 5.9.1] Federally Enforceable Through Title V Permit

21. {4286} An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and 5.9.2.3 of Rule 4401, or the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.9.2] Federally Enforceable Through Title V Permit

22. {4287} An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401 5.9.3] Federally Enforceable Through Title V Permit

23. {4288} Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 4 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401 5.9.4] Federally Enforceable Through Title V Permit

24. {4289} The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401 5.9.4] Federally Enforceable Through Title V Permit

25. {4290} The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4 of Rule 4401. [District Rule 4401 5.9.5] Federally Enforceable Through Title V Permit

26. {4291} The time of the initial leak detection shall be the start of the repair period specified in Table 4 of Rule 4401. [District Rule 4401 5.9.6] Federally Enforceable Through Title V Permit

27. {4292} If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401 5.9.7] Federally Enforceable Through Title V Permit

28. {4293} The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401 6.1.1] Federally Enforceable Through Title V Permit

29. {4295} An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401 6.1.3] Federally Enforceable Through Title V Permit

30. {4296} The results of source tests conducted pursuant to Section 4.6.2 of Rule 4401 shall be submitted to the APCO within 60 days after the completion of the source test. [District Rule 4401 6.1.4] Federally Enforceable Through Title V Permit

31. {4297} Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401 6.1.5] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. {4298} Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401 6.1.6] Federally Enforceable Through Title V Permit

33. {4299} An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1.7] Federally Enforceable Through Title V Permit

34. {4300} Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401 6.1.8] Federally Enforceable Through Title V Permit

35. {4301} Operator shall submit to the APCO not later than June 14, 2007 a list of all gauge tanks, as defined in Section 3.17. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401 6.1.9] Federally Enforceable Through Title V Permit

36. {4302} The results of gauge tank TVP testing conducted pursuant to Section 6.2.5 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401 6.1.10] Federally Enforceable Through Title V Permit

37. {4303} An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401 6.1.11] Federally Enforceable Through Title V Permit

38. {4304} An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 4401 6.2.1] Federally Enforceable Through Title V Permit

39. {4305} If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401 6.2.2] Federally Enforceable Through Title V Permit

40. {4306} If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 for a vapor control system which does not have a VOC destruction device. [District Rule 4401 6.2.3] Federally Enforceable Through Title V Permit

41. {4307} An operator seeking approval pursuant to Section 6.2.2 or Section 6.2.3 shall submit a written request and supporting information to the APCO. The District shall evaluate the request and if approved by the APCO, the District shall provide EPA and ARB with a copy of the evaluation and shall request EPA and ARB approval. The District evaluation and the APCO request shall be deemed approved unless EPA or ARB objects to such approval in writing within 45 days of the receipt of the APCO request. [District Rule 4401 6.2.4] Federally Enforceable Through Title V Permit

42. {4308} An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.10 of Rule 4401. [District Rule 4401 6.2.5] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

43. {4309} The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401 6.3.1] Federally Enforceable Through Title V Permit

44. {4310} VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401 6.3.2] Federally Enforceable Through Title V Permit

45. {4311} Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401 6.3.3] Federally Enforceable Through Title V Permit

46. {4312} The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401 6.3.5] Federally Enforceable Through Title V Permit

47. {4313} Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401 6.4] Federally Enforceable Through Title V Permit

48. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. Permittee shall maintain at the facility the copies of the training records of the training program. [District Rule 4401, 6.1.7 & 6.5] Federally Enforceable Through Title V Permit

49. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

50. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 5.7.3 and 6.7] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-448-6

EXPIRATION DATE: 02/28/2007

DRAFT

SECTION: SE30 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
750 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, GLOBE WASH TANK

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-460-5 **EXPIRATION DATE:** 02/28/2007

DRAFT

SECTION: SW30 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
750 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, G & WA WASH TANK

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-509-5 **EXPIRATION DATE:** 02/28/2007

SECTION: SW32 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK #TK3-7

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-529-5 **EXPIRATION DATE:** 02/28/2007

SECTION: SW4 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK #0.5GK27

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-530-5

EXPIRATION DATE: 02/28/2007

DRAFT

SECTION: SW5 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK #0.5GK25

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-531-5 **EXPIRATION DATE:** 02/28/2007

SECTION: SW4 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK #0.5GK26

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-586-5 **EXPIRATION DATE:** 02/28/2007

SECTION: SW04 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, GOLD STANDARD DRAIN TANK

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-592-4 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
8,890 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, S. PROCESS WASH TANK

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-594-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
4,530 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, SETTLING #37 AUTHORIZED TO RECEIVE FLUIDS FROM S-1131 AND S-1127

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-598-24 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
43,000 BBL 80' DIA X 48' HIGH FIXED ROOF CRUDE OIL PRODUCTION TANK SURGE #5 (STATION 36) WITH GAS BLANKETING AND VAPOR CONTROL SYSTEM INCLUDING 5 STEAM GENERATORS, DOGGR APPROVED VAPOR DISPOSAL WELLS, AND SULFUR REMOVAL SYSTEM

PERMIT UNIT REQUIREMENTS

1. Tank shall only be vented to vapor control system shared with crude oil processing tanks #S-1131-608, '-613, '-629, '-630, '-638, '-641, '-650, '-651, '-1097 and vapor control system listed on S-1131-885. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Sulfatreat system shall be located downstream of sampling point used for verification that gas processed by tank S-1131-598 contains < 10% VOC by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank is authorized to receive fluids from facilities S-1131 and S-1127. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Collected VOC vapors shall be incinerated in steam generators S-1131-82, '-95, '-98, '-99, and '-859, or disposed of in Department of Oil, Gas, and Geothermal Resources (DOGGR) approved vapor disposal well(s). [District Rule 2201] Federally Enforceable Through Title V Permit
6. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
7. Permittee shall maintain records of number and type of components in gas service installed. Permittee shall update such records when new gas handling components are installed. Permittee shall maintain records of components exempted from counting, and the basis for exemption. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Fugitive VOC emission rate, calculated using the Oil and Gas Production Operations Average Emission Factors, U.S. EPA Protocol for Equipment Leak Emission Estimates, Table 2-4 (EPA-453/R-95-017) November 1995 from the total number of vapor components associated with tank and vapor control system shall not exceed 113.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The fugitive VOC emission rate does not include piping and components handling produced fluids with API gravity less than 30 degrees. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The fugitive VOC emission rate does not include piping and components handling produced fluids having less than 10% VOC by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The fugitive VOC emission rate does not include components in water/oil service (water content of fluids handled greater than 50%). Permittee shall maintain records of annual testing to demonstrate that such fluid streams have at least 50% water by weight. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Operator shall conduct quarterly sampling from the tank vapor control system's emergency gas exhaust header sample point to qualify for exemption from fugitive component counts for components handling fluids with less than 10% VOC by weight. If 8 consecutive quarterly samplings show compliance, then sampling frequency shall only be required annually. Such sampling is deemed representative of tanks S-1131-608, -613, -629, -630, -638, -641, -650, -651, and -1097. [District Rule 2201] Federally Enforceable Through Title V Permit
13. VOC content of vapor shall be determined by ASTM D1945, ASTM D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Permittee shall maintain a written record of the VOC content of the gas sampled. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Tank shall be equipped with an operational and calibrated stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Tank roof, tank shell, tank vapor space appurtenances, vapor control system piping, and vapor control system components shall be inspected and monitored using EPA Method 21 at least monthly. Items found to be not leaking may then be inspected and monitored at least once every 3 months until a leak is detected at which time the inspection and monitoring frequency shall revert to monthly until such time that two consecutive monthly inspections reveal with no leaks at which time the inspection and monitoring frequency shall revert to at least once every 3 months. [District Rule 2201] Federally Enforceable Through Title V Permit
17. A visible mist, liquid dripping at the rate of more than 3 drops per minute, and vapor leaks of 50,000 ppm or greater VOC as methane shall be repaired as expeditiously as possible but in no case beyond 24 hours of detecting the leak and shall be re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 10,000 ppm and less than 50,000 ppm VOC as methane shall be repaired within 5 days of detecting the leak and re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 1,000 ppm and less than 10,000 ppm VOC as methane shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Upon detection of a leak, permittee shall tag the leak with a uniquely numbered tag, and shall record the leak location, component leaking, identification tag number, leak magnitude, date of leak detection, date of repair, method of repair, and post-repair monitoring measurement. Such records of leaks shall be maintained current and shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Components not accessible for EPA Method 21 inspection shall be visually and auditorily checked for leaks at least weekly and shall be monitored using EPA Method 21 at least annually. Any leak detected visually or auditorially shall be recorded and the leak shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. Any leak detected using EPA Method 21 shall be repaired according the leak magnitude as described above and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit
20. In addition to the requirements above, pressure relief devices shall be inspected and monitored for leaks within 3 days of any known, likely, or suspected venting of such devices. [District Rule 2201] Federally Enforceable Through Title V Permit
21. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

24. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

25. True Vapor Pressure (TVP) of any organic liquid, except for crude oil with an API gravity of 20 degrees or less, shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

26. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

27. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

28. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

29. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

30. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

31. When a D.O.G.G.R. disposal well is changed, or a new well is added, permittee shall provide District with a copy of D.O.G.G.R. approval for each vapor disposal well prior to use for vapor injection. [District Rules 1070; and 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from a common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

34. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

35. Permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2010] Federally Enforceable Through Title V Permit

37. Prior to taking the vapor control systems off-line, the water removal rate shall be controlled to maximize the fluid level in the tank and minimize the thickness of the oil pad. The liquid level shall be raised to displace at least 90% of the tank liquid capacity using water. The inflow of crude oil and water shall be stopped and the vapor control system shall continue to operate for at least 24 hours prior to opening the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

38. After the inflow of crude oil and water has stopped and the vapor control system has operated for at least 24 hours, the tank shall be isolated or disconnected from the vapor control system, the tank drain shall be opened, the pressure-vacuum relief valve shall be opened or bypassed, and the tank shall be drained. [District Rule 2010] Federally Enforceable Through Title V Permit

39. The tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2010] Federally Enforceable Through Title V Permit

40. Steam Cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2010] Federally Enforceable Through Title V Permit

41. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2010] Federally Enforceable Through Title V Permit

42. Within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2010] Federally Enforceable Through Title V Permit

43. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-599-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
5,410 BBL FIXED-ROOF CRUDE OIL WASH TANK #1-A AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS (S-1131 AND S-1127)

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-600-4 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
5,920 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, #6600 S OT

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-601-4 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
5,920 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, #6600 N OT

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-602-4 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
8,890 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, N. PROCESS WASH TANK

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-603-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
4,470 BBL FIXED-ROOF CRUDE OIL SETTLING TANK #43 AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS (S-1131 AND S-1127)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-606-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
4,470 BBL FIXED ROOF CRUDE OIL SETTLING TANK #42 AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS (S-1131 AND S-1127)

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-608-21 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
10,000 BBL 55' DIA X 24' HIGH FIXED ROOF CRUDE OIL PRODUCTION TANK, SHIPPING #41 (STATION 36) VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1131-598

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank is authorized to receive fluids from facilities S-1131 and S-1127. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank is authorized to receive fluids from station 36 "Surge" tanks receiving production from steam-enhanced wells with closed well casing vents. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
5. Permittee shall maintain records of number and type of components in gas service installed. Permittee shall update such records when new gas handling components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fugitive VOC emission rate, calculated using the Oil and Gas Production Operations Average Emission Factors, U.S. EPA Protocol for Equipment Leak Emission Estimates, Table 2-4 (EPA-453/R-95-017) November 1995 from the total number of vapor components associated with tank and vapor control system shall not exceed 6.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank roof, tank shell, tank vapor space appurtenances, vapor control system piping, and vapor control system components shall be inspected and monitored using EPA Method 21 at least monthly. Items found to be not leaking may then be inspected and monitored at least once every 3 months until a leak is detected at which time the inspection and monitoring frequency shall revert to monthly until such time that two consecutive monthly inspections reveal with no leaks at which time the inspection and monitoring frequency shall revert to at least once every 3 months. [District Rule 2201] Federally Enforceable Through Title V Permit
8. A visible mist, liquid dripping at the rate of more than 3 drops per minute, and vapor leaks of 50,000 ppm or greater VOC as methane shall be repaired as expeditiously as possible but in no case beyond 24 hours of detecting the leak and shall be re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 10,000 ppm and less than 50,000 ppm VOC as methane shall be repaired within 5 days of detecting the leak and re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 1,000 ppm and less than 10,000 ppm VOC as methane shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Upon detection of a leak, permittee shall tag the leak with a uniquely numbered tag, and shall record the leak location, component leaking, identification tag number, leak magnitude, date of leak detection, date of repair, method of repair, and post-repair monitoring measurement. Such records of leaks shall be maintained current and shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Components not accessible for EPA Method 21 inspection shall be visually and auditorily checked for leaks at least weekly and shall be monitored using EPA Method 21 at least annually. Any leak detected visually or auditorially shall be recorded and the leak shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. Any leak detected using EPA Method 21 shall be repaired according the leak magnitude as described above and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

11. In addition to the requirements above, pressure relief devices shall be inspected and monitored for leaks within 3 days of any known, likely, or suspected venting of such devices. [District Rule 2201] Federally Enforceable Through Title V Permit

12. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

14. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

15. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

16. True Vapor Pressure (TVP) of any organic liquid, except for crude oil with an API gravity of 20 degrees or less, shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

17. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

18. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

19. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

20. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

22. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from a common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

24. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

25. Permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2010] Federally Enforceable Through Title V Permit

27. Prior to taking the vapor control systems off-line, the water removal rate shall be controlled to maximize the fluid level in the tank and minimize the thickness of the oil pad. The liquid level shall be raised to displace at least 90% of the tank liquid capacity using water. The inflow of crude oil and water shall be stopped and the vapor control system shall continue to operate for at least 24 hours prior to opening the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

28. After the inflow of crude oil and water has stopped and the vapor control system has operated for at least 24 hours, the tank shall be isolated or disconnected from the vapor control system, the tank drain shall be opened, the pressure-vacuum relief valve shall be opened or bypassed, and the tank shall be drained. [District Rule 2010] Federally Enforceable Through Title V Permit

29. The tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2010] Federally Enforceable Through Title V Permit

30. Steam Cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2010] Federally Enforceable Through Title V Permit

31. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2010] Federally Enforceable Through Title V Permit

32. Within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2010] Federally Enforceable Through Title V Permit

33. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-610-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
4,530 BBL FIXED ROOF CRUDE OIL SETTLING TANK #20 AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS (S-1131 AND S-1127)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-613-19 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
10,000 BBL 55' DIA X 24' HIGH FIXED ROOF CRUDE OIL PRODUCTION TANK, SHIPPING #40 (STATION 36) VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1131-598

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank is authorized to receive fluids from facilities S-1131 and S-1127. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank is authorized to receive fluids from station 36 "Surge" tanks receiving production from steam-enhanced wells with closed well casing vents. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
5. Permittee shall maintain records of number and type of components in gas service installed. Permittee shall update such records when new gas handling components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fugitive VOC emission rate, calculated using the Oil and Gas Production Operations Average Emission Factors, U.S. EPA Protocol for Equipment Leak Emission Estimates, Table 2-4 (EPA-453/R-95-017) November 1995 from the total number of vapor components associated with tank and vapor control system shall not exceed 5.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank roof, tank shell, tank vapor space appurtenances, vapor control system piping, and vapor control system components shall be inspected and monitored using EPA Method 21 at least monthly. Items found to be not leaking may then be inspected and monitored at least once every 3 months until a leak is detected at which time the inspection and monitoring frequency shall revert to monthly until such time that two consecutive monthly inspections reveal with no leaks at which time the inspection and monitoring frequency shall revert to at least once every 3 months. [District Rule 2201] Federally Enforceable Through Title V Permit
8. A visible mist, liquid dripping at the rate of more than 3 drops per minute, and vapor leaks of 50,000 ppm or greater VOC as methane shall be repaired as expeditiously as possible but in no case beyond 24 hours of detecting the leak and shall be re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 10,000 ppm and less than 50,000 ppm VOC as methane shall be repaired within 5 days of detecting the leak and re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 1,000 ppm and less than 10,000 ppm VOC as methane shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Upon detection of a leak, permittee shall tag the leak with a uniquely numbered tag, and shall record the leak location, component leaking, identification tag number, leak magnitude, date of leak detection, date of repair, method of repair, and post-repair monitoring measurement. Such records of leaks shall be maintained current and shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Components not accessible for EPA Method 21 inspection shall be visually and auditorily checked for leaks at least weekly and shall be monitored using EPA Method 21 at least annually. Any leak detected visually or auditorially shall be recorded and the leak shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. Any leak detected using EPA Method 21 shall be repaired according the leak magnitude as described above and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

11. In addition to the requirements above, pressure relief devices shall be inspected and monitored for leaks within 3 days of any known, likely, or suspected venting of such devices. [District Rule 2201] Federally Enforceable Through Title V Permit

12. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

14. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

15. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

16. True Vapor Pressure (TVP) of any organic liquid, except for crude oil with an API gravity of 20 degrees or less, shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

17. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

18. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

19. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

20. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

22. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from a common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

24. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

25. Permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2010] Federally Enforceable Through Title V Permit

27. Prior to taking the vapor control systems off-line, the water removal rate shall be controlled to maximize the fluid level in the tank and minimize the thickness of the oil pad. The liquid level shall be raised to displace at least 90% of the tank liquid capacity using water. The inflow of crude oil and water shall be stopped and the vapor control system shall continue to operate for at least 24 hours prior to opening the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

28. After the inflow of crude oil and water has stopped and the vapor control system has operated for at least 24 hours, the tank shall be isolated or disconnected from the vapor control system, the tank drain shall be opened, the pressure-vacuum relief valve shall be opened or bypassed, and the tank shall be drained. [District Rule 2010] Federally Enforceable Through Title V Permit

29. The tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2010] Federally Enforceable Through Title V Permit

30. Steam Cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2010] Federally Enforceable Through Title V Permit

31. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2010] Federally Enforceable Through Title V Permit

32. Within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2010] Federally Enforceable Through Title V Permit

33. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-615-8 **EXPIRATION DATE:** 02/28/2007

DRAFT

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
5,410 BBL FIXED ROOF CRUDE OIL WASH TANK #2-B AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS (S-1131 AND S-1127)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-619-8 **EXPIRATION DATE:** 02/28/2007

DRAFT

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
5,410 BBL FIXED ROOF CRUDE OIL WASH TANK #1-B AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS (S-1131 AND S-1127)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-620-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
5,410 BBL FIXED ROOF CRUDE OIL WASH TANK #2 AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS (S-1131 AND S-1127)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-621-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
4,470 BBL FIXED ROOF CRUDE OIL SETTLING TANK #45 AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS (S-1131 AND S-1127)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-622-4 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
52,460 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK #60GK2

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-623-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
4,470 BBL FIXED ROOF CRUDE OIL SETTLING TANK #44 AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS (S-1131 AND S-1127)

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-625-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
4,470 BBL FIXED ROOF CRUDE OIL SETTLING TANK #46 AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS (S-1131 AND S-1127)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-626-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
8,890 BBL FIXED ROOF CRUDE OIL WASH TANK #10-2 AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-627-8 **EXPIRATION DATE:** 02/28/2007

DRAFT

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
8,890 BBL FIXED ROOF CRUDE OIL WASH TANK #10-3 AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-628-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
8,890 BBL FIXED ROOF CRUDE OIL WASH TANK #10-1 AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-629-11 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
37,600 BBL FIXED ROOF CRUDE SURGE TANK #6 (STATION 36) WITH VAPOR CONTROL SYSTEM LISTED ON S-1131-598

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank is authorized to receive fluids from facilities S-1131 and S-1127. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
4. Permittee shall maintain records of number and type of components in gas service installed. Permittee shall update such records when new gas handling components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fugitive VOC emission rate, calculated using the Oil and Gas Production Operations Average Emission Factors, U.S. EPA Protocol for Equipment Leak Emission Estimates, Table 2-4 (EPA-453/R-95-017) November 1995 from the total number of vapor components associated with tank and vapor control system shall not exceed 6.6 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall be equipped with an operational and calibrated stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank roof, tank shell, tank vapor space appurtenances, vapor control system piping, and vapor control system components shall be inspected and monitored using EPA Method 21 at least monthly. Items found to be not leaking may then be inspected and monitored at least once every 3 months until a leak is detected at which time the inspection and monitoring frequency shall revert to monthly until such time that two consecutive monthly inspections reveal with no leaks at which time the inspection and monitoring frequency shall revert to at least once every 3 months. [District Rule 2201] Federally Enforceable Through Title V Permit
8. A visible mist, liquid dripping at the rate of more than 3 drops per minute, and vapor leaks of 50,000 ppm or greater VOC as methane shall be repaired as expeditiously as possible but in no case beyond 24 hours of detecting the leak and shall be re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 10,000 ppm and less than 50,000 ppm VOC as methane shall be repaired within 5 days of detecting the leak and re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 1,000 ppm and less than 10,000 ppm VOC as methane shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Upon detection of a leak, permittee shall tag the leak with a uniquely numbered tag, and shall record the leak location, component leaking, identification tag number, leak magnitude, date of leak detection, date of repair, method of repair, and post-repair monitoring measurement. Such records of leaks shall be maintained current and shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Components not accessible for EPA Method 21 inspection shall be visually and auditorily checked for leaks at least weekly and shall be monitored using EPA Method 21 at least annually. Any leak detected visually or auditorially shall be recorded and the leak shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. Any leak detected using EPA Method 21 shall be repaired according the leak magnitude as described above and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

11. In addition to the requirements above, pressure relief devices shall be inspected and monitored for leaks within 3 days of any known, likely, or suspected venting of such devices. [District Rule 2201] Federally Enforceable Through Title V Permit

12. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

14. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

15. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

16. True Vapor Pressure (TVP) of any organic liquid, except for crude oil with an API gravity of 20 degrees or less, shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

17. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

18. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

19. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

20. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

22. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from a common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

24. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

25. Permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2010] Federally Enforceable Through Title V Permit

27. Prior to taking the vapor control systems off-line, the water removal rate shall be controlled to maximize the fluid level in the tank and minimize the thickness of the oil pad. The liquid level shall be raised to displace at least 90% of the tank liquid capacity using water. The inflow of crude oil and water shall be stopped and the vapor control system shall continue to operate for at least 24 hours prior to opening the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

28. After the inflow of crude oil and water has stopped and the vapor control system has operated for at least 24 hours, the tank shall be isolated or disconnected from the vapor control system, the tank drain shall be opened, the pressure-vacuum relief valve shall be opened or bypassed, and the tank shall be drained. [District Rule 2010] Federally Enforceable Through Title V Permit

29. The tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2010] Federally Enforceable Through Title V Permit

30. Steam Cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2010] Federally Enforceable Through Title V Permit

31. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2010] Federally Enforceable Through Title V Permit

32. Within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2010] Federally Enforceable Through Title V Permit

33. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-630-11 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
1,579,200 GALLON FIXED ROOF CRUDE SURGE TANK #7 (STATION 36) WITH VAPOR CONTROL SYSTEM LISTED ON S-1131-598

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank is authorized to receive fluids from facilities S-1131 and S-1127. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
4. Permittee shall maintain records of number and type of components in gas service installed. Permittee shall update such records when new gas handling components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fugitive VOC emission rate, calculated using the Oil and Gas Production Operations Average Emission Factors, U.S. EPA Protocol for Equipment Leak Emission Estimates, Table 2-4 (EPA-453/R-95-017) November 1995 from the total number of vapor components associated with tank and vapor control system shall not exceed 5.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall be equipped with an operational and calibrated stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank roof, tank shell, tank vapor space appurtenances, vapor control system piping, and vapor control system components shall be inspected and monitored using EPA Method 21 at least monthly. Items found to be not leaking may then be inspected and monitored at least once every 3 months until a leak is detected at which time the inspection and monitoring frequency shall revert to monthly until such time that two consecutive monthly inspections reveal with no leaks at which time the inspection and monitoring frequency shall revert to at least once every 3 months. [District Rule 2201] Federally Enforceable Through Title V Permit
8. A visible mist, liquid dripping at the rate of more than 3 drops per minute, and vapor leaks of 50,000 ppm or greater VOC as methane shall be repaired as expeditiously as possible but in no case beyond 24 hours of detecting the leak and shall be re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 10,000 ppm and less than 50,000 ppm VOC as methane shall be repaired within 5 days of detecting the leak and re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 1,000 ppm and less than 10,000 ppm VOC as methane shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

9. Upon detection of a leak, permittee shall tag the leak with a uniquely numbered tag, and shall record the leak location, component leaking, identification tag number, leak magnitude, date of leak detection, date of repair, method of repair, and post-repair monitoring measurement. Such records of leaks shall be maintained current and shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Components not accessible for EPA Method 21 inspection shall be visually and auditorily checked for leaks at least weekly and shall be monitored using EPA Method 21 at least annually. Any leak detected visually or auditorially shall be recorded and the leak shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. Any leak detected using EPA Method 21 shall be repaired according the leak magnitude as described above and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

11. In addition to the requirements above, pressure relief devices shall be inspected and monitored for leaks within 3 days of any known, likely, or suspected venting of such devices. [District Rule 2201] Federally Enforceable Through Title V Permit

12. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

14. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

15. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

16. True Vapor Pressure (TVP) of any organic liquid, except for crude oil with an API gravity of 20 degrees or less, shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

17. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

18. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

19. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

20. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

22. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from a common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

24. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

25. Permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2010] Federally Enforceable Through Title V Permit

27. Prior to taking the vapor control systems off-line, the water removal rate shall be controlled to maximize the fluid level in the tank and minimize the thickness of the oil pad. The liquid level shall be raised to displace at least 90% of the tank liquid capacity using water. The inflow of crude oil and water shall be stopped and the vapor control system shall continue to operate for at least 24 hours prior to opening the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

28. After the inflow of crude oil and water has stopped and the vapor control system has operated for at least 24 hours, the tank shall be isolated or disconnected from the vapor control system, the tank drain shall be opened, the pressure-vacuum relief valve shall be opened or bypassed, and the tank shall be drained. [District Rule 2010] Federally Enforceable Through Title V Permit

29. The tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2010] Federally Enforceable Through Title V Permit

30. Steam Cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2010] Federally Enforceable Through Title V Permit

31. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2010] Federally Enforceable Through Title V Permit

32. Within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2010] Federally Enforceable Through Title V Permit

33. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-631-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
5,410 BBL FIXED ROOF CRUDE OIL WASH TANK #1 AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-632-8 **EXPIRATION DATE:** 02/28/2007

DRAFT

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
8,890 BBL FIXED ROOF CRUDE OIL WASH TANK #10-5 AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-633-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
8,890 BBL FIXED ROOF CRUDE OIL WASH TANK #10-6 AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-634-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
8,890 BBL FIXED ROOF CRUDE OIL WASH TANK #10-4 AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-635-8 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
5,410 BBL FIXED ROOF CRUDE OIL WASH TANK #2-A AUTHORIZED FOR RECEIPT OF FLUIDS FROM STATION 36 "SURGE" TANKS RECEIVING PRODUCTION FROM STEAM-ENHANCED WELLS WITH CLOSED WELL CASING VENTS

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-636-4 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
10,570 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, #10000 SHIP

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-638-11 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
37,600 BBL FIXED ROOF CRUDE SURGE TANK #2 (STATION 36) WITH VAPOR CONTROL SYSTEM LISTED ON S-1131-598

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank is authorized to receive fluids from facilities S-1131 and S-1127. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
4. Permittee shall maintain records of number and type of components in gas service installed. Permittee shall update such records when new gas handling components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fugitive VOC emission rate, calculated using the Oil and Gas Production Operations Average Emission Factors, U.S. EPA Protocol for Equipment Leak Emission Estimates, Table 2-4 (EPA-453/R-95-017) November 1995 from the total number of vapor components associated with tank and vapor control system shall not exceed 7.4 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall be equipped with an operational and calibrated stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank roof, tank shell, tank vapor space appurtenances, vapor control system piping, and vapor control system components shall be inspected and monitored using EPA Method 21 at least monthly. Items found to be not leaking may then be inspected and monitored at least once every 3 months until a leak is detected at which time the inspection and monitoring frequency shall revert to monthly until such time that two consecutive monthly inspections reveal with no leaks at which time the inspection and monitoring frequency shall revert to at least once every 3 months. [District Rule 2201] Federally Enforceable Through Title V Permit
8. A visible mist, liquid dripping at the rate of more than 3 drops per minute, and vapor leaks of 50,000 ppm or greater VOC as methane shall be repaired as expeditiously as possible but in no case beyond 24 hours of detecting the leak and shall be re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 10,000 ppm and less than 50,000 ppm VOC as methane shall be repaired within 5 days of detecting the leak and re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 1,000 ppm and less than 10,000 ppm VOC as methane shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Upon detection of a leak, permittee shall tag the leak with a uniquely numbered tag, and shall record the leak location, component leaking, identification tag number, leak magnitude, date of leak detection, date of repair, method of repair, and post-repair monitoring measurement. Such records of leaks shall be maintained current and shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Components not accessible for EPA Method 21 inspection shall be visually and auditorily checked for leaks at least weekly and shall be monitored using EPA Method 21 at least annually. Any leak detected visually or auditorially shall be recorded and the leak shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. Any leak detected using EPA Method 21 shall be repaired according the leak magnitude as described above and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

11. In addition to the requirements above, pressure relief devices shall be inspected and monitored for leaks within 3 days of any known, likely, or suspected venting of such devices. [District Rule 2201] Federally Enforceable Through Title V Permit

12. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

14. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

15. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

16. True Vapor Pressure (TVP) of any organic liquid, except for crude oil with an API gravity of 20 degrees or less, shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

17. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

18. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

19. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

20. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

22. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from a common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

24. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

25. Permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2010] Federally Enforceable Through Title V Permit

27. Prior to taking the vapor control systems off-line, the water removal rate shall be controlled to maximize the fluid level in the tank and minimize the thickness of the oil pad. The liquid level shall be raised to displace at least 90% of the tank liquid capacity using water. The inflow of crude oil and water shall be stopped and the vapor control system shall continue to operate for at least 24 hours prior to opening the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

28. After the inflow of crude oil and water has stopped and the vapor control system has operated for at least 24 hours, the tank shall be isolated or disconnected from the vapor control system, the tank drain shall be opened, the pressure-vacuum relief valve shall be opened or bypassed, and the tank shall be drained. [District Rule 2010] Federally Enforceable Through Title V Permit

29. The tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2010] Federally Enforceable Through Title V Permit

30. Steam Cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2010] Federally Enforceable Through Title V Permit

31. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2010] Federally Enforceable Through Title V Permit

32. Within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2010] Federally Enforceable Through Title V Permit

33. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-641-11 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
37,600 BBL FIXED ROOF CRUDE SURGE TANK #1 (STATION 36) WITH VAPOR CONTROL SYSTEM LISTED ON S-1131-598

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank is authorized to receive fluids from facilities S-1131 and S-1127. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
4. Permittee shall maintain records of number and type of components in gas service installed. Permittee shall update such records when new gas handling components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fugitive VOC emission rate, calculated using the Oil and Gas Production Operations Average Emission Factors, U.S. EPA Protocol for Equipment Leak Emission Estimates, Table 2-4 (EPA-453/R-95-017) November 1995 from the total number of vapor components associated with tank and vapor control system shall not exceed 6.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall be equipped with an operational and calibrated stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank roof, tank shell, tank vapor space appurtenances, vapor control system piping, and vapor control system components shall be inspected and monitored using EPA Method 21 at least monthly. Items found to be not leaking may then be inspected and monitored at least once every 3 months until a leak is detected at which time the inspection and monitoring frequency shall revert to monthly until such time that two consecutive monthly inspections reveal with no leaks at which time the inspection and monitoring frequency shall revert to at least once every 3 months. [District Rule 2201] Federally Enforceable Through Title V Permit
8. A visible mist, liquid dripping at the rate of more than 3 drops per minute, and vapor leaks of 50,000 ppm or greater VOC as methane shall be repaired as expeditiously as possible but in no case beyond 24 hours of detecting the leak and shall be re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 10,000 ppm and less than 50,000 ppm VOC as methane shall be repaired within 5 days of detecting the leak and re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 1,000 ppm and less than 10,000 ppm VOC as methane shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Upon detection of a leak, permittee shall tag the leak with a uniquely numbered tag, and shall record the leak location, component leaking, identification tag number, leak magnitude, date of leak detection, date of repair, method of repair, and post-repair monitoring measurement. Such records of leaks shall be maintained current and shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Components not accessible for EPA Method 21 inspection shall be visually and auditorily checked for leaks at least weekly and shall be monitored using EPA Method 21 at least annually. Any leak detected visually or auditorially shall be recorded and the leak shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. Any leak detected using EPA Method 21 shall be repaired according the leak magnitude as described above and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

11. In addition to the requirements above, pressure relief devices shall be inspected and monitored for leaks within 3 days of any known, likely, or suspected venting of such devices. [District Rule 2201] Federally Enforceable Through Title V Permit

12. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

14. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

15. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

16. True Vapor Pressure (TVP) of any organic liquid, except for crude oil with an API gravity of 20 degrees or less, shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

17. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

18. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

19. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

20. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

22. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from a common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

24. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

25. Permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2010] Federally Enforceable Through Title V Permit

27. Prior to taking the vapor control systems off-line, the water removal rate shall be controlled to maximize the fluid level in the tank and minimize the thickness of the oil pad. The liquid level shall be raised to displace at least 90% of the tank liquid capacity using water. The inflow of crude oil and water shall be stopped and the vapor control system shall continue to operate for at least 24 hours prior to opening the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

28. After the inflow of crude oil and water has stopped and the vapor control system has operated for at least 24 hours, the tank shall be isolated or disconnected from the vapor control system, the tank drain shall be opened, the pressure-vacuum relief valve shall be opened or bypassed, and the tank shall be drained. [District Rule 2010] Federally Enforceable Through Title V Permit

29. The tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2010] Federally Enforceable Through Title V Permit

30. Steam Cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2010] Federally Enforceable Through Title V Permit

31. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2010] Federally Enforceable Through Title V Permit

32. Within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2010] Federally Enforceable Through Title V Permit

33. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-650-11 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
37,600 BBL FIXED ROOF CRUDE SURGE TANK #4 (STATION 36) WITH VAPOR CONTROL SYSTEM LISTED ON S-1131-598

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank is authorized to receive fluids from facilities S-1131 and S-1127. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
4. Permittee shall maintain records of number and type of components in gas service installed. Permittee shall update such records when new gas handling components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fugitive VOC emission rate, calculated using the Oil and Gas Production Operations Average Emission Factors, U.S. EPA Protocol for Equipment Leak Emission Estimates, Table 2-4 (EPA-453/R-95-017) November 1995 from the total number of vapor components associated with tank and vapor control system shall not exceed 7.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall be equipped with an operational and calibrated stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank roof, tank shell, tank vapor space appurtenances, vapor control system piping, and vapor control system components shall be inspected and monitored using EPA Method 21 at least monthly. Items found to be not leaking may then be inspected and monitored at least once every 3 months until a leak is detected at which time the inspection and monitoring frequency shall revert to monthly until such time that two consecutive monthly inspections reveal with no leaks at which time the inspection and monitoring frequency shall revert to at least once every 3 months. [District Rule 2201] Federally Enforceable Through Title V Permit
8. A visible mist, liquid dripping at the rate of more than 3 drops per minute, and vapor leaks of 50,000 ppm or greater VOC as methane shall be repaired as expeditiously as possible but in no case beyond 24 hours of detecting the leak and shall be re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 10,000 ppm and less than 50,000 ppm VOC as methane shall be repaired within 5 days of detecting the leak and re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 1,000 ppm and less than 10,000 ppm VOC as methane shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Upon detection of a leak, permittee shall tag the leak with a uniquely numbered tag, and shall record the leak location, component leaking, identification tag number, leak magnitude, date of leak detection, date of repair, method of repair, and post-repair monitoring measurement. Such records of leaks shall be maintained current and shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Components not accessible for EPA Method 21 inspection shall be visually and auditorily checked for leaks at least weekly and shall be monitored using EPA Method 21 at least annually. Any leak detected visually or auditorially shall be recorded and the leak shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. Any leak detected using EPA Method 21 shall be repaired according the leak magnitude as described above and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

11. In addition to the requirements above, pressure relief devices shall be inspected and monitored for leaks within 3 days of any known, likely, or suspected venting of such devices. [District Rule 2201] Federally Enforceable Through Title V Permit

12. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

14. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

15. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

16. True Vapor Pressure (TVP) of any organic liquid, except for crude oil with an API gravity of 20 degrees or less, shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

17. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

18. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

19. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

20. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

22. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from a common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

24. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

25. Permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2010] Federally Enforceable Through Title V Permit

27. Prior to taking the vapor control systems off-line, the water removal rate shall be controlled to maximize the fluid level in the tank and minimize the thickness of the oil pad. The liquid level shall be raised to displace at least 90% of the tank liquid capacity using water. The inflow of crude oil and water shall be stopped and the vapor control system shall continue to operate for at least 24 hours prior to opening the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

28. After the inflow of crude oil and water has stopped and the vapor control system has operated for at least 24 hours, the tank shall be isolated or disconnected from the vapor control system, the tank drain shall be opened, the pressure-vacuum relief valve shall be opened or bypassed, and the tank shall be drained. [District Rule 2010] Federally Enforceable Through Title V Permit

29. The tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2010] Federally Enforceable Through Title V Permit

30. Steam Cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2010] Federally Enforceable Through Title V Permit

31. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2010] Federally Enforceable Through Title V Permit

32. Within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2010] Federally Enforceable Through Title V Permit

33. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-651-11 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
37,600 BBL FIXED ROOF CRUDE SURGE TANK #3 (STATION 36) WITH VAPOR CONTROL SYSTEM LISTED ON S-1131-598

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank is authorized to receive fluids from facilities S-1131 and S-1127. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
4. Permittee shall maintain records of number and type of components in gas service installed. Permittee shall update such records when new gas handling components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fugitive VOC emission rate, calculated using the Oil and Gas Production Operations Average Emission Factors, U.S. EPA Protocol for Equipment Leak Emission Estimates, Table 2-4 (EPA-453/R-95-017) November 1995 from the total number of vapor components associated with tank and vapor control system shall not exceed 7.7 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall be equipped with an operational and calibrated stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank roof, tank shell, tank vapor space appurtenances, vapor control system piping, and vapor control system components shall be inspected and monitored using EPA Method 21 at least monthly. Items found to be not leaking may then be inspected and monitored at least once every 3 months until a leak is detected at which time the inspection and monitoring frequency shall revert to monthly until such time that two consecutive monthly inspections reveal with no leaks at which time the inspection and monitoring frequency shall revert to at least once every 3 months. [District Rule 2201] Federally Enforceable Through Title V Permit
8. A visible mist, liquid dripping at the rate of more than 3 drops per minute, and vapor leaks of 50,000 ppm or greater VOC as methane shall be repaired as expeditiously as possible but in no case beyond 24 hours of detecting the leak and shall be re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 10,000 ppm and less than 50,000 ppm VOC as methane shall be repaired within 5 days of detecting the leak and re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 1,000 ppm and less than 10,000 ppm VOC as methane shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a leak, permittee shall tag the leak with a uniquely numbered tag, and shall record the leak location, component leaking, identification tag number, leak magnitude, date of leak detection, date of repair, method of repair, and post-repair monitoring measurement. Such records of leaks shall be maintained current and shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Components not accessible for EPA Method 21 inspection shall be visually and auditorily checked for leaks at least weekly and shall be monitored using EPA Method 21 at least annually. Any leak detected visually or auditorially shall be recorded and the leak shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. Any leak detected using EPA Method 21 shall be repaired according the leak magnitude as described above and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

11. In addition to the requirements above, pressure relief devices shall be inspected and monitored for leaks within 3 days of any known, likely, or suspected venting of such devices. [District Rule 2201] Federally Enforceable Through Title V Permit

12. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

14. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

15. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

16. True Vapor Pressure (TVP) of any organic liquid, except for crude oil with an API gravity of 20 degrees or less, shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

17. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

18. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

19. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

20. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

22. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from a common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

24. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit

25. Permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2010] Federally Enforceable Through Title V Permit

27. Prior to taking the vapor control systems off-line, the water removal rate shall be controlled to maximize the fluid level in the tank and minimize the thickness of the oil pad. The liquid level shall be raised to displace at least 90% of the tank liquid capacity using water. The inflow of crude oil and water shall be stopped and the vapor control system shall continue to operate for at least 24 hours prior to opening the tank. [District Rule 2010] Federally Enforceable Through Title V Permit

28. After the inflow of crude oil and water has stopped and the vapor control system has operated for at least 24 hours, the tank shall be isolated or disconnected from the vapor control system, the tank drain shall be opened, the pressure-vacuum relief valve shall be opened or bypassed, and the tank shall be drained. [District Rule 2010] Federally Enforceable Through Title V Permit

29. The tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2010] Federally Enforceable Through Title V Permit

30. Steam Cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2010] Federally Enforceable Through Title V Permit

31. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2010] Federally Enforceable Through Title V Permit

32. Within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2010] Federally Enforceable Through Title V Permit

33. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-652-4

EXPIRATION DATE: 02/28/2007

DRAFT

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
54,460 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK #60GK1

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-663-4 **EXPIRATION DATE:** 02/28/2007

SECTION: SE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
250 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK #TK2-4

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-670-4 **EXPIRATION DATE:** 02/28/2007

SECTION: SW05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK #0.5GK37

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-671-4

EXPIRATION DATE: 02/28/2007

DRAFT

SECTION: SW05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK #0.5GK36

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-702-4 **EXPIRATION DATE:** 02/28/2007

SECTION: 09 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
250 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, #TK8-10

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-1131-716-19 **EXPIRATION DATE:** 02/28/2007

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 6280 STEAM ENHANCED OIL PRODUCTION WELLS WITH CLOSED CASING VENTS PRODUCING TO TANKS WITH VAPOR CONTROL

PERMIT UNIT REQUIREMENTS

1. Operation shall include no more than 6,280 steam enhanced crude oil production wells with closed casing vents. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain a current listing of all steam-enhanced wells in the central Kern County fields heavy oil production stationary source with closed casing vents that direct fluids to uncontrolled storage tanks and a current listing of all permit numbers of front-line equipment receiving produced fluids from the wells; shall update the list whenever a well or front-line equipment is added, replaced or deleted; and shall make such listing readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Well casing vents shall remain closed at all times except during periods of actual service or repair when wells are not producing. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Any increase to the maximum number of steam enhanced oil production wells with closed casing vents shall require prior authorization by an Authority to Construct. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Steam-enhanced production wells with closed well casing vents shall each have a visible identification number. Field personnel shall be provided with written instructions concerning proper operation and maintenance of the closed casing vent wells. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Total number of well casing and casing vent leaks from steam-enhanced oil production wells in this TEOR operation shall not exceed one leak detected for each 20 wells tested, with a minimum of 362 wells tested. A leak is defined as a reading in excess of 10,000 ppm when measured with a portable hydrocarbon detection instrument calibrated with methane in accordance with EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Components to be screened shall be identified and categorized according to the following equipment types: connectors, flanges, open-ended lines (sample connections, drains, bleed valves, etc.), pump seals, valves with visible actuators, and other (pressure relief devices, compressor seals, polished rods stuffing boxes, meters, etc.). Components shall be further identified and categorized according to the following types of service: gas/vapor, liquid with an API gravity of 20 degrees or more, and liquid with an API gravity less than 20 degrees. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Number of fugitive components serving well casing and casing vents shall not exceed: 55,998 valves; 151 pump seals; 1,508,592 connectors; 110,634 flanges; 6,566 open-ended lines (sample connections, drains, bleed valves, etc.); and 6,280 other (pressure relief devices, compressor seals, polished rods stuffing boxes, meters, etc). [District Rule 2201] Federally Enforceable Through Title V Permit
9. Component screening shall be performed using a portable hydrocarbon detection instrument calibrated with methane in accordance with EPA Reference Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Portable hydrocarbon detection instrument shall be operated and calibrated in accordance with recommendations in CAPCOA/CARB's California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities (February, 1999): detection instrument shall be calibrated with methane; instrument flow rate range shall be maintained at 0.7 to 1.2 liters per minute; 5 second response time to maximum reading shall be achieved; instrument probe outside diameter of 3/16 inch; and background screening distance shall be no less than 25 centimeters. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Flanges shall be monitored with portable hydrocarbon detection instrument along the entire circumference of the flange-gasket interface. Threaded connections, tubing fittings, and other types of non-permanent joints shall be monitored along the entire circumference of joint interface. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Valves shall be monitored with portable hydrocarbon detection instrument where the stem comes through the packing gland, and at any attached or connected body flange(s), bonnet flange(s), or plug(s). [District Rule 2201] Federally Enforceable Through Title V Permit
13. All other components such as diaphragms, dump arms, instruments, meters, polished rods stuffing boxes shall be monitored at all points of possible emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The crude oil production from wells associated with this permit unit shall not lie within 1,000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
15. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
16. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
17. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
18. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit
19. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
20. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

22. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

23. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

24. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

25. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

26. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

27. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

28. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

29. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

30. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

31. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

33. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

34. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

35. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

36. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

37. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

38. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

39. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

40. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

41. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

42. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

43. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

44. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

45. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

46. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

47. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

48. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

49. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

50. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

51. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

52. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

53. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit

54. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit

55. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

56. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-724-4 **EXPIRATION DATE:** 02/28/2007

SECTION: NE05 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
GASOLINE DISPENSING OPERATION WITH TWO 10,000 GALLON UNDERGROUND STORAGE TANKS SERVED BY OPW PHASE I ENHANCED VAPOR RECOVERY SYSTEM (VR-102-A), AND THREE FUELING POINTS WITH THREE GASOLINE DISPENSING NOZZLES SERVED BY HEALY PHASE II ENHANCED VAPOR RECOVERY SYSTEM WITHOUT ISD (VR-201-E) (KERN RIVER)

PERMIT UNIT REQUIREMENTS

1. The permittee shall store or dispose of gasoline in closed, non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4621, 5.6] Federally Enforceable Through Title V Permit
2. The vapor recovery systems and their components shall be installed, operated, and maintained in accordance with the State certification requirements. [District Rules 4621, 5.2; and 4622, 5.1] Federally Enforceable Through Title V Permit
3. The Phase I and Phase II vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621, 5.2; and 4622, 5.1] Federally Enforceable Through Title V Permit
4. Each ARB certified vapor recovery system shall be tested within 60 days of major modification or installation, except as otherwise allowed by this permit. For this condition, a major modification is considered to be replacing, repairing, or upgrading 75% or more of the certified system. [District Rule 4622, 6.4] Federally Enforceable Through Title V Permit
5. The ARB certified vapor recovery system and all of its components shall be maintained in good repair. Any ARB certified gasoline vapor recovery system, which has been installed and has been issued a permit to operate, shall not be removed regardless of the amount of gasoline dispensed or how the gasoline is delivered to the facility. [District Rule 4622, 5.2] Federally Enforceable Through Title V Permit
6. No owner or operator shall tamper with, or permit tampering with, the ARB certified vapor recovery system in a manner that would impair the operation or effectiveness of the system. [District Rule 4622, 5.9] Federally Enforceable Through Title V Permit
7. All nozzles shall be equipped with coaxial hose configurations. [District Rule 4622, 5.1] Federally Enforceable Through Title V Permit
8. Each gasoline storage tank shall be equipped with a permanent submerged fill pipe. [District Rule 4621, 5.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Each storage tank subject to this permit shall be equipped with an ARB certified Phase I vapor recovery system, which shall prevent at least 95% by weight of all gasoline vapors displaced during the filling of storage tanks from entering the atmosphere. The transfer of gasoline from any delivery vessel to any stationary storage container with 250 gallon capacity or more shall not be allowed unless the container is equipped with an ARB certified Phase I system and maintained and operated according to manufacturers specifications. [District Rule 4621, 5.2] Federally Enforceable Through Title V Permit

10. Each dispensing system shall be equipped with an ARB certified Phase II vapor recovery system which shall prevent at least 95% by weight of all gasoline vapors displaced during refueling of vehicles from entering the atmosphere. [District Rule 4622, 5.1] Federally Enforceable Through Title V Permit

11. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rules 4622, 3.25; and 2520, 9.1] Federally Enforceable Through Title V Permit

12. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo tank which attest to the vapor integrity of the tank. [District Rule 4621, 5.7] Federally Enforceable Through Title V Permit

13. No person shall top off a motor vehicle fuel tank. [District Rule 4622, 5.6] Federally Enforceable Through Title V Permit

14. No gasoline shall be transferred into vehicle fuel tanks if the vapor recovery system contains any defect listed in Section 94006 of Title 17 of the California Code of Regulations or in Section 5.4 of SJVUAPCD Rule 4622 (as amended February 17, 1994) until the defect has been repaired, replaced, or adjusted as necessary to correct the defect, and the District has reinspected the system or has authorized its use pending reinspection. [District Rule 4622, 5.4] Federally Enforceable Through Title V Permit

15. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622, 5.4] Federally Enforceable Through Title V Permit

16. Any defects identified shall be tagged "Out of Order"; the tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defect has been repaired, replaced or adjusted. In the case of defects identified by the District, tagged equipment shall be rendered inoperable and the tag shall not be removed until the District has been notified of the repairs, and/or the District has inspected and authorized the tagged equipment for use. A log containing at least the following shall be maintained: date and type of defect identified and date repaired, replaced or corrected. [District Rules 4622, 5.4] Federally Enforceable Through Title V Permit

17. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621, 6.3; and 4622, 5.2] Federally Enforceable Through Title V Permit

18. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621, 6.3; and 4622, 5.2] Federally Enforceable Through Title V Permit

19. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621, 6.3 and 4622, 6.4] Federally Enforceable Through Title V Permit

20. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621, 5.3; and 4622, 6.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

21. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621, 6.2] Federally Enforceable Through Title V Permit

22. The permittee shall perform and pass a Dynamic Back Pressure Test using ARB TP-201.4 at least once every 12 months. [District Rule 4622, 6.4, 6.5] Federally Enforceable Through Title V Permit

23. The permittee shall perform and pass a Static Leak Test for Underground Tanks using ARB TP-201.3 in accordance with the Executive Order specified in this permit for the Phase II Vapor Recovery System at least once every 12 months. [District Rules 4621, 5.3; and 4622, 6.4, 6.5] Federally Enforceable Through Title V Permit

24. The permittee shall perform and pass a Vapor-to-Liquid Volume Ratio Test using the test procedure defined in the Executive Order specified in this permit for the Phase II Vapor Recovery System at least once every six (6) months. [District Rule 4622, 6.4, 6.5] Federally Enforceable Through Title V Permit

25. The permittee shall perform and pass a Static Pressure Test for the Healy Clean Air Separator using the test procedure defined in the Executive Order specified in this permit for the Phase II Vapor Recovery System at least once every 12 months. [District Rule 4622, 6.4, 6.5] Federally Enforceable Through Title V Permit

26. The permittee shall perform and pass a Dispenser vapor Line Tightness test for each dispenser using the test procedure defined in the Installation, Operation and Maintenance manual of the Executive Order specified in this permit for the Phase II Vapor Recovery System at least once every 12 months. [District Rule 4622, 6.4, 6.5] Federally Enforceable Through Title V Permit

27. The permittee shall perform and pass a Pressure Integrity of Drop Tube Drain Valve Assembly Test using ARB TP-201.1C or a Pressure Integrity of Drop Tube Overfill Protection Devices Test using ARB TP-201.1D if an overfill protection device is installed, at least once every 36 months. [District Rule 4621, 5.3] Federally Enforceable Through Title V Permit

28. The permittee shall perform and pass a Static Torque of Rotatable Phase I Adaptors test using ARB procedure TP-201.1B at least once every 36 months. [District Rule 4621, 5.3] Federally Enforceable Through Title V Permit

29. The District shall be notified within 24 hours of the facility's pass/fail status after the performance of each test. [District Rule 1081] Federally Enforceable Through Title V Permit

30. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rules 4621, 6.1; and 4622, 6.2] Federally Enforceable Through Title V Permit

31. Vapor recovery systems and gasoline dispensing equipment shall be maintained leak-free as verified using EPA Test Method 21 and visual inspection. Leak testing shall be performed at least annually and within 60 days of all major modifications. For this condition, a major modification is considered to be replacing, repairing, or upgrading 75% or more of the certified system. A leak is defined as the dripping at a rate of more than three (3) drops per minute of liquid containing VOCs or a reading as methane in excess of 10,000 ppm as determined using EPA Method 21. [District Rules 4621, 3.19, 5.1, 5.6; and 4622, 3.17, 5.1, 5.6, 6.5] Federally Enforceable Through Title V Permit

32. Each operator shall maintain a leak inspection log containing, at a minimum, the following: inspector's name, location and description of component type where any leak is found; date of leak detection, emission level (ppm) if applicable, and date leak is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. Operator shall maintain all records of required monitoring data and support information for inspection for a period of five years. [District Rules 4621, 6.1; and 4622, 6.1, 6.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. The operator shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with Section 5.4 of Rule 4622. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) All applicable ARB Executive Orders, Approval Letters, and District Permits; 2) The manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 3) System and/or component testing requirements, including test schedules and passing criteria for each of the standard tests. The owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements; 4) Protocol for performing periodic maintenance inspections including the components to be inspected and the defects requiring repair; and 5) Additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622, 6.3] Federally Enforceable Through Title V Permit

35. The operator shall conduct periodic maintenance inspections based on the amount of gasoline dispensed by the facility in a calendar month as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621, 5.5; and 4622, 5.3] Federally Enforceable Through Title V Permit

36. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621, 5.5] Federally Enforceable Through Title V Permit

37. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the fueling instructions required by this permit are clearly displayed with the appropriate toll-free complaint phone number and toxic warning signs; 2) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 3) the hoses are not torn, flattened or crimped; 4) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 5) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622, 5.3] Federally Enforceable Through Title V Permit

38. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622, 5.4] Federally Enforceable Through Title V Permit

39. The gasoline throughput for this permit unit shall not exceed 600,000 gallons in any one calendar year. [District Rule 4622, 5.2] Federally Enforceable Through Title V Permit

40. The operator shall maintain monthly and annual gasoline throughput records. [District Rules 4621, 6.1; and 4622, 6.2] Federally Enforceable Through Title V Permit

41. The operator shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622, 6.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

42. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622, 6.3] Federally Enforceable Through Title V Permit

43. All records required by this permit shall be retained on-site for a period of at least five years, and shall be made available for inspection upon request. [District Rule 4622, 6.1, 6.2] Federally Enforceable Through Title V Permit

44. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4621 (as amended December 20, 2007), and 4622 (as amended December 20, 2007). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

45. This unit is not associated with loading at a bulk gasoline terminal (as defined in 40CFR$^{\perp}$ 60.501). Therefore, the requirements of 40 CFR 60 Subparts XX do not apply to this permit unit. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-833-3 **EXPIRATION DATE:** 02/28/2007

SECTION: NW5 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
240 BHP DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

DRAFT

PERMIT UNIT REQUIREMENTS

1. {2413} No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101, 5.1] Federally Enforceable Through Title V Permit
2. {2414} Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
3. The engine shall be equipped with a positive crankcase ventilation (PCV) system or a crankcase emissions control device of at least 90% control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 5.7.4 and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702, 5.7.2] Federally Enforceable Through Title V Permit
6. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [17 CCR 93115]
8. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule 4702, 4.2.1] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702, 5.7.3] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.), and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rules 4702, 5.7 and 2520, 9.4.2 and 17 CCR 93115] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

11. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [District Rule 2520, 9.4.2 and 17 CCR 93115] Federally Enforceable Through Title V Permit

12. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 4702, 6.2 and 2520, 9.4.2 and 17 CCR 93115] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-858-12 **EXPIRATION DATE:** 02/28/2007

SECTION: SE29 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED NATIONAL STEAM GENERATOR (HSG# 50-43; DIS# 20628-79) WITH FLUE GAS RECIRCULATION, NORTH AMERICAN MODEL #5131-HGCR-62.5 BURNER, AND NORTH AMERICAN OPTIMIZER - (CANFIELD LEASE

DRAFT

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
5. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
6. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
7. Emission rates shall not exceed the following PM10: 0.109 lb/MMBtu, SOx (as SO2): 1.026 lb/MMBtu, NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2, VOC: 0.006 lb/MMBtu, and CO: 0.029 lb/MMBtu or 39 ppmv @ 3% O2. [District Rules 2201, 4305, and 4351] Federally Enforceable Through Title V Permit
8. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rules 2201 and 4406] Federally Enforceable Through Title V Permit
9. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4406] Federally Enforceable Through Title V Permit
10. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

11. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months, except as provided below. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit

12. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit

13. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit

14. Compliance demonstration (source testing) shall be conducted by independent testing laboratories and shall be witnessed or authorized by the District. Sample collection shall be done by an ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

15. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

16. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

17. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans, or other test methods approved by the District. [District Rules 1081, 4305, and 4351] Federally Enforceable Through Title V Permit

18. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

19. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit

20. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3 and Kern County Rules 404 and 408] Federally Enforceable Through Title V Permit

22. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit

23. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

27. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

31. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rule 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

33. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

34. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

35. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301 and 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

36. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

37. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

38. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-859-13 **EXPIRATION DATE:** 02/28/2007

SECTION: SE05 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR (HSG# 50-51; DIS# 19161- 75) WITH A NORTH AMERICAN MODEL GLE MAGNA-FLAME, LOW NOX BURNER, FLUE GAS RECIRCULATION (FGR) SYSTEM AND NORTH AMERICAN OPTIMIZER (SAN JOAQUIN LOWER)

DRAFT

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No less than 4.54 miles of roads shall be paved and maintained to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Only hot mix asphalt of a type conforming to Caltrans Standard Specifications shall be used in the paving or maintenance of roads used to provide particulate matter offsets for Project 62 and 95. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Kern County Rule 407] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 1.026 lb-SOx/MMBtu, 0.108 lb-PM10/MMBtu, or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Emissions from the steam generator shall not exceed either of the following limits: 54.0 lb-NOx/day or 43.5 lb-CO/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.0182 lb-NOx/MMBtu or 39 ppmvd CO @ 3% O2 or 0.029 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4351, 5.1] Federally Enforceable Through Title V Permit
8. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rules 2201 and 4351] Federally Enforceable Through Title V Permit
9. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit
10. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Flue gas recirculation shall be utilized, as needed, in conjunction with low-NOx burner to maintain ongoing compliance with permitted emission limits. [District Rules 2201, 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

12. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

13. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

14. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

15. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit

16. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

17. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit

18. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5 and 4306, 5.5.5] Federally Enforceable Through Title V Permit

21. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit

22. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

23. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

24. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

25. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

26. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

27. If the steam generator is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. If the steam generator is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM D 1072, D 3031, D 4084, D 3246, double GC for H2S and mercaptans, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. If the steam generator is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rule 4406, 4.0] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rule 4406, 4.0] Federally Enforceable Through Title V Permit

32. The fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 4305, 6.2, 4306, 6.2, and 4351, 6.2] Federally Enforceable Through Title V Permit

33. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit

34. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District Rule 2201] Federally Enforceable Through Title V Permit

35. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, and 4306, 6.1] Federally Enforceable Through Title V Permit

37. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301, and 4801 (Kern County Rule 407). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

38. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

39. {4194} Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

40. {4314} Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-861-2 **EXPIRATION DATE:** 02/28/2007

SECTION: SW32 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
1,354 BBL 35.5 FT. HIGH X 17 FT. DIAMETER, FIXED ROOF, CONSTANT LEVEL, CRUDE OIL WASH TANK

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank shall operate at constant liquid level, and the maximum temperature of the liquid stored shall not exceed 165 degrees Fahrenheit [District Rule 2201] Federally Enforceable Through Title V Permit
2. True vapor pressure of liquid stored in this permit unit shall not exceed 0.4 psia without prior District approval [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with an operational stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall keep accurate monthly records of the storage temperature of liquids stored in the tank, and such records shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate records of Reid vapor pressure updated at least once every 12 months, for a period of five years, and shall make records readily available for District inspection upon request. [District Rule 2201; and 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
8. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
9. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
10. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
11. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

12. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-862-2 **EXPIRATION DATE:** 02/28/2007

SECTION: SW32 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
1,354 BBL 35.5 FT. HIGH X 17 FT. DIAMETER, FIXED ROOF, CONSTANT LEVEL, CRUDE OIL WASH TANK

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank shall operate at constant liquid level, and the maximum temperature of the liquid stored shall not exceed 165 degrees Fahrenheit [District Rule 2201] Federally Enforceable Through Title V Permit
2. True vapor pressure of liquid stored in this permit unit shall not exceed 0.4 psia without prior District approval [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with an operational stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall keep accurate monthly records of the storage temperature of liquids stored in the tank, and such records shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate records of Reid vapor pressure updated at least once every 12 months, for a period of five years, and shall make records readily available for District inspection upon request. [District Rule 2201; and 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
8. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
9. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
10. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
11. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

12. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-877-13 **EXPIRATION DATE:** 02/28/2007

SECTION: 04 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MM BTU/HR STRUTHERS NATURAL GAS/VAPOR RECOVERY GAS FIRED STRUTHERS STEAM GENERATOR #46 WITH FGR, NORTH AMERICAN MODEL GLE 4231 BURNER AND O2 CONTROLLER (CENTRAL PLANT)

DRAFT

PERMIT UNIT REQUIREMENTS

1. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
2. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
3. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
4. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit
5. Steam generator shall be equipped with operational fuel gas volume flowmeter and vapor recovery gas volume flowmeter. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Exhaust gas stack shall be equipped with adequate provisions facilitating the collection of gas samples consistent with EPA Test Methods. [District Rules 2201 and 1081] Federally Enforceable Through Title V Permit
7. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rules 2201 and 4406] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

8. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4406] Federally Enforceable Through Title V Permit

9. Only PUC quality natural gas and noncondensible TVR gas from tank battery and associated FWKO vessels served by vapor control system listed on S-1132-8, S-1132-90, S-1131-885, S-1131-1040, and TEOR vapor control gas from S-1131-903 and -909 shall be combusted in this unit without prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Total sulfur content of PUC quality natural gas combusted shall not exceed 0.2 grain/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Emission rates shall not exceed any of the following: SOx (as SO2): 64.0 lb/day, PM10: 115.2 lb/day, or VOC: 4.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Emission rates, except during startup and shutdown, shall not exceed any of the following: NOx (as NO2): 0.018 lb/MMBtu or 15 ppmvd @ 3% O2, or CO: 28 ppmvd @ 3% O2. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4351, 5.1] Federally Enforceable Through Title V Permit

14. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit

15. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit

16. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit

17. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit

18. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit

19. Compliance demonstration (source testing) shall be conducted by independent testing laboratories and shall be witnessed, or authorized by the District. Sample collection shall be done by ARB certified testing laboratory. [District Rules 1081 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

21. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit

23. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3 and Kern County Rules 404 and 408] Federally Enforceable Through Title V Permit

25. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit

26. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by double GC performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4306, 6.2.1] Federally Enforceable Through Title V Permit

30. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 4305, 6.3.2 and 4306, 6.3.2] Federally Enforceable Through Title V Permit

34. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rule 2520, 9.3.2, 4305, 6.3.2 and 4306, 6.3.2] Federally Enforceable Through Title V Permit

35. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). These tune-up procedures shall be completed according to District Rule 4304 (Adopted October 19, 1995) and tune-up test results shall show comparable results for each unit in the group. [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4306, 6.3.2] Federally Enforceable Through Title V Permit

36. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4306, 6.3.2] Federally Enforceable Through Title V Permit

37. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, and 4306, 6.1] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301 and 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

42. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, and 4320, 5.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

43. Formerly S-1143-3.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-879-18 **EXPIRATION DATE:** 02/28/2007

SECTION: 04 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR STRUTHERS NATURAL GAS/VAPOR RECOVERY GAS-FIRED STEAM GENERATOR WITH A NORTH AMERICAN GLE LOW-NOX BURNER WITH FGR AND AN O2 CONTROLLER (#70, CENTRAL PLANT)

PERMIT UNIT REQUIREMENTS

1. Steam generator shall be equipped with operational fuel gas volume flowmeter and vapor recovery gas volume flowmeter. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Exhaust gas stack shall be equipped with adequate provisions facilitating the collection of gas samples consistent with EPA Test Methods. [District Rules 2201 and 1081] Federally Enforceable Through Title V Permit
3. Only PUC quality natural gas and noncondensible TVR gas from tank battery and associated FWKO vessels served by vapor control system listed on S-1132-8, S-1132-90, S-1131-885, S-1131-1040, and TEOR vapor control gas from S-1131-903 and -909 shall be combusted in this unit without prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.055 lb-SOx/MMBtu, 0.013 lb-PM10/MMBtu, or 0.0028 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.0182 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4351, 5.1] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit
9. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit
10. Emissions from the steam generator shall not exceed either of the following limits: 54.0 lb-NOx/day or 55.5 lb-CO/day. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit

12. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

13. {2417} Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [County Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus)] Federally Enforceable Through Title V Permit

14. If the steam generator is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. If the steam generator is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM D 1072, D 3031, D 4084, D 3246, double GC for H2S and mercaptans, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. If the steam generator is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

18. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit
21. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit
22. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit
23. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5 and 4306, 5.5.5] Federally Enforceable Through Title V Permit
24. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
25. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx and CO emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
26. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
27. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
28. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
29. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit

31. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District Rule 2201] Federally Enforceable Through Title V Permit

32. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, and 4306, 6.1] Federally Enforceable Through Title V Permit

34. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301 and 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

35. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

36. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

37. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

38. Formerly S-1143-5.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-880-12 **EXPIRATION DATE:** 02/28/2007

SECTION: 04 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR STRUTHERS NATURAL GAS/VAPOR RECOVERY GAS-FIRED STEAM GENERATOR #140 WITH A NORTH AMERICAN MODEL #GLE-4231 LOW-NOX BURNER AND FLUE GAS RECIRCULATION (CENTRAL PLANT)

DRAFT

PERMIT UNIT REQUIREMENTS

1. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
2. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
3. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
4. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit
5. Steam generator shall be equipped with operational fuel gas volume flowmeter and vapor recovery gas volume flowmeter. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All wells producing from strata steamed by this unit shall be connected to a District-approved emissions control system, have District-approved closed casing vents or be District-approved uncontrolled cyclic wells. [District Rule 4401] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

7. Only PUC quality natural gas and noncondensible TVR gas from tank battery and associated FWKO vessels served by vapor control system listed on S-1132-8, S-1132-90, S-1131-885, S-1131-1040, and TEOR vapor control gas from S-1131-903 and -909 shall be combusted in this unit without prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit

8. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rule 1081] Federally Enforceable Through Title V Permit

9. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 1081] Federally Enforceable Through Title V Permit

10. The permittee shall keep daily records of the amount of natural gas combusted and the amount of TEOR/TVR gas incinerated. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit

11. Emission rates shall not exceed any of the following: SOx (as SO2): 105.1 lb/day, PM10: 19.2 lb/day, or VOC: 4.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Emission rates, except during startup and shutdown, shall not exceed any of the following: NOx (as NO2): 0.018 lb/MMBtu or 15 ppmvd @ 3% O2, or CO: 1.90 lb/hr or 41 ppmvd @3% O2. [District Rules 2201, 4305, 5.1 and 4306, 5.1] Federally Enforceable Through Title V Permit

13. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit

14. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit

15. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit

16. The stack concentration of NOx (as NO2), CO, and O2 shall be measured at least on a monthly basis, using District approved portable analyzers, in any calendar month in which the unit operates. [District Rules 2201, 2520, 9.3.2, 4305 and 4306] Federally Enforceable Through Title V Permit

17. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit

18. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit

19. Compliance demonstration (source testing) shall be conducted by independent testing laboratories and shall be witnessed, or authorized by the District. Sample collection shall be done by ARB certified testing laboratory. [District Rules 1081 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

21. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

22. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit

23. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3 and Kern County Rules 404 and 408] Federally Enforceable Through Title V Permit

25. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit

26. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by double GC performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4306, 6.2.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 4305, 6.3.2 and 4306, 6.3.2] Federally Enforceable Through Title V Permit

34. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rule 2520, 9.3.2, 4305, 6.3.2 and 4306, 6.3.2] Federally Enforceable Through Title V Permit

35. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). These tune-up procedures shall be completed according to District Rule 4304 (Adopted October 19, 1995) and tune-up test results shall show comparable results for each unit in the group. [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4306, 6.3.2] Federally Enforceable Through Title V Permit

36. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4306, 6.3.2] Federally Enforceable Through Title V Permit

37. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, and 4306, 6.1] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301 and 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

42. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

43. Formerly S-1143-6-8.

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-1131-881-13 **EXPIRATION DATE:** 02/28/2007

SECTION: 04 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR STRUTHERS NATURAL GAS/VAPOR RECOVERY GAS-FIRED STEAM GENERATOR WITH A NORTH AMERICAN GLE LOW-NOX BURNER WITH FLUE GAS RECIRCULATION (FGR) AND AN O2 CONTROLLER (CENTRAL PLANT)

PERMIT UNIT REQUIREMENTS

1. Steam generator shall be equipped with the following operational instrumentation: fuel gas volume flowmeter, vapor recovery gas volume flowmeter. [District Rules 2201 and 4305] Federally Enforceable Through Title V Permit
2. All wells producing from strata steamed by this unit shall be connected to a District-approved emissions control system, have District-approved closed casing vents or be District-approved uncontrolled cyclic wells. [District Rule 4401] Federally Enforceable Through Title V Permit
3. Only PUC quality natural gas and noncondensible TVR gas from tank battery and associated FWKO vessels served by vapor control system listed on S-1132-8, S-1132-90, S-1131-885, S-1131-1040, and TEOR vapor control gas from S-1131-903 and -909 shall be combusted in this unit without prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
4. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
5. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
6. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
7. Emissions from the steam generator shall not exceed any of the following limits: 0.07 lb-SOx/MMBtu, 0.013 lb-PM10/MMBtu, or 0.0028 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.0182 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4351, 5.1] Federally Enforceable Through Title V Permit
9. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit

12. Emissions from the steam generator shall not exceed either of the following limits: 54.0 lb-NOx/day or 55.5 lb-CO/day. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit

14. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

15. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

16. {2417} Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [County Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus)] Federally Enforceable Through Title V Permit

17. If the steam generator is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. If the steam generator is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM D 1072, D 3031, D 4084, D 3246, double GC for H2S and mercaptans, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. If the steam generator is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

23. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit

24. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

25. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit

26. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit

27. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5 and 4306, 5.5.5] Federally Enforceable Through Title V Permit

28. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

29. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx and CO emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

30. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

31. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

33. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

34. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit

35. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rule 1081] Federally Enforceable Through Title V Permit

36. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 1081] Federally Enforceable Through Title V Permit

37. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District Rule 2201] Federally Enforceable Through Title V Permit

38. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, and 4306, 6.1] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301 and 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

44. Formerly S-1143-6-8.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-883-13 **EXPIRATION DATE:** 02/28/2007

SECTION: 4 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MM BTU/HR STRUTHERS NATURAL GAS/VAPOR RECOVERY GAS FIRED STRUTHERS STEAM GENERATOR (#143) WITH A NORTH AMERICAN MODEL GLE MAGNA-FLAME LOW NOX BURNER, FLUE GAS RECIRCULATION (FGR) SYSTEM AND O2 CONTROLLER (CENTRAL PLANT)

DRAFT

PERMIT UNIT REQUIREMENTS

1. Only PUC quality natural gas and noncondensible TVR gas from tank battery and associated FWKO vessels served by vapor control system listed on S-1132-8, S-1132-90, S-1131-885, S-1131-1040, and TEOR vapor control gas from S-1131-903 and -909 shall be combusted in this unit without prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain with the permit a current listing of all thermally enhanced well vent control systems and tank vapor recovery systems providing vapors to this steam generator and shall make such listing readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. Flue gas recirculation shall be utilized, as needed, in conjunction with low-NOx burner to maintain ongoing compliance with permitted emission limits. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.07 lb-SOx/MMBtu, 0.013 lb-PM10/MMBtu, or 0.0028 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.0182 lb-NOx/MMBtu or 41 ppmvd CO @ 3% O2 or 0.03 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4351, 5.1] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit
9. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit
10. Emissions from the steam generator shall not exceed either of the following limits: 54.0 lb-NOx/day or 45.0 lb-CO/day. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

11. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit

12. Whenever the flue gas recirculation (FGR) system on this unit is switched from the open to the closed position, or from the closed to the open position, compliance source testing for NOx and CO emissions shall be conducted within 60 days of change of FGR operation date unless source testing with FGR system in both the open and closed position has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

13. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

14. {2417} Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [County Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus)] Federally Enforceable Through Title V Permit

15. If the steam generator is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. If the steam generator is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM D 1072, D 3031, D 4084, D 3246, double GC for H2S and mercaptans, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. If the steam generator is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

19. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

21. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit
22. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit
23. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit
24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5 and 4306, 5.5.5] Federally Enforceable Through Title V Permit
25. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
26. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx and CO emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
27. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
28. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
29. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
30. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit

32. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rule 1081] Federally Enforceable Through Title V Permit

33. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 1081] Federally Enforceable Through Title V Permit

34. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District NSR Rule] Federally Enforceable Through Title V Permit

35. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, and 4306, 6.1] Federally Enforceable Through Title V Permit

37. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301 and 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

38. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

39. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

40. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

41. Formerly S-1143-9.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-884-15 **EXPIRATION DATE:** 02/28/2007

SECTION: 04 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MM BTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STRUTHERS STEAM GENERATOR #144 EQUIPPED WITH NORTH AMERICAN MAGNA-FLAME GLE ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION. (CENTRAL PLANT)

DRAFT

PERMIT UNIT REQUIREMENTS

1. Only PUC quality natural gas and noncondensible TVR gas from tank battery and associated FWKO vessels served by vapor control system listed on S-1132-8, S-1132-90, S-1131-885, S-1131-1040, and TEOR vapor control gas from S-1131-903 and -909 shall be combusted in this unit without prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain with the permit a current listing of all thermally enhanced well vent control systems and tank vapor recovery systems providing vapors to this steam generator and shall make such listing readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. Flue gas recirculation shall be utilized, as needed, in conjunction with low-NOx burner to maintain ongoing compliance with permitted emission limits. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.07 lb-SOx/MMBtu, 0.013 lb-PM10/MMBtu, or 0.0028 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.0182 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4351, 5.1] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit
9. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit
10. Emissions from the steam generator shall not exceed either of the following limits: 54.0 lb-NOx/day or 55.5 lb-CO/day. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

11. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit

12. Whenever the flue gas recirculation (FGR) system on this unit is switched from the open to the closed position, or from the closed to the open position, compliance source testing for NOx and CO emissions shall be conducted within 60 days of change of FGR operation date unless source testing with FGR system in both the open and closed position has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

13. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

14. {2417} Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [County Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus)] Federally Enforceable Through Title V Permit

15. If the steam generator is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. If the steam generator is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM D 1072, D 3031, D 4084, D 3246, double GC for H2S and mercaptans, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. If the steam generator is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

19. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

21. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit

22. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit

23. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit

24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5 and 4306, 5.5.5] Federally Enforceable Through Title V Permit

25. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

26. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx and CO emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

27. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

28. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

29. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

30. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit

32. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rule 1081] Federally Enforceable Through Title V Permit

33. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 1081] Federally Enforceable Through Title V Permit

34. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District Rule 2201] Federally Enforceable Through Title V Permit

35. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, and 4306, 6.1] Federally Enforceable Through Title V Permit

37. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301 and 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

38. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

39. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

40. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

41. Formerly S-1143-10.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-885-21 **EXPIRATION DATE:** 02/28/2007

SECTION: SW03 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
5,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #3K-L75 WITH VAPOR CONTROL SYSTEM

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank is authorized to receive fluids from facilities S-1131 and S-1127. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Well vent vapor control systems S-1131-903, S-1131-909, and S-1131-598 may discharge vapors into compressor suction of this operation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall maintain records of number and type of components in gas service installed. Permittee shall update such records when new gas handling components are installed. Permittee shall maintain records of components exempted from counting, and the basis for exemption. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fugitive VOC emission rates shall be calculated using the Oil and Gas Production Operations Average Emission Factors, U.S. EPA Protocol for Equipment Leak Emission Estimates, Table 2-4 (EPA-453/R-95-017) November 1995 and the total number of vapor components. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC emission rate from components associated with vapor recovery trunk-line up to and including vapor compressors and approved disposal devices shall not exceed 23.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. VOC emission rate from vapor service components associated with this tank, up to the tie-in with the vapor recovery unit trunk-line, shall not exceed 5.33 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The fugitive VOC emission rate does not include piping and components handling produced fluids with API gravity less than 30 degrees. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The fugitive VOC emission rate does not include piping and components handling produced fluids having less than 10% VOC by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The fugitive VOC emission rate does not include components in water/oil service (water content of fluids handled greater than 50%). Permittee shall maintain records of annual testing to demonstrate that such fluid streams have at least 50% water by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Operator shall conduct quarterly sampling from the tank vapor control system's inlet header to qualify for exemption from fugitive component counts for components handling fluids with less than 10% VOC by weight. If 8 consecutive quarterly samplings show compliance, then sampling frequency shall only be required annually. Such sampling is deemed representative of tanks S-1131-608, -613, -629, -630, -638, -641, -650, -651, and -1097. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. VOC content of vapor shall be determined by ASTM D1945, ASTM D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Permittee shall maintain a written record of the VOC content of the gas sampled. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Collected VOC vapors shall be incinerated in steam generators S-1131-82, '-95, '-98, '-99, '-859, '-877, '-879, '-880, '-881, '-883, '-884, and '908 or disposed of in Department of Oil, Gas, and Geothermal Resources (DOGGR) approved vapor disposal well(s). [District Rule 2201] Federally Enforceable Through Title V Permit
15. Fluids stored or handled by tank shall be routed exclusively to the vapor-controlled "Surge" tanks at Station 36 (S-1131-598, '-629, '-630, '-638, '-641, '-650, '-651, and '-1097). [District Rule 2201] Federally Enforceable Through Title V Permit
16. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit
17. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
18. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit
19. Permittee shall notify the District Compliance division at least 24 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit
20. Prior to opening the tank to allow tank cleaning one of the following procedures must be followed: 1) operate the vapor control system for at least 24 hours after all the liquid in the tank has been drained; or 2) use liquid displacement, conducted by filling the tank with a suitable liquid such as water, clean produced water, or organic liquids with a TVP less than 0.5 psia; or conducted by floating the oil pad off with water such that 90% of the tank liquid capacity is displaced; or 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) displace vapors by filling the tank with a suitable gas, including air, nitrogen, carbon dioxide, or natural gas containing less than 10% VOC by weight, until a vapor displacement equivalent to at least 2.3 times the tank capacity is achieved; or 5) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V/Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations . [District Rule 2080] Federally Enforceable Through Title V Permit
21. The tank shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit
22. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit
23. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit
24. Within 48 hours after refilling the tank with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

26. Tank shall be equipped with an operational and calibrated stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit

27. Tank roof, tank shell, tank vapor space appurtances, vapor control system piping, and vapor control system components shall be inspected and monitored using EPA Method 21 at least monthly. Items found to be not leaking may then be inspected and monitored at least once every 3 months until a leak is detected at which time the inspection and monitoring frequency shall revert to monthly until such time that two consecutive monthly inspections reveal with no leaks at which time the inspection and monitoring frequency shall revert to at least once every 3 months. [District Rule 2201] Federally Enforceable Through Title V Permit

28. A visible mist, liquid dripping at the rate of more than 3 drops per minute, and vapor leaks of 50,000 ppm or greater VOC as methane shall be repaired as expeditiously as possible but in no case beyond 24 hours of detecting the leak and shall be re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 10,000 ppm and less than 50,000 ppm VOC as methane shall be repaired within 5 days of detecting the leak and re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 1,000 ppm and less than 10,000 ppm VOC as methane shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

29. Upon detection of a leak, permittee shall tag the leak with a uniquely numbered tag, and shall record the leak location, component leaking, identification tag number, leak magnitude, date of leak detection, date of repair, method of repair, and post-repair monitoring measurement. Such records of leaks shall be maintained current and shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

30. Components not accessible for EPA Method 21 inspection shall be visually and auditorily checked for leaks at least weekly and shall be monitored using EPA Method 21 at least annually. Any leak detected visually or auditorially shall be recorded and the leak shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. Any leak detected using EPA Method 21 shall be repaired according the leak magnitude as described above and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

31. In addition to the requirements above, pressure relief devices shall be inspected and monitored for leaks within 3 days of any known, likely, or suspected venting of such devices. [District Rule 2201] Federally Enforceable Through Title V Permit

32. True vapor pressure of any liquid introduced in this permit unit shall be less than 0.5 psia at (or before) tank liquid inlet and at tank storage temperature. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit

33. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

34. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

35. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. True Vapor Pressure (TVP) of any organic liquid, except for crude oil with an API gravity of 20 degrees or less, shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
37. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
38. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
39. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
40. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
41. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
42. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit
43. Permittee shall provide District with a copy of D.O.G.G.R. approval for each vapor disposal well prior to use for vapor injection. [District Rule 1070] Federally Enforceable Through Title V Permit
44. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. Formerly S-1143-21. [District Rule 2010] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-886-18 **EXPIRATION DATE:** ~~02/28/2007~~

SECTION: SW03 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
210,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #3K-S76 WITH VAPOR CONTROL SYSTEM LISTED ON S-1131-885

PERMIT UNIT REQUIREMENTS

1. Tank is authorized to receive fluids from facilities S-1131 and S-1127. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Well vent vapor control systems S-1131-903 and S-1131-909 may discharge vapors into compressor suction of this operation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC emission rate from vapor service components associated with this tank, up to the tie-in with the vapor recovery unit trunk-line, shall not exceed 5.33 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain an accurate fugitive component count and resultant emissions calculated using emission factors from U.S. EPA Publication 453/R-95-017, or other District-approved emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Steam generators authorized to incinerate collected VOC vapors are S-1131-877,'-880, '-881, '-882, '-883, and '-908. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Fluids stored or handled by tank shall be routed exclusively to the vapor-controlled "Surge" tanks at Station 36 (S-1131-598, '-629, '-630, '-638, '-641, '-650, '-651, and '-1097). [District Rule 2201] Federally Enforceable Through Title V Permit
8. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit
9. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
10. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit
11. Permittee shall notify the District Compliance division at least 24 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

12. Prior to opening the tank to allow tank cleaning one of the following procedures must be followed: 1) operate the vapor control system for at least 24 hours after all the liquid in the tank has been drained; or 2) use liquid displacement, conducted by filling the tank with a suitable liquid such as water, clean produced water, or organic liquids with a TVP less than 0.5 psia; or conducted by floating the oil pad off with water such that 90% of the tank liquid capacity is displaced; or 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) displace vapors by filling the tank with a suitable gas, including air, nitrogen, carbon dioxide, or natural gas containing less than 10% VOC by weight, until a vapor displacement equivalent to at least 2.3 times the tank capacity is achieved; or 5) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V/Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations . [District Rule 2080] Federally Enforceable Through Title V Permit
13. The tank shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit
14. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit
15. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit
16. Within 48 hours after refilling the tank with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
17. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit
18. Tank shall be equipped with an operational and calibrated stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Tank roof, tank shell, tank vapor space appurtances, vapor control system piping, and vapor control system components shall be inspected and monitored using EPA Method 21 at least monthly. Items found to be not leaking may then be inspected and monitored at least once every 3 months until a leak is detected at which time the inspection and monitoring frequency shall revert to monthly until such time that two consecutive monthly inspections reveal with no leaks at which time the inspection and monitoring frequency shall revert to at least once every 3 months. [District Rule 2201] Federally Enforceable Through Title V Permit
20. A visible mist, liquid dripping at the rate of more than 3 drops per minute, and vapor leaks of 50,000 ppm or greater VOC as methane shall be repaired as expeditiously as possible but in no case beyond 24 hours of detecting the leak and shall be re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 10,000 ppm and less than 50,000 ppm VOC as methane shall be repaired within 5 days of detecting the leak and re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 1,000 ppm and less than 10,000 ppm VOC as methane shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit
21. Upon detection of a leak, permittee shall tag the leak with a uniquely numbered tag, and shall record the leak location, component leaking, identification tag number, leak magnitude, date of leak detection, date of repair, method of repair, and post-repair monitoring measurement. Such records of leaks shall be maintained current and shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

22. Components not accessible for EPA Method 21 inspection shall be visually and auditorily checked for leaks at least weekly and shall be monitored using EPA Method 21 at least annually. Any leak detected visually or auditorially shall be recorded and the leak shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. Any leak detected using EPA Method 21 shall be repaired according the leak magnitude as described above and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

23. In addition to the requirements above, pressure relief devices shall be inspected and monitored for leaks within 3 days of any known, likely, or suspected venting of such devices. [District Rule 2201] Federally Enforceable Through Title V Permit

24. True vapor pressure of any liquid introduced in this permit unit shall be less than 0.5 psia at (or before) tank liquid inlet and at tank storage temperature. [District Rule 4623] Federally Enforceable Through Title V Permit

25. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

26. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

27. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

28. True Vapor Pressure (TVP) of any organic liquid, except for crude oil with an API gravity of 20 degrees or less, shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

29. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

30. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

31. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

32. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

33. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

34. Permittee shall provide District with a copy of D.O.G.G.R. approval for each vapor disposal well prior to use for vapor injection. [District Rule 1070] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

36. Formerly S-1143-22. [District Rule 2010] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-891-17 **EXPIRATION DATE:** 02/28/2007

SECTION: SE04 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
5,000 BBL FIXED ROOF PETROLEUM STORAGE TANK WITH VAPOR CONTROL SYSTEM LISTED ON S-1131-885

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank is authorized to receive fluids from facilities S-1131 and S-1127. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Well vent vapor control systems S-1131-903 and S-1131-909 may discharge vapors into compressor suction of this operation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC emission rate from vapor service components associated with this tank, up to the tie-in with the vapor recovery unit trunk-line, shall not exceed 5.33 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain an accurate fugitive component count and resultant emissions calculated using emission factors from U.S. EPA Publication 453/R-95-017, or other District-approved emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Steam generators authorized to incinerate collected VOC vapors are S-1131-877,'-880, '-881, '-882, '-883, and '-908. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Fluids stored or handled by tank shall be routed exclusively to the vapor-controlled "Surge" tanks at Station 36 (S-1131-598, '-629, '-630, '-638, '-641, '-650, '-651, and '-1097). [District Rule 2201] Federally Enforceable Through Title V Permit
8. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit
9. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
10. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit
11. Permittee shall notify the District Compliance division at least 24 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

12. Prior to opening the tank to allow tank cleaning one of the following procedures must be followed: 1) operate the vapor control system for at least 24 hours after all the liquid in the tank has been drained; or 2) use liquid displacement, conducted by filling the tank with a suitable liquid such as water, clean produced water, or organic liquids with a TVP less than 0.5 psia; or conducted by floating the oil pad off with water such that 90% of the tank liquid capacity is displaced; or 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) displace vapors by filling the tank with a suitable gas, including air, nitrogen, carbon dioxide, or natural gas containing less than 10% VOC by weight, until a vapor displacement equivalent to at least 2.3 times the tank capacity is achieved; or 5) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V/Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations . [District Rule 2080] Federally Enforceable Through Title V Permit
13. The tank shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit
14. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit
15. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit
16. Within 48 hours after refilling the tank with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
17. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit
18. Tank shall be equipped with an operational and calibrated stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Tank roof, tank shell, tank vapor space appurtances, vapor control system piping, and vapor control system components shall be inspected and monitored using EPA Method 21 at least monthly. Items found to be not leaking may then be inspected and monitored at least once every 3 months until a leak is detected at which time the inspection and monitoring frequency shall revert to monthly until such time that two consecutive monthly inspections reveal with no leaks at which time the inspection and monitoring frequency shall revert to at least once every 3 months. [District Rule 2201] Federally Enforceable Through Title V Permit
20. A visible mist, liquid dripping at the rate of more than 3 drops per minute, and vapor leaks of 50,000 ppm or greater VOC as methane shall be repaired as expeditiously as possible but in no case beyond 24 hours of detecting the leak and shall be re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 10,000 ppm and less than 50,000 ppm VOC as methane shall be repaired within 5 days of detecting the leak and re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 1,000 ppm and less than 10,000 ppm VOC as methane shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit
21. Upon detection of a leak, permittee shall tag the leak with a uniquely numbered tag, and shall record the leak location, component leaking, identification tag number, leak magnitude, date of leak detection, date of repair, method of repair, and post-repair monitoring measurement. Such records of leaks shall be maintained current and shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

22. Components not accessible for EPA Method 21 inspection shall be visually and auditorily checked for leaks at least weekly and shall be monitored using EPA Method 21 at least annually. Any leak detected visually or auditorially shall be recorded and the leak shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. Any leak detected using EPA Method 21 shall be repaired according the leak magnitude as described above and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

23. In addition to the requirements above, pressure relief devices shall be inspected and monitored for leaks within 3 days of any known, likely, or suspected venting of such devices. [District Rule 2201] Federally Enforceable Through Title V Permit

24. True vapor pressure of any liquid introduced in this permit unit shall be less than 0.5 psia at (or before) tank liquid inlet and at tank storage temperature. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit

25. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

26. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

27. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

28. True Vapor Pressure (TVP) of any organic liquid, except for crude oil with an API gravity of 20 degrees or less, shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

29. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

30. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

31. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

32. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

33. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

34. Permittee shall provide District with a copy of D.O.G.G.R. approval for each vapor disposal well prior to use for vapor injection. [District Rule 1070] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

36. Formerly S-1143-27. [District Rule 2010] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-892-17 **EXPIRATION DATE:** 02/28/2007

SECTION: SE04 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
5,000 BBL FIXED ROOF PETROLEUM STORAGE TANK WITH VAPOR CONTROL SYSTEM LISTED ON S-1131-885

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank is authorized to receive fluids from facilities S-1131 and S-1127. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Well vent vapor control systems S-1131-903 and S-1131-909 may discharge vapors into compressor suction of this operation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC emission rate from vapor service components associated with this tank, up to the tie-in with the vapor recovery unit trunk-line, shall not exceed 5.33 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain an accurate fugitive component count and resultant emissions calculated using emission factors from U.S. EPA Publication 453/R-95-017, or other District-approved emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Steam generators authorized to incinerate collected VOC vapors are S-1131-877,'-880, '-881, '-882, '-883, and '-908. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Fluids stored or handled by tank shall be routed exclusively to the vapor-controlled "Surge" tanks at Station 36 (S-1131-598, '-629, '-630, '-638, '-641, '-650, '-651, and '-1097). [District Rule 2201] Federally Enforceable Through Title V Permit
8. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit
9. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
10. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2010] Federally Enforceable Through Title V Permit
11. Permittee shall notify the District Compliance division at least 24 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

12. Prior to opening the tank to allow tank cleaning one of the following procedures must be followed: 1) operate the vapor control system for at least 24 hours after all the liquid in the tank has been drained; or 2) use liquid displacement, conducted by filling the tank with a suitable liquid such as water, clean produced water, or organic liquids with a TVP less than 0.5 psia; or conducted by floating the oil pad off with water such that 90% of the tank liquid capacity is displaced; or 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) displace vapors by filling the tank with a suitable gas, including air, nitrogen, carbon dioxide, or natural gas containing less than 10% VOC by weight, until a vapor displacement equivalent to at least 2.3 times the tank capacity is achieved; or 5) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V/Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations . [District Rule 2080] Federally Enforceable Through Title V Permit
13. The tank shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit
14. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit
15. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit
16. Within 48 hours after refilling the tank with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
17. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit
18. Tank shall be equipped with an operational and calibrated stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Tank roof, tank shell, tank vapor space appurtances, vapor control system piping, and vapor control system components shall be inspected and monitored using EPA Method 21 at least monthly. Items found to be not leaking may then be inspected and monitored at least once every 3 months until a leak is detected at which time the inspection and monitoring frequency shall revert to monthly until such time that two consecutive monthly inspections reveal with no leaks at which time the inspection and monitoring frequency shall revert to at least once every 3 months. [District Rule 2201] Federally Enforceable Through Title V Permit
20. A visible mist, liquid dripping at the rate of more than 3 drops per minute, and vapor leaks of 50,000 ppm or greater VOC as methane shall be repaired as expeditiously as possible but in no case beyond 24 hours of detecting the leak and shall be re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 10,000 ppm and less than 50,000 ppm VOC as methane shall be repaired within 5 days of detecting the leak and re-monitored using EPA Method 21 upon completion of the repair. Vapor leaks equal to or greater than 1,000 ppm and less than 10,000 ppm VOC as methane shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit
21. Upon detection of a leak, permittee shall tag the leak with a uniquely numbered tag, and shall record the leak location, component leaking, identification tag number, leak magnitude, date of leak detection, date of repair, method of repair, and post-repair monitoring measurement. Such records of leaks shall be maintained current and shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

22. Components not accessible for EPA Method 21 inspection shall be visually and auditorily checked for leaks at least weekly and shall be monitored using EPA Method 21 at least annually. Any leak detected visually or auditorially shall be recorded and the leak shall be repaired within 14 days of leak detection and shall be re-monitored using EPA Method 21 upon completion of the repair. Any leak detected using EPA Method 21 shall be repaired according the leak magnitude as described above and shall be re-monitored using EPA Method 21 upon completion of the repair. [District Rule 2201] Federally Enforceable Through Title V Permit

23. In addition to the requirements above, pressure relief devices shall be inspected and monitored for leaks within 3 days of any known, likely, or suspected venting of such devices. [District Rule 2201] Federally Enforceable Through Title V Permit

24. True vapor pressure of any liquid introduced in this permit unit shall be less than 0.5 psia at (or before) tank liquid inlet and at tank storage temperature. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit

25. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

26. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

27. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

28. True Vapor Pressure (TVP) of any organic liquid, except for crude oil with an API gravity of 20 degrees or less, shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

29. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

30. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit

31. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

32. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

33. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

34. Permittee shall provide District with a copy of D.O.G.G.R. approval for each vapor disposal well prior to use for vapor injection. [District Rule 1070] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

36. Formerly S-1143-28. [District Rule 2010] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-903-14 **EXPIRATION DATE:** 02/28/2007

SECTION: NW09 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 316 STEAM-ENHANCED OIL PRODUCTION WELLS (241 STEAM DRIVE WELLS/75 CYCLIC WELLS)

DRAFT

PERMIT UNIT REQUIREMENTS

1. Well casing vents shall remain closed at all times except during periods of actual service or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Fluids produced from these steam-enhanced wells with closed well casing vents and cyclic wells with closed casing vents shall be introduced only to tanks S-1131-885, '-886, '-891, and '-892, or to S-1131-598, '-629, '-630, '-638, '-641, '-650, '-651, and '-1097 that are vented to an approved operational vapor collection and control system achieving 99% control, or to permit exempt storage equipment as defined by Rule 2020, Section 6.6. [District Rule 2201] Federally Enforceable Through Title V Permit
3. VOC emission rate shall not exceed 201.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC content of hydrocarbons in gas processed shall not exceed 30.7% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
5. VOC content shall be tested annually using methods and procedures approved by the District. VOC sampling shall be conducted under circumstances representative of normal operation, and shall consist of sampling of at least one well per producing zone. VOC content shall be analyzed using the latest version of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be analyzed by CARB Method 422. [District Rule Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions calculated using the average fugitive emissions factors in the USEPA's 1995 Protocol for Equipment Leak Emission Estimates (EPA-453/R-95-017, Table 2-4). [District Rule 2201] Federally Enforceable Through Title V Permit
7. Total uncontrolled VOC emissions from all well vents shall be reduced by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain a current listing of all wells assigned to this permit. The listing shall be updated monthly and made readily available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
10. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
11. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit
13. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
14. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
15. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
16. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
17. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
18. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
19. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
20. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
22. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
23. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
24. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
25. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit
26. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
27. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
28. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
29. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
30. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
31. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
32. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

34. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

36. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

37. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

38. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

39. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

40. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

41. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

42. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

43. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

44. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

45. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

46. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

47. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit

48. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit

49. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

50. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

51. Formerly S-1143-40.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-908-16 **EXPIRATION DATE:** 02/28/2007

SECTION: 4 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
62.5 MM BTU/HR STRUTHERS NATURAL GAS/VAPOR RECOVERY GAS FIRED STRUTHERS STEAM GENERATOR (#71) WITH A NORTH AMERICAN GLE LOW-NOX BURNER, A FLUE GAS RECIRCULATION SYSTEM (FGR), AND O2 CONTROLLER

PERMIT UNIT REQUIREMENTS

1. {450} Particulate matter emissions shall not exceed 0.1 grain/dscf at operating conditions, nor 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rule 4201 and District Rule 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
2. Only PUC quality natural gas and noncondensible TVR gas from tank battery and associated FWKO vessels served by vapor control system listed on S-1132-8, S-1132-90, S-1131-885, S-1131-1040, and TEOR vapor control gas from S-1131-903 and -909 shall be combusted in this unit without prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Permittee shall measure and record, at least monthly, the sulfur content and BTU content of the vapor recovery gas incinerated in this unit. [District Rule 4406, 4.0] Federally Enforceable Through Title V Permit
4. Permittee shall measure and record the natural gas sulfur content and BTU content at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rule 4406, 4.0] Federally Enforceable Through Title V Permit
5. Flue gas recirculation shall be utilized, as needed, in conjunction with low-NOx burner to maintain ongoing compliance with permitted emission limits. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Emissions from the steam generator shall not exceed any of the following limits: 0.055 lb-SOx/MMBtu, 0.013 lb-PM10/MMBtu, or 0.0028 lb-VOC/MMBtu. [District Rules 2201 and 4301, 5.2] Federally Enforceable Through Title V Permit
7. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.0182 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4351, 5.1] Federally Enforceable Through Title V Permit
8. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rules 2201 and 4351, 5.1] Federally Enforceable Through Title V Permit
9. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit

11. Emissions from the steam generator shall not exceed either of the following limits: 54.0 lb-NOx/day or 55.5 lb-CO/day. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Kern County Rule 407] Federally Enforceable Through Title V Permit

13. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit

14. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. If the steam generator is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. If the steam generator is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM D 1072, D 3246, D 4084, double GC for H2S and mercaptans, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. If the steam generator is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

19. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100 (amended December 17, 1992), the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

21. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit

22. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

23. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit

24. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

25. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit

26. The fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 4305, 6.2, 4306, 6.2, and 4351, 6.2] Federally Enforceable Through Title V Permit

27. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit

28. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5 and 4306, 5.5.5] Federally Enforceable Through Title V Permit

29. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx and CO emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

31. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

32. All units in a group for which representative units are source tested for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches at any time to an alternate fuel type then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

33. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

34. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit

35. Permittee shall maintain daily records of volume of natural gas burned and vapor recovery system gas incinerated. [District NSR Rule] Federally Enforceable Through Title V Permit

36. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, 4306, 6.1, and 4351, 6.1] Federally Enforceable Through Title V Permit

38. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301, and 4801 (Kern County Rule 407). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

39. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

41. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

42. Formerly S-1143-90.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-909-14 **EXPIRATION DATE:** 02/28/2007

SECTION: SW03 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 490 STEAM-ENHANCED OIL PRODUCTION WELLS (320 STEAM DRIVE WELLS/170 CYCLIC WELLS)

DRAFT

PERMIT UNIT REQUIREMENTS

1. Well casing vents shall remain closed at all times except during periods of actual service or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Fluids produced from these steam-enhanced wells with closed well casing vents and cyclic wells with closed casing vents shall be introduced only to tanks S-1131-885, '-886, '-891, and '-892, or to S-1131-598, '-629, '-630, '-638, '-641, '-650, '-651, and '-1097 that are vented to an approved operational vapor collection and control system achieving 99% control, or to permit exempt storage equipment as defined by Rule 2020, Section 6.6. [District Rule 2201] Federally Enforceable Through Title V Permit
3. VOC emission rate shall not exceed 311.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC content of hydrocarbons in gas processed shall not exceed 30.7% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
5. VOC content shall be tested annually using methods and procedures approved by the District. VOC sampling shall be conducted under circumstances representative of normal operation, and shall consist of sampling of at least one well per producing zone. VOC content shall be analyzed using the latest version of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be analyzed by CARB Method 422. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions calculated using the average fugitive emissions factors in the USEPA's 1995 Protocol for Equipment Leak Emission Estimates (EPA-453/R-95-017, Table 2-4). [District Rule 2201] Federally Enforceable Through Title V Permit
7. Total uncontrolled VOC emissions from all well vents shall be reduced by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain a current listing of all wells assigned to this permit. The listing shall be updated monthly and made readily available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
10. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
11. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit
13. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
14. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
15. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
16. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
17. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
18. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
19. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
20. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
22. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
23. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
24. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
25. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit
26. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
27. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
28. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
29. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
30. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
31. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
32. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

34. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

36. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

37. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

38. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

39. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

40. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

41. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

42. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

43. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

44. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

45. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

46. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

47. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit

48. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit

49. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

50. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

51. Formerly S-1143-91.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-912-7 **EXPIRATION DATE:** 02/28/2007

SECTION: SE04 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR WITH A NORTH AMERICAN GLE LOW-NOX BURNER AND A FLUE GAS RECIRCULATION (FGR) SYSTEM (RASMUSSEN LEASE)

DRAFT

PERMIT UNIT REQUIREMENTS

1. The operator shall fire the unit only on natural gas. The combined sulfur content of all fuels supplied to this steam generator shall not exceed 1.0 gr S/100 scf. [District Rules 2201; and 4320, 5.4] Federally Enforceable Through Title V Permit
2. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rules 2201; and 4320, 5.2] Federally Enforceable Through Title V Permit
3. Emissions from the steam generator shall not exceed any of the following limits: 0.014 lb-PM10/MMBtu or 0.003 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Except during startup and shutdown, emissions shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.018 lb-NOx/MMBtu and 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201; 4305, 5.1; 4306, 5.1; and 4320, 5.2] Federally Enforceable Through Title V Permit
5. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum emissions from the steam generator, including start-up and shutdown periods, shall not exceed any of the following limits: 54.0 lb-NOx/day, 9,855 lb-NOx/year, 55.5 lb-CO/day, and 14,235 lb-CO/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown. [District Rules 4305, 5.5, 6.1; 4306, 5.3, 6.1; and 4320, 5.6, 6.1] Federally Enforceable Through Title V Permit
8. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; 4306, 3.22, 3.25; and 4320, 3.25, 3.29] Federally Enforceable Through Title V Permit
9. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

11. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; and 4306, 6.3] Federally Enforceable Through Title V Permit

12. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

13. If the unit is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. Each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 4320, 5.2 and 5.7] Federally Enforceable Through Title V Permit

14. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by test methods referenced in this permit. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; 4306, 6.2; and 4320, 6.2] Federally Enforceable Through Title V Permit

16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4; and 4306, 5.4] Federally Enforceable Through Title V Permit

19. Source testing shall be conducted using the methods and procedures approved by the District. Source testing for compliance demonstration shall be conducted by independent testing laboratories, and shall be witnessed, or authorized by District personnel. Sample collection shall be by ARB certified testing laboratory. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

21. Permittee shall submit an analysis to the District demonstrating compliance with the fuel sulfur content and higher heating value within 60 days of startup and at least once every 12 months. The sulfur content and higher heating value of the fuel shall be determined using the test methods referenced in this permit or certified by a third party fuel supplier. [District Rule 4320, 6.2] Federally Enforceable Through Title V Permit

22. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 1081; 2201; 4305, 5.5; 4306, 5.5; and 4320, 5.8] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1; and 4306, 6.1] Federally Enforceable Through Title V Permit

24. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit

25. Permittee shall maintain daily records of volume of fuel gas burned, sulfur content as determined by analytical testing or fuel supplier invoices/certifications, and permit number(s) of systems providing gas for incineration. [District Rules 2201; and 4320, 5.2, 5.7] Federally Enforceable Through Title V Permit

26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; 2520, 9.4.2; 4305, 6.1; 4306, 6.1; and 4320, 6.1] Federally Enforceable Through Title V Permit

27. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of District Rule 4201 (as amended December 17, 1992), 4301 (as amended December 17, 1992), 4351 (as amended August 21, 2003), 4406 (as amended December 17, 1992), and 4801 (as amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

28. {1669} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

29. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.1, 5.3] Federally Enforceable Through Title V Permit

30. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-917-10 **EXPIRATION DATE:** 02/28/2007

SECTION: 28 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 141 STEAM-ENHANCED OIL PRODUCTION WELLS WITH CLOSED CASING VENTS

DRAFT

PERMIT UNIT REQUIREMENTS

1. Well casing vents shall remain closed at all times except during periods of actual service or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Fluids produced from these steam-enhanced wells with closed well casing vents and cyclic wells with closed casing vents shall be introduced only to tanks S-1131-598, '-629, '-630, '-638, '-641, '-650, '-651, and '-1097 that are vented to an approved operational vapor collection and control system achieving 99% control, or to permit exempt storage equipment as defined by District Rule 2020, Section 6.6 (Amended March 21, 2002). [District Rule 2201] Federally Enforceable Through Title V Permit
3. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions according to Table 2-4 (Oil and Gas Production Operations Average Emission Factors) of USEPA's protocol for Equipment Emission Estimates - EPA -453/R-95-017. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC emission rate shall not exceed 212.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
6. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
7. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
8. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit
9. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

10. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

11. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

12. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

13. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

14. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

15. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

16. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

17. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

18. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

19. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

20. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

21. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

22. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

23. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

24. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

25. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

26. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

27. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

28. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

29. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

30. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

31. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

32. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

33. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

34. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

36. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

37. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

38. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

39. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

40. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

41. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit
43. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit
44. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit
45. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit
46. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
47. Formerly permit number S-1133-27-8 and S-1109-688-0.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-932-10 **EXPIRATION DATE:** ~~02~~/28/2007

SECTION: 25 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL PRODUCTION OPERATION (#'S A-1 & A-2) SERVING 168 STEAM ENHANCED WELLS - CLOSED WELL CASING VENTS, ROUTE PRODUCTION TO VAPOR CONTROLLED TANKS AND EXEMPT EQUIPMENT (FEE A LEASE)

DRAFT

PERMIT UNIT REQUIREMENTS

1. Well casing vents shall remain closed at all times except during periods of actual service or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Fluids produced from these steam-enhanced wells with closed well casing vents and cyclic wells with closed casing vents shall be introduced only to tanks S-1131-598, '-629, '-630, '-638, '-641, '-650, '-651, and '-1097 that are vented to an approved operational vapor collection and control system achieving 99% control, or to permit exempt storage equipment as defined by District Rule 2020, Section 6.6 (Amended March 21, 2002). [District Rule 2201] Federally Enforceable Through Title V Permit
3. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions according to Table 2-4 (Oil and Gas Production Operations Average Emission Factors) of USEPA's protocol for Equipment Emission Estimates - EPA -453/R-95-017. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC emission rate shall not exceed 203.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
6. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
7. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
8. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

10. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

11. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

12. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

13. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

14. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

15. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

16. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

17. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

18. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

20. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

21. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

22. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

23. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

24. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

25. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

26. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

27. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

28. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

29. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

30. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

31. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

32. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

33. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

34. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

36. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

37. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

38. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

39. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

40. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

41. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit
43. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit
44. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit
45. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit
46. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
47. Formerly permit numbers S-1133-31-8 and S-1109-691-0.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-941-13 **EXPIRATION DATE:** 02/28/2007

SECTION: 25 **TOWNSHIP:** 28S **RANGE:** 27E

DRAFT

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT EMISSIONS UNIT: 27.5 MMBTU/HR THERMOTICS VAPOR CONTROL/NATURAL GAS-FIRED STEAM GENERATOR #29 WITH FLUE GAS RECIRCULATION AND AMETEK THERMOX O2 CONTROLLER (LEASE FEE A) (GROUP II)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. All combustion equipment shall be operated to maintain emission standards. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All wells producing from strata steamed by this unit shall be connected to a District-approved emissions control system, have District-approved closed casing vents or be District-approved uncontrolled cyclic wells. [District Rule 4401] Federally Enforceable Through Title V Permit
6. Emission rates for this unit shall not exceed any of the following: PM-10: 0.093 lb/MMBTU, SOx (as SO2): 0.184 lb/MMBTU, NOx (as NO2): 0.036 lb/MMBTU or 30 ppmvd @3% O2, VOC: 0.007 lb/MMBTU, or CO: 0.033 lb/MMBTU or 45 ppmvd @3% O2. [District Rules 2201, 4305, and 4351] Federally Enforceable Through Title V Permit
7. Compliance with the sulfur emissions limit (as SO2) may be demonstrated by firing the unit only on PUC or FERC regulated natural gas; or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rule 4301] Federally Enforceable Through Title V Permit
8. Fuel hhv for source test purposes shall be certified by a third party fuel supplier or determined using ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 1081] Federally Enforceable Through Title V Permit
9. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4305, and 4351] Federally Enforceable Through Title V Permit
10. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months, except as provided below. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit
12. Source test results from an individual unit that is identical to this unit, in terms of rated capacity, operational conditions, fuel used, and control method, as approved by the APCO, will satisfy the NOx and CO source testing requirement. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit
13. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
16. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District NSR Rule and 4305] Federally Enforceable Through Title V Permit
17. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
18. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
19. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(Last Amended December 19,1993). [District Rule 1081, and Kern County Rule 108.1] Federally Enforceable Through Title V Permit
20. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. {588} Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
22. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. [District Rule 2520, 9.3.2 and District Rule 4301, 5.2.1] Federally Enforceable Through Title V Permit
23. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

27. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

29. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rule 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

30. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

31. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

35. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

36. Formerly permit number S-1133-1-15 and S-1109-671-0.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-943-13 **EXPIRATION DATE:** 02/28/2007

SECTION: 25 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR O-PAR GAS-FIRED STEAM GENERATOR #31, WITH AMETEK THERMOX O2 CONTROLLER (LEASE FEE A)

DRAFT

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. All combustion equipment shall be operated to maintain emission standards. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All wells producing from strata steamed by this unit shall be connected to a District-approved emissions control system, have District-approved closed casing vents or be District-approved uncontrolled cyclic wells. [District Rule 4401] Federally Enforceable Through Title V Permit
6. This steam generator shall operate only as a replacement standby unit for units S-1131-941. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
7. Annual fuel use shall not exceed 90 billion Btu. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
8. Permittee shall install and maintain a non-resettable, totalizing mass or volumetric fuel flow meter. A master meter, which measures fuel to all units in a group of similar units, may satisfy these requirements if approved by the APCO in writing. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
9. Permittee shall tune the unit at least once each calendar year in which it operates in accordance with the procedure in Rule 4304. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
10. Permittee shall maintain records of monthly and annual fuel consumption and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit
11. Emission rates for this unit shall not exceed any of the following: PM-10: 0.075 lb/MMBTU, SOx (as SO2): 0.081 lb/MMBTU, NOx (as NO2): 0.117 lb/MMBTU, VOC: 0.007 lb/MMBTU, or CO: 0.033 lb/MMBTU. [District NSR Rule, Rules 4201, 3.1; 4301, 5.2.1, 5.2.3, 4305, 4351, and 4801] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

13. Compliance with the sulfur emissions limit (as SO2) may be demonstrated by firing the unit only on PUC or FERC regulated natural gas; or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rule 2520, 9.4.2 and District Rule 4301, 5.2.1] Federally Enforceable Through Title V Permit

14. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. Fuel hhv for source test purposes shall be certified by a third party fuel supplier or determined using ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 1081] Federally Enforceable Through Title V Permit

16. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081, and Kern County Rule 108.1] Federally Enforceable Through Title V Permit

19. Sulfur emissions shall not exceed 0.11 lb of sulfur per million BTU of heat input, averaged over 3 - one hour periods. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas; multiplying the reported sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by a combination of source testing for sulfur compounds and fuel analysis. Compliance may be demonstrated for this unit individually, or by showing that the total emissions of sulfur compounds from all steam generators located at the stationary source with ATC or PTO issued prior to September 12, 1979 does not exceed the emissions that would result if each unit was operating in compliance with the specified limit. [Kern County Rule 424 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4305, and 4351] Federally Enforceable Through Title V Permit

21. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

23. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

24. Formerly permit number S-1133-21-11 and S-1109-682-0.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-944-9 **EXPIRATION DATE:** 02/28/2007

SECTION: 06 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL PRODUCTION OPERATION (#'S B-1 & B-2) SERVING 71 STEAM ENHANCED WELLS - CLOSED WELL CASING VENTS, ROUTE PRODUCTION TO VAPOR CONTROLLED TANKS AND EXEMPT EQUIPMENT (FEE B LEASE)

PERMIT UNIT REQUIREMENTS

1. Well casing vents shall remain closed at all times except during periods of actual service or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Fluids produced from these steam-enhanced wells with closed well casing vents and cyclic wells with closed casing vents shall be introduced only to tanks S-1131-598, '-629, '-630, '-638, '-641, '-650, '-651, and '-1097 that are vented to an approved operational vapor collection and control system achieving 99% control, or to permit exempt storage equipment as defined by District Rule 2020, Section 6.6 (Amended March 21, 2002). [District Rule 2201] Federally Enforceable Through Title V Permit
3. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions according to Table 2-4 (Oil and Gas Production Operations Average Emission Factors) of USEPA's protocol for Equipment Emission Estimates - EPA -453/R-95-017. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC emission rate shall not exceed 106.8 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
6. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
7. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
8. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

9. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

10. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

11. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

12. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

13. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

14. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

15. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

16. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

17. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

18. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

20. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

21. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

22. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

23. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

24. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

25. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

26. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

27. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

28. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

29. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

30. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

31. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

33. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

34. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

36. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

37. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

38. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

39. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

40. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

41. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit
43. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit
44. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit
45. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit
46. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
47. Formerly permit number S-1133-30-6 and S-1109-690-0.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-958-10 **EXPIRATION DATE:** 02/28/2007

DRAFT

SECTION: 30 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL PRODUCTION OPERATION (#'S C-1, C-2 & C-3) SERVING 95 STEAM DRIVE WELLS - CLOSED WELL CASING VENTS, ROUTE PRODUCTION TO VAPOR CONTROLLED TANKS AND EXEMPT EQUIPMENT (FEE C LEASE)

PERMIT UNIT REQUIREMENTS

1. Well casing vents shall remain closed at all times except during periods of actual service or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Fluids produced from these steam-enhanced wells with closed well casing vents and cyclic wells with closed casing vents shall be introduced only to tanks S-1131-598, '-629, '-630, '-638, '-641, '-650, '-651, and '-1097 that are vented to an approved operational vapor collection and control system achieving 99% control, or to permit exempt storage equipment as defined by District Rule 2020, Section 6.6 (Amended March 21, 2002). [District Rule 2201] Federally Enforceable Through Title V Permit
3. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions according to Table 2-4 (Oil and Gas Production Operations Average Emission Factors) of USEPA's protocol for Equipment Emission Estimates - EPA -453/R-95-017. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC emission rate shall not exceed 142.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
6. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
7. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
8. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

9. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

10. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

11. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

12. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

13. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

14. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

15. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

16. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

17. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

18. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

20. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

21. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

22. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

23. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

24. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

25. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

26. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

27. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

28. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

29. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

30. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

31. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

33. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

34. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

36. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

37. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

38. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

39. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

40. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

41. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit
43. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit
44. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit
45. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit
46. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
47. Formerly permit number S-1133-29-7 and S-1109-689-0.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-961-4

EXPIRATION DATE: 02/28/2007

DRAFT

SECTION: NE30 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
5,000 BBL FIXED ROOF WASH TANK, KERN RIVER (FEE C LEASE)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
9. Formerly permit number S-1133-42-2 and S-1109-702-0.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-962-4 **EXPIRATION DATE:** 02/28/2007

SECTION: NE30 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
5,000 BBL FIXED ROOF WATER STORAGE TANK, KERN RIVER (FEE C LEASE)

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
9. Formerly permit number S-1133-43-1 and S-1109-703-0.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-963-4

EXPIRATION DATE: 02/28/2007

DRAFT

SECTION: NE30 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
5,000 BBL FIXED ROOF WATER STORAGE TANK, KERN RIVER (FEE C LEASE)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
9. Formerly permit number S-1133-44-1 and S-1109-704-0.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-964-4

EXPIRATION DATE: 02/28/2007

DRAFT

SECTION: NE30 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF SKIM TANK, KERN RIVER (FEE C LEASE)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
9. Formerly permit number S-1133-45-2 and S-1109-705-0.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-966-13 **EXPIRATION DATE:** ~~02/28/2007~~

SECTION: 30 **TOWNSHIP:** 28S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT EMISSIONS UNIT: 27.5 MMBTU/HR THERMOTICS VAPOR CONTROL/NATURAL GAS-FIRED STEAM GENERATOR #24 WITH FLUE GAS RECIRCULATION AMETEK THERMOX O2 CONTROLLER (FEE C LEASE)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. All combustion equipment shall be operated to maintain emission standards. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All wells producing from strata steamed by this unit shall be connected to a District-approved emissions control system, have District-approved closed casing vents or be District-approved uncontrolled cyclic wells. [District Rule 4401] Federally Enforceable Through Title V Permit
6. Emission rates for this unit shall not exceed any of the following: PM-10: 0.070 lb/MMBTU, SOx (as SO2): 0.184 lb/MMBTU, NOx (as NO2): 0.036 lb/MMBTU or 30 ppmvd @3% O2, VOC: 0.007 lb/MMBTU, or CO: 0.033 lb/MMBTU or 45 ppmvd @3% O2. [District Rules 2201, 4305, and 4351] Federally Enforceable Through Title V Permit
7. Compliance with the sulfur emissions limit (as SO2) may be demonstrated by firing the unit only on PUC or FERC regulated natural gas; or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rule 4301] Federally Enforceable Through Title V Permit
8. Fuel hhv for source test purposes shall be certified by a third party fuel supplier or determined using ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 1081] Federally Enforceable Through Title V Permit
9. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4305, and 4351] Federally Enforceable Through Title V Permit
10. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months, except as provided below. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit
12. Source test results from an individual unit that is identical to this unit, in terms of rated capacity, operational conditions, fuel used, and control method, as approved by the APCO, will satisfy the NOx and CO source testing requirement. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit
13. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
16. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rules 2201 and 4305] Federally Enforceable Through Title V Permit
17. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
18. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
19. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(Last Amended December 19,1993). [District Rule 1081, and Kern County Rule 108.1] Federally Enforceable Through Title V Permit
20. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. {588} Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
22. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. [District Rule 2520, 9.3.2 and District Rule 4301, 5.2.1] Federally Enforceable Through Title V Permit
23. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

27. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

29. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rule 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

30. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

31. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

35. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

36. Formerly permit number S-1133-3-14 and S-1109-673-0.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-976-10 **EXPIRATION DATE:** 02/28/2007

SECTION: SE19 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 23 MMBTU/HR STRUTHERS GAS-FIRED STEAM GENERATOR WITH FLUE GAS RECIRCULATION AND OXYGEN CONTROLLER/ANALYZER (#13, DIS # 27537-66)

DRAFT

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. Emission rates shall not exceed: PM10; 0.009 lb/MMBtu, SOx (as SO2); 0.005 lb/MMBtu, NOx (as NO2); 0.036 lb/MMBtu or 30 ppmv @ 3% O2, VOC; 0.003 lb/MMBtu, or CO; 0.002 lb/MMBtu or 2.7 ppmv @ 3% O2. [District Rules 2201, 4305, and 4351] Federally Enforceable Through Title V Permit
5. Except during periods of steam generator startup/shutdown, steam generator shall not be operated unless flue gas recirculation system is operating. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
6. Steam generator may be equipped with a programmable logic controller (PLC). [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
7. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
8. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rules 2520, 9.3.2, 9.4.2 and 4305] Federally Enforceable Through Title V Permit
9. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
10. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months, except as provided below. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
12. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
13. Source test results from an individual unit that is identical to this unit, in terms of rated capacity, operational conditions, fuel used, and control method, as approved by the APCO, will satisfy the NOx and CO source testing requirement. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
14. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4305, and 4351] Federally Enforceable Through Title V Permit
15. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
16. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
17. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The permittee shall maintain records of fuel type and quantity for each day of operation, in the format approved by the District. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1, 5.2.3 and Kern County Rules 404 and 408] Federally Enforceable Through Title V Permit
21. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
22. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
23. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2, 4305, 6.2.1, and 4351, 6.2.1] Federally Enforceable Through Title V Permit

26. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

30. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

31. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

33. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of District Rules 4201, 4301 and 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. {1686} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

36. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

37. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

38. Formerly S-1109-2.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-987-10 **EXPIRATION DATE:** 02/28/2007

SECTION: SE19 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR THERMOTICS NATURAL GAS/CASING GAS-FIRED STEAM GENERATOR WITH A NORTH AMERICAN MODEL GLE MAGNA-FLAME LOW NOX BURNER, OXYGEN CONTROLLER/ANALYZER AND FLUE GAS RECIRCULATION (FGR) SYSTEM (R-3, DIS# 27474-81)

DRAFT

PERMIT UNIT REQUIREMENTS

1. Only PUC quality natural gas and noncondensible TVR gas from tank battery and associated FWKO vessels served by vapor control system listed on S-1132-8, S-1132-90, S-1131-885, S-1131-1040, and TEOR vapor control gas from S-1131-903 and -909 shall be combusted in this unit without prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain with the permit a current listing of all thermally enhanced well vent control systems and tank vapor recovery systems providing vapors to this steam generator and shall make such listing readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
3. {588} Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
4. Emissions from the steam generator shall not exceed any of the following limits: 0.052 lb-SOx/MMBtu, 0.044 lb-PM10/MMBtu, or 0.005 lb-VOC/MMBtu. [District Rules 2201 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
5. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.0182 lb-NOx/MMBtu or 31 ppmvd CO @ 3% O2 or 0.023 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4351, 5.1] Federally Enforceable Through Title V Permit
6. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit
8. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit
9. Emissions from the steam generator shall not exceed either of the following limits: 54.0 lb-NOx/day or 34.5 lb-CO/day. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

10. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit
11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
12. {2417} Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [County Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus)] Federally Enforceable Through Title V Permit
13. If the steam generator is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. If the steam generator is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM D 1072, D 3031, D 4084, D 3246, double GC for H2S and mercaptans, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. If the steam generator is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit
20. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit
21. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit
22. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5 and 4306, 5.5.5] Federally Enforceable Through Title V Permit
23. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
24. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx and CO emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
25. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
26. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
27. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
28. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

29. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit

30. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, and 4306, 6.1] Federally Enforceable Through Title V Permit

32. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

33. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

34. Formerly S-1109-91.

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-1131-992-10 **EXPIRATION DATE:** 02/28/2007

SECTION: NE29 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR THERMOTICS GAS/CASING GAS-FIRED STEAM GENERATOR WITH OXYGEN CONTROLLER/ANALYZER AND FLUE GAS RECIRCULATION (PRICEWELL, #P-9, DIS# 27472-81)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. Unit shall be exclusively gas/casing gas-fired and have no provisions for oil firing. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Testing for fuel gas and casing gas sulfur and BTU content shall be conducted no less than monthly. [District Rule 1081] Federally Enforceable Through Title V Permit
6. Emission rates shall not exceed: PM10; 0.029 lb/MMBtu, SOx (as SO2); 0.052 lb/MMBtu, NOx (as NO2); 0.036 lb/MMBtu or 30 ppmv @ 3% O2, VOC; 0.005 lb/MMBtu, or CO; 30.7 ppmv @ 3% O2. [District Rules 2201, 4305, and 4351] Federally Enforceable Through Title V Permit
7. Except during periods of steam generator startup/shutdown, steam generator shall not be operated unless flue gas recirculation system is operating. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
8. Steam generator may be equipped with a programmable logic controller (PLC). [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
9. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rules 2520, 9.3.2, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
12. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months, except as provided below. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
13. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
14. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
15. Source test results from an individual unit that is identical to this unit, in terms of rated capacity, operational conditions, fuel used, and control method, as approved by the APCO, will satisfy the NOx and CO source testing requirement. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans, or other test methods approved by the District. [District Rules 1081, 4305 and 4351] Federally Enforceable Through Title V Permit
17. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
19. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
20. Permittee shall maintain daily records of volume of fuel gas and casing gas burned, monthly fuel gas and casing gas sulfur content and BTU content, and source of casing gas. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(Last Amended December 19,1993). [District Rule 1081 and Kern County Rule 108.1] Federally Enforceable Through Title V Permit
22. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
23. {588} Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
24. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2, 4305, 6.2.1 and 4351, 6.2.1] Federally Enforceable Through Title V Permit

29. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

31. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

33. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

34. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. Nitrogen oxide (NOx) emission concentrations in ppmv shall be referenced at dry stack gas conditions, and shall be calculated to 3.00 percent by volume stack gas oxygen and averaged over 60 minutes, and lb/MMBtu rates shall be calculated as lb NO2/MMBtu of heat input (hhv). [District Rules 2520, 9.3.2, 4305, 5.0, 8.2 and/or 4351, 8.1] Federally Enforceable Through Title V Permit

36. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

39. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

40. Formerly S-1109-97.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-993-9 **EXPIRATION DATE:** 02/28/2007

SECTION: NE29 **TOWNSHIP:** 28S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR C.E. NATCO GAS/CASING GAS-FIRED STEAM GENERATOR WITH OXYGEN CONTROLLER/ANALYZER, FLUE GAS RECIRCULATION (PRICEWELL, P-3, DIS# 28773-85)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. Only PUC-quality natural gas or a combination of natural gas and casing gas shall be used as fuel. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Testing for fuel gas and casing gas sulfur and BTU content shall be conducted no less than monthly. [District Rule 1081] Federally Enforceable Through Title V Permit
6. Emission rates shall not exceed: PM10; 0.0063 lb/MMBtu, SOx (as SO2); 0.0243 lb/MMBtu, NOx (as NO2); 0.036 lb/MMBtu or 30 ppmv @ 3% O2, VOC; 0.0042 lb/MMBtu, or CO; 18.7 ppmv @ 3% O2. [District Rules 2201, 4305 and 4351] Federally Enforceable Through Title V Permit
7. Except during periods of steam generator startup/shutdown, steam generator shall not be operated unless flue gas recirculation system is operating. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
8. Steam generator may be equipped with a programmable logic controller (PLC). [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
9. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rules 2520, 9.3.2, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

11. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
12. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months, except as provided below. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
13. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
14. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
15. Source test results from an individual unit that is identical to this unit, in terms of rated capacity, operational conditions, fuel used, and control method, as approved by the APCO, will satisfy the NOx and CO source testing requirement. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans, or other test methods approved by the District. [District Rules 1081, 4305, and 4351] Federally Enforceable Through Title V Permit
17. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
19. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
20. Permittee shall maintain daily records of volume of fuel gas and casing gas burned, monthly fuel gas and casing gas sulfur content and BTU content, and source of casing gas. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(Last Amended December 19,1993). [District Rule 1081 and Kern County Rule 108.1] Federally Enforceable Through Title V Permit
22. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
23. {588} Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
24. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2, 4305, 6.2.1 and 4351, 6.2.1] Federally Enforceable Through Title V Permit

29. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

31. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

33. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

34. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. Nitrogen oxide (NOx) emission concentrations in ppmv shall be referenced at dry stack gas conditions, and shall be calculated to 3.00 percent by volume stack gas oxygen and averaged over 60 minutes, and lb/MMBtu rates shall be calculated as lb NO2/MMBtu of heat input (hhv). [District Rules 2520, 9.3.2, 4305, 5.0, 8.2 and/or 4351, 8.1] Federally Enforceable Through Title V Permit

36. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

39. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

40. Formerly S-1109-104.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-994-10 **EXPIRATION DATE:** 02/28/2007

SECTION: SE09 **TOWNSHIP:** 29S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR C.E. NATCO GAS/CASING GAS-FIRED STEAM GENERATOR WITH LO-NOX BURNER, OXYGEN CONTROLLER/ANALYZER AND FLUE GAS RECIRCULATION (MCMANUS, PL-8, DIS# 4322-78)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. Unit shall be exclusively gas/casing gas-fired and have no provisions for oil firing. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Testing for fuel gas and casing gas sulfur and BTU content shall be conducted no less than monthly. [District Rule 1081] Federally Enforceable Through Title V Permit
6. Emission rates shall not exceed: PM10; 0.045 lb/MMBtu, SOx (as SO2); 0.062 lb/MMBtu, NOx (as NO2); 0.036 lb/MMBtu or 30 ppmv @ 3% O2, VOC; 0.005 lb/MMBtu, or CO; 26.7 ppmv @ 3% O2. [District Rules 2201, 4305 and 4351] Federally Enforceable Through Title V Permit
7. Except during periods of steam generator startup/shutdown, steam generator shall not be operated unless flue gas recirculation system is operating. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
8. Steam generator may be equipped with a programmable logic controller (PLC). [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
9. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rules 2520, 9.3.2, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
12. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months, except as provided below. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
13. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
14. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
15. Source test results from an individual unit that is identical to this unit, in terms of rated capacity, operational conditions, fuel used, and control method, as approved by the APCO, will satisfy the NOx and CO source testing requirement. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans, or other test methods approved by the District. [District Rules 1081, 4305 and 4351] Federally Enforceable Through Title V Permit
17. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
19. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
20. Permittee shall maintain daily records of volume of fuel gas and casing gas burned, monthly fuel gas and casing gas sulfur content and BTU content, and source of casing gas. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(Last Amended December 19,1993). [District Rules 1081 and Kern County Rule 108.1] Federally Enforceable Through Title V Permit
22. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
23. {588} Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
24. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2, 4305, 6.2.1 and 4351, 6.2.1] Federally Enforceable Through Title V Permit

29. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

31. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

33. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

34. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. Nitrogen oxide (NOx) emission concentrations in ppmv shall be referenced at dry stack gas conditions, and shall be calculated to 3.00 percent by volume stack gas oxygen and averaged over 60 minutes, and lb/MMBtu rates shall be calculated as lb NO2/MMBtu of heat input (hhv). [District Rules 2520, 9.3.2, 4305, 5.0, 8.2 and/or 4351, 8.1] Federally Enforceable Through Title V Permit

36. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

39. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

40. Formerly S-1109-108.

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-1131-995-10 **EXPIRATION DATE:** 02/28/2007

SECTION: 03 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION SERVING 35 STEAM DRIVE WELLS WITH CLOSED CASING VENTS

PERMIT UNIT REQUIREMENTS

1. Well casing vents shall remain closed at all times except during periods of actual service or repair when wells are not producing. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain a current listing of all steam-enhanced wells in the central Kern County fields heavy oil production stationary source with closed casing vents that direct fluids to uncontrolled storage tanks and a current listing of all permit numbers of front-line equipment receiving produced fluids from the wells; shall update the list whenever a well or front-line equipment is added, replaced or deleted; and shall make such listing readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Any increase to the maximum number of steam enhanced oil production wells with closed casing vents shall require prior authorization by Authority to Construct or APCO approval of application for transfer of ownership of Permit to Operate. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The crude oil production from wells associated with this permit unit shall not lie within 1,000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
5. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions according to Table 2-4 (Oil and Gas Production Operations Average Emission Factors) of USEPA's protocol for Equipment Emission Estimates - EPA -453/R-95-017. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC emission rate shall not exceed 52.6 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
8. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
9. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit
11. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
12. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
13. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
14. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
15. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
16. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
17. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
18. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
20. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
21. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
22. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
23. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit
24. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
25. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
26. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
27. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
28. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
29. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
30. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

32. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

33. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

34. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

35. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

36. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

37. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

38. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

39. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

40. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

41. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

43. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

44. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

45. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit

46. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit

47. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

48. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

49. Formerly permit number S-1109-110-1.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-996-10 **EXPIRATION DATE:** 02/28/2007

SECTION: 02 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION SERVING 40 STEAM DRIVE WELLS - CLOSED WELL CASING VENTS, ROUTE PRODUCTION TO VAPOR CONTROLLED TANKS AND EXEMPT EQUIPMENT (KCL 2)

DRAFT

PERMIT UNIT REQUIREMENTS

1. Well casing vents shall remain closed at all times except during periods of actual service or repair when wells are not producing. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain a current listing of all steam-enhanced wells in the central Kern County fields heavy oil production stationary source with closed casing vents that direct fluids to uncontrolled storage tanks and a current listing of all permit numbers of front-line equipment receiving produced fluids from the wells; shall update the list whenever a well or front-line equipment is added, replaced or deleted; and shall make such listing readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Any increase to the maximum number of steam enhanced oil production wells with closed casing vents shall require prior authorization by Authority to Construct or APCO approval of application for transfer of ownership of Permit to Operate. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions according to Table 2-4 (Oil and Gas Production Operations Average Emission Factors) of USEPA's protocol for Equipment Emission Estimates - EPA -453/R-95-017. [District Rule 2201] Federally Enforceable Through Title V Permit
5. VOC emission rate shall not exceed 37.6 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The crude oil production from wells associated with this permit unit shall not lie within 1,000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
7. Implementation of the proposed abandonment of the well casing collection system shall conform to a District-approved well vent abandonment plan. [District Rule 2201] Federally Enforceable Through Title V Permit
8. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
9. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
10. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit
12. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
13. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
14. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
15. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
16. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
17. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
18. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
19. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
21. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
22. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
23. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
24. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit
25. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
26. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
27. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
28. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
29. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
31. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

33. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

34. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

36. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

37. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

38. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

39. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

40. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

41. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

42. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

43. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

44. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

45. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

46. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit

47. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit

48. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

49. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

50. Formerly permit number S-1109-111-0.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-997-10 **EXPIRATION DATE:** 02/28/2007

SECTION: SE13 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR THERMOTICS NATURAL GAS/CASING GAS-FIRED STEAM GENERATOR WITH A NORTH AMERICAN MODEL GLE MAGNA-FLAME BURNER WITH FLUE GAS RECIRCULATION (FGR) AND AN OXYGEN CONTROLLER/ANALYZER (ANGUS 2, DIS# 4509-81)

DRAFT

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. Emissions from the steam generator shall not exceed any of the following limits: 0.075 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.0182 lb-NOx/MMBtu or 27 ppmvd CO @ 3% O2 or 0.02 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4351, 5.1] Federally Enforceable Through Title V Permit
6. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit
8. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit
9. Emissions from the steam generator shall not exceed either of the following limits: 54.0 lb-NOx/day or 30.0 lb-CO/day. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit
11. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
12. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
13. {2417} Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [County Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus)] Federally Enforceable Through Title V Permit
14. If the steam generator is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. If the steam generator is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM D 1072, D 3031, D 4084, D 3246, double GC for H2S and mercaptans, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. If the steam generator is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
18. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit

21. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

22. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit

23. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit

24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5 and 4306, 5.5.5] Federally Enforceable Through Title V Permit

25. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

26. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx and CO emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

27. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

28. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

29. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

31. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit

32. Permittee shall maintain daily records of volume of fuel gas and casing gas burned, source of casing gas, and monthly fuel gas and casing gas sulfur content and BTU content. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, and 4306, 6.1] Federally Enforceable Through Title V Permit

35. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

36. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

37. Formerly S-1109-118.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-998-9 **EXPIRATION DATE:** 02/28/2007

SECTION: SW34 **TOWNSHIP:** 28S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR C.E. NATCO GAS/CASING GAS-FIRED STEAM GENERATOR W/OXYGEN CONTROLLER/ANALYZER, FLUE GAS RECIRCULATION (HOPCO, H-2, DIS# 39454-87)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. Only PUC-quality natural gas or a combination of natural gas and casing gas shall be used as fuel. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Testing for fuel gas and casing gas sulfur and BTU content shall be conducted no less than monthly. [District Rule 1081] Federally Enforceable Through Title V Permit
6. Emission rates shall not exceed: PM10: 0.007 lb/MMBtu; SOx (as SO2): 0.030 lb/MMBtu; NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2; VOC: 0.006 lb/MMBtu; or CO: 18.7 ppmv @ 3% O2. [District Rules 2201, 4305, and 4351] Federally Enforceable Through Title V Permit
7. Except during periods of steam generator startup/shutdown, steam generator shall not be operated unless flue gas recirculation system is operating. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
8. Steam generator may be equipped with a programmable logic controller (PLC). [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
9. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rule 2520, 9.3.2, 9.4.2, and 4305] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
12. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months, except as provided below. [District Rules 2201, 4305, and 4351] Federally Enforceable Through Title V Permit
13. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
14. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
15. Source test results from an individual unit that is identical to this unit, in terms of rated capacity, operational conditions, fuel used, and control method, as approved by the APCO, will satisfy the NOx and CO source testing requirement. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans, or other test methods approved by the District. [District Rules 1081, 4305, and 4351] Federally Enforceable Through Title V Permit
17. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
19. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
20. Permittee shall maintain daily records of volume of fuel gas and casing gas burned, source of casing gas, monthly fuel gas and casing gas sulfur content and BTU content. [District Rule 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(Last Amended December 19,1993). [District Rule 1081, and Kern County Rules 108.1] Federally Enforceable Through Title V Permit
22. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
23. {588} Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
24. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rule 2520, 9.3.2 and District Rule 4301, 5.2.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

29. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

31. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rule 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

33. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

34. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. Nitrogen oxide (NOx) emission concentrations in ppmv shall be referenced at dry stack gas conditions, and shall be calculated to 3.00 percent by volume stack gas oxygen and averaged over 60 minutes, and lb/MMBtu rates shall be calculated as lb NO2/MMBtu of heat input (hhv). [District Rule 2520, 9.3.2, 4305, 5.0, 8.2 and/or 4351, 8.1] Federally Enforceable Through Title V Permit

36. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

39. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

40. Formerly S-1109-121.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-999-9 **EXPIRATION DATE:** 02/28/2007

DRAFT

SECTION: SE19 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR C.E. NATCO NATURAL GAS/CASING GAS-FIRED STEAM GENERATOR WITH A NORTH AMERICAN MODEL GLE MAGNA-FLAME LOW NOX BURNER, OXYGEN CONTROLLER/ANALYZER AND FLUE GAS RECIRCULATION (FGR) SYSTEM (RAMBLER, R-7, DIS# 12466-82)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Flue gas recirculation shall be utilized, as needed, in conjunction with low-NOx burner to maintain ongoing compliance with permitted emission limits. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Emissions from the steam generator shall not exceed any of the following limits: 0.03 lb-SOx/MMBtu, 0.007 lb-PM10/MMBtu, or 0.006 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.0182 lb-NOx/MMBtu or 25 ppmvd CO @ 3% O2 or 0.0185 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4351, 5.1] Federally Enforceable Through Title V Permit
5. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. Permittee shall maintain records of duration of each start-up and shutdown that exceeds two hours. [District Rules 4305, 5.5, and 4306, 5.3] Federally Enforceable Through Title V Permit
7. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 3.21, 3.25; and 4306, 3.22, 3.25] Federally Enforceable Through Title V Permit
8. Emissions from the steam generator shall not exceed either of the following limits: 54.0 lb-NOx/day or 27.8 lb-CO/day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3; 4306, 6.3; and 4351, 6.3.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Whenever the flue gas recirculation (FGR) system on this unit is switched from the open to the closed position, or from the closed to the open position, compliance source testing for NOx and CO emissions shall be conducted within 60 days of change of FGR operation date unless source testing with FGR system in both the open and closed position has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit
11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
12. {2417} Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [County Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus)] Federally Enforceable Through Title V Permit
13. If the steam generator is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. If the steam generator is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM D 1072, D 3031, D 4084, D 3246, double GC for H2S and mercaptans, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. If the steam generator is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit
18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4 and 4306, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100; NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; SOx (lb/MMBtu) - EPA Method 6, 6C, 8 or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, fuel gas sulfur content and EPA Method 19 to calculated emissions; Fuel Gas Sulfur Content - EPA Method 11 or EPA Method 15 or ASTM D1072, D3246, D4084, or grab sample analysis by double GC; Fuel Gas HHV - ASTM D1826 or D1945 in conjunction with ASTM D3588. PM10 (lb/scf) - EPA Methods 5 (both filterable and condensible), 201A and 202, or CARB Method 5; Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100; Stack Gas Velocity (ft/min) - EPA Method 2; Stack Gas Moisture Content (%) - EPA Method 4. [District Rules 1081; 4305, 6.2; and 4306, 6.2] Federally Enforceable Through Title V Permit
20. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1 and 4306, 5.5.1] Federally Enforceable Through Title V Permit
21. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 5.5; and 4306, 5.5] Federally Enforceable Through Title V Permit
22. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5 and 4306, 5.5.5] Federally Enforceable Through Title V Permit
23. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
24. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx and CO emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
25. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
26. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
27. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit
28. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rules 2520, 9.3.2, 4305, 6.3.2, 4306, 6.3.2, and 4351, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

29. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1 and 4306, 6.1] Federally Enforceable Through Title V Permit

30. Permittee shall maintain daily records of volume of fuel gas and casing gas burned, source of casing gas, and monthly fuel gas and casing gas sulfur content and BTU content. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any non-certified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, and 4306, 6.1] Federally Enforceable Through Title V Permit

33. Only PUC-quality natural gas or a combination of natural gas and casing gas shall be used as fuel. [District NSR Rule] Federally Enforceable Through Title V Permit

34. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

35. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

36. Formerly S-1109-127.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1000-9 **EXPIRATION DATE:** 02/28/2007

SECTION: SE19 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR C.E. NATCO GAS/CASING GAS-FIRED STEAM GENERATOR WITH OXYGEN CONTROLLER/ANALYZER, FLUE GAS RECIRCULATION (RAMBLER, R-8, DIS# 12468-82)

DRAFT

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. Only PUC-quality natural gas or a combination of natural gas and casing gas shall be used as fuel. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Testing for fuel gas and casing gas sulfur and BTU content shall be conducted no less than monthly. [District Rule 1081] Federally Enforceable Through Title V Permit
6. Emission rates shall not exceed: PM10: 0.0065 lb/MMBtu; SOx (as SO2): 0.0083 lb/MMBtu; NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2; VOC: 0.0041 lb/MMBtu; or CO: 18.7 ppmv @ 3% O2. [District Rules 2201, 4305 and 4351] Federally Enforceable Through Title V Permit
7. Except during periods of steam generator startup/shutdown, steam generator shall not be operated unless flue gas recirculation system is operating. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
8. Steam generator may be equipped with a programmable logic controller (PLC). [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
9. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rules 2520, 9.3.2, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

11. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
12. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months, except as provided below. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
13. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
14. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
15. Source test results from an individual unit that is identical to this unit, in terms of rated capacity, operational conditions, fuel used, and control method, as approved by the APCO, will satisfy the NOx and CO source testing requirement. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans, or other test methods approved by the District. [District Rules 1081, 4305 and 4351] Federally Enforceable Through Title V Permit
17. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
19. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
20. Permittee shall maintain daily records of volume of fuel gas and casing gas burned, source of casing gas, and monthly fuel gas and casing gas sulfur content and BTU content. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(Last Amended December 19,1993). [District Rule 1081 and Kern County Rule 108.1] Federally Enforceable Through Title V Permit
22. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
23. {588} Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
24. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2, 4305, 6.2.1 and 4351, 6.2.1] Federally Enforceable Through Title V Permit

29. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

31. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

33. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

34. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. Nitrogen oxide (NOx) emission concentrations in ppmv shall be referenced at dry stack gas conditions, and shall be calculated to 3.00 percent by volume stack gas oxygen and averaged over 60 minutes, and lb/MMBtu rates shall be calculated as lb NO2/MMBtu of heat input (hhv). [District Rules 2520, 9.3.2, 4305, 5.0, 8.2 and/or 4351, 8.1] Federally Enforceable Through Title V Permit

36. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

39. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

40. Formerly S-1109-128.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1001-10 **EXPIRATION DATE:** 02/28/2007

SECTION: SE09 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR C.E. NATCO GAS/CASING GAS-FIRED STEAM GENERATOR W/OXYGEN CONTROLLER/ANALYZER, FLUE GAS RECIRCULATION (CHINA 3, DIS#12467-82

DRAFT

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. Only PUC quality natural gas and/or scrubbed TEOR gas from Sulfa-Check unit of S-1131-1040 shall be used as fuel. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Compliance with SOx emission rate shall be demonstrated by daily emission calculations using heating values & amounts of natural gas/TEOR gas burned in this unit and the outlet H2S concentration from Sulfa Check unit of S-1131-1040. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Testing for fuel gas and casing gas sulfur and BTU content shall be conducted no less than monthly. [District Rule 1081] Federally Enforceable Through Title V Permit
7. Emission rates shall not exceed: PM10: 0.006 lb/MMBtu; SOx (as SO2): 0.008 lb/MMBtu; NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2; VOC: 0.0041 lb/MMBtu; or CO: 18.7 ppmv @ 3% O2. [District Rules 2201, 4305, and 4351] Federally Enforceable Through Title V Permit
8. Except during periods of steam generator startup/shutdown, steam generator shall not be operated unless flue gas recirculation system is operating. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
9. Steam generator may be equipped with a programmable logic controller (PLC). [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
10. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
11. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rule 2520, 9.3.2, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
13. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months, except as provided below. [District Rules 2201, 4305, 4306, and 4351] Federally Enforceable Through Title V Permit
14. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
15. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
16. Source test results from an individual unit that is identical to this unit, in terms of rated capacity, operational conditions, fuel used, and control method, as approved by the APCO, will satisfy the NOx and CO source testing requirement. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
17. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans, or other test methods approved by the District. [District Rules 1081, 4305, and 4351] Federally Enforceable Through Title V Permit
18. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
19. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records of volume of fuel gas and casing gas burned, and monthly fuel gas and casing gas sulfur content and BTU content. [District Rule 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
22. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(Last Amended December 19,1993). [District Rule 1081, and Kern County Rules 108.1] Federally Enforceable Through Title V Permit
23. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
24. {588} Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
25. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rule 2520, 9.3.2 and District Rule 4301, 5.2.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

30. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

32. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rule 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

33. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

34. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

35. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. Nitrogen oxide (NOx) emission concentrations in ppmv shall be referenced at dry stack gas conditions, and shall be calculated to 3.00 percent by volume stack gas oxygen and averaged over 60 minutes, and lb/MMBtu rates shall be calculated as lb NO2/MMBtu of heat input (hhv). [District Rule 2520, 9.3.2, 4305, 5.0, 8.2 and/or 4351, 8.1] Federally Enforceable Through Title V Permit

37. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

40. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

41. Formerly S-1109-129.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1002-9 **EXPIRATION DATE:** 02/28/2007

SECTION: NE29 **TOWNSHIP:** 28S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR C.E. NATCO STEAM GENERATOR WITH NORTH AMERICAN STAGED COMBUSTION AND FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. Compliance source testing for NOx, CO and fuel gas sulfur content shall be conducted at least once every 12 month period that the unit is operated (or as approved by the District). [District Rule 2201] Federally Enforceable Through Title V Permit
5. Compliance source testing shall be conducted under conditions representative of normal operation. [District Rule 1081] Federally Enforceable Through Title V Permit
6. Emission factors for this unit shall not exceed any of the following: PM-10: 0.006 lb/MMBTU, SOx (as SO2): 0.005 lb/MMBTU, NOx (as NO2): 0.036 lb/MMBTU or 30 ppmvd @3% O2, VOC: 0.003 lb/MMBTU, or CO: 0.002 lb/MMBTU or 3 ppmvd @3% O2. [District Rules 2201, 4305 and 4351] Federally Enforceable Through Title V Permit
7. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
8. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rules 2520, 9.3.2, 9.4.2 and 4305] Federally Enforceable Through Title V Permit
9. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

10. Compliance source testing for NOx and CO shall be conducted not less than once every 12 months, except as provided below. [District Rules 2201 and 4305] Federally Enforceable Through Title V Permit
11. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit
12. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
13. Source test results from an individual unit that is identical to this unit, in terms of rated capacity, operational conditions, fuel used, and control method, as approved by the APCO, will satisfy the NOx and CO source testing requirement. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
14. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
15. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
16. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
17. Compliance with SOx emission limits shall be demonstrated by natural gas sulfur contents analysis at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans, or other test methods approved by the District. [District Rules 1081 and 4305] Federally Enforceable Through Title V Permit
19. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(Last Amended December 19,1993). [District Rule 1081 and Kern County Rule 108.1] Federally Enforceable Through Title V Permit
20. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. {588} Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
22. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
23. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2, 4305, 6.2.1 and 4351, 6.2.1] Federally Enforceable Through Title V Permit

27. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

29. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

30. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

31. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. Nitrogen oxide (NOx) emission concentrations in ppmv shall be referenced at dry stack gas conditions, and shall be calculated to 3.00 percent by volume stack gas oxygen and averaged over 60 minutes, and lb/MMBtu rates shall be calculated as lb NO2/MMBtu of heat input (hhv). [District Rules 2520, 9.3.2, 4305, 5.0, 8.2 and/or 4351, 8.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

37. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

38. Formerly permit number S-1109-135-14.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1003-9 **EXPIRATION DATE:** 02/28/2007

SECTION: SW34 **TOWNSHIP:** 28S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR C.E. NATCO GAS/CASING GAS-FIRED STEAM GENERATOR W/ OXYGEN CONTROLLER/ANALYZER, FLUE GAS RECIRCULATION (HOPCO, H-3, DIS# 39455-87)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. Only PUC-quality natural gas or a combination of natural gas and casing gas shall be used as fuel. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Testing for fuel gas and casing gas sulfur and BTU content shall be conducted no less than monthly. [District Rule 1081] Federally Enforceable Through Title V Permit
6. Emission rates shall not exceed: PM10: 0.007 lb/MMBtu; SOx (as SO2): 0.030 lb/MMBtu; NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2; VOC: 0.006 lb/MMBtu; or CO: 18.7 ppmv @ 3% O2. [District Rules 2201, 4305, and 4351] Federally Enforceable Through Title V Permit
7. Except during periods of steam generator startup/shutdown, steam generator shall not be operated unless flue gas recirculation system is operating. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
8. Steam generator may be equipped with a programmable logic controller (PLC). [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
9. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rule 2520, 9.3.2, 9.4.2, and 4305] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
12. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months except as provided below. [District Rules 2201, 4305, 4306, and 4351] Federally Enforceable Through Title V Permit
13. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
14. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
15. Source test results from an individual unit that is identical to this unit, in terms of rated capacity, operational conditions, fuel used, and control method, as approved by the APCO, will satisfy the NOx and CO source testing requirement. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans, or other test methods approved by the District. [District Rules 1081, 4305, and 4351] Federally Enforceable Through Title V Permit
17. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
19. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
20. Permittee shall maintain daily records of volume of fuel gas and casing gas burned, source of casing gas, and monthly fuel gas and casing gas sulfur content and BTU content. [District Rule 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(Last Amended December 19,1993). [District Rule 1081, and Kern County Rules 108.1] Federally Enforceable Through Title V Permit
22. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
23. {588} Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
24. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rule 2520, 9.3.2 and District Rule 4301, 5.2.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

29. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

31. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rule 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

33. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

34. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

35. Nitrogen oxide (NOx) emission concentrations in ppmv shall be referenced at dry stack gas conditions, and shall be calculated to 3.00 percent by volume stack gas oxygen and averaged over 60 minutes, and lb/MMBtu rates shall be calculated as lb NO2/MMBtu of heat input (hhv). [District Rule 2520, 9.3.2, 4305, 5.0, 8.2 and/or 4351, 8.1] Federally Enforceable Through Title V Permit

36. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

39. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

40. Formerly S-1109-136.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1004-9 **EXPIRATION DATE:** 02/28/2007

SECTION: NE29 **TOWNSHIP:** 28S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR C.E. NATCO GAS/CASING GAS-FIRED STEAM GENERATOR W/ OXYGEN CONTROLLER/ANALYZER, FLUE GAS RECIRCULATION (PRICEWELL, H-4)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. Only PUC-quality natural gas or a combination of natural gas and casing gas shall be used as fuel. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Testing for fuel gas and casing gas sulfur and BTU content shall be conducted no less than monthly. [District Rule 1081] Federally Enforceable Through Title V Permit
6. Emission rates shall not exceed: PM10: 0.007 lb/MMBtu; SOx (as SO2): 0.030 lb/MMBtu; NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2; VOC: 0.006 lb/MMBtu; or CO: 18.7 ppmv @ 3% O2. [District Rules 2201, 4305 and 4351] Federally Enforceable Through Title V Permit
7. Except during periods of steam generator startup/shutdown, steam generator shall not be operated unless flue gas recirculation system is operating. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
8. Steam generator may be equipped with a programmable logic controller (PLC). [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
9. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rules 2520, 9.3.2, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
12. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 12 months, except as provided below. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
13. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
14. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
15. Source test results from an individual unit that is identical to this unit, in terms of rated capacity, operational conditions, fuel used, and control method, as approved by the APCO, will satisfy the NOx and CO source testing requirement. [District Rules 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans, or other test methods approved by the District. [District Rules 1081, 4305 and 4351] Federally Enforceable Through Title V Permit
17. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
19. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
20. Permittee shall maintain daily records of volume of fuel gas and casing gas burned, source of casing gas, and monthly fuel gas and casing gas sulfur content and BTU content. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(Last Amended December 19,1993). [District Rule 1081 and Kern County Rule 108.1] Federally Enforceable Through Title V Permit
22. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
23. {588} Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
24. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2, 4305, 6.2.1 and 4351, 6.2.1] Federally Enforceable Through Title V Permit

29. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

31. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

33. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

34. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. Nitrogen oxide (NOx) emission concentrations in ppmv shall be referenced at dry stack gas conditions, and shall be calculated to 3.00 percent by volume stack gas oxygen and averaged over 60 minutes, and lb/MMBtu rates shall be calculated as lb NO2/MMBtu of heat input (hhv). [District Rules 2520, 9.3.2, 4305, 5.0, 8.2 and/or 4351, 8.1] Federally Enforceable Through Title V Permit

36. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

39. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

40. Formerly S-1109-137.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1007-9 **EXPIRATION DATE:** 02/28/2007

SECTION: 20 **TOWNSHIP:** 28S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION WITH UP TO 170 STEAM DRIVE WELLS SERVED BY WELL VENT VAPOR CONTROL SYSTEM (MARCO A&B LEASE) (WILMAR LEASE)

PERMIT UNIT REQUIREMENTS

1. Volatile Organic Compound (VOC) emissions shall not exceed 292.6 lb VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Total uncontrolled VOC emissions from all well vents shall be reduced by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fluids produced from these steam-enhanced wells with closed well casing vents and cyclic wells with closed casing vents shall be introduced only to tanks S-1131-598, '629, '630, '638, '641, '650, '651 and '-1097 that are vented to an approved vapor collection and control system achieving 99% control, or to permit exempt storage equipment as defined by Rule 2020, Section 6.6. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall maintain a current listing of all wells assigned to this permit. The listing shall be updated monthly and made readily available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions calculated using EPA 1995 Protocol for Equipment Leak Emission Estimates, EPA-453/R-95-017, table 2-4. [District Rule 2201] Federally Enforceable Through Title V Permit
6. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
7. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
8. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
9. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

11. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

12. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

13. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

14. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

15. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

16. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

17. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

18. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

19. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

21. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

22. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

23. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

24. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

25. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

26. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

27. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

28. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

29. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

30. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

31. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

32. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

34. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

36. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

37. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

38. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

39. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

40. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

41. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

42. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

43. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit
44. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit
45. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit
46. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit
47. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
48. Formerly permit number S-1109-172-5.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1008-9 **EXPIRATION DATE:** 02/28/2007

SECTION: 19 **TOWNSHIP:** 28S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION WITH UP TO 118 STEAM DRIVE WELLS SERVED BY WELL VENT VAPOR CONTROL SYSTEM INCLUDING GAS/LIQUID SEPARATORS, HEAT EXCHANGER, VAPOR COMPRESSOR, CONDENSERS, AND OPTIONAL H2S SCRUBBING SYSTEM FOR CORROSION CONTROL WITH NON-CONDENSIBLE VAPOR PIPED TO SG'S S-1131-987, -990, -999, AND -1000, AND/OR FLARE S-1131-1085, OR SERVED BY VAPOR-CONTROLLED STATION 36 TANKS (RAMBLER LEASE)

PERMIT UNIT REQUIREMENTS

1. Well vents shall include provisions for collection and incineration of vapor in District-approved well vent vapor control system. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Final vapor condenser shall be equipped with an operational exhaust gas temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Condensate shall discharge to existing dehydration tanks only. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Total uncontrolled VOC emissions from all well vents shall be reduced by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
5. VOC emissions associated with the components added for the installation of sulfur scrubber vessel shall be less than 0.50 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. To verify compliance with the VOC emissions limit established for the sulfur scrubber vessel installation, permittee shall maintain an accurate count and estimate of emissions for the added components in gas/light liquid service, in accordance with CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Volatile Organic Compound (VOC) emissions shall not exceed 85.2 lb VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. To verify compliance with the VOC emissions limit of this permit, permittee shall maintain an accurate count and estimate of emissions of the components in gas/light liquid service, in accordance with CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv (non-leaking) and > 10,000 ppmv (leaking). Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
9. At least once per year, components in gas/light liquid service shall be inspected for leaks, visually and in accordance with EPA Method 21, with an instrument calibrated with methane, to ensure compliance with the provisions of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Upon detection of a leak greater than 10,000 ppmv or 3 drops per minute, facility operator shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Any component leak greater than 10,000 ppmv or 3 drops per minute shall be repaired to a leak-free condition within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Operator shall maintain an inspection log containing the following: type of component leaking; date and method of detection; date and type of repair made and the emission level after leak is repaired. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Well casing vents or downstream valves may be closed if the well is idle or if the well is producing to tanks S-1131-598, '-629, '-630, '-638, '-641, '-650, '-651, and '1097 that are vented to an approved operational vapor collection and control system achieving 99% control. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Permittee shall maintain a current listing of all wells connected to the well vent vapor control system including whether the well vent or a downstream valve is currently closed or open. The listing shall be updated monthly and made readily available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

15. The crude oil production from wells associated with this permit unit shall not lie within 1,000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit

16. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

17. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

18. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

19. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit

20. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

21. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

23. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

24. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

25. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

26. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

27. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

28. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

29. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

30. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

31. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

32. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

34. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

35. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

36. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

37. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

38. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

39. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

40. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

41. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

42. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

43. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

44. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

45. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

46. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

47. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

48. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

49. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

50. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

51. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

52. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

54. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit

55. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit

56. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

57. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

58. Formerly permit number S-1109-173-7.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1010-9 **EXPIRATION DATE:** 02/28/2007

SECTION: 29 **TOWNSHIP:** 28S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL PRODUCTION OPERATION WITH UP TO 37 STEAM ENHANCED OIL PRODUCTION WELLS - CLOSED WELL CASING VENTS, ROUTE PRODUCTION TO VAPOR CONTROLLED TANKS AND EXEMPT EQUIPMENT (PARKER LEASE)

PERMIT UNIT REQUIREMENTS

1. Total uncontrolled VOC emissions from all well vents shall be reduced by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Fluids produced from these steam-enhanced wells with closed well casing vents and cyclic wells with closed casing vents shall be introduced only to tanks S-1131-598, '629, '630, '638, '641, '650, '651 and '-1097 that are vented to an approved vapor collection and control system achieving 99% control, or to permit exempt storage equipment as defined by Rule 2020, Section 6.6. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Permittee shall maintain a current listing of all wells assigned to this permit. The listing shall be updated monthly and made readily available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
4. Volatile organic compound (VOC) emission rate shall not exceed 63.7 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions calculated using EPA 1995 Protocol for Equipment Leak Emission Estimates, EPA-453/R-95-017, table 2-4. [District Rule 2201] Federally Enforceable Through Title V Permit
6. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
7. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
8. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
9. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

10. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

11. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

12. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

13. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

14. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

15. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

16. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

17. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

18. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

19. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

21. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

22. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

23. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

24. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

25. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

26. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

27. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

28. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

29. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

30. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

31. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

32. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

34. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

36. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

37. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

38. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

39. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

40. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

41. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

42. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

43. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit
44. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit
45. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit
46. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit
47. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
48. Formerly S-1109-175-3.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1011-9 **EXPIRATION DATE:** 02/28/2007

SECTION: 29 **TOWNSHIP:** 28S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION SERVING UP TO 42 STEAM ENHANCED WELLS - CLOSED WELL CASING VENTS, ROUTE PRODUCTION TO VAPOR CONTROLLED TANKS AND EXEMPT EQUIPMENT (POTOMAC LEASE)

PERMIT UNIT REQUIREMENTS

1. Total uncontrolled VOC emissions from all well vents shall be reduced by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Fluids produced from these steam-enhanced wells with closed well casing vents and cyclic wells with closed casing vents shall be introduced only to tanks S-1131-598, '629, '630, '638, '641, '650, '651 and '-1097 that are vented to an approved vapor collection and control system achieving 99% control, or to permit exempt storage equipment as defined by Rule 2020, Section 6.6. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Permittee shall maintain a current listing of all wells assigned to this permit. The listing shall be updated monthly and made readily available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
4. Volatile organic compound (VOC) emission rate shall not exceed 72.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions calculated using EPA 1995 Protocol for Equipment Leak Emission Estimates, EPA-453/R-95-017, table 2-4. [District Rule 2201] Federally Enforceable Through Title V Permit
6. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
7. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
8. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
9. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

10. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
11. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
12. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
13. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
14. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
15. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
16. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
17. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
18. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
19. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

21. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

22. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

23. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

24. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

25. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

26. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

27. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

28. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

29. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

30. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

31. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

32. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

34. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

36. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

37. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

38. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

39. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

40. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

41. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

42. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

43. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

44. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit

45. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit

46. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

47. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

48. Formerly S-1109-176-5.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1012-9 **EXPIRATION DATE:** 02/28/2007

SECTION: 28 **TOWNSHIP:** 28S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION SERVING UP TO 126 STEAM ENHANCED WELLS (BISHOP A LEASE)

DRAFT

PERMIT UNIT REQUIREMENTS

1. Total uncontrolled VOC emissions from all well vents shall be reduced by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Fluids produced from these steam-enhanced wells with closed well casing vents and cyclic wells with closed casing vents shall be introduced only to tanks S-1131-598, '629, '630, '638, '641, '650, '651 and '-1097 that are vented to an approved vapor collection and control system achieving 99% control, or to permit exempt storage equipment as defined by Rule 2020, Section 6.6. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Permittee shall maintain a current listing of all wells assigned to this permit. The listing shall be updated monthly and made readily available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
4. Volatile organic compound (VOC) emission rate shall not exceed 216.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions calculated using EPA 1995 Protocol for Equipment Leak Emission Estimates, EPA-453/R-95-017, table 2-4. [District Rule 2201] Federally Enforceable Through Title V Permit
6. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
7. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
8. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
9. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

10. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

11. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

12. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

13. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

14. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

15. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

16. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

17. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

18. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

19. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

21. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

22. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

23. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

24. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

25. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

26. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

27. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

28. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

29. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

30. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

31. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

32. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

34. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

36. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

37. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

38. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

39. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

40. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

41. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

42. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

43. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

44. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit

45. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit

46. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

47. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

48. Formerly S-1109-184-4.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1013-9 **EXPIRATION DATE:** 02/28/2007

SECTION: 28 **TOWNSHIP:** 28S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION SERVING UP TO 73 STEAM ENHANCED WELLS (BISHOP B LEASE)

PERMIT UNIT REQUIREMENTS

1. Total uncontrolled VOC emissions from all well vents shall be reduced by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Fluids produced from these steam-enhanced wells with closed well casing vents and cyclic wells with closed casing vents shall be introduced only to tanks S-1131-598, '629, '630, '638, '641, '650, '651 and '-1097 that are vented to an approved vapor collection and control system achieving 99% control, or to permit exempt storage equipment as defined by Rule 2020, Section 6.6. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Permittee shall maintain a current listing of all wells assigned to this permit. The listing shall be updated monthly and made readily available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
4. Volatile organic compound (VOC) emission rate shall not exceed 125.7 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions calculated using EPA 1995 Protocol for Equipment Leak Emission Estimates, EPA-453/R-95-017, table 2-4. [District Rule 2201] Federally Enforceable Through Title V Permit
6. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
7. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
8. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
9. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

11. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

12. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

13. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

14. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

15. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

16. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

17. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

18. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

19. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

21. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

22. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

23. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

24. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

25. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

26. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

27. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

28. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

29. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

30. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

31. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

32. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

33. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

34. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

36. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

37. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

38. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

39. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

40. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

41. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

42. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

43. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

44. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit

45. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit

46. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

47. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

48. Formerly permit number S-1109-185-6.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1014-12 **EXPIRATION DATE:** 02/28/2007

SECTION: 28 **TOWNSHIP:** 28S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION SERVING UP TO 40 STEAM ENHANCED WELLS (STAUFFER LEASE)

PERMIT UNIT REQUIREMENTS

1. Total uncontrolled VOC emissions from all well vents shall be reduced by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Fluids produced from these seam-enhanced wells with closed well casing vents and cyclic wells with closed casing vents shall be introduced only to tanks S-1131-598, '-629, '-630, '-638, '-641, '-650, '-651 and '-1097 that are vented to an approved operational vapor collection and control system achieving 99% control, or to permit exempt storage equipment as defined by Rule 2020, Section 6.6. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Permittee shall maintain a current listing of all wells assigned to this permit. The listing shall be updated monthly and made readily available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
4. Volatile organic compound (VOC) emission rate shall not exceed 68.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
6. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
7. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
8. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

10. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

11. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

12. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

13. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

14. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

15. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

16. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

17. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

18. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

20. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

21. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

22. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

23. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

24. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

25. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

26. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

27. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

28. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

29. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

30. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

31. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

32. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

33. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

34. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

36. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

37. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

38. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

39. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

40. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

41. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

43. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit

44. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit

45. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

46. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

47. Formerly S-1109-201-1.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1016-10 **EXPIRATION DATE:** 02/28/2007

SECTION: SE13 **TOWNSHIP:** 28S **RANGE:** 27E

DRAFT

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 62.5 MMBTU/HR C.E. NATCO GAS/CASING GAS-FIRED STEAM GENERATOR NORTH AMERICAN BURNER (MODEL NA 5131GCR-62.5) AND FLUE GAS RECIRCULATION (ANGUS)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. Compliance source testing for NOx, CO and fuel gas sulfur content shall be conducted at least once every 12 month period that the unit is operated (or as approved by the District). [District Rule 1081] Federally Enforceable Through Title V Permit
5. Compliance source testing shall be conducted under conditions representative of normal operation. [District Rule 1081] Federally Enforceable Through Title V Permit
6. Emission factors for this unit shall not exceed any of the following: PM-10: 0.045 lb/MMBTU, SOx (as SO2): 0.0673 lb/MMBTU, NOx (as NO2): 0.036 lb/MMBTU or 30 ppmvd @3% O2, VOC: 0.006 lb/MMBTU, or CO: 0.020 lb/MMBTU or 27 ppmvd @3% O2. [District Rule 2201, 4305, and 4351] Federally Enforceable Through Title V Permit
7. The stack concentration of NOx (as NO2), CO and O2 shall be measured at least on a monthly basis using district approved portable analyzers in any calendar month in which the unit operates. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
8. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2 and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for district inspection upon request. [District Rule 2520, 9.3.2, 9.4.2 and 4305] Federally Enforceable Through Title V Permit
9. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after one (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans, or other test methods approved by the District. [District Rules 1081, 4305, and 4351] Federally Enforceable Through Title V Permit
11. Compliance source testing for fuel gas sulfur content shall be conducted at least once every 12 months (or as approved by the District). [District Rule 1081] Federally Enforceable Through Title V Permit
12. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted within 60 days of startup, and not less than once every 12 months, except as provided below. [District Rules 2520, 9.3.2, 4305 and 4351] Federally Enforceable Through Title V Permit
13. Source testing to demonstrate compliance with NOx and CO emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
14. If permittee fails any compliance demonstration for NOx and CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
15. Source test results from an individual unit that is identical to this unit, in terms of rated capacity, operational conditions, fuel used, and control method, as approved by the APCO, will satisfy the NOx and CO source testing requirement. [District Rule 2520, 9.3.2 and 4305] Federally Enforceable Through Title V Permit
16. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
19. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(Last Amended December 19,1993). [District Rule 1081, and Kern County Rules 108.1] Federally Enforceable Through Title V Permit
20. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. {588} Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
22. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rule 2520, 9.3.2 and District Rule 4301, 5.2.1] Federally Enforceable Through Title V Permit
23. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

27. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. (This requirement shall not supersede a more stringent NSR or PSD permit testing requirement.) [District Rules 2520, 9.3.2, 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

29. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rule 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

30. All units in a group for which representative units are source tested for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

31. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

32. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. Nitrogen oxide (NOx) emission concentrations in ppmv shall be referenced at dry stack gas conditions, and shall be calculated to 3.00 percent by volume stack gas oxygen and averaged over 60 minutes, and lb/MMBtu rates shall be calculated as lb NO2/MMBtu of heat input (hhv). [District Rule 2520, 9.3.2, 4305, 5.0, 8.2 and/or 4351, 8.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320, 5.3] Federally Enforceable Through Title V Permit

37. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070; and 4320, 5.3] Federally Enforceable Through Title V Permit

38. Formerly S-1109-221-15.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1017-9 **EXPIRATION DATE:** 02/28/2007

SECTION: SE13 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION WITH UP TO 31 STEAM DRIVE WELLS AND 12 CYCLIC WELLS WITH CLOSED CASING VENTS

DRAFT

PERMIT UNIT REQUIREMENTS

1. Operation shall include no more than 31 steam drive crude oil production wells with closed casing vents and 12 cyclic crude oil production wells with closed casing vents [District Rule 2201] Federally Enforceable Through Title V Permit
2. Well casing vents shall remain closed at all times except during periods of actual service or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fluids produced from these steam-enhanced wells with closed well casing vents and cyclic wells with closed casing vents shall be introduced only to tanks S-1131-598, '629, '630, '638, '641, '650, '651 and '-1097 that are vented to an approved vapor collection and control system achieving 99% control, or to permit exempt storage equipment as defined by Rule 2020, Section 6.6. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Any increase to the maximum number of steam enhanced oil production wells with closed casing vents shall require prior authorization by an Authority to Construct. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Steam-enhanced production wells with closed well casing vents shall each have a visible identification number. Field personnel shall be provided with written instructions concerning proper operation and maintenance of the closed casing vent wells. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain a current and accurate list of all steam-enhanced wells with closed casing vents authorized by this permit and shall update the list whenever a well is added, replaced, or deleted. Upon request, the current list of wells authorized by this permit shall be submitted to the District's Compliance Division. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall retain copies of all previous lists of steam-enhanced wells with closed casing vents authorized by this permit and shall make such lists readily available for District inspection upon request for a period of at least five (5) years. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Portable hydrocarbon detection instrument shall be operated and calibrated in accordance with recommendations in CAPCOA/CARB's California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities (February, 1999): detection instrument shall be calibrated with methane; instrument flow rate range shall be maintained at 0.7 to 1.2 liters per minute; 5 second response time to maximum reading shall be achieved; instrument probe outside diameter of 3/16 inch; and background screening distance shall be no less than 25 centimeters. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Flanges shall be inspected with portable hydrocarbon detection instrument along the entire circumference of the flange-gasket interface. Threaded connections, tubing fittings, and other types of non-permanent joints shall be monitored along the entire circumference of joint interface. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

10. Valves shall be inspected with portable hydrocarbon detection instrument where the stem comes through the packing gland, and at any attached or connected body flange(s), bonnet flange(s), or plug(s). [District Rule 2201] Federally Enforceable Through Title V Permit

11. Polished rod stuffing boxes and all other components shall be inspected at all points of possible emissions. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Volatile organic compound (VOC) emission rate shall not exceed 88.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The crude oil production from wells associated with this permit unit shall not lie within 1,000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit

14. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

15. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

16. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

17. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit

18. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

19. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

20. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

21. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

22. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

24. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

25. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

26. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

27. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

28. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

29. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

30. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

31. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

32. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

33. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

34. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

35. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

36. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

37. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

38. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

39. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

40. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

41. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

42. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

43. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

44. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

45. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

46. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

47. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

48. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

49. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

50. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

51. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

52. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit

53. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit

54. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

55. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

56. Formerly permit number S-1109-222-5.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1019-3 **EXPIRATION DATE:** 02/28/2007

SECTION: SE13 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 2.7 MMBTU/HR C.E. NATCO GAS/CASING GAS-FIRED HEATER TREATER (ANGUS)

DRAFT

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2070] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4307] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4307 and all other applicable District regulations. [District Rule 4307] Federally Enforceable Through Title V Permit
4. If continuous operation oxygen analyzer/controller is utilized, excess O2 shall be maintained between 0.5 and 3.0%. If not utilized, excess air shall be maintained at no less than 15%. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Compliance source testing for NOx, CO and fuel gas sulfur content shall be conducted at least once every 12 month period that the unit is operated (or as approved by the District). [District Rule 1081] Federally Enforceable Through Title V Permit
6. Compliance source testing shall be conducted under conditions representative of normal operation. [District Rule 1081] Federally Enforceable Through Title V Permit
7. Emission factors for this unit shall not exceed any of the following: PM-10: 0.045 lb/MMBTU, SOx (as SO2): 0.0328 lb/MMBTU, NOx (as NO2): 0.117 lb/MMBTU, VOC: 0.014 lb/MMBTU, or CO: 0.036 lb/MMBTU. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081, and Kern County Rule 108.1] Federally Enforceable Through Title V Permit
9. Copies of all test results to determine compliance with the conditions of this permit shall be maintained. Operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
11. Particulate matter emissions shall not exceed 0.1 grain/dscf at operating conditions. [District Rule 4201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

12. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas; or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

13. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6, 6A, 6B, 6C; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period [Kern County Rule 407]. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. Source testing shall be performed for NOx (ppmv) according to EPA Method 7E (or ARB Method 100) and EPA Method 10 (or ARB Method 100) for CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. Nitrogen oxide (NOx) emission concentrations in ppmv shall be referenced at dry stack gas conditions, and shall be calculated to 3.00 percent by volume stack gas oxygen and averaged over 60 minutes, and lb/MMBtu rates shall be calculated as lb NO2/MMBtu of heat input (hhv). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. In years that the equipment is operated, NOx, and CO emissions shall be measured with annual source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1031-7 **EXPIRATION DATE:** 02/28/2007

SECTION: 09 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 30 STEAM-ENHANCED OIL PRODUCTION WELLS WITH CLOSED WELL CASING VENTS - CHINA LEASE

DRAFT

PERMIT UNIT REQUIREMENTS

1. Well casing vents shall remain closed at all times except during periods of actual service or repair when wells are not producing. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain a current listing of all steam-enhanced wells in the central Kern County fields heavy oil production stationary source with closed casing vents that direct fluids to uncontrolled storage tanks and a current listing of all permit numbers of front-line equipment receiving produced fluids from the wells; shall update the list whenever a well or front-line equipment is added, replaced or deleted; and shall make such listing readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Any increase to the maximum number of steam enhanced oil production wells with closed casing vents shall require prior authorization by Authority to Construct or APCO approval of application for transfer of ownership of Permit to Operate. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Volatile organic compound (VOC) emission rate shall not exceed 66.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain, for a period of at least five years, accurate records of well casing fugitive components and well casing vent piping fugitive component counts and leak screening values, and calculate fugitive emissions using District-approved emission factors. Permittee shall make records of component counts, screening values, and calculations readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The crude oil production from wells associated with this permit unit shall not lie within 1,000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
7. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and Kern County Rule 108.1] Federally Enforceable Through Title V Permit
8. Portable hydrocarbon detection instrument shall be operated and calibrated in accordance with recommendations in CAPCOA/CARB's California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities (February, 1999): detection instrument shall be calibrated with methane; instrument flow rate range shall be maintained at 0.7 to 1.2 liters per minute; 5 second response time to maximum reading shall be achieved; instrument probe outside diameter of 3/16 inch; and background screening distance shall be no less than 25 centimeters. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Flanges shall be monitored with portable hydrocarbon detection instrument along the entire circumference of the flange-gasket interface. Threaded connections, tubing fittings, and other types of non-permanent joints shall be monitored along the entire circumference of joint interface. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

10. Valves shall be monitored with portable hydrocarbon detection instrument where the stem comes through the packing gland, and at any attached or connected body flange(s), bonnet flange(s), or plug(s). [District Rule 2201] Federally Enforceable Through Title V Permit

11. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

12. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

13. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

14. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit

15. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

16. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

17. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

18. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

19. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

20. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

21. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

22. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

23. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

24. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

25. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

26. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

27. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

28. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

29. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

30. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

31. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

32. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

34. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

36. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

37. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

38. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

39. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

40. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

41. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

42. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

43. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

44. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

45. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

46. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

47. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

48. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

49. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit

50. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit

51. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

52. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

53. Formerly S-1109-335-4.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1032-7 **EXPIRATION DATE:** 02/28/2007

SECTION: 10 **TOWNSHIP:** 29S **RANGE:** 28E

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 30 STEAM-ENHANCED OIL PRODUCTION WELLS WITH CLOSED WELL CASING VENTS - RODGERS LEASE

DRAFT

PERMIT UNIT REQUIREMENTS

1. Well casing vents shall remain closed at all times except during periods of actual service or repair when wells are not producing. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain a current listing of all steam-enhanced wells in the central Kern County fields heavy oil production stationary source with closed casing vents that direct fluids to uncontrolled storage tanks and a current listing of all permit numbers of front-line equipment receiving produced fluids from the wells; shall update the list whenever a well or front-line equipment is added, replaced or deleted; and shall make such listing readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Any increase to the maximum number of steam enhanced oil production wells with closed casing vents shall require prior authorization by Authority to Construct or APCO approval of application for transfer of ownership of Permit to Operate. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Volatile organic compound (VOC) emission rate shall not exceed 66.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain, for a period of at least five years, accurate records of well casing fugitive components and well casing vent piping fugitive component counts and leak screening values, and calculate fugitive emissions using District-approved emission factors. Permittee shall make records of component counts, screening values, and calculations readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The crude oil production from wells associated with this permit unit shall not lie within 1,000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
7. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
8. Portable hydrocarbon detection instrument shall be operated and calibrated in accordance with recommendations in CAPCOA/CARB's California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities (February, 1999): detection instrument shall be calibrated with methane; instrument flow rate range shall be maintained at 0.7 to 1.2 liters per minute; 5 second response time to maximum reading shall be achieved; instrument probe outside diameter of 3/16 inch; and background screening distance shall be no less than 25 centimeters. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Flanges shall be monitored with portable hydrocarbon detection instrument along the entire circumference of the flange-gasket interface. Threaded connections, tubing fittings, and other types of non-permanent joints shall be monitored along the entire circumference of joint interface. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Valves shall be monitored with portable hydrocarbon detection instrument where the stem comes through the packing gland, and at any attached or connected body flange(s), bonnet flange(s), or plug(s). [District Rule 2201] Federally Enforceable Through Title V Permit

11. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

12. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

13. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

14. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit

15. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

16. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

17. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

18. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

19. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

20. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

21. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

22. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

23. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

24. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

25. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

26. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

27. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

28. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

29. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

30. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

31. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

32. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

34. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

36. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

37. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

38. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

39. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

40. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

41. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

42. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

43. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

44. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

45. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

46. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

47. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

48. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

49. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit

50. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit

51. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

52. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

53. Formerly S-1109-336-3.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1131-1033-12 **EXPIRATION DATE:** 02/28/2007

SECTION: SW34 **TOWNSHIP:** 28S **RANGE:** 28E

DRAFT

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 40 STEAM-ENHANCED OIL PRODUCTION WELLS WITH CLOSED CASING VENTS AND PRODUCTION ROUTED EXCLUSIVELY TO VAPOR-CONTROLLED TANKS

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Fluids produced from these steam-enhanced wells with closed well casing vents and cyclic wells with closed casing vents shall be introduced only to tanks S-1131-598, '-629, '-630, '-638, '-641, '-650, '-651 and '-1097, that are vented to an approved operational vapor collection and control system achieving 99% control, or to permit exempt storage equipment as defined by Rule 2020, Section 6.6. [District Rule 2201] Federally Enforceable Through Title V Permit
3. VOC emission rate shall not exceed 82.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall maintain with the permit accurate fugitive component counts. Fugitive VOC emissions shall be calculated using the average fugitive emissions factors in the USEPA's 1995 Protocol for Equipment Leak Emission Estimates (EPA-453/R-95-017, Table 2-4). [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain a current listing of all wells assigned to this permit. The listing shall be updated monthly and made readily available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
6. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
7. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit
8. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
9. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1 and 5.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

11. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

12. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

13. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

14. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

15. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

16. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

17. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

18. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

19. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

21. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

22. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5] Federally Enforceable Through Title V Permit

23. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

24. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

25. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

26. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

27. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

28. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit

29. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

30. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

31. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

32. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

33. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1] Federally Enforceable Through Title V Permit

34. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

35. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

36. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

37. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.I if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

38. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2] Federally Enforceable Through Title V Permit

39. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

40. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

41. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

42. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

43. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

44. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1 and 6.5] Federally Enforceable Through Title V Permit

45. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1 and 6.6] Federally Enforceable Through Title V Permit

46. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

47. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

48. Formerly permit number S-1109-356-1.

DRAFT