San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

FEB 2 8 2014

Mr John Franzia
Bronco Wine Company
6342 Bystrum Road
Ceres, CA 95307

Re Notice of Preliminary Decision – Title V Permit Renewal
District Facility # N-1665
Project # N-1132811

Dear Mr Franzia

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Bronco Wine Company at 6342 Bystrum Road in Ceres, California

The notice of preliminary decision for this project will be published approximately three days from the date of this letter After addressing all comments made during the 30-day public notice and the 45-day EPA comment periods, the District intends to issue the renewed Federally Mandated Operating Permit Please submit your written comments on this project within the 30-day public comment period, as specified in the enclosed public notice

Thank you for your cooperation in this matter If you have any questions, please contact Mr Jim Swaney, Permit Services Manager, at (559) 230-5900

Sincerely

David Warner
Director of Permit Services

Enclosures

cc Mike Tollstrup, CARB (w/enclosure) via email
cc Gerardo C Rios, EPA (w/enclosure) via email

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto CA 95356 8718
Tel (209) 557 6400 FAX (209) 557 6475

Central Region (Main Office)
1990 E Gettysburg Avenue
Fresno CA 93726 0244
Tel (559) 230 6000 FAX (559) 230 6061

Southern Region
34946 Flyover Court
Bakersfield CA 93308 9725
Tel 661 392 5500 FAX 661 392 5585

www valleyair org www healthyairliving com

P nt d ecy l d paper

SAN JOAQUIN VALLEY
AIR POLLUTION CONTROL DISTRICT

Proposed Title V Permit Renewal Evaluation
Bronco Wine Company
N-1665

TABLE OF CONTENTS

I	PROPOSAL	1
II	FACILITY LOCATION	1
III	EQUIPMENT LISTING	1
IV	GENERAL PERMIT TEMPLATE USAGE	2
V	SCOPE OF EPA AND PUBLIC REVIEW	2
VI	FEDERALLY ENFORCEABLE REQUIREMENTS	2
VII	REQUIREMENTS NOT FEDERALLY ENFORCEABLE	4
VIII	PERMIT REQUIREMENTS	5
IX	PERMIT SHIELD	13
X	PERMIT CONDITIONS	13
XI	ATTACHMENTS	13

A Renewed Title V Operating Permit
B Previous Title V Operating Permit
C Detailed Facility List

TITLE V PERMIT RENEWAL EVALUATION

Winery Facility

Engineer	Kamaljit Sran
Date	January 21, 2014

Facility Number	N-1665
Facility Name	Bronco Wine Company
Mailing Address	6342 Bystrum Road Ceres, CA 95307
Contact Name	John G Franzia, Jr
Phone	(209) 272-3012
Responsible Official	John G Franzia Jr
Title	Co-President
Project #	N-1132811
Deemed Complete	August 12, 2013

I PROPOSAL

Bronco Wine Company was issued an initial Title V permit on April 7, 2008 As required by District Rule 2520, the applicant is requesting a permit renewal The existing Title V permit shall be reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the issuance of the last renewal Title V permit

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements It also specifically identifies all additions deletions and/or changes made to permit conditions or equipment descriptions

II FACILITY LOCATION

Bronco Wine Company is located at 6342 Bystrum Road, Ceres in Stanislaus County CA

III EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as Attachment C

IV GENERAL PERMIT TEMPLATE USAGE

The applicant does not propose to use any model general permit templates

V SCOPE OF EPA AND PUBLIC REVIEW

The applicant is not requesting any model general permit templates Therefore all federally enforceable conditions in this current Title V permit will be subject to EPA and public review

VI FEDERALLY ENFORCEABLE REQUIREMENTS

A Rules Updated

- District Rule 2020, Exemptions
  (amended December 19, 2002 ⇒ amended August 18 2011)
- District Rule 2201, New and Modified Stationary Source Review Rule
  (amended December 19 2005 ⇒ amended April 21 2011)
- District Rule 4702, Internal Combustion Engines – Phase 2
  (amended June 16 2005 ⇒ amended August November 14 2013)

B Rules Removed

No rules were removed

C Rules Added

- District Rule 4694 Wine Fermentation and Storage Tanks (amended December 15, 2005)[1]
- CFR 63, Subpart ZZZZ - National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines

D Rules Not Updated

- District Rule 1070 Inspections (amended December 17,1992)
- District Rule 1081 Source Sampling (amended December 16,1993)

[1] *This rule was approved into District s SIP plan by USEPA on November 29 2012*

- District Rule 1100, Equipment Breakdown (amended December 17,1992)
- District Rule 1160, Emission Statements (adopted November 18, 1992)
- District Rule 2010, Permits Required (amended December 17, 1992)
- District Rule 2031, Transfer of Permits (amended December 17, 1992)
- District Rule 2040, Applications (amended December 17, 1992)
- District Rule 2070, Standards for Granting Applications (amended December 17, 1992)
- District Rule 2080, Conditional Approval (amended December 17, 1992)
- District Rule 2520, Federally Mandated Operating Permits (amended June 21, 2001)
- District Rule 4101, Visible Emissions (amended February 17, 2005)
- District Rule 4201, Particulate Matter Concentration (amended December 17 1992)
- District Rule 4202, Particulate Matter - Emission Rate (amended December 17 1992)
- District Rule 4301, Fuel Burning Equipment (amended December 17, 1992)
- District Rule 4601, Architectural Coatings (amended October 31, 2001)
- District Rule 4621 Gasoline Transfer into Stationary Storage Containers, Delivery Vessels, and Bulk Plants (amended December 19 2013)
- District Rule 4622, Transfer of Gasoline into Vehicle Fuel Tanks (amended December 19, 2013)
- District Rule 4801 Sulfur Compounds (amended December 17, 1992)
- District Rule 8011, General Requirements (amended August 19, 2004)
- District Rule 8021, Construction, Demolition, Excavation, Extraction, and Other Earthmoving Activities (amended August 19, 2004)

- District Rule 8031, Bulk Materials (amended August 19 2004)
- District Rule 8041, Carryout and Trackout (amended August 19, 2004)
- District Rule 8051, Open Areas (amended August 19, 2004)
- District Rule 8061, Paved and Unpaved Roads (amended August 19, 2004)
- District Rule 8071, Unpaved Vehicle/Equipment Traffic Areas (amended September 16, 2004)
- 40 CFR Part 64 Compliance Assurance Monitoring (CAM)
- 40 CFR Part 61, Subpart M, National Emission Standard for Asbestos
- 40 CFR Part 82 Subparts B and F, Stratospheric Ozone

VII REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements The District-only requirements are not a part of the Title V Operating Permits The terms and conditions that are part of the facility's Title V permit are designated as 'Federally Enforceable Through Title V Permit'

For this facility, the following are not federally enforceable and will not be discussed in further detail

A Rules Added (None)

B Rules Not Updated

1 District Rule 4102 Nuisance (as amended December 17, 1992)

Condition 40 of the facility-wide requirements (N-1665-0-2) is based on District Rule 4102 and will therefore not be discussed any further

2 District Rule 4694 Wine Fermentation and Storage Tanks (amended December 15, 2005)

The purpose of this rule is to reduce emissions of Volatile Organic Compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources The rule is

applicable to any facility with VOC emissions in excess of 10 tons per year For those facilities to which the rule applies, the requirements of the rule are applicable to any fermentation or storage tank with capacity in excess of 5,000 gallons The rule was adopted on December 15, 2005 and submitted to EPA for approval into the State Implementation Plan (SIP)

On November 29, 2012, the EPA approved an amended SIP submittal which excludes the fermentation provisions of the Rule 4694 while maintaining the storage provisions Therefore, the fermentation provisions are not federally enforceable All other provisions are considered to be federally enforceable

Conditions 41 through 45 of the facility-wide requirements (N-1665-0-2) are based on District Rule 4694 fermentation requirements and are therefore not federally enforceable

Condition 8 of the requirements for permit units (N-1665-6-2 through -10-2 and -17-2 through -449-2) is based on District Rule 4694 fermentation requirements and is therefore not federally enforceable through District Rule 4694

VIII PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements therefore, this compliance section will only address rules that have been amended or added since the issuance of the previous Title V permit or un-amended rules for which the original permit conditions have been revised

A District Rule 2020 - Exemptions

District Rule 2020 lists equipment which is specifically exempt from obtaining permits and specifies recordkeeping requirements to verify such exemptions The amendments to this rule do not have any affect on current permit requirements and will therefore not be addressed in this evaluation

B District Rule 2201 - New and Modified Stationary Source Review Rule

District Rule 2201 has been amended since this facility's initial Title V permit was issued This Title V permit renewal does not constitute a modification per section 3 26, defined as an action including at least one of the following items

1) Any change in hours of operation, production rate, or method of operation of an existing emissions unit which would necessitate a change in permit conditions
2) Any structural change or addition to an existing emissions unit which would necessitate a change in permit conditions Routine replacement shall not be considered to be a structural change
3) An increase in emissions from an emissions unit caused by a modification of the Stationary Source when the emissions unit is not subject to a daily emissions limitation
4) Addition of any new emissions unit which is subject to District permitting requirements
5) A change in a permit term or condition proposed by an applicant to obtain an exemption from an applicable requirement to which the source would otherwise be subject

Therefore, the updated requirements of this rule are not applicable at this time

C District Rule 2520 - <u>Federally Mandated Operating Permits</u>

There are no federally applicable Greenhouse Gas (GHG) requirements for this source It should be noted that the Mandatory Greenhouse Gas Reporting rule (40 CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40 CFR 71 2) Therefore, there will be no further discussion of GHG in this evaluation

D District Rule 4694 - <u>Wine Fermentation and Storage Tanks</u>

On November 29 2012, the EPA approved an amended SIP submittal which excludes the fermentation provisions of the Rule 4694 while maintaining the storage provisions Therefore, the fermentation provisions are not federally enforceable All other provisions are considered to be federally enforceable

Section 5 2 requires the operators of any wine storage tank having an internal volume equal to or greater than 5 000 gallons shall comply with all of the following requirements when storing wine

5 2 1 The tank shall be equipped and operated with a pressure-vacuum relief valve meeting all of the following requirements

- The pressure-vacuum relief valve shall operate within 10% of the maximum allowable working pressure of the tank,

- The pressure-vacuum relief valve shall operate in accordance with the manufacturer s instructions, and
- The pressure-vacuum relief valve shall be permanently labeled with the operating pressure settings
- The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21

5 2 2 The temperature of the stored wine shall be maintained at or below 75°F

- Temperature of the stored wine shall be determined and recorded at least once per week
- For each batch of wine, operators shall achieve the storage temperature of 75°F or less within 60 days after completing fermentation

The following conditions will be included in each these storage tanks permits to ensure compliance with the above sections

- This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694]

- The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694]

- The temperature of the wine stored in this tank shall be maintained at or below 75°F The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine, the operator shall achieve the storage temperature of 75°F or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75°F or less was achieved [District Rule 4694]

Section 6 4 2 requires that weekly records be kept of wine volume and temperature of wine contained in each storage tank The following conditions will enforce on-going compliance with this section

- Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred shall be maintained [District Rules 2201 and 4694]

- The operator shall record, on a daily basis, the total gallons of wine contained in the tank [District Rules 2201 and 4694]

Compliance is expected with this Rule

E District Rule 4702 - <u>Internal Combustion Engines – Phase 2</u>

In the latest amendments to this rule the language in Section 4 2 was amended to consolidate requirements for emergency standby and low-use engines The language was streamlined for reader clarity No changes to the existing requirements made to this section Therefore, amendments to rule do not change requirements of permit unit N-1665-452-2 & -507-2

F 40 CFR 63, Subpart ZZZZ - <u>National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines</u>

a 94 5 HP Diesel Fired IC Engine Driving Emergency electrical generator (N-1665-452-2)
b 105 HP Diesel Fired IC Engine Driving Emergency Fire Pump (N-1665-507-2)

The requirements of 40 CFR Part 63 Subpart ZZZZ National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines, are applicable to owners and operators of a stationary RICE located at a major or area source of HAP emissions This facility is not a major source of HAP emissions and is therefore by definition, and area source of HAP emissions Therefore the requirements of this subpart are applicable to this engine

The subject engines were installed before 2006, therefore, as defined by Section 63 65 90(iii), this engine can be classified as existing stationary RICE In accordance with Section 63 6595 the emission limitations and operating limits for existing stationary RICE at an area source of HAP emissions do not become applicable until May 1, 2013 for compression ignited engines

However, the requirements of this regulation will be included in this project for future reference

§63 6603(a) states the owner or operator of an existing emergency stationary RICE located at an area source of HAP emissions must comply with the requirements listed in Table 2(d)(4) & (d)(5)

Table 2d - Requirements for Existing Stationary RICE Located at Area Sources

For each	You must meet the following requirements except during periods of startup	During periods of startup you must
4 Emergency stationary CI RICE and black start stationary CI RICE [2]	a Change oil and filter every 500 hours of operation or annually whichever comes first and replace as necessary	N/A
5 Emergency stationary SI RICE black start stationary SI RICE non emergency non black start 4SLB stationary RICE >500 HP that operate 24 hours or less per calendar year non emergency non black start 4SRB stationary RICE >500 HP that operate 24 hours or less per calendar year [2]	b Inspect air cleaner every 1 000 hours of operation or annually whichever comes first and replace as necessary	N/A
	c Inspect all hoses and belts every 500 hours of operation or annually whichever comes first and replace as necessary	N/A

[2] If an emergency engine is operating during an emergency and it is not possible to shut down the engine in order to perform the management practice requirements on the schedule required in Table 2d of this subpart or if performing the management practice on the required schedule would otherwise pose an unacceptable risk under Federal State or local law the management practice can be delayed until the emergency is over or the unacceptable risk under Federal State or local law has abated The management practice should be performed as soon as practicable after the emergency has ended or the unacceptable risk under Federal State or local law has abated Sources must report any failure to perform the management practice on the schedule required and the Federal State or local law under which the risk was deemed unacceptable

The following conditions will ensure compliance with the requirements of this section

- The engine's oil and filter shall be changed every 1 000 hours of operation or every 12 months, whichever comes first [40 CFR 63 6603/66 6640 Table 2d Row 1 a]
- The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months whichever comes first and replaced as necessary [40 CFR 63 6603/63 6640 Table 2d Row 1 b]
- The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months whichever comes first, and replaced as necessary [40 CFR 63 6603/63 6640 Table 2d Row 1 c]
- The permittee shall keep records of the maintenance conducted on the engine [40 CFR 63 6655(e)]

§63 6625(f) states the owner or operator of an existing emergency CI stationary RICE located at an area source of HAP emissions must install a non-resettable hour meter if one is not already installed

Existing condition 4 of the requirements for these permit units ensure compliance with requirements of this section

§63 6625(f)(ii), states the owner or operator of an existing emergency CI stationary RICE located at an area source of HAP emissions may operate the emergency stationary RICE for the purpose of maintanence checks and readiness testing, provided that the tests are recommended by Federal State or local government, the manufacturer, the vendor or the insurance company associated with the engine Maintenance checks and readiness testing of such units is limited to 100 hours per year The owner or operator may petition the Administrator for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the owner or operator maintains records indicating that Federal, State, or local standards require maintenance and testing of emergency RICE beyond 100 hours per year

Existing condition 10 of the requirements for these permit units ensure compliance with requirements of this section

§63 6625(h) states the owner or operator of an existing stationary RICE must minimize the engine's time spent at idle during start and minimze the engine's startup time to a period needed for appropriate and safe loading of the engine not to exceed 30 minutes, after which time the emission standards applicable to all time other than startup in Tables 1a, 2a, 2c, and 2d to this subpart apply

The Table 2d applicable to existing stationary RICE located at area sources of HAP emissions does not specify any startup requirements for emergency engines

§63 6640(f) applies to emergency stationary RICE The facility shall operate the emergency stationary RICE according to the requirements in paragraphs (f)(1)(i) through (iii) of this section Any operation other than emergency operation, maintenance and testing, and operation in non-emergency situations for 50 hours per year, as described in paragraphs (f)(1)(i) through (iii) of this section, is prohibited If the facility does not operate the engine according to the requirements in paragraphs (f)(1)(i) through (iii) of this section, the engine will not be considered an emergency engine under this subpart and will need to meet all requirements for non-emergency engines

Operation of these engines is restricted by District Rule 4702 to maintenance, testing and required regulatory purposes, and during emergency situations Therefore requirement of this section is pre-empted by requirements of District Rule 4702

The operator must continuously comply with the emissions and operating limitations and work or management practices as required by the following

Table 6 to Subpart ZZZZ of Part 63 - Continuous Compliance With Emission Limitations, Operating Limitations, Work Practices, and Management Practices

For each	Complying with the requirement to	You must demonstrate continuous compliance by
9 Existing emergency and black start stationary RICE located at an area source of HAP	a Work or Management practices	i Operating and maintaining the stationary RICE according to the manufacturer's emission related operation and maintenance instructions or ii Develop and follow your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions

Existing condition 11 of the requirements for these permit units ensure compliance with requirements of this section

§63 6655(a) states, the operator must keep the records described belows

(4) Records of all required maintenance performed on the air pollution control and monitoring equipment
(5) Records of actions taken during periods of malfunction to minimize emissions in accordance with §63 6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation

§63 6655(d) states the operator must keep the records required in Table 6 of this subpart to show continuous compliance with each emission or operating limitation that appplies

§63 6655(e) states the operator shall keep records of the maintenance conducted on the stationary RICE in order to demonstrate that the facility operated and maintained the statioary RICE and after-treatment control device (if any) according to the facility's own maintenance plan if the following stationary RICE are owned or operated

(2) An existing stationary emergency RICE
(3) An existing stationary RICE located at an area source of HAP emissions subject to management practices as shown in Table 2d to this subpart

§63 6655(f) states that an owner or operator of any of an existing emergency stationary RICE located at an area source of HAP emissions that does not meet the standards applicable to non-emergency engines shall keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter The owner or operator must document how many hours are spent for emergency operation including what classified the operation as emergency and how many hours are spent for non-emergency operation If the engines are used for demand response operation, the owner or operator must keep records of the notification of the emergency situation, and the time the engine was operated as part of demand response

Existing condition 10 of the requirements for these permit units ensure compliance with requirements of this section

G 40 CFR Part 64-CAM

<u>§64 2 – Applicability</u>

This section requires Compliance Assurance Monitoring (CAM) for units that meet the following three criteria
1) the unit must have an emission limit for the pollutant,
2) the unit must have add-on controls for the pollutant, these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers and
3) the unit must have a pre-control potential to emit of greater than the major source thresholds

CAM applicability and requirements for this facility have been addressed in the initial TV permit issuance For the permit units that were installed since issuance of initial TV CAM applicability and requirements are being addressed as following

a <u>N-1665-452-2 Electrical Generator</u>
As unit N-1665-452-2 does not have add-on controls for any pollutant, therefore CAM is not applicable to this unit

b <u>N-1665-507-2 Fire Pump</u>
As unit N-1665-507-2 does not have add-on controls for any pollutant, therefore CAM is not applicable to this unit

c <u>N-1665-1-5 12 6 MMBtu Boiler</u>

This boiler has add-on controls only for NOx in the form of FGR The boiler is equipped with ultra low NOx burner which are guaranteed to have NOx emissions of 15 ppmv @ 3% O_2 or 0 018 lb/MMBtu

Therefore uncontrolled NOx emissions from a 12 6 MMBtu/hr unit is calculated as shown below

0 018 lb/MMBtu x 12 685 MMBtu/hr x 8,760 hrs/year = 1 988 lb/year

Therefore CAM is not applicable for NOx Major source threshold for NOx is 20 000 lb/yr year

d N-1665-496-1 Winery Wastewater Treatment Operation

As unit N-1665-496-1 does not have add-on controls for any pollutant, therefore CAM is not applicable to this unit

e N-1665-497-3 thru -506-3 and -508-2 thru -513-2 Wine Stroage Tanks

As unit these wine storage tanks does not have any add-on controls for any pollutant therefore CAM is not applicable to these units

IX PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed

A Requirements Addressed by Model General Permit Templates

The applicant does not propose to use any model general permit templates

B Requirements not Addressed by Model General Permit Templates

The applicant is not requesting any permit shields

C Obsolete Permit Shields From Existing Permit Requirements

The original permits did not contain any permit shields

X PERMIT CONDITIONS

See Attachment A – Draft Renewed Title V Operating Permit

XII ATTACHMENTS

A Draft Renewed Title V Operating Permit
B Expiring Title V Operating Permit
C Detailed Facility List

FACILITY N 1665 0 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

FACILITY-WIDE REQUIREMENTS

1 The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary [District Rule 1100 6 1 and Stanislaus County Rule 110] Federally Enforceable Through Title V Permit

2 The District shall be notified in writing within ten days following the correction of any breakdown condition The breakdown notification shall include a description of the equipment malfunction or failure the date and cause of the initial failure the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations [District Rule 1100, 7 0 and Stanislaus County Rule 110] Federally Enforceable Through Title V Permit

3 {4364} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source [District Rule 1160, 5 0] Federally Enforceable Through Title V Permit

4 {4365} Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance the use of which may cause the issuance of air contaminants or the use of which may eliminate reduce or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07) [District Rule 2010 3 0 and 4 0 and 2020] Federally Enforceable Through Title V Permit

5 {4366} The permittee must comply with all conditions of the permit including permit revisions originated by the District All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA) including provisions to limit potential to emit are enforceable by the EPA and Citizens under the CAA Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations and is grounds for enforcement action, for permit termination, revocation reopening and reissuance, or modification or for denial of a permit renewal application [District Rules 2070 7 0 2080 and 2520 9 9 1 and 9 13 1] Federally Enforceable Through Title V Permit

6 {4367} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District [District Rule 2031] Federally Enforceable Through Title V Permit

7 {4368} Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District [District Rule 2040] Federally Enforceable Through Title V Permit

8 {4369} The operator shall maintain records of required monitoring that include 1) the date place and time of sampling or measurement 2) the date(s) analyses were performed 3) the company or entity that performed the analysis 4) the analytical techniques or methods used, 5) the results of such analysis and 6) the operating conditions at the time of sampling or measurement [District Rule 2520 9 4 1] Federally Enforceable Through Title V Permit

9 {4370} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement or report Support information includes copies of all reports required by the permit and for continuous monitoring instrumentation all calibration and maintenance records and all original strip chart recordings [District Rule 2520 9 4 2] Federally Enforceable Through Title V Permit

FACILITY WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

10 {4371} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement All instances of deviations from permit requirements must be clearly identified in such reports [District Rule 2520 9 5 1] Federally Enforceable Through Title V Permit

11 {4372} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions as defined in the permit For the purpose of this condition promptly means as soon as reasonably possible, but no later than 10 days after detection The report shall include the probable cause of such deviations and any corrective actions or preventive measures taken All required reports must be certified by a responsible official consistent with section 10 0 of District Rule 2520 (6/21/01) [District Rules 2520, 9 5 2 and 1100 7 0] Federally Enforceable Through Title V Permit

12 {4373} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit [District Rule 2520 9 7] Federally Enforceable Through Title V Permit

13 {4374} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit [District Rule 2520 9 8 2] Federally Enforceable Through Title V Permit

14 {4375} The permit may be modified revoked reopened and reissued, or terminated for cause The filing of a request by the permittee for a permit modification revocation and reissuance or termination or a notification of planned changes or anticipated noncompliance does not stay any permit condition [District Rule 2520 9 8 3] Federally Enforceable Through Title V Permit

15 {4376} The permit does not convey any property rights of any sort, or any exclusive privilege [District Rule 2520 9 8 4] Federally Enforceable Through Title V Permit

16 {4377} The Permittee shall furnish to the District, within a reasonable time any information that the District may request in writing to determine whether cause exists for modifying revoking and reissuing or terminating the permit or to determine compliance with the permit Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or for information claimed to be confidential the permittee may furnish such records directly to EPA along with a claim of confidentiality [District Rule 2520 9 8 5] Federally Enforceable Through Title V Permit

17 {4378} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations [District Rule 2520 9 9] Federally Enforceable Through Title V Permit

18 {4379} Upon presentation of appropriate credentials a permittee shall allow an authorized representative of the District to enter the permittee s premises where a permitted source is located or emissions related activity is conducted or where records must be kept under condition of the permit [District Rule 2520, 9 13 2 1] Federally Enforceable Through Title V Permit

19 {4380} Upon presentation of appropriate credentials a permittee shall allow an authorized representative of the District to have access to and copy at reasonable times any records that must be kept under the conditions of the permit [District Rule 2520 9 13 2 2] Federally Enforceable Through Title V Permit

20 {4381} Upon presentation of appropriate credentials a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices or operations regulated or required under the permit [District Rule 2520, 9 13 2 3] Federally Enforceable Through Title V Permit

21 {4382} Upon presentation of appropriate credentials a permittee shall allow an authorized representative of the District to sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements [District Rule 2520, 9 13 2 4] Federally Enforceable Through Title V Permit

22 No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition [District Rule 4101 and Stanislaus County Rule 401] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

23 {4384} No person shall manufacture blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District [District Rule 4601 5 1] Federally Enforceable Through Title V Permit

24 {4385} All VOC containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use [District Rule 4601 5 4] Federally Enforceable Through Title V Permit

25 {4386} The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6 1 and 6 3 (12/17/09) [District Rule 4601, 6 1 and 6 3] Federally Enforceable Through Title V Permit

26 {4387} With each report or document submitted under a permit requirement or a request for information by the District or EPA the permittee shall include a certification of truth, accuracy, and completeness by a responsible official [District Rule 2520 9 13 1 and 10 0] Federally Enforceable Through Title V Permit

27 {4388} If the permittee performs maintenance on or services repairs or disposes of appliances the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82 Subpart F [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

28 {4389} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82 Subpart B [40 CFR Part 82 Subpart B] Federally Enforceable Through Title V Permit

29 {4390} Disturbances of soil related to any construction, demolition excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4 0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004) [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

30 {4391} Outdoor handling storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031 unless specifically exempted under Section 4 0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004) [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

31 {4392} An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5 0 unless specifically exempted under Section 4 0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004) [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

32 {4393} Whenever open areas are disturbed, or vehicles are used in open areas the facility shall comply with the requirements of Section 5 0 of District Rule 8051 unless specifically exempted under Section 4 0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004) [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

33 {4394} Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4 0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004) [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

34 {4395} Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5 1 1 of District Rule 8071 Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5 1 2 of District Rule 8071 On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area the owner/operator shall comply with the requirements of Section 5 1 3 of District Rule 8071 On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5 1 4 of District Rule 8071 All sources shall comply with the requirements of Section 5 0 of District Rule 8071 unless specifically exempted under Section 4 0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004) [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

35 {4396} Any owner or operator of a demolition or renovation activity as defined in 40 CFR 61 141, shall comply with the applicable inspection, notification removal and disposal procedures for asbestos containing materials as specified in 40 CFR 61 145 (Standard for Demolition and Renovation) [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

36 {4397} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits including emission limits standards and work practices to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District) The certification shall include the identification of each permit term or condition the compliance status whether compliance was continuous or intermittent the methods used for determining the compliance status and any other facts required by the District to determine the compliance status of the source [District Rule 2520 9 16] Federally Enforceable Through Title V Permit

37 {4398} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months prior to the permit expiration date [District Rule 2520, 5 2] Federally Enforceable Through Title V Permit

38 {4399} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply [District Rule 2520 9 1 1] Federally Enforceable Through Title V Permit

39 On April 30 2008 the initial Title V permit was issued The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division These reports are due within 30 days after the end of the reporting period [District Rule 2520] Federally Enforceable Through Title V Permit

40 {98} No air contaminant shall be released into the atmosphere which causes a public nuisance [District Rule 4102]

41 This facility shall annually achieve the Required Annual Emission Reductions (RAER) as specified in the facility's APCO-approved Three Year Compliance Plan for District Rule 4694 [District Rule 4694]

42 A Three Year Compliance Plan that demonstrates compliance with the requirements of Section 5 1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District every three years thereafter on or before December 1 [District Rule 4694]

43 A Three Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District every three years on or before July 1 [District Rule 4694]

44 An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of District Rule 4694 shall be submitted to the District by every year thereafter on or before March 1 [District Rule 4694]

45 Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three Year Compliance Plan and shall maintain all records necessary to demonstrate compliance [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 1 5 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
12 6 MMBTU/HR HURST MODEL 300 NATURAL GAS FIRED BOILER WITH ST JOHNSON MODEL RX 300F ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1 All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere [District Rule 2201] Federally Enforceable Through Title V Permit

2 Particulate matter emissions shall not exceed 0 1 grains/dscf in concentration [District Rule 4201] Federally Enforceable Through Title V Permit

3 The unit shall only be fired on PUC-regulated natural gas [District Rule 2201] Federally Enforceable Through Title V Permit

4 Emissions rates from the natural gas-fired unit shall not exceed any of the following limits 15 ppmv NOx @ 3% O2 or 0 018 lb-NOx/MMBtu 0 00285 lb-SOx/MMBtu 0 005 lb-PM10/MMBtu 200 ppmv CO @ 3% O2 or 0 148 lb-CO/MMBtu 0 004 lb-VOC/MMBtu [District Rules 2201 4305 and 4306] Federally Enforceable Through Title V Permit

5 Pursuant to Rule 4320 beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year Payments are due by July 1 of each year Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320 [District Rule 4320] Federally Enforceable Through Title V Permit

6 All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3 0 of District Rule 4306 [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

7 The permittee shall monitor and record the stack concentration of NOx CO and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications Monitoring shall not be required if the unit is not in operation i e the unit need not be started solely to perform monitoring Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8 If either the NOx or CO concentrations corrected to 3% O2 as measured by the portable analyzer exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible but no longer than 1 hour of operation after detection If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action The permittee must then correct the violation show compliance has been re-established, and resume monitoring procedures If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100 the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

9 All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate The analyzer shall be calibrated maintained and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive minute period [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

10 The permittee shall maintain records of (1) the date and time of NOx CO and O2 measurements (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer (4) exhaust gas analyzer calibration records and (5) a description of any corrective action taken to maintain the emissions within the acceptable range [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

11 This unit shall be tested for compliance with the NOx and CO emissions limits at least once every twelve (12) months After demonstrating compliance on two (2) consecutive annual source tests the unit shall be tested not less than once every thirty six (36) months If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits the source testing frequency shall revert to at least once every twelve (12) months [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

12 The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

13 Source testing shall be conducted using the methods and procedures approved by the District The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing [District Rule 1081] Federally Enforceable Through Title V Permit

14 NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis or EPA Method 19 on a heat input basis [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

15 CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100 [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

16 Stack gas oxygen (O2) shall be determined using EPA Method 3 or 3A or ARB Method 100 [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

17 For emissions source testing the arithmetic average of three 30-consecutive minute test runs shall apply If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

18 Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis Such records shall be maintained and retained on site for a minimum of five (5) years and shall be made available for District inspection upon request [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

19 Permittee shall determine sulfur content of combusted gas annually or shall demonstrate that the combusted gas is provided from a PUC or FERC regulated source [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20 The results of each source test shall be submitted to the District within 60 days thereafter [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 5-3 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
GASOLINE DISPENSING OPERATION WITH ONE 5 200 GALLON CONVAULT ABOVEGROUND STORAGE TANK SERVED BY TWO POINT PHASE I VAPOR RECOVERY SYSTEM AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G 70 116-F)

PERMIT UNIT REQUIREMENTS

1 The Phase I, Phase II and Standing Loss Control Vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection the Division of Occupational Safety and Health of the Department of Industrial Relations and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification [District Rules 4621 and 4622 and CH&SC 41950] Federally Enforceable Through Title V Permit

2 This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales [District Rule 4622] Federally Enforceable Through Title V Permit

3 The storage container(s) shall be installed, maintained, and operated such that they are leak-free [District Rule 4621] Federally Enforceable Through Title V Permit

4 The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

5 A leak is defined as the dripping of VOC containing liquid at a rate of more than three (3) drops per minute or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10 000 ppmv as methane, above background when measured in accordance with EPA Test Method 21 [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

6 No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container which attest to the vapor integrity of the container [District Rule 4621] Federally Enforceable Through Title V Permit

7 No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met 1) the defect has been repaired replaced, or adjusted as necessary to correct the defect 2) the District has been notified and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components), and 3) all major defects after repair, are duly entered into the Operations and Maintenance (O&M) manual [District Rule 4622] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8 Upon identification of any major defects the permittee shall tag "Out of-Order all dispensing equipment for which vapor recovery has been impaired Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired replaced, or adjusted as necessary In the case of defects identified by the District tagged equipment shall be rendered inoperable and the tag shall not be removed until the District has been notified of the repairs and the District has either reinspected the system or authorized the tagged equipment for use [District Rule 4622] Federally Enforceable Through Title V Permit

9 The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information 1) copies of all vapor recovery performance tests 2) all applicable ARB Executive Orders, Approval Letters and District Permits 3) the manufacturer's specifications and instructions for installation operation repair and maintenance required pursuant to ARB Certification Procedure CP 201, and any additional instruction provided by the manufacturer 4) system and/or component testing requirements including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements) and 5) additional O&M instructions if any that are designed to ensure compliance with the applicable rules regulations ARB Executive Orders and District permit conditions, including replacement schedules for failure or wear prone components [District Rule 4622] Federally Enforceable Through Title V Permit

10 The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows A) less than 2,500 gallons - one day per month, B) 2,500 to less than 25 000 gallons - one day per week or C) 25 000 gallons or greater five days per week All inspections shall be documented within the O & M Manual [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

11 Periodic maintenance inspections of the Phase I vapor recovery system shall include at a minimum, verification that 1) the fill caps and vapor caps are not missing damaged or loose 2) the fill cap gasket and vapor cap gaskets are not missing or damaged 3) the fill adapter and vapor adapter are securely attached to the risers 4) where applicable, the spring loaded submerged fill tube seals properly against the coaxial tubing 5) the dry break (poppet-valve) is not missing or damaged and 6) the submerged fill tube is not missing or damaged [District Rule 4621] Federally Enforceable Through Title V Permit

12 Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum verification that 1) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable faceplate/facecone bellows latching device spring vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism automatic shut off mechanism and hold open latch (unless prohibited by law or the local fire control authority) 2) the hoses are not torn flattened or crimped 3) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable and 4) the vapor processing unit is functioning properly for operations that are required to have or possess such a unit [District Rule 4622] Federally Enforceable Through Title V Permit

13 In the event of a separation due to a drive off, the permittee shall unless otherwise specified in the applicable ARB Executive Order conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service [District Rule 4622] Federally Enforceable Through Title V Permit

14 The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date unless otherwise required under the applicable ARB Executive Order [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

15 The permittee shall perform and pass a Static Leak Test ' Determination of Static Pressure Performance of Vapor Recovery Systems at Gasoline Dispensing Facilities with Aboveground Tanks" in accordance with the Executive Order specified in this permit for the Phase I Vapor Recovery System at least once every 12 months [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

16 If a rotatable Phase I vapor adaptor is installed the permittee shall perform and pass a Static Torque of Rotatable Phase I Adaptors test using ARB procedure TP 201 1B at least once every 36 months [District Rule 4621] Federally Enforceable Through Title V Permit

17 For certified Phase II vapor recovery systems with liquid removal devices the permittee shall perform and pass an ARB TP 201 6 Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid The amount of liquid in the vapor path shall be measured by lowering the gasoline dispensing nozzle into a container until such time that no more liquid drains from the nozzle The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker The vapor path shall be inspected once per month if monthly throughput is below 2 500 gallons or once per week otherwise [District Rule 4622] Federally Enforceable Through Title V Permit

18 If a Liquid Condensate Trap is installed, the permittee shall perform and pass a Liquid Condensate Trap Compliance Test using the test procedure defined in the Executive Order specified in this permit for the Phase II Vapor Recovery System at least once every 12 months [District Rule 4622] Federally Enforceable Through Title V Permit

19 If a Liquid Condensate Trap is installed it shall be (1) maintained without leaks (2) accessible for inspection upon request, (3) capable of automatic evacuation of liquid and (4) equipped with an alarm system in case of failure of the evacuation system [District Rule 4622] Federally Enforceable Through Title V Permit

20 A person conducting testing of, or repairs to a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification) [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

21 A person performing installation of or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified The ICC certification shall be renewed every 24 months [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

22 Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

23 The permittee shall notify the District at least 7 days prior to each performance test The test results shall be submitted to the District no later than 30 days after the completion of each test [District Rule 4621] Federally Enforceable Through Title V Permit

24 The permittee shall maintain a copy of all test results The test results shall be dated and shall contain the name address and telephone number of the company responsible for system installation and testing [District Rule 4622] Federally Enforceable Through Title V Permit

25 The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system The repair log shall include the following 1) date and time of each repair 2) the name and applicable certification numbers of the person(s) who performed the repair and if applicable the name address and phone number of the person's employer 3) description of service performed 4) each component that was repaired serviced or removed 5) each component that was installed as replacement if applicable and 6) receipts or other documents for parts used in the repair and, if applicable work orders which shall include the name and signature of the person responsible for performing the repairs [District Rule 4622] Federally Enforceable Through Title V Permit

26 The O&M manual shall be kept at the dispensing operation and made available to any person who operates inspects, maintains repairs or tests the equipment at the operation as well as to District personnel upon request [District Rule 4622] Federally Enforceable Through Title V Permit

27 The permittee shall maintain monthly and annual gasoline throughput records [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

28 All records required by this permit shall be retained on site for a period of at least five years and shall be made available for District inspection upon request [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 6 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
2 648 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 21) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 7 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
1 999 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 22) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 8 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
1 999 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 23) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 9 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
4 012 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 40) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-10 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
4 012 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 41) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 17 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
6 700 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 59) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-18 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
6 652 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 60) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 21 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
6 074 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 63) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 22-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 71) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 23-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 72) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 24 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 73) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 25 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 74 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 26-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 75) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-27 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 76) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 28 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 77) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 29 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 78) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 30 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 83) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 31-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 84) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 32-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 85) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-33 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 89) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 34-2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 90) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 38 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 093 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 104) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 39 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 500 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 105) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-40 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 520 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 106) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694]
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694]
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694]
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694]
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694]
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694]
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694]
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-41 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 520 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 107) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 42 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 110) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-43 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 111) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-44 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 112) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 45 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 113) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 46 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 114) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-47 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 115) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-48 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 116) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 49 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 117) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 50-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 118) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 51 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 119) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 52 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 120) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-53-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
12 406 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 121) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 54-2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
12 406 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 122) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 55-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
12 406 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 123) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 56 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
11 888 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 124) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 57 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
11 888 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 125) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 58-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 126) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 59 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 130) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 60 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 131) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 61 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 132) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 62 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 133) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 63 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 134) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 64-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 135) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-65-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
14 771 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 141) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 66 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
14 771 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 142) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-67-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
14 771 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 143) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-68-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
15 069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 144) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 69 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 150) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-70 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 151) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 71 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 152) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-72-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 153) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 73-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 154) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 74 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 155) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 75-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 156) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 76 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 157) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 77 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 158) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 78 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 159) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 79 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 160) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-80 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 161) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-81-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 162) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 82-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 163) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 83-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 164) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 84 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 165) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 85-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 166) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-86-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 167) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-87-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 168) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 88 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 169) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-89-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 170) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-90 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 171) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 91-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 172) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 92 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 173) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-93 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 174) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 94-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 175) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 95-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 176) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 96-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 177) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-97 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 178) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 98-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 179) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-99-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 180) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 100 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 181) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-101 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 182) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-102 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 183) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 103 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 184) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 104 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 185) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 105 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 186) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 106 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
19 967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 220) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 107-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
19 967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 221) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 108 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
19 967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 222) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-109 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
19 967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 223) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-110 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
19 967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 224) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 111 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
19 967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 225) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 112 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
19 967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 226) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-113-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
19 967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 227) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 117 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
24 863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 251) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 118 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
24 863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 252) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-119-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
24 693 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 253) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 120-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
24 693 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 254) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 121 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
24 863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 255) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 122 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
24 863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 256) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-123-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
31 562 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 301) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 124 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
31 562 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 302) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 125-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
31 562 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 303) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-126-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
55 033 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 501) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-127-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
54 971 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 502) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 128 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
55 017 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 503) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-129-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 504) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-130-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
54 881 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 505) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 131 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
55 141 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 506) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 132 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
54 930 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 507) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 133 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
55 030 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 508) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 134-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 511) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-135 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 512) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-136-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 513) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-137-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 514) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 138 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 515) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-139-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 516) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 140 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 517) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-141-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 518) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 142 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 519) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-143-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 520) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-144-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 521) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-145 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 522) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 146 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 523) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 147 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 524) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 148 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 525) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 149-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 526) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-150-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 527) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-151-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 528) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 152 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 529) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 153 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
52 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 530) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 154-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
105 690 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1001) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-155-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
105 690 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1002) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-156-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
105 690 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1003) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 157 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1004) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-158-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1005) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-159 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION

106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1006) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 160 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
105 690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1011) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-161-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
105 690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1012) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 162 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
105 690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1013) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 163-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
105 690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1014) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 164 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
105 690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1015) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 165-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
105 690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1016) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-166 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
105 690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1017) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 167 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
105 690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1018) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-168-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1031) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-169-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1032) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 170 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1033) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 171 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1034) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 172 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1035) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-173-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1036) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-174-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1037) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 175-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1038) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-176 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1039) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 177 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1040) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-178 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1041) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-179-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1042) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-180-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1043) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 181 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1044) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-182-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1045) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-183-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1046) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 184 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1047) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-185 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1048) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 186 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1049) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 187 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1050) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 188-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1051) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 189 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1052) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 190 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1053) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 191 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1054) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 192 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1055) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 193 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1056) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 194 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1057) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 195 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1061) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 196 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1062) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 197 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1063) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 198 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1064) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 199 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1065) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 200-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1066) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 201-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1067) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-202-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1071) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-203-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1072) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 204 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1073) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 205 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1074) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-206-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1075) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 207-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1076) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 208 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1077) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 209 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1081) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 210 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1082) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 211 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1083) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-212 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1084) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-213 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1085) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-214-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1086) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-215 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1087) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-216 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1101) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 217 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1102) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 218 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1103) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-219 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1104) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 220-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1105) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-221 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1106) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 222 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1107) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 223 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1111) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 224 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1112) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 225 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1113) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 226 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1114) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 227 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1115) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-228-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1116) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 229-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
106 274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1117) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-230-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
13 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1301) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 231 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
13 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1302) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 232 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
13 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1303) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 233 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
13 275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1304) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 234-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
15 069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1501) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 235 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
15 069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1502) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 236 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
15 069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1503) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 237 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
15 069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1504) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-238 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
15 069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1505) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 239-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
15 069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1506) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-240 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2001) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-241 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2002) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 242 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
215 054 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2011) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 243 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
215 054 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2012) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 244 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
215 054 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2013) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-245-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 846 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2014) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 246 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 846 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2015) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 247-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 846 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2016) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-248-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2017) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-249 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2018) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 250-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2019) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 251 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2020) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 252-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2021) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 253-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2022) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-254-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2023) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 255 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2024) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 256 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2025) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 257 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2031) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 258-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2032) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-259 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2033) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 260 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2034) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-261 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
217 836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2035) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-262-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2051) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-263 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2052) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-264 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2053) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 265 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2054) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 266-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2055) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 267 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2056) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 268 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2057) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 269 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2058) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-270 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2059) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 271 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2060) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-272-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2061) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 273 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2062) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-275 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2072) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 276 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2073) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 277-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2074) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 278 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2075) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 279-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2076) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-280 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2077) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 281 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2078) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-282-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2079) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-283 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2080) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 284 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION

216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2081) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 285 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2082) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 286 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2121) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 287 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2122) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 288 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2123) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 289 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2124) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 290 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2125) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 291 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2131) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 292 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2132) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 293 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2133) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-294-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2134) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 295 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2135) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 296-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2141) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-297-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2142) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 298 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2143) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 299 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2144) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 300-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2145) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-301-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2146) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 302 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2151) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-303 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2152) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 304-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2153) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 305-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2154) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-306 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2155) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 307 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
216 191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2156) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 308 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
24 665 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2401) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-309-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
24 665 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2402) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 310 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
24 665 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2403) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-311-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3021) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 312 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3022) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-313-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3023) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 314 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3024) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 315 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3025) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 316-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3026) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 317 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION

350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3027) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 318 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3028) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 319 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3029) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 320 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3030) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 321 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3031) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-322 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3032) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-323 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3033) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 324 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3034) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 325 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3035) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-326 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3036) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 327 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3037) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 328-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3038) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 329 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3039) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 330 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3040) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 332 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3042) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 333-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3043) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-334-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3044) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 335 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3045) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 336 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3046) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 337 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3047) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 338 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3048) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 339 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3049) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-340-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3050) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-341 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3052) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-342-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3053) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-343 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3054) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-344-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3055) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-345 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3056) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 346 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3057) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 347 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3058) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-348 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3059) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-349-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3060) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-350-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3061) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 351 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3062) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 352 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3063) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 353 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3064) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 354 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3065) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 355 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3066) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 356 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3067) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 357 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3068) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 358 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3069) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 359-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3070) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 360 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3071) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-361 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3072) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 362-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3073) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 363 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3074) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-364 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3075) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 365 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3076) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 366 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3077) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 367 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3078) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 368 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3079) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-369 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3080) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-370-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3086) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-371 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3087) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 372-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3088) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 373 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3089) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 374-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3090) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 375-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3096) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 376 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3097) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 377 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3098) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 378 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3099) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 379 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3100) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 380 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3106) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-381-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3107) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 382-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3108) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 383 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3109) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 384-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3110) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-385 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3116) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-386-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3117) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-387-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3118) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 388 2 **EXPIRATION DATE:** 04/30/2013

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3119) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 389-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3120) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-390 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3126) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-391 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3127) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 392 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3128) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 393 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3129) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 394 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3130) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 395 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3136) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-396-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3137) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 397 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3138) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 398-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3139) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 399 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3140) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-400 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3146) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 401 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3147) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 402 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3148) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 403 2

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3149) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-404 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3150) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-405 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3156) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-406-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3157) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-407 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3158) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 408 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3159) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-409 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
350 450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3160) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-410-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
5 048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5001) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-411 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
5 048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5002) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-412-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
5 048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5003) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-413 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
5 048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5004) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-414 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
5 048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5005) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-415 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
5 048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5006) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-416-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
5 048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5007) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 417 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
5 048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5008) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-418 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
5 048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5009) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 419 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
5 048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5010) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-420-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
5 048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5011) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-421 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
5 048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5012) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-422 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
625 878 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 6004) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-423 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7001) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-424 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7002) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 425 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7003) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-426 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7005) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-427 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7006) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-428-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7007) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-429 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7008) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-430-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7009) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-431 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7010) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-432-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7011) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-433 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7012) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-434-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7013) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-435 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7014) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-436-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7015) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-437 2 **EXPIRATION DATE:** 04/30/2013

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7016) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-438 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7041) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-439 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7042) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-440-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7043) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-441-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7044) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-442 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7051) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 443 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7052) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-444 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7053) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-445 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
703 546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7054) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine the maximum temperature of each batch of wine placed stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 446 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
10 040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK A164) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-447-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
1 948 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK C1) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine, the pressure vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-448-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
1 948 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK C2) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine the maximum temperature of each batch of wine placed, stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-449 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
1 948 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK C3) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 Except when used for fermentation of wine the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings [District Rule 4694] Federally Enforceable Through Title V Permit

2 Except when used for fermentation of wine, the pressure vacuum relief valve shall be installed and operated in accordance with the manufacturer s instructions [District Rule 4694] Federally Enforceable Through Title V Permit

3 Except when used for fermentation of wine the pressure-vacuum relief valve and wine storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rule 4694] Federally Enforceable Through Title V Permit

4 The temperature of each batch of wine placed, stored or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation [District Rule 4694] Federally Enforceable Through Title V Permit

5 Except when used for fermentation of wine, the maximum temperature of each batch of wine placed stored or held in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

6 Except when used for fermentation of wine records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred [District Rule 4694] Federally Enforceable Through Title V Permit

7 Except when used for fermentation of wine the wine batch identifier and volume processed or stored in the tank shall be recorded weekly [District Rule 4694] Federally Enforceable Through Title V Permit

8 The following information shall be recorded for each fermentation batch processed in this tank 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694) [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-452-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
94 5 BHP CATERPILLAR MODEL C4 4 (2442/1800) TIER 2 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1 Particulate matter emissions shall not exceed 0 1 grains/dscf in concentration [District Rule 4201] Federally Enforceable Through Title V Permit

2 The exhaust stack shall vent vertically upward The vertical exhaust flow shall not be impeded by a rain cap, roof overhang, or any other obstruction [District Rule 4102]

3 Only CARB certified diesel fuel containing not more than 0 0015% sulfur by weight is to be used [District Rules 2201 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit

4 This engine shall be equipped with an operational non resettable elapsed time meter or other APCO approved alternative [District Rule 4702 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

5 This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

6 An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee [District Rule 4702] Federally Enforceable Through Title V Permit

7 Emissions from this IC engine shall not exceed any of the following limits 4 95 g-NOx/bhp hr, 0 60 g CO/bhp-hr, or 0 35 g VOC/bhp-hr [District Rule 2201 13 CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit

8 Emissions from this IC engine shall not exceed 0 15 g PM10/bhp hr based on USEPA certification using ISO 8178 test procedure [District Rules 2201 & 4102 and 13 CCR 2423 & 17 CCR 93115] Federally Enforceable Through Title V Permit

9 During periods of operation for maintenance, testing, and required regulatory purposes the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example check engine fluid levels, battery cables and connections change engine oil and filters, replace engine coolant and/or other operational characteristics as recommended by the manufacturer or supplier) [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

10 This engine shall be operated only for maintenance, testing required regulatory purposes, and during emergency situations Operation of the engine for maintenance testing, and required regulatory purposes shall not exceed 50 hours per calendar year [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11 The permittee shall maintain monthly records of emergency and non emergency operation Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example load testing, weekly testing, rolling blackout general area power outage etc) and records of operational characteristics monitoring For units with automated testing systems, the operator may as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

12 The engine's oil and filter shall be changed every 1,000 hours of operation or every 12 months whichever comes first [40 CFR 63 6603/66 6640 Table 2d, Row 1 a] Federally Enforceable Through Title V Permit

13 The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary [40 CFR 63 6603/63 6640 Table 2d Row 1 b] Federally Enforceable Through Title V Permit

14 The engine s hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first and replaced as necessary [40 CFR 63 6603/63 6640 Table 2d, Row 1 c] Federally Enforceable Through Title V Permit

15 The permittee shall keep records of the maintenance conducted on the engine [40 CFR 63 6655(e)] Federally Enforceable Through Title V Permit

16 All records shall be maintained and retained on site for a minimum of five (5) years, and shall be made available for District inspection upon request [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

17 This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program or for an interruptible power contract [District Rule 4702] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665-496 1

EXPIRATION DATE: 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
WINERY WASTEWATER TREATMENT OPERATION

PERMIT UNIT REQUIREMENTS

1 {98} No air contaminant shall be released into the atmosphere which causes a public nuisance [District Rule 4102]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-497 3 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
14 218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1410) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 This tank shall be equipped with and operated with a pressure vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694 5 2 1] Federally Enforceable Through Title V Permit

2 The pressure vacuum relief valve and storage tank shall remain in a gas tight condition, except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694, 5 2 1] Federally Enforceable Through Title V Permit

3 The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved [District Rules 2201 and 4694 5 2 2] Federally Enforceable Through Title V Permit

4 The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit

5 The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit

6 The maximum wine storage throughput in this tank calculated on a twelve month rolling basis, shall not exceed 425 000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit

7 Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred shall be maintained [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

8 The operator shall record on a daily basis total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

9 The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit

10 All records shall be retained on site for a period of at least five years and made available for District inspection upon request [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 498-3 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
14 218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1411) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694 5 2 1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694 5 2 1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved [District Rules 2201 and 4694 5 2 2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15 000 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 425 000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred shall be maintained [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record on a daily basis total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on site for a period of at least five years and made available for District inspection upon request [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-499 3 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
14 218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1412) WITH A PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure vacuum relief valve which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694 5 2 1] Federally Enforceable Through Title V Permit
2. The pressure vacuum relief valve and storage tank shall remain in a gas tight condition, except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694 5 2 1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved [District Rules 2201 and 4694, 5 2 2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15 000 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank calculated on a twelve month rolling basis shall not exceed 425 000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch the volume percent ethanol in the batch, and the volume of wine transferred shall be maintained [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record on a daily basis total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request [District Rules 1070 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 500 3 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
14 218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1413) WITH A PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 This tank shall be equipped with and operated with a pressure vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank operate in accordance with the manufacturer's instructions and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694, 5 2 1] Federally Enforceable Through Title V Permit

2 The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694, 5 2 1] Federally Enforceable Through Title V Permit

3 The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved [District Rules 2201 and 4694, 5 2 2] Federally Enforceable Through Title V Permit

4 The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit

5 The maximum wine storage throughput in this tank shall not exceed 15 000 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit

6 The maximum wine storage throughput in this tank calculated on a twelve month rolling basis shall not exceed 425 000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit

7 Daily throughput records including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred shall be maintained [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

8 The operator shall record on a daily basis, total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

9 The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit

10 All records shall be retained on-site for a period of at least five years and made available for District inspection upon request [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 501 3 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
14 218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1414) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank operate in accordance with the manufacturer s instructions and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694 5 2 1] Federally Enforceable Through Title V Permit

2 The pressure vacuum relief valve and storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694, 5 2 1] Federally Enforceable Through Title V Permit

3 The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved [District Rules 2201 and 4694, 5 2 2] Federally Enforceable Through Title V Permit

4 The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit

5 The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit

6 The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 425 000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit

7 Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred shall be maintained [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

8 The operator shall record on a daily basis total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

9 The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit

10 All records shall be retained on site for a period of at least five years and made available for District inspection upon request [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 502 3 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
14 218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1415) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure vacuum relief valve which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694, 5 2 1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694 5 2 1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved [District Rules 2201 and 4694 5 2 2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15 000 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank calculated on a twelve month rolling basis shall not exceed 425 000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch the volume percent ethanol in the batch, and the volume of wine transferred shall be maintained [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record on a daily basis, total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request [District Rules 1070 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 503 3 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
14 218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1416) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694 5 2 1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694, 5 2 1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved [District Rules 2201 and 4694 5 2 2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank calculated on a twelve month rolling basis shall not exceed 425 000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred, shall be maintained [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record on a daily basis total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request [District Rules 1070 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 504-3 **EXPIRATION DATE:** 04/30/2013

EQUIPMENT DESCRIPTION
14 218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1417) WITH A PRESSURE/VACUUM VALVE

DRAFT

PERMIT UNIT REQUIREMENTS

1 This tank shall be equipped with and operated with a pressure-vacuum relief valve which shall operate within 10% of the maximum allowable working pressure of the tank operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694 5 2 1] Federally Enforceable Through Title V Permit

2 The pressure vacuum relief valve and storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694 5 2 1] Federally Enforceable Through Title V Permit

3 The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved [District Rules 2201 and 4694 5 2 2] Federally Enforceable Through Title V Permit

4 The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit

5 The maximum wine storage throughput in this tank shall not exceed 15 000 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit

6 The maximum wine storage throughput in this tank calculated on a twelve month rolling basis shall not exceed 425 000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit

7 Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

8 The operator shall record on a daily basis total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

9 The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit

10 All records shall be retained on site for a period of at least five years and made available for District inspection upon request [District Rules 1070 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-505 3 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
14 218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1418) WITH A PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1 This tank shall be equipped with and operated with a pressure vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694 5 2 1] Federally Enforceable Through Title V Permit

2 The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694 5 2 1] Federally Enforceable Through Title V Permit

3 The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved [District Rules 2201 and 4694 5 2 2] Federally Enforceable Through Title V Permit

4 The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit

5 The maximum wine storage throughput in this tank shall not exceed 15 000 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit

6 The maximum wine storage throughput in this tank calculated on a twelve month rolling basis shall not exceed 425 000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit

7 Daily throughput records including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred, shall be maintained [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

8 The operator shall record on a daily basis total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

9 The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit

10 All records shall be retained on-site for a period of at least five years and made available for District inspection upon request [District Rules 1070 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 506 3 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
14 218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1419) WITH A PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve which shall operate within 10% of the maximum allowable working pressure of the tank operate in accordance with the manufacturer's instructions and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694, 5 2 1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694 5 2 1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved [District Rules 2201 and 4694 5 2 2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 425 000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record on a daily basis total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N-1665 507 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
150 BHP CUMMINS MODEL CFP5E F50 TIER 3 CERTIFIED DIESEL FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

PERMIT UNIT REQUIREMENTS

1 Particulate matter emissions shall not exceed 0 1 grains/dscf in concentration [District Rule 4201] Federally Enforceable Through Title V Permit

2 {1898} The exhaust stack shall vent vertically upward The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang or any other obstruction [District Rule 4102]

3 Only CARB certified diesel fuel containing not more than 0 0015% sulfur by weight is to be used [District Rules 2201 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit

4 This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

5 This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier [District Rule 4702 and 40 CFR 63 Subpart ZZZZ]

6 An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee [District Rule 4702] Federally Enforceable Through Title V Permit

7 Emissions from this IC engine shall not exceed any of the following limits 2 54 g-NOx/bhp hr, 0 69 g CO/bhp-hr, or 0 06 g VOC/bhp hr [District Rule 2201 and 13 CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit

8 Emissions from this IC engine shall not exceed 0 088 g PM10/bhp hr based on USEPA certification using ISO 8178 test procedure [District Rules 2201 and 4102 and 13 CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit

9 During periods of operation for maintenance testing and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example check engine fluid levels battery cables and connections change engine oil and filters replace engine coolant and/or other operational characteristics as recommended by the manufacturer or supplier) [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

10 This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing and Maintenance of Water-Based Fire Protection Systems", 1998 edition Total hours of operation for all maintenance testing and required regulatory purposes shall not exceed 100 hours per calendar year [District Rule 4702 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11 The permittee shall maintain monthly records of emergency and non emergency operation Records shall include the number of hours of emergency operation the date and number of hours of all testing and maintenance operations and the purpose of the operation (for example load testing weekly testing rolling blackout general area power outage etc) For units with automated testing systems the operator may as an alternative to keeping records of actual operation for testing purposes maintain a readily accessible written record of the automated testing schedule [District Rule 4702 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

12 The engine's oil and filter shall be changed every 1,000 hours of operation or every 12 months whichever comes first [40 CFR 63 6603/66 6640 Table 2d Row 1 a] Federally Enforceable Through Title V Permit

13 The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary [40 CFR 63 6603/63 6640 Table 2d Row 1 b] Federally Enforceable Through Title V Permit

14 The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary [40 CFR 63 6603/63 6640 Table 2d Row 1 c] Federally Enforceable Through Title V Permit

15 The permittee shall keep records of the maintenance conducted on the engine [40 CFR 63 6655(e)] Federally Enforceable Through Title V Permit

16 All records shall be maintained and retained on site for a minimum of five (5) years, and shall be made available for District inspection upon request [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 508 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
23 609 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B231) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank operate in accordance with the manufacturer's instructions and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure vacuum relief valve and storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75°F The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine, the operator shall achieve the storage temperature of 75°F or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75°F or less was achieved [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine throughput in this tank shall not exceed 23,609 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine throughput in this tank calculated on a 12 month rolling basis, shall not exceed 232 000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred shall be maintained [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on site for a period of at least five years and made available for District inspection upon request [District Rules 1070 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 509 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
23 609 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B232) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure vacuum relief valve and storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75°F The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine, the operator shall achieve the storage temperature of 75°F or less within 60 days after completing fermentation and shall maintain records to show when the required storage temperature of 75°F or less was achieved [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine throughput in this tank shall not exceed 23 609 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine throughput in this tank, calculated on a 12 month rolling basis, shall not exceed 232 000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred, shall be maintained [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
8. The operator shall record on a daily basis, total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on site for a period of at least five years and made available for District inspection upon request [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 510 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
14 376 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B141) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75°F The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine, the operator shall achieve the storage temperature of 75°F or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75°F or less was achieved [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine throughput in this tank shall not exceed 14 376 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine throughput in this tank calculated on a 12 month rolling basis shall not exceed 232 000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred, shall be maintained [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
8. The operator shall record on a daily basis total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on site for a period of at least five years and made available for District inspection upon request [District Rules 1070 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-511-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
14 376 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B142) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1 This tank shall be equipped with and operated with a pressure vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank operate in accordance with the manufacturer's instructions and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

2 The pressure vacuum relief valve and storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

3 The temperature of the wine stored in this tank shall be maintained at or below 75°F The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine the operator shall achieve the storage temperature of 75°F or less within 60 days after completing fermentation and shall maintain records to show when the required storage temperature of 75°F or less was achieved [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

4 The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit

5 The maximum wine throughput in this tank shall not exceed 14,376 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit

6 The maximum wine throughput in this tank calculated on a 12 month rolling basis shall not exceed 232,000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit

7 Daily throughput records including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

8 The operator shall record on a daily basis total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

9 The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit

10 All records shall be retained on site for a period of at least five years and made available for District inspection upon request [District Rules 1070 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665-512 2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 290 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B71) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve which shall operate within 10% of the maximum allowable working pressure of the tank operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75°F The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine, the operator shall achieve the storage temperature of 75°F or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75°F or less was achieved [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine throughput in this tank shall not exceed 7,290 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine throughput in this tank calculated on a 12 month rolling basis shall not exceed 232 000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch the volume percent ethanol in the batch, and the volume of wine transferred shall be maintained [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
8. The operator shall record on a daily basis total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT N 1665 513-2 **EXPIRATION DATE:** 04/30/2013

DRAFT

EQUIPMENT DESCRIPTION
7 290 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B72) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve which shall operate within 10% of the maximum allowable working pressure of the tank operate in accordance with the manufacturer's instructions and be permanently labeled with the operating pressure settings [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas tight condition except when the operating pressure of the tank exceeds the valve set pressure A gas tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21 [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75°F The temperature of the stored wine shall be determined and recorded at least once per week For each batch of wine, the operator shall achieve the storage temperature of 75°F or less within 60 days after completing fermentation and shall maintain records to show when the required storage temperature of 75°F or less was achieved [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14 0 percent by volume [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine throughput in this tank shall not exceed 7 290 gallons per day [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine throughput in this tank calculated on a 12 month rolling basis shall not exceed 232,000 gallons per year [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records including records of filling and emptying operations the dates of such operations a unique identifier for each batch the volume percent ethanol in the batch and the volume of wine transferred shall be maintained [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
8. The operator shall record on a daily basis total gallons of wine contained in the tank [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period calculated monthly) [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request [District Rules 1070 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

ATTACHMENT B

Expiring Title V Operating Permits