



AUG 28 2012

James Foster  
Golden State Vintners/Franzia-McFarland  
PO Box 90  
Tracy, CA 95378

**Re: Notice of Preliminary Decision - Federally Mandated Operating Permit  
District Facility # S-882  
Project # S-1110989**

Dear Mr. Foster:

Enclosed for your review and comment is the District's analysis of Golden State Vintners/Franzia-McFarland's application for the Federally Mandated Operating Permit for its wine and brandy production facility, 31795 Whisler Rd, McFarland, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,



David Warner  
Director of Permit Services

cc: Juscelino Siongco, Permit Services Engineer

Attachments

**Seyed Sadredin**  
Executive Director/Air Pollution Control Officer

---

**Northern Region**  
4800 Enterprise Way  
Modesto, CA 95356-8718  
Tel: (209) 557-6400 FAX: (209) 557-6475

**Central Region (Main Office)**  
1990 E. Gettysburg Avenue  
Fresno, CA 93726-0244  
Tel: (559) 230-6000 FAX: (559) 230-6061

**Southern Region**  
34946 Flyover Court  
Bakersfield, CA 93308-9725  
Tel: 661-392-5500 FAX: 661-392-5585



AUG 28 2012

Gerardo C. Rios, Chief  
Permits Office (AIR-3)  
U.S. EPA - Region IX  
75 Hawthorne St  
San Francisco, CA 94105

**Re: Notice of Preliminary Decision - Federally Mandated Operating Permit  
District Facility # S-882  
Project # S-1110989**

Dear Mr. Rios:

Enclosed for your review and comment is the District's analysis of Golden State Vintners/Franzia-McFarland's application for the Federally Mandated Operating Permit for its wine and brandy production facility, 31795 Whisler Rd, McFarland, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 45-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,



David Warner  
Director of Permit Services

cc: Juscelino Siongco, Permit Services Engineer

Attachments

**Syed Sadredin**  
Executive Director/Air Pollution Control Officer

---

**Northern Region**  
4800 Enterprise Way  
Modesto, CA 95356-8718  
Tel: (209) 557-6400 FAX: (209) 557-6475

**Central Region (Main Office)**  
1990 E. Gettysburg Avenue  
Fresno, CA 93726-0244  
Tel: (559) 230-6000 FAX: (559) 230-6061

**Southern Region**  
34946 Flyover Court  
Bakersfield, CA 93308-9725  
Tel: 661-392-5500 FAX: 661-392-5585



AUG 28 2012

Mike Tollstrup, Chief  
Project Assessment Branch  
Air Resources Board  
P O Box 2815  
Sacramento, CA 95812-2815

**Re: Notice of Preliminary Decision - Federally Mandated Operating Permit  
District Facility # S-882  
Project # S-1110989**

Dear Mr. Tollstrup:

Enclosed for your review and comment is the District's analysis of Golden State Vintners/Franzia-McFarland's application for the Federally Mandated Operating Permit for its wine and brandy production facility, 31795 Whisler Rd, McFarland, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,

David Warner  
Director of Permit Services

cc: Juscelino Siongco, Permit Services Engineer

Attachments

**Seyed Sadredin**  
Executive Director/Air Pollution Control Officer

---

**Northern Region**  
4800 Enterprise Way  
Modesto, CA 95356-8718  
Tel: (209) 557-6400 FAX: (209) 557-6475

**Central Region (Main Office)**  
1990 E. Gettysburg Avenue  
Fresno, CA 93726-0244  
Tel: (559) 230-6000 FAX: (559) 230-6061

**Southern Region**  
34946 Flyover Court  
Bakersfield, CA 93308-9725  
Tel: 661-392-5500 FAX: 661-392-5585

**NOTICE OF PRELIMINARY DECISION  
FOR THE PROPOSED ISSUANCE OF  
FEDERALLY MANDATED OPERATING PERMITS**

NOTICE IS HEREBY GIVEN that the San Joaquin Valley Air Pollution Control District solicits public comment on the proposed issuance of the Federally Mandated Operating permits to Golden State Vintners/Franzia-McFarland for its wine and brandy production facility, 31795 Whisler Rd, McFarland, California.

The District's analysis of the legal and factual basis for this proposed action, project #S-1110989, is available for public inspection at [http://www.valleyair.org/notices/public\\_notices\\_idx.htm](http://www.valleyair.org/notices/public_notices_idx.htm) and the District office at the address below. There are no emission changes associated with this proposed action. This will be the public's only opportunity to comment on the specific conditions of the proposed Federally Mandated Operating initial permits. If requested by the public, the District will hold a public hearing regarding issuance of this initial permit. For additional information, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900. Written comments on the proposed initial permit must be submitted within 30 days of the publication date of this notice to DAVID WARNER, DIRECTOR OF PERMIT SERVICES, SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT, 1990 E. GETTYSBURG AVE, FRESNO, CALIFORNIA 93726-0244.

**SAN JOAQUIN VALLEY  
UNIFIED AIR POLLUTION CONTROL DISTRICT**

**GOLDEN STATE VINTNERS/FRANZIA-MCFARLAND**

**PROPOSED ENGINEERING EVALUATION**

**TABLE OF CONTENTS**

<b>Section .....</b>	<b>Page</b>
<b>I. PROPOSAL .....</b>	<b>1</b>
<b>II. FACILITY LOCATION .....</b>	<b>1</b>
<b>III. EQUIPMENT LISTING .....</b>	<b>1</b>
<b>IV. GENERAL PERMIT TEMPLATE USAGE .....</b>	<b>1</b>
<b>V. SCOPE OF EPA AND PUBLIC REVIEW .....</b>	<b>2</b>
<b>VI. APPLICABLE REQUIREMENTS ADDRESSED BY GENERAL PERMIT TEMPLATES.....</b>	<b>2</b>
<b>VIII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE .....</b>	<b>4</b>
<b>IX. COMPLIANCE .....</b>	<b>5</b>
<b>X. PERMIT SHIELD .....</b>	<b>19</b>
<b>XI. PERMIT CONDITIONS.....</b>	<b>20</b>

**ATTACHMENT A – DETAILED FACILITY PRINTOUT  
ATTACHMENT B – EXEMPT EQUIPMENT  
ATTACHMENT C – SJVUAPCD PERMITS**

# TITLE V APPLICATION REVIEW

Project #: S-1110989  
Deemed Complete: April 15, 2011

Engineer: Juscelino Siongco  
Date: August 23, 2012

Facility Number: S-882  
Facility Name: Golden State Vintners/Franzia-McFarland  
Mailing Address: PO Box 90  
Tracy, CA 95378

Contact Name: James Foster  
Phone: (661) 792-2100

Responsible Official: James Foster  
Title: Plant Manager/Senior Winemaker

## I. PROPOSAL

Golden State Vintners/Franzia-McFarland is proposing that an initial Title V permit be issued for its winery at 31795 Whisler Rd, McFarland in Kern County, CA. The purpose of this evaluation is to identify all applicable requirements, determine if the facility will comply with those applicable requirements, and to provide the legal and factual basis for proposed permit conditions.

## II. FACILITY LOCATION

Golden State Vintners/Franzia-McFarland is located at 31795 Whisler Rd, McFarland in Kern County, CA.

## III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is shown in Attachment A.

A summary of the exempt equipment categories which describe the insignificant activities or equipment at the facility not requiring a permit is shown in Attachment B. This equipment is not exempt from facility-wide requirements.

## IV. GENERAL PERMIT TEMPLATE USAGE

The applicant is requesting to use the following model general permit templates:

a. SJV-UM-0-3, Facility-wide Umbrella General Permit Template

The applicant has requested to utilize template #SJV-UM-03, Facility-wide Umbrella General Permit Template for unit S-882-0-1. Based on the information submitted on the Template Qualification Form, the applicant qualifies for the use of this template.

## V. SCOPE OF EPA AND PUBLIC REVIEW

Certain segments of the proposed Operating Permit are based on model general permit templates that have been previously subject to EPA and public review. The terms and conditions from the model general permit templates are included in the proposed permit and are not subject to further EPA and public review.

For permit applications utilizing model general permit templates, public and agency comments on the District's proposed actions are limited to the applicant's eligibility for model general permit template, applicable requirements not covered by the model general permit template, and the applicable procedural requirements for issuance of Title V Operating Permits.

The following permit conditions, including their underlying applicable requirements, originate from model general permit templates and are not subject to further EPA or public review.

Conditions 1 through 40 of the requirements for facility-wide permit S-882-0-1.

## VI. REQUIREMENTS ADDRESSED BY GENERAL PERMIT TEMPLATES

District Rule 1100, Equipment Breakdown (amended December 17, 1992) (Non-SIP replacement for Fresno County Rule 110)

District Rule 1160, Emission Statements (adopted November 18, 1992)

District Rule 2010, Permits Required (amended December 17, 1992)

District Rule 2020, Exemptions (amended August 18, 2011)<sup>1</sup>

District Rule 2031, Transfer of Permits (amended December 17, 1992)

District Rule 2040, Applications (amended December 17, 1992)

District Rule 2070, Standards for Granting Applications (amended December 17, 1992)

District Rule 2080, Conditional Approval (amended December 17, 1992)

---

<sup>1</sup> The amendments made to this rule on August 18, 2011 have no impact to this source; therefore template SJV-UM-0-3 is still valid for this project.

District Rule 2520, Sections 5.2, 9.1.1, 9.4, 9.5, 9.7, 9.8, 9.9, 9.13.1, 9.13.2, 9.16 and 10.0, Federally Mandated Operating Permits (amended June 21, 2001)

District Rule 4101, Visible Emissions (amended February 17, 2005)

District Rule 4601, Architectural Coatings (amended December 17, 2009)

District Rule 8011, General Requirements (amended August 19, 2004)

District Rule 8021, Construction, Demolition, Excavation, and Other Earthmoving Activities (amended August 19, 2004)

District Rule 8031, Bulk Materials (amended August 19, 2004)

District Rule 8041, Carryout and Trackout (amended August 19, 2004)

District Rule 8051, Open Areas (amended August 19, 2004)

District Rule 8061, Paved and Unpaved Roads (amended August 19, 2004)

District Rule 8071, Unpaved Vehicle/Equipment Traffic Areas (amended September 16, 2004)

40 CFR Part 82, Subpart B and F, Stratospheric Ozone

40 CFR Part 61, Subpart M, National Emission Standard for Asbestos

## **VII. REQUIREMENTS NOT ADDRESSED BY GENERAL PERMIT TEMPLATES**

District Rule 1081, Source Sampling (amended December 16, 1993)

District Rule 2201, New and Modified Stationary Source Review Rule (amended April 21, 2011)

District Rule 2520, Federally Mandate Operating Permits (amended June 21, 2001)

District Rule 4201, Particulate Matter Concentration (amended December 17, 1992)

District Rule 4305, Boilers, Steam Generators, and Process Heaters – Phase 2 (amended August 21, 2003)

District Rule 4306, Boilers, Steam Generators, and Process Heaters – Phase 3 (amended October 16, 2008)

District Rule 4320, Advanced Emission Reduction Option for Boilers, Steam Generators, and Process Heaters Greater than 5.0 MMBtu/hr (adopted October 16, 2008)

District Rule 4621, Gasoline Transfer into Stationary Storage Containers, Delivery Vessels, and Bulk Plants (amended December 20, 2007)

District Rule 4694, Wine Fermentation and Storage Tanks (adopted December 15, 2005)

40 CFR Part 60, Subpart Dc, Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units

40 CFR Part 64, Compliance Assurance Monitoring (CAM)

## **VIII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE**

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as Federally Enforceable through Title V Permit.

This facility is subject to the following rules that are not currently federally enforceable:

### **District Rule 4102 – Nuisance**

This rule prevents the discharge from any source whatsoever such quantities of air contaminants or other materials which cause injury, detriment, nuisance or annoyance to any considerable number of persons or to the public or which endanger the comfort, repose, health or safety of any such person or the public or which cause or have a natural tendency to cause injury or damage to business or property.

#### **a. S-882-0-1 – Facility-Wide Requirements**

- Condition 41 on the proposed permit complies with this rule.

### **District Rule 4694 – Wine Fermentation and Storage Tanks**

The purpose of this rule is to reduce emissions of volatile organic compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources. The rule is applicable to any facility with VOC emissions in excess of 10 tons per year. For those facilities to which the rule applies, the requirements of the rule are applicable to any fermentation or storage tank with capacity in excess of 5,000 gallons. The rule was adopted on December 15, 2005 and submitted to EPA for approval into the State Implementation Plan (SIP).

On August 18, 2011, the District approved an amended SIP submittal which excludes the fermentation provisions of the rule while maintaining the storage provisions. Therefore, the fermentation provisions are not federally enforceable. All other provisions are federally enforceable and will be discussed in Section IX of this application review under District Rule 4694.

a. S-882-0-1 – Facility-Wide Requirements

- Conditions 42 through 46 on the proposed permit are based on the wine fermentation provisions of District Rule 4694 and therefore, are not federally enforceable.

b. S-882-11-1, -12-1, -13-1, -14-1, -15-1, -16-1, -17-1, -18-1, -19-1, -20-1, -21-1, -22-1, -23-1, -24-1, -25-1, -26-1, -27-1, -28-1, -29-1, -30-1, -31-1, -32-1, -33-1, -34-1, -35-1, -36-1, -37-1, -38-1, -39-1, -40-1, -41-1, -42-1, -43-1, -44-1, -45-1, -46-1, -47-1, -48-1, -49-1, -50-1, -51-1, -83-1, -84-1, -85-1, -86-1, – Steel Red and White Wine Fermentation and Wine Storage Tanks

- Condition 8 on the proposed permits is based on the fermentation provisions of the rule and is not federally enforceable.

## **IX. COMPLIANCE**

### **A. Requirements Addressed by Model General Permit Templates**

#### **1. Facility Wide Requirements**

The applicant is proposing to use a general permit template to address federally applicable facility-wide requirements. Section IV of template SJV-UM-0-3 includes a demonstration of compliance for all applicable requirements. Template conditions have been added to the facility wide requirements as condition numbers 1 through 40 to assure compliance with these requirements.

### **B. Requirements Not Addressed by Model General Permit Templates**

#### **1. District Rule 1081 – Source Sampling**

The permit units are subject to the District Rule 2201 upon application for Authority to Construct (ATC). In accordance with the White Paper for Streamlined Development of Part 70 Permit Applications, dated July 10, 1995, conditions from the resulting Permit to Operate (PTO) were addressed to define how NSR permit terms should be incorporated into the Title V permit.

a. S-882-1-6: 29.3 MMBtu/hr Sellers Engineering Model 105-E Natural Gas-Fired Boiler with a Low NO<sub>x</sub> Burner

- Conditions 14 and 19 in the proposed permit comply with this rule.

- b. S-882-2-6: 30 MMBtu/hr Sellers Engineering Natural Gas-Fired Boiler, Model 105-E, with a Low NO<sub>x</sub> Burner and an Induced Flue Gas Recirculation System (South Unit)
  - Conditions 14 and 19 in the proposed permit comply with this rule.

## **2. District Rule 2080 – Conditional Approval**

The purpose of this rule is to grant authority to the APCO to issue or revise specific written conditions on an Authority to Construct or a Permit to Operate to assure compliance with air contaminant emission standards or limitations.

- a. S-882-105-1: 2,538 Gallon Steel Wine Storage Tank
  - Condition 1 in the proposed permit complies with this rule.
- b. S-882-125-1: Winery Wastewater Collection Pump
  - Condition 1 in the proposed permit complies with this rule.
- c. S-882-126-1, -127-1, -128-1, -129-1, and -130-1: Ethanol Storage Tank
  - Condition 1 in the proposed permit complies with this rule.

## **3. District Rule 2201, New and Modified Stationary Source Review Rule**

The permit units are subject to the District Rule 2201 upon application for Authority to Construct (ATC). In accordance with the White Paper for Streamlined Development of Part 70 Permit Applications, dated July 10, 1995, conditions from the resulting Permit to Operate (PTO) were addressed to define how NSR permit terms should be incorporated into the Title V permit.

- a. S-882-0-1: Facility-Wide Requirements
  - Conditions 1 through 5 from the current PTO have been included as conditions 42 through 46 on the requirements for the proposed permit.
  - Condition 6 from the current PTO has been subsumed by condition 9 on the requirements for the proposed permit.

- b. S-882-1-6: 29.3 MMBtu/hr Sellers Engineering Model 105-E Natural Gas-Fired Boiler with a Low NO<sub>x</sub> Burner
- Condition 1 from the current PTO has been moved to the Facility-Wide permit as condition 41.
  - Condition 2 from the current PTO has been moved to the Facility-Wide permit as condition 22.
  - Conditions 3 through 21 from the current PTO have been included as conditions 1 through 19 on the requirements for the proposed permit.
  - Condition 22 from the current PTO has been included as condition 20 on the requirements for the proposed permit. The condition has been revised to daily fuel usage recordkeeping required by 40 CFR 60.48c(g).
  - Condition 23 from the current PTO has been included as condition 21 on the requirements for the proposed permit.
- c. S-882-2-6: 30 MMBtu/hr Sellers Engineering Natural Gas-Fired Boiler, Model 105-E, with a Low NO<sub>x</sub> Burner and an Induced Flue Gas Recirculation System (South Unit)
- Condition 1 from the current PTO has been moved to the Facility-Wide permit as condition 41.
  - Condition 2 from the current PTO has been moved to the Facility-Wide permit as condition 22.
  - Conditions 3 through 22 from the current PTO have been included as conditions 1 through 20 on the requirements for the proposed permit.
  - Condition 23 from the current PTO has been included as condition 22 on the requirements for the proposed permit.
- d. S-882-4-1: Gasoline Dispensing Operation with One 350 Gallon and One 500 Gallon Phase I and Phase II Exempt Aboveground Gasoline Storage Tanks Served by 2 Nozzles
- Condition 1 from the current PTO has been included as condition 1 on the requirements for the proposed permit.
- e. S-882-11-1, -12-1, -13-1, -14-1, -15-1, -16-1, -17-1, -18-1, -19-1, -20-1, -21-1, -22-1, -23-1, -24-1, -25-1, -26-1, -27-1, -28-1, -29-1, -30-1, -31-1, -32-1, -33-1, -34-1, -35-1, -36-1, -37-1, -38-1, -39-1, -40-1, -41-1, -42-1, -43-1, -44-1, -45-1, -46-1, -47-1, -48-1, -49-1, -50-1, -51-1, -83-1, -84-1, -85-1, and -86-1: Steel Red and White Wine Fermentation and Wine Storage Tanks

- Condition 1 from the current PTO has been moved to the Facility-Wide permit as condition 41.
  - Conditions 2 through 9 from the current PTO have been included as conditions 1 through 8 on the requirements for the proposed permit.
- f. S-882-52-1: Steel Wine Storage Tank
- Condition 1 from the current PTO has been moved to the Facility-Wide permit as condition 41.
  - Conditions 2 through 8 from the current PTO have been included as conditions 1 through 7 on the requirements for the proposed permit. Reference to use of fermentation of wine has been removed since it was erroneously included in the condition during the unit's initial permitting. Facility email dated 8/20/2007 did not include the unit for use as a fermenter.
  - Condition 9 from the current PTO has been deleted since the unit is not used as a fermenter per facility email dated 8/20/2007.
- g. S-882-53-1, -54-1, -55-1, -56-1, -57-1, -58-1, -59-1, -60-1, -61-1, -62-1, -63-1, -64-1, -65-1, -66-1, -67-1, -68-1, -69-1, -70-1, -71-1, -72-1, -73-1, -74-1, -75-1, -76-1, -77-1, -78-1, -79-1, -80-1, -81-1, -82-1, -87-1, -88-1, -89-1, -90-1, -91-1, -92-1, -93-1, -94-1, -95-1, -96-1, -97-1, -98-1, -99-1, -100-1, -101-1, -102-1, -103-1, -104-1, -106-1, -107-1, -108-1, -109-1, -110-1, -111-1, -112-1, -113-1, -114-1, -115-1, -116-1, -117-1, -118-1, -119-1, -120-1, -121-1, -122-1, -123-1, and -124-1: Steel Wine Storage Tank
- Condition 1 from the current PTO has been moved to the Facility-Wide permit as condition 41.
  - Conditions 2 through 8 from the current PTO have been included as conditions 1 through 7 on the requirements for the proposed permit.
- h. S-882-105-1: 2,538 Gallon Steel Wine Storage Tank
- Condition 1 from the current PTO has been moved to the Facility-Wide permit as condition 41.
- i. S-882-125-1: Winery Wastewater Collection Pump
- Condition 1 from the current PTO has been moved to the Facility-Wide permit as condition 41.

- j. S-882-126-1, -127-1, -128-1, -129-1, and -130-1: Ethanol Storage Tank
- Condition 1 from the current PTO has been moved to the Facility-Wide permit as condition 41.

#### **4. District Rule 2520, Federally Mandated Operating Permits**

The purpose of this rule is to provide for the following: an administrative mechanism for issuing operating permits for new and modified sources of air contaminants in accordance with requirements of 40 CFR Part 70; an administrative mechanism for issuing renewed operating permits for sources of air contaminants in accordance with requirements of 40 CFR Part 70; an administrative mechanism for revising, reopening, revoking, and terminating operating permits for sources of air contaminants in accordance with requirements of 40 CFR Part 70; an administrative mechanism for incorporating requirements authorized by preconstruction permits issued under District Rule 2201 (New and Modified Stationary Source Review) in a Part 70 permit as administrative amendments, provided that such permits meet procedural requirements substantially equivalent to the requirements of 40 CFR 70.7 and 70.8, and compliance requirements substantially equivalent to those contained in 40 CFR 70.6; and the applicable federal and local requirements to appear on a single permit.

##### Greenhouse Gas Requirements

There are no federally applicable Greenhouse Gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40CFR 71.2). Therefore, there will be no further discussion of GHG in this evaluation.

#### **5. District Rule 4201, Particulate Matter Concentration**

The purpose of this rule is to protect the ambient air quality by establishing a particulate matter emission standard. Section 3.1 requires emissions to be at or below 0.1 grains of particulate matter per dry standard cubic foot of exhaust gas.

##### Natural Gas-Fired Boilers

The following calculation shows that the boilers in this facility firing on natural gas emit less than 0.1 grains of particulate matter per dry standard cubic foot of exhaust gas.

Natural Gas-Fired:

$$\left(\frac{7.6 \text{ lb PM}}{10^6 \text{ ft}^3}\right)\left(\frac{1 \text{ MMBtu}}{8710 \text{ dscf}}\right)\left(\frac{1 \text{ scf}}{950 \text{ Btu}}\right)\left(\frac{7000 \text{ gr}}{1 \text{ lb}}\right) = 0.006 \frac{\text{grains}}{\text{dscf}}$$

Where:

$$7.6 \frac{\text{lb} \cdot \text{PM}}{10^6 \cdot \text{ft}^3} = \text{uncontrolled emission factor for natural gas fired boilers (AP42, Table 1.4 - 12)}$$

$$\frac{950 \text{ Btu}}{\text{scf}} = \text{the minimum expected higher heating value of natural gas (AP42, 1.4.1)}$$

$$\frac{8710 \text{ dscf}}{\text{MMBtu}} = \text{F factor, Fd, for natural gas (40CFR§60, App. A, Meth. 19, Table 19 - 1)}$$

$$\frac{7000 \text{ gr}}{1 \text{ lb}} = \text{conversion factor (AP42, Appendix A)}$$

- a. S-882-1-6: 29.3 MMBtu/hr Sellers Engineering Model 105-E Natural Gas-Fired Boiler with a Low NO<sub>x</sub> Burner
  - Condition 1 on the proposed permit complies with this rule.
- b. S-882-2-6: 30 MMBtu/hr Sellers Engineering Natural Gas-Fired Boiler, Model 105-E, with a Low NO<sub>x</sub> Burner and an Induced Flue Gas Recirculation System (South Unit)
  - Condition 1 on the proposed permit complies with this rule.

## 6. District Rule 4305, Boilers, Steam Generators and Process Heaters – Phase 2

The purpose of this rule is to limit emissions of oxides of nitrogen (NO<sub>x</sub>) and carbon monoxide (CO) from boilers, steam generators, and process heaters. This rule applies to any gaseous fuel or liquid fuel fired boiler, steam generator, or process heater with a rated heat input greater than 5 million Btu per hour.

Since emissions limits of District Rule 4306 and all other requirements are equivalent or more stringent than District Rule 4305 requirements, compliance with District Rule 4306 requirements as shown in the following section will satisfy requirements of District Rule 4305.

**7. District Rule 4306, Boilers, Steam Generators and Process Heaters – Phase 3**

The purpose of this rule is to limit emissions of oxides of nitrogen (NO<sub>x</sub>) and carbon monoxide (CO) from boilers, steam generators, and process heaters. This rule applies to any gaseous fuel or liquid fuel fired boiler, steam generator, or process heater with a rated heat input greater than 5 million Btu per hour.

§5.0 Requirements

§5.1 NO<sub>x</sub> and CO Emission Limits

§5.1.1 Except for units subject to Sections 5.2, NO<sub>x</sub> and carbon monoxide (CO) emissions shall not exceed the limits specified in Table 1.

Category	Operated on Gaseous Fuel		
	NO <sub>x</sub> Limit		CO Limit (ppmv)
	Standard option	Enhanced Option	
H. Units limited by Permit to Operate to an annual heat input of 9 billion Btu/year to 30 billion Btu/year	30 ppmv or 0.036 lb/MMBtu	No option	400

§5.4 Monitoring Provisions

§5.4.2 The operator of any unit subject to the applicable emission limits in Sections 5.1 shall install and maintain an operational APCO approved Continuous Emissions Monitoring System (CEMS) for NO<sub>x</sub>, CO, and oxygen, or implement an APCO-approved Alternate Monitoring System. An APCO approved CEMS shall comply with the requirements of 40 Code of Federal Regulations (CFR) Part 51, 40 CFR Parts 60.7 and 60.13 (except subsection h), 40 CFR Part 60 Appendix B (Performance Specifications) and 40 CFR Part 60 Appendix F (Quality Assurance Procedures, and applicable provisions of Rule 1080 (Stack Monitoring)). An APCO approved Alternate Monitoring System shall monitor one or more of the following:

- §5.4.2.1 periodic NO<sub>x</sub> and CO exhaust emission concentrations,
- §5.4.2.2 periodic exhaust oxygen concentration,
- §5.4.2.3 flow rate of reducing agent added to exhaust,
- §5.4.2.4 catalyst inlet and exhaust temperature,
- §5.4.2.5 catalyst inlet and exhaust oxygen concentration,
- §5.4.2.6 periodic flue gas recirculation rate,
- §5.4.2.7 other operational characteristics.

§5.4.3 For units subject to the requirements of Section 5.2.1 or 5.2.2, the operator shall monitor, at least on a monthly basis, the operational characteristics recommended by the manufacturer and approved by the APCO.

§5.4.4 The operator of any Category H unit listed in Section 5.1.1 Table 1 and any unit subject to Section 5.2.1 or 5.2.2 shall install and maintain an operational non-resettable, totalizing mass or volumetric flow meter in each fuel line to each unit. Volumetric flow measurements shall be periodically compensated for temperature and pressure. A master meter, which measures fuel to all units in a group of similar units, may satisfy these requirements if approved by the APCO in writing. The cumulative annual fuel usage may be verified from utility service meters, purchase or tank fill records, or other acceptable methods, as approved by the APCO.

#### §5.5 Compliance Determination

§5.5.1 The operator of any unit shall have the option of complying with either the applicable heat input (lb/MMBtu) emission limits or the concentration (ppmv) emission limits specified in Section 5.1. The emission limits selected to demonstrate compliance shall be specified in the source test proposal pursuant to Rule 1081 (Source Sampling).

§5.5.2 All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0.

§5.5.4 For emissions monitoring pursuant to Sections 5.4.2, 5.4.2.1, and 6.3.1 using a portable NO<sub>x</sub> analyzer as part of an APCO approved Alternate Emissions Monitoring System, emission readings shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15-consecutive-minute sample reading or by taking at least five (5) readings evenly spaced out over the 15-consecutive-minute period.

§5.5.5 For emissions source testing performed pursuant to Section 6.3.1 for the purpose of determining compliance with an applicable standard or numerical limitation of this rule, the arithmetic average of three (3) 30-consecutive-minute test runs shall apply. If two (2) of three (3) runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit.

## §6.2 Test Methods

The following test methods shall be used unless otherwise approved by the APCO and EPA.

§6.2.1 Fuel hhv shall be certified by third party fuel supplier or determined by:

§6.2.1.2 ASTM D 1826-88 or D 1945-81 in conjunction with ASTM D 3588-89 for gaseous fuels.

§6.2.2 Oxides of nitrogen (ppmv) - EPA Method 7E, or ARB Method 100.

§6.2.3 Carbon monoxide (ppmv) - EPA Method 10, or ARB Method 100.

§6.2.4 Stack gas oxygen - EPA Method 3 or 3A, or ARB Method 100.

§6.2.5 NO<sub>x</sub> Emission Rate (Heat Input Basis) - EPA Method 19.

§6.2.6 Stack gas velocities - EPA Method 2.

§6.2.7 Stack gas moisture content - EPA Method 4.

## §6.3 Compliance Testing

§6.3.1 Each unit subject to the requirements in Sections 5.1 or 5.2.3 shall be source tested to determine compliance with the applicable emission limits at least once every 12 months, (no more than 30 days before or after the required annual source test date). Units that demonstrate compliance on two consecutive 12-month source tests may defer the following 12-month source test for up to 36 months (no more than 30 days before or after the required 36-month source test date).

a. S-882-1-6: 29.3 MMBtu/hr Sellers Engineering Model 105-E Natural Gas-Fired Boiler with a Low NO<sub>x</sub> Burner

- Conditions 4 through 13, 15 through 18, 20, and 21 on the proposed permit comply with this rule.

b. S-882-2-6: 30 MMBtu/hr Sellers Engineering Natural Gas-Fired Boiler, Model 105-E, with a Low NO<sub>x</sub> Burner and an Induced Flue Gas Recirculation System (South Unit)

- Conditions 4 through 13, 15 through 18, 20, and 21 on the proposed permit comply with this rule.

## 8. District Rule 4320 – Advanced Emission Reduction Options for Boilers, Steam Generators, and Process Heaters Greater than 5.0 MMBtu/hr

The purpose of this rule is to limit the emissions of oxides of nitrogen (NO<sub>x</sub>), carbon monoxide (CO), oxides of sulfur (SO<sub>2</sub>), and particulate

matter 10 microns or less (PM<sub>10</sub>) from boilers, steam generators, and process heaters. This rule applies to any gaseous fuel or liquid fuel fired boiler, steam generator, or process heater with a total rated heat input greater than 5 million Btu per hour.

§5.1 states that operators of a unit(s) shall comply with all applicable requirements of the rule and one of the following, on a unit-by-unit basis:

§5.1.1 requires the unit comply with the emission limits specified in §5.2 and 5.4; or

§5.1.2, Pay an annual emissions fee to the District as specified in §5.3 and comply with the control requirements specified in §5.4.

§5.1.3, Comply with the applicable Low-use Unit requirements of §5.5.

§5.2 NO<sub>x</sub> and CO Emission Limits

§5.2.1 On and after the indicated Compliance Deadline, units shall not be operated in a manner which exceeds the applicable NO<sub>x</sub> emissions limit specified in Table 1. On and after October 1, 2008, units shall not be operated in a manner to which exceeds a carbon monoxide (CO) emissions limit of 400 ppmv.

Table 1: NO <sub>x</sub> Emission Limits			
Category	NO <sub>x</sub> Limit	Authority to Construct	Compliance Deadline
E. Units, from any Category, that were installed prior to January 1, 2009 and limited by a Permit to Operate to an annual heat input >1.8 billion Btu/year but < 30 billion Btu/year.	Standard Schedule 9 ppmv or 0.011 lb/MMBtu	Twelve months before the next unit replacement but no later than January 1, 2013.	At the next unit replacement but no later than January 1, 2014

§5.4 states the particulate matter control requirements.

§5.4.1 To limit particulate matter emissions, an operator shall comply with one of the following requirements:

§5.4.1.1 On and after the applicable NO<sub>x</sub> Compliance Deadline specified in §5.2 Table 1, operators shall fire units exclusively on PUC-quality natural gas, commercial propane, butane, or liquefied petroleum gas, or a combination of such gases;

§5.4.1.2 On and after the applicable NO<sub>x</sub> Compliance Deadline specified in §5.2 Table 1, operators shall limit fuel sulfur content to no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet; or

§5.4.1.3 On and after the applicable NO<sub>x</sub> Compliance Deadline specified in §5.2 Table 1, operators shall install and properly operate an emission control system that reduces SO<sub>2</sub> emissions by at least 95% by weight; or limit exhaust SO<sub>2</sub> to less than or equal to 9 ppmv corrected to 3.0% O<sub>2</sub>.

a. S-882-1-6: 29.3 MMBtu/hr Sellers Engineering Model 105-E Natural Gas-Fired Boiler with a Low NO<sub>x</sub> Burner

- Condition 22 on the proposed permit complies with this rule.

b. S-882-2-6: 30 MMBtu/hr Sellers Engineering Natural Gas-Fired Boiler, Model 105-E, with a Low NO<sub>x</sub> Burner and an Induced Flue Gas Recirculation System (South Unit)

- Condition 23 on the proposed permit complies with this rule.

**9. District Rule 4621 – Gasoline Transfer into Stationary Storage Containers, Delivery Vessels, and Bulk Plants**

The purpose of this rule is to limit VOC emissions from stationary storage containers, delivery vessels, and bulk plants and to provide the administrative requirements for determining compliance with this rule.

a. S-882-4-1: Gasoline Dispensing Operation with One 350 Gallon and One 500 Gallon Phase I and Phase II Exempt Aboveground Gasoline Storage Tanks Served by 2 Nozzles.

- Condition 1 on the proposed permit complies with this rule.

**10. District Rule 4694, Wine Fermentation and Storage Tanks (Storage Tank Provisions Only)**

The purpose of this rule is to reduce emissions of volatile organic compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources. The rule is applicable to any facility with VOC emissions in excess of 10 tons per

year. For those facilities to which the rule applies, the requirements of the rule are applicable to any fermentation or storage tank with capacity in excess of 5,000 gallons.

As previously discussed in Section VIII, on August 18, 2011 the District approved an amended SIP submittal which excludes the fermentation provisions of District Rule 4694 while maintaining the storage provisions. Therefore, only the storage provisions are federally enforceable and will be discussed below.

§5.2 places specific restrictions on wine storage tanks with 5,000 gallons or more in capacity when such tanks are not constructed of wood or concrete.

§5.2.1 requires these tanks to be equipped and operated with a pressure-vacuum relief valve meeting all of the following requirements:

- The pressure-vacuum relief valve shall operate within 10% of the maximum allowable working pressure of the tank,
- The pressure-vacuum relief valve shall operate in accordance with the manufacturer's instructions, and
- The pressure-vacuum relief valve shall be permanently labeled with the operating pressure settings.
- The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21.

§5.2.2 requires that the temperature of the stored wine be maintained at or below 75 °F.

§6.4 requires that weekly records be kept of wine volume and temperature in each storage tank and that all records be retained for five years.

- a. S-882-11-1, -12-1, -13-1, -14-1, -15-1, -16-1, -17-1, -18-1, -19-1, -20-1, -21-1, -22-1, -23-1, -24-1, -25-1, -26-1, -27-1, -28-1, -29-1, -30-1, -31-1, -32-1, -33-1, -34-1, -35-1, -36-1, -37-1, -38-1, -39-1, -40-1, -41-1, -42-1, -43-1, -44-1, -45-1, -46-1, -47-1, -48-1, -49-1, -50-1, -51-1, -83-1, -84-1, -85-1, and -86-1: Steel Red and White Wine Fermentation and Wine Storage Tanks
  - Conditions 1 through 7 on the proposed permits ensure compliance with the rule.

- b. S-882-52-1, 53-1, -54-1, -55-1, -56-1, -57-1, -58-1, -59-1, -60-1, -61-1, -62-1, -63-1, -64-1, -65-1, -66-1, -67-1, -68-1, -69-1, -70-1, -71-1, -72-1, -73-1, -74-1, -75-1, -76-1, -77-1, -78-1, -79-1, -80-1, -81-1, -82-1, -87-1, -88-1, -89-1, -90-1, -91-1, -92-1, -93-1, -94-1, -95-1, -96-1, -97-1, -98-1, -99-1, -100-1, -101-1, -102-1, -103-1, -104-1, -106-1, -107-1, -108-1, -109-1, -110-1, -111-1, -112-1, -113-1, -114-1, -115-1, -116-1, -117-1, -118-1, -119-1, -120-1, -121-1, -122-1, -123-1, and -124-1: Steel Wine Storage Tank

- Conditions 1 through 7 on the proposed permits ensure compliance with the rule.

**11. 40 CFR 60, Subpart Dc, Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units**

This subpart applies to each steam generating unit for which construction, modification, or reconstruction is commenced after June 9, 1989 and that has a maximum design heat input capacity of 100 MMBtu/hr or less, but greater than or equal to 10 MMBtu/hr.

- a. S-882-1-6: 29.3 MMBtu/hr Sellers Engineering Model 105-E Natural Gas-Fired Boiler with a Low NO<sub>x</sub> Burner

- Condition 20 on the proposed permit complies with this rule.

- b. S-882-2-6: 30 MMBtu/hr Sellers Engineering Natural Gas-Fired Boiler, Model 105-E, with a Low NO<sub>x</sub> Burner and an Induced Flue Gas Recirculation System (South Unit)

- Condition 21 on the proposed permit complies with this rule.

**12. 40 CFR Part 64, CAM**

40 CFR Part 64 requires Compliance Assurance Monitoring (CAM) for units that meet the following three criteria:

- 1) the unit must have an emission limit for the pollutant;
- 2) the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
- 3) the unit must have a pre-control potential to emit of greater than the major source thresholds.

- a. S-882-1-6: 29.3 MMBtu/hr Sellers Engineering Model 105-E Natural Gas-Fired Boiler with a Low NO<sub>x</sub> Burner

This permit unit has emissions limits for NO<sub>x</sub>, SO<sub>x</sub>, PM<sub>10</sub>, CO, and VOC but it does not have add-on controls for these criteria pollutants. Therefore, this permit unit is not subject to CAM for NO<sub>x</sub>, SO<sub>x</sub>, PM<sub>10</sub>, CO, and VOC.

- b. S-882-2-6: 30 MMBtu/hr Sellers Engineering Natural Gas-Fired Boiler, Model 105-E, with a Low NO<sub>x</sub> Burner and an Induced Flue Gas Recirculation System (South Unit)

This permit unit has emissions limits for SO<sub>x</sub>, PM<sub>10</sub>, CO, and VOC but it does not have add-on controls for these criteria pollutants. Therefore, this permit unit is not subject to CAM for SO<sub>x</sub>, PM<sub>10</sub>, CO, and VOC.

This permit may be subject to CAM for NO<sub>x</sub> since there is a NO<sub>x</sub> limit, and it has add-on controls in the form of FGR. However, the following calculation shows the pre-control NO<sub>x</sub> potential to emit is less than the major source threshold of 20,000 pounds NO<sub>x</sub>/year as shown below. Therefore, this unit is not subject to CAM.

The natural gas controlled-low NO<sub>x</sub> emission factor is 50 lb/MMscf or 0.049 lb/MMBtu (AP-42, 1.4-5, July 1998). The maximum rating for this unit is 30 MMBtu/hr.

**30 MMBtu/hr x 0.049 lb NO<sub>x</sub>/MMBtu x 8760 hrs/year = 12,877 lbs-NO<sub>x</sub>/year < 20,000 lbs-NO<sub>x</sub>/yr**

- c. S-882-4-1: Gasoline Dispensing Operation with One 350 Gallon and One 500 Gallon Phase I and Phase II Exempt Aboveground Gasoline Storage Tanks Served by 2 Nozzles

This permit unit does not have emissions limits for NO<sub>x</sub>, SO<sub>x</sub>, PM<sub>10</sub>, CO, and VOC. Therefore, this permit unit is not subject to CAM for NO<sub>x</sub>, SO<sub>x</sub>, PM<sub>10</sub>, CO, and VOC.

- d. S-882-11-1, -12-1, -13-1, -14-1, -15-1, -16-1, -17-1, -18-1, -19-1, -20-1, -21-1, -22-1, -23-1, -24-1, -25-1, -26-1, -27-1, -28-1, -29-1, -30-1, -31-1, -32-1, -33-1, -34-1, -35-1, -36-1, -37-1, -38-1, -39-1, -40-1, -41-1, -42-1, -43-1, -44-1, -45-1, -46-1, -47-1, -48-1, -49-1, -50-1, -51-1, -83-1, -84-1, -85-1, and -86-1: Steel Red and White Wine Fermentation and Wine Storage Tanks

The emission units have a condition that the temperature of the wine stored shall not exceed 75 F which is based on the storage provisions

of District Rule 4694. This requirement meets CAM's definition of an emission limitation or standard.

The tanks are equipped with a pressure-vacuum relief valve as the add-on control device that does not meet the CAM's definition of a control device. Therefore, the emission units are not subject to CAM.

- e. S-882-52-1, 53-1, -54-1, -55-1, -56-1, -57-1, -58-1, -59-1, -60-1, -61-1, -62-1, -63-1, -64-1, -65-1, -66-1, -67-1, -68-1, -69-1, -70-1, -71-1, -72-1, -73-1, -74-1, -75-1, -76-1, -77-1, -78-1, -79-1, -80-1, -81-1, -82-1, -87-1, -88-1, -89-1, -90-1, -91-1, -92-1, -93-1, -94-1, -95-1, -96-1, -97-1, -98-1, -99-1, -100-1, -101-1, -102-1, -103-1, -104-1, -105-1, -106-1, -107-1, -108-1, -109-1, -110-1, -111-1, -112-1, -113-1, -114-1, -115-1, -116-1, -117-1, -118-1, -119-1, -120-1, -121-1, -122-1, -123-1, and -124-1: Steel Wine Storage Tank

The emission units have a condition that the temperature of the wine stored shall not exceed 75 F which is based on the storage provisions of District Rule 4694. This requirement meets CAM's definition of an emission limitation or standard.

The tanks are equipped with a pressure-vacuum relief valve as the add-on control device that does not meet the CAM's definition of a control device. Therefore, the emission units are not subject to CAM.

- f. S-882-125-1: Winery Wastewater Collection Pump

These permit units have no emissions limits for any criteria pollutants. Therefore, there permit units are not subject to CAM.

- g. S-882-126-1, -127-1, -128-1, -129-1, and -130-1: Ethanol Storage Tank

These permit units have no emissions limits for any criteria pollutants. Therefore, there permit units are not subject to CAM.

## **X. PERMIT SHIELD**

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

A. Requirements Addressed by Model General Permit Templates

By using the model general permit template listed in Section IV of this evaluation, the applicant has requested that a permit shield be issued for requirements addressed in the template. The basis for each permit shield is discussed in the Permit Shield section of each template.

**XI. PERMIT CONDITIONS**

See draft operating permit beginning on the following page.

# San Joaquin Valley Air Pollution Control District

FACILITY: S-882-0-1

EXPIRATION DATE: 01/31/2013

## FACILITY-WIDE REQUIREMENTS

1. {4362} The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. {4363} The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. {4364} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. {4365} Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. {4366} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.9.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. {4367} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. {4368} Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. {4369} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. {4370} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: GOLDEN STATE VINTNERS/Franzia-MCFARLAND  
Location: 31795 WHISLER RD, MCFARLAND, CA 93250

S-882-0-1, Aug 23 2012 9:41AM - SONGCOJ

10. {4371} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. {4372} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. {4373} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. {4374} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. {4375} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. {4376} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. {4377} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. {4378} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. {4379} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. {4380} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. {4381} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. {4382} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

22. {4383} No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
23. {4384} No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. {4385} All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. {4386} The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. {4387} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. {4388} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. {4389} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. {4390} Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit
30. {4391} Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit
31. {4392} An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit
32. {4393} Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit
33. {4394} Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

34. {4395} Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit
35. {4396} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit
36. {4397} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. {4398} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. {4399} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. {4400} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. {4401} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
42. This facility shall annually achieve the Required Annual Emission Reductions (RAER) as specified in the facility's APCO-approved Three-Year Compliance Plan for District Rule 4694. [District Rule 4694]
43. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2006, and every three years thereafter on or before December 1. [District Rule 4694]
44. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District by no later than July 1, 2007, and every three years thereafter on or before July 1. [District Rule 4694]

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

45. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District by no later than February 1, 2008, and every year thereafter on or before February 1. [District Rule 4694]
46. Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]
47. On month, day, year, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-1-6

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

29.3 MMBTU/HR SELLERS ENGINEERING MODEL 105-E NATURAL GAS-FIRED BOILER WITH A LOW NOX BURNER

## PERMIT UNIT REQUIREMENTS

---

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit
5. Maximum annual heat input of the unit shall not exceed 30 billion Btu per calendar year (equivalent to a total natural gas consumption rate of 30 million scf/year). [District Rules 2201, 4305 and 4306] Federally Enforceable Through Title V Permit
6. Emissions rates from the natural gas-fired unit shall not exceed any of the following limits: 30 ppmvd NO<sub>x</sub> @ 3% O<sub>2</sub> or 0.036 lb-NO<sub>x</sub>/MMBtu, 0.00285 lb-SO<sub>x</sub>/MMBtu, 0.0076 lb-PM<sub>10</sub>/MMBtu, 400 ppmvd CO @ 3% O<sub>2</sub> or 0.2911 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305 and 4306] Federally Enforceable Through Title V Permit
7. The permittee shall monitor and record the stack concentration of NO<sub>x</sub>, CO, and O<sub>2</sub> at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
8. If either the NO<sub>x</sub> or CO concentrations corrected to 3% O<sub>2</sub>, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent and the measured NO<sub>x</sub> and CO concentrations corrected to 3% O<sub>2</sub>, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
11. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
12. Source testing to measure NO<sub>x</sub> and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
13. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. NO<sub>x</sub> emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
16. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
17. Stack gas oxygen (O<sub>2</sub>) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
18. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
19. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
20. The owner or operator shall record and maintain records of the amount of fuel combusted during each operating day. [40 CFR 60.48c(g)(1)] Federally Enforceable Through Title V Permit
21. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit
22. On and after January 1, 2014, the boiler shall be in full compliance with District Rule 4320 (10/16/08), Section 5.2, Table 1, Category E. [District Rule 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-2-6

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

30 MMBTU/HR SELLERS ENGINEERING NATURAL GAS-FIRED BOILER, MODEL 105-E, WITH A LOW-NOX BURNER AND AN INDUCED FLUE GAS RECIRCULATION SYSTEM (SOUTH UNIT)

## PERMIT UNIT REQUIREMENTS

---

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit
5. Maximum annual heat input of the unit shall not exceed 30 billion Btu per calendar year. [District Rules 2201, 4305 and 4306] Federally Enforceable Through Title V Permit
6. Emissions from the natural gas-fired unit shall not exceed any of the following limits: 30 ppmvd NO<sub>x</sub> @ 3% O<sub>2</sub>, 0.00285 lb-SO<sub>x</sub>/MMBtu, 0.0076 lb-PM<sub>10</sub>/MMBtu, 200 ppmvd CO @ 3% O<sub>2</sub>, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit
7. The permittee shall monitor and record the stack concentration of NO<sub>x</sub>, CO, and O<sub>2</sub> at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
8. If either the NO<sub>x</sub> or CO concentrations corrected to 3% O<sub>2</sub>, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent and the measured NO<sub>x</sub> and CO concentrations corrected to 3% O<sub>2</sub>, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
11. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
12. Source testing to measure NO<sub>x</sub> and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
13. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. NO<sub>x</sub> emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
16. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
17. Stack gas oxygen (O<sub>2</sub>) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
18. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
19. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
20. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit
21. The owner or operator shall record and maintain records of the amount of fuel combusted during each operating day. [40 CFR 60.48c(g)(1)] Federally Enforceable Through Title V Permit
22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit
23. On and after January 1, 2014, the boiler shall be in full compliance with District Rule 4320 (10/16/08), Section 5.2, Table 1, Category E. [District Rule 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-4-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

GASOLINE DISPENSING OPERATION WITH ONE 350 GALLON AND ONE 500 GALLON PHASE I AND PHASE II EXEMPT ABOVEGROUND GASOLINE STORAGE TANKS SERVED BY 2 NOZZLES (INSTALLED BEFORE JULY 1, 1975)

## PERMIT UNIT REQUIREMENTS

---

1. The tank is to be equipped with a submerged fill pipe that extends to within six (6) inches of the bottom of the tank. [District Rule 4621] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-11-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #1) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-12-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #2) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-13-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #3) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-14-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #4) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-15-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #5) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-16-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #6) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-17-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #7) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-18-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #8) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-19-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #9) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-20-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #10) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-21-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #11) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-22-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #12) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-23-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #13) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-24-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #14) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-25-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #15) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-26-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #16) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-27-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #17) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-28-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #18) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-29-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #19) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-30-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #20) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-31-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #21) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-32-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #22) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-33-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #23) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-34-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #24) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-35-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #25) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-36-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #26) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-37-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #27) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-38-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #28) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-39-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #29) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-40-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #30) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-41-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #31) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-42-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #32) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-43-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #33) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-44-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #34) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-45-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #35) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-46-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #36) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-47-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #37) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-48-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #38) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-49-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #39) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-50-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #40) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-51-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #41) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-52-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #42) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-53-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #43) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-54-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #44) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-55-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #45) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-56-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #46) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-57-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #47) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-58-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #48) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-59-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #49) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-60-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #50) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-61-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #51) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-62-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #52) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-63-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #53) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-64-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #54) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-65-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #55) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-66-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #56) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-67-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #57) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-68-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #58) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-69-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #59) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-70-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #60) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-71-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #61) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-72-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #62) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-73-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #63) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-74-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #64) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-75-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #65) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-76-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #66) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-77-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #67) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-78-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #68) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-79-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #69) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-80-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #70) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-81-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #71) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-82-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

215,674 GALLON STEEL WINE STORAGE TANK (TANK #72) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-83-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

215,674 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #73) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-84-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

215,674 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #74) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-85-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

215,674 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #75) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-86-1

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

215,674 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #76) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-87-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #77) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-88-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #78) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-89-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #79) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-90-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #80) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-91-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #81) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-92-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #82) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-93-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #83) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-94-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #84) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-95-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

7,489 GALLON STEEL WINE STORAGE TANK (TANK #85) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-96-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

7,489 GALLON STEEL WINE STORAGE TANK (TANK #86) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-97-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #87) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-98-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #88) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-99-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #89) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-100-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #90) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-101-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #91) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-102-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #92) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-103-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #93) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-104-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #94) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-105-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

2,538 GALLON STEEL WINE STORAGE TANK (TANK #95) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-106-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

350,446 GALLON STEEL WINE STORAGE TANK (TANK #96) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-107-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

350,446 GALLON STEEL WINE STORAGE TANK (TANK #97) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-108-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

350,446 GALLON STEEL WINE STORAGE TANK (TANK #98) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-109-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

350,446 GALLON STEEL WINE STORAGE TANK (TANK #99) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-110-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,314 GALLON STEEL WINE STORAGE TANK (TANK #P1) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-111-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,314 GALLON STEEL WINE STORAGE TANK (TANK #P2) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-112-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,314 GALLON STEEL WINE STORAGE TANK (TANK #P3) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-113-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,314 GALLON STEEL WINE STORAGE TANK (TANK #P4) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-114-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

350,446 GALLON STEEL WINE STORAGE TANK (TANK #100) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-115-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

350,446 GALLON STEEL WINE STORAGE TANK (TANK #101) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-116-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK #105) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-117-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK #106) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-118-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK #107) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-119-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK #108) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-120-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK #109) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-121-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK # 110) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-122-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK # 111) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-123-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK # 112) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-124-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

5,469 GALLON STEEL WINE STORAGE TANK (TANK # 113) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

PERMIT UNIT: S-882-125-1

EXPIRATION DATE: 01/31/2013

EQUIPMENT DESCRIPTION:  
WINERY WASTEWATER COLLECTION SUMP

DRAFT

## PERMIT UNIT REQUIREMENTS

---

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-126-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,314 GALLON ETHANOL STORAGE TANK (TANK #P-1) WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

PERMIT UNIT: S-882-127-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

25,252 GALLON ETHANOL STORAGE TANK (TANK #P-7) WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

PERMIT UNIT: S-882-128-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

25,252 GALLON ETHANOL STORAGE TANK (TANK #P-8) WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-129-1

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

25,252 GALLON ETHANOL STORAGE TANK (TANK #P-9) WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

PERMIT UNIT: S-882-130-1

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

25,252 GALLON ETHANOL STORAGE TANK (TANK #P-10) WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# Attachment A

## Detailed Facility Printout

**Detailed Facility Report**  
For Facility=882 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

<b>GOLDEN STATE VINTNERS/FRANZIA-MCFARLAND</b>	<b>FAC #</b>	<b>S 882</b>	<b>TYPE:</b>	<b>TitleV</b>	<b>EXPIRE ON:</b>	<b>01/31/2013</b>
<b>31795 WHISLER, RD</b>	<b>STATUS:</b>	<b>A</b>	<b>TOXIC ID:</b>		<b>AREA:</b>	<b>5 / 316</b>
<b>MCFARLAND, CA 93250</b>	<b>TELEPHONE:</b>	<b>5595283033</b>			<b>INSP. DATE:</b>	<b>11/12</b>

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-882-1-5	29,300 kBtu/hr boiler	3020-02 H	1	1,030.00	1,030.00	A	29.3 MMBTU/HR SELLERS ENGINEERING MODEL 105-E NATURAL GAS-FIRED BOILER WITH A LOW NOX BURNER
S-882-2-5	30,000 KBtus/hr	3020-02 H	1	1,030.00	1,030.00	A	30 MMBTU/HR SELLERS ENGINEERING NATURAL GAS-FIRED BOILER, MODEL 105-E, WITH A LOW-NOX BURNER AND AN INDUCED FLUE GAS RECIRCULATION SYSTEM (SOUTH UNIT)
S-882-4-0	2 NOZZLE	3020-11 A	2	34.00	68.00	A	GASOLINE DISPENSING OPERATION WITH ONE 350 GALLON AND ONE 500 GALLON PHASE I AND PHASE II EXEMPT ABOVEGROUND GASOLINE STORAGE TANKS SERVED BY 2 NOZZLES (INSTALLED BEFORE JULY 1, 1975)
S-882-11-0	217,443 gallons	3020-05 E	1	246.00	246.00	A	217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #1) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-12-0	217,443 gallons	3020-05 E	1	246.00	246.00	A	217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #2) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-13-0	217,443 gallons	3020-05 E	1	246.00	246.00	A	217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #3) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-14-0	217,443 gallons	3020-05 E	1	246.00	246.00	A	217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #4) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-15-0	217,443 gallons	3020-05 E	1	246.00	246.00	A	217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #5) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-16-0	217,443 gallons	3020-05 E	1	246.00	246.00	A	217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #6) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-17-0	217,443 gallons	3020-05 E	1	246.00	246.00	A	217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #7) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-18-0	217,443 gallons	3020-05 E	1	246.00	246.00	A	217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #8) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-19-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #9) WITH PRESSURE VACUUM VALVE AND INSULATION

**Detailed Facility Report**  
For Facility=882 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-882-20-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #10) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-21-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #11) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-22-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #12) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-23-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #13) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-24-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #14) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-25-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #15) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-26-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #16) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-27-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #17) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-28-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #18) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-29-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #19) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-30-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #20) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-31-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #21) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-32-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #22) WITH PRESSURE VACUUM VALVE AND INSULATION

**Detailed Facility Report**  
For Facility=882 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-882-33-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #23) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-34-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #24) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-35-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #25) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-36-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #26) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-37-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #27) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-38-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #28) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-39-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #29) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-40-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #30) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-41-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #31) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-42-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #32) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-43-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #33) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-44-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #34) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-45-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #35) WITH PRESSURE VACUUM VALVE AND INSULATION

**Detailed Facility Report**  
For Facility=882 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-882-46-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #36) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-47-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #37) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-48-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #38) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-49-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #39) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-50-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #40) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-51-0	106,931 gallons	3020-05 E	1	246.00	246.00	A	106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #41) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-52-0	13,354 gallons	3020-05 B	1	93.00	93.00	A	13,354 GALLON STEEL WINE STORAGE TANK (TANK #42) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-53-0	13,354 gallons	3020-05 B	1	93.00	93.00	A	13,354 GALLON STEEL WINE STORAGE TANK (TANK #43) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-54-0	13,354 gallons	3020-05 B	1	93.00	93.00	A	13,354 GALLON STEEL WINE STORAGE TANK (TANK #44) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-55-0	13,354 gallons	3020-05 B	1	93.00	93.00	A	13,354 GALLON STEEL WINE STORAGE TANK (TANK #45) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-56-0	13,354 gallons	3020-05 B	1	93.00	93.00	A	13,354 GALLON STEEL WINE STORAGE TANK (TANK #46) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-57-0	13,354 gallons	3020-05 B	1	93.00	93.00	A	13,354 GALLON STEEL WINE STORAGE TANK (TANK #47) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-58-0	13,354 gallons	3020-05 B	1	93.00	93.00	A	13,354 GALLON STEEL WINE STORAGE TANK (TANK #48) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-59-0	13,354 gallons	3020-05 B	1	93.00	93.00	A	13,354 GALLON STEEL WINE STORAGE TANK (TANK #49) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-60-0	13,354 gallons	3020-05 B	1	93.00	93.00	A	13,354 GALLON STEEL WINE STORAGE TANK (TANK #50) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-61-0	13,354 gallons	3020-05 B	1	93.00	93.00	A	13,354 GALLON STEEL WINE STORAGE TANK (TANK #51) WITH PRESSURE VACUUM VALVE AND INSULATION

**Detailed Facility Report**  
For Facility=882 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-882-62-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #52) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-63-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #53) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-64-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #54) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-65-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #55) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-66-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #56) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-67-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #57) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-68-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #58) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-69-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #59) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-70-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #60) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-71-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #61) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-72-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #62) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-73-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #63) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-74-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #64) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-75-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #65) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-76-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #66) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-77-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #67) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-78-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #68) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-79-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #69) WITH PRESSURE VACUUM VALVE AND INSULATION

**Detailed Facility Report**  
For Facility=882 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-882-80-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #70) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-81-0	28,682 gallons	3020-05 C	1	135.00	135.00	A	28,682 GALLON STEEL WINE STORAGE TANK (TANK #71) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-82-0	215,674 gallons	3020-05 E	1	246.00	246.00	A	215,674 GALLON STEEL WINE STORAGE TANK (TANK #72) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-83-0	215,674 gallons	3020-05 E	1	246.00	246.00	A	215,674 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #73) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-84-0	215,674 gallons	3020-05 E	1	246.00	246.00	A	215,674 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #74) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-85-0	215,674 gallons	3020-05 E	1	246.00	246.00	A	215,674 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #75) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-86-0	215,674 gallons	3020-05 E	1	246.00	246.00	A	215,674 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #76) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-87-0	51,416 gallons	3020-05 D	1	185.00	185.00	A	51,416 GALLON STEEL WINE STORAGE TANK (TANK #77) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-88-0	51,416 gallons	3020-05 D	1	185.00	185.00	A	51,416 GALLON STEEL WINE STORAGE TANK (TANK #78) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-89-0	51,416 gallons	3020-05 E	1	246.00	246.00	A	51,416 GALLON STEEL WINE STORAGE TANK (TANK #79) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-90-0	51,416 gallons	3020-05 D	1	185.00	185.00	A	51,416 GALLON STEEL WINE STORAGE TANK (TANK #80) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-91-0	51,416 gallons	3020-05 D	1	185.00	185.00	A	51,416 GALLON STEEL WINE STORAGE TANK (TANK #81) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-92-0	51,416 gallons	3020-05 D	1	185.00	185.00	A	51,416 GALLON STEEL WINE STORAGE TANK (TANK #82) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-93-0	51,416 gallons	3020-05 D	1	185.00	185.00	A	51,416 GALLON STEEL WINE STORAGE TANK (TANK #83) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-94-0	51,416 gallons	3020-05 D	1	185.00	185.00	A	51,416 GALLON STEEL WINE STORAGE TANK (TANK #84) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-95-0	7,489 gallons	3020-05 B	1	93.00	93.00	A	7,489 GALLON STEEL WINE STORAGE TANK (TANK #85) WITH PRESSURE VACUUM VALVE AND INSULATION

**Detailed Facility Report**  
For Facility=882 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-882-96-0	7,489 gallons	3020-05 B	1	93.00	93.00	A	7,489 GALLON STEEL WINE STORAGE TANK (TANK #86) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-97-0	6,828 gallons	3020-05 B	1	93.00	93.00	A	6,828 GALLON STEEL WINE STORAGE TANK (TANK #87) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-98-0	6,828 gallons	3020-05 B	1	93.00	93.00	A	6,828 GALLON STEEL WINE STORAGE TANK (TANK #88) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-99-0	6,828 gallons	3020-05 B	1	93.00	93.00	A	6,828 GALLON STEEL WINE STORAGE TANK (TANK #89) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-100-0	6,828 gallons	3020-05 B	1	93.00	93.00	A	6,828 GALLON STEEL WINE STORAGE TANK (TANK #90) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-101-0	6,828 gallons	3020-05 B	1	93.00	93.00	A	6,828 GALLON STEEL WINE STORAGE TANK (TANK #91) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-102-0	6,828 gallons	3020-05 B	1	93.00	93.00	A	6,828 GALLON STEEL WINE STORAGE TANK (TANK #92) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-103-0	6,828 gallons	3020-05 B	1	93.00	93.00	A	6,828 GALLON STEEL WINE STORAGE TANK (TANK #93) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-104-0	6,828 gallons	3020-05 B	1	93.00	93.00	A	6,828 GALLON STEEL WINE STORAGE TANK (TANK #94) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-105-0	2,538 gallons	3020-05 A	1	75.00	75.00	A	2,538 GALLON STEEL WINE STORAGE TANK (TANK #95) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-106-0	350, 446 gallons	3020-05 E	1	246.00	246.00	A	350,446 GALLON STEEL WINE STORAGE TANK (TANK #96) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-107-0	350, 446 gallons	3020-05 E	1	246.00	246.00	A	350,446 GALLON STEEL WINE STORAGE TANK (TANK #97) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-108-0	350, 446 gallons	3020-05 E	1	246.00	246.00	A	350,446 GALLON STEEL WINE STORAGE TANK (TANK #98) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-109-0	350, 446 gallons	3020-05 E	1	246.00	246.00	A	350,446 GALLON STEEL WINE STORAGE TANK (TANK #99) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-110-0	106,314 gallons	3020-05 E	1	246.00	246.00	A	106,314 GALLON STEEL WINE STORAGE TANK (TANK #P1) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-111-0	106,314 gallons	3020-05 E	1	246.00	246.00	A	106,314 GALLON STEEL WINE STORAGE TANK (TANK #P2) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-112-0	106,314 gallons	3020-05 E	1	246.00	246.00	A	106,314 GALLON STEEL WINE STORAGE TANK (TANK #P3) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-113-0	106,314 gallons	3020-05 E	1	246.00	246.00	A	106,314 GALLON STEEL WINE STORAGE TANK (TANK #P4) WITH PRESSURE VACUUM VALVE AND INSULATION

**Detailed Facility Report**  
For Facility=882 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-882-114-0	350,446 gallons	3020-05 E	1	246.00	246.00	A	350,446 GALLON STEEL WINE STORAGE TANK (TANK #100) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-115-0	350,446 gallons	3020-05 E	1	246.00	246.00	A	350,446 GALLON STEEL WINE STORAGE TANK (TANK #101) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-116-0	55,220 gallons	3020-05 D	1	185.00	185.00	A	55,220 GALLON STEEL WINE STORAGE TANK (TANK #105) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-117-0	55,220 gallons	3020-05 D	1	185.00	185.00	A	55,220 GALLON STEEL WINE STORAGE TANK (TANK #106) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-118-0	55,220 gallons	3020-05 D	1	185.00	185.00	A	55,220 GALLON STEEL WINE STORAGE TANK (TANK #107) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-119-0	55,220 gallons	3020-05 D	1	185.00	185.00	A	55,220 GALLON STEEL WINE STORAGE TANK (TANK #108) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-120-0	55,220 gallons	3020-05 D	1	185.00	185.00	A	55,220 GALLON STEEL WINE STORAGE TANK (TANK #109) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-121-0	55,220 gallons	3020-05 D	1	185.00	185.00	A	55,220 GALLON STEEL WINE STORAGE TANK (TANK # 110) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-122-0	55,220 gallons	3020-05 D	1	185.00	185.00	A	55,220 GALLON STEEL WINE STORAGE TANK (TANK # 111) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-123-0	55,220 gallons	3020-05 D	1	185.00	185.00	A	55,220 GALLON STEEL WINE STORAGE TANK (TANK # 112) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-124-0	5,469 gallons	3020-05 B	1	93.00	93.00	A	5,469 GALLON STEEL WINE STORAGE TANK (TANK # 113) WITH PRESSURE VACUUM VALVE AND INSULATION
S-882-125-0	20 hp	3020-01 A	1	87.00	87.00	A	WINERY WASTEWATER COLLECTION SUMP
S-882-126-0	106,314 gallons	3020-05 E	1	246.00	246.00	A	106,314 GALLON ETHANOL STORAGE TANK (TANK #P-1) WITH PRESSURE/VACUUM VALVE
S-882-127-0	25,252 gallons	3020-05 C	1	135.00	135.00	A	25,252 GALLON ETHANOL STORAGE TANK (TANK #P-7) WITH PRESSURE/VACUUM VALVE
S-882-128-0	25,252 gallons	3020-05 C	1	135.00	135.00	A	25,252 GALLON ETHANOL STORAGE TANK (TANK #P-8) WITH PRESSURE/VACUUM VALVE
S-882-129-0	25,252 gallons	3020-05 C	1	135.00	135.00	A	25,252 GALLON ETHANOL STORAGE TANK (TANK #P-9) WITH PRESSURE/VACUUM VALVE
S-882-130-0	25,252 gallons	3020-05 C	1	135.00	135.00	A	25,252 GALLON ETHANOL STORAGE TANK (TANK #P-10) WITH PRESSURE/VACUUM VALVE

Number of Facilities Reported: 1

# Attachment B

## Exempt Equipment

**San Joaquin Valley  
Unified Air Pollution Control District  
Title V Application - INSIGNIFICANT ACTIVITIES**

COMPANY NAME: **Golden State Vintners dba Franzia McFarland**

FACILITY ID: **S -882**

Check the box next to the exemption category from Rule 2020 which describes any insignificant activity or equipment at your facility not requiring a permit.

Exemption Category	Rule 2020 Citation	√	Exemption Category	Rule 2020 Citation	√
Structure or incinerator assoc. with a structure designed as a dwelling for 4 families or less	4.1		Containers used to store refined lubricating oils	6.6.8	✓
Locomotives, airplanes, and watercraft used to transport passengers or freight	4.4		Unvented pressure vessels used exclusively to store liquified gases or assoc with exempt equipment	6.6.9 or 6.13	✓
Natural gas or LPG-fired boilers or other indirect heat transfer units of 5 MMBtu/hr or less	6.1.1		Portable tanks used exclusively to store produced fluids for ≤ six months	6.6.10	
Piston-type i.c.engine with maximum continuous rating of 50 braking horsepower (bhp) or less	6.1.2		Mobile transport tanks on delivery vehicles of VOCs	6.6.11	
Gas turbine engines with maximum heat input rating of 3 MMBtu/hr or less	6.1.3		Loading racks used for the transfer of less than 4,000 gal/day of unheated organic material with initial boiling point ≥ 302 F or of fuel oil with specific gravity ≥ 0.8251	6.7.1.1	
Space heating equipment other than boilers	6.1.4	✓	Loading racks used for the transfer of asphalt, crude or residual oil stored in exempt tanks, or crude oil with specific gravity ≥ 0.8762	6.7.1.2	
Cooling towers with a circulation rate less than 10,000 gal/min, and that are not used for cooling of process water, or water from barometric jets or condensers++	6.2	✓	Equipment used exclusively for the transfer of refined lubricating oil	6.7.2	
Use of less than 2 gal/day of graphic arts materials	6.3		Equipment used to apply architectural coatings	6.8.1	
Equipment at retail establishments used to prepare food for human consumption	6.4.1		Unheated, non-conveyorized cleaning equipment with < 10 ft <sup>2</sup> open area; using solvents with initial boiling point ≥ 248 F; and < 25 gal/yr. evaporative losses	6.9	
Ovens at bakeries with total daily production less than 1,000 pounds and exempt by sec. 6.1.1	6.4.3		Brazing, soldering, or welding equipment	6.10	✓
Equipment used exclusively for extruding or compression molding of rubber or plastics, where no plastisizer or blowing agent is used	6.5		Equipment used to compress natural gas	6.11	
Containers used to store clean produced water	6.6.1		Fugitive emissions sources assoc. with exempt equipment	6.12	✓
Containers ≤ 100 bbl used to store oil with specific gravity ≥ 0.8762	6.6.2		Pits and Ponds as defined in Rule 1020	6.15	
Containers ≤ 100 bbl installed prior to 6/1/89 used to store oil with specific gravity ≥ 0.8762	6.6.3		On-site roadmix manufacturing and the application of roadmix as a road base material	6.17	
Containers with a capacity ≤ 250 gallons used to store organic material where the actual storage temperature < 150 F	6.6.4		Emissions less than 2 lb/day from units not included above	6.19	✓
Containers used to store unheated organic material with an initial boiling point ≥ 302 F	6.6.5		Venting PUC quality natural gas from for sole purpose of pipeline and compressor repair and or maintenance	7.2	
Containers used to store fuel oils or non-air-blown asphalt with specific gravity ≥ 0.9042	6.6.6		Non-structural repairs & maintenance to permitted equipment	7.3	✓
Containers used to store petroleum distillates used as motor fuel with specific gravity ≥ 0.8251	6.6.7	✓	Detonation of explosives ≤ 100 lb/day and 1,000 lb/year	7.4	

No insignificant activities (Check this box if no equipment in the above categories exist at your facility.)

# Attachment C

## SJVUAPCD Permits



# Permit to Operate

**FACILITY:** S-882

**EXPIRATION DATE:** 01/31/2013

**LEGAL OWNER OR OPERATOR:**  
**MAILING ADDRESS:**

GOLDEN STATE VINTNERS/FRANZIA-MCFARLAND  
ATTN: A/P 2827  
PO BOX 90  
TRACY, CA 95378-0090

**FACILITY LOCATION:**

31795 WHISLER RD  
MCFARLAND, CA 93250

**FACILITY DESCRIPTION:**

WINE AND BRANDY

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

**Seyed Sadredin**  
Executive Director / APCO

**David Warner**  
Director of Permit Services

# San Joaquin Valley Air Pollution Control District

FACILITY: S-882-0-0

EXPIRATION DATE: 01/31/2013

## FACILITY-WIDE REQUIREMENTS

---

1. This facility shall annually achieve the Required Annual Emission Reductions (RAER) as specified in the facility's APCO-approved Three-Year Compliance Plan for District Rule 4694. [District Rule 4694]
2. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2006, and every three years thereafter on or before December 1. [District Rule 4694]
3. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District by no later than July 1, 2007, and every three years thereafter on or before July 1. [District Rule 4694]
4. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District by no later than March 1, 2008, and every year thereafter on or before March 1. [District Rule 4694]
5. Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]
6. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070]

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: GOLDEN STATE VINTNERS/FRANZIA-MCFARLAND  
Location: 31795 WHISLER RD, MCFARLAND, CA 93250  
S-882-0-0: May 8 2012 9:01AM - SIONGCOJ

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-1-5

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

29.3 MMBTU/HR SELLERS ENGINEERING MODEL 105-E NATURAL GAS-FIRED BOILER WITH A LOW NOX BURNER

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201]
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201]
5. The unit shall only be fired on PUC-regulated natural gas. [District Rule 2201, 40 CFR 60.45c(c) and 40 CFR 60.47c(c)]
6. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. [District Rules 2201, 4305, and 4306]
7. Maximum annual heat input of the unit shall not exceed 30 billion Btu per calendar year (equivalent to a total natural gas consumption rate of 30 million scf/year). [District Rules 2201, 4305 and 4306]
8. Emissions rates from the natural gas-fired unit shall not exceed any of the following limits: 30 ppmvd NO<sub>x</sub> @ 3% O<sub>2</sub> or 0.036 lb-NO<sub>x</sub>/MMBtu, 0.00285 lb-SO<sub>x</sub>/MMBtu, 0.0076 lb-PM<sub>10</sub>/MMBtu, 400 ppmvd CO @ 3% O<sub>2</sub> or 0.2911 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305 and 4306 5.1.1; 40 CFR 60.45c(c) and 60.47c(c)]
9. The permittee shall monitor and record the stack concentration of NO<sub>x</sub>, CO, and O<sub>2</sub> at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306]
10. If either the NO<sub>x</sub> or CO concentrations corrected to 3% O<sub>2</sub>, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306]
12. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent and the measured NO<sub>x</sub> and CO concentrations corrected to 3% O<sub>2</sub>, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306]
13. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306]
14. Source testing to measure NO<sub>x</sub> and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305 and 4306]
15. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306]
16. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081]
17. NO<sub>x</sub> emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305 and 4306]
18. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305 and 4306]
19. Stack gas oxygen (O<sub>2</sub>) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305 and 4306]
20. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306]
21. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]
22. Records of monthly and annual fuel usage shall be maintained. [District Rules 1070, 4305, and 4306; 40 CFR 60.48c(c)]
23. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306; 40 CFR 60.48c(i)]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-2-5

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

30 MMBTU/HR SELLERS ENGINEERING NATURAL GAS-FIRED BOILER, MODEL 105-E, WITH A LOW-NOX BURNER AND AN INDUCED FLUE GAS RECIRCULATION SYSTEM (SOUTH UNIT)

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201]
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201]
5. The unit shall only be fired on PUC-regulated natural gas. [District Rule 2201]
6. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. [District Rules 2201, 4305, and 4306]
7. Maximum annual heat input of the unit shall not exceed 30 billion Btu per calendar year. [District Rules 2201, 4305 and 4306]
8. Emissions from the natural gas-fired unit shall not exceed any of the following limits: 30 ppmvd NO<sub>x</sub> @ 3% O<sub>2</sub>, 0.00285 lb-SO<sub>x</sub>/MMBtu, 0.0076 lb-PM<sub>10</sub>/MMBtu, 200 ppmvd CO @ 3% O<sub>2</sub>, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, and 4306]
9. The permittee shall monitor and record the stack concentration of NO<sub>x</sub>, CO, and O<sub>2</sub> at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306]
10. If either the NO<sub>x</sub> or CO concentrations corrected to 3% O<sub>2</sub>, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306]
12. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent and the measured NO<sub>x</sub> and CO concentrations corrected to 3% O<sub>2</sub>, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306]
13. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306]
14. Source testing to measure NO<sub>x</sub> and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305 and 4306]
15. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306]
16. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081]
17. NO<sub>x</sub> emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305 and 4306]
18. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305 and 4306]
19. Stack gas oxygen (O<sub>2</sub>) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305 and 4306]
20. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306]
21. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]
22. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306]
23. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-4-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

GASOLINE DISPENSING OPERATION WITH ONE 350 GALLON AND ONE 500 GALLON PHASE I AND PHASE II EXEMPT ABOVEGROUND GASOLINE STORAGE TANKS SERVED BY 2 NOZZLES (INSTALLED BEFORE JULY 1, 1975)

## PERMIT UNIT REQUIREMENTS

---

1. The tank is to be equipped with a submerged fill pipe that extends to within six (6) inches of the bottom of the tank.  
[District Rule 4621]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-11-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #1) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-12-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #2) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-13-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #3) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-14-0

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #4) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-15-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #5) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-16-0

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #6) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-17-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #7) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-18-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

217,443 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #8) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-19-0

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #9) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-20-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #10) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-21-0

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #11) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-22-0

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #12) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-23-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #13) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-24-0

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #14) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-25-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #15) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-26-0

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #16) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-27-0

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #17) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-28-0

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #18) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-29-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #19) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-30-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #20) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-31-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #21) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-32-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #22) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-33-0

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #23) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-34-0

EXPIRATION DATE: 01/31/2013

## EQUIPMENT DESCRIPTION:

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #24) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-35-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #25) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-36-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #26) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-37-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #27) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-38-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #28) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-39-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #29) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-40-0

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #30) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-41-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #31) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-42-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #32) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-43-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #33) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-44-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #34) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-45-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #35) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-46-0

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #36) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-47-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #37) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-48-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #38) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-49-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #39) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-50-0

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #40) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-51-0

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,931 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #41) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-52-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #42) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-53-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #43) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-54-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #44) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-55-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #45) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-56-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #46) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-57-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #47) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-58-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #48) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-59-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #49) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-60-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #50) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-61-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

13,354 GALLON STEEL WINE STORAGE TANK (TANK #51) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-62-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #52) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-63-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #53) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-64-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #54) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-65-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #55) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-66-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #56) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-67-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #57) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-68-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #58) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-69-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #59) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-70-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #60) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-71-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #61) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-72-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #62) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-73-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #63) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-74-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #64) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-75-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #65) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-76-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #66) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-77-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #67) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-78-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #68) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-79-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #69) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-80-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #70) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-81-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

28,682 GALLON STEEL WINE STORAGE TANK (TANK #71) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-82-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

215,674 GALLON STEEL WINE STORAGE TANK (TANK #72) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-83-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

215,674 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #73) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-882-84-0

EXPIRATION DATE: 01/31/2013

**EQUIPMENT DESCRIPTION:**

215,674 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #74) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-85-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

215,674 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #75) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-86-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

215,674 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #76) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]
9. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-87-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #77) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-88-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #78) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-89-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #79) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-90-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #80) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-91-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #81) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-92-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #82) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-93-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #83) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-94-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

51,416 GALLON STEEL WINE STORAGE TANK (TANK #84) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-95-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

7,489 GALLON STEEL WINE STORAGE TANK (TANK #85) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-96-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

7,489 GALLON STEEL WINE STORAGE TANK (TANK #86) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-97-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #87) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-98-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #88) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-99-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #89) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-100-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #90) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-101-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #91) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-102-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #92) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-103-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #93) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-104-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

6,828 GALLON STEEL WINE STORAGE TANK (TANK #94) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-105-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

2,538 GALLON STEEL WINE STORAGE TANK (TANK #95) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-106-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

350,446 GALLON STEEL WINE STORAGE TANK (TANK #96) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-107-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

350,446 GALLON STEEL WINE STORAGE TANK (TANK #97) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-108-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

350,446 GALLON STEEL WINE STORAGE TANK (TANK #98) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-109-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

350,446 GALLON STEEL WINE STORAGE TANK (TANK #99) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-110-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,314 GALLON STEEL WINE STORAGE TANK (TANK #P1) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-111-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,314 GALLON STEEL WINE STORAGE TANK (TANK #P2) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-112-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,314 GALLON STEEL WINE STORAGE TANK (TANK #P3) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-113-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,314 GALLON STEEL WINE STORAGE TANK (TANK #P4) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-114-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

350,446 GALLON STEEL WINE STORAGE TANK (TANK #100) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-115-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

350,446 GALLON STEEL WINE STORAGE TANK (TANK #101) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-116-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK #105) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-117-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK #106) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-118-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK #107) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-119-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK #108) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-120-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK #109) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-121-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK # 110) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-122-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK # 111) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-123-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

55,220 GALLON STEEL WINE STORAGE TANK (TANK # 112) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-124-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

5,469 GALLON STEEL WINE STORAGE TANK (TANK # 113) WITH PRESSURE VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
3. The pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
4. The pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
5. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
6. The maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
7. Records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694]
8. The wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-125-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**  
WINERY WASTEWATER COLLECTION SUMP

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-126-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

106,314 GALLON ETHANOL STORAGE TANK (TANK #P-1) WITH PRESSURE/VACUUM VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: GOLDEN STATE VINTNERS/Franzia-MCFARLAND

Location: 31795 WHISLER RD, MCFARLAND, CA 93250

S-882-126-0 : May 8 2012 9:07AM - SIONGCCJ

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-127-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

25,252 GALLON ETHANOL STORAGE TANK (TANK #P-7) WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: GOLDEN STATE VINTNERS/Franzia-MCFARLAND

Location: 31795 WHISLER RD, MCFARLAND, CA 93250

S-882-127-0 : May 8 2012 9:07AM - SIONGCOJ

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-128-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

25,252 GALLON ETHANOL STORAGE TANK (TANK #P-8) WITH PRESSURE/VACUUM VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-129-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

25,252 GALLON ETHANOL STORAGE TANK (TANK #P-9) WITH PRESSURE/VACUUM VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-882-130-0

**EXPIRATION DATE:** 01/31/2013

**EQUIPMENT DESCRIPTION:**

25,252 GALLON ETHANOL STORAGE TANK (TANK #P-10) WITH PRESSURE/VACUUM VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: GOLDEN STATE VINTNERS/FRANZIA-MCFARLAND

Location: 31795 WHISLER RD, MCFARLAND, CA 93250

S-882-130-0 : May 8 2012 9:07AM - SIONGCOJ