

Well No. 12 C

Unused - No power - Pump in well 7/11/67

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA



Log No. 8402
Rec. March 18, 1965
Well No.
Permit No. 22060
Do not fill in

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner THE ANACONDA COMPANY (WELL 12 C) Driller THE ANACONDA COMPANY

Address Address Lic. No.

Location of well: NW 1/4 SW 1/4 Sec. 4., T.13.N/S, R.25.E, in LYON County
or

Water will be used for milling Total depth of well 465 feet

Size of drilled hole 20" to 155', 18" to 300', 16" to 465' Weight of casing per linear foot 40 lbs.

Thickness of casing 1/4 inch Temp. of water 65°

Diameter and length of casing 20" to 148'; 18" to 294'; 16" to 455'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.

If nonflowing well give depth of standing water from surface 6'

If flowing well describe control works.
(Type and size of valve, etc.)

Date of commencement of well Dec. 18, 1964 Date of completion of well Jan. 26, 1965

Type of well rig Bucyrus-Erie Model 42T Churn Drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Silt & clay
5	440	435	Fine silt & sand with layers of clay varying from 6 inches to 2 feet
440	465	25	Fine gravel cemented with clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 6' to 440 ft.

Other aquifers

First water at 6 feet.

Casing perforated

from 200 to 455 ft.

Size of perforations

1/8" x 6"



