BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION (Pumalpina)
28906318.01000	APN 7351-33-37

DRILLING METHOD:	BORING NUMBER
Mark M25 vibratory hammer Hand auger	SBL0311
SAMPLING METHOD:	SHEET
1.5" acetate sleeve, cont'g core Hand auger	1 OF 1
	DRILLING
SURFACE CONDITIONS:	START TIME: 0843 DATE: 5-13-03
0.5' Concrete	FINISH TIME: 0903 DATE: 5-13-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							0	A/C
							1	CL
							2	
		0842			0.1	SSS01707		
							3	SM
		0852			239			
							4	
		0857			50.1		5	
							6	
							7	
							8	
							9	
							10	

Concrete

Brown sandy CLAY w/ gravel and trace silt

- rust stains, orange

Olive-brown silty very fine-fine SAND w/ little clay, faint to mod. diesel odor

- Becomes some clay

Boring completed to @ 5.1' on 5-13-03

BY Mark Wheeler DATE 5-13-03 CHECKED BY PCM

BORING LOG

LOCATION OF BORING



JOB NUMBER	LOCATION (Philadelphia)
28906318.01000	APN 7351-33-37

DRILLING METHOD:	BORING NUMBER
Mark M25 vibratory hammer Hand Auger	SBL0312
SAMPLING METHOD:	SHEET
1.5" acetate sleeve, continuous core 2" Brass sleeve, manual drive	1 OF 1
	DRILLING
	START / FINISH
SURFACE CONDITIONS:	TIME: 0920 / 0948
0.25' Asphalt ~~Concrete~~	DATE: 5-13-03 / 5-13-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								GM	Very dark grayish-brown (10YR, 3/2) silty GRAVEL
							1		
								CL	Dark yellowish-brown (10YR, 4/6) and olive-brown CLAY w/ fine sand and silt,
		0928			0.1	SS501768	2		
							3		
		0934					4		
		0941			1.1				-Becomes olive
					1.5		5		
									Boring completed to 5.0' on 5-13-03
							6		
							7		
							8		
							9		
							10		

BY Mark Wanek DATE 5-13-03 CHECKED BY DLM

BORING LOG

LOCATION OF BORING: Refrigeration Units (concrete pad)



DATUM... ELEVATION

DRILLING CONTRACTOR Gregg

BY Mark Ulanke DATE 5-13-03 CHECKED BY PLM

JOB NUMBER	LOCATION
28906318.01000	APN 7351-33-34

DRILLING METHOD:	BORING NUMBER
Mark M25 vibratory hammer Hand Auger	SBLO313

SAMPLING METHOD:	SHEET
1.5" acetate sleeves, cont's core 2" Brass sleeve, Manual drive	1 OF 2

SURFACE CONDITIONS:	DRILLING START TIME	DRILLING FINISH TIME
0.25' Asphalt	1005	1045
	DATE 5-13-03	DATE 5-13-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								SM	Very dark grayish-brown (10 YR. 3/2) silty fine SAND w/ gravel
							1	CL	Brown fine sandy CLAY w/ trace gravel, damp, med stiff - stiff
		1010			4.9		2		
							3		
								SM	to fine Olive-brown silty very fine SAND, moist, dense
	4.0 / 3.2	1030 1024					4		
									f. very faint styrene odor
							5		- root casts faint, moderate odor, no ground staining
					20.7				
							6		
					92.5		7		
	4.0 / 3.3	1036			141 20.7		8		- Odor chemical odor becomes strong; root casts v. very faint, decreased silt
							9		
		1036			1607	SSS01769	10		

BORING LOG

LOCATION OF BORING

JOB NUMBER: 289063I8.01000

LOCATION: APN 7351-33-34

DRILLING METHOD: Mark II 25 vibratory hammer, Hand auger

BORING NUMBER: SBL0313

SAMPLING METHOD: 1.5" acetate sleeves, cont's core; 2" brass sleeve, manual drive

SHEET: 2 OF 2

DRILLING: START TIME 1005 DATE 5-13-03; FINISH TIME 1045 DATE 5-13-03

SURFACE CONDITIONS: 0.25' Asphalt

DATUM... ELEVATION

DRILLING CONTRACTOR Gregg

BY Mark Wanek DATE 5-13-03 CHECKED BY DUM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							10	SM
					994		11	
								ML
	4.0 / 3.8	1640					12	
							13	
							14	SM
							15	
							16	
							17	
							18	
							19	
							20	

Light olive-brown gravelly SILT w/ very fine sand, mottled rust-colored root casts, moist, dense, strong VOC odor, no staining

- Becomes no gravel
- Becomes sandy w/ trace clay

Olive-brown silty very fine SAND w/ trace clay, moist, dense, root casts, strong VOC odor,

Boring completed to ~16' on 5-13-03

BORING LOG

LOCATION OF BORING



JOB NUMBER	LOCATION
289063/8.01000	APN 7351-33-34

DRILLING METHOD:	BORING NUMBER
Mod M25 vibratory hammer Hand Auger	SBL0314
SAMPLING METHOD:	SHEET
1.5" acetate sleeves cont's core 2" brass sleeves	1 OF 2
	DRILLING START TIME 1100 DATE 5-13-03 / FINISH TIME 1135 DATE 5-13-03
SURFACE CONDITIONS:	
0.25' asphalt	

DATUM... ELEVATION

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/c	Asphalt
								SM	Very dense grayish-brown (10YR 3/2) silty, med. SAND w/ gravel, moist, med. dense
							1	CL	Brown silty CLAY w/ fine sand & trace gravel, moist, stiff
		1105			57.1		2		
					31.3	SS501770		SC	Olive-brown clayey, fine SAND w/ silt, moist, dense, root casts apparent & not apparent odor or staining
							3		
	4.0 / 3.5	1128			13.0		4	SM	~~Be~~ Dark yellowish-brown (10YR 4/6) silty fine to SAND w/ trace clay, moist, dense root casts apparent
							5		
					15.3		6		-Becomes decreased silt, lighter yellowish-brown (10YR 3/6), faint chem. odor
							7		
					2.2				
									to light
	4.0 / 2.8	1132			32.1		8		-Becomes Olive-brown, moderate chem. odor
							9		- Becomes Olive from 9.4-9.8 - Becomes little silt, fine-med. grained, loose-med dense
					28.8		10		

BY Mark Wanek DATE 5-13-03 CHECKED BY DLM

BORING LOG

LOCATION OF BORING

DATUM... ELEVATION

JOB NUMBER	LOCATION
2890618.01000	APN 7351-33-34

DRILLING METHOD: Mod. MS5 vibrating hammer; Hand Auger

BORING NUMBER: SBL0314

SAMPLING METHOD: 1.5" Acetate liners, ctd. on; 2" Brass sleeve, manual drive

SHEET: 2 OF 2

DRILLING: START TIME 1100 DATE 5-13-03; FINISH TIME 1135 DATE 5-13-03

SURFACE CONDITIONS: 0.25' Asphalt

DRILLING CONTRACTOR Gregg

BY Mark Wauck DATE 5-13-03 CHECKED BY DLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							10	SM
					1.7		11	
	4.0 / 3.2	1134					12	
					~~1000~~ 35.9		13	ML
					35.9		14	
							15	
							16	
							17	
							18	
							19	
							20	

- Becomes some silt, darker olive-brown

- Becomes light olive-brown, silty, very fine ~~SAND~~ sand, root casts, dense, moderate chem odor

light olive-brown very fine sandy SILT, moist, dense, root casts

- Gypsum inclusions

- olive-gray clayey inclusions, decreased sand

Boring Completed to ~16' on 5-13-03

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION (Parc Bell)
28906318.01000	APN 7351-33-20

DRILLING METHOD:	BORING NUMBER
~~Mart #425 vibrating hammer~~ Hand Auger	SBL0315
SAMPLING METHOD:	**SHEET**
~~Mart #425 sampler sleeves, etc~~ 2" brass sleeve	1 OF 1

SURFACE CONDITIONS:	DRILLING START TIME	DRILLING FINISH TIME
0.25' Asphalt	1300	1315
	DATE 5-13-03	DATE 5-13-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							0	A/C
								CL
							1	
		1305			9.9	SS501771	2	
		1310			3.5		3	
							4	
		1315			2.4			
							5	
							6	
							7	
							8	
							9	
							10	

A/C Asphalt

CL Dark yellowish-brown (10YR, 4/6) ~~sandy~~ and brown sandy CLAY w/ trace silt and ~~trace~~ gravel

-Becomes brown to olive-brown, decrease in sand

-Becomes brown and dark reddish-brown

Boring completed to 4.9' on 5-13-03

BY Mark Wanek DATE 5-13-03 CHECKED BY DLM

BORING LOG

LOCATION OF BORING



DATUM... Green ELEVATION

JOB NUMBER	LOCATION (Pac Bell)
28906318.01000	APN 7351-33-20

DRILLING METHOD:	BORING NUMBER
Hand Auger	SBL0316
SAMPLING METHOD:	SHEET
2" Brass Sleeves / manual drive	1 OF 1
	DRILLING

SURFACE CONDITIONS:	START TIME	FINISH TIME
0.35' Asphalt	1340	1355
	START DATE	FINISH DATE
	5-13-03	5-13-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							0	A/C
								SC
							1	
		1341			2.3	SSS01772	2	
		1344			2.0			
							3	
							4	
		1353			1.7		5	
							6	
							7	
							8	
							9	
							10	

A/C Asphalt

SC Olive-brown clay and brown clayey fine SAND w/ silt and trace gravel

~Becomes olive-brown

Boring completed to 5.1' on 5-13-03

BY Mark Wanek DATE 5-13-03 CHECKED BY DLM

BORING LOG

LOCATION OF BORING — Asphalt Parking — 0 10 ~~45~~ 20



DATUM... Pac Bell Bldg — ELEVATION

JOB NUMBER	LOCATION (Pac Bell)
28906318.01000	APN 7351-33-20

DRILLING METHOD:	BORING NUMBER
Hand auger	SBL0317
SAMPLING METHOD:	SHEET
2" Brass sleeve/manual drive	1 OF 1
	DRILLING START / FINISH
SURFACE CONDITIONS:	TIME: 1413 ~~1529~~ / 1430 ~~1556~~
Grass	DATE: 5.13.03 / 5.13.03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							0	SC
						SS01773	1	
		1415 ~~1526~~			2.6		2	
		~~1537~~					3	
		1425			0.4		4	
							5	
							6	
							7	
							8	
							9	
							10	

Brown clayey fine SAND, wet, Med. dense.

- Becomes dark yellowish-brown

- Becomes brown

Boring Completed to 5.0' on 5-13-03

BY Mark Wenek DATE 5-13-03 CHECKED BY PLM

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION
28906318.01000	APN 7351

DRILLING METHOD: Hand Auger; Mark MZ5 vibratory hammer

BORING NUMBER: SBL0318

SAMPLING METHOD: 2" Brass sleeves / Immacted liner; 1.5" acetate sleeves / continuous cores

SHEET: 1 OF 2

SURFACE CONDITIONS: 0.25' Asphalt

DRILLING START	DRILLING FINISH
TIME 1525	TIME 1550
DATE 5.13.03	DATE 5.13.03

DRILLING CONTRACTOR Gregg

BY Mark Wanke DATE 5-13-03 CHECKED BY DUM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Brown silty CLAY w/ trace very fine + fine sand
							1		
		1526			2.6	SS501774	2		
							3		
								silt	Olive-brown silty fine SAND w/ trace clay. Moist, dense, ~~wet roots~~
	4.0 / 4.0	1538					4		
					0.1		5		Rock coats appear
							6		
					0.1				
		1538			0.3	SS501775	7		
	4.0 / 3.7	1540			1.1		8		
							9		← gypsum inclusion
									- Becomes olive, very fine sand, increased silt
					1.7		10		- Becomes olive-brown, gypsum inclusions

BORING LOG

LOCATION OF BORING

DATUM... ELEVATION

JOB NUMBER	LOCATION
28906318.01000	APN 7351-

DRILLING METHOD: Mark M25 vibrating hammer; Hand Auger

BORING NUMBER: SBL0318

SAMPLING METHOD: 2" Brass sleeve/ custom manual slide; 1.5" acetate liners / continuous core

SHEET: 2 OF 2

SURFACE CONDITIONS: 0.25' Asphalt

DRILLING START TIME	DRILLING FINISH TIME
1585	1550
DRILLING START DATE	DRILLING FINISH DATE
5.13.03	5-13-03

DRILLING CONTRACTOR Gregg

BY Mark Wenk DATE 5-13-03 CHECKED BY Plm

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							10	SM	
							11		
					0.1			ML	Olive light olive-brown sandy SILT w/ some gravel, moist, dense, root casts prominent
							12		
	4.0 / 3.3	1545			0.1				
							13		- Becomes increased sand
							14		- Becomes olive-brown w/ trace clay
					0.8			SM	Olive-brown silty, very fine SAND w/ trace clay, gypsum inclusions
							15		
					0.6				
							16		
									Boring completed to ~16' on 5-13-03
							17		
							18		
							19		
							20		

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION (DVS shoes)
28906318.01000	APN 7351-34-65

DRILLING METHOD:	BORING NUMBER
~~Hand~~ Auger to 5.2'	SBL0319
Mar M25 vibrating hammer	
SAMPLING METHOD:	SHEET
3" Brass sleeve / manual drive	1 OF 2
1.5" Acetate liners, cuttis core	DRILLING

SURFACE CONDITIONS:	START TIME	FINISH TIME
	1600	1620
0.3' Asphalt	START DATE	FINISH DATE
	5.13.03	5.13.03

DRILLING CONTRACTOR Gregg

BY Mark Wurcel DATE 5-13-03 CHECKED BY DLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	
								SM	Very dark grayish-brown (10YR 3/2) silty fine SAND w/ gravel, moist, loose - med. dense
							1		
		1601			1.2	SSS01776	2	SC	Brown (10YR 4/3) to dark yellowish-brown (10YR 4/6) clayey fine SAND w/ silt & trace gravel
							3		
	4.0 / 3.3	1613					4	SM	Dark brown (10YR) to dark yellowish-brown (10 YR 4/6) silty fine SAND w/ little clay
					1.2		5		
					0.5		6	SW	Yellowish-brown very fine-coarse SAND, wet, loose (fill?)
								SM	Olive-brown (2.5Y) silty, very fine-fine SAND, moist, dense; gypsum inclusions, root casts
		1613			0.5	SSS01777	7		↳ Becomes light olive-brown (2.5Y) gravelly w/ increased silt
							8		
	4.0 / 3.8	1616			0.1				
							9		~~Brown~~ w/ clay
					0.2		10		~Cobbles to ~0.1' diam.

BORING LOG

LOCATION OF BORING

DATUM... ELEVATION

DRILLING CONTRACTOR Cregg

BY Mark Wanek CHECKED BY DCM

DATE 5-13-03

JOB NUMBER	LOCATION
28906318.01000	APN 7351-34-65 (DVS shown)

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.2' Mori M25 vibratory hammer	SBL0319
SAMPLING METHOD:	SHEET 2 OF 2
2" Brass sleeves / manual drive 1.5" acetate liners / continuous core	DRILLING START / FINISH
SURFACE CONDITIONS:	TIME: 1600 / 1620
0.3' Asphalt	DATE: 5-13-03 / 5-13-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							10	SM	Becomes olive-brown (2.5Y, 4/4) no gravel or gypsum, root casts
					0.1		11		
	4.0 / 3.8	1618			0.5		12	CL	Olive-brown CLAY w/ trace - Becomes sandy
							13	SM	Olive-brown silty very fine SAND, damp w/ trace clay, moist, dense, root casts
					0.1		14		- root casts prominent
							15		- trace gravel
					0.1		16		- Becomes mottled w/ rust color, gypsum increased silt
							17		Boring completed to ~16' on 5-13-03
							18		
							19		
							20		

BORING LOG

LOCATION OF BORING



DATUM... Scale 1"=40'

ELEVATION

JOB NUMBER	LOCATION (ENOVA)
28906518.01000	APN 7351-34-05

DRILLING METHOD:	BORING NUMBER
Hand auger to 5.1'	SBLO320
Mar 1425 vibratory hammer	
SAMPLING METHOD:	SHEET 1 OF 2
1.5" Acetate sleeves, dedicated one	
2" brass sleeves / Manual drive	DRILLING START / FINISH
SURFACE CONDITIONS:	TIME 0725 / 0800
0.3' Asphalt	DATE 5-14-03 / 5-14-03

DRILLING CONTRACTOR Gregg

BY Mark Wheeler DATE 5-14-03 CHECKED BY DCM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								SC	~~Fill~~ Dark yellowish-brown (10 YR, 4/4) clayey SAND, moist, dense (SC)
							1		
		0731			0.0	SS501778	2		
							3		
							4		
	4.0 / 3.4	0747							
							5		
					0.1				- Root casts apparent (faint)
					0.1		6		
							7	SM	Dark yellowish-brown (10 YR, 4/4) silty very fine SAND, moist dense, (SM) to fine
					0.1				
							8		- Becomes med. dense
	4.0 / 3.9	0750			0.1				- Becomes dense, root casts
							9		
					0.1		10		- Becomes light olive-brown (2.5Y, 5/6) little trace clay, gypsum

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION (CENOVA)
28906318.01000	APN 7351-34-~~69~~ 65

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.1'	SBL0320
Mart 1425 Vibrating Hammer	
SAMPLING METHOD:	**SHEET**
2.5" Acetate sleeves, cont's core	2 OF 2
2" Brass sleeve / manual driver	**DRILLING**
	START / FINISH
SURFACE CONDITIONS:	TIME: 0725 / 0800
0.3' Asphalt	DATE: 5-14-03 / 5-14-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							10	SM	
									- Becomes no clay
							11		
									- Becomes little clay
					0.1		12		
	4.0 / 3.8	0756			0.1				- Gravel from 12.7-12.9'
							13	SC	Light olive-brown (2.5Y, 5/4) clayey, fine SAND w/ silt, moist, dense, root casts prominent Some gypsum
					0.1		14		
									- Roots casts very prominent
							15		
					0.1		16		Boring completed to 16' on 5-14-03
							17		
							18		
							19		
							20		

BY Mark Edwards DATE 5-14-03 CHECKED BY DLA

BORING LOG

LOCATION OF BORING



JOB NUMBER	LOCATION (DVS Shoes)
289063 18.01000	APN 7351-34-65

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.2'	SBL0321
Mail M25 Vibratory Hammer	
SAMPLING METHOD:	SHEET
1.5" acetate sleeves, cont's core	1 OF 2
2" Brass sleeves, manual drive	DRILLING
	START / FINISH
SURFACE CONDITIONS:	TIME: 0825 / 0853
0.3' Asphalt	DATE: 5-14-03 / 5-14-03

DRILLING CONTRACTOR Cal-Eng

BY Mark Wanek DATE 5-14-03 CHECKED BY PCM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Dark brown (10 YR 3/3) silty CLAY w/ fine sand and trace gravel, moist, stiff
							1		- Becomes some gravel
		0826			0.1		2		
							3		- Large rock
								SC	Light olive-brown (2.5Y, 5/4) clayey fine SAND w/ silt, moist, dense
	4.0 / 3.7	0846			9.6 / ~~31.6~~		4		
							5		- Decreased clay
									- Becomes increased silt, gypsum inclusions
							6	SM	Light olive-brown (2.5Y, 5/4) silty, fine SAND w/ little clay, moist, dense, root casts
					10.1				- Large root casts (~0.2' long), root particles
							7		
					6.1				- Becomes gravelly (chert gravel) from 7.5-7.7'
							8		- Becomes no clay
	4.0 / 3.8	0850			61.3				
						SSS01779	9		
									- Becomes gravelly from ~9.4-9.7' (chert gravel)
					1.9		10		Becomes little clay

BORING LOG

LOCATION OF BORING

DATUM... ELEVATION

JOB NUMBER	LOCATION
289063 18.01000	APN 7351-34-65

DRILLING METHOD: Hand Auger to 5.2'
☒ Mari auto vibratory hammer

BORING NUMBER: SB10321

SAMPLING METHOD: 1.5" acetate liners / cuts core
2" Brass sleeve / manual drive

SHEET: 2 OF 2

SURFACE CONDITIONS: 0.3' Asphalt

DRILLING START TIME	DRILLING FINISH TIME
0825	0855
DATE	DATE
5-14-03	5-14-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							10	SM
							11	
					20.3		12	
	4.0 / 3.8	0853			2.4			
							13	SC
					0.5		14	
							15	
					9.6		16	
							17	
							18	
							19	
							20	

SM
- Trace gravel
- Becomes trace clay, root casts prominent

SC
Olive-brown (2.5Y 4/3) clayey fine SAND w/ some silt, moist, dense, root casts prominent,

- Mottled w/ 1:1 Fe gypsum

- Trace gravel

Boring completed to ~16' on 5-14-03

BY Mark Wilson CHECKED BY Dan

DATE 5-14-03

BORING LOG

LOCATION OF BORING





JOB NUMBER	LOCATION (DVS Shoes)
28906318.01000	APN 7351-34-695

DRILLING METHOD:	BORING NUMBER
Hand Auger to 6.0'	SBL0322
Mari MS5 vibrating hammer	
SAMPLING METHOD:	SHEET 1 OF 2
1.5" acetate sleeves / continuous core	DRILLING START / FINISH
2" brass sleeve / manual drive	TIME 0925 / 1006
SURFACE CONDITIONS:	DATE 5-14-03 / 5-14-03
0.3' Asphalt	

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	
								CL	Very dark grayish-brown (10 YR 3/2) and olive-brown (2.5Y, 4/3) CLAY w/ trace silt and very fine sand, damp, very stiff
		0930			0.8	SS501780	1		
							2		
							3		
	4.0 / 3.7	0954					4	SM	Yellowish-brown (10 YR, 5/4) silty, very fine - fine SAND w/ some clay, moist, med. dense
							5		
					0.3		6		- Root casts prominent
					0.1		7	drive	
						SS501781			- Becomes olive-brown (2.5Y, 4/4), trace clay
					0.4		8		root casts faint, no clay
	4.0 / 3.3	0957			0.1				- Becoming
							9		
					0.1		10		- Pale yellow (2.5Y, 7/3) gravelly silt from 10.2 - 10.5

BY Mark Wanek DATE 5-14-03 CHECKED BY Dan

BORING LOG

LOCATION OF BORING

DATUM... ELEVATION

JOB NUMBER	LOCATION (DVS sheet)
28906318.01000	APN 7351-34-65

DRILLING METHOD: Hand auger to 6.0'; Mori M25 vibrating hammer

BORING NUMBER: SBLO 322

SAMPLING METHOD: 1.5" acetate sleeves, continuous core; 2" brass sleeves manual drive

SHEET: 2 OF 2

SURFACE CONDITIONS: 0.3' Asphalt

DRILLING: START TIME 0925, DATE 5-14-03; FINISH TIME 1006, DATE 5-14-03

DRILLING CONTRACTOR Cascade

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							10	SM
							11	
					0.1			
							12	SC
	4.0 / 3.1	1000			0.1			
							13	
					0.1			
							14	
					0.1			
							15	
							16	
							17	
							18	
							19	
							20	

- Pale yellow (2.5Y, 7/3) gravelly, silt from 2.0-10.5'

- Becomes light olive-brown (2.5Y, 5/4) w/ some clay

- Trace gravel

Light olive-brown (2.5Y 5/4) clayey fine SAND w/ silt, moist, dense, root casts

Becomes

- trace gravel

- Root casts faint

Boring completed to ~16' on 5-14-03

BY Wade Wanke DATE 5-14-03 CHECKED BY DLM

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION (ENOVA)
289063 18.01000	APN 7351-34-65

DRILLING METHOD:	BORING NUMBER
Hand auger to 4.5'	SBLO323
Mari M25 vibratory hammer	
SAMPLING METHOD:	SHEET
1.5" acetate sleeve, continuous	1 OF 2
2" Brass sleeve / manual drive	DRILLING START TIME 1025 DATE 5-15-03 / FINISH TIME 1100 DATE 5-15-03
SURFACE CONDITIONS:	
0.5' asphalt	

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	
							1	GM	
		1020			0.1		2	CL	Dark yellowish-brown (10YR, 4/4) sandy CLAY w/ silt, moist, stiff
							3		-Becomes trace gravel
	4.0 / 3.8	1047			10.5	SS501794	4	SM	-Becomes olive-gray (5Y, 4/2), petrochemical odor & staining; Moderate silty fine SAND w/ little clay & trace gravel
							5		-Becomes olive-brown (2.5Y, 4/3) w/ gray med. Sand inclusions, some gravel
							6		-Becomes trace clay -Becomes olive-gray (5Y, 4/2)
					5.2		7		-Becomes dark yellowish-brown (10YR, 4/4), little or no a -Becomes strong brown (7.5YR, 4/6)
							8	CL	strong brown (7.5YR 4/6) sandy CLAY w/ silt, moist, med. stiff -Becomes olive-brown (2.5Y, 4/3)
					1.0		9		
	4.0 / 3.7	1054			0.1				-Becomes darker (2.5Y, 4/4), root casts appear
					0.1		10		

BY Mark Wineh DATE 5-15-03 CHECKED BY DLM

BORING LOG

LOCATION OF BORING

JOB NUMBER 28906318.01000

LOCATION ENOVA APN 7351-34-65

DRILLING METHOD: Hand auger to 4.5' Mari 425 vibratory hammer

BORING NUMBER SBL0323

SAMPLING METHOD: 1.5" acetate sleeves, continuous core 2" Brass sleeve / manual drive

SHEET 2 OF 2

DRILLING CONTRACTOR Gregg

DATUM... ELEVATION

SURFACE CONDITIONS: 0.5' asphalt

DRILLING START TIME 1025 DATE 5-15-03

DRILLING FINISH TIME 1100 DATE 5-15-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							10	CL	
									- Becomes gravelly
							11	SM-ML	- Becomes light olive-brown (2.5Y 5/3) silty, very fine SAND, moist, very dense, fair root casts
					0.1		12		
	4.0/3.0	1056			0.1		13		- Becomes increased silt
					0.1		14		
					1.8		15		
							16		
							17		Boring Completed to ~16.5' on 5-15-03
							18		
							19		
							20		

BY Mark Wenke CHECKED BY Plan

DATE 5-15-03

DAMES & MOORE

BORING LOG

LOCATION OF BORING



JOB NUMBER	LOCATION (REMOVAL)
~~289735~~ 289063/8.01000	APN 7351-34-#65

DRILLING METHOD:	BORING NUMBER
Hand auger to 3.0'	
Mud MZ5 vibratory hammer	SBL0324
SAMPLING METHOD:	SHEET
1.5" acetate sleeves	1 OF 2
2" Brass sleeve/casual drive	DRILLING
	START / FINISH
SURFACE CONDITIONS:	TIME: 1115 / 1215
0.5' asphalt	DATE: 5-15-03 / 5-15-03

DRILLING CONTRACTOR Cascade

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							0	
								A/C
							1	SM
							2	CL
		1117			0.4			
							3	SC
	4.0 / 3.0	1159			8.8			
								SM
					11.3		4	
							5	
					11.8	55501795	6	
							7	
	4.0 / 3.6	1204			4.1			
							8	
					12.8		9	
							10	
					2.8			

Asphalt

Very dark grayish-brown (10YR 3/2) silty, fine-med SAND w/ gravel & trace clay.

Very dark grayish-Olive-brown (2.5Y, 4/3) and brown (2.5Y, 3/2 CLAY w/ sand and ~~trace~~ some gravel

Olive-brown ~~mott~~ (2.5Y, 4/3) ~~and~~ clayey, very fine SAND w/ trace gravel, moist, dense, petroleum odor

Dark olive-gray (5Y, 3/2) silty very fine SAND ~~mod~~ moist, med. dense, moderate odor & staining

- Becomes olive (5Y, 4/3)

- Becomes dark olive-gray (5Y, 3/2)

- Trace gravel from 8.9-9.0

- Trace gravel from 9.5-9.6
Increased silt, gypsum

- Gravelly from 10.3-10.5

BY Mark Wanek DATE 5-15-03 CHECKED BY Dm

BORING LOG

LOCATION OF BORING

JOB NUMBER	LOCATION
28906318.01000	APN 7351-34-65

DRILLING METHOD: Hand auger to 3.0'; Mark M25 vibratory hammer

BORING NUMBER: SB10324

SAMPLING METHOD: 1.5" acetate sleeves, continuous core; 2" lexan sleeves, manual drive

SHEET: 2 OF 2

DRILLING: START TIME 1115 DATE 5-15-03; FINISH TIME 1215 DATE 5-15-03

SURFACE CONDITIONS: 0.5' Asphalt

DRILLING CONTRACTOR Gregg

DATUM... ELEVATION

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							10	SM
					2.8			
	4.0 / 3.8	1209			2.7		11	CL
							12	
					2.4		13	
							14	
					10.0		15	
							16	
							17	
							18	
							19	
							20	

Dark olive-gray (5Y, 3/2) CLAY w/ silt and little very fine sand, moist, med. stiff, slight odor, mod. staining.

- Trace gravel, gypsum

- Becomes olive-gray (5Y, 4/2)
- 0.1' gravelly clay

Boring completed to ~15' on 5-15-03

BY Mark Wenck CHECKED BY DLM

DATE 5-15-03

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION
28906318.01000	(Douglas) APN 7351-34-64

DRILLING METHOD:	BORING NUMBER
Hand auger to 5.7'	
Mari M25 vibratory hammer	SBL0325
SAMPLING METHOD:	SHEET
2" Brass sleeve / manual drive	1 OF 2
1.5" acetate liner, continuous core	DRILLING

SURFACE CONDITIONS:	START TIME	FINISH TIME
0.3' Asphalt	1215	1250
	DATE	DATE
	5-14-03	5-14-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Very dark grayish-brown (10YR, 3/2) sandy clay w/ little silt, moist,
							1		
		1220			0.1	SS501782	2		
							3		
	4.0 / 3.8	9 1233			0.1		4		- Becomes dark yellowish-brown (10YR, 4/4)
							5		- Brick fragments - Becomes increased sand, fine-med. grained
					0.5		6		
							7		
					0.1	SS501783		SC	Dark yellowish-brown (10YR, 4/4) clayey very fine SAND, ~~wet~~ moist, med. dense
							8		
	4.0 / 3.1	1245 1239			0.2			SM	Olive-brown (2.5Y, 4/4) silty, fine SAND moist, dense, faint root casts
							9		
					0.9		10		- Becomes gravelly from 10.1 – 10.3 feet

BY Mark Wenek DATE 5-14-03 CHECKED BY [illegible]

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER: 28906318.01000

LOCATION (Dongkuk): APN 7351 - 34 - 004

DRILLING METHOD: Hand Auger to 5.7'; Mar/ MZ5 vibratory hammer

BORING NUMBER: SBL0325 SBL0235

SAMPLING METHOD: 1.5" acetate sleeves, cont's core; 2" Brass sleeves / manual drive

SHEET: 2 OF 2

DRILLING: START TIME 1215, FINISH TIME 1250; START DATE 5-14-03, FINISH DATE 5-14-03

SURFACE CONDITIONS: 0.3' Asphalt

DATUM... ELEVATION

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							10	SM	
					0.7		11	CL	Light olive-brown (2.5Y, 5/4) SM silty CLAY w/ some very fine SAND
								SM	
	4.0 / 2.8	1248			2.0		12		Olive-brown (2.5Y, 4/4) silty very fine SAND, moist med. dense
							13		
					0.2				
							14		Becomes - Trace gravel
					0.4				- root casts prominent
							15		
							16		Boring completed to ~16' on 5.14.03
							17		
							18		
							19		
							20		

BY Mark Wanek DATE 5-14-03 CHECKED BY Dan

DAMES & MOORE

BORING LOG



JOB NUMBER	LOCATION (NS1)
28906318.01000	APN 7351-34-76

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.3'	
Mart MZ5, vibratory hammer	SBL0326
SAMPLING METHOD:	SHEET
1.5" Acetate liners, continuous core	1 OF 2
2" Brass sleeve / manual drive	DRILLING

SURFACE CONDITIONS:	START TIME	FINISH TIME
0.45' Asphalt	1450	1520
	DATE	DATE
	5-14-03	5-14-03

DRILLING CONTRACTOR Gregg

BY Mark Wenek DATE 5-14-03 CHECKED BY DCM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
							1	CL MW SM	~~Grayish-b~~ mw Yellowish-brown (10YR 5/4) and light brownish-gray (10YR 6/2) silty fine sand w/ trace clay, moist, med. dense
							2	CL	dark Dark grayish-brown (10YR 4/2) and yellowish-brown (10YR 4/6) CLAY w/ fine sand & some silt, moist, soft
		1456			0.4	SSS01784			
	4.0/3.7	1510			mw		3		
							4		
							5		
					0.2		6		
							7		
					1.3	SSS01785			
					0.5		8		
	4.0/3.7	1513			1.2				
							9		
					0.3			SM	Light olive-brown (2.5Y, 5/4) silty very fine SAND, moist, dense, faint root casts
							10		
					1.2				

BORING LOG

LOCATION OF BORING

DATUM... ELEVATION

JOB NUMBER	LOCATION
28906318.010000	APN 7351-34-76

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.3' Mart 1425 vibratory hammer	SBL0326
SAMPLING METHOD:	SHEET 2 OF 2
1.5" acetate sleeves, 2" brass sleeve / manual drive	DRILLING START TIME 1450 DATE 5-14-03; FINISH TIME 1520 DATE 5-14-03
SURFACE CONDITIONS: 0.45' Asphalt	

DRILLING CONTRACTOR Gregg

BY Mark Wanek DATE 5-14-03 CHECKED BY DLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
								SM	
					1.2		10		
							11		
	4.0 / 2.4	1516			0.1		12		- Becomes trace clay
									- Trace ~~clay~~ gravel, diminished bioturbation
							13		
									Becomes
									- Trace gravels, increased bioturbation
					0.2		14		
							15		
							16		Boring completed to ~16' on 5-14-03.
							17		
							18		
							19		
							20		

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION
28906318.01000	(NSI) APN 7351-34-76

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.2' Mari M25 vibratory hammer	SBL0327
SAMPLING METHOD:	SHEET
1.5" acetate liners / continuous core 2" Brass sleeve / manual drive	1 OF 2
	DRILLING START TIME 1525 DATE 5-14-03 / FINISH TIME 1645 DATE 5-14-03
SURFACE CONDITIONS: 0.3' Asphalt	

DRILLING CONTRACTOR Gregg

BY Mark Lukert CHECKED BY DLM DATE 5-14-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
							1	CL	Very dk brown (10YR,) and brown (10YR,) silty CLAY w/ little fine sand, moist, stiff
						MW	2		- Becomes some fine sand,
		1530			0.5	SS501786			
	4.0 / 3.7	1632					3		
					0.6		4		
					1.6		5	SM	Dark yellowish-brown (10YR 4/6) silty fine SAND moist, dense - very dense, faint root casts, gypsum
					0.3	SS501787	6		
	4.0 / 3.8	1634			0.1		7		
							8	SP	Yellowish-brown (10YR, 5/8) fine SAND w/ trace silt, moist, loose - med. dense
							9		
							10	SM	(sharp contact) Dark greyish-brown (10YR, 4/2) silty very fine - fine sand, moist, very dense, heavily bioturbated
					1.0 MW				

DAMES & MOORE

BORING LOG

LOCATION OF BORING

DATUM... ELEVATION

DRILLING CONTRACTOR Gregg

BY Mark Wanek CHECKED BY DMM

DATE 5-14-03

JOB NUMBER	LOCATION (NSI)
28906318.01000	APN 7351-34-76

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.2'	
Mobil M25 vibratory hammer	SBL0327
SAMPLING METHOD:	SHEET
1.5" acetate sleeves, continuous core	2 OF 2
2" Brass sleeve, manual drive	DRILLING

SURFACE CONDITIONS:	START TIME	FINISH TIME
0.3' Asphalt	1525	1645
	DATE	DATE
	5-14-03	5-14-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							10	SM
							11	
					1.0		12	
	4.0 / 3.2	1640			0.4			
							13	
							14	
					0.1		15	
							16	
							17	
							18	
							19	
							20	

- trace gypsum
- Becomes brown (7.5Y, 4/3) w/ some clay
- decreased bioturbation

Boring completed to ~16' on 5-14-03

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... 0 30 ELEVATION

JOB NUMBER	28906318.01000
LOCATION	(NSI) APN 7351-34-76
DRILLING METHOD:	Hand auger to 5.0' Mari M25 vibratory hammer
BORING NUMBER	SBL0328
SAMPLING METHOD:	1.5" acetate sleeves, cont. core 2" brass sleeve / ~~Dpt~~ manual drive
SHEET	1 OF 2
SURFACE CONDITIONS:	0.3' Asphalt
DRILLING START TIME	1650
DRILLING FINISH TIME	1715
DRILLING START DATE	5-14-03
DRILLING FINISH DATE	5-14-03

DRILLING CONTRACTOR Gregg

BY Mark Wample DATE 5-15-14-03 CHECKED BY DLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Brown & dark brown CLAY w/ some silt and fine sand
							1		
							2		
		1650			0.1	55501788			
							3		
							4		
	4.0 / 3.7	1704							
					0.1		5		
								SM	(sharp contact)
					0.1		6		Yellowish-brown (10YR, 5/4) silty very fine SAND with trace clay, moist, dense; root casts
							7		-Becomes no clay
						55501789			
					0.1				
	4.0 / 3.3	1708			0.1		8		-Becomes olive-brown (2.5Y, 4/4), trace clay
							9		-gypsum inclusions
					0.2				
							10		bio- -no gypsum, heavily turbated

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER: 28906318.01000

LOCATION (NSI): APN 7351-54-76

DRILLING METHOD: Hand auger to 5.0'; Mod M25 vibratory hammer

BORING NUMBER: SB20328

SAMPLING METHOD: 1.5" acetate sleeves, cts core; 2" Brass sleeves / Mangeldrive

SHEET: 2 OF 2

DRILLING: START TIME 1650, DATE 5-14-03; FINISH TIME 1715, DATE 5-14-03

SURFACE CONDITIONS: 0.3' Asphalt

DATUM... ELEVATION

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							10	SM
							11	
					0.1			
							12	
	4.0 / 3.0	1712			0.1			
							13	
					0.1			
							14	
					0.1			
							15	
							16	
							17	
							18	
							19	
							20	

- 0.1' of light yellowish-brown (10YR, 6/4) silty gravel
- root casts faint, decreased silt

Boring Completed to ~16' on 5-15-03

BY Mark Wheet DATE 5-14-03 CHECKED BY DCM

DAMES & MOORE

BORING LOG

LOCATION OF BORING



JOB NUMBER	LOCATION (19831 Magellan - Irvine)
28906318.01000	APN 7351-34-45

DRILLING METHOD:	BORING NUMBER
Hand auger to 5.1'	
Mark 1125 vibratory hammer	SBL0329
SAMPLING METHOD:	SHEET
1.5" acetate sleeves / cont's core	1 OF 2
2" Brass sleeve / Manual drive	DRILLING

SURFACE CONDITIONS:	START TIME	FINISH TIME
0.25' Asphalt	0740	0815
	DATE 5-15-03	DATE 5-15-03

DRILLING CONTRACTOR Gregg

BY Mark Wenek DATE 5-15-03 CHECKED BY DLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Dark yellowish-brown (10YR 4/4) CLAY w/ little silt & trace fine sand and gravel, moist, stiff
		0744			0.1	SSS01790	1		
							2		- cobbles to 0.1' diam.
								SC	Dark yellowish brown (10YR 4/6) clayey fine SAND, moist, med. dense
							3		
	4.0 / 3.8	0804					4		
					0.1		5		
								SM	- Becomes light olive-brown (2.5Y, 5/4), root casts appear
					0.1		6		Light olive-brown (2.5Y, 5/4) silty fine SAND w/ trace clay, moist, dense, faint root casts
						SSS01791	7		
					1.2				
	4.0 / 3.0	0806			0.1		8		- Becomes yellowish-brown (10YR 5/4), slight gypsum
							9		- Becomes little silt, trace gravel, med. dense
					0.1		10		

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER 2890618.01000

LOCATION Prentiss APN 7351-34-45

DRILLING METHOD: Hand auger to 5.1' Mari MZ5 vibratory hammer

BORING NUMBER 329 SBL0239

SAMPLING METHOD: 1.5" acetate liners, cuti's core 2" brass sleeve / manual drive

SHEET 2 OF 2

DRILLING CONTRACTOR Gregg

DATUM... ELEVATION

SURFACE CONDITIONS: 0.25' Asphalt

DRILLING START TIME 0740 DATE 5-15-03 FINISH TIME 0815 DATE 5-15-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
					0.1		10	SM	
									- Becomes no gravel
									- Becomes trace gravel
					0.1		11		
							12		
	4.0 / 3.8	0810			0.1				- Becomes trace clay, no gravel
							13		
									- Becomes some clay, trace gravel
									- Becomes gravelly
					0.1			SC	Light olive-brown (2.5Y, 5/4) clayey very fine SAND w/ some silt, moist, dense, root casts
							14		
									- Root casts prominent
							15	SM	Yellowish-brown (10YR, 5/4) silty, very fine SAND w/ trace gravel & clay, moist, med. dense, root casts
					0.2				
							16		
							17		
							18		
							19		
							20		

BY Mark Wauck DATE 5-25-03 CHECKED BY DJM

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... SBL0330 ELEVATION

JOB NUMBER	LOCATION (Premises)
28906318.01000	APN 7351-34-45

DRILLING METHOD: Hand Auger to 5.3'; Mark MK25 vibratory hammer

BORING NUMBER: SBL0330

SAMPLING METHOD: 1.5" acetate sleeves / Cont's cores; 2" Brass sleeves / manual drive

SHEET 1 OF 2

SURFACE CONDITIONS: 0.6' Asphalt

DRILLING START TIME	DRILLING FINISH TIME	DATE
0840	0915	5-15-03

DRILLING CONTRACTOR Gregg

BY Mark Wanek DATE 5-15-03 CHECKED BY DM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0		
								A/C	Asphalt
							1	GM	Brown (10YR, 5/3) silty GRAVEL w/ fine-med. Sand, damp, dense (Road base)
							2		
								CL	Dark. grayish-brown (10YR, 4/2) CLAY w/ trace silt, ~~sand~~ fine sand, and gravel
		0842			0.5	SSS01792	3		
							4		
	4.0 / 2.6	0905							- Becomes sandy, brown (10YR, 4/3)
							5	FC	
					0.1				
							6	SM	Brown (10YR, 4/3) silty very fine-fine SAND ~~soft~~, moist, dense, faint root casts, Gypsum inclusions
					0.1				
					0.3		7		
								SC	Light yellowish-brown (10YR, 6/4) clayey very fine SAND w/ silt, moist, dense, faint root casts
	4.0 / 3.4	0908			0.1		8		
						SSS01793			
							9		
					0.1			SM	Light olive-brown (2.5Y, 5/4) silty, very fine-fine SAND w/ trace gravel
							10		

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER: 2890618.01000

LOCATION: APN 7351-34-45

DRILLING METHOD: Hand Auger to 5.3'; Mar I M25 vibratory hammer

BORING NUMBER: SBL0330

SAMPLING METHOD: 1.5" acetate sleeves, 2 per run; 2" Brass sleeves / manual drive

SHEET: 2 OF 2

DRILLING CONTRACTOR: Gregg

DATUM... ELEVATION

SURFACE CONDITIONS: 0.6' Asphalt

DRILLING START TIME: 0840 DATE: 5-15-03

DRILLING FINISH TIME: 0915 DATE: 5-15-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							10	SM	- Gypsum inclusions - Trace clay
					0.1		11		
	4.0 / 3.9	0911			0.1		12	SC CL	Light olive-brown (2.5Y, 5/4) sandy CLAY w/ some silt, moist, med. stiff, root casts
							13	ML SC	Pale yellow (2.5Y, 7/3) gravelly silty/fine sand, dry, very l... Light olive brown (2.5Y, 5/3) clayey fine SAND w/ silt
					0.3		14		
							15		- Becomes trace gravel
					0.1		16		
							17		Boring completed to ~16' on 5-15-03
							18		
							19		
							20		

BY: Mark Lehmann CHECKED BY: DCM DATE: 5-15-03

DAMES & MOORE

BORING LOG

LOCATION OF BORING

~~NE~~ NW corner, bkm

N

10 0 20

DATUM... + SBL0331 ELEVATION

JOB NUMBER 28906318.01000

LOCATION ~~Encino~~ (bkm) APN 7351-34-65

DRILLING METHOD: Hand Auger to 5.1'; Mar I M25 Vibratory Hammer

BORING NUMBER SBL0331

SAMPLING METHOD: 2" Brass sleeve / manual driver; 1.5" acetate sleeves, cont'g core

SHEET 1 OF 2

DRILLING: START TIME 1405 DATE 5-15-03; FINISH TIME 1435 DATE 5-15-03

SURFACE CONDITIONS: 0.15' Asphalt

DRILLING CONTRACTOR Engr

BY Mark Wanek CHECKED BY DCM

DATE 5-15-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Very dark grayish-brown (10YR, 3/2) and dark yellowish-brown (10YR, 4/6) CLAY w/ fine sand and trace silt and gravel
							1		
							2		
		1410			0.5	SS01796			
							3		
	4.0 / 3.1	1426					4	SC	Olive-brown (2.5Y, 4/3) clayey fine SAND w/ trace silt
							5		
					0.3				- root casts apparent
							6		
					0.1				- Becomes increased silt
							7		
					0.3			SM	Light olive-brown (2.5Y, 5/4) silty, very fine SAND w/ some clay, damp, very dense, root casts
	4.0 / 2.8	1426			1.6		8		
						SS01797			w/ silt
							9	SC	Olive-brown (2.5Y, 4/4) clayey, fine SAND, damp, very dense, faint root casts
					0.2				
								SM	olive-brown (2.5Y, 4/3) silty fine SAND w/ some clay, ~~very~~ damp, very dense, root casts
							10		

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER: 28906318.01000

LOCATION: (6km) APN 7351-34-63

DRILLING METHOD: Hand auger to ~~15~~ 5.1' Marl 1125

BORING NUMBER: SBL0331

SAMPLING METHOD: 2" Brass sleeve / manual drive

SHEET: 2 OF 2

DRILLING START TIME: 1405 DATE: 5-15-03

DRILLING FINISH TIME: 1435 DATE: 5-15-03

DATUM... ELEVATION

SURFACE CONDITIONS: 0.15' asphalt

DRILLING CONTRACTOR: Gregg

BY: Mark Schuck CHECKED BY: DCM DATE: 5-15-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
								SM	
							10		
					1.0		11		
							12		
	4.0 / 3.2	1431			1.3				
							13		- trace gypsum
									- Becomes m clay, med. dense - dense
					0.3		14		
									- Becomes little silt
					0.1				- Becomes silty
							15		
							16		Boring completed to ~16' on 5-15-03
							17		
							18		
							19		
							20		

DAMES & MOORE

BORING LOG

LOCATION OF BORING



JOB NUMBER	LOCATION
28906318.01000	APN 7351-34-63

DRILLING METHOD:	BORING NUMBER
Hand auger to 5.2' Mark M25 vibratory hammer	SBL0332
SAMPLING METHOD:	SHEET
1.5" acetate sleeve / continuous core 2" brass sleeve / manual drive	1 OF 2
	DRILLING START TIME 1445 DATE 5-15-03 / FINISH TIME 1515 DATE 5-15-03
SURFACE CONDITIONS:	
0.15' Asphalt	

DRILLING CONTRACTOR Gregg

BY Mark Wenck DATE 5-15-03 CHECKED BY DLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Dark brown (10YR 3/3) CLAY w/ sand and silt, moist, very stiff
							1		- Becomes sandy w/ trace gravel
							2		
		1450			1.1	55501798			
							3		
							4	SM	~~Strong~~ Dark yellowish-brown (10YR 4/4) silty w/ trace clay very fine SAND, moist, very dense, ~~root casts~~
	4.0 / 3.5	1504			0.5		5		- Root casts appear
							6		~~no clay~~
					0.3				- Becomes w/ silt & med. dense
							7		- Dark brown (10YR 3/3) clayey inclusions
					0.2				
	4.0 / 3.0	1506			0.3		8		- Becomes w/ clay, very dense
							9		- 0.3' lens of pale yellow gravelly silt
									- Becomes trace to little gravel, gypsum
					0.1		10		

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER	LOCATION
28906318.01000	APN 7351-34-63

DRILLING METHOD:	BORING NUMBER
Hand auger to 5.2' Manual 1425 vibratory hammer	SBL0332
SAMPLING METHOD:	SHEET
1.5" acetate liner, continuous core 2" brass sleeve, manual drive	2 OF 2
	DRILLING START / FINISH
SURFACE CONDITIONS:	TIME / TIME
0.15' asphalt	1445 / 1515
	DATE / DATE
	5-15-03 / 5-15-03

DATUM... ELEVATION

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
								SM
							10	
					0.2			
							11	
							12	
	4.0 / 3.4	1510			2.1			
							13	
					0.1			
							14	
							15	
					0.2			
							16	
							17	
							18	
							19	
							20	

SM

- Becomes no clay, no gravel

- Trace gravel

- Becomes little gravel

Boring completed to ~16' on 5-15-03

BY Mark Hand DATE 5-15-03 CHECKED BY [illegible]

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION Scale 1"=50'

JOB NUMBER	LOCATION (bkm)
28906318.01000	APN 7351-34-63

DRILLING METHOD:	BORING NUMBER
Hand auger to 5.4' Mod M25 vibratory hammer	SBL0333
SAMPLING METHOD:	SHEET
2" Brass sleeves,	1 OF 2
	DRILLING START / FINISH
SURFACE CONDITIONS:	TIME: 1518 / 1615
0.15 0.2' Asphalt	DATE: 5-15-03 / 5-15-03

DRILLING CONTRACTOR Kregg

BY Mark Ulrich CHECKED BY Dubin DATE 5-15-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Very dark grayish-brown (10 YR, 3/2) CLAY
							1		
		1520			0.3	SS501800	2		
							3		
	4.0 / 3.7	1609					4	SM	Dark yellowish-brown (10 YR, 4/4)
							5		
					0.1		6		- trace gravel, root casts
								CL	Brown (10 YR, 4/3) SANDY CLAY w/ silt, moist, stiff
					0.5			SM	Dark yellowish-brown
						SS501801	7		
					0.6				
	4.0 / 3.6	1611			0.1		8	CL	Dark yellowish-brown (10 YR 4/4) CLAY w/ trace silt, moist, very stiff, root casts
							9		
								SM	Yellowish-brown (10 YR, 5/4) silty, very fine SAND, moist, dense, root casts
					0.1		10		- Root casts prominent

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER: 28106318.01000

LOCATION: APN 7351-34-63

DRILLING METHOD: Hand Auger to 5.4'
Mar-1 MZ5 Vibratory hammer

BORING NUMBER: SBL0333

SAMPLING METHOD: 1.5" acetate sleeves, core's core
2" brass sleeve / manual drive

SHEET: 2 OF 2

DRILLING: START TIME 1518 DATE 5-15-03; FINISH TIME 1615 DATE 5-15-03

DATUM... ELEVATION

SURFACE CONDITIONS: 0.2' asphalt

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							10	SM	
							11		
					0.6				
							12	GM	light gray (10YR, 7/1) silty gravelly GRAVEL (chert)
	4.0 / 3.8	1614			0.1			ML	Dark brown (10YR, 4/3) very fine sandy SILT w/ trace clay.
							13	SM	- 0.1' gravelly lense
									Light yellowish-brown (10YR, 6/4) silty very fine SAND w/ trace gravel, moist, dense, faint
					0.1		14		
									- Gravel to 0.05'
									- Becomes Some gravel
							15		- Sharp change to yellowish-brown (10YR 5/4), w/ little clay, no gravel
					0.1		16		
									Boring completed to -16' on 5-15-03
							7		
							8		
							9		
							0		

BY Mark Wheeler CHECKED BY [signature]

DATE 5-16-03

DAMES & MOORE

BORING LOG

LOCATION OF BORING



JOB NUMBER	LOCATION
28906318.01000	APN 7351-34-63 (bkm)

DRILLING METHOD: Hand Auger to 5.2'; Mari M25 vibratory hammer

BORING NUMBER: SBL0334

SAMPLING METHOD: 1.5" acetate sleeves, cut's core; 2" brass sleeve, manual drive

SHEET: 1 OF 2

SURFACE CONDITIONS: 0.2' asphalt

DRILLING START	DRILLING FINISH
TIME: 0820	TIME: 0900
DATE: 5-16-03	DATE: 5-16-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Very dark gray (10 YR, 3/1) sandy clay w/ silt, moist, med. stiff
							1		
		0825			0.4	SSS01802	2		
						MW			
							3		
							4	SC	Light olive-brown (2.5 Y, 5/4) clayey very fine SAND
	4.0 / 3.5	0845							
							5		
					0.1				Root casts apparent
							6		
					1.0				
							7		
					0.2	SSS11803		SM	
							8		Yellowish-brown (10 YR, 5/6) silty fine SAND w/ trace clay, moist, dense, root casts
	4.0 / 3.2	0847			0.7				
							9		
									- Becomes dark yellowish-brown (10 YR, 4/4), ~~sand~~ w/ clay, very dense
					0.1		10		2 0.1' lens ~~pale yellow~~ very pale brown (10 YR, 7/3) gravel

BY Mark Lehnert DATE 5-16-03 CHECKED BY DCM

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER 23906318 e10ec

LOCATION Hea APN 7351-34-63

DRILLING METHOD: Hand augered to 5.2' Mark M25 vibratory hammer

BORING NUMBER SBL0334

SAMPLING METHOD: 1.5" acetate sleeves, Pratt's core 2" brass sleeve, manual drive

SHEET 2 OF 2

DRILLING CONTRACTOR Geo-Test

DATUM... ELEVATION

SURFACE CONDITIONS: 0.2 Asphalt

DRILLING START TIME 0820 DATE 5-16-03

DRILLING FINISH TIME 0900 DATE 5-16-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							10	SM	
									- Becomes w/ very pale brown gravel
					0.2		11		- Becomes no gravel, light yellowish brown (10YR, 6/4), trace clay, at ~10.9'
									Very pale brown (10YR, 7/4) ~~silty~~ GRAVEL w/ silty sand, ~~wet~~ damp, very dense
	4.0 / 3.0	0850			0.3		12	GM	
								SM	Yellowish-brown (10YR, 5/4) very fine SAND w/ some silt, moist, med. dense, faint root casts
							13		
					0.1				- 0.1' lens pale brown (10YR, 6/3) gravel
							14		- Becomes light olive-brown (2.5Y, 5/4), silty
								GM	Gray (2.5Y, 6/1) ~~silty~~ sandy GRAVEL w/ silt, damp, very dense
					0.1		15	SM	Light olive-brown (~2.5Y, 5/4) silty very fine SAND, ~~wet~~ w/ trace clay, moist, dense, faint root casts
							16		Boring completed to ~16' on 5-16-03
							17		
							18		
							19		
							20		

BY Mark Wanek DATE 5-16-03 CHECKED BY Dunn

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER 28906318.01000

LOCATION (Restaurant Depot) APN 7351-33-34

DRILLING METHOD: Hand auger to 5.1' Mar/ M25 vibratory hammer

BORING NUMBER SBL0335

SAMPLING METHOD: 1.5" acetate sleeve, continuous core 2" Brass sleeve / manual drive

SHEET 1 OF 2

DRILLING START TIME 0950 DATE 5-16-03 FINISH TIME 1015 DATE 5-16-03

SURFACE CONDITIONS: 0.5' Concrete

DRILLING CONTRACTOR Gregg

BY Mark Cisneros DATE 5-16-03 CHECKED BY DCM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Concrete
							1	SW/SM	Very dark grayish-brown (10YR 3/2) silty, very fine-very coarse SAND w/ gravel, wet, loose
							2	SC	Yellowish-brown (10YR 5/4) clayey fine SAND, w/ silt, wet, med. dense.
		0953							
							3		
							4	SM	
	4.0 / 3.8	1003			1.8				Olive-brown (2.5Y, 4/3) silty very fine SAND, wet loose - med. dense
							5		
									- Becomes moist, root casts apparent (faint), ~~med~~ dense
					0.1		6		
							7		
					4.6		8		
	4.0 / 2.0	1006			9.0				- Becomes yellowish-brown (10YR 5/4), some silt, very fine-fine ~~SAND~~ sand
							9		- Becomes olive-brown (2.5Y 4/3), fine sand, med. dense
					6.7		10		L Becomes grayish-brown, light odor and staining

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER 28906318.01000

LOCATION (Restaurant Depot) APN 7351-33-34

DRILLING METHOD: Hand auger to 5.1'
Mark MZ5 vibratory hammer

BORING NUMBER SBL0335

SAMPLING METHOD: 1.5" acetate sleeves, continuous core
2" Brass sleeves, manual driven

SHEET 2 OF 2

DRILLING CONTRACTOR Gregg

DATUM... ELEVATION

SURFACE CONDITIONS: 0.5' Concrete

DRILLING START TIME 0950 DATE 5-16-03

DRILLING FINISH TIME 1015 DATE 5-16-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
					6.7		10	SM
							11	
							12	
	4.0 / 3.9	1011			9.8			
							13	
							14	
					23.7			
							15	
		~~1514~~ 1519	15.4-15.9		28.8	SSS01804	16	
							17	
							18	
							19	
							20	

- Recovered w/ clay & trace gravel, ~~moist~~ light olive-brown (2.5Y, 5/3)

- Becomes no clay or gravel, root casts prominent olive-brown (2.5Y, 4/4)

- Becomes dark grayish-brown (2.5Y, 4/2), slightly increased odor, trace clay, dense

Boring completed to ~16' on 5-16-03

BY Mark Wester DATE 5-16-03 CHECKED BY DCM

DAMES & MOORE

BORING LOG



JOB NUMBER	LOCATION
28906318.01000	(Restaurant Depot) APN 7351-33-34

DRILLING METHOD:	BORING NUMBER
Hand auger to 5.25' Marl M25 vibratory hammer	SBL0336
SAMPLING METHOD:	**SHEET**
1.5" acetate sleeve, continuous core 2" brass sleeve/manual drive	1 OF 2
	DRILLING

SURFACE CONDITIONS:	START TIME	FINISH TIME
0.5' Concrete	1115 ~~1115~~	1150
	START DATE	FINISH DATE
	5-16-03	5-16-03

DRILLING CONTRACTOR Gregg

BY Mark Wenk DATE 5-16-03 CHECKED BY Dan

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0		
								A/C	Concrete
							1	CL	Very dark grayish-brown (10YR, 3/2) CLAY w/ very fine sand & some silt, moist, stiff
							2		
		1120							
							3	SC	Dark yellowish-brown (10YR, 4/4) clayey fine SAND w/ little silt, moist, dense
	4.0 / 3.8	1135					4		
							5		
					2.6				- root casts apparent, gypsum
							6		
					8.5				
							7	SM	Olive-brown (2.5Y, 4/4) silty very fine SAND ~~w~~ w/ trace clay, ~~moist~~, moist, med. dense, root casts
									faint odor
					4.4				petrochem (Eucalyptus-like ?)
	4.0 / 2.8	1139			13.0		8		- Decreased silt
							9		- Becomes ~~some silt~~, light olive-brown (2.5Y, 5/4) some silt, med. dense, moderate petrochem odor, no root casts
			9.5-10.0		63.4	SSS01805	10		

BORING LOG

LOCATION OF BORING

JOB NUMBER	LOCATION
28906318.01000	APN 7351-33-34

DRILLING METHOD:	BORING NUMBER
Hand Auger to Mari 4425 vibratory hammer	SBL0336
SAMPLING METHOD:	SHEET
1.5" acetate sleeves, continuous core 2" brass sleeve, manual drive	2 OF 2

DRILLING CONTRACTOR Geopro

DATUM... ELEVATION

SURFACE CONDITIONS: 0.5' Concrete

DRILLING START TIME	DRILLING FINISH TIME
1115	1150
DRILLING START DATE	DRILLING FINISH DATE
5-16-03	5-16-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
			9.5-10.0		63.4	SSS01805	10	SM	
					33.3		11		
	4.0 / 3.7	1143			19.2		12		
								SC	Olive-brown (2.5Y, 4/4) clayey fine SAND w/ silt, ~~root coal~~ moist, dense, root casts, moderate odor
							13		
					18.7				
							14	CL	Light olive-brown (2.5Y, 5/4) CLAY w/ little very fine sand and trace silt, moist, stiff, heavily bioturbated - Becomes sandy
							15		
					30.4			SM	Dark yellowish-brown (10YR, 3/6) silty very fine SAND w/ little clay, moist, dense, root casts
							16		
									Boring completed to ~16' on 5-16-03
							17		
							18		
							19		
							20		

BY Mark Wanek CHECKED BY Plan

DATE 5-16-03

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER 2.2906318.01000	LOCATION (Viking) APN 7351-31-20
DRILLING METHOD: Hand Auger to 7.0' Mark M25 Vibrating hammer	BORING NUMBER SBL0337
SAMPLING METHOD: 2" brass sleeve manual drive 1.5" acetate liners, continuous	SHEET 1 OF 2
SURFACE CONDITIONS: 0.2' Asphalt	DRILLING START TIME 0900 DATE 6-4-03 / FINISH TIME 1025 DATE 6-4-03

DRILLING CONTRACTOR Gregg

BY Mark Lalanette DATE 6-4-03 CHECKED BY PLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0		
								A/C	Asphalt
								~~GW~~ SM	Dark brown (10YR, 3/3) silty very fine - fine SAND w/ gravel, moist, dense
							1		
						SS501806	2		
							3		
	4.0 / 3.2						4		(10YR, 3/4) - Becomes dark yellowish-brown, ~~trace~~ gravel and clay
							5		
									- Becomes yellowish-brown (10YR, 5/6), no gravel or clay
							6		
						SS501807			
							7		- Becomes dark yellowish-brown (10YR, 4/4), trace clay
	4.0 / 4.0				2.2		8		- Root casts apparent
							9		
							10		
					0.3			SC	Dark yellowish-brown (10YR, 4/6) clayey fine SAND w/ silt, moist, dense

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER: 2890357.01000

LOCATION: APN 7351-31-20

DRILLING METHOD: Hand auger to 7.0'; Mark 1425 vibratory hammer

BORING NUMBER: SBL0337

SAMPLING METHOD: 2" Brass sleeve, manual drive; 1.5" acetate liner, continuous

SHEET: 2 OF 2

DRILLING: START TIME 0900 DATE 6-4-03; FINISH TIME 1025 DATE 6-4-03

DATUM... ELEVATION

SURFACE CONDITIONS: 0.2' Asphalt

DRILLING CONTRACTOR Gregg

BY Matt Unemke DATE 6-04-03 CHECKED BY DMM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
					0.3		10	SM/SC
							11	
					1.1		12	
	4.0/2.9				0.3			
							13	SM
					0.6		14	
					0.3		15	
							16	
							17	
							18	
							19	
							20	

10 SM/SC: Dark yellowish-brown ~~sandy~~ clayey fine SAND w/ silt, moist, loose, root casts

13 SM: Dark yellowish-brown (10YR, 4/6) silty fine SAND w/ 1-11% clay, moist, med. dense

14 - Becomes decreased silt, no clay

16 Boring completed to ~16' on 6-4-03

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION
289063318.01000	(Viking) APN 7351-31-20
DRILLING METHOD: Hand Auger to 5.0' Mobil M25 vibratory hammer	BORING NUMBER SBL0338
SAMPLING METHOD: 2" Brass sleeves, manual drive 1.5" acetate liners, continuous core	SHEET 1 OF 2
SURFACE CONDITIONS: 0.2' Asphalt	DRILLING START TIME 1030 DATE 6-4-03 / FINISH TIME DATE 6-4-03

DRILLING CONTRACTOR Geoprobe

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								SM	Dark brown (10YR, 3/3) silty very fine-fine SAND w/ gravel, moist, dense
						SS501808	2		
	4.0 / 3.5			6	0.1		4	CL	Dark brown (10YR, 3/3) sandy CLAY w/ some silt
					0.1		6	SM	Yellowish-brown (10YR, 5/6) silty, very fine SAND, moist, very dense, faint root casts
									-Becomes brownish-yellow (10YR, 6/6)
					0.1	SS501809	7		
	4.0 / 3.0				0.2		8		-Becomes yellowish-brown (10YR 5/6)
							9		
					0.1		10		-Root casts more prominent

BY Mark Lidarik DATE 6-4-03 CHECKED BY DLM

DAMES & MOORE

BORING LOG

LOCATION OF BORING

DATUM... ELEVATION

JOB NUMBER 28906318.01000

LOCATION (Viking) APN 7351-31-20

DRILLING METHOD: Mac1 M25 vibratory hammer. Hand Auger to 5.0'

BORING NUMBER SBL0338

SAMPLING METHOD: ~~Hand Auger~~ 2" brass sleeve 1.5" acetate liner, cont's core

SHEET 2 OF 2

SURFACE CONDITIONS: 0.2' Asphalt

DRILLING START TIME 1030 DATE 6-4-03

DRILLING FINISH TIME DATE 6-4-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
					0.1		10	SM
					0.1		11	
	4.0 / 3.3				0.1		12	
							13	
					0.1			
							14	
					0.1		15	
							16	
							17	
							18	
							19	
							20	

- Becomes dark yellowish-brown (10 YR 4/6) little clay
  - Becomes light olive-brown (to 2.5Y 5/3)
- Becomes olive-brown (2.5Y 4/4), some clay

Boring completed to ~16' on 6-4-03

BY Mark Wanek CHECKED BY DLW

DATE 6-4-03

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION (Viking)
28906318.01000	APN 7351-31-20

DRILLING METHOD:	BORING NUMBER
Hand Augers to 5.1' Mari M25 vibratory hammer	SBL0339
SAMPLING METHOD:	SHEET
2" Brass sleeves, manual drive 1.5" Acetate liner / continuous core	1 OF 2
	DRILLING START TIME / FINISH TIME
SURFACE CONDITIONS:	
0.2' Asphalt	DATE 6-4-03 / DATE 6-4-03

DRILLING CONTRACTOR Gregg

BY Mark Wong CHECKED BY DLM

DATE 6-4-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	SM	Asphalt Dark brown (10YR, 3/3) silty fine SAND w/ gravel, moist, dense
					0.2	SSS01811	1		
							2	A/C	Concrete slab.
							3	CL	Dark yellowish-brown (10YR, 3/4) CLAY w/ fine sand & silt, moist, stiff
					0.1		4		
	4.0 / 3.4								
					0.1		5		
							6	SM	light olive-brown (to 2.5Y, 5/4) silty very fine SAND, damp, dense, root casts.
					0.2	SSS01812	7		
							8		-Becomes yellowish-brown (10YR, 5/4)
	4.0 / 3.4				0.1				
							9		
							10	CL	Olive-brown (2.5Y, 4/4) Sandy CLAY w/ some silt, moist, stiff, root casts prominent
					0.1				

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER 28906318.01000

LOCATION Viking APN 7351-31-20

DRILLING METHOD: Hand augers to 5.1' Mobil Mk 5 vibratory hammer

BORING NUMBER SBL0339

SAMPLING METHOD: 2" Brass sleeve, manual drive 1.5" acetate liners, continuous core

SHEET 2 OF 2

DRILLING START TIME / FINISH TIME

SURFACE CONDITIONS: 0.2' Asphalt

DRILLING START DATE 6-4-03 / FINISH DATE 6-4-03

DRILLING CONTRACTOR Gregg

DATUM... ELEVATION

BY Mark Unruh DATE 6-4-03 CHECKED BY DLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
					0.1		10	SM / CL
							11	
					0.1			
							12	
	4.0 / 3.2				0.1			SM
							13	
					0.1		14	
							15	
					0.1			
							16	
							17	
							18	
							19	
							20	

SM / CL: Olive-brown (2.5Y, 4/4) sandy CLAY w/ some silt, moist, stiff, root casts prominent

SM: Yellowish-brown (10YR, 5/4) silty, very fine-fine SAND, moist, dense, root casts prominent

Boring completed to ~16' on 6-4-03 MW

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION (Viking)
~~85~~ 2890318.010000	APN 7351-31-20

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.3'	SBL0340
Mark M25 vibratory hammer	SHEET 1 OF 2
SAMPLING METHOD:	DRILLING START TIME / FINISH TIME
2" Brass sleeve, manual drive	
1.5" acetate liner, continuous core	
SURFACE CONDITIONS:	DRILLING START DATE 6-4-03 / FINISH DATE 6-4-03
0.2' Asphalt	

DRILLING CONTRACTOR Cascade

BY Mark Wanetter DATE 6-4-03 CHECKED BY DLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0		
								SM	Dark grayish brown (10YR 4/2) silty
							1		- Rough hand augering - ~~rocky~~ gravelly
							2		
							3		(10YR 3/3) - Becomes dark brown, wet, oily smell
	4.0 / 3.3				0.1	SS501810	4		- oily odor faint
							5	CL	Brown (7.5YR 4/3) sandy CLAY w/ little silt, moist, very stiff, root casts
					0.1		6	SM	yellowish-brown (10YR 5/6) silty very fine sand, moist, very dense, root casts prominent
							7		
					0.1				
	4.0 / 3.4				0.1		8		- Becomes light olive-brown (to 2.5Y 5/4) increased silt, root casts faint, med. dense
							9		- Becomes yellowish-brown (10YR 5/4)
					0.1		10	CL	- Becomes some clay, decreased silt
									Dark yellowish-brown (10YR 4/4) sandy CLAY w/ silt, moist, stiff, root casts faint

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER: 2890618.01000

LOCATION: APN 7351-31-20

DRILLING METHOD: Mobil MB5 vibratory hammer
Hand auger to 5.3'

BORING NUMBER: SBL0340

SAMPLING METHOD: 2" Brass sleeve, manual drive
1.5" acetate liner, continuous core

SHEET: 2 OF 2

DRILLING START TIME:

DRILLING FINISH TIME:

SURFACE CONDITIONS: 0.2' Asphalt

DRILLING START DATE: 6-4-03

DRILLING FINISH DATE: 6-4-03

DATUM...

ELEVATION

DRILLING CONTRACTOR Gregg

BY Mark Adams

DATE 6-4-03

CHECKED BY PLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							10	CL
							11	SM
					0.1			
							12	
					0.1			
							13	
					0.0		14	
					0.2		15	
							16	
							17	
							18	
							19	
							20	

Light olive-brown (2.5Y, 5/6) silty very fine sand, moist, dense, root casts

- Becomes dark yellowish-brown (10YR, 4/6) med. dense, decreased silt, faint root casts

Boring completed to ~16' on or 6-4-03

DAMES & MOORE

BORING LOG

(Ace Clearwater)

LOCATION OF BORING — N Property Boy



DATUM... ELEVATION

JOB NUMBER	LOCATION
28906318.01000	APN 7351-34-43

DRILLING METHOD:	BORING NUMBER
Hand auger to 5.0' Mark M25, vibratory hammer	SBL0341
SAMPLING METHOD:	SHEET
2" brass sleeve, manual drive 1.5" acetate liner, cont's core	1 OF 2
	DRILLING
	START / FINISH
SURFACE CONDITIONS:	TIME: / 0815
0.3' Asphalt	DATE: 6-5-03 / 6-5-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Very dark gray (2.5Y, 3/1) CLAY w/ fine sand and silt, moist, stiff
							1		
					0.2		2		
							3		- Becomes moderate - strong oily odor, staining
					0.1	SS501813			- Becomes faint odor, wet
	4.0 / 3.8				0.1		4		- Becomes moist
							5		- Becomes brown (7.5Y, 4/3), decreased sand, root casts (10YR, 4/4)
					0.1				- Becomes dark yellowish-brown, trace gypsum
							6		- Becomes sandy, root casts prominent
							7		
					0.1		8		- Becomes yellowish (10YR, 4/6)
	4.0 / 3.3				0.7			SM	Dark yellowish-brown (10YR, 4/6) silty fine SAND, moist, strong root casts prominent
							9		
							10		
					0.6				

BY Mark Wheeler DATE 6-5-03 CHECKED BY DLM

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER	LOCATION
25906318.01000	AFN 7351-34-43

DRILLING METHOD: Hand Auger to 5.0'; Mod MK25 vibratory hammer

BORING NUMBER: SBLO341

SAMPLING METHOD: 2" Brass sleeve, manual drive; 1.5" acetate liner, continuous core

SHEET: 2 OF 2

DRILLING: START TIME —; FINISH TIME 0815; START DATE 6-5-03; FINISH DATE 6-5-03

SURFACE CONDITIONS: 0.3' Asphalt

DRILLING CONTRACTOR Gregg

DATUM... ELEVATION

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							10	SM
					0.6			
							11	
							12	
	4.0 / 3.5				5.4			
							13	
					0.0		14	
							15	
					14			
							16	
							17	
							18	
							19	
							20	

- Becomes little clay
- Becomes traces clay, root casts, faint
- Becomes olive-brown (to 2.5Y 4/3) ~~and layer~~ interspersed w/ olive (5Y, 4/3)

Boring completed at ~16' on 6-5-03

BY Mark Wright DATE 6-5-03 CHECKED BY DLM

DAMES & MOORE

BORING LOG

LOCATION OF BORING (Proposed) 0 Scale 1"=40' 40 (Proposed) to Viking Bldg



JOB NUMBER	LOCATION
28906318.01000	(Viking) APN 7351-31-20

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.1' Mark M25 vibratory hammer	SBL0342
SAMPLING METHOD:	SHEET
2" Brass sleeve, manual hammer 1.5" acetate liners, cont's core	1 OF 2
	DRILLING START TIME / FINISH TIME
SURFACE CONDITIONS:	
0.25' Asphalt	DATE 6-5-03 / DATE 6-5-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Brown (10YR, 4/3) Sandy CLAY w/ gravel & silt, mottled w/ dark gray (10YR, 4/1)
							1		- Becomes decreased gravel
							2		
					0.0				- Becomes gravelly from 2.5-2.7'
							3		- Becomes dark olive-gray (5Y, 3/2) moderate-strong pet. oil. staining
					0.2	SS501814			- Becomes black (10YR, 2/1) oily, heavy staining
	4.0/3.9				0.1		4		~~- Becomes black (10YR, 2/1), oily smell, heavy staining~~ - Becomes
							5	SM	Yellowish-brown (10YR 5/8) silty fine SAND w/ gravel (cobbles to ~0.15')
					0.1		6	CL	Dark brown (7.5YR, 3/3) CLAY w/ trace very fine sand and silt, moist, med. stiff - Becomes little sand
								SM	Dark yellowish-brown (10YR, 4/6) silty fine SAND w/ trace clay, moist, dense, root casts (faint)
							7		
					0.1		8		
	4.0/2.7				0.1				Becomes - increased silt
							9		
							10		
					0.1				- Becomes Mod. dense

BY Mark Wardell DATE 6-5-03 CHECKED BY DCM

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER	LOCATION
28906318.01000	APN 7351-3-20

DRILLING METHOD:	BORING NUMBER
Hand Augers to Mari MZ5 vibratory hammer	SBL0342
SAMPLING METHOD:	SHEET
2" Brass sleeve, manual drive 1.5" acetate liners, cores cut	2 OF 2
	DRILLING START TIME / FINISH TIME
SURFACE CONDITIONS:	DATE 6-5-03 / DATE 6-5-03
Asphalt	

DATUM... ELEVATION

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
					0.1		10	SM	
					0.1				
							11		
								CL	Yellowish-brown (10YR 5/4) sandy CLAY w/ some silt moist, med. stiff, root casts
	4.0 / 3.0				0.1		12		
							13		
								SM	Dark yellowish-brown (10YR, 4/4) silty fine SAND w/ trace clay, moist, dense, faint root casts
							14		
					0.1		15		-Becomes w/ silt, med. dense.
							16		Boring completed to ~16' on 6-5-03
							17		
							18		
							19		
							20		

BY Mark Schuett DATE 6-5-03 CHECKED BY DLM

DAMES & MOORE

BORING LOG

LOCATION OF BORING



Scale 1" = 40'

1 to Viking Bldg

Machine Shop / Cafeteria area

orig. loc. (+N)

+SBL0343

DATUM... +SBL0342 ELEVATION

JOB NUMBER	LOCATION Viking
28906318.01000	APN 7351-31-20

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.1' Mark 1425 vibratory hammer	SBL0343
SAMPLING METHOD:	SHEET 1 OF 2
2" Brass sleeve, manual drive 1.5" acetate sleeves, continuous core	DRILLING START TIME / FINISH TIME
SURFACE CONDITIONS:	DATE 6-5-03 / DATE 6-5-03
0.25' Asphalt	

DRILLING CONTRACTOR Gregg

BY Mark Wanek DATE 6-5-03 CHECKED BY PLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Dark brown (10YR 3/3) sandy CLAY w/ silt and some gravel, brick fragments, moist-moist, med. stiff
							1		
					0.1	SSS01815			- Becomes gravelly from ~1.8-2.1'
							2		
							3		
									- Becomes gravelly
	4.0 / 3.8				0.0		4		
							5		- Becomes trace very fine sand, w/ some gravel and silt, faint root casts
					0.1		6	SM	Dark yellowish-brown (10YR, 4/6) silty fine SAND w/ trace clay, moist, dense, root casts
							7		- Becomes med. dense
					0.0	SSS01816			- trace gypsum
	4.0 / 3.3				0.3		8		- Becomes wet
							9		- Becomes light olive-brown (2.5Y, 5/4), very fine-fine sand, dense
					0.1		10		

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER	LOCATION
28906318.01000	APN 7351-31-20

DRILLING METHOD: Hand Auger to 5.1'; Mark H25 vibratory hammer

BORING NUMBER: SBL0343

SAMPLING METHOD: 2" Brass sleeve, manual drive; 1.5" acetate sleeve, cont's core

SHEET: 2 OF 2

DRILLING: START TIME / FINISH TIME

SURFACE CONDITIONS: 0.25' Asphalt

DRILLING: START DATE 6-5-03 / FINISH DATE 6-5-03

DRILLING CONTRACTOR Gregg

DATUM... ELEVATION

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
					0.1		10	SM
					0.0		11	
								CL
	4.0 / 3.0				0.5		12	
								SM
							13	
					0.1		14	
					0.1		15	
							16	
							17	
							18	
							19	
							20	

- Becomes dark yellowish brown (10YR, 4/4), little clay, med. dense

Yellowish-brown (10YR, 5/4) sandy CLAY w/ silt, moist, med. stiff, trace gypsum and few root casts

Yellowish-brown (10YR, 5/4) silty fine SAND w/ trace clay, moist, ~~med~~ dense, root casts.

- Becomes decreased silt, med. dense.

Boring completed to ~ 16' on 6-5-03

BY Mark Wenck DATE 6-5-03 CHECKED BY DLM

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION (Viking)
28906318.01000	APN 7351-31-20
DRILLING METHOD: Hand Auger to 3.4' / Marl M25 vibratory hammer	BORING NUMBER SBL 0344 (~~SB~~)
SAMPLING METHOD: ~~Hand~~ 2" Brass sleeves, manual drive / 1.5" acetate liner, continuous core	SHEET 1 OF 2
	DRILLING START TIME / FINISH TIME
SURFACE CONDITIONS: 0.25' asphalt	DATE 6-5-03 / DATE 6-5-03

DRILLING CONTRACTOR Gregg

BY Mark Wanek DATE 6-5-03 CHECKED BY PLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
							1	SM/CL	Dark brown (10YR, 3/3) ~~and dark~~ CLAY and dark yellowish-brown (10YR, 4/4) silty fine-med SAND, (melted together), brick fragments, gravel, moist, soft-med. stiff/ dense (fill)
						SS501817	2		- pieces of ceramic tile, cement
								GM	Gray (10YR, 6/1) + light gray (10YR, 7/1) silty GRAVEL (uniform in size, ~ 0.08')
	4.0/3.2				0.2		3	CL	Brown (7.5YR, 4/2) CLAY w/ little Sand and trace silt, moist, ~~den~~ med. stiff, root casts
							4		- Becomes strong brown (7.5YR, 4/6)
					0.1		5	SM	Strong brown (7.5YR, 5/6) silty fine SAND w/ trace clay & gravel, root casts
					0.1		6		
					0.1	SS501818	7		- Becomes yellowish-brown (10YR, 5/4)
	4.0/3.1						8	SC	Yellowish-brown (10YR, 5/4) clayey fine SAND w/ silt, moist, dense, root casts
					0.2			SM	Dark yellowish-brown (10YR, 4/4) silty fine SAND w/ little clay, moist, med. dense.
					0.1		9		
							10		

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER	LOCATION
28906318.01000	APN 7351-31-20

DRILLING METHOD: Hand auger to Mark 1425, vibratory hammer

BORING NUMBER: SBL0344

SAMPLING METHOD: 2" Brass sleeve, Manual drive 1.5" acetate liner, Cont's core

SHEET: 2 OF 2

DRILLING: START TIME / FINISH TIME

SURFACE CONDITIONS: 0.25' asphalt

DRILLING: START DATE 6-5-03 / FINISH DATE 6-5-03

DATUM... ELEVATION

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
					0.1		10	FM	
								CL	
	4.0/2.8				0.1		11		Yellowish brown (10YR, 5/3) sandy CLAY w/ silt, moist, med. stiff, root casts
							12		
					0.1				
							13		- Becomes more yellower (10YR, 5/4), increased sand, soft, root casts faint
					0.1				
							14		
							15		Boring completed to ~15' on 6-5-03
							16		
							17		
							18		
							19		
							20		

BY Mark Wenzel CHECKED BY DLM

DATE 6-5-03

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION (Viking)
28906318.01000	APN 7351-31-20

DRILLING METHOD:	BORING NUMBER
Hand auger to 5.0'	
Mobil M25 vibratory hammer	SBL0345
SAMPLING METHOD:	SHEET
2" Brass sleeve, manual drive	1 OF 2
1.5" acetate liner, continuous	DRILLING
	START / FINISH
SURFACE CONDITIONS:	TIME / TIME
0.25' Asphalt	DATE / DATE
	6-5-03 / 6-5-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							0	A/C
								SM
							1	
						SSS01819	2	
							3	
	4.0 / 3.8				0.1		4	
								CL
							5	
					0.1		6	
	4.0 / 3.4 MW				0.1	SSS01820	7	
	4.0 / 3.4				0.4		8	SC
							9	
					0.3		10	
								SM

Asphalt

Dark brown (10YR, 3/3) silty very fine-fine SAND w/ gravel & some clay, moist, dense

Dark yellowish-brown (10YR, 3/4) sandy CLAY w/ some silt, moist, stiff, root casts

- Becomes little sand & silt,

- Becomes sandy, trace gypsum

Dark yellowish-brown (10YR, 4/4) clayey fine SAND w/ some silt, moist, very dense, root casts

BY Mark Ward DATE 6-5-03 CHECKED BY Dum

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER	LOCATION
28906318.01000	APN 7351-31-20

DRILLING METHOD:	BORING NUMBER
Hand augers to ~~+5" acetate liner~~; Mod 1725 Vibratory	SBL0345
SAMPLING METHOD:	SHEET 2 OF 2
2" Brass sleeve, Manual drive 1.5" acetate liner, continuous core	DRILLING START / FINISH
SURFACE CONDITIONS: 0.25' Asphalt	TIME / TIME
	DATE 6-5-03 / DATE 6-5-03

DATUM... ELEVATION

DRILLING CONTRACTOR Gregg

BY Mark Wanek DATE 6-5-03 CHECKED BY DLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
					0.3		10	SC ~~SM~~	
								SM	Dark yellowish-brown (10YR 4/4) silty fine SAND w/ some clay, moist, dense, root casts
					0.1		11		Becomes med. dense
							12	CL	Dark yellowish-brown (10YR, 4/4) CLAY w/ sand & little silt, moist, very stiff, root casts
					0.5				
							13		
								SM	Dark yellowish-brown (10YR, 4/4) silty fine SAND w/ trace clay, moist, dense, root casts faint
					0.2		14		
					0.2		15		
							16		Boring completed to ~16' on 6-5-03
							17		
							18		
							19		
							20		

DAMES & MOORE

BORING LOG

LOCATION OF BORING: SBL0346 (N)

Asphalt Parking

Nikon Bldg

Landscaping

0 25 50

Scale 1"=50'

DATUM... ELEVATION

JOB NUMBER	28906318.01000
LOCATION	~~Viking~~ Nikon
APN	7351-33-23
DRILLING METHOD:	Hand Auger to 5.0' Mari M25 w/ vibratory hammer
BORING NUMBER	SBL0346
SAMPLING METHOD:	2" brass sleeves, manual drive 1.5" acetate liner, continuous core
SHEET	1 OF 2
SURFACE CONDITIONS:	0.2' Asphalt
DRILLING START TIME	
DRILLING FINISH TIME	
DRILLING START DATE	6-9-03
DRILLING FINISH DATE	6-9-03

DRILLING CONTRACTOR Gregg

BY Marko Wanecke DATE 6-9-03 CHECKED BY DLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Very dark gray (10YR. 3/1) CLAY w/ fine sand and some gravel, moist, stiff
							1		
							2		
							3		
							4		- Becomes sandy, brown (10YR. 4/3)
							5	SM	Olive-brown (2.5Y. 4/3) and light yellowish-brown (10YR. 6/4) silty, fine SAND w/ some little clays, root casts, slight volatile odor, damp, dense, light staining
	4.0/3.9						6		
							7		
							8		- Becomes ~~light~~ to olive-brown
							9		- Becomes moderate odor, light staining (light olive-brown (2.5Y, 5/6) no or very faint root casts
	4.0/3.8					SSS01821			
							10		

BORING LOG

LOCATION OF BORING

DATUM... ELEVATION

DRILLING CONTRACTOR Cregg

BY Mark Wenzel DATE 6-9-03 CHECKED BY DLM

JOB NUMBER	LOCATION
289063 18.01000	APN 7351-33-23

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.0'	SBL034b
Marl M25 vibratory hammer	
SAMPLING METHOD:	SHEET
2" brass sleeve, manual drive	2 OF 2
1.5" acetate liner, continuous core	DRILLING
	START TIME / FINISH TIME
SURFACE CONDITIONS:	
0.2' Asphalt	DATE 6-9-03 / DATE 6-9-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
								SM	
							10		
							11		
							12		- Becomes w/ silt, med. dense, faint odor
							13		
	4.0 / 3.8								- Becomes pale yellow (2.5Y, 7/3) and olive-brown (2.5Y, 4/4), silty, very fine sand w/ gravel, very dense
							14	CL / SM	Light olive-brown (2.5Y, 5/4) silty CLAY w/ trace very fine sand, moist, soft Yellowish-brown (10YR 5/4) silty very fine SAND, trace gypsum, moist, dense, root casts, faint petrochemical odor
							15		
							16		- 0.2' lens of light olive-brown clay
							17		Boring completed to ~17' on 6-9-03
							18		
							19		
							20		

BORING LOG

LOCATION OF BORING



DATUM... Nikon Bldg

ELEVATION Landscaping

JOB NUMBER	LOCATION (Nikon)
28906318.01000	APN 735-33-23

DRILLING METHOD:	BORING NUMBER
Hand Auger to 4.9'	
Mark 1425 vibratory hammer	SBL0347
SAMPLING METHOD:	SHEET
2" Brass sleeves, manual drive	1 OF 2
1.5" acetate liner, continuous core	DRILLING

SURFACE CONDITIONS:	START TIME	FINISH TIME
0.2' Asphalt	DATE 6-9-03	DATE 6-9-03

DRILLING CONTRACTOR Gregg

BY Mark Ward DATE 6-9-03 CHECKED BY DLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Very dark gray (10YR, 3/1) CLAY w/ fine sand and some gravel, moist, stiff
							1		
							2		- Becomes sandy
							3		- Becomes brown (10 YR, 4/3)
							4	SC	Dark yellowish-brown (10YR, 4/6) clayey fine SAND w/ some silt, moist, dense, faint odor
							5		- Root casts
	4.0 / 3.5						6	SM	Dark yellowish-brown (10 YR, 4/6) silty fine SAND w/ little clay, moist, dense, root casts, faint odor
							7		
							8		
							9		- Becomes yellowish-brown (10 YR, 5/6), root casts faint, odor moderate
	4.0 / 3.7						10		- Becomes mottled w/ olive-brown (~~10YR~~ 2.5Y, 4/4)

BORING LOG

LOCATION OF BORING

DATUM... ELEVATION

JOB NUMBER	LOCATION
289063/8.01000	APN 7351-33-23

DRILLING METHOD:	BORING NUMBER
Hand Auger to ~4.9 feet Mar 425 vibratory hammer	SBL0347

SAMPLING METHOD:	SHEET
~~4.5~~ 2" Brass sleeve, manual drive 1.5" acetate liner, continuous core	2 OF 2

SURFACE CONDITIONS:	DRILLING START TIME	DRILLING FINISH TIME
0.2' Asphalt	DATE 6-9-03	DATE 6-9-03

DRILLING CONTRACTOR Greg

BY Mark Wheeler DATE 6-9-03 CHECKED BY DJM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							10	SM	
									• Becomes mottled w/ olive-brown (~~10~~ 2.5Y, 4/4) (Light staining?)
							11		• Becomes decreased silt, med. dense
							12		
						SSS01822			
							13		
	4.0 / 3.0								
							14	CL	Light olive-brown (2.5Y, 5/6) silty CLAY w/ some very fine sand, moist, soft-med. stiff, rootcasts, moderate odor
								SM	Light olive-brown (2.5Y, 5/4) silty very fine SAND moist, med. dense, trace gypsum
							15		
									- Becomes interlayered w/ clay
							16		
							17		
									Boring completed to ~17' on 6-9-03
							18		
							19		
							20		

BORING LOG

LOCATION OF BORING



JOB NUMBER	LOCATION (Viking)
28706XX318.01000	APN 7351-31-20

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.1' Mar. M25 vibratory hammer	SBL0348
SAMPLING METHOD:	SHEET
2" brass sleeve, manual drive 1.5" acetate liner	1 OF 2
	DRILLING START / FINISH
SURFACE CONDITIONS:	TIME / TIME
0.25' Asphalt	DATE 6-9-03 / DATE 6-9-03

DRILLING CONTRACTOR Groff

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								SM	Grayish brown (10YR, 5/2) silty fine SAND w/ gravel and clay, moist, dense
							1		
							2		
					0.4		3		- Becomes black, gravelly, petroleum odor
							4		- Bec Debris (concrete?) rough hand augering
						SS01823		CL	
	4.0/3.9				0.2		5		- Becomes brown (10YR, 4/3) w/ some sand and trace silt, no gravel, root casts, no odor
							6	SM	Dark yellowish-brown (10YR, 4/6) silty fine SAND w/ trace clay, moist, dense, root casts
					0.1		7		
							8		- Becomes yellowish-brown (10YR, 5/4)
					0.2		9		
	4.0/3.0				0.2		10		

BY Mark Wanek CHECKED BY PCM

DATE 6-9-03

BORING LOG

LOCATION OF BORING

JOB NUMBER: 289063 18.01000

LOCATION: APN 7351-31-20

DRILLING METHOD: Hand Auger to Mini M25 vibratory hammer

BORING NUMBER: SBL 0348

SAMPLING METHOD: 2" Brass sleeve, manual drive 1.5" acetate liner

SHEET: 2 OF 2

DRILLING START TIME:

DRILLING FINISH TIME:

DATUM...

ELEVATION

SURFACE CONDITIONS: 0.25' Asphalt

DRILLING START DATE: 6-9-03

DRILLING FINISH DATE: 6-9-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							10	Soil
					0.1			
							11	
					0.2		12	
	4.0 / 1.7				0.1		13	
					0.1		14	
							15	
							16	
							17	
							18	
							19	
							20	

-Becomes dark yellowish-brown (10YR 4/6), med. dense

Boring completed to ~17' on 6-9-03

BY Mark Ashcraft CHECKED BY DLM

DATE 6-9-03

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION (Viking)
28906318.01000	APN 7351 ~~7352~~-33-20

DRILLING METHOD:	BORING NUMBER
Hand Auger to 4' Mark M25 vibratory hammer	SBL0349
SAMPLING METHOD:	SHEET 1 OF 2
2" brass sleeve, manual drive 1.5" acetate sleeve, continuous core	DRILLING START TIME / FINISH TIME
SURFACE CONDITIONS: 0.25 Asphalt	DATE 6-9-03 / DATE 6-9-03

DRILLING CONTRACTOR Geo-Test

BY Mark Wheeler DATE 6-9-03 CHECKED BY DLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Very dark grayish-brown (10YR, 3/2) silty CLAY w/ fine sand & little gravel, moist, stiff
							1		
						SS501824	2		
							3		
							4		- Concrete-lined ~~former~~ storm structure (former sump?)
							5		
	4.0 / 3.5				0.6		6	SM	Dark yellowish-brown (10YR, 4/6) silty fine SAND w/ trace clay, moist, dense, root casts
					0.1	SS501825	7		
							8		
							9	CL	~~and~~ Dark yellowish-brown (10YR, 4/4) sandy clay w/ ~~silt~~ trace silt, moist, dense, root casts
					0.1		10		
	4.0 / 3.2				0.1				

BORING LOG

LOCATION OF BORING

DATUM... ELEVATION

JOB NUMBER	LOCATION
28906318.01000	APN 7351-31-20

DRILLING METHOD:	BORING NUMBER
Hand Auger to 4' Mark M25 vibratory hammer	SBL0349
SAMPLING METHOD:	SHEET
2" brass sleeve, MANUAL drive 1.5" acetate liner, continuous core	2 OF 2
	DRILLING START TIME / FINISH TIME
SURFACE CONDITIONS:	DATE 6-9-03 / DATE 6-9-03
0.25' Asphalt	

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							10	CL/ML ~~SM~~ SM	
	4.0 / 3.2				0.1				Yellowish-brown (10YR, 5/4) silty, fine SAND w/ trace clay, moist, dense, root casts / burrows
							11		
							12		
					0.1		13		* Becomes med. dense
							14		
							15		Boring completed to ~15'
							16		
							17		
							18		
							19		
							20		

BY Mark Wenck DATE 6-9-03 CHECKED BY DLM

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION (viking)
28706318.01000	APN 7351-31-20

DRILLING METHOD:	BORING NUMBER
Hand Auger to 2.9'	SBL0350
SAMPLING METHOD:	SHEET
2" Brass sleeve, manual drive	1 OF 1
	DRILLING START TIME / FINISH TIME
SURFACE CONDITIONS:	DATE 6-9-03 / DATE 6-9-03
0.25' Asphalt	

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
					0.1	SS501826	0	A/C
							1	SM
							2	
							3	
							4	
							5	
							6	
							7	
							8	
							9	
							10	

A/C

Brown (10YR 4/3) silty fine-med SAND w/ gravel and some clay

~~Ref~~ Boring completed to 2.9'
(Refusal - unknown utility)

BY Mark Wanek DATE 6-9-03 CHECKED BY DLM

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION
28906318.01000	Viking 7351 - 31-20

DRILLING METHOD:	BORING NUMBER
Hand Auger to 2.7'	SBL0351
SAMPLING METHOD:	SHEET
2" Brass Sleeve, manual drive	1 OF 1

DRILLING	START	FINISH
TIME		
DATE	6-9-03	6-9-03

SURFACE CONDITIONS: 0.25' Aspheet

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
						MW 55501827	0	A/C
							1	CL
							2	No Sample
							3	
							4	
							5	
							6	
							7	
							8	
							9	
							10	

Asphalt

Very dark grayish-brown (10YR, 3/2) silty CLAY w/ sand & gravel, moist, med. stiff-stiff

~~Refusal at~~ Boring completed to ~2.7' on 6-9-03 (Refusal-concrete)

BY Mark Wanek CHECKED BY DCM

DATE 6-9-03

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION
28906318.01000	(Ferro Union) APN 7351-34-58

DRILLING METHOD:	BORING NUMBER
Marl M25 auger Hand auger	SBL0352
SAMPLING METHOD:	SHEET
2" Brass sleeve manual drive	1 OF 1
	DRILLING START / FINISH
SURFACE CONDITIONS:	TIME / TIME
0.65' Concrete	09/0
	DATE / DATE
	6-10-03 / 6-10-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							0	
								A/C
							1	SM
							2	
						SSS01827		
							3	
							4	
							5	
							6	
							7	
							8	
							9	
							10	

Concrete

Very dark brown (10YR, 2/2) silty fine - very coarse SAND w/ gravel, moist, dense, heavy-end hydrocarbon odor

Boring completed to 2.6' (refusal) on 6-10-03

BY Mark Wenke DATE 6-10-03 CHECKED BY DWM

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION (Ferro Union)
28906318201000	APN 7351-34-58

DRILLING METHOD:	BORING NUMBER
Mari M2.5 auger, 4" bit Hand auger	SBL0353
SAMPLING METHOD:	**SHEET**
2" Brass sleeve, manual drive	1 OF 1
	DRILLING
	START / FINISH
SURFACE CONDITIONS:	TIME / TIME
0.5' Concrete	DATE 6-10-03 / DATE 6-10-03

DRILLING CONTRACTOR Gregg

BY Mark Wagner DATE 6-10-03 CHECKED BY DCM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Concrete
							1	CL	Very dark gray (10YR 3/1) CLAY w/ Sand and some silt and gravel, moist, stiff
							2		
							3		
					0.1	55501828	4		- Becomes dark grayish-brown (2.5Y, 4/2), sandy, soft
							5	SC	~~B~~ ~~Brown~~ dark yellowish-brown (10YR, 4/4) clayey fine SAND w/ some gravel, moist, med. dense
							6		Boring completed to 5.0' on 6-10-03
							7		
							8		
							9		
							10		

BORING LOG

LOCATION OF BORING



DATUM... Ferro-Union Bldg. ELEVATION

JOB NUMBER	LOCATION (Ferro Union)
2890618.01000	APN 7351-34-58
DRILLING METHOD:	BORING NUMBER
Mobil M25 auger, 4" O.D. Hand Auger	SBL0354
SAMPLING METHOD:	SHEET
2" Brass sleeve, manual drive	1 OF 1
#	DRILLING START / FINISH
SURFACE CONDITIONS:	TIME / TIME
0.5' Concrete	DATE 6-10-03 / DATE 6-10-03

DRILLING CONTRACTOR Cascade

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Concrete
							1	CL	Very dark grayish-brown (10 YR 3/2) clay w/ some fine sand & silt, trace gravel, moist
					0.2	SSS01829	2		
							3		Boring completed to 2.8' (Refusal - pipe ?)
							4		
							5		
							6		
							7		
							8		
							9		
							10		

BY Mark Wanek CHECKED BY DLM

DATE 6-10-03

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION
28906318.01000	APN 7351-34-58

DRILLING METHOD:	BORING NUMBER
Mark MZS auger, 4" I.D. Hand auger	SBL0355
SAMPLING METHOD:	**SHEET**
2" brass sleeves	1 OF 1
	DRILLING
	START / FINISH
SURFACE CONDITIONS:	TIME / TIME
0.25' Asphalt	DATE 6-10-03 / DATE 6-10-03

DRILLING CONTRACTOR Gregg

BY Mark Wanek DATE 6-10-03 CHECKED BY DUM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								GM	Very dark grayish brown (10YR, 3/1), & light olive gray (10YR, 7/2) silty GRAVEL w/ fine sand & some clay
							1		
						SSS01838	2	CL	Very dark gray (10YR, 3/1) CLAY w/ little fine sand, & trace silt & gravel, moist, stiff
							3		~~Hand auger~~ (7') Boring opens up into void space > 5' deep.
							4		
							5		
							6		
							7		
							8		
							9		
							10		

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION
28906818.01000	APN 7351-34-58

DRILLING METHOD:	BORING NUMBER
Manl M25 auger, 4" bit Hand auger	SBL0356
SAMPLING METHOD:	SHEET
2" Brass sleeve, manual drive	1 OF 1
	DRILLING START / FINISH
SURFACE CONDITIONS:	TIME / TIME
0.25' Asphalt	DATE 6-10-03 / DATE 6-10-03

DRILLING CONTRACTOR Gregg

BY Mark Wanek DATE 6-10-03 CHECKED BY DCM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								GM	Dark grayish-brown (10YR, 4/2) silty GRAVEL w/ sand & little clay, damp, dense
							1		
						SSS01831	2	CL	Very dark grayish-brown (10YR, 3/2) CLAY w/ sand & silt and trace gravel, moist, stiff
							3		(54, 4/4) - Becomes olive, sandy w/ silt
							4		
							5	SM	Dark yellowish-brown (10YR, 4/6) silty fine sand w/ trace clay, moist, dense Boring completed to 5.0' very dense
							6		
							7		
							8		
							9		
							10		

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION
28906318.01000	IFS APN 7351-33-31

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.0'	SBL0357
SAMPLING METHOD:	SHEET 1 OF 1
2" Brass sleeve, hammer drive	DRILLING START TIME 1355 DATE 6-10-03 / FINISH TIME 1420 DATE 6-10-03
SURFACE CONDITIONS: 0.25' Asphalt	

DRILLING CONTRACTOR Cal-Eng

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								GM	Very dark grayish-brown (10YR, 3/2) silty Gravel w/ clay & fine sand, moist, dense.
							1	CL	Dark yellowish-brown (10YR, 4/4) & brown (10YR, 4/3) sandy CLAY w/ silt & trace gravel, moist, dense.
		1400			0.1	SSS01832	2		
							3		
							4		
							5		Boring completed to 5.0' on 6-10-03
							6		
							7		
							8		
							9		
							10		

BY Mark Wawra DATE 6-10-03 CHECKED BY DLM

BORING LOG

LOCATION OF BORING

0 40
Scale 1"=60'



DATUM... ELEVATION

JOB NUMBER 2890638.01000

LOCATION Ferro-Union 7351 - 34.58

DRILLING METHOD: Hand Auger to 15.0'

BORING NUMBER SBL0358

SAMPLING METHOD: 2" Brass sleeve, manual drive

SHEET 1 OF 2

DRILLING START TIME 1030 DATE 6-23-03 FINISH TIME 1115 DATE 6-23-03

SURFACE CONDITIONS: Soil (clay)

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
					1.0		1	
					1.3		2	
		1045			1.2	SS501833	3	
							4	
							5	
							6	
							7	
							8	
							9	
							10	

0 CL

Brown (10YR, 4/3) CLAY w/ fine sand, moist, med. stiff

- Becomes olive gray (5Y, 4/2) & dk olive-gray (5Y, 3/2), very stiff, faint petroleum odor, little gravel

- Becomes brown (10YR, 4/3), some sand, little gravel, med. stiff

- Becomes yellowish-brown (10YR, 5/4), sandy w/ silt

BY Mark Wilmeth DATE 6-23-03 CHECKED BY [illegible]

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER 2890618.01000 7351-34-58

LOCATION Ferro - Union APN 7351-34-58

DRILLING METHOD: Hand Auger to 15.0'

BORING NUMBER SBL0358

SAMPLING METHOD: 2" Brass sleeve, manual drive

SHEET 2 OF 2

DRILLING START TIME 1030 HO DATE 6-23-03

DRILLING FINISH TIME 1055 1115 DATE 6-23-03

SURFACE CONDITIONS: Soil

DATUM... ELEVATION

DRILLING CONTRACTOR Cregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							10	SM
							11	
							12	
							13	
							14	
							15	
							16	
							17	
							18	
							19	
							20	

- Becomes yellow-brown (10YR, 5/5)

Boring completed to 15.0' on 6-23-03

BY Mark Wiese CHECKED BY Dlm

DATE 6-23-03

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION
2890318.01000	Fenco-Ulrich APN 7351-34-58
DRILLING METHOD: Hand Auger to 15.8'	BORING NUMBER SBL0359
SAMPLING METHOD: 2" Brass sleeve, manual drive	SHEET 1 OF 2
	DRILLING START 1100 / FINISH 1150
SURFACE CONDITIONS: Clay	TIME / DATE 6-23-03

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							0	CL
							1	
							2	
		1105			0.2			
							3	
							4	
							5	
		1130			0.2	SSS01834		
							6	
							7	SM
							8	
							9	
							10	

0 CL — Very dark gray (10YR, 3/1) and brown (10YR, 4/3) clay w/ some fine-coarse sand & trace gravel, damp, very stiff

- Becomes dark olive-gray (5Y, 3/2) & very dark gray (5Y, 3/1), moist, root & hair, faint petroleum odor, med. stiff

- Becomes very dark gray (2.5Y, 3/1) and black (2.5Y, 2.5/1), organic odor

7 SM — Becomes dark yellowish-brown (10YR, 4/6), sandy

Dark yellowish-brown (10YR, 4/6) silty very fine-fine SAND, moist, loose

BY Mark Wiedorn DATE 6-23-03 CHECKED BY DLM

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER: 28906318.01000

LOCATION: APN 7351-34-58

DRILLING METHOD: Hand Auger to 15.8'

BORING NUMBER: 359 SBL0360...

SAMPLING METHOD: 2" Brass sleeve, Manual drive

SHEET: 2 OF 2

DRILLING START TIME: 1100 DATE: 6-23-03

DRILLING FINISH TIME: 1150 DATE: 6-23-03

DATUM... ELEVATION

SURFACE CONDITIONS: Clear

DRILLING CONTRACTOR: Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							10	SM
							11	
							12	
							13	
							14	
							15	
							16	
							17	
							18	
							19	
							20	

Boring completed to 15.8' on 6-23-03

BY: Mark Schmidt DATE: 6-23-03 CHECKED BY: DLM

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION
28906318.01000	Feiro Union APN 7351-34-58
DRILLING METHOD: Mobil M25, Vibrating hammer	BORING NUMBER SBL0360
SAMPLING METHOD: 1.5" acetate sleeve, cont's core	SHEET 1 OF 2
	DRILLING START TIME 1200 DATE 6-23-03 / FINISH TIME 1300 DATE 6-23-03
SURFACE CONDITIONS: 0.2' Asphalt	

DRILLING CONTRACTOR Gregg

BY Mark Wanek DATE 6-23-03 CHECKED BY DUM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	
	4.0 / 2.8							CL	Very dark brown (10YR, 2/2) CLAY w/ sand & some silt, moist, med. stiff
							1		
		1207			0.3	SSS 01835	2		- faint petroleum odor / organic odor
							3		
	4.0 / 3.6						4		
							5		
							6	SM	Yellowish-brown (10YR, 5/6) silty, very fine SAND, moist, dense, rust casts
							7		
	4.0 / 3.4						8		Brownish light olive-brown (2.5Y, 5/4)
							9		
							10		

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER	LOCATION
2890618.01000	APN 7351-34-58'

DRILLING METHOD:	BORING NUMBER
Mark 1425 vibratory hammer	SBL0360

SAMPLING METHOD:	SHEET
1.5" acetate liners.	2 OF 2

DRILLING CONTRACTOR Gregg

DATUM... ELEVATION

SURFACE CONDITIONS:	DRILLING START TIME	DRILLING FINISH TIME
0.2' asphalt	1200	1300
	DATE 6-23-03	DATE 6-23-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							10	SM	
							11		
							12		
	4.0 / 3.9				1.7				
							13		- Becomes loose, clayey, increased root mats
									- Becomes increased silt
							14		
							15		
							16		
									Boring completed to ~16' on 6-23-03
							7		
							8		
							9		
							0		

BY Mike Wanke DATE 6-23-03 CHECKED BY DLM

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION
28906318.01000	Ferro-Union APN 7351-34-58

DRILLING METHOD: Hand Auger to 15.3'

BORING NUMBER: SBL0361

SAMPLING METHOD: 2" Brass sleeve, manual drive

SHEET: 1 OF 2

DRILLING: START TIME 1500 DATE 6-23-03; FINISH TIME 1545 DATE 6-23-03

SURFACE CONDITIONS: CLAY

DRILLING CONTRACTOR Gregg

BY Mark Wanek DATE 6-25-03 CHECKED BY DLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							0	
							1	
					0.3		2	
							3	
		1520			5.5	SSS01836	4	
					32			
							5	
							6	
							7	
							8	
							9	
							10	
								CL-SC

Brown (10YR 4/3) CLAY w/ sand & some silt, moist, med. stiff

- Becomes very dark grey (5Y 3/1)

- Becomes olive grey (5Y 4/2), moderate-strong petroleum odor at 3.6'

- Becomes yellowish-brown (10YR 5/6), ~~[illegible]~~ sandy, no pet. odor at ~7.7'

Yellowish-brown (10YR 5/6) sand, CLAY-clayey fine SAND, moist, med dense

BORING LOG

LOCATION OF BORING

JOB NUMBER: 25906318.01000

LOCATION: APN · 7351-34-58

DRILLING METHOD: Hand Auger to 15.3'

BORING NUMBER: SBL 0361

SAMPLING METHOD: 2" Brass Sleeve, manual drive

SHEET: 2 OF 2

DRILLING START TIME: 1500 DATE: 6-23-03

DRILLING FINISH TIME: 1545 DATE: 6-23-03

DATUM... ELEVATION

SURFACE CONDITIONS: Clay

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							10	SC-CL
							11	SM
							12	
							13	
							14	
							15	
							16	
							17	
							18	
							19	
							20	

Light olive-brown (2.5Y, 5/4) silty, very fine SAND w/ trace clay, moist, med. dense

"Boring completed to 15.3' on 6-23-03

BY Mark Johnson CHECKED BY DUM

DATE 6-23-03

DAMES & MOORE

BORING LOG

SBL0360

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER 28906318.01000

LOCATION Ferro-Union APN 7351-34-58

DRILLING METHOD: Mari M25 vibratory hammer

BORING NUMBER SBL0362

SAMPLING METHOD: 1.5" Acetate liner, cont's core

SHEET 1 OF 2

DRILLING CONTRACTOR Geo-Eng

DRILLING START TIME 1550 DATE 6-23-03

DRILLING FINISH TIME 1640 DATE 6-23-03

SURFACE CONDITIONS: CLAY

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	CL	Very dark grayish-brown (10YR, 3/2) CLAY w/ sand and trace gravel, mottled w/ dark yellowish-brown (10YR, 4/4)
	4.0 / 3.6	1610			0.2		1		
					1.7	SSS01837	2		
									- Becomes solid color dark brown (10YR, 3/3) no gravel
							3		
					0.6				
	4.0 / 3.7	1620			0.2		4		
							5		
					0.3 / 1.7 ppm		6		- Becomes trace gravel
							7	SM	yellowish-brown (5/4) silty very fine SAND ~~w/ clay~~
					0.2 / 0.6 ppm				
							8		
	4.0 / 3.6	1628			0.6				
							9		- Becomes dark yellowish-brown (10YR, 4/4), root casts, trace gypsum
					1.9		10		

BY Mark Wanek DATE 6-23-03 CHECKED BY DUM

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER: 2890638.01000

LOCATION: APN 7351-34-58

DRILLING METHOD: Mark M25 vibratory hammer

BORING NUMBER: SBL0362

SAMPLING METHOD: 1.5" acetate liners, cont'l core

SHEET: 2 OF 2

DRILLING START TIME: 1550 DATE: 6-23-03

DRILLING FINISH TIME: 1640 DATE: 6-23-03

SURFACE CONDITIONS: clay

DATUM... ELEVATION

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
					1.9		10	SM
							11	
					0.9			
							12	
	4.0 / 3.9	1637			0.5			
							13	
							14	
							15	
					1.2			
							16	
							17	
							18	
							19	
							20	

- Becomes light olive-brown (2.5 YR, 5/4) decreased silt, mod. dense

Boring completed to ~16' on 6-23-03

BY Mark Ubaldo DATE 6-23-03 CHECKED BY DLM

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION
28906318.01000	AS Johnston APN 7351-33-26

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.6' Mad M25, vibration hammer	SBL0363
SAMPLING METHOD:	SHEET
2" Brass sleeve, manual drive 1.5" acetate liners, continuous core	1 OF 2

DRILLING CONTRACTOR Gregg

DRILLING START TIME	DRILLING FINISH TIME
0730	0840
DATE 6-24-03	DATE 6-24-03

SURFACE CONDITIONS: 0.3' Asphalt

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								CL	Very dark gray (10YR, 3/1) CLAY w/ trace fine sand and silt and moist, stiff
							1		
							2		
					12.5				- Becomes olive-brown (2.5Y, 4/3), w/ gravel
					0.1				slight volatile/petrochemical odor
							3		
							4		
	4.0 / 3.1	0823			1.2				
							5	GW	Black (10YR, 2.5/1) clayey gravel, dry, very dense
								CL	Dark olive-gray (5Y, 3/2) CLAY w/ sand and some silt, moist, med. stiff, light pet. odor
					0.1		6		
							7		
		0823	6.8-7.8		30.9	SSSD1838			
					82 MW			SM	Very dark gray (5Y, 3/1) silty fine SAND moist, med. dense, mod. volatile odor
	4.0 / 3.4	0830			0.2		8		
							9		
					34 MW				
							10		- Becomes olive-brown (2.5Y, 4/3) & light olive-brown (2.5Y, 5/6)

BY Mark Wanek DATE 6-24-03 CHECKED BY DLM

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER	LOCATION
28906318.01000	APN 7351-33-26

DRILLING METHOD:	BORING NUMBER
Hand Auger to 5.6' H25, vibratory	SBL0363
SAMPLING METHOD:	SHEET
2" Brass Sleeve, manual drive 1.5" acetate liner, continuous core	2 OF 2

DRILLING CONTRACTOR Gregg

DATUM... ELEVATION

DRILLING	START	FINISH
TIME	0730	0840
DATE	6-24-03	6-24-03

SURFACE CONDITIONS:
0.3' Asphalt

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
					34		10	SM	
									- faint not coats
							11		
					~~39.9~~ 7				
							12		
	4.0 / 3.8	0835			0.1 ~~0.2~~				- decreased odor
							13		
					2.8 ~~3.4~~				- increased odor
							14		
							15		
									- Becomes light olive-brown (2.5Y 5/6), little odor
					2.7		16		
									~~Becomes~~ Boring completed to ~16' on 6-24-03
							17		
							18		
							19		
							20		

BY Mark Wenk CHECKED BY Dan

DATE 6-24-03

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... ELEVATION

JOB NUMBER	LOCATION (Arden)
28906318.01000	APN 7351-31-22/28

DRILLING METHOD: Hand Auger to 2.5'; Mark M25 vibratory hammer

BORING NUMBER: SBL0364

SAMPLING METHOD: 2" Brass sleeve, manual drive; 1.5" acetate liner, continuous core

SHEET: 1 OF 2

SURFACE CONDITIONS: 0.25' Asphalt

DRILLING

START TIME	FINISH TIME
0850	0950
START DATE	FINISH DATE
6-24-03	6-24-03

DRILLING CONTRACTOR Cruzen

BY Mark Wanek CHECKED BY DLM

DATE 6-24-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
								SC	Light yellowish-brown (2.5Y, 6/4) clayey fine SAND w/ silt and gravel/very coarse sand
							1		
							2		
	4.0/3.8	0930	2.0-2.5		0.2	SS501839			
	4.0/3.8				0.2		3		
					0.1				
							4		
								CL	Dark grayish-brown (10YR, 4/2) & dark yellowish-brown (10YR, 4/4) sandy CLAY w/ some silt and gravel
							5		
							6		
					0.1				
	4.0/3.1	0947			0.1		7		Becomes gravelly
		0947	7.0-7.5		0.1	SS501840			
							8		
								SC	Dark yellowish-brown (10YR, 4/4) clayey fine SAND w/ silt, moist, med. dense, root casts
							9		
					0.1				
							10		

DAMES & MOORE

BORING LOG

LOCATION OF BORING

JOB NUMBER: 28906318.01000

LOCATION: APN 7351-31-22/28

DRILLING METHOD: Hand Aug- to 2.5'; Mcrl M25 vibratory hammer

BORING NUMBER: SBL03B64

SAMPLING METHOD: 2" Brass sleeve, manual drive; 1.5" acetate liners, continuous core

SHEET: 2 OF 2

DRILLING: START TIME 0850, DATE 6-24-03; FINISH TIME 0950, DATE 6-24-03

SURFACE CONDITIONS: 0.25' Asphalt

DATUM... ELEVATION

DRILLING CONTRACTOR Gregg

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
					0.1		10	SC	
	4.0 / 3.2				0.1		11		Brown Sand
							12		
					0.1		13	SM	Dark yellowish-brown (10YR 4/4) silty fine-med grained SAND w/ clay (decreasing gradually to trace clay by bottom of boring)
							14		
							15		Boring completed to ~14.5' on 6-24-03
							16		
							17		
							18		
							19		
							20		

BY Mike Jarvis CHECKED BY DCM

DATE 6-24-03

DAMES & MOORE

BORING LOG

LOCATION OF BORING



DATUM... Scale 1"=10'

ELEVATION

JOB NUMBER	LOCATION
28906318.01000	Arden APN 735-31-21

DRILLING METHOD:	BORING NUMBER
Mark M25 vibratory hammer	SBL0365
SAMPLING METHOD:	SHEET
1.5" acetate sleeves	1 OF 2
	DRILLING START / FINISH
SURFACE CONDITIONS:	TIME: 1030 / 1200
0.25' Asphalt	DATE: 6-24-03 / 6-24-03

DRILLING CONTRACTOR Gregg

BY Mark Wanek DATE 6-24-03 CHECKED BY DLM

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH	
							0	A/C	Asphalt
	4.0 / 2.8	1048			0.1			CL	Dark brown (10YR, 3/3) sandy CLAY w/ silt & fine gravel
							1		
		1048	1.5-2.0		0.2	SSS01841	2		
									- Becomes intermittent concrete / gravel debris
							3		
							4		
	4.0 / 1.0				0.1				- Becomes no concrete, gravelly, mottled w/ dark yellowish-brown
					0.1		5		
							6		
							7		
	4.0 / 3.7	1115					8		Fibrous pipe
		1115	9.25-9.75		0.1	SSS01842	9	SC	Dark yellowish-brown (10YR, 4/6) clayey fine SAND w/ silt, moist, dense, root casts
							10		

BORING LOG

LOCATION OF BORING

JOB NUMBER 28906318.01000

LOCATION Arden APN 7351-31-21

DRILLING METHOD: Mod 1125 vibratory hammer

BORING NUMBER SBL036&5

SAMPLING METHOD: 1.5" acetate sleeves

SHEET 2 OF 2

DRILLING CONTRACTOR Greaf

DATUM... ELEVATION

SURFACE CONDITIONS: 0.25' Asphalt

DRILLING START TIME 1030 DATE 6-24-03

DRILLING FINISH TIME 1200 DATE 6-24-03

SAMPLER TYPE	FEET DRIVEN / FEET RECOVERED	TIME	SAMPLE DEPTH	BLOWS/FT. SAMPLER	PID SAMPLE	SAMPLE NO.	DEPTH IN FEET	SOIL GRAPH
							10	SC
							11	
					0.1			
							12	
	4.0 / 2.1	1145						
							13	
					0.1		14	
							15	
							16	
							17	
							18	
							19	
							20	

- Root casts more prominent
- Becomes increased silt

Boring completed to 16' on 6-24-03

BY Mike Lubenetz DATE 6-24-03 CHECKED BY Dun

DAMES & MOORE