Preliminary Comments from Members of the EPA Science Advisory Board (SAB) Panel for the Review of EPA's Hydraulic Fracturing Study Plan

As Of May 18, 2011

COMMENTS FROM DR. CONNIE K. SCHREPPEL

Comments to 4/28/11 Draft SAB Report on the Review of EPA's Draft Hydraulic Fracturing Study Plan

The Honorable Lisa P. Jackson
Administrator
U.S. Environmental Protection Agency
1200 Pennsylvania Avenue, N.W.
Washington, D.C. 20460

Subject: Review of EPA's Draft Hydraulic Fracturing Study Plan

Dear Administrator Jackson:

In January 2010, EPA's Office of Research and Development (ORD) initiated planning for a study to assess the potential impacts of hydraulic fracturing on drinking water resources, and developed a Scoping Document in March 2010 that was reviewed by the Science Advisory Board (SAB) in an open meeting on April 7-8, 2010. SAB's Report on its review of the study scope was provided to the Administrator in June 2010. EPA considered SAB's comments, and then developed a draft Hydraulic Fracturing Study Plan and requested SAB review of the draft Study Plan. The draft Study Plan assesses the potential impacts of hydraulic fracturing on drinking water resources, and identifies the driving factors that affect the severity and frequency of any potential impacts. The draft Study Plan proposes to assess potential impacts from five aspects of the water lifecycle associated with hydraulic fracturing: Water Acquisition, Chemical Mixing, Well Injection, Flowback and Produced Water, and Water Treatment and Waste Disposal. As noted in the draft Study Plan, EPA plans to study each of the hydraulic fracturing (HF) lifecycle stages through literature reviews, data gathering and analysis, modeling, laboratory investigations, field investigations, and case studies. The Study Plan includes engagement with states and a variety of companies and organizations to leverage existing data and knowledge.

The SAB was asked to comment on various aspects of EPA's approach for the Study Plan, including the proposed water lifecycle framework for the Study Plan, the proposed research questions, and the proposed research approach, activities, and outcomes. The enclosed report provides the advice and recommendations of the SAB through the efforts of the SAB Hydraulic Fracturing Study Plan Review Panel.

In general, the SAB believes that EPA's research approach as presented in the draft Study Plan is appropriate. The SAB recommends several changes for the Study Plan in order to meet the limited schedule and budget constraints of the project. In this spirit the SAB identifies several areas of the Study Plan that can be narrowed and focused. The SAB believes that EPA is taking on an enormous challenge with limited budget and within a very limited time frame.

EPA identified specific potential outcomes for the research related to each step in the HF water lifecycle. The SAB believes that all of the potential water acquisition research outcomes, and that most but not all of the potential chemical mixing research outcomes can be achieved. The SAB believes that some of the potential well injection research outcomes, flowback and produced water research outcomes, and wastewater treatment and waste disposal research outcomes can be achieved.

The SAB believes that the Study Plan provides inadequate detail on how to address the overall research questions presented and discussed within the draft Study Plan, and that EPA should develop more specific research questions that could be answered within the budget and time constraints of the project. The SAB believes it will not be possible to cover all facets of the proposed research activities for the assessment of potential impacts of HF well injection on drinking water resources within the time allotted for the research activities. The SAB recommends that EPA use a wide variety of sources available to EPA in order to increase the chances of success of the research program, and analyze data from HF service companies and states to provide additional insight.

The SAB also recommends that EPA consider three steps of the risk assessment paradigm (i.e., hazard identification, dose-response assessment, exposure assessment, and risk characterization) to assess and prioritize research activities for each water lifecycle stage presented in the draft Study Plan, and to focus research questions. The SAB recommends that EPA focus on potential human exposure, followed by hazard identification if sufficient time and resources are available. The SAB anticipates that the primary opportunity for human health exposure is likely to be through surface waters, and recommends that EPA's first order human health exposure assessment focus on surface water management of flowback and produced waters, and disposal of treated waste water. The SAB recommends that no toxicity testing be conducted at this time due to time and cost constraints, and that EPA should evaluate through existing databases the toxicity of selected constituents determined to have a high potential for exposure.

The SAB has a number of suggestions for improving the draft Study Plan and EPA's hydraulic fracturing activities. Some of the key SAB suggestions include the following:

- Clarify whether the research focus is strictly on hydraulic fracturing in shale gas production or will consider hydraulic fracturing in conventional natural gas production, coal bed methane production, or other types of natural gas and oil extraction activity. Do not generalize focused research results across all types of HF activity.

- Identify and characterize potential environmental justice concerns associated with hydraulic fracturing and explicitly recognize such concerns in the research questions.

- Define and differentiate flowback and produced water, and clearly distinguish such waters from other water used during the hydraulic fracturing process. This is a key recommendation because the handling, treatment and disposal of flowback and produced water represents the most likely important route of exposure and potential for adverse impacts on drinking water on a national level.

- Gather currently available information on the composition of flowback and produced water from the hydraulic fracturing process, including proprietary information where possible.

- Reconsider the present definition of "drinking water resources" related to hydraulic fracturing activities as waters limited to those with less than 10,000 mg/L of total dissolved solids, given recent advances in membrane desalination and likely changes in perspectives of what constitutes potential drinking water sources in the future.

- Include the following constituents in EPA's analysis of impacts of water acquisition and other HF processes on water quality: hydrogen sulfide, ammonium, radon, iron, manganese, arsenic, selenium, total organic carbon, and bromide, in addition to HF fluid constituents and formation chemicals. EPA should also assess the potential of constituents in HF-impacted waters to form disinfection by-products during drinking water treatment.

- Avoid a focus on Maximum Contaminant Level (MCL) parameters in analyzing potential impacts of HF on water quality, as MCLs are insufficient for assessing all potentially significant impacts on drinking water quality.

- Focus study of flowback and produced water constituents on literature searches on POTW and industry management practices with similar waters, and assess the need for any special storage, handling, management, or disposal controls for solid residuals after treatment. Hydraulic fracturing return flows contain many constituents that are similar to those for which treatment technologies exist within the practice of industrial wastewater treatment.

- Identify or estimate the uncertainty or confidence in all research conclusions.

The SAB appreciates the opportunity to provide EPA's Office of Research and Development with advice on this important subject. We look forward to receiving the Agency's response and potential future discussions with the Agency.

Sincerely,

Dr. Deborah L. Swackhamer, Chair
Science Advisory Board

Dr. David A. Dzombak, Chair
SAB Hydraulic Fracturing Study Plan
Review Panel

Enclosure

NOTICE

This report has been written as part of the activities of the EPA Science Advisory Board (SAB), a public advisory group providing extramural scientific information and advice to the Administrator and other officials of the Environmental Protection Agency. The SAB is structured to provide balanced, expert assessment of scientific matters related to problems facing the Agency. This report has not been reviewed for approval by the Agency and, hence, the contents of this report do not necessarily represent the views and policies of the Environmental Protection Agency, nor of other agencies in the Executive Branch of the Federal government, nor does mention of trade names of commercial products constitute a recommendation for use. Reports of the SAB are posted on the EPA Web Site at http://www.epa.gov/sab.

U.S. Environmental Protection Agency
Science Advisory Board
HYDRAULIC FRACTURING STUDY PLAN REVIEW PANEL

CHAIR

Dr. David A. Dzombak, Walter J. Blenko Sr. Professor of Environmental Engineering, Department of Civil and Environmental Engineering, Carnegie Mellon University, Pittsburgh, PA

PANEL MEMBERS

Dr. George Alexeeff, Acting Director, Office of Environmental Health Hazard Assessment, California Environmental Protection Agency, Oakland, CA

Dr Tom Ballestero, Professor, Civil Engineering, University of New Hampshire, Durham, NH

Dr. Mark Benjamin, Professor, Department of Civil and Environmental Engineering, University of Washington, Seattle, WA

Dr. Michel Boufadel, Professor of Environmental Engineering, Civil and Environmental Engineering, College of Engineering, Temple University, Philadelphia, PA

Dr. Elizabeth Boyer, Associate Professor, School of Forest Resources and Assistant Director, Pennsylvania State Institutes of Energy & the Environment, and Director, Pennsylvania Water Resources Research Center, Pennsylvania State University, University Park, PA

Mr. David Burnett, Directory of Technology, GPRI, Department of Petroleum Engineering, Look College of Engineering, Texas A&M University, College Station, TX

Dr. Thomas L. Davis, Professor, Department of Geophysics, Colorado School of Mines, Golden, CO

Dr. Shari Dunn-Norman, Professor, Geological Sciences and Engineering, Missouri University of Science and Technology, Rolla, MO

Dr. John P. Giesy, Professor and Canada Research Chair, Veterinary Biomedical Sciences and Toxicology Centre, University of Saskatchewan, Saskatoon, Saskatchewan, Canada

Dr. Jeffrey Griffiths, Associate Professor, Department of Public Health and Community Medicine, School of Medicine, Tufts University, Boston, MA

Dr. Philip Gschwend, Professor, Civil and Environmental Engineering, Massachusetts Institute of Technology, Cambridge, MA

Dr. Cynthia M. Harris, Director and Professor, Institute of Public Health, Florida A&M University, Tallahassee, FL

Dr. Nancy K. Kim, Senior Executive, Health Research, Inc., Troy, NY

Dr. Cindy M. Lee, Professor, Department of Environmental Engineering and Earth Sciences, Clemson University, Anderson, SC

Dr. Duncan Patten, Research Professor, Hydroecology Research Program, Department of Land Resources and Environmental Sciences, Montana State University, Bozeman, MT

Dr. Stephen Randtke, Professor, Department of Civil, Environmental, and Architectural Engineering, University of Kansas, Lawrence, KS

Dr. Danny Reible, Professor, Department of Civil, Architectural and Environmental Engineering, University of Texas, Austin, TX

Dr. Connie Schreppel, Director of Water Quality, Mohawk Valley Water Authority, Utica, NY

Dr. Geoffery Thyne, Sr. Research Scientist, Enhanced Oil Recovery Institute, University of Wyoming, University of Wyoming, Laramie, WY

Dr. Jeanne VanBriesen, Professor, Civil and Environmental Engineering, Carnegie Mellon University, Pittsburgh, PA

Dr. Radisav Vidic, Professor and Chairman, Civil and Environmental Engineering, University of Pittsburgh, Pittsburgh, PA

SCIENCE ADVISORY BOARD STAFF

Mr. Edward Hanlon, Designated Federal Officer, U.S. Environmental Protection Agency, Science Advisory Board Staff, Washington, DC

Table of Contents

1. EXECUTIVE SUMMARY 1

2. INTRODUCTION 10

2.1. BACKGROUND 10
2.2. CHARGE TO THE PANEL 11

3. RESPONSE TO THE CHARGE QUESTIONS 13

3.1. WATER USE IN HYDRAULIC FRACTURING 13
3.2. RESEARCH QUESTIONS 15
3.3. RESEARCH APPROACH 20
3.4. PROPOSED RESEARCH ACTIVITIES - WATER ACQUISITION 29
3.5. PROPOSED RESEARCH ACTIVITIES - CHEMICAL MIXING 32
3.6. PROPOSED RESEARCH ACTIVITIES - FLOWBACK AND PRODUCED WATER 35
3.7. PROPOSED RESEARCH ACTIVITIES - WELL INJECTION 41
3.8. PROPOSED RESEARCH ACTIVITIES - WASTEWATER TREATMENT AND WASTE DISPOSAL 45
3.9. RESEARCH OUTCOMES 48

APPENDIX A: EPA'S CHARGE TO THE PANEL 58

Abbreviations and Acronyms

BMP	Best Management Practices
BTEX	Benzene, Toluene, Ethylbenzene, and Xylenes
CWT	Centralized Waste Treatment
CWA	Clean Water Act
DOE	U.S. Department of Energy
DBP	Disinfection By-product
EPA	U.S. Environmental Protection Agency
HF	Hydraulic Fracturing
MCL	Maximum Contaminant Levels
NETL	DOE's National Energy Technology Laboratory
O&M	Operation & Maintenance
ORD	EPA Office of Research and Development
POTW	Publicly Owned Treatment Works
PWSS	Public Water Supply Systems
QSAR	Quantitative Structure-Activity Relationships
Rn	Radon
SAB	EPA Science Advisory Board
TDS	Total Dissolved Solids
TOC	Total Organic Carbon
UIC	Underground Injection Control
USDW	Underground Sources of Drinking Water
USGS	U.S. Geological Survey

1. EXECUTIVE SUMMARY

In January 2010, EPA's Office of Research and Development (ORD) initiated planning for a study to assess the potential impacts of hydraulic fracturing on drinking water resources. EPA proposed a study scope in March 2010 that was reviewed by the Science Advisory Board (SAB) in an open meeting on April 7-8, 2010; SAB's Report on its review of the study scope was provided to the Administrator in June 2010. Subsequently, EPA developed a draft *Hydraulic Fracturing Study Plan* and requested SAB review of the draft Plan. The draft *Study Plan* assesses the potential impacts of hydraulic fracturing on drinking water resources, and identifies the driving factors that affect the severity and frequency of any potential impacts. The draft *Study Plan* proposes to assess potential impacts from five aspects of the water lifecycle associated with hydraulic fracturing: Water Acquisition, Chemical Mixing, Well Injection, Flowback and Produced Water, and Water Treatment and Waste Disposal. As noted in the draft Study Plan, EPA plans to conduct this lifecycle analysis through literature reviews, data gathering and analysis, modeling, laboratory investigations, and field investigations and case studies.

The SAB was asked to comment on various aspects of EPA's approach for the Study Plan, including EPA's proposed water lifecycle framework for the study plan, EPA's proposed research questions that would address whether or not hydraulic fracturing impacts drinking water resources, and EPA's proposed research approach, activities, and outcomes. The enclosed report provides the advice and recommendations of the SAB through the efforts of the SAB Hydraulic Fracturing Study Plan Review Panel.

In general, the SAB found that EPA's overall approach for the draft EPA Study Plan to be appropriate and comprehensive. The SAB recommends several changes for the Study Plan in order to meet the limited schedule and budget constraints of the project. The SAB also identifies several areas of the Study Plan that can be enhanced and focused. While a more detailed description of the technical recommendations is described in this SAB Report, the key points and recommendations are highlighted below.

<u>Charge Question 1: Water Use in Hydraulic Fracturing</u>

In general, the SAB believes that EPA's use of the water lifecycle depicted in Figure 7 of the draft Study Plan is an appropriate framework to characterize hydraulic fracturing and to identify the potential drinking water issues. However, the SAB has several recommendations to strengthen the framework and provide an improved assessment of potential drinking water issues. EPA's framework should take a broader view with regard to water quantity than depicted in Figure 7, and link water fluxes associated with hydraulic fracturing to water flows in the surrounding natural hydrological cycle. The water mass balance that accounts for waters entering and leaving the system is a critical issue, and EPA should initially focus the water mass balance assessment towards the case study efforts. EPA should also assess interbasin transfers of flowback and produced water in order to identify possible water quality and quantity issues

associated with such transfers. In addition, EPA should consider additional sources of water quality impacts beyond those indicated in Figure 9a.

Charge Question 2: Research Questions

EPA has identified a comprehensive set of research questions to address the primary mechanisms and pathways that can allow hydraulic fracturing to impact drinking water resources. The questions cover each step of the life cycle of a hydraulic fracturing process that can impact drinking water and are appropriately focused on the unique aspects of hydraulic fracturing that can lead to such impacts. The SAB provides suggestions for supplementing and revising the existing questions. These suggestions are designed to recognize explicitly key issues that may not be adequately addressed in the current questions or to frame more appropriately the questions given the limited available time and funding to the effort. The SAB is concerned that many of the questions may not be answerable given the limited available time and funding.

The SAB has overarching comments that may affect the primary and secondary research questions and how they are answered at each life cycle stage. An important challenge facing the study is the diverse nature of hydraulic fracturing operations around the country. The geological setting, the hydrological setting, the community setting and the requirements and standard operating procedures at each stage of the hydraulic fracturing life cycle vary across the country. These differences can give rise to fundamental differences in the nature of the impacts to drinking water resources.

Potential impacts to drinking water may be the result of the hydraulic fracturing process or the result of the manner in which it is implemented. Identifying potential impacts to drinking water resources that are associated with failure to employ best management practices may not be useful unless the linkage to those management practices is identified.

Another overarching issue is the importance of assessing uncertainty at each step in the research study. Given time and resource constraints, the studies will not be able to answer all questions with a high degree of certainty. The SAB recommends that EPA explicitly identify or estimate the uncertainty or confidence in all research conclusions. The quality of the information on which the research was based as well as any uncertainties arising in the conduct of the research should be evaluated, at least in a preliminary manner.

An additional overarching issue is that EPA needs to view the environmental concerns and issues in the context of the local community, and that potential outcomes should be identified by EPA for environmental justice issues. Concerns such as environmental justice and the effects of hydraulic fracturing on disproportionately impacted communities should be an explicit research question. The SAB recommends that potential environmental justice concerns associated with hydraulic fracturing should be identified and characterized as part of the current study and that this should be explicitly recognized in the research questions. The SAB recommends that a separate section of the research plan be devoted explicitly to environmental justice issues. A key component of this is a need to assess the impact of hydraulic fracturing in context with other

environmental challenges and difficulties associated with societal adaption to change that might be faced by the community to develop a sense of the cumulative impact. In addition, the SAB is concerned that certain communities may be bearing a disproportionate share of the environmental and human health risk burden relative to the communities benefitting from hydraulic fracturing activities. EPA should consider environmental justice perspectives when assessing local environmental and health impacts through analyses such as cost-benefit evaluations which often integrate over larger scales.

The Study Plan should address the cumulative consequences of carrying out multiple HF operations in a single watershed or region. While detailed research on cumulative impacts may be beyond the scope of the current study, the incremental impacts of hydraulic fracturing operations should be well characterized in the current study and a framework for assessment of cumulative impacts should be established. This will provide the foundation for subsequent assessment of total environmental exposures and risks, and cumulative impacts.

In addition, the SAB recommends that EPA clarify whether the research focus is on hydraulic fracturing in shale gas production, conventional natural gas production, coal bed methane production, or other types of hydraulic fracturing activity.

In addition to these general concerns, the SAB has a number of specific concerns associated with the research questions at individual lifecycle stages. These are presented in the discussion associated with the subsequent charge questions.

Charge Question 3: Research Approach

The SAB believes that EPA is taking on an enormous challenge with limited budget and within a limited time frame. EPA should conduct a well-focused study so that critical research questions are identified, approaches are designed that will enable answering those questions, and analysis is included to validate the conclusions that are reached.

The SAB believes that the Study Plan provides inadequate detail on how to address the overall research questions presented in Table 2 and discussed within the draft Study Plan, and that EPA should present more specific research questions that could be answered within the budget and time constraints of the project. To the extent that the Study Plan is being designed to inform decision-making related to an EPA regulatory framework, the framework should include specific research questions aimed at this objective.

The SAB finds that the scenario evaluation does not, but should, cross all research questions. The SAB notes that scenario evaluations beyond the case studies for water acquisition and flowback water, and their modeling, would particularly assist EPA's research effort.

A suggested area for additional specific research is on the capacity of microseismic data to provide detailed information about extent of fracturing and to assist in the hydraulic fracturing modeling (see discussion under Charge Question 4).

The SAB believes that the Study Plan provides limited detail on anticipated data acquisition, analysis, management, and storage (including model simulation results), and recommends that EPA revise the draft Study Plan to include such details. The SAB recommends that EPA consider using existing data acquisition and analysis methods rather than develop new methods due to time and budget constraints. EPA should also carefully consider the quality of various types of data that would be used within the analysis (industry data, local and non-industry data), and consider archiving samples for later use.

The SAB finds that the Study Plan overemphasizes case studies in the study approach, and underemphasizes the review and analysis of existing data and the use of scenario analysis. The SAB believes there is significant value to the synthesis of existing data, and that EPA should review all available data sources to learn from what is already known about the relationship of hydraulic fracturing and drinking water resources. The SAB also provides citations for additional literature that EPA should consider in order to ensure a comprehensive understanding of the trends in the hydraulic fracturing process and the potential impacts of hydraulic fracturing on drinking water resources.

<u>Charge Question 4(a): Proposed Research Activities - Water Acquisition</u>

The SAB recommends that EPA reconsider the definition of “drinking water resources” related to hydraulic fracturing activities as waters with less than 10,000 mg/L of total dissolved solids, given recent advances in membrane desalination and likely changes in perspectives of what constitutes potential drinking water sources in the future.

The SAB recommends that the Study Plan include an additional research effort to collect baseline data in a given area before HF activity begins, so that significant changes in water availability or water quality caused by HF activity can be more readily documented.

SAB also recommends that EPA consider developing a “vulnerability index” or a list of criteria that could be used to indicate situations where a water supply is vulnerable to adverse impacts on water quality or quantity. SAB recognizes that given EPA’s limited available time and budget, this activity could potentially be delayed until there is more experience.

The SAB recommends that EPA’s list of analytes that would be studied to assess the impacts of water acquisition and other HF activities on water quality should specifically include the following constituents: hydrogen sulfide, ammonium, radon, iron, manganese, arsenic, selenium, total organic carbon, and bromide, in addition to HF fluid constituents and likely formation chemicals (e.g., benzene, toluene, ethylbenzene, and xylenes - BTEX, surfactants, and biocides). EPA should also assess the potential of constituents in HF-impacted waters to form disinfection by-products(including trihalomethanes, haloacetic acids, total organic halogen, and other halogenated organic compounds) in drinking water treatment.

Also, the SAB believes that Maximum Contaminant Levels (MCLs) established under the Safe Drinking Water Act are not sufficient for assessing all potentially significant impacts on drinking water quality. The SAB recommends that EPA include in its analysis potential impacts on water

quality that do not involve MCL exceedances. EPA should also examine trends in water quality associated with HF water acquisition and determine whether adverse impacts will result if these trends continue.

Charge Question 4(b): Proposed Research Activities - Chemical Mixing

The SAB supports EPA's proposed approach to analyze existing data rather than collect samples for analysis, and believes that EPA's planned effort to gather data from nine hydraulic fracturing service companies will likely provide sufficient information on the composition of HF fluids provided the companies cooperate and supply the information in a timely manner. SAB recommends that EPA also gather HF fluid composition data from state(s) collecting such data, and consider the role that recycling and reuse of HF fluids will play in influencing both quantity and composition of HF fluids.

Given the limited available time and budget for the current project, the SAB believes that in-depth study of toxicity is not possible, and thus supports EPA's plan to evaluate the toxicity of the selected constituents of selected constituents determined to have a high potential for exposure through existing databases. SAB recommends that EPA assess potential pathways of exposure to the public through drinking water (while recognizing that other important exposure routes such as through air and diet may also exist).

While it would be helpful if EPA developed indicators of contamination, it may be difficult to achieve a practical indicator approach within the time allotted for the current study. The SAB also believes that EPA should give low priority to development of analytical methods for specific components for which there are no existing certified methods.

SAB generally supports EPA's plans to identify factors that influence the likelihood of contamination of drinking water resources. Although SAB believes that EPA will identify a number of factors that influence the likelihood of contamination of drinking water resources, the list of factors may not be complete, the project time and budget will not allow time for a complete evaluation of the factors, and the results should not be generalized across all HF sites.

SAB does not believe that case studies alone will provide sufficient information regarding effectiveness of mitigation approaches in reducing impacts to drinking water resources. SAB suggests that EPA analyze data from HF service companies and states in order to provide additional insight. The retrospective case studies may also be a source of useful information about approaches that failed to prevent or control impacts.

Charge Question 4(c): Proposed Research Activities - Well Injection

The SAB believes that EPA's proposed research activities for the assessment of potential impacts of well injection related to hydraulic fracturing on drinking water resources are scientifically adequate. The SAB believes it will not be possible to cover all facets of the proposed research within the time allotted for the research activities, and recommends that EPA narrow the scope of activities to specific case studies and site investigations and use a wide

variety of sources available to EPA in order to increase the success of the research program. The SAB provides a number of specific suggestions for focusing EPA's fundamental and secondary research questions associated with this topic area. The SAB recommends that EPA should research well drilling and cementing practices separately from the hydraulic fracturing process. With the cooperation of service companies, full access to data, and careful selection of case studies, the SAB believes that the proposed research can adequately address most of the fundamental questions associated with possible impacts of the injection and fracturing processes on drinking water resources.

Charge Question 4(d): Proposed Research Activities - Flowback and Produced Water

The SAB believes that the handling of the flowback and produced water represents the most likely important route of exposure and potential for adverse impacts on drinking water resources from the development of unconventional gas resources on a national level. The SAB recommends that EPA more clearly, in the main body of the plan, define and differentiate flowback and produced water, and clearly distinguish such waters from other water used during the hydraulic fracturing process.

The SAB supports EPA's plan to gather information on the composition of flowback and produced water from the hydraulic fracturing process as much as possible from currently available data. The SAB recommends the collection of water quality data from specific points in time and from carefully selected locations, including the ongoing studies on the quality of surface waters in the regions with significant hydraulic fracturing activity. EPA should evaluate quality assurance/quality control (QA/QC) aspects of the studies that would be assessed or conducted by EPA.

The SAB recommends that EPA consider the use of a risk assessment framework analysis (i.e., hazard identification, exposure, toxicity, and risk characterization) to assess and prioritize research activities for the lifecycle stages of flowback and produced water. At this time, EPA should focus on potential human exposure followed by hazard identification if sufficient time and resources are available for each lifecycle stage and use the paradigm to assist in problem formulation. The SAB anticipates that the primary opportunity for human health exposure is likely to be through surface waters, and recommends that EPA's first order human health exposure assessment focus on surface water management of flowback and produced waters. The SAB recommends that EPA not conduct toxicity testing at this time.

Charge Question 4(e): Proposed Research Activities - Wastewater Treatment and Waste Disposal

Hydraulic fracturing return flows contain many constituents that are similar to those for which treatment technologies exist within the state of practice of industrial wastewater treatment. For those constituents, SAB believes that EPA should conduct a thorough literature review to identify existing treatment technologies that are currently being used to treat HF wastewater, identify knowledge relevant to hydraulic fracturing return flows, and identify constituents of HF return waters that might merit additional attention. SAB recommends that EPA review the

documented data in the retrospective case studies to assess the efficacy and success of industrial wastewater treatment operations and pre-treatment operations for hydraulic fracturing return flows. Only a limited number of Publicly Owned Treatment Plants (POTWs) have the ancillary treatment technologies needed to remove the constituents in hydraulic fracturing return waters. SAB recommends that EPA focus its efforts towards literature searches on POTW and industry management practices that can minimize the adverse effects associated with certain constituents such as total dissolved solids (TDS), natural organic matter (NOM), bromide, and radioactive species, rather than on characterizing those effects. In addition, EPA should assess the need for any special storage, handling, management, or disposal controls for solid residuals after treatment. EPA should also consider industrial practices in which the hydraulic fracturing return flows have been used for irrigation.

Charge Question 5: Research Outcomes

The SAB focused on the potential research outcomes that EPA identified for each step in the HF water lifecycle. These potential research outcomes are identified in Chapter 6 of the draft Study Plan, at the end of the discussion of each stage of the water lifecycle. For each potential research outcome listed in the draft report, the SAB determined whether the outcome is likely to be achieved in whole, in part, or not at all, by the proposed research.

The SAB believes that all of the potential water acquisition research outcomes identified by EPA can be achieved. EPA can identify possible impacts on water availability and quality associated with large-volume water withdrawals for hydraulic fracturing. Also, EPA could determine the cumulative effects of large volume water withdrawals within a watershed and aquifer, and develop metrics that can be used to evaluate the vulnerability of water resources. While the SAB believes that these research outcomes can be accomplished at HF sites that are carefully characterized in the case studies, the potential for extrapolation of these findings to other sites will be limited. The SAB is thus unclear as to the extent to which the achievement of the water acquisition research outcomes will provide value to the project. Regarding the assessment of current water resource management practices related to hydraulic fracturing, the SAB believes that EPA can accomplish this task through collection of data on water management practices from a representative cross-section of the industry. However, it is unclear whether the "assessment" referred to in this outcome would comprise only data-gathering about existing `management practices or a more in-depth analysis of the effectiveness of the practices.

The SAB believes that most but not all of the potential chemical mixing research outcomes identified by EPA can be achieved. EPA can summarize available data on the identity and frequency of use of many (but not all) hydraulic fracturing chemicals, the concentrations at which the chemicals are typically injected, and the total amounts used, assuming cooperation from the HF service companies is forthcoming. The SAB believes it will be difficult for EPA to identify comprehensively the toxicity of chemical additives, apply tools to prioritize data gaps, and identify chemicals for further assessment. The SAB does not believe that it will be possible for EPA to collect and evaluate new data on human toxicity of HF chemical additives given the cost and time constraints of the current project. EPA should collect and review pre-existing data on toxicity of HF additives, and conduct a limited effort to estimate toxicity, based on

quantitative structure-activity relationships (QSARs), for HF additives for which no pre-existing toxicity data exist and a high potential for exposure exposure is likely. The SAB believes that EPA may not be able to identify a set of contamination indicators associated with hydraulic fracturing, for various reasons. However, the SAB believes that EPA's consideration of inorganic salts and organic HF additives (for which analytical methods already exist) as contamination indicators might can support e the research outcome related to toxicity assessment. The SAB believes that EPA can determine the likelihood that surface spills will result in the contamination of drinking water resources, to the extent that specific chemicals are identified, and their transport and transformation characterized, as part of the current project. Lastly, assuming that HF service companies are forthcoming with information about their chemical storage and mixing management practices, and that a broad data-gathering effort is undertaken, EPA's assessment of management practices related to on-site chemical storage and mixing is achievable as part of the proposed research.

The SAB believes that some but not all of the potential well injection research outcomes identified by EPA can be achieved. EPA should be able to determine the frequency and severity of well failures, as well as the factors that contribute to them, if thorough historical data on well failures are provided by the HF service companies and if EPA determines the number of hydraulic fracturing wells. The SAB believes that while EPA could identify the key conditions that increase or decrease the likelihood of the interaction of existing pathways with hydraulic fractures through modeling, such an outcome will have limited value because the simulated outcomes will be strongly dependent on assumptions and choices made about how to represent the physical system. These assumptions and choices may not be well constrained by reliable data. While the SAB believes that EPA can evaluate water quality before, during, and after injection, the evaluation might have to be continued substantially beyond the end of the initial research before the outcome can be established with reasonable confidence. The SAB does not believe that EPA can determine in the current study the identity, mobility, and fate of all potential contaminants, including fracturing fluid additives and/or naturally occurring substances (e.g., formation fluid, gases, trace elements, radionuclides, organic material) and their toxic effects. The SAB anticipates that the determination of toxic effects will be limited to those contaminants for which the toxicity has already been assessed. However, the SAB believes that the goal of quantifying the mobility and fate of the contaminants that are deemed to be of highest priority is achievable. Lastly, the SAB does not believe that establishing certified analytical methods for detecting and quantifying HF additives is an achievable goal for the current study, given the constraints of time and funding.

The SAB believes that some but not all of the potential flowback and produced water research outcomes identified by EPA can be achieved. EPA should be able to compile existing data relating to the identity, quantity, and toxicity of flowback and produced water components. The SAB recommends against EPA investing resources to develop analytical methods to identify and quantify flowback and produced water components given the constraints on time and funding, and does not think this is achievable. EPA can develop a prioritized list of components requiring future studies relating to toxicity and human health effects. The SAB believes that while EPA could determine the likelihood that surface spills will result in the contamination of drinking water resources, this likelihood will be highly site specific and will not be quantifiable with a

simple, general model, and thus the SAB does not believe that the outcome can be achieved. The SAB also does not believe that EPA can achieve its outcome to evaluate risks posed to drinking water resources by current methods for on-site management of wastes produced by hydraulic fracturing. The data that EPA anticipates collecting with regard to on-site management of HF wastes are not well defined, and it is unclear how the data obtained will be translated into a useful, generalized evaluation of the risks associated with on-site management of HF wastes.

The SAB believes that some but not all of the potential wastewater treatment and waste disposal research outcomes identified by EPA can be achieved. EPA can evaluate current treatment and disposal methods of flowback and produced water resulting from hydraulic fracturing activities with respect to the inorganic constituents of HF wastes, with minimal or no new laboratory research. However, the SAB does not believe such an evaluation can be achieved for the organic constituents in situations where the HF wastes are a small portion of the total waste stream entering the treatment plant. The SAB believes that EPA may be able to achieve an outcome that will assess the short- and long-term effects resulting from inadequate treatment of hydraulic fracturing wastewaters. However, this potential outcome can be achieved only for a very limited range of effects.

2. INTRODUCTION

2.1. **Background**

In January 2010, EPA's Office of Research and Development (ORD) initiated planning for a study to assess the potential impacts of hydraulic fracturing on drinking water resources. EPA proposed a study scope in March 2010 that was reviewed by the Science Advisory Board (SAB) in an open meeting on April 7-8, 2010; SAB's Report on its review of the study scope was provided to the Administrator in June 2010. In its response to EPA[1] in June 2010, the SAB endorsed a lifecycle approach for the study plan, and recommended that: (1) initial research be focused on potential impacts to drinking water resources, with later research investigating more general impacts on water resources; (2) five to ten in-depth case studies be conducted at "locations selected to represent the full range of regional variability of hydraulic fracturing across the nation"; and (3) engagement with stakeholders occur throughout the research process.

Subsequently, EPA developed a draft *Hydraulic Fracturing Study Plan* and requested SAB review of the draft Plan. The draft *Study Plan* assesses the potential impacts of hydraulic fracturing on drinking water resources, and identifies the driving factors that affect the severity and frequency of any potential impacts. The draft *Study Plan* proposes to assess potential impacts from five aspects of the water lifecycle associated with hydraulic fracturing: Water Acquisition, Chemical Mixing, Well Injection, Flowback and Produced Water, and Water Treatment and Waste Disposal. As noted in the draft Study Plan, EPA plans to conduct this lifecycle analysis through literature reviews, data gathering and analysis, modeling, laboratory investigations, and field investigations and case studies.

The SAB was asked to comment on various aspects of EPA's approach for the Study Plan, including EPA's proposed water lifecycle framework for the study plan, EPA's proposed research questions that would address whether or not hydraulic fracturing impacts drinking water resources, and EPA's proposed research approach, activities, and outcomes. EPA identified the proposed research questions from stakeholder meetings and a review of the existing literature on hydraulic fracturing. Stakeholders also helped EPA to identify the potential case study sites discussed in the draft study plan. The enclosed report provides the advice and recommendations of the SAB through the efforts of the SAB Hydraulic Fracturing Study Plan Review Panel. EPA will consider the comments from the SAB during the development of its final plan to study the potential impacts of hydraulic fracturing on drinking water resources.

The Panel met on March 7-8, 2011, to review and provide advice to EPA on the scientific adequacy, suitability and appropriateness of EPA's draft Study Plan. The Panel reviewed the draft EPA study plan, and considered public comments and oral statements that were received.

[1] http://yosemite.epa.gov/sab/sabproduct.nsf/0/CC09DE2B8B4755718525774D0044F929/$File/EPA-SAB-10-009-unsigned.pdf

The SAB's advice is provided in the attached SAB Report. The Panel held follow-up public teleconference calls on May 19 and May 25, 2011, to discuss the external draft SAB Report dated XXXX, 2011. The updated external draft SAB Report dated XXXX, 2011, was submitted to the chartered SAB for discussion at the XXXX, 2011, public teleconference. The external draft SAB Report was revised based on comments received from the Board. Comments from the SAB will be considered during the development of the final plan to study the potential impacts of hydraulic fracturing on drinking water resources.

2.2. **Charge to the Panel**

The Agency's Charge to the Panel (Appendix A) included a total of five questions, which were broken into nine total charge questions that were reviewed by the Panel:

Charge Question 1: Water Use in Hydraulic Fracturing

EPA has used the water lifecycle shown in Figure 7 to characterize hydraulic fracturing and to identify the potential drinking water issues. Please comment on the appropriateness of this framework for the study plan. Within the context of the water lifecycle, does the study plan adequately identify and address the areas of concern?

Charge Question 2: Research Questions

EPA has identified both fundamental and secondary research questions in Table 2. Has EPA identified the correct research questions to address whether or not hydraulic fracturing impacts drinking water resources, and if so, what those potential impacts may be?

Charge Question 3: Research Approach

The approach for the proposed research is briefly described in Chapter 5. Please provide any recommendations for conducting the research outlined in this study plan, particularly with respect to the case studies. Have the necessary tools (i.e., existing data analysis, field monitoring, laboratory experiments, and modeling) been identified? Please comment on any additional key literature that should be included to ensure a comprehensive understanding of the trends in the hydraulic fracturing process.

Charge Question 4(a): Proposed Research Activities - Water Acquisition

Proposed research activities are provided for each stage of the water lifecycle and summarized in Figure 9. Will the proposed research activities adequately answer the secondary questions listed in Table 2 for the Water Acquisition stage of the water lifecycle? Please provide any suggestions for additional research activities.

Charge Question 4(b): Proposed Research Activities - Chemical Mixing

Proposed research activities are provided for each stage of the water lifecycle and summarized in Figure 9. Will the proposed research activities adequately answer the secondary questions listed in Table 2 for the Chemical Mixing stage of the water lifecycle? Please provide any suggestions for additional research activities.

Charge Question 4(c): Proposed Research Activities - Well Injection

Proposed research activities are provided for each stage of the water lifecycle and summarized in Figure 9. Will the proposed research activities adequately answer the secondary questions listed in Table 2 for the Well Injection stage of the water lifecycle? Please provide any suggestions for additional research activities.

Charge Question 4(d): Proposed Research Activities - Flowback and Produced Water

Proposed research activities are provided for each stage of the water lifecycle and summarized in Figure 9. Will the proposed research activities adequately answer the secondary questions listed in Table 2 for the Flowback and Produced Water stage of the water lifecycle? Please provide any suggestions for additional research activities.

Charge Question 4(e): Proposed Research Activities - Wastewater Treatment and Waste Disposal

Proposed research activities are provided for each stage of the water lifecycle and summarized in Figure 9. Will the proposed research activities adequately answer the secondary questions listed in Table 2 for the Wastewater Treatment and Waste Disposal stage of the water lifecycle? Please provide any suggestions for additional research activities.

Charge Question 5: Research Outcomes

If EPA conducts the proposed research, will we be able to:

a. Identify the key impacts, if any, of hydraulic fracturing on drinking water resources; and
b. Provide relevant information on the toxicity and possible exposure pathways of chemicals associated with hydraulic fracturing?

3. RESPONSE TO THE CHARGE QUESTIONS

3.1. **Water Use in Hydraulic Fracturing**

Charge Question 1: EPA has used the water lifecycle shown in Figure 7 to characterize hydraulic fracturing and to identify the potential drinking water issues. Please comment on the appropriateness of this framework for the study plan. Within the context of the water lifecycle, does the study plan adequately identify and address the areas of concern?

General Comments

In general, the SAB believes that EPA's use of the water lifecycle depicted in Figure 7 of the draft study plan is an appropriate framework to characterize hydraulic fracturing and to identify the potential drinking water issues. However, the SAB has several recommendations to strengthen the framework and provide an improved assessment of potential drinking water issues. EPA's framework should take a broader view with regard to water quantity than depicted in Figure 7, and link water fluxes associated with hydraulic fracturing to water flows in the surrounding natural hydrological cycle. The water mass balance assessment is a critical effort, and EPA should initially focus the water mass balance assessment towards the case study efforts. EPA should also assess interbasin transfers of flowback and produced water in order to identify possible water quality and quantity issues associated with such transfers. In addition, EPA should assess additional sources of water quality impacts beyond those indicated in Figure 9a.

Specific Comments

First, EPA's framework should take a broader view with regard to water quantity than depicted in the Figure. That broader view should involve imbedding water fluxes associated with hydraulic fracturing to water flows in the surrounding natural hydrological cycle. To take this broader view, EPA should consider reformatting Figure 7 to put a box around the block diagram that links to the hydrological cycle. Also, within the first block of the framework (i.e., the water acquisition block), EPA should change the wording from 'Water availability' to 'Water availability and environmental flows', and also change the wording from 'Impact of water withdrawal on water quality' to 'Impact on environmental fluxes and water quality'.

The SAB agrees that assessing the water mass balance for any particular site or collection of sites is an important undertaking and supports EPA's efforts to conduct this analysis. The SAB believes that EPA should initially focus this water mass balance assessment towards the case study efforts. A critical issue associated with water mass balance is assessing and accounting for the change in hydrologic/environmental flows. When assessing the water balance interconnection between natural flow and flow associated with hydraulic fracturing activities, a

large water volume is removed and stored for hydraulic fracturing activities, and EPA should tie that water into the broad hydrological cycle on a regional scale.

In addition, SAB recommends that EPA include feedback loops that assess interbasin transfers of flowback and produced water, in order to identify possible water quality and quantity issues associated with such transfers.

Regarding water quality impacts, SAB believes that other sources of impacts beyond those indicated in the Figure 9a should be assessed. For example, when assessing the fate and mass balance of potential contaminants associated with hydraulic fracturing operations, EPA should consider the potential release of volatile organic contaminants and other contaminants to the air. Such releases could potentially result in contamination of water supply sources, and it is important to note that unhealthy exposures can result from breathing air as well as through drinking water. It is also important to recognize that substantial credibility in the results for individual chemicals will result when complete mass balances (i.e., summations of transfers to air, water, soil, and other media) are assessed. In addition, spatial and temporal issues are relevant to assessing water quality impacts. The SAB recognizes that there are difficulties in incorporating spatial and temporal issues into the water quality impact assessment, but EPA should attempt to provide some boundaries for these issues to assist in determining what future work may be useful. The SAB also recognizes that expanding the study to include air is not within the scope of the document, but EPA should take the opportunity in this study to note when and where air impacts may occur and the likely importance of those impacts to assist in determining what future work may be necessary to evaluate air impacts.

3.2. **Research Questions**

Charge Question 2: EPA has identified both fundamental and secondary research questions in Table 2. Has EPA identified the correct research questions to address whether or not hydraulic fracturing impacts drinking water resources, and if so, what those potential impacts may be?

3.2.1. General Comments

EPA has identified a comprehensive set of research questions to address the primary mechanisms and pathways that can allow hydraulic fracturing to impact drinking water resources. The questions cover each step of the life cycle of a hydraulic fracturing process that can impact drinking water and are appropriately focused on the unique aspects of hydraulic fracturing that can lead to such impacts. The SAB provides suggestions for supplementing and revising the existing questions. These suggestions are designed to recognize explicitly key issues that may not be adequately addressed in the current questions or to frame more appropriate questions given the limited available time and funding to the effort. The SAB is concerned that many of the questions may not be answerable given the limited available time and funding.

The SAB has overarching comments that may affect the primary and secondary research questions and how they are answered at each life cycle stage. An important challenge facing the study is the diverse nature of hydraulic fracturing operations around the country. The geological setting, the hydrological setting, the community setting and the requirements and standard operating procedures at each stage of the hydraulic fracturing life cycle vary across the country. These differences can give rise to fundamental differences in the nature of the impacts to drinking water resources. For example, the limited availability of reinjection wells in the Marcellus Shale region gives rise to a completely different set of potential impacts to drinking water than in areas where reinjection of produced waters is routine.

Potential impacts to drinking water may be the result of hydraulic fracturing or the result of the manner in which it is implemented. Identifying potential impacts to drinking water resources that are associated with failure to employ best management practices may not be useful unless the linkage to those management practices is identified. This is of particular concern in retrospective case studies in that it may not be possible to separate risks associated with management practices from risks of hydraulic fracturing.

Another overarching issue is the importance of assessing uncertainty at each step in the research study. Given time and resource constraints, the studies will not be able to answer all questions with a high degree of certainty. The SAB recommends that EPA explicitly identify or estimate the uncertainty or confidence in all research conclusions. The quality of the information on which the research was based as well as any uncertainties arising in the conduct of the research should be evaluated, at least in a preliminary manner. This is particularly true for case studies

and evaluations of current practices in that it is expected that these portions of the research will be based upon grey literature sources that have not been peer reviewed or subject to the same quality constraints that will govern the proposed studies. The need to collect proprietary information may also limit the quality of the research product.

An additional overarching issue is that EPA needs to view the environmental concerns and issues in the context of the local community, and that at a potential outcome should be identified by EPA for environmental justice issues. Concerns such as environmental justice and the effects of hydraulic fracturing on disproportionately impacted communities should be an explicit research question. The SAB recommends that potential environmental justice concerns associated with hydraulic fracturing should be identified and characterized as part of the current study and that this should be explicitly recognized in the research questions. The SAB recommends that a separate section of the research plan be devoted explicitly to environmental justice issues.

Another key component is the need to assess the impact of hydraulic fracturing in context with other environmental challenges that might be faced by the community to develop a sense of the cumulative impact.

The Study Plan should address the cumulative consequences of carrying out multiple HF operations in a single watershed or region. While detailed research on cumulative impacts may be beyond the scope of the current study, the incremental impacts of hydraulic fracturing operations should be well characterized in the current study and a framework for assessment of cumulative impacts should be established. This will provide the foundation for subsequent assessment of total environmental exposures and risks, and cumulative impacts.

In addition, the SAB recommends that EPA clarify whether the research focus is on hydraulic fracturing in shale gas production, conventional natural gas production, coal bed methane production, or other types of hydraulic fracturing activity.
In addition to these general concerns, the SAB has a number of specific concerns noted below associated with the research questions at individual lifecycle stages. Additional specific comments on each of the lifecycle stages are included within this Report's responses to Charge Questions 4(a) through 4(e).

3.2.2. Specific Comments

Water Acquisition

The impacts associated with water acquisition are clearly related to the volume of water required and the availability and quality of such water to the community impacted. EPA should assess the volume of water in context with the needs and availability of water to the surrounding community, and a series of secondary questions should be added to reflect this. For example: What are the depths of functional groundwater wells in the area of hydraulic fracturing and what is the potential relationship between these wells and hydraulic fracturing activities both on the surface and below ground?

The Study Plan proposes a sustainability analysis that will reflect minimum river flow requirements and aquifer drawdown for drought, average, and wet precipitation years. Minimum river flow requirements need to be determined as suggested, but also, more importantly, "what are the environmental flow requirements." Minimum flows and environmental flows are quite different concepts. Also, these flow requirements should be determined based on hydrological processes in the region where hydraulic fracturing is being practiced.

The Study Plan also emphasizes the relationship between water acquisition (related to availability) and water quality. Additional questions should relate this relationship to different sources of water. For example: How different will impacts of water withdrawal be on different water sources, e.g., different stream types (perennial and intermittent) and lakes, and their water quality based on their different base geology?

The draft Study Plan should recognize the differences between acquiring low quality water that is not considered a valuable resource to the community as opposed to displacing agricultural or drinking water that could be used by the community. This is an area where the cumulative impacts of well field development as opposed to single well impacts will be important. For example, a secondary question addressing this might be: What are the cumulative effects of water acquisition for multiple well sites relative to the effects of one or limited well sites?

<u>Chemical mixing</u>

The fundamental question in this area is focused on accidental releases during the mixing process. The secondary questions appropriately emphasize the importance of the composition and potential toxicity of the fracturing fluids. Similarly, the total volumes and the physical and chemical properties of the constituents must be identified to address potential impacts at subsequent life cycle stages. The total quantities and physical and chemical properties can also be useful in subsequent evaluations of other issues not within the scope of the present study, for example, air emissions from the chemical mixing operations. The SAB recommends that the secondary question be expanded to explicitly recognize the need for information regarding volumes and physical and chemical properties of the mixing components.

The potential toxicity of the fracturing fluids will likely be addressed primarily through literature sources. The SAB strongly discourages using any of EPA's limited resources for toxicity studies of chemical constituents. SAB recommends that EPA explicitly recognize this problem in the framing of the secondary questions.

EPA should assess the likelihood of releases during chemical mixing and the relationship of the frequency and volume of releases to best management practices to the extent possible. SAB recommends that EPA add an explicit secondary question to address this need. For example: Have different practices for chemical mixing resulted in different frequencies of spills and different volumes of spills when they occur?

<u>Well injection</u>

This stage of the life cycle of hydraulic fracturing should be explicitly separated into well construction and well completion. Drilling and cementing are construction activities whereas fracturing is considered a completion activity. Well construction may lead to impacts on drinking water resources and any weaknesses or failures in construction will lead to subsequent problems during operations. Well construction (and subsequent post-use closure) could be considered another life-cycle stage for hydraulic fracturing so that the potential impacts to drinking water resources could be addressed by specific research questions. Since subsequent well-bore failure is likely associated with problems during construction, a secondary question focused on the ability to detect and correct well-bore construction problems prior to or during injection may be appropriate. A secondary question on the influence of management practices, such as cementing casings all the way to the surface, should also be included. For example: What have been the management practices relative to cementing casings and what has been the history of failure of different practices? Refracturing a formation may put additional stresses on a well, particularly if refracturing is conducted years after initial construction. It may not be possible to address this in the proposed study, but any existing evidence of this problem as a possible mechanism for drinking water impacts should be reviewed.

The remaining secondary questions are appropriate for the well injection and operation portion of the life cycle. The secondary questions should explicitly recognize, however, that the fate and transport of substances of concern includes not only substances introduced by the fracturing fluids but other substances that might be mobilized or rendered more toxic by the introduction of the fracturing fluid. For example, will changes in redox conditions in the subsurface due to fracturing fluid injection lead to redox changes and mobilization of metals such as arsenic, selenium and chromium or encourage/discourage specific metabolic processes?

The volume and depth of injection relative to subsurface drinking water resources is an important factor in the potential impact of the injection of fracturing fluids. As indicated previously, placing these quantities in context (cumulative impacts of adjacent wells, differences in geology and water availability, quality and location) is difficult given time and resource constraints, but the study should attempt to do so to the extent possible. A specific factor in some areas that may influence injection behavior is the presence of unplugged historical wells. A secondary question is recommended that explicitly recognizes the need to place results in the context of the local geology and history. For example: What is the relationship between well injection depths and impacts of injection fluids and local geology and historic use of the geology and hydrology as evidenced by unplugged wells?

Since hydraulic fracturing occurs in the deep subsurface environment where it is difficult to assess effects on ground water resources, the operation and injection life cycle of a hydraulic fracturing well has significant uncertainties. This lifecycle analysis is a critical component of the proposed study.

<u>Flowback and produced water</u>

The SAB believes that the draft Study Plan's secondary questions in this lifecycle stage correctly emphasize the importance of the composition of the flowback and produced water and its

variability. How the composition of the flowback and produced water may vary as a function of management practices and local geology is important but difficult to assess given time and resource constraints. EPA should address this question to the extent possible, including an assessment of the uncertainty in the conclusions. A secondary question explicitly identifying this as an area of concern may be appropriate. For example: What factors such as management and local geology can be identified as primary drivers of composition of flowback and produced water, and what is the uncertainty of this determination?

The SAB believes that given the constraints of time and funding, EPA should attempt to identify the fate of fracturing fluid components that are deemed to be of highest priority that are introduced with the injection. A specific secondary question that asks "what fraction of the injected components are returned to the surface and what is the likely fate of any components not returned to the surface" may be appropriate.

As with chemical mixing, EPA should identify the cause and likelihood of spills or releases of flowback or produced water, as well as management practices that reduce their likelihood or mitigate their impact. It may be appropriate for EPA to expand the existing secondary questions to explicitly identify the need for identifying the likelihood of spills or releases and the effectiveness of mitigation practices.

Wastewater treatment and disposal

The form and potential impacts of wastewater treatment and disposal vary significantly with local conditions and practices. The lack of available reinjection wells in the Marcellus Shale area creates substantially greater concern for wastewater treatment practices in this area. EPA should explicitly identify these variations across the country and include a secondary question that recognizes the need to assess these variations. For example: How does the potential for reinjection vary across the country and across geological formations where hydraulic fracturing is practiced?

Specific issues associated with wastewater treatment are not currently identified in the secondary questions. Inorganic species such as salinity and bromide, and radioactive produced water (e.g., from Marcellus shale), for which conventional wastewater treatment is largely ineffective, are of major concern. The presence of these constituents has also led to concerns about potential ecological effects and effects on drinking water treatment downstream the(e.g., formation of brominated disinfection by-products). The SAB recommends that EPA add a secondary question focusing on these contaminants of concern. For example: What is the potential for inorganic species such as salinity and bromide, as well as radioactivity from produced water, for which conventional wastewater treatment is largely ineffective, to enter drinking water resources downstream from water and wastewater treatment facilities?

Comment [c1]: Because of the recent presentation of research by Dr. Stanley States and research from Carnegie Mellon University, PADEP has 'requested' that none of the municipal or industrial waste treatment plants in PA accept Marcellus Shale wastewater after May 19, 2011. This is a major accomplishment for the PA drinking water utilities. The data clearly show that bromide in the source water significantly increases the concentration of THMs in drinking water as well as the proportion of the more toxic brominated species. The research also indicates that conventional drinking water treatment processes are ineffective in removing bromide from the source water. Furthermore, their extensive, ongoing survey of the Allegheny River and its tributaries indicates that the principal contributor of bromide to the river is industrial wastewater plants which treat Marcellus Shale flowback water. Municipal POTWs that treat this wastewater don't appear to contribute bromide to the rivers, presumably because they chlorinate the treated effluent prior to discharge. In effect, they are forming the THMs at the wastewater plants and the THMs volatize from the river. To date, no other potential sources of bromide appear to be significant. This includes steel plants that may be using brominated compounds to control biological growth in cooling towers or coal fired power plant that may be using brominated compounds to treat cooling towers or to control mercury emissions in air.

3.3. **Research Approach**

Charge Question 3: The approach for the proposed research is briefly described in Chapter 5. Please provide any recommendations for conducting the research outlined in this study plan, particularly with respect to the case studies. Have the necessary tools (i.e., existing data analysis, field monitoring, laboratory experiments, and modeling) been identified? Please comment on any additional key literature that should be included to ensure a comprehensive understanding of the trends in the hydraulic fracturing process.

3.3.1. General Comments

The SAB believes that EPA is taking on an enormous challenge with limited budget and within a limited time frame. EPA should conduct a well-focused study so that critical research questions are identified, approaches are designed that will enable answering those questions, and analysis is included to validate the conclusions that are reached. At the same time, EPA's framework should take a broader view with regard to water quantity than depicted in Figure 7, and link water fluxes associated with hydraulic fracturing to water flows in the surrounding natural hydrological cycle.

The SAB believes that the Study Plan provides inadequate detail on how to address the overall research questions presented in Table 2 and discussed within the draft Study Plan, and that EPA should present more specific research questions that could be answered within the budget and time constraints of the project (see 3.2 above). To the extent that the Study Plan is being designed to inform decision-making related to an EPA regulatory framework, the framework should include specific research questions aimed at this objective.

The SAB finds that the scenario evaluation does not, but should, cross all research questions. The SAB notes that scenario evaluations beyond the case studies for water acquisition and flowback water, and their modeling, would particularly assist EPA's research effort.

A suggested area for additional specific research is on the capacity of microseismic data to provide detailed information about the extent of fracturing and to assist in the hydraulic fracturing modeling (see discussion under Charge Question 4).

The SAB also believes that the Study Plan provided limited detail on anticipated data analysis, management, and storage (including model simulation results), and recommends that EPA revise the draft Study Plan to include such details. The SAB recommends that EPA consider using existing data analysis methods rather than developing new methods due to time and budget constraints. EPA should also carefully consider the quality of various types of data that would be used within the analysis (industry data, local and non-industry data). It is imperative for EPA to set a standard for use of data and prior research information (including citations) that would support the present research effort. The SAB notes that while anecdotal information may

provide useful data, EPA should classify the data as such. The SAB also suggests that EPA consider archiving samples for later use.

The SAB finds that the Study Plan generally overemphasizes case studies in the study approach, and underemphasizes the review and analysis of existing data and the use of scenario analysis. However, the SAB recognizes that case studies will likely provide accurate information on hydraulic fracturing fluids and well operations, and difficulties associated with collecting proprietary information may also limit the quality of the research product. The SAB believes there is significant value to the synthesis of existing data, and that EPA should review all available data sources to learn from what is already known about the relationship of hydraulic fracturing and drinking water resources. The SAB also provides citations for additional literature that EPA should consider to ensure a comprehensive understanding of the trends in the hydraulic fracturing process and the potential impacts of hydraulic fracturing on drinking water resources.

3.3.2. Specific Comments

In addition to the general comments provided above, the SAB specifically considered issues of research approach including: partnering, the value of the case studies, the role of scenario evaluation, the analysis of existing data, and the methods described for the research. The SAB's recommendations for each of these topics are provided below.

Partnering

Table A2 lists a significant EPA role in the research and some collaborators within the federal agencies (U.S. Department of Energy National Energy Technology Laboratory, NETL, and U.S. Geological Survey, USGS). Table F1 includes extensive collaborators for the case study work. However, it is not clear what collaborators might be involved in the analysis of existing data, the extent of the existing data, the laboratory studies or the scenario development and analysis. While EPA has extensive expertise and the timeline is short on this study, the SAB recommends EPA consider expanding the research team to include researchers with experience in this area of investigation (especially those with experience in well construction and fracturing operations).

Case Studies

The SAB generally agrees that the case study approach would be a useful endeavor, since case studies could potentially provide high quality data from specific hydraulic fracturing sites related to the core research questions to be answered. However, the draft Study Plan did not provide adequate justification for the purpose of the case studies, link the expected results to the specific research questions, or explain how models will be integrated among the different research components. Thus, there was insufficient information to evaluate the likelihood of success from this research approach. The SAB recommends that Table 1 be revised to include an additional column indicating how case studies link to research questions.

The SAB believes it is uncertain whether useful case study results could be achieved within the budget and schedule limitations. It is not clear that EPA will be able to find or conduct sufficient case studies to provide answers to the current broadly defined research questions. Further, there is concern that the number of case studies planned might be insufficient to span the range of geological and hydrological regimes where drilling is active or anticipated. There is concern that the case studies will ultimately be too limited in scope for results to be applied generally. Thus, the Panel discussed the total number of case studies needed to yield useful data for the research project, and whether a statistically acceptable number of case studies could be undertaken to meet the research objectives, as well as consider issues of environmental justice. The SAB did not reach consensus on this point because the purpose of the case studies was not clear. The SAB recommends EPA prepare a scoping document that provides clear budgetary framework for the planned case studies.

The retrospective case studies described include 3-5 sites where possible drinking water contamination was observed related to hydraulic fracturing. All the sites described are in small geographic areas and represent potential groundwater contamination. No case study deals with the potential effects of large scale, basin-wide disposal practices on drinking water resources. The SAB recommends that EPA conduct at least one case study with this larger watershed-scale focus. The SAB specifically suggests that EPA consider conducting a case study in the Ohio River Basin of Southwestern Pennsylvania, since this is a location where such watershed-scale drinking water impacts are suspected.

The prospective case studies appear to be at small geographic scale and, similar to the retrospective case studies and, do not incorporate a watershed level approach. The SAB expresses concern that the prospective case studies did not have clearly defined boundaries. For example, it was unclear if waste disposal would be incorporated in the case studies. The SAB recommends a full life cycle approach, as EPA has proposed for this project, be applied to the prospective case studies, where life cycle includes the acquisition of water through to disposal of wastewater across multiple potential options. The case study plan describes monitoring, but insufficient detail was provided to assess the suitability of the target chemicals. The SAB recommends that the case study monitoring plan target specific measurements and not be developed as a general plan.

The SAB discussed the relative merit of prospective versus retrospective case studies, especially given the budget constraints. After extensive discussion of the importance of the different components of each type of case study, the Panel concluded that there was value in each. While the difficulties of completing both case study formats within the limited time and budget available was discussed, the SAB recommends EPA include both prospective and retrospective case studies as planned because the studies address different questions and perspectives. The SAB notes that retrospective studies conducted at sites with known environmental and health issues would provide information on sources, fate and transport of releases of hydraulic fracturing contaminants to the environment. The prospective studies will help identify limitations of existing studies and data, what data are needed for future studies, and situations where hydraulic fracturing would be less likely to present significant environmental or health problems. The prospective studies would also provide useful information on water mass

balance, well drilling operations, treatment system performance, health and safety issues of chemical mixing, and other issues. The SAB notes that while prospective studies may not provide useful information on long term hydraulic fracturing performance in deep formations, such studies may be helpful and representative for assessing impacts from hydraulic fracturing operations that occur at the surface because techniques for assessing surface environments are much better developed. The SAB recommends that EPA take a long view, and consider what kind of data will be desired in ten years in order to design the data collection protocols for the prospective studies. Further, the SAB notes that the selected case study locations must be chosen based on reasonable, mechanistically possible contamination scenarios, incorporating uncertainty.

Scenario Evaluation

The SAB notes that the scenario evaluation component of the research plan was not as clearly articulated as the case studies. For example, it is unclear how "typical management and engineering practices in representative geological settings" will be selected for scenario generation or how system vulnerability will be incorporated into models. The Panel discussed using scenario evaluations to examine "worst case scenarios" and establish boundaries for subsequent research tasks. For example, if the worst case scenario in a given situation would lead to nondetectable levels of contamination, then monitoring for contaminants in that setting would waste previous resources. If scenario modeling shows that ground water contamination would occur only after a long period of time, then that scenario would use additional scenario modeling rather than monitoring wells to assess potential groundwater contamination. If scenario modeling shows that the greatest potential for contamination occurs only during "start up" operations in a given area, that suggests a good location for a prospective study with the monitoring designed to coincide with the onset of HF operations.

The SAB notes that the scenario evaluation focus does not cross all research questions (according to the tables in the appendices of the EPA's draft Study Plan). For example, the potential effects of water acquisition on drinking water quality are not included in scenario evaluation. Since that potential effect is also not incorporated extensively in the case studies, the SAB is concerned that it might be neglected. Similarly, no scenario evaluation is proposed for research on flowback and produced water and its disposal. The SAB recommends that modeling to evaluate scenarios be used across all research questions identified. Further, the SAB notes the central role that modeling studies play in designing monitoring, laboratory work and even what is addressed in the case studies. Scenario evaluation can be a unifying driver for the study by integrating the different approaches to focus on a key set of answerable questions.

Analysis of Existing Data

Although the draft Study Plan describes analysis of existing data as a key starting point for the research plan, the details of this approach are unclear. Chapter 5 provides only brief details, while Figure 9a shows this as a significant part of the draft Study Plan. EPA's 2004 study clearly documented the lack of existing data and thus EPA should identify what new data is available and better articulate applicability of the new data to the research questions. The Panel discussed at length the limitations of the small data set that will be generated from the limited number of case studies that will be conducted in the available time and budget. These limitations suggest the analysis of all existing available data will be even more critical to answer the research questions identified. The SAB recommends EPA more carefully consider the nature and extent of existing data in this field, and provide details of the planned analysis of these data. For example, the SAB suggests looking at (1) data on existing source water conditions and the water quantity and quality needed for ecological ("environmental") flows, (2) data on existing well technologies, and (3) data on existing disposal technologies.

Field and Laboratory Methods

Overall the draft Study Plan inadequately described the field and laboratory methods that would be utilized and thus provided insufficient information to allow full evaluation by the SAB. Field monitoring was not well described, and the laboratory scale experimentation and analysis was only briefly described in the draft Study Plan. The modeling components did not explain the physical mechanism that could be encountered, such as density-dependent flows, thermally-induced flows, and surface water-groundwater interaction. In addition, the inclusion of a necessary probability framework was unclear. The modeling components did not explain the physical mechanism that could be encountered, such as density-dependent flows, thermally-induced flows, and surface water-groundwater interaction. In addition, the inclusion of a necessary probability framework was unclear. The use of isotopic analysis was mentioned for both gas and water analysis but the SAB believes that more detail is needed to assess this approach. It was unclear to the SAB if the tools that will be used provide sufficient data for a toxicological review or for an analysis of cumulative or synergistic effects for chemicals determined to have a high potential for exposure. Method development was mentioned a number of times, but the SAB concludes that there is insufficient time or resources to develop new methods during this study. The SAB recommends EPA employ known methods and use scenario modeling and mass balances to identify worst case outcomes. It would be helpful if EPA identified conservative or persistent indicator chemicals common to most or all fracturing fluids to narrow the analytical focus.

3.3.3. Additional Literature

Additional literature that EPA should consider to ensure a comprehensive understanding of the trends in the hydraulic fracturing process, and the potential impacts of hydraulic fracturing on drinking water resources, include the following:

Alberta Environment. Water management framework: Instream flow needs and water management system for the lower Athabasca River. 2008. *Alberta Environment and Fisheries and Oceans Canada*. July 31,2008. http://environment.alberta.ca/documents/Athabasca_RWMF_Technical.pdf.

American Petroleum Institute. Overview of Exploration and Production Waste Volumes and Waste Management Practices in the United States. 2000. American Petroleum Institute. http://www.api.org/aboutoilgas/sectors/explore/waste-management.cfm.

Chen, G., M.E. Chenevert, M.M. Sharma, and M. Yu. A study of wellbore stability in shales including poroelastic, chemical, and thermal effects. 2003. *Journal of Petroleum Science and Engineering* 38 (3-4): 167-176.

Chenevert, M.E., and M. Amanullah. Shale Preservation and Testing Techniques for Borehole-Stability Studies. 2001. *Journal of Society of Petroleum Engineers Drilling & Completion* 16(3): 146-149.

Cheung, K., Klassen, P., Mayer, B., Goodarzi, F., and Aravena, R. Major ion and isotope geochemistry of fluids and gases from coalbed methane and shallow groundwater wells in Alberta, Canada. 2010. *Applied Geochemistry* 25: 1307-1329.

Clark, C.E., and J.A. Veil. Produced Water Volumes and Management Practices in the United States. 2009. *U.S. Department of Energy*, Office of Fossil Energy, Argonne National Laboratory National Energy Technology Laboratory, Environmental Science Division. ANL/EVS/R-09/1. http://www.evs.anl.gov/pub/dsp_detail.cfm?PubID=2437.

Copeland, D., Fielder, R., Gadde, P., Griffin, L., Sharma, M.M., Sigal, R., Sullivan, R., and Weiers, L. Slick Water and Hybrid Fracturing Treatments: Some Lessons Learned. 2005. *Journal of Petroleum Technology* 57(3): 54-55.

Dayan, A., S.M. Stracener, and P.E. Clark. Proppant Transport in Slick-Water Fracturing of Shale-Gas Formations. 2009. *Society of Petroleum Engineers Annual Technical Conference and Exhibition* – October 4-7, 2009, New Orleans, LA.

Dewan, J.T., and Chenevert, M.E. A model for filtration of water-base mud during drilling: determination of mudcake parameters. 2001. *Petrophysics*, 42 (3): 237–250.

Fertl, W.H. Abnormal Formation Pressures. 1976. New York, Elsevier, 382p.

Fisher, K., and N. Warpinski. Hydraulic Fracture Height Growth – Real Data", SPE 145949. To be presented at the 2011 Society of Petroleum Engineers Annual Technical Conference and Exhibition (ATCE), October 30- November 2, 2011 in Denver, Colorado.

Fisher, K. Microseismic mapping confirms the integrity of aquifers in relation to created fractures. Halliburton, Inc., and Pinnacle, Inc. http://www.efdsystems.org/Portals/25/2010-11%20Microseismic%20Mapping_Kevin_Fisher.pdf.

Geertsma, J. 1989. Two-dimensional fracture propagation models. Recent Advances in Hydraulic Fracturing. *Society of Petroleum Engineers*, Monograph Series #12: 81-94. Richardson, Texas.

Geertsma, J., and F. de Klerk. A rapid method of predicting width and extent of hydraulically induced fracture. 1969. *Journal of Petroleum Technology* 21 (12): 1571-1581.

Ghalambor, A., A. Syed, and W.D. Norman, editors. The Frac Pack Handbook. 2009. *Society of Petroleum Engineers*.

Grunewald, B., D. Arthur, B. Langhus, T. Gillespie, B. Binder, D. Warner, J. Roberts, and D.O. Cox. Assistance to Oil and Gas State Agencies and Industry through Continuation of Environmental and Production Data Management and a Water Regulatory Initiative. 2002. U.S. Department of Energy Office of Fossil Energy. Report Number DOE/BC/15141-1. http://www.osti.gov/energycitations/purl.cover.jsp?purl=/794997-PNbtJn/.

Hubbert, M.K., and W.W. Rubey. Role of fluid pressure in mechanics of overthrust faulting, I. 1959. *Geological Society of America Bulletin* 70: 115-166.

King, G.E. Thirty Years of Gas Shale Fracturing: What Have We Learned. 2010. *Society of Petroleum Engineers Annual Technical Conference and Exhibition* – September 19-22, 2010, Florence, Italy.

Mitchell, R.R., C.L. Summer, D.D. Bush, S.A. Blonde, G.K. Hurlburt, E.M. Snyder, S.A. Snyder and J.P. Giesy. 2002. SCRAM: A Scoring and Ranking System for Persistent, Bioaccumulative, and Toxic Substances for the North American Great Lakes: Resulting Chemical Scores and Rankings. *Human and Ecological Risk Assessment* 8:537-557.

National Research Council. Management and Effects of Coal Bed Methane Produced Water in the Western United States. 2010. *National Academies Press* - National Academy of Sciences - Committee on Management and Effects of Coalbed Methane Development and Produced Water in the Western United States; Committee on Earth Resources; National Research Council, Washington, DC.

Powley, D. Pressures and hydrogeology in petroleum basins. 1990. *Earth-Science reviews* 29: 215-226.

Prudic, D.E. Evaluating cumulative effects of ground-water withdrawals on streamflow. 2007. *University of Nevada Reno*. 347 pages. http://gradworks.umi.com/32/58/3258837.html.

Rahm, D. Regulating hydraulic fracturing in shale gas plays: The case of Texas. 2011. *Energy Policy* 39: 2974–2981.

Rubey, M.W., and M.K. Hubbert. Role of fluid pressure in mechanics of overthrust faulting, II. 1959. *Geological Society of America Bulletin* 70: 166-205.

Kargbo, D.M., Wilhelm, R.G., and Campbell, D.J. Natural gas plays in the Marcellus Shale: Challenges and potential opportunities. 2010. *Environmental Science and Technology* 44:5679-5684.

Larsen, B., and Gudmundsson, A. Linking of fractures in layered rocks: Implications for permeability. 2010. *Tectonphysics* 492:108-120.

Sharma, M.M. Chapter 6: Formation Damage. 2007. *Petroleum Engineering Handbook, Volume 4 - Production Engineering*. Society of Petroleum Engineers. pp 1-33. ISBN: 978-1-55563-131-4

Sharma, M.M, and Zhai, Z. Modeling hydraulic fractures in unconsolidated sands. 2006. *Journal of Petroleum Technology* 58(3): 54-55.

Smith, M.B., and J.W. Shlyapobersky. Basics of hydraulic fracturing. In *Reservoir Stimulation, 3rd ed*. 2000. Ed. M.J. Economides and K.G. Nolte. New York: John Wiley.

Snyder, E.M, S.A. Snyder, J.P. Giesy, S.A. Blondi, G.K. Hurlburt, C.L. Summer, R.R. Mitchell and D.M. Bush. 1999. SCRAM: A Scoring and Ranking System for Persistent, Bioaccumulative, and Toxic Substances for the North American Great Lakes. Part I. Structure of the Scoring and Ranking System. *Environmental Science and Pollution Research* 7:51-61.

Snyder, E.M, S.A. Snyder, J.P. Giesy, S.A. Blondi, G.K. Hurlburt, C.L. Summer, R.R. Mitchell, and D.M. Bush. 1999. SCRAM: A Scoring and Ranking System for Persistent, Bioaccumulative, and Toxic Substances for the North American Great Lakes. Part II. Bioaccumulation Potential and Persistence. *Environmental Science and Pollution Research* 7:116-120.

Snyder, E.M, S.A. Snyder, J.P. Giesy, S.A. Blondi, G.K. Hurlburt, C.L. Summer, R.R. Mitchell and D.M. Bush. 1999. SCRAM: A Scoring and Ranking System for Persistent, Bioaccumulative, and Toxic Substances for the North American Great Lakes. Part III. Acute and Subacute or Chronic Toxicity. *Environmental Science and Pollution Research* 7:176-184.

Snyder, E.M., S.A. Snyder, J.P. Giesy, S.A. Blondi, G.K. Hurlburt, C.L. Summer, R.R. Mitchell and D.M. Bush. 1999. SCRAM: A Scoring and Ranking System for Persistent, Bioaccumulative, and Toxic Substances for the North American Great Lakes. Part IV. Results from Model Chemicals, Sensitivity Analysis, and Discriminatory Power. *Environmental Science and Pollution Research* 7:220-224.

Soeder, D.J. The Marcellus Shale: Resources and reservations. 2010. EOS, Transactions, *American Geophysical Union* 91(32):277-278.

State Review of Oil and Natural Gas Environmental Regulations (STRONGER, Inc.) http://www.strongerinc.org/index.asp.

Theodori, G.L. Community and Community Development in Resource-Based Areas: Operational Definitions Rooted in an Interactional Perspective. 2005. *Society and Natural Resources* 18:661–669.

Theodori, G.L. Public opinion on exploration and production of oil and natural gas in environmentally sensitive areas. 2009. *16th International Petroleum and BioFuels Environmental Conference*, Houston, TX, November 3-5, 2009.

Theodori, G.L., N. Miller, G.T. Kyle, and W.E. Fox. 2009. Exploration and production of oil and natural gas in environmentally sensitive areas: Views from the public. *15th International Symposium on Society and Resource Management*, Vienna, Austria, July 5-8, 2009.

Theodori, G.L., B.J. Wynveen, W.E. Fox, and D.B. Burnett. 2009. Public perception of desalinated water from oil and gas field operations: Data from Texas. *Society and Natural Resources* 22 (7): 674-685.

Tuttle, M.L.W., and Breit, G.N. Weathering of the New Albany Shale, Kentucky, USA: 1. Weathering zones defined by mineralogy and major-element composition. 2009. *Journal of Applied Geochemistry* 24:1549-1564.

Tuttle, M.L.W., Breit, G.N., and Goldhaber, M.B. Weathering of the New Albany Shale, Kentucky: 2. Redistribution of minor and trace elements. 2009. *Journal of Applied Geochemistry* 24:1565-1578.

U.S. Army Engineer Waterways Experiment Station. Ecological Effects of Water Level Reductions in the Great Lakes Basin: Report on a Technical Workshop. 1999. John W. Barko, Ph.D., Technical Coordinator. *U.S. Army Engineer Research and Development Center Environmental Laboratory*, Vicksburg, MS. December 16-17, 1999. http://www.glc.org/wateruse/biohydro/pdf/vicksburg/VicksburgReport.pdf.

Yu, M., G. Chen, M.E. Chenevert, and M.M. Sharma. Chemical and Thermal Effects on Wellbore Stability of Shale Formations. 2001. *Society of Petroleum Engineers Annual Technical Conference and Exhibition* – September 30-October 3, 2001, New Orleans, LA.

Yu, M., M.E. Chenevert, and M.M. Sharma. Chemical–mechanical wellbore instability model for shales: accounting for solute diffusion. 2003. *Journal of Petroleum Science and Engineering* 38 (3-4): 131-143.

3.4. **Proposed Research Activities - Water Acquisition**

Charge Question 4(a): Proposed research activities are provided for each stage of the water lifecycle and summarized in Figure 9. Will the proposed research activities adequately answer the secondary questions listed in Table 2 for the Water Acquisition stage of the water lifecycle? Please provide any suggestions for additional research activities.

3.4.1. General Comments

A majority of the Panel recommended that the definition of "drinking water resources" related to hydraulic fracturing activities should be broadened to be more than just waters with less than 10,000 mg/L of total dissolved solids, given recent advances in membrane desalination and likely changes in perspectives of what constitutes potential drinking water sources in the future. This recommendation refers to the technical subject of desalination in general and issues involving ground water resources and reuse of water resources. Some Panel members raised concerns that definitions of drinking water resources are often handled differently by the states, and that addressing this issue may be beyond the scope of the study.

The SAB recommends that the draft Study Plan include an additional desired research outcome to collect baseline data in a given area as part of a prospective case study before HF activity begins, so that significant changes in water availability or water quality caused by HF activity can be more readily documented. One outcome of this effort is identification of recommended baseline data that should be collected before HF begins so that significant impacts can be more readily observed after HF begins. EPA should consider developing a "vulnerability index" or a list of criteria that could be used in the future to indicate situations where a water supply is vulnerable to adverse impacts on water quality or quantity.

The SAB recommends that EPA's list of analytes that would be studied to assess the impacts of water acquisition and other HF activities on water quality should specifically include the following constituents: hydrogen sulfide, ammonium, radon, iron, manganese, arsenic, selenium, total organic carbon, and bromide. In addition, EPA should also assess the potential of constituents in HF-impacted waters to form disinfection by-products (including trihalomethanes, haloacetic acids, other halogenated organic compounds and disinfection by-products formed by other disinfecting agents such as chloramines) in drinking water treatment.

In addition, the SAB believes that Maximum Contaminant Levels (MCLs) established under the Safe Drinking Water Act are not sufficient for assessing all potentially significant impacts on drinking water quality. The SAB recommends that EPA include in its analysis potential impacts on water quality that do not involve MCL exceedances. EPA should also examine trends in water quality associated with HF water acquisition and determine whether adverse impacts will result if these trends continue.

The SAB has a number of specific comments noted below associated with this lifecycle stage. Additional specific comments on the research questions for this lifecycle stage are included within this Report's response to Charge Question 2.

3.4.2. Specific Comments

The draft Study Plan states (p. 1) that EPA defines "drinking water resources" to include underground sources of drinking water (USDWs), which are defined in the glossary as aquifers capable of supplying a public water system and having a TDS concentration of 10,000 mg/L or less. It is reasonable to consider very deep, highly saline aquifers isolated from drinking water resources as potential sites for waste injection, but shallower brackish waters are increasingly being considered as potential sources of supply. Furthermore, some relatively saline aquifers could potentially be used for future "aquifer storage and recovery" operations, and it is likely that state and federal regulatory agencies will take measures to prevent them from being polluted in the years ahead. The SAB recommends that EPA reconsider this definition, given recent advances in membrane desalination and current and future water shortages in many parts of the U.S., and determine whether it is still an appropriate definition to use.

The draft Study Plan does not explicitly address the obstacles private well owners and small public water supply systems (PWSSs) may encounter if they experience adverse impacts on water availability or water quality that they believe are related to HF activities. Unlike larger users, private well owners and small PWSSs will generally lack the financial resources to hire experts to prove that their water resources have been adversely impacted. This problem is related to both management practices and environmental justice (as discussed in Section 9 of the draft Study Plan), and is an issue for anyone whose private well is impacted. The SAB also recommends that the draft Study Plan include an additional desired research outcome to develop a recommended protocol for collecting baseline data in a given area before HF activity begins, so that significant changes in water availability or water quality caused by HF activity can be more readily documented. EPA should consider developing a "vulnerability index" or a list of criteria that could be used to indicate situations where a water supply is vulnerable to adverse impacts on water quality or quantity, such that further evaluation may be warranted.

EPA's list of analytes to be considered in studying the impacts of water acquisition (and other HF activities) on water quality (Table G1) should explicitly include: 1) hydrogen sulfide, a toxic and corrosive substance that also imparts a strongly offensive odor to air and water, exerts an oxygen demand in streams, and exerts a high oxidant demand (e.g., chlorine demand) when present in a public water supply; 2) ammonium, a compound naturally present in many alluvial aquifers and some deeper formation that exerts a large chlorine demand and is also toxic to many aquatic organisms; 3) radon, a radioactive gas that could potentially be released into drinking water by HF activities; 4) iron, manganese, arsenic, and selenium, constituents that may be mobilized by HF activities, including water withdrawal; and 5) total organic carbon (TOC), bromide and potential disinfection by-products, including trihalomethanes, haloacetic acids, and other halogenated organic compounds.

The SAB believes that Maximum Contaminant Levels (MCLs) established under the Safe Drinking Water Act are not sufficient for assessing all potentially significant impacts on drinking water quality. For example, changes in nutrient or carbon loading to a stream that do not directly cause an MCL to be exceeded can still cause changes in water quality, such as increased production of taste- and odor-causing compounds or disinfection by-product (DBP) precursors, resulting in increased treatment costs or degradation of drinking water quality. An increase in bromide in source waters may cause an increase in cancer risk (if more carcinogenic brominated species are preferentially formed) even if the MCLs for DBPs are not exceeded. A significant increase in the chloride concentration can cause considerably economic loss to a community even if the secondary MCL for total dissolved solids (TDS) of 500 mg/L is not exceeded. Therefore, the SAB recommends that EPA include in its analysis potential impacts on water quality that do not involve MCL exceedances. EPA should also examine trends in water quality associated with HF water acquisition and determine whether adverse impacts will result if these trends continue, e.g., if HF water acquisition activities continue to increase in the area up to the maximum level that can be reasonably expected.

3.5. **Proposed Research Activities - Chemical Mixing**

Charge Question 4(b): Proposed research activities are provided for each stage of the water lifecycle and summarized in Figure 9. Will the proposed research activities adequately answer the secondary questions listed in Table 2 for the Chemical Mixing stage of the water lifecycle? Please provide any suggestions for additional research activities.

3.5.1. General Comments

The SAB supports EPA's proposed approach to analyze existing data rather than collecting samples for analysis, and believes that EPA's planned effort to gather data from nine hydraulic fracturing service companies will likely provide sufficient information on the composition of HF fluids provided the companies cooperate and supply the information in a timely manner. SAB recommends that EPA also gather HF fluid composition data from state(s) collecting such data, and consider the role that recycling and reuse of HF fluids will play in influencing both quantity and composition of HF fluids.

Given the limited available time and budget for the current project, the SAB believes that in-depth study of toxicity is not possible, and thus supports EPA's plan to evaluate the toxicity of the selected constituents through existing databases. EPA should clarify which of the selected constituents have no or limited available toxicity information within existing databases. SAB recommends that EPA assess potential pathways of exposure to the public through drinking water.

While it would be helpful if EPA developed indicators of potential contamination, it may be difficult to achieve a practical indicator approach within the time allotted for the current study. The SAB also believes that EPA should give low priority to development of analytical methods for specific components for which there are no existing certified methods.

SAB generally supports EPA's plans to identify factors that influence the likelihood of contamination of drinking water resources. Although SAB believes that EPA will identify a number of factors that influence the likelihood of contamination of drinking water resources, the list of factors may not be complete, the project time and budget will not allow time for a complete evaluation of the factors, and the results should not be generalized across all HF sites.

SAB does not believe that case studies alone will provide sufficient information regarding effectiveness of mitigation approaches in reducing impacts to drinking water resources. SAB suggests that EPA analyze data from HF service companies and states in order to provide additional insight. The retrospective case studies may also be a source of useful information about approaches that failed to prevent or control impacts.

The SAB has a number of specific comments noted below associated with this lifecycle stage. Additional specific comments on the research questions for this lifecycle stage are included within this Report's response to Charge Question 2.

3.5.2. Specific Comments

<u>What is the composition of hydraulic fluids and what are the toxic effects of these constituents?</u>

The draft Study Plan indicated that the approach to be used in answering the question about composition of hydraulic fracturing (HF) fluids and toxicity of the components will be to analyze existing data. The SAB believes that EPA's planned effort to gather data from nine hydraulic fracturing service companies is an approach that is likely to answer the question on composition of HF fluids, provided the companies cooperate and supply the information in a timely manner. The SAB supports the analysis of existing data rather than reverse engineering of collected samples of fluids. Appendix C of the Draft Plan indicated that all companies have agreed to comply with the request and that information should be submitted by the end of January 2011. The selected companies are likely to provide a comprehensive list given the size of the companies and their geographic coverage. The level of detail requested should provide the EPA with data adequate to answer the question. The SAB notes that a few states are collecting relevant data either as a requirement of permitting (e.g., Wyoming) or on a voluntary basis (e.g., Pennsylvania) that can be of use to the EPA for this question. The SAB also recommends that EPA consider the role that recycling and reuse of HF fluids will play in composition.

The SAB supports the EPA plan to determine the toxicity of the selected constituents by using existing databases. The use of existing knowledge about the toxicity was endorsed by the SAB because of the short time available for the study and the limited resources. The SAB emphasizes the importance of determining the potential pathways of exposure to the public through drinking water. The SAB also supports the development of a prioritized list of compounds for which toxicity is unknown but given the likelihood of exposure should be tested for toxicity. The SAB notes that developing a first order hazard assessment for the components of HF fluids was worthwhile, but that in-depth study of toxicity is not considered possible given the time and funding constraints. Scenario modeling may be useful in developing the list of priorities for toxicity testing.

The SAB finds the development of potential chemical indicators of contamination an appealing approach. The consensus of the SAB is that it may be difficult to achieve a practical indicator approach within the time allotted for the study. The EPA can likely develop a list of possible indicators for which analytical methods exist that can be tested in the prospective case studies and scenario modeling. Tracers that can be added might be another tactic to consider but must take into consideration public and industry concerns about such an approach.

The SAB also suggests that development of analytical methods for specific components for which there are no existing certified methods should be given a low priority. The EPA should focus on existing methods for the near term effort and develop a list of priorities for future efforts based on the first order hazard assessment.

In addition, the Ground Water Protection Council (GWPC) and the Interstate Oil and Gas Compact Commission (IOGCC), with funding support from the U.S. Department of Energy (DOE), unveiled a web-based national registry on April 11, 2011 disclosing the chemical additives used in the hydraulic fracturing process on a well-by-well basis (www.fracfocus.org). EPA should consider these data when assessing the composition and toxicity of HF fluids. The information on the web site covers wells drilled starting in 2011. A fact sheet on the effort is available from the State of Oklahoma (http://www.iogcc.state.ok.us/national-registry-provides-public-and-regulators-access-to-information-on-chemical-additiv).

What factors may influence the likelihood of contamination of drinking water resources?

The SAB concludes that the EPA will be able to identify a number of factors that influence the likelihood of contamination, but the list of factors may not be complete and should not be generalized across all HF sites. The EPA indicated that it will analyze existing data and use the retrospective case studies to answer this question. The SAB expresses support in general for the planned approach to answering this question. The information request to the nine HF services companies will likely provide input on some of the factors (e.g., total quantities used, chemical and physical properties of components, etc.). The EPA will also search the existing literature for research about potential contamination of drinking water resources using the list of chemicals supplied through the information request. The states may provide information about the spills that may have affected drinking water resources. The SAB supports EPA's plan to develop a list of the knowledge gaps about factors influencing the contamination of drinking water for future research efforts. The SAB is concerned that several factors will be site specific and difficult to generalize across the range of geographical areas that are involved in HF activities. The SAB suggests that the EPA will need a full understanding of all the activities involved such as the cleaning of mixing vessels or tanker trucks and handling of the wash water. The SAB notes that the prospective case studies are potentially useful in answering this question; however, the SAB also notes that these case studies may only provide insight into best management practices that are not necessarily in use at the average site. The number of retrospective and prospective case studies that can be evaluated in the given time will be limited.

How effective are mitigation approaches in reducing impacts to drinking water resources?

The SAB expresses concern that the prospective case studies alone may not provide adequate answers for this question. The partners involved in the prospective case studies will likely follow best management practices and take extra precautions, therefore, these limited number of case studies may not provide answers about the management practices to mitigate impacts to drinking water resources at a more typical HF site. The analysis of data supplied by the HF service companies and states may be helpful in providing additional insight. The retrospective case studies may be a source of useful information about approaches that failed to reduce impacts.

3.6. **Proposed Research Activities - Well Injection**

Charge Question 4(c): Proposed research activities are provided for each stage of the water lifecycle and summarized in Figure 9. Will the proposed research activities adequately answer the secondary questions listed in Table 2 for the Well Injection stage of the water lifecycle? Please provide any suggestions for additional research activities.

3.6.1. General Comments

The SAB believes that EPA's proposed research activities for the assessment of potential impacts of well injection related to hydraulic fracturing on drinking water resources is scientifically adequate. The SAB believes it will not be possible to cover all facets of the proposed research within the time allotted for the research activities, and recommends that EPA narrow the scope of activities to specific case studies and site investigations and use a wide variety of sources available to EPA in order to increase the success of the research program. The SAB provides a number of specific suggestions for focusing EPA's fundamental and secondary research questions associated with this topic area. The SAB recommends that EPA should research well drilling and cementing practices separately from the hydraulic fracturing process. With the cooperation of service companies, full access to data, and careful selection of case studies, the SAB believes that the proposed research can adequately address most of the fundamental questions associated with possible impacts of the injection and fracturing processes on drinking water resources.

The SAB has a number of specific comments noted below associated with this lifecycle stage. Additional specific comments on the research questions for this lifecycle stage are included within this Report's response to Charge Question 2.

3.6.2. Specific Comments

Fundamental Research Question

The fundamental research question addressed under the topic of well injection is "What are the possible impacts of the injection and fracturing process on drinking water resources?" Addressing the fundamental question involves establishing different degrees of risk - from catastrophic (e.g., earthquakes) to manageable risk. There are different risks dependent on different geologic and hydrogeologic conditions requiring a prioritization of research to be conducted. By conducting retrospective and prospective case studies as outlined in the draft Study Plan the various risk factors and their interdependence can be evaluated. While not totally encompassing, the research will aid in addressing the fundamental research question pertaining to possible impacts.

As a starting point, the SAB recognizes that there are three escape mechanisms for contaminants that might affect drinking water: escape through the well, through the cementing practice, and

through the hydraulic fracturing process itself. The consensus of the Panel is that well drilling and cementing practice be researched separately from the hydraulic fracturing process itself. In doing so, the SAB believes it is essential that EPA prioritize the research to address the fundamental question of the potential influence of the hydraulic fracturing process on drinking water resources and contamination of aquifers given the charge to the EPA from Congress, and given the limited time frame allocated to this study.

As discussed in Section 3.7 of this Report, SAB recommends that the handling of the flowback and produced water be provided first priority for exposure assessments. However, since groundwater can potentially be contaminated by HF in a number of ways (including leakage from storage, leakage from the injection wells, leakoff during hydrofracking potentially along faults or up abandoned wells, and seepage into the ground if used for irrigation), a strong secondary emphasis should be placed on assessing exposures through potential groundwater contamination. The SAB also recognizes that while discharges to surface water tend to be transient, groundwater contamination is more likely to lead to long-term contamination and long-term exposure. In addition, surface water contamination is much more likely to impact relatively large water utilities that are better able to monitor both raw and finished water quality, to recognize that contamination is occurring, and to treat or address such contamination. In addition, groundwater is preferentially used as a source of supply by smaller utilities and communities (including rural communities) and by the overwhelming majority of non-community water systems. Many such supplies are only minimally monitored, and their owners often lack the resources to independently protect the aquifers from which their supplies are drawn. Unlike surface waters, groundwater is susceptible to contamination by methane and radon; and groundwater is more susceptible to contamination by VOCs, including the BTEX compounds that have reportedly been used at times to prepare HF fluids.

<u>Secondary Research Questions</u>

Discussion under item 4(c) focused on four secondary research questions:

1) *How effective are well construction practices at containing gases and fluids before, during and after fracturing?*

The SAB believes that EPA's research activities regarding well construction practice should be split into two categories – the drilling and cementing practices (i.e., well bore integrity during construction) versus well integrity during the fracturing process itself. Regulatory agencies in some states may have access to data on well bore integrity that can enable the EPA to address specific examples of well bore and well failure. The SAB suspects that the data will be 'spotty', however, and may vary from state to state. The value of 'mining' such data may be in the retrospective case studies to evaluate risk. It will be area- and site-dependent. In addition, there are thousands of underground injection wells currently that are controlled by the Underground Injection Control Program (UIC) that can shed light on the general topic of well bore and well integrity.

EPA should revise the Study Plan to define the data that would be collected to assess well failure and to relate relevant factors into a risk assessment model. The Study Plan should also be specific about how the frequency of well failures will be determined because the method to be used is not obvious in the draft Study Plan. The well architecture itself is shifting away from vertical wells to highly deviated wells with multi-zone completions. EPA may have to specifically focus and direct its research activities based on well type in order to adequately evaluate the effectiveness of well construction practices and the risk of contamination of groundwater resources.

The hydraulic fracturing process needs to be addressed separately. The SAB recommends that EPA conduct research on factors such as depth of the hydraulic fracturing and proximity to underground aquifers, the geology of the subsurface, the hydrogeologic framework, stresses in the subsurface, the fluids used in the process, and the interaction with the rock and fluids in the subsurface. By addressing these factors in a systematic manner through the use of case studies, modeling and laboratory analyses, risk assessment modeling may be undertaken to prioritize risk related to the process itself.

In the case studies EPA could provide special focus on the key factors necessary in establishing a risk assessment model. A shortcoming of this approach is that typical risk assessments do not include the potential for catastrophic failure. Treating end members within a risk assessment model can aid in creating transparency and hazard preparedness. Modeling the hydraulic fracture process through finite difference or finite element mathematical modeling may give insights into criteria for establishing risk.

Finally, EPA should identify and choose case study sites where hydraulic fracturing is being conducted in relatively shallow environments in proximity to drinking water aquifers. Microseismic monitoring, if available, could be used to help create appropriate fracture models. In areas of variable topography, underground mining, or in karst regions within the subsurface, stress variances can induce a variation in fracture growth.

2) *What are the potential impacts of pre-existing artificial or natural pathways/features on contaminant transport?*

The SAB generally agrees that geologic and hydrogeologic characterization is necessary, but notes this is a difficult task to undertake especially within the limited budget and time for the study. The SAB recommends that EPA's first step should be to focus on specific areas where the most complete data on these topics are available. The SAB also suggests that EPA use the resources of other governmental agencies such as the U.S. Geological Survey to address subsurface characterization and to establish analogous injection sites (e.g., carbon dioxide sequestration projects). Site characterization is an essential ingredient of determining the viability of sites to store carbon dioxide. The U.S. Department of Energy may be able to provide EPA with information on stresses in the subsurface, which is a significant factor to consider. It is also essential for EPA to establish stress profiles and determine the mechanical stratigraphy and hydrological properties of the case study areas. Generally, the data are available to engage in site characterization as part of the case studies that will be selected and undertaken.

The SAB believes that a major concern to be addressed is the presence of faults in the subsurface. Not all faults are transmissive in nature, and numerous studies have documented faults as seals or sealing faults. The SAB notes that a key concern is what happens when there is injection near a fault. Generally, it is industry practice to avoid faults by conducting reflection seismic profiling to identify faults. These studies are often conducted for purposes of geosteering to avoid faults and drilling out of zone. However, sub-seismic faults exist, making it difficult to avoid faults altogether. Microseismic monitoring can assist in determining what happens if a hydraulic fracture is conducted near a fault. EPA should consider gathering available seismic profile data to assist in evaluating the potential for releases to underground sources of drinking water. Whether or not the fault is transmissive requires other forms of study including transient pressure testing.

The SAB recommends that EPA identify a shallow site with faults as one of the prospective case studies. The SAB expresses concern about fracture fluids propagating in fault and fracture zones. These fluids can occur in gaseous or liquid state and have different mobility and flow characteristics. Mobile gases can move along fault and fractures zones in a relatively short time; liquids will take longer to move than gases. Different fluids create different potential problems and a variety of scenarios needs to be investigated. The SAB suggests that EPA focus additional research on the different fluids associated with the hydraulic fracturing process. The SAB recommends that EPA conduct soil geochemistry studies which may shed light on the question of gas transport associated with the hydraulic fracturing process.

The SAB recognizes that the use of a chemical tracer may aid the monitoring effort, but notes that the tracer would have to be carefully and judiciously chosen. The tracer design must be unique, unambiguously related to the hydraulic fracturing process, identifiable, non-toxic and non-reactive.

The SAB believes that long term monitoring is preferred over short term monitoring with respect to monitoring of HF impacts on water resources. The SAB recognizes that EPA may have difficulty in precisely determining cause and effect associations within the monitoring networks, for various reasons. If fractures are only opened during the hydraulic fracturing process, a very short time period for mobilization can occur. In low permeability formations, however, it may take considerable time for pressure to abate. Fluid flow in these low permeability reservoirs is non-Darcy flow involving diffusion. Upon production, pressure drawdown occurs and fractures close over time.

In addition, abandoned wells and mines are potential primary conduits to near surface aquifers as well as surface waters. The identification of abandoned wells is problematic, and the SAB recommends that EPA assess the role these wells and old mine workings play in certain parts of the country relative to hydraulic fracturing operations.

3) What chemical/physical/biological processes could impact the fate and transport of substances in the subsurface?

The SAB recommends that EPA conduct activities to identify the chemicals used in the hydraulic fracturing process and their chemical and physical properties. Biological processes and the details regarding how the biological impact will be investigated are unclear in the draft Study Plan. . .

In addition, the chemicals contained in the flowback or produced waters need to be analyzed. A major concern is the interaction of the fracturing process with the chemicals within formations and whether this interaction increases the potential for contamination of water resources in a given area. This disclosure would aid in the determination of risk factors and assist the development of a risk assessment process. To focus on toxicity issues, the primary composition of the chemicals used in the hydraulic fracturing process and their interaction with the natural compounds in the subsurface need to be addressed in this study. Research should also address the potential degradation of these products and reactions over time. The Study Plan implies that this research would only involve laboratory studies. The SAB believes that the results may not be representative of what happens in the field. SAB recommends that analysis of samples collected in conjunction with the case studies be included in answering this question in addition to the laboratory studies. SAB also recommends that modeling be conducted to assist in answering this question, if there are models available that can predict the decomposition products from reactions of HF fluids with formation materials.

4) What are the toxic effects of naturally occurring substances?

The SAB believes that EPA's proposed research activities may answer the question about the known toxic effects of naturally occurring substances. EPA is proposing to compile existing toxicity information and use structure activity relationships and predictive toxicology tools to estimate hazards for substances with little or no data. The SAB cautions EPA on spending resources on predicting the toxicities of substances if those toxicities are unknown, unless EPA knows that the probability of exposure to a particular substance is high. The SAB also notes that Table 5 is fairly general and does not include radon or alkanes and that Table D2 should be included in the discussion in Section 6.3.5. If EPA uses predictive toxicology tools, EPA should also include some description of data quality associated with such tools (human data versus Structure Activity Relationship data, SAR).

As mentioned in the previous paragraph, the SAB, however, recommends that the level of effort using predictive toxicology tools should be informed by the likelihood of exposure (both frequency and concentration) to specific substances from hydraulic fracturing activities. If exposure to specific substances is likely, this activity is worthwhile. If exposure to specific substances is extremely unlikely, this activity should not be undertaken or should have a low priority.

Two other potential products of this research activity are to prioritize a list of chemicals requiring further toxicity study and to develop Provisional Peer-Reviewed Toxicity Values (PPRTVs) for chemicals of concern. The SAB also recommends that these activities have a low priority if exposure to a substance is not likely and/or levels of exposure are minimal (e.g., parts

per trillion). For prioritizing chemicals for further study, EPA should review the process it used to develop its most recent Contaminant Candidate List (CCL) and apply any lessons learned.

The SAB also recommends that EPA consider hazard broadly and include risks that these substances may have (explosions) that are not due to toxicity. EPA should also acknowledge any aesthetic impacts that both naturally occurring and well-injection derived substances may have on drinking water quality.

Suggestions for Additional Research Activities

The SAB provides the following suggestions for additional research activities:

1) Conduct hydraulic fracturing studies in areas that are highly stressed (e.g., shale formations) which when unloaded, may have the potential to fracture. Stresses should be measured and quantified at certain sites. Modeling studies could be incorporated to address various scenarios. Studies should include worst case scenarios and catastrophic failures such as the creation of earthquakes.

2) Identify and characterize common and best practices for well construction (e.g., casing design, construction under different scenarios, settings, failure rates, life expectancies, and performance of cements under a variety of hydraulic fracturing conditions), and determine whether such practices meet minimum standards from a public water supply perspective. EPA should consider gathering available information on this topic from the American Petroleum Institute and the National Ground Water Association.

3) Research fluids and fluid movements associated with hydraulic fracturing in terms of mobility. There are gaseous and liquid states, different flow paths, different flow mechanisms, and potentially even “hybrid” reactions under different temperature and pressure regimes.

4) Review Tables 5, D2 (needs to be included in section 6.3.5), and D3 for completeness (e.g., radon is not included). Toxicity studies, if exposure is likely, may need to be undertaken.

5) EPA should consider using predictive toxicology tools as a way to identify possible problematic constituents of various HF fluids. This activity may be carried out separately from activities associated with EPA’s Study Plan so as not to affect the timeliness and completeness of EPA’s Study Plan.

3.7. **Proposed Research Activities – Flowback and Produced Water**

Charge Question 4(d): Proposed research activities are provided for each stage of the water lifecycle and summarized in Figure 9. Will the proposed research activities adequately answer the secondary questions listed in Table 2 for the Flowback and Produced Water stage of the water lifecycle? Please provide any suggestions for additional research activities.

3.7.1. General Comments

The SAB believes that the handling of the flowback and produced water represents the most likely important route of exposure and potential for adverse impacts on drinking water resources from the development of unconventional gas resources on a national level. The SAB recommends that EPA define and differentiate flowback and produced water in the main body of the Study Plan, and clearly distinguish such waters from other water used during the hydraulic fracturing process. While SAB recommends that the handling of the flowback and produced water be provided first priority for exposure assessments, since groundwater can potentially be contaminated by HF in a number of ways (including leakage from storage, leakage from the injection wells, leakoff during hydrofracking potentially along faults or up abandoned wells, and seepage into the ground if used for irrigation), a strong secondary emphasis should be placed on assessing exposures through potential groundwater contamination.

The SAB supports EPA's plan to gather information on the composition of flowback and produced water from the hydraulic fracturing process as much as possible from currently available data. The SAB recommends the collection of water quality data from specific points in time and from carefully selected locations, including the ongoing studies on the quality of surface waters in the regions with significant hydraulic fracturing activity. EPA should evaluate quality assurance/quality control (QA/QC) aspects of the studies that would be assessed or conducted by EPA.

The SAB recommends that EPA consider the use of a risk assessment framework to assess and prioritize research activities for the lifecycle stages of flowback and produced water. The SAB recommends that EPA focus on potential human exposure, followed by hazard identification if sufficient time and resources are available. The SAB anticipates that the primary opportunity for human health exposure is likely to be through surface waters, and recommends that EPA's first order human health exposure assessment focus on surface water management of flowback and produced waters. The SAB recommends that EPA not conduct toxicity testing at this time.

The SAB has a number of specific comments noted below associated with this lifecycle stage. Additional specific comments on the research questions for this lifecycle stage are included within this Report's response to Charge Question 2.

3.7.2. Specific Comments

The SAB suggests the handling of the flowback and produced water represent the most important route of exposure and potential for adverse environmental impacts from the development of unconventional gas resources on a national level. This is particularly true in situations where Class II Underground Injection Control (UIC) wells are not the main disposal alternative. A lifecycle approach is an important component of this study, and this lifecycle must be correctly characterized. This requires a distinction between flowback and produced water and an incorporation of the issue of recycling in the overall water management strategy. Both flowback and produced water potentially contain both harmful and non-harmful chemical products. The SAB suggests that EPA define and differentiate flowback and produced water, and clearly distinguish such waters from other water used during the hydraulic fracturing process. It is difficult to distinguish between flowback and produced water. Several Panel members suggested to categorize flowback and produced water as post-fracturing produced water. After hydraulic fracturing occurs, brine from the fractured formations begins to flow back. At the outset the flowback water is comprised mainly of the liquids that were injected, and those liquids are also mixed with in-situ or "connate" water. As flow continues, the volume declines and more and more of the flowback water content is naturally occurring brine. Each gas shale play is different – with some wells showing less than 30% recovery of the injected liquids while other wells easily recover 70% of the injected liquids.

The SAB recommends that EPA consider the use of a risk assessment framework to assess and prioritize research activities for the lifecycle stages of flowback and produced water. The SAB further believes that EPA should conduct a risk assessment paradigm analysis (i.e., hazard identification, dose-response assessment, exposure assessment, and risk management) for each lifecycle stage and use the paradigm to assist in problem formulation. Consequently, it is expected that the main outcomes of this study would be less deterministic and more probabilistic in nature. The SAB recommends that EPA focus on potential human exposure, followed by hazard identification if sufficient time and resources are available. The SAB emphasized that the primary opportunity for human health exposure is likely to be through surface waters, and recommends that EPA's first order human health exposure assessment focus on surface water management of flowback and produced waters. The SAB suggests that there is no need to conduct toxicity testing at this time.

The SAB agrees with EPA that it is very important to gather information on the composition of flowback and produced water from the hydraulic fracturing process, to the extent these data are currently available. EPA should consider contacting Publicly Owned Treatment Works (POTWs) who accept this water for treatment, accessing the Colorado Oil and Gas Commission database, and assessing ongoing U.S. Department of Energy National Energy Technology Laboratory projects, particularly since the sampling and analysis to be conducted as part of this study would be rather limited. Within the human exposure assessment, EPA should assess which chemicals are of primary concern and their probability for transport in groundwater and air. The SAB recommends that water quality data be collected from specific points in time and from carefully selected locations, including the ongoing studies on the quality of surface waters in the regions with significant hydraulic fracturing activity. In cases where actual concentrations

of contaminants are needed to assess potential environmental impacts, including toxic effects, it would be necessary to validate QA/QC aspects of the studies that collected these data. It is expected that the prospective case studies would follow requisite QA/QC protocols. Development of new analytical techniques may be beyond the capability of the proposed study in terms of time and budget; there is likely sufficient information in the literature to utilize when conducting sample collection and analysis as part of this study.

The Study Plan appears to emphasize the focus of study and research towards shale formations, but also notes that coal bed methane and other types of hydraulic fracturing are to be considered (see page 4, section 2.3). The Study Plan should clarify and specify the research focus for this lifecycle stage (e.g., whether the focus for gathering information is on hydraulic fracturing in shale units, natural gas production, coal bed methane production, other types of hydraulic fracturing activity, or a combination of the above).

The SAB suggests a number of specific research questions under the response to Charge Question 2, and provides a few additional suggested specific research questions:

- Inventory types of water being used in hydraulic fracturing to answer questions regarding how much high quality water is being used (e.g., water less than 10,000 mg/L Total Dissolved Solids) vs. lower quality waters.

- Inventory flowback and produced water quality for different geographic regions and by HF product used to facilitate specific environmental monitoring and improve reporting outcomes as well as to inform first responders in the case of spills and leaks and to develop necessary management (treatment) approaches as a function of ultimate disposal alternatives.

- Consider normal industrial practices at coal bed methane hydraulic fracturing facilities. These facilities have documented best management approaches for produced waters, and also have identified boundaries for use of and expectations associated with produced water quality and hazard scenarios and spills.

- Assess industry practices on containment technologies and releases from pits and liners with leaky seals, and describe the “best management practices” for handling flowback and produced water during storage and transport.

- The SAB suggests that identification of potential for leaks and spills during storage and transport should be based on documented events in the past, which can serve to assess the probability for the release of contaminants during different stages of flowback and produced water management provided that trends in management practices are taken into consideration.

- Assess potential adverse environmental impacts associated with buried pits and impoundments through evaluating the quality of soils and groundwater near such structures.

- The SAB suggests that the disposal of flowback and produced water to existing POTWs and Centralized Waste Treatment (CWT) facilities needs to be evaluated in terms of the fate of key constituents (e.g., chloride, bromide, radium) that may be relevant for drinking water treatment facilities downstream of these wastewater treatment plants.

3.8. **Proposed Research Activities - Wastewater Treatment and Waste Disposal**

Charge Question 4(e): Proposed research activities are provided for each stage of the water lifecycle and summarized in Figure 9. Will the proposed research activities adequately answer the secondary questions listed in Table 2 for the Wastewater Treatment and Waste Disposal stage of the water lifecycle? Please provide any suggestions for additional research activities.

3.8.1. General Comments

Hydraulic fracturing return flows contain many constituents that are similar to those for which treatment technologies exist within the state of practice of industrial wastewater treatment. For those constituents, SAB believes that EPA should conduct a thorough literature review to identify existing treatment technologies that are currently being used to treat HF wastewater, identify knowledge relevant to hydraulic fracturing return flows, and identify constituents of HF return waters that might merit additional attention. SAB recommends that EPA review the documented data in the retrospective case studies to assess the efficacy and success of industrial wastewater treatment operations and pre-treatment operations for hydraulic fracturing return flows. Only a limited number of Publicly Owned Treatment Plants (POTWs) have the ancillary treatment technologies needed to remove the constituents in hydraulic fracturing return waters. SAB recommends that EPA focus its efforts towards literature searches on POTW and industry management practices that can minimize the adverse effects associated with certain constituents such as total dissolved solids (TDS), natural organic matter (NOM), bromide, and radioactive species, rather than on characterizing those effects. In addition, EPA should assess the need for any special storage, handling, management, or disposal controls for solid residuals after treatment. EPA should also consider industrial practices in which the hydraulic fracturing return flows have been used for irrigation.

The SAB has a number of specific comments noted below associated with this lifecycle stage. Additional specific comments on the research questions for this lifecycle stage are included within this Report's response to Charge Question 2.

3.8.2. Specific Comments

The SAB recommends that the research question itself be reworded to, "What is the appropriate treatment of hydraulic fracturing (HF) wastewater, and how does the hydraulic fracturing wastewater affect treatment plants (both water and wastewater)?" The issue at hand is whether inadequate treatment is common, as well as the consequences.

Hydraulic fracturing return flows contain many constituents that are similar to those for which treatment technologies exist within the state of practice of industrial wastewater treatment. For those constituents, a thorough literature review should be conducted to match treatability studies and treatment technologies that are currently being used to treat HF wastewater to hydraulic

fracturing return flows, and to identify constituents of HF wastes that might merit additional attention. The EPA retrospective case studies should review the documented data to assess the efficacy and success of industrial wastewater treatment operations and pre-treatment operations for hydraulic fracturing wastewater (return flows). Such studies need to critically assess characteristics of: volumes and flowrates; influent and effluent concentrations; the fate of the treated water; management practices, and the disposal of solid residuals. Rather than just a handful of retrospective studies as proposed, the full richness of available data should be explored. In addition, facilities maintenance (aspects, requirements, frequency, etc.) and cost factors (capital, Operation & Maintenance at different stages of the life-cycle need documentation.

Few POTWs are designed to remove many of the contaminants of the hydraulic fracturing process. Dissolved solids are not removed in such systems, and in high concentrations they can disrupt some unit operations. This phenomenon has been well-studied, so the research on this topic should focus on industry management practices that can minimize the adverse effects, rather than on characterizing those effects or the thresholds at which they become significant. All POTWs that now accept hydraulic fracturing return flows should be included in the retrospective studies in the assessment of the impacts of TDS. Similarly, the effects of increased NOM and bromide concentrations on disinfection byproducts formation in drinking water treatment processes and on corrosion of water distribution networks can be assessed based on a thorough literature review and information that the service companies likely have on the salt content of the wastewaters. Radioactive species also deserve special attention. Therefore, once again, the research should focus on management options to avoid concentrations that lead to adverse effects, rather than on studying the effects themselves.

Comment [c2]: Same comment as on pg 20 Because of the recent presentation of research by Dr. Stanley States and research from Carnegie Mellon University, PADEP has 'requested' that none of the municipal or industrial waste treatment plants in PA accept Marcellus Shale wastewater after May 19, 2011. This is a major accomplishment for the PA drinking water utilities. The data clearly show that bromide in the source water significantly increases the concentration of THMs in drinking water as well as the proportion of the more toxic brominated species. The research also indicates that conventional drinking water treatment processes are ineffective in removing bromide from the source water. Furthermore, their extensive, ongoing survey of the Allegheny River and its tributaries indicates that the principal contributor of bromide to the river is industrial wastewater plants which treat Marcellus Shale flowback water. Municipal POTWs that treat this wastewater don't appear to contribute bromide to the rivers, presumably because they chlorinate the treated effluent prior to discharge. In effect, they are forming the THMs at the wastewater plants and the THMs volatize from the river. To date, no other potential sources of bromide appear to be significant. This includes steel plants that may be using brominated compounds to control biological growth in cooling towers or coal fired power plant that may be using brominated compounds to treat cooling towers or to control mercury emissions in air.

The EPA effort should include studying the impact on water treatment plants of the potential increased burden of analyzing for contaminants in the treated effluent from any plants (POTWs or industrial) that treat hydraulic fracturing wastewater and discharge the treated effluent upstream of water treatment plants. Controlled release and dilution of the wastewater is one such management method and deserves discussion and investigation. If specific contaminants in hydraulic fracturing return flows are identified as posing a significant risk to a drinking water supply source, then pre-treatment options for those contaminants should be investigated. Also, POTW life cycle costs in light of this new stream of wastewater should be addressed. Pilot scale testing objectives are in need of articulation.

Solid residuals from POTWs are typically taken to landfills, incinerated, or applied to land (there may be some intermediate steps). If some hydraulic fracturing wastewater contaminants are collected in the POTW residuals stream, then the need for any special storage, handling, management, or disposal controls should be assessed. The EPA retrospective studies need to investigate this issue. In states that allow land application of POTW residuals, there is a large data set on sludge quality and chemistry. The prospective studies might be designed to assess the ability to predict treatment performance, and then predict the real time genesis of outflow and residuals composition from the POTWs.

EPA should also consider industrial practices where the hydraulic fracturing return flows have been used for irrigation.

The draft Study Plan should address the cumulative consequences of carrying out multiple HF operations in a single watershed or region.., however this is an important line of inquiry (the watershed scale) recommended by the SAB. Examples of such consequences include causing a water body to exceed its total maximum daily load limit, which may cause the waterbody to be considered impaired and placed on the "303(d) list" of impaired waters (stream segments, lakes) that the Clean Water Act requires all states to submit for EPA approval. The SAB notes that an important impact of the cumulative HF wastewater discharges in a region might be missed if the focus is entirely on discharges from individual developments. This is especially true given the fact that entire regions now under development or consideration for development of these hydrocarbon resources. Some example study questions include: "What is the assimilative capacity of natural systems (wetlands, lakes, streams) to accommodate hydraulic fracturing treated wastewaters?" or, "Is this the best expenditure of ecosystem services?", or, "Is this an equitable expenditure of environmental services?"

The U.S. Department of Energy collaboration associated with treatment technologies should be more clearly articulated and defined, as well as the anticipated collaboration with any other entities mentioned in the proposal.

3.9. **Research Outcomes**

Charge Question 5: If EPA conducts the proposed research, will we be able to:

a. Identify the key impacts, if any, of hydraulic fracturing on drinking water resources; and

b. Provide relevant information on the toxicity and possible exposure pathways of chemicals associated with hydraulic fracturing?

3.9.1. General Comments

The two charge sub-questions are inherently very broad, primarily because of the heterogeneity of hydraulic fracturing operations. For example, the potential 'key impacts' of hydraulic fracturing are likely to depend strongly on local geological and hydrological conditions, and the magnitude of those impacts is likely to depend on the site-specific details of the fracturing operation and the management practices that are in place, both for routine operation and for dealing with emergency situations such as flooding and spills. For this reason, the short (but not particularly helpful) response to the charge question is: 'Yes at some sites and under certain conditions, and No at others or under other conditions.' While one could try to identify the most important conditional factors that influence the impacts of HF at different sites and then prepare a response to the charge question for each of the corresponding contingencies, the SAB believes that such an approach would lead to a large and unwieldy matrix of conditional contingencies that would not be particularly valuable to EPA or the stakeholders.

The SAB focused on the potential research outcomes that the EPA identified for each step in the HF water lifecycle. These potential research outcomes are identified in Chapter 6 of the draft Study Plan, at the end of the discussion of each stage of the water lifecycle. For each potential research outcome listed in the draft report, the SAB attempted to determine whether the outcome is likely to be achieved in whole, in part, or not at all, by the proposed research. The SAB recognizes that the ability to achieve a particular potential outcome is contingent on local conditions and therefore cannot be assessed for all sites in a limited research program. Nevertheless, the potential research outcomes are much more specific than the charge question and the SAB believes this specificity allows for more focused evaluation.

The SAB recognizes that the EPA did not claim that the listed potential research outcomes were comprehensive, or that the lists comprised the most important outcomes that the research would achieve. However, the potential research outcomes appeared as the final entry in the sections describing the various steps in the HF water life cycle, and the SAB believes that EPA intended the lists to capture most of the key outcomes that EPA hoped would be achieved. The SAB considered whether other, non-listed research outcomes might affect SAB's response to the charge question, but did not identify any non-listed outcomes that would significantly alter this SAB assessment.

The SAB also suggests that EPA include an additional likely outcome of the research project: the generation of new research ideas for reducing the potential adverse effects of HF activities (for example, ways to reduce water usage, identify BMPs, or develop 'greener' HF additives).

3.9.2. Specific Comments

Potential Research Outcomes: Water Acquisition (Section 6.1)

The potential research outcomes related to water acquisition identified in the draft Study Plan were:

a) Identify possible impacts on water availability and quality associated with large volume water withdrawals for hydraulic fracturing.

b) Determine the cumulative effects of large volume water withdrawals within a watershed and aquifer.

c) Develop metrics that can be used to evaluate the vulnerability of water resources.

d) Provide an assessment of current water resource management practices related to hydraulic fracturing.

SAB's response to these outcomes is as follows:

a) The SAB considers Outcome 6.1a to be largely a conceptual outcome that can be achieved by understanding the steps involved in hydraulic fracturing and the environment in which it is conducted. The phrase "possible impacts" suggests that the task can be accomplished by brainstorming among a broad and representative group of technical experts and stakeholders. A significant amount of such brainstorming has already occurred, and most of the possible impacts of HF have probably been identified. Continued attention should be paid to this task throughout the project to increase the chance of identifying other, less obvious potential impacts, based on data collected and observations made as the research progresses. Thus, the SAB believes that Outcome 6.1a can be achieved.

b, c) The possible cumulative effects of large volume withdrawals from a watershed have been documented in many prior water resource investigations unrelated to HF (see U.S. Army Engineer Waterways Experiment Station, 1999; Prudic, D.E., 2007; and Alberta Environment, 2007). These effects are highly site-specific, and many studies on withdrawal do not address impacts on water quality. Most large withdrawals are tied to either high density areas or agriculture, and HF activities can be within low density non-agricultural areas. The outcome of water withdrawals will be accomplished at HF sites that are carefully characterized in case studies, and the potential for extrapolation of the findings to other sites will be limited due to the

unique site-specific ecological and developmental factors associated with the locations for each case study.

The situation is largely the same with respect to establishment of metrics for evaluating the vulnerability of water resources to withdrawal of large volumes of water. It might be possible to establish metrics that relate specifically to HF environments and activities, such as the presence of pre-existing hydraulic interconnections in the underground (e.g., from mines) or the generation of such pathways during the HF process. However, while these metrics might be categorized as generally applicable, the data needed to apply them are detailed and site-specific, so it is unclear whether simply identifying the metrics represents a valuable outcome.

d) It is unclear to the SAB whether the "assessment" referred to in this outcome would comprise only data-gathering about existing management practices or a more in-depth analysis of the effectiveness of the practices. If the former, then the task can be accomplished by collection of data on water management practices from a representative cross-section of the industry. If the latter, then the metrics for evaluating the practices need to be carefully developed, and it is not clear that the EPA has paid sufficient attention to this effort to allow it to succeed.

Potential Research Outcomes: Chemical Mixing (Section 6.2)

The potential research outcomes related to chemical mixing identified in the draft Study Plan were:

a) Summarize available data on the identity and frequency of use of various hydraulic fracturing chemicals, the concentrations at which the chemicals are typically injected, and the total amounts used.

b) Identify the toxicity of chemical additives, and apply tools to prioritize data gaps and identify chemicals for further assessment.

c) Identify a set of chemical indicators associated with hydraulic fracturing fluids and associated analytical methods.

d) Determine the likelihood that surface spills will result in the contamination of drinking water resources.

e) Assess current management practices related to on-site chemical storage and mixing.

SAB's response to these outcomes is as follows:

a) SAB believes that Potential Outcome 6.2a is achievable, assuming cooperation from the HF service companies is forthcoming. The Panel noted that a state agency in Wyoming is currently collecting data on chemical use in HF, and the EPA should take maximum advantage of that effort, as well as any similar efforts undertaken by other states, federal, or non-governmental agencies.

b) The SAB does not believe that it is possible, within the cost and time constraints of the proposed research, to collect and evaluate new data on human toxicity of HF chemical additives. The SAB does believe that any pre-existing data on toxicity of HF additives should be collected and critically reviewed as part of the research, and that only limited efforts (such as toxicity estimates using quantitative structure-activity relationships, or QSARs for those additives with a high potential for exposure) should be made to estimate toxicity of HF additives for which there is no pre-existing toxicity data. The review of existing data and of the QSARs should be used to identify chemicals for further assessment.

c) The logical potential chemical indicators of HF fluids are the HF additives themselves and, in some cases, specific salt ions or aggregate measures of salt concentration (e.g., specific conductivity, TDS). The HF additives are usually added at low concentrations into the injected water, and they are likely to be partially modified (e.g., by microbial action), volatilized, and/or diluted substantially before entering a drinking water resource. Development of analytical methods for detecting low concentrations of such chemicals can be very time-consuming and costly. On the other hand, in situations where the concentration of salts can serve as an indicator of HF fluids, no research is needed to choose the specific indicator (either chloride or TDS is likely to be as good as any other choice), and no methods development is required. Therefore, the SAB recommends that during this project, inorganic salts and, possibly, organic HF additives for which analytical methods already exist be used as chemical indicators of the presence of HF fluids in water resources. If it is determined, based on other components of the research, that some HF chemicals might be particularly valuable indicators of the presence of HF fluids, then efforts to develop analytical methods for those chemicals can be undertaken subsequently.

It should be noted that, if a chemical that is present in the formation water (e.g., chloride) is chosen as the indicator and is found at elevated concentrations in a nearby water resource, the possibility can be raised that the concentration increase would have occurred even in the absence of HF activity. Barring the unlikely possibility that a direct pathway for the chemical from the HF environs to the water resource can be established, this issue falls more in the legal than the scientific domain (i.e., what is the burden of proof needed to attribute the higher concentration to HF activity?). In addition, establishing that an increase in concentration has occurred at a site where HF activity has been ongoing for several years would require some historical record of the concentration of the indicator prior to HF activity; at a site where HF activity is starting (i.e., the site of a prospective case study), it would require that the indicator appear in the water resource within one or at most two years for the potential outcome to be achieved during this research project. Neither of these scenarios can be assured, even if an appropriate indicator is selected. Use of HF additives as indicators does not suffer from this drawback but, as noted above, it is likely to be considerably more difficult to detect such additives in the water resource. For these reasons, although the SAB is supportive of the search for an indicator chemical as part of this project, it is not convinced that an appropriate indicator will be found (i.e., this outcome is a worthy goal, but it might not be achieved).

d) There is no question that surface spills of HF fluids are potential sources of contamination to shallow aquifers or surface waters. The likelihood that such contamination will actually occur

depends strongly on management practices and on the local geology and hydrology, the management practices for the HF liquid waste stream, as well as the magnitude of the spill and the types of retardation and/or transformations to which the chemicals are susceptible. Useful information on the possible modes of transport and transformation of HF chemicals can be obtained in laboratory studies, but such studies also depend on the hydrogeological conditions and are often costly to conduct. The SAB believes that a general question about "the likelihood that surface spills will result in the contamination of drinking water resources" is unanswerable, but that it can be answered once site-specific and contaminant-specific information is available. Because of the cost of obtaining the necessary contaminant-specific information, it is appropriate for the EPA to identify the chemicals that pose the greatest risk to human and environmental health before initiating such studies. To the extent that those chemicals can be identified, and their transport and transformation characterized, as part of this research project, the outcome can be achieved for those chemicals. If these tasks cannot be completed as part of the current research project, then the research will still generate a useful outcome, but the goal of determining the likelihood of contamination of drinking water resources will not be achieved.

e) Assuming that HF service companies are forthcoming with information about their chemical storage and mixing management practices, and that a broad data-gathering effort is undertaken, an assessment of management practices related to on-site chemical storage and mixing is achievable as part of the proposed research. It should be noted that chemical storage and mixing in HF are not obviously and fundamentally different from the corresponding activities in many other industrial settings. The implicit question that is being addressed by this potential outcome is whether the management practices are appropriate for the risks and challenges that exist for chemical storage and mixing at HF sites. Data regarding current practices, when combined with an assessment of the risks associated with chemical storage and mixing, should help answer this question.

<u>Potential Research Outcomes: Well Injection (Section 6.3)</u>

The potential research outcomes related to well injection identified in the draft Study Plan were:

a) Determine the frequency and severity of well failures, as well as the factors that contribute to them.

b) Identify the key conditions that increase or decrease the likelihood of the interaction of existing pathways with hydraulic fractures.

c) Evaluate water quality before, during, and after injection.

d) Determine the identity, mobility, and fate of potential contaminants, including fracturing fluid additives and/or naturally occurring substances (e.g., formation fluid, gases, trace elements, radionuclides, organic material) and their toxic effects.

e) Develop analytical methods for detecting chemicals associated with hydraulic fracturing events.

SAB's response to these outcomes is as follows:

a) Outcome 6.3a is achievable if thorough historical data on well failures are provided by the HF service companies and if EPA determines the number of hydraulic fracturing wells. The draft Study Plan indicates that "EPA will select a representative sample of sites and request the complete well files for the sites" and "will analyze the well files to assess the typical causes, frequency, and severity of well failures." From these statements, it is clear that EPA anticipates full cooperation from service companies. If that cooperation is forthcoming, then this task will be achievable and could yield valuable information.

b) EPA proposes to achieve potential Outcome 6.3b primarily or exclusively via computer modeling of contaminant transport under various "hydraulic fracturing well injection scenarios," taking into account features of both the engineering systems and the local geology. Such modeling will undoubtedly shed some light on the potential contamination of drinking water sources during the well injection phase of HF operations. However, the simulated outcomes will be strongly dependent on assumptions and choices made about how to represent the physical system, and the SAB has concerns that these assumptions and choices are not well constrained by reliable data. As a result, converting the modeling outcomes to useful interpretive or predictive outcomes may be problematic if the modeling assumptions and choices are not well constrained by reliable data.

As currently phrased, the claimed potential outcome is excessively broad and is unlikely to be achieved in a way that is of significant practical value. For example, the presence of many pre-existing interconnected fractures is likely to facilitate interaction of existing pathways with hydraulic fractures, but that conclusion is intuitive. Modeling could probably be carried out to identify some details of pre-existing fractures that pose especially high risk for interaction with hydraulic fractures. The effort required for such modeling is large, but in many cases much of the modeling might already have been completed as part of the pre-drilling analysis. EPA should request any geophysical data, well logs, etc., that the developers of sites have accumulated and use that information to the extent possible in this portion of the research

c) The SAB assumes that the water quality referred to in potential Outcome 6.3c was the water quality of the drinking water source that might be at risk of contamination as a result of HF activities. The plan to evaluate water quality before, during, and after injection of the HF fluids indicates that this potential outcome applies primarily or exclusively to the prospective case studies. While there is no doubt that such an evaluation can be carried out, the water quality parameters that are analyzed will probably undergo minimal change during the relatively short duration of the research program. In addition, the need to rely on inorganic salts as tracers for the HF fluids (because analytical methods for the organic additives are either not available at all, or not yet proven for the concentrations and matrices of interest) will complicate the interpretation of the data, because it will raise the question of whether hydraulic fracturing was truly the cause of any observed change in TDS.

The SAB has some concern that the absence of a strong contaminant signal could be misinterpreted as support for the null hypothesis (i.e., that the contaminants cannot migrate to the water body), when in fact it simply reflects a time lag between the initiation of HF activities and the appearance of HF fluids in the water source that is longer than the observation period. The SAB believes that the water quality evaluation that will be carried out is a worthwhile effort, but that it might have to be continued substantially beyond the end of the initial research before the outcome can be established with reasonable confidence.

d) Potential Outcome 6.3d is written in a way that suggests that the identity, mobility, fate, and toxicity of all potentially significant contaminants will be determined as part of the project, and that outcome is clearly not achievable. As noted elsewhere in this report, the SAB recommends that no toxicity testing be carried out as part of the current research. If that recommendation is accepted, the determination of toxic effects will be limited to those contaminants for which the toxicity has already been assessed. However, the goal of quantifying the mobility and fate of the contaminants that are deemed to be of highest priority is achievable. Given the plethora of HF additives and naturally occurring substances of potential interest, the SAB recommends that the contaminants of primary concern be identified based on an initial investigation of their usage rates, physical/chemical properties, and potential routes of human exposure, and that transport-and-fate studies be carried out only on those contaminants, by a combination of laboratory, field, and computer modeling experiments.

e) The SAB does not believe that developing new analytical methods for detecting and quantifying HF additives is an achievable goal for the current research program, given the constraints of time and funding.

<u>Potential Research Outcomes: Flowback and Produced Water (Section 6.4)</u>

The potential research outcomes related to flowback and produced water identified in the draft Study Plan were:

a) Compile information on the identity, quantity, and toxicity of flowback and produced water components.

b) Develop analytical methods to identify and quantify flowback and produced water components.

c) Provide a prioritized list of components requiring future studies relating to toxicity and human health effects.

d) Determine the likelihood that surface spills will result in the contamination of drinking water resources.

e) Evaluate risks posed to drinking water resources by current methods for on-site management of wastes produced by hydraulic fracturing.

SAB's response to these outcomes is as follows:

a) The compilation of existing data relating to the identity, quantity, and toxicity of flowback and produced water components is achievable as part of the research, and the SAB believes that successful completion of this step is critical. The SAB wishes to reiterate its belief that the toxicity data collected as part of this effort should be restricted to data that are already in the scientific literature.

b) The SAB does not support use of resources from the current project to develop new analytical methods for detecting components of the flowback and produced water.

c) The SAB believes that preparation of a prioritized list of components for future investigation with respect to toxicity and human health effects is an appropriate and desirable outcome of the research. Priority should be given to those compounds that have a combination of significant anticipated health effects and significant potential routes of exposure to humans.

d) The likelihood that surface spills will result in contamination of drinking water resources depends on the volume of the spill, the identities and concentrations of the contaminants in the spillage, and the details of the potential pathways from the site of the spill to the water resource. Therefore, this likelihood is highly site specific and cannot be quantified by some generalized equation. The SAB believes that the EPA understands and appreciates this site-specificity, but the wording of potential outcome 6.4d does not reflect that understanding; therefore, if the potential outcome is interpreted literally, it cannot be achieved. The SAB recommends that EPA consider revising this potential outcome so that it refers to development of procedures that can be used to assess the likelihood that various types of surface spills will lead to significant contamination of drinking water resources, when the procedures are applied to specific spill scenarios in specific hydrogeologic settings.

e) The data that the EPA anticipates collecting with regard to on-site management of HF wastes are vague. The draft plan indicates the data will be collected from literature reviews, retrospective case studies, and prospective case studies, but it is unclear exactly what information will be sought. Statements such as, “it will be informative to compare the typical management practices to unexpected situations that may lead to impacts…on drinking water resources” and “information will also be collected on the ways in which wastewater is transported for treatment or disposal” suggest that the research will, at best, generate a list of some management (and probably some mismanagement) practices. However, it is difficult to see how such data will be translated into a useful, generalized evaluation of the risks associated with on-site management of HF wastes.

<u>Potential Research Outcomes: Wastewater Treatment and Waste Disposal (Section 6.5)</u>

The potential research outcomes related to wastewater treatment and waste disposal identified in the draft Study Plan were:

a) Evaluate treatment and disposal methods that are currently being used to treat flowback and produced water resulting from hydraulic fracturing activities.

b) Assess the short- and long-term effects resulting from inadequate treatment of hydraulic fracturing wastewaters.

SAB's response to these outcomes is as follows:

a) The SAB interpreted potential outcome 6.5a as comprising both the effectiveness with which components of HF wastes can be removed from the waste stream using treatment and disposal methods that are currently being used to treat HF wastewater, and the effect of such wastes on the performance of treatment processes with respect to removal and/or degradation of other (non-HF) waste components. It should be noted that, in some cases, the HF wastes might be reused by injection into new wells, and the changes in water quality associated with such reinjection should be considered when assessing the composition of the wastes needing treatment. The draft Study Plan identifies pre-treatment of HF wastewaters prior to direct land application or prior to discharge to a community wastewater treatment system, as well as discharge directly to a community wastewater treatment system (without pre-treatment) as potential treatment/disposal methods. The draft Study Plan notes that substantial work that addresses these issues has been completed by DOE NETL, and that only research to fill in the remaining knowledge gaps will be carried out as part of the proposed project. It is not clear that an assessment of the effectiveness of pre-treatment for solutions that will be re-injected is an important research activity for this project.

The inorganic constituents in HF wastes can be removed from the solution only by desalination processes such as reverse osmosis, and the effectiveness of these processes is relatively well-established. Some of the organic constituents of HF wastes might be removed by biodegradation, volatilization, or adsorption, but few studies have attempted to track these compounds as they pass through a treatment plant, and the feasibility of doing so is complicated by the low concentrations of those compounds that are expected to be present once the HF fluids have been diluted by other influents to the plant.

The effects of the major inorganic contaminants in HF waste fluids on wastewater treatment processes and on soils have been extensively studied in other contexts, and the results of that research should be taken into account, along with the results of the DOE research. The effects of the organic contaminants on process performance will be more difficult to evaluate, other than anecdotally, for the same reasons that make the fate of the compounds themselves difficult to assess.

Based on the above considerations, the SAB believes that potential outcome 6.5a is likely achievable with respect to the inorganic constituents of HF wastes, with minimal or no new laboratory research. However, the same cannot be said for the organic constituents. For the organic constituents, it is unlikely that this potential outcome will be achieved in situations where the HF wastes are a small portion of the total waste stream entering the treatment plant.

The outcome might be achieved in a scenario where the HF wastes account for the majority of the influent to the treatment process (e.g., in a pre-treatment step at the HF site).

b) Taken in conjunction with the research plan for topic 6.5, it appears that potential outcome 6.5b is referring primarily to the effects that components of HF wastewaters might have on drinking water quality (e.g., TDS in drinking water, DBP formation during disinfection of drinking water) and the infrastructure of wastewater and drinking water treatment systems (e.g., increasing corrosion rates). Although the potential outcome is written as though a wide (or even comprehensive) range of such effects will be investigated, in truth only a couple will be explored. Furthermore, even those effects are probably better studied by combining mass balance calculations with existing literature on DBP formation and corrosion. The SAB's assessment is that this potential outcome can be achieved for a very limited range of effects, and that very little new laboratory research is required to do so.

APPENDIX A: EPA's CHARGE TO THE PANEL

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

Office of Research and Development

February 9, 2011

MEMORANDUM

SUBJECT: Request for review of the *Draft Plan to Study the Potential Impacts of Hydraulic Fracturing on Drinking Water Resources*

FROM: Fred S. Hauchman, Director ***/Signed/***
Office of Science Policy (8104R)

TO: Edward Hanlon, Designated Federal Officer
EPA Science Advisory Board Staff (1400R)

This memorandum requests that the Science Advisory Board (SAB) review and comment on the EPA Office of Research and Development's (ORD) *Draft Plan to Study the Potential Impacts of Hydraulic Fracturing on Drinking Water Resources*. The purpose of this draft study plan is to identify research activities that will answer the following questions:

- Can hydraulic fracturing impact drinking water resources?
- If so, what are the conditions associated with the potential impacts on drinking water resources?

Background

Hydraulic fracturing, which involves the pressurized injection of water, chemical additives, and proppants into geological formations, induces fractures in the formation that stimulate the flow of natural gas or oil, thus increasing the volume of gas or oil that can be recovered from coalbeds, shales, and tight sands. As natural gas production has increased, so have concerns about the potential environmental and human health impacts of hydraulic fracturing in the U.S., particularly with respect to drinking water resources. In its Fiscal Year 2010 Appropriation Conference Committee Directive to EPA, the U.S. House of Representatives urged EPA to conduct a study of hydraulic fracturing and its relationship to drinking water, specifically:

> *"The conferees urge the Agency to carry out a study on the relationship between hydraulic fracturing and drinking water, using a credible approach that relies on the best available science, as well as independent sources of information. The conferees expect the study to be conducted through a transparent, peer-reviewed process that will ensure the validity and accuracy of the data. The Agency shall consult with other Federal agencies as well as appropriate State and interstate regulatory agencies in carrying out the study, which should be prepared in accordance with the Agency's*

quality assurance principles."

In March 2010, EPA asked the SAB to review an initial research scoping document related to hydraulic fracturing.[2] This document outlined the initial approach for determining the scope of the study, potential research questions, and an initial approach for conducting the study. In its response to EPA[3] in June 2010, the SAB endorsed a lifecycle approach for the study plan, and recommends that: (1) initial research be focused on potential impacts to drinking water resources, with later research investigating more general impacts on water resources; (2) five to ten in-depth case studies be conducted at "locations selected to represent the full range of regional variability of hydraulic fracturing across the nation"; and (3) engagement with stakeholders occur throughout the research process.

Following the receipt of the SAB comments in June 2010, EPA developed the attached *Draft Plan to Study the Potential Impacts of Hydraulic Fracturing on Drinking Water Resources*. The draft plan focuses on the full lifecycle of water in the hydraulic fracturing process, from water acquisition, through the mixing of chemicals and actual fracturing, to the post-fracturing stage, including the management of flowback and produced water and its ultimate treatment and/or disposal. The research questions outlined in the study plan address how activities in each of these stages may impact drinking water resources. EPA has identified these research questions from stakeholder meetings and a review of the existing literature on hydraulic fracturing. Stakeholders have also helped EPA to identify the potential case study sites discussed in the draft study plan.

Specific Request

ORD requests that the SAB comment on the scope, proposed research questions, research approach, research activities, and research outcomes outlined in the *Draft Plan to Study the Potential Impacts of Hydraulic Fracturing on Drinking Water Resources*. Comments from the SAB will be considered during the development of the final plan to study the potential impacts of hydraulic fracturing on drinking water resources.

We appreciate the efforts of the SAB to prepare for the upcoming review of the *Draft Plan to Study the Potential Impacts of Hydraulic Fracturing on Drinking Water Resources*, and we look forward to discussing the plan in detail on March 7-8, 2011. Questions regarding the enclosed materials should be directed to Susan Burden at burden.susan@epa.govburden.susan@epa.govburden.susan@epa.govburden.susan@epa.govburden.susan@epa.govburden.susan@epa.govburden.susan@epa.govburden.susan@epa.govburden.susan@epa.gov or 202-564-6308.

[2] http://yosemite.epa.gov/sab/sabproduct.nsf/0/3B745430D624ED3B852576D400514B76/$File/Hydraulic%20Frac%20Scoping%20Doc%20for%20SAB-3-22-10%20Final.pdf

[3] http://yosemite.epa.gov/sab/sabproduct.nsf/0/CC09DE2B8B4755718525774D0044F929/$File/EPA-SAB-10-009-unsigned.pdf

Charge to the SAB

We ask the SAB to focus on the questions below during the review of the *Draft Plan to Study the Potential Impacts of Hydraulic Fracturing on Drinking Water Resources:*

2. **Water Use in Hydraulic Fracturing**
   EPA has used the water lifecycle shown in Figure 7 to characterize hydraulic fracturing and to identify the potential drinking water issues. Please comment on the appropriateness of this framework for the study plan. Within the context of the water lifecycle, does the study plan adequately identify and address the areas of concern?

3. **Research Questions**
   EPA has identified both fundamental and secondary research questions in Table 2. Has EPA identified the correct research questions to address whether or not hydraulic fracturing impacts drinking water resources, and if so, what those potential impacts may be?

4. **Research Approach**
   The approach for the proposed research is briefly described in Chapter 5. Please provide any recommendations for conducting the research outlined in this study plan, particularly with respect to the case studies. Have the necessary tools (i.e., existing data analysis, field monitoring, laboratory experiments, and modeling) been identified? Please comment on any additional key literature that should be included to ensure a comprehensive understanding of the trends in the hydraulic fracturing process.

5. **Proposed Research Activities**
   Proposed research activities are provided for each stage of the water lifecycle and summarized in Figure 9. Will the proposed research activities adequately answer the secondary questions listed in Table 2 for each stage of the water lifecycle? Please provide any suggestions for additional research activities.

6. **Research Outcomes**
   If EPA conducts the proposed research, will we be able to:
   a. Identify the key impacts, if any, of hydraulic fracturing on drinking water resources; and
   b. Provide relevant information on the toxicity and possible exposure pathways of chemicals associated with hydraulic fracturing?

Attachment: *Draft Plan to Study the Potential Impacts of Hydraulic Fracturing on Drinking Water Resources*